



## Numerics

---

- 10-Class WAN Edge Model, 515
- 1P2Q1T queuing and dropping, 401–404
- 1P2Q2T queuing and dropping, 405–408
- 1P3Q1T mode, 322
- 1P3Q1T queuing and dropping, 408–410
- 1P3Q8T queuing and dropping, 411–414
- 1P7Q8T queuing and dropping, 415–418
- 1PxQyT queuing, 36
- 2Q2T queuing and dropping, 396–398
  - show qos info config 2q2 tx verification command, 398
  - show qos info runtime verification command, 399–400
  - show queuing interface verification command, 400
- 33 percent limit (sum of LLQs), 450
- 4Q1T mode, 322
- 802.11e, 275–277
- 802.1D, classes of service, 279
- 802.1Q/p, translating to and from DSCP, 92–93

## A

---

- access control entries (ACEs), 225
- access layer
  - Catalyst 3550 QoS design, 325
  - policers, 54
- access point (AP), 271
- access switches
  - configuring to conditionally trust CoS, 319
- access switches (campus networks), 291
- access-edge QoS design, 290
- access-edge trust boundaries, 302
  - Conditionally Trusted Endpoint Models, 303, 307–312
  - Trusted Endpoint Models, 302–304
  - Untrusted Endpoint Models, 304–307
- access-edge utilization, 293
- ACEs (access control entries), 225
- ACLs, MQC-based class maps, 233
- adaptive jitter buffers, 36
- admission control, 197
- admission criterion (Real-Time class), 563–565
- ADSL (Asynchronous Digital Subscriber Lines), 672
- aggregate policers (Catalyst 6500), 258
- aggregation routers, 505–507
- algorithms
  - MDRR, 585
  - queuing, 133
    - CBWFQ, 140
    - comparison, 138
    - PQ-WFQ, 139
    - priority queuing, 137
    - WFQ, 137
  - shaping, 120
  - token bucket algorithms, 105
- analog gateways, 303
- Anti-Replay drops, 638, 656
- Anti-Replay functionality (IPSec QoS design), 654–656
- any-to-any videoconferencing, 548–549
- AP (access point), 271
- applications
  - data applications by class, 46–47
  - Mission-Critical Data, 43
  - Streaming-Video, 41
  - unidirectional, 513
- architectures (MPLS VPNs). *See* MPLS VPN-QoS design
- Assured Forwarding, 16
- asymmetric links, 677
- Asynchronous Digital Subscriber Lines (ADSL), 672
- ATM, 176
  - PVC bundles, 147
  - Tx-rings, 489
  - WAN edge link-specific QoS design
    - ATM-FR SIW, 497–501
    - high-speed links, 494–495
    - medium-speed links, 493
    - slow-speed links, 488–493
    - very-high-speed links, 496–497
- ATM CLP (ATM Cell-Loss Priority bit), 84
- ATM inverse multiplexing over ATM, 493
- ATM networks, 121–122
- ATM PVC bundles, slow-speed, 490–492

ATM-FR SIW (ATM-to-Frame Relay Service Interworking), 497–498  
 slow-speed links, 499–501  
 attacks (worms), 50–54  
 authentication  
 ESP, 654  
 IPSec, 657  
 AutoQoS (Automatic QoS), 24–25  
 Enterprise feature, 25–26  
 evolution of, 28

## B

backbone, 583–587  
 bandwidth  
 Catalyst 4500, 251  
 Eight-Class Model, 461  
 guarantees, 137, 565  
 ISDN, 501  
 provisioning, 143, 645  
 Best-Effort class, 449  
 Real-Time class, 449  
 teleworker V3PN QoS, 674–677  
 WAN aggregators, 449  
 VoIP, 646  
 reservations, 195  
 RSVP, 196–197  
 statements, on class default, 457  
 VoIP streams, 36–38  
 Bc (committed burst), 105, 479  
 Be (excess burst), 110, 480  
 bearer traffic  
 jitter, 36–38  
 latency, 34–35  
 loss, 34  
 Best-Effort class  
 bandwidth provisioning, 449  
 enabling WRED, 457  
 Best-Effort data, 44  
 best-effort networks, 11  
 best-effort service, 15  
 binary exponential backoff, 274  
 branch router QoS design, 513  
 case study, 535–540  
 LAN edge, 517

branch-to-campus classification and marking, 519–525  
 DSCP-to-CoS remapping, 518  
 NBAR known worm classification and policing, 526–535  
 WAN edge, 514–515  
 branch-to-branch traffic, 548  
 branch-to-campus classification and marking, 519–521  
 NBAR application classification, 523–525  
 source or destination IP address marking, 520  
 TCP/UDP classification, 522  
 broadband  
 serialization mitigation through TCP maximum segment size tuning, 678–679  
 split tunneling, 679–681  
 UDP-based video applications, 678  
 broadband-access technologies, 671  
 cable, 673  
 DSL, 672  
 buffer space, 135  
 buffers, 36–38  
 Bulk Data class, 44

## C

cable, 671–673  
 DOCSIS 1.1 specification, 678  
 Integrated Unit + Access Models, 684–685  
 overhead, 676–677  
 uplink connections, 677  
 CAC (call admission control), 205  
 CallManager locations CAC, 209–211  
 defined, 206  
 GK CAC, 211  
 local CAC tools, 208  
 measurement-based CAC tools, 208  
 prering CAC, 212  
 resource-based CAC tools, 209  
 RSVP, 212  
 tool categories, 207  
 VoIP CAC through RSVP, 215  
 Call-Signaling  
 MPLS VPN CE QoS design considerations, 553  
 campus QoS design, 295  
 Call-Signaling traffic, jitter, 38

- CallManager environments, 296–301
- CallManager locations CAC, 209–211
- CallManager services, 295
- campus Catalyst switches, 24
- campus networks
  - oversubscription ratios, 291
  - QoS design. *See* campus QoS design
  - traffic, 339
  - underutilization, 290
- campus QoS design, 289–290
  - access switches, 291
  - Call-Signaling, 295
  - case study, 422–439
  - Catalyst 2950
    - Conditionally Trusted IP Phone + PC
      - Advanced Model, 322
    - Conditionally Trusted IP Phone + PC
      - Basic Model, 319–320
    - queuing, 322–325
    - Trusted Endpoint Model, 314–315
    - Untrusted Multiapplication Server Model, 315–319
    - Untrusted PC with SoftPhone Model, 315
  - Catalyst 2970/3750, 342–343
    - Conditionally Trusted IP Phone + PC
      - Basic Model, 346–348
    - enabling/disabling QoS, 343
    - queuing/dropping, 351–356
    - Trusted Endpoint Model, 343–346
    - Unconditionally Trusted IP Phone + PC
      - Basic Model, 348–351
    - Untrusted PC with SoftPhone Model, 344
    - Untrusted Server Model, 345
  - Catalyst 3550, 325–327
    - Conditionally Trusted IP Phone + PC
      - Advanced Model, 333–336
    - Conditionally Trusted IP Phone + PC
      - Basic Model, 331–333
    - queuing and dropping, 336–341
    - Trusted Endpoint Model, 327
    - Untrusted PC with SoftPhone Model, 327–329
    - Untrusted Server Model, 330–331
  - Catalyst 4500, 357–358
    - Conditionally Trusted IP Phone + PC
      - Advanced Model, 364–366
    - Conditionally Trusted IP Phone + PC
      - Basic Model, 362–364
    - queuing, 366–370
    - show qos dbl command, 370
    - show qos interface command, 371–372
    - show qos maps dscp tx-queue command, 370–371
    - Trusted Endpoint Model, 359
    - Untrusted PC with SoftPhone Model, 359–360
    - Untrusted Server Model, 360–362
  - Catalyst 6500, 372, 374
    - 1P2Q1T queuing and dropping, 401–404
    - 1P2Q2T queuing and dropping, 405–408
    - 1P3Q1T queuing and dropping, 408–410
    - 1P3Q8T queuing and dropping, 411–414
    - 1P7Q8T queuing and dropping, 415–418
    - 2Q2T queuing and dropping, 396–400
    - CatOS defaults/recommendations, 375
    - Conditionally Trusted IP Phone + PC
      - Advanced Model, 387–391
    - Conditionally Trusted IP Phone + PC
      - Basic Model, 386–387
    - congestion avoidance, 384
    - PFC3 distribution-layer Per-User
      - Microflow Policing, 419
    - queuing/dropping, 391–396
    - show port qos command, 376–377
    - Trusted Endpoint Model, 375
    - Untrusted PC with SoftPhone Model, 378–382
    - Untrusted Server Model, 383–386
  - defining designs, 292
  - DoS/worm mitigation, 292–294
  - WAN aggregator/branch router handoff, 420–422
- campus-to-branch traffic, 548
- CAR (committed access rate), 79, 107–108
- case studies
  - branch router QoS design, 535–540
  - campus QoS design, 422–439
  - IPSec VPN QoS design, 686
    - telecommuter router, 694–695
    - V3PN branch router design, 691–693
    - VPN headend design, 687–689
    - WAN aggregator QoS design, 689–690

- MPLS VPN QoS design, 616
  - CE routers, 617-619
  - PE routers, 620-630
  - P routers, 630-631
- WAN aggregation router QoS design, 505-507
- Catalyst 2950, 314-315
  - classification, marking, and mapping, 233
  - Conditionally Trusted IP Phone + PC Advanced Model, 322
  - Conditionally Trusted IP Phone + PC Basic Model, 319
  - CoS-to-DSCP map, 233
  - DSCP-to-CoS map, 234
  - policing and markdown, 234
  - queuing, 235, 322-323
    - show wr-queue bandwidth command, 324
    - show wr-queue cos-map command, 325
  - range keyword, 315
  - Trusted Endpoint Model, 314-315
  - Untrusted Multiapplication Server Model, 315-318
    - show class-map and show policy-map verification commands, 318
    - show mls masks qos verification command, 319
    - show mls qos interface policers verification command, 318
  - Untrusted PC with SoftPhone Model, 315
  - vs. Catalyst 3550, 231
- Catalyst 2970, 242, 342-343
  - classification, marking, and mapping, 243
  - Conditionally Trusted IP Phone + PC Basic Model, 346-348
  - enabling/disabling QoS, 343
  - policing and markdown, 244
  - queuing/dropping, 244-246, 351-356
  - Trusted Endpoint Model, 343-346
  - Unconditionally Trusted IP Phone + PC Basic Model, 348-351
  - Untrusted PC with SoftPhone Model, 344
  - Untrusted Server Model, 345
- Catalyst 3550, 235, 325-327
  - classification, marking, and mapping, 237
  - Conditionally Trusted IP Phone + PC Advanced Model, 333-336
  - Conditionally Trusted IP Phone + PC Basic Model, 331-333
  - DSCP mutation maps, 237
  - policing and markdown, 238-239
  - queuing and dropping, 240-241, 336-339
    - show mls qos interface buffers verification command, 340
    - show mls qos interface queuing verification command, 341
  - Trusted Endpoint Model, 327
  - Untrusted PC with SoftPhone Model, 327-329
  - Untrusted Server Model, 330-331
- Catalyst 3750, 242, 342-343
  - classification, marking, and mapping, 243
  - Conditionally Trusted IP Phone + PC Advanced Model, 348-351
  - Conditionally Trusted IP Phone + PC Basic Model, 347-348
  - enabling/disabling QoS, 343
  - policing and markdown, 244
  - queuing/dropping, 244-246, 351-356
  - Trusted Endpoint Model, 343-346
  - Untrusted PC with SoftPhone Model, 344
  - Untrusted Server Model, 345
- Catalyst 4500, 247, 357-358
  - classification, marking, and mapping, 248-249
  - Conditionally Trusted IP Phone + PC Advanced Model, 364-366
  - Conditionally Trusted IP Phone + PC Basic Model, 362-364
  - DSCP-to-queue maps, 251
  - enabling QoS, 248
  - policing and markdown, 249-250
  - queuing, 366-370
  - queuing and dropping, 250-252
  - show qos dbl command, 370
  - show qos interface command, 371-372
  - show qos maps dscp tx-queue command, 370-371
  - Trusted Endpoint Model, 359
  - Untrusted PC with SoftPhone Model, 359-360
  - Untrusted Server Model, 360-362
- Catalyst 6500, 252, 372, 374
  - CatOS
    - 1P2Q1T queuing and dropping, 401-404
    - 1P2Q2T queuing and dropping, 405-408
    - 1P3Q1T queuing and dropping, 408-410
    - 1P3Q8T queuing and dropping, 411-414
    - 1P7Q8T queuing and dropping, 415-418

- 2Q2T queuing and dropping, 396–400
- Conditionally Trusted IP Phone + PC
  - Advanced Model, 387–391
- Conditionally Trusted IP Phone + PC
  - Basic Model, 386–387
- congestion avoidance, 384
- defaults/recommendations, 375
- queuing/dropping, 391–396
- Trusted Endpoint Model, 375
- Untrusted PC with SoftPhone Model, 378–379, 381–382
- Untrusted PC with SoftPhone Model Model, 379–382
- Untrusted Server Model, 383–386
- classification, marking and mapping, 254–256
- enabling QoS, 254
- PFC QoS, 261
- PFC3 distribution-layer Per-User Microflow Policing, 419
- policing and markdown, 257–259
- queuing and dropping, 259–263
- Supervisor 720, 253
- Trusted Endpoint Model
  - show port qos command, 376–377
- VLAN-based QoS, 254
- WRED-drop thresholds, 262
- Catalyst 6500 configuring microflow policers, 257
- Catalyst QoS Models, 224
  - classification, 225
  - policing, 227
  - queuing, 228–230
- CatOS defaults/recommendations, 375
- CBR (constraint-based routing), 603
- CBWFQ (Class-Based Weighted Fair Queuing), 133, 139–140
- CDP (Cisco Discover Protocol), 307
- CE bit, 163
- CE design, 556–563
- CE routers, MPLS VPN QoS design case study, 617–619
- CEF (Cisco Express Forwarding), 74
- Channel Utilization field, 278
- CIR (committed information rate), 105
  - Frame Relay networks, 479
  - policing behavior based on percentages, 118
- Cisco 12000 routers
  - priority command, 587
  - queuing, 585
- Cisco Discover Protocol (CDP), 307
- Cisco Express Forwarding (CEF), 74
- class default policing, 112
- class selectors, 16
- class-based Frame Relay traffic shaping, 123–124
- class-based marking, 77
- class-based policing, 79, 109
  - benefits, 109
  - single-rate three-color marker/policer, 110–112
  - two-rate three-color marker/policer, 112–113
- class-based shaping, 126–127
- Class-Based Weighted Fair Queuing (CBWFQ), 133
- classes of service (802.1D), 279
- classification, 57, 68–69
  - branch-to-campus, 519
  - Catalyst 2950, 233
  - Catalyst 2970, 243
  - Catalyst 3550, 237
  - Catalyst 3750, 243
  - Catalyst 4500, 248–249
  - Catalyst 6500, 254–256
  - Catalyst QoS models, 225
  - NBAR application, 523–524
  - source or destination IP addresses, 520
  - TCP/UDP, 522
  - tools, 70
    - MQC-based class maps, 71–72
    - NBAR, 73–77
- Code Red, 527
- codecs (frame-based), 34
- CodeRedv2, 528
- color-aware policing, 116–117
- color-blind policing, 117
- commands, 47–48
  - commit all command, 377
  - dbl policy command, 367
  - frame-relay fragment command, 481
  - match protocol dlsw command, 48
  - max-reserved-bandwidth, 559–563
  - mls qos cos override interface command, 316
  - ping vrf command, 601–602
  - ppp multilink links minimum command, 504
  - priority-queue out command, 240
  - qos dbl command, 367
  - qos map dscp to tx-queue command, 367
  - show atm bundle command, 493
  - show atm pvc command, 489
  - show atm vc command, 492

- show class-map verification command, 318
- show controllers command, 451
- show frame-relay fragment command, 482
- show ima interface atm command, 495
- show ip access-list command, 521
- show ip bgp vpnv4 all command, 615
- show ip nbar map command, 525
- show ip rsvp interface command, 599
- show ip rsvp neighbor command, 599
- show mls masks qos verification command, 319
- show mls qos command, 358
- show mls qos interface buffers verification command, 340
- show mls qos interface policers verification command, 318
- show mls qos interface queuing verification command, 341
- show mls qos interface statistics verification command, 329
- show mls qos maps command, 356
- show mls qos maps dscp-output-q command, 356
- show mpls interface command, 600
- show mpls traffic-eng topology command, 614–615
- show mpls traffic-eng tunnels command, 601
- show mpls traffic-eng tunnels summary command, 600
- show policy command, 456
- show policy interface command, 469
- show policy interface verification command, 329
- show policy-map verification command, 318
- show port qos commands, 376–377
- show ppp multilink command, 478
- show qos acl verification command, 380
- show qos command, 358
- show qos dbl command, 370
- show qos info config 2q2 tx verification command, 398
- show qos info runtime verification command, 399–400
- show qos interface command, 371–372
- show qos maps dscp tx-queue command, 370–371
- show qos maps verification command, 379
- show qos policer verification command, 381
- show qos statistics verification command, 382
- show queuing interface verification command, 400
- show wrp-queue bandwidth command, 324
- show wrp-queue cos-map command, 325
- trust-device command, 386
- tx-queue command, 367
- tx-ring-limit command, 490
- wrr-queue bandwidth command, 322
- wrr-queue cos-map command, 240
- wrr-queue dscp-map interface configuration command, 339
- wrr-queue queue-limit command, 240
- wrr-queue queue-limit interface command, 338
- show mls qos map, 320
- commit all command, 377
- committed access rate (CAR), 79, 107–108
- committed burst rate (Bc, 105, 479
- committed information rate. *See* CIR
- compatibility (802.1D classes of service), 279
- compression
  - G.729 voice compression, 170
  - hardware compression, 181
- Conditionally Trusted Endpoint Models (Trust Boundaries), 303, 307–312
- Conditionally Trusted IP Phone + PC Advanced Model, 322
  - Catalyst 2970/3750, 348–351
  - Catalyst 3550, 333–336
  - Catalyst 4500, 364–366
  - Catalyst 6500, 387–391
- Conditionally Trusted IP Phone + PC Basic Model, 319, 346–347
  - Catalyst 2970/3750, 346–348
  - Catalyst 3550, 331–333
  - Catalyst 4500, 362–364
  - Catalyst 6500, 386–387
- configuring
  - 1P2Q2T queuing, 407
  - 1P3Q1T queuing, 410
  - 1P3Q1T queuing model, 337
  - 1P3Q8T queuing, 412
  - 1P7Q8T queuing, 416–417
  - Catalyst 2950 switches
    - Conditionally Trusted IP Phone + PC Advanced Model, 322

- Conditionally Trusted IP Phone + PC
  - Basic Model, 319–320
- queuing, 322–323
- Trusted Endpoint Model, 314–315
- Untrusted Multiapplication Server Model, 315–316, 318–319
- Untrusted PC with SoftPhone Model, 315
- CoS-to-queue mapping (Catalyst 3550), 240
- cRTP for ATM links, 176
- DSCP mutation, 238
- FR-VATS, 125
- individual policer on Catalyst 4500, 250
- IPSec authentication, 657
- MCMP for an ISDN interface, 185
- microflow policing on Catalyst 6500, 257
- MLP LFI, 184
- MPLS DS-TE, 606–613
- MPLS per-VPN TE, 592–598
- PFC, 255
- policing, 234
- QoS on Cisco APs, 281
- queuing (Catalyst 2950), 235
- RSVP, 196
- SRR shaping and sharing weights on Catalyst 2970/3750, 246
- trust on Catalyst 6500, 255
- VLAN-based QoS on Catalyst 6500, 254
- WRED, 162
- configuring WRED-drop thresholds, 262
- confirming traffic, 107
- congestion avoidance
  - Catalyst 6500, 384
  - tools, 159
    - DSCP-based WRED, 162–163
    - explicit congestion notification, 163
    - RED, 160
    - WRED, 161–162
- congestion-management tools, 133
  - converged networks, 135–136
- connecting trusted endpoints, 304
- consistent QoS behavior, 453
- constraint-based routing (CBR), 603
- constricted channels, 159
- control plane QoS
  - IP routing, 48–49
  - network management, 49
- controlled load, 15, 197
- controlling traffic
  - branch-to-branch, 548
  - campus-to-branch, 548
- converged networks
  - congestion-management tools, 135–136
  - QoS, 12–14
- convergence, 449
- Core Best-Effort class, 584
- Core Critical Data class, 584
- core QoS considerations, 582
  - aggregate bandwidth overprovisioning, 583
  - DiffServ in the backbone
    - platform specific considerations, 585–587
    - Three-Class Provider-Core Model, 583–585
  - MPLS traffic engineering, 587
    - basic, 588–590
    - MPLS DS-TE, 603–615
    - MPLS per-VPN TE, 591–602
- Core Real-Time class, 584
- CoS values, assigning queues, 240
- CoS-to-DSCP maps
  - Catalyst 2950, 233
  - Catalyst 6500, 256
- control plane provisioning, 657
- CQ (custom queuing), 137
- cRTP (RTP header compression), 172
  - class-based header compression, 178–179
  - configuring for ATM links, 176
  - formats, 173
    - Cisco proprietary format, 173
    - IETF format, 174
    - IPHC, 173
  - formats and encapsulation summary, 177–178
  - incompatibility with IPSec, 643–644
  - Layer 2 encapsulation protocol support, 175
    - ATM, 176
    - Frame Relay, 176
    - HDLC, 175
    - PPP, 175
  - LLQ, 145
  - policing and shaping, 180
  - tunnels, 180
- crypto engine, 651–652
- cTCP (TCP header compression), 171
- custom queuing (CQ), 137



CWmax, 278, 282  
 CWmin, 274, 278, 282

## D

### data

- applications by class, 46–47
- QoS, 42–43
  - Best-Effort data, 44
  - DLSw+, 47–48
  - locally defined Mission-Critical Data, 45
  - Transactional Data/Interactive Data, 45
- data frames (802.11), 272
- data VLANs (DVLANS), 314
- datagrams, 153
- data-link connection identifiers (DLCIs), 123
- data-link switching plus (DLSw+), 47–48
- DBL (dynamic buffer limiting), 366–367
- DCF (Distributed Coordination Function), 272
  - Interframe Spaces, 272
  - random backoffs, 273
- DDR (dial-on-demand routing), 503
- DDT (delay to dial tone), 38
- delay budgets (IPSec VPNs), 647
- delay to dial tone (DDT), 38
- delay variation, 13–14. *See also* jitter
- deploying
  - IPSec VPNs via DMVPN, 646
  - LFI tools, 450
  - policers, 106
  - QoS designs, 62
  - Untrusted Server Model on Catalyst 2950, 315
- designing QoS
  - classification and marking principles, 57
  - deployment, 62
  - DoS and worm mitigation principles, 61–62
  - policing and markdown principles, 57–58
  - queuing and dropping principles, 58–60
- destination IP address classification, 520
- DHCP, translating to Frame Relay DE bit, 94
- dial-on-demand routing (DDR), 503
- Differentiated Services code points (DSCPs), 87
- DiffServ, 16
  - advantages of DiffServ model, 16
  - deploying in backbone
    - platform specific considerations, 585–587

- Three-Class Provider-Core Model, 583–585

DIFS, 272

Digital Subscriber Line. *See* DSL

disabling

- flow control, 327
- native DLSw+ ToS markings, 48
- QoS on Catalyst 2970/3750, 343

Discard class placeholder, 568

Distributed Coordination Function (DCF), 272

distributed platform frame relay links, 486–487

distributed platform QoS, 453

distributed traffic shaping (DTS), 128, 486

Distributed-Platform/Consistent QoS Behavior QoS Baseline Model, 465–466

distribution layer, Catalyst 3550 QoS design, 325

DLCIs (data-link connection identifiers), 123

dlsw tos disable command, 48

dlsw tos map command, 47

DLSw+ (data-link switching plus), 47–48

DMVPNS (Dynamic Multipoint Virtual Private Networks), 646

DOCSIS 1.1 specification, 674, 678

dominating links (VoIP), 449

DoS attacks

- campus network mitigation strategies, 292–294
- mitigation principles, 61–62

downstream QoS, 271

drop thresholds (Catalyst 2970 and 3750), 245

dropping, 58–60

- Anti-Replay, 656

- Catalyst 2970, 244–246

- Catalyst 3550, 240–241, 336–339

- Catalyst 3750, 244–246

- Catalyst 4500, 250–252

- Catalyst 6500, 259–263, 391–394

- 1P2Q1T queuing and dropping, 401–404

- 1P2Q2T queuing and dropping, 405–408

- 1P3Q1T queuing and dropping, 408–410

- 1P3Q8T queuing and dropping, 411–414

- 1P7Q8T queuing and dropping, 415–418

- 2Q2T queuing and dropping, 396–400

DSCPs (Differentiated Services code points), 87

- DSCP-based WRED, 162–164

- mutation maps (Catalyst 3550), 237

DSCP-to-CoS maps

- Catalyst 2950, 234

- Catalyst 3550, 237

DSCP-to-CoS remapping, 518  
 DSCP-to-queue maps  
   Catalyst 4500, 251  
 DSL (Digital Subscriber Line), 671-672  
   Integrated Unit + Access Models, 684-685  
   Integrated Unit/Dual-Unit models, 682  
   uplink connections, 677  
 DSL (AAL5 + PPPoE) overhead, 675-676  
 DSLAM (DSL Access Multiplexer), 671  
 DTS (distributed traffic shaping), 128, 486  
 Dual-Unit Model, 669, 682  
 DVLANs (data VLANs), 314  
 dynamic buffer limiting (DBL), 366  
 Dynamic Multipoint Virtual Private Networks (DMVPNs), 646

## E

EAP (Extensible Authentication Protocols), 308  
 ECN bit, 164-165  
 ecn keyword, 165  
 ECT bit, 163  
 EDCF (Enhanced Distributed Coordination Function), 275-277  
 EI (Enhanced Image), 232  
 Eight-Class Model, 460-462  
 Eight-Class Site-to-Site V3PN Model, 660-664  
 EMI (Enhanced Multilayer Software Image), 243  
 enabling  
   MLPoATM, 499  
   QoS  
     Catalyst 4500, 248  
     Catalyst 6500, 254  
     Catalyst 2970/3750, 343  
 encryption, delay budgets, 648  
 end users' network expectations, 9  
 endpoints, 201, 304  
 end-to-end QoS, 10  
 Enhanced Distributed Coordination Function (EDCF), 275, 277  
 Enhanced Image (EI), 232  
 Enhanced Multilayer Software Image (EMI), 243  
 enterprise resource planning (ERP), 42  
 ERP (enterprise resource planning), 42  
 errors (Anti-Replay), 655  
 ESP authentication, 654

Ethernet 802.1Q tunnels, 82  
 Ethernet 802.1Q/p, 81-82  
 Ethernet downstream, 271  
 evolution of QoS, 29  
 exceeding traffic, 107  
 excess burst rate (Be), 110, 480  
 expedited forwarding, 16  
 explicit congestion notification, 163  
 Extensible Authentication Protocols (EAP), 308

## F

FIFO Tx-ring, 152  
 Five-Class Model, 456-459  
 Five-Class Provider-Edge Model, 565-566  
   MPLS VPN CE QoS design considerations, 561-563  
 Fixed Slot Time Default values, 278  
 flow control, disabling, 327  
 Four-Class Provider-Edge Model, 565  
   MPLS VPN CE QoS design considerations, 559-561  
 fragment sizes  
   distributed platform Frame Relay links, 486  
   WAN link fragmentation, 183-184  
 frame-based codecs, 34  
 Frame Relay  
   cRTP, 176  
   Frame-Relay fragmentation, 185  
     FRF.11.1 and FRF.12.1, 187-188  
     LFI for Frame Relay/ATM service interworking, 188-189  
     PVCs, 186-187  
   PIPQ, 150  
   WAN edge link-specific QoS design, 478  
     Bc, 479  
     Be, 480  
     CIR, 479  
     distributed platform links, 486-487  
     high-speed links, 484-485  
     medium-speed links, 482-484  
     slow-speed links, 480-482  
 Frame Relay bundles, 148  
 Frame Relay DE bit, translating to from DSCHP, 94  
 Frame Relay Dual-FIFO, 150  
 Frame Relay traffic shaping (FRTS), 122-123

- Frame Relay voice-adaptive traffic shaping (FR-VATS), 124–125
- Frame-Relay DE bit, 83
- frame-relay fragment command, 481
- FRF.11.1 and FRF.12.1
  - fragmenting, 187–188
- FRF.8, 189
- FRTS (Frame Relay traffic shaping), 122–123
- FR-VATS (Frame Relay voice-adaptive traffic shaping), 124–125

## G - H

---

- G.729 voice compression, 170
- G.SHDSL, 673
- gatekeepers (GK), 211
- generic traffic shaping, 126
- GK (gatekeepers), 211
- GK CAC, 211
- global synchronization, 159
- goals of convergence, 449
- guaranteed load service, 197
- guaranteed services, 15
- guarantees (bandwidth), 137, 195, 565
  
- handoffs (WAN aggregator/branch router), 420–422
- hardware compression, 181
- hardware crypto engines, 652
- HDLC (High-Level Data Link Control), 135, 175
- header-compression techniques, 170
  - class-based header compression, 178–179
  - formats,
    - Cisco propriety format, 173
    - IETF format, 174
    - IPHC, 173
  - Layer 2 encapsulation protocol support, 175
    - ATM, 176
    - Frame Relay, 176
    - HDLC, 175
    - PPP, 175
  - RTP header compression (cRTP), 172
  - standards, 171
  - TCP header compression (cTCP), 171
- hierarchical class-based shaping, 127
- hierarchical policing, 114

- High Link-Speed QoS Class Models, 459
  - Distributed-Platform/Consistent QoS Behavior
    - QoS Baseline Model, 465–466
  - Eight-Class model, 460–462
    - QoS Baseline Model, 463–465
- High-Level Data Link Control (HDLC), 135
- high-speed ATM links, 494–495
- high-speed frame relay links, 484–485
- high-speed leased lines, 472–476
  - pkts matched statistics, 477
  - show policy interface command, 473
  - show ppp multilink command, 478
- horizontal separation of traffic, 107
- how qos dbl command, 370
- hub routers
  - WAN aggregators, 548
- hub-and-spoke topology, 548, 646

## I

---

- IANA (Internet Assigned Numbers Authority), 522
- IETF (Internet Engineering Task Force), 7
- IETF format, 174
- IMA (ATM inverse multiplexing over ATM), 493
- Integrated Services, 6
- Integrated Unit + Access Model, 669–670, 684–685
- Integrated Unit Model, 668, 682
- Interactive Data, 45
- Interactive-Video, 39
- Interframe Spaces, 272
- Internal DSCP value, 225
- Internet Assigned Numbers Authority (IANA), 522
- interoperability (RSVP), 213
- IntServ, 7, 15
- IP configuring stations, 303
- IP header compression format (IPHC), 171–173
- IP Precedence, 567
- IP routing, 48–49
- ip rsvp bandwidth command, 215
- IP RTP header compression, 451
- IP RTP priority, 139
- IP telephony, 307
- IP ToS (IP type of service), 86–87
- IP VPN Multiservice, 551
- IPHC (IP header compression format), 171–173

- IPSec
    - authentication, 657
    - incompatibility with cRTP, 643–644
    - LLQ, 145
    - prefragmentation, 190
  - IPSec-encrypted G.729 packets, 642
  - IPSec Encryption Engines, 652
  - IPSec QoS design, 635
    - Anti-Replay functionality, 655
    - anti-replay functionality, 654–656
    - bandwidth provisioning, 645–646
    - control plane provisioning, 657
    - cRTP and IPSec incompatibility, 643–644
    - delay budget increases, 647
    - headend VPN edge QoS options for site-to-site V3PNs, 665–666
    - packet overhead increases, 640–642
    - pre-encryption queuing, 651–653
    - prefragmentation, 645
    - QoS Pre-Classify, 649
    - site-to-site V3PN, 637
      - IPSec transport mode (encrypting an IP GRE tunnel), 638
      - IPSec tunnel mode (encrypting an IP GRE tunnel), 639–640
      - IPSec tunnel mode (No IP GRE tunnel), 638
    - site-to-site V3PN QoS models
      - Eight-Class Site-to-Site V3PN Model, 660–664
      - Six-Class Site-to-Site V3PN Model, 658–659
    - teleworker V3PN QoS, 666–667
      - asymmetric links and unidirectional QoS, 677
      - bandwidth provisioning, 674–677
      - broadband-access technologies, 671–673
      - deployment models, 667–670
      - topologies, 646
      - ToS byte preservation, 649
      - VPNs, 635
    - IPSec transport mode (encrypting an IP GRE tunnel), 638
    - IPSec tunnel mode (encrypting an IP GRE tunnel), 639–640
    - IPSec tunnel mode (No IP GRE tunnel), 638
    - IPSec VPN QoS design (case study), 686
      - telecommuter router, 694–695
      - V3PN branch router design, 691–693
      - VPN headend design, 687–689
      - WAN aggregator QoS design, 689–690
  - ISDN, 671
    - WAN edge link-specific QoS design
      - CallManager CAC limitations, 503
      - MLP packet reordering, 502
      - variable bandwidth, 501
      - voice and data on multiple ISDN B channels, 503–504
  - ITDP/UDP ports (CallManager environments), 296–301
- ## J - K
- 
- jitter, 13, 35, 450
  - jitter buffers, 37–38
    - adaptive, 36
    - underruns, 14
  - keywords, 358
- ## L
- 
- LAN edge QoS design, 517
    - branch-to-campus classification and marking, 519–525
    - DSCP-to-CoS remapping, 518
    - NBAR known worm classification and policing, 526–535
  - LANs
    - switching environments, 223
    - QoS for wired vs. wireless, 270
  - latency
    - converged networks, 13
    - VoIP, 34–35
  - Layer 2
    - access (MPLS VPN CE QoS design), 550–551
    - marking fields, 81–82
      - ATM CLP, 84
      - Frame-Relay DE bit, 83
      - MPLS EXP bits, 84
    - queuing mechanisms, 150
    - queuing subsystems, 136

Layer 3 marking fields, 88-90

Layer 3 queuing mechanisms

- CBWFQ, 139-140
- legacy, 136-137
- LLQ, 133, 140, 199, 450, 652- 653
  - ATM PVC bundles, 147
  - bandwidth provisioning, 143-144
  - cRTP, 145
  - IPSec, 145
  - LFI, 147
  - MLP and Frame Relay bundles, 148
  - operation, 141
  - policing, 142
  - VoFR, 149

Layer 3 queuing subsystems, 135

leased lines, 467

- high-speed, 472-478
- medium-speed, 471
- slow-speed, 467-470

legacy Layer 3 queuing mechanisms, 136-137

LFI (Link Fragmentation and Interleaving)

- for Frame Relay/ATM service interworking, 188-189

LLQ, 147

tools, 182, 450

line card queuing structures (catalyst 6500), 393-396

links

- asymmetric, 677
- ATM
  - high-speed, 494-495
  - medium-speed, 493
  - slow-speed, 488-493
  - very-high-speed, 496-497
- capacity, 293
- Eight-Class Site-to-Site V3PN Model, 662
- Frame Relay networks
  - distributed platform, 486-487
  - high-speed, 484-485
  - medium-speed, 482-484
  - slow-speed, 480-482
- speed, 452
- VoIP, dominating, 449

link-specific tools, 19, 169

LLQ (low-latency queuing), 133, 140, 199, 450, 652-653

- ATM PVC bundles
  - LLQ, 147

- bandwidth provisioning, 143-144
- cRTP, 145
- IPSec, 145
- LFI, 147
- MLP and Frame Relay bundles, 148
- operation, 141
- policing, 142
- VoFR, 149
  - VoIP and multiple levels of data, 141

local CAC tools, 208

locally defined Mission-Critical Data, 45

loss (voice), 34

low link speeds (WANs), 450

low-latency queuing. *See* LLQ

LS VPN QoS design, 613-615

## M

mapping

- Catalyst 2950, 233
- Catalyst 2970, 243
- Catalyst 3550, 237
- Catalyst 3750, 243
- Catalyst 4500, 248-249
- Catalyst 6500, 254-256
- IP Precedence, 567
- Mapping Models (enterprise-to-service provider)
  - Five-Class Provider-Edge Model, 565-566
  - Four-Class Provider-Edge Model, 565
  - Three-Class Provider-Edge Model, 563-564

markdown, 57-58

- Catalyst 2950, 234
- Catalyst 2970, 244
- Catalyst 3550, 238-239
- Catalyst 3750, 244
- Catalyst 4500, 249-250
- Catalyst 6500, 257-259
- Catalyst QoS Models, 227

markers (policers as), 107

marking, 57, 68-69

- branch-to-campus, 519
- Catalyst 2970, 243
- Catalyst 3550, 237

- Catalyst 3750, 243
- Catalyst 4500, 248–249
- Catalyst 6500, 254–256
- DLSw+ traffic, 48
- MPLS VPN CE QoS design considerations, 554–556
- tools
  - class-based marking, 77
  - class-based policing, 79
  - Layer 2 marking fields, 81–84
  - Layer 3 marking fields, 86–87
  - Layer 3 tunnel marking tools, 88–90
  - translating Layer 2 and Layer 3 packet markings, 90–98
  - voice gateway packet marking, 79–81
- traffic, 304
- match protocol commands, 75
- match protocol dlsw command, 48
- max-reserved-bandwidth command, 559–563
- max-reserved-bandwidth interface command, 143
- MCMP (Multiclass Multilink PPP), 185
- MDRR (modified-deficit round-robin) algorithm, 585
- mean opinion scores (MOS), 35
- measurement-based CAC tools, 208
- Media Gateway Control Protocol (MGCP), 79
- Medium Link-Speed QoS Class Models, 454
- medium-speed ATM links, 493
- medium-speed frame relay links, 482–484
- medium-speed leased lines, 471
- MGCP (Media Gateway Control Protocol), 79
- Microflow policers, 257
- Mission-Critical Data applications, 43–45
- mitigating serialization delay, 678
- MLP (Multi Point-to-Point Protocol), 136
- MLP bundles, 148
- MLP LFI (Multilink PPP Link Fragmentation and Interleaving), 183–185
- MLP packets, reordering, 502
- MLPoATM, 488–489, 499
- MLPoFR (MLP over Frame Relay), 177
- mls prefix keyword, 358
- mls qos cos override command, 316
- modified-deficit round-robin (MDRR) algorithm, 585
- modular QoS CLI based class maps, 71–72, 233
- Modular QoS Command-Line Interface (MQC), 19–20
- MOS (mean opinion scores), 35
- MPLS DiffServ Tunneling modes, 566
  - Pipe Mode, 573–582
  - Short Pipe Mode, 569–573
  - Uniform Mode, 567–569
- MPLS EXP bits, 84
- MPLS Traffic Engineering, 199, 587
  - basic, 588–590
  - MPLS DS-TE, 603–605
    - configuring, 606–612
    - P-router configuration, 612–613
    - show ip bgp vpnv4 all command, 615
    - show mpls traffic-eng topology command, 614
  - MPLS per-VPN TE, 591–598
    - ping vrf tunnels command, 601–602
    - show ip rsvp interface command, 599
    - show ip rsvp neighbor command, 599
    - show mpls interface command, 600
    - show mpls traffic-eng tunnels command, 601
    - show mpls traffic-eng tunnels summary command, 600
- MPLS VPN CE QoS design
  - special considerations, 550–552
    - Five-Class Provider-Edge Model, 561–563
    - Four-Class Provider-Edge Model, 559–561
    - Layer 2 access, 550–551
    - marking/re-marking, 554–556
    - service-provider service-level agreements, 551
    - TCP and UDP, 553–554
    - Three-Class Provider-Edge Model, 556–559
    - voice and call signaling, 553
    - voice and video, 553
- MPLS VPN QoS design, 547
  - case studies, 616
    - CE routers, 617–619
    - PE routers, 620–630
    - P routers, 630–631

- core considerations, 582
  - aggregate bandwidth overprovisioning, 583
  - DiffServ in the backbone, 583–587
  - MPLS traffic engineering, 587–612
- need for QoS, 548–550
- MQC (Modular QoS Command-Line Interface), 19–20
- MQC/ACL classification, 233
- MQC-based class maps, 71–72
  - ACLs, 233
- multiaction policing, 115
- Multi Point-to-Point Protocol (MLP), 136
- Multiclass Multilink PPP (MCMP), 185
- multilink fragment-delay 10 command, 185
- Multilink PPP Link Fragmentation and Interleaving (MLP LFI), 183–185
- multiple priority classes, 72

## N

- NAT transparency feature overhead, 675
- NBAR (Network-Based Application Recognition), 25, 72
  - application classification, 523–524
  - known-worm classification and policing, 526
    - Code Red, 527
    - CodeRedv2, 528
    - future worms, 533–534
    - NIMDA, 529
    - policing worms, 534–535
    - RPC DCOM/W32MS Blaster, 531–532
    - Sasser worm, 532–533
    - SQL Slammer, 530
  - Packet Description Language Modules (PDLMs), 520
  - protocol classification, 74–76
  - RTP payload classification, 77
- NBAR exchange PDLM, 532
- NBAR netbios PDLM, 532
- NBMA (nonbroadcast multiaccess), 119
- nested hierarchical policing, 115
- Network-Based Application Recognition. *See* NBAR

- networks
  - Best-Effort, 11
  - end user expectations, 9
  - management (QoS), 49
  - VoIP design considerations, 34
- NIMDA, 529
- nonbroadcast multiaccess (NBMA), 119

## O - P

- out-of-profile traffic, 227
- overprovisioning LLQ traffic, 450
- P routers, 549
- packets, 18
  - MLP, reordering, 502
  - overhead increases (IPSec QoS design), 640–642
  - packetization delay, 13
  - prefragmentation, 644
- PAK\_priority, 153, 452, 657
- PAK\_priority flag, 49
- PBR (policy-based routing), 79
- PBS (peak burst size), 112
- PDLMs (NBAR Packet Description Language Modules), 74, 520
- PE QoS considerations, 563
  - Enterprise-to-Service Provider Mapping Models
    - Five-Class Provider-Edge Model, 565–566
    - Four-Class Provider-Edge Model, 565
    - Mapping Models, 563
    - Three-Class Provider-Edge Model, 563–564
  - MPLS DiffServ Tunneling modes, 566
    - Pipe Mode, 573–582
    - Short Pipe Mode, 569–573
    - Uniform Mode, 567–569
- PE routers, 620–630
- peak burst size (PBS), 112
- peak information rate (PIR), 112, 118
- peak rate, 121
- peak-rate shaping, 121
- percent keyword, 140
- percentage-based policing, 116

- percentage-based shaping, 127
- performance (cRTP), 181
- per-Port/per-VLAN policing, 239
- PE-to-P design, 583
- PFC, configuring, 255
- PFC3, 253
- PFC3 distribution-layer Per-User Microflow Policing (Catalyst 6500), 419
- PIFS, 272
- ping vrf command, 601–602
- Pipe Mode, 573–582
- PIPQ (PVC Interface Priority queuing), 150
- PIR (peak information rate), 112, 118
- pkts matched statistics, 477
- placeholders. 568
- PoC (proof-of-concept) tests, 62
- police statements, 72
- policers, 103, 107
  - CAR, 107–108
  - class-based, 109
    - benefits, 109
    - single-rate three-color marker/policer, 110–112
    - two-rate three-color marker/policer, 112–113
  - color-aware policing, 116–117
  - color-blind policing, 117
  - compared to shapers, 104
  - default, 117
  - deploying, 106
  - DoS/worm mitigation (campus networks), 293
  - hierarchical policing, 114
    - as markers, 107
    - microflow, 257
    - multiaction policing, 115
    - percentage-based policing, 116
- policies
  - access switches, 291
  - LAN switching environments, 223
  - on P routers, 549
  - on routers, 549
- policing, 57–58
  - Catalyst 2950, 234
  - Catalyst 2970, 244
  - Catalyst 3550, 238–239
  - Catalyst 3750, 244
  - Catalyst 4500, 249–250
  - Catalyst 6500, 257–259
  - Catalyst QoS Models, 227
    - class-based, 79
    - cRTP, 180
    - LLQ, 142
    - worms, 534–535
- policy-based routing (PBR), 79
- policy-map, 20
- porting software QoS to hardware, 223
- ports
  - presetting those used by SoftPhone, 315
  - trust states, 225
- PPP, 175
- ppp multilink links minimum command, 504
- PPPoFR (PPP over Frame Relay), 177
- PQ (priority queuing), 137
- PQ-WFQ, 137–139
- pre-encryption queuing, 651–653
- prefragmentation, 645
  - IPSec transport mode, 639
  - IPSec tunnel mode, 638
- prering CAC, 212
- prioritization, 679
- priority classes, police statements, 72
- priority queuing, 137
- priority-queue out command, 240
- propagation delay, 13
- protecting video, 557
- Protocol Description Language Module (PDLM), 74, 520
- P routers, 630–631
- provisioning (bandwidth), 645–646
- proxies, 201
- P-to-P design, 583
- PVC Interface Priority queuing (PIPQ), 150
- PVCs
  - bundling, 492
  - fragmenting, 186–187
  - VoFR, 188

## Q

- QBSS IE (QoS basic service set information element), 278
- QoS
  - access-edge design, 290
  - branch routers, 513–514



- campus networks. *See* campus QoS design
- Catalyst Models. *See* Catalyst QoS models
- Cisco APs, 280–281
- classification and marking principles, 57
- control plane
  - IP routing, 48–49
  - network-management, 49
- converged networks, 12–14
- data, 42–43
  - Best-Effort data, 44
  - DLSw+, 47–48
  - locally defined Mission-Critical Data, 45
  - Transactional Data/Interactive Data, 45
- deploying, 62
- design principles, 55
- DiffServ, 16
- disabling on Catalyst 2970/3750, 343
- DoS and worm mitigation principles, 61–62
- enabling on Catalyst 2970/3750, 343
- end-to-end, 10
- evolution of, 7–8, 26, 29
- guidance, 27
- historical perspective, 5–6
- IntServ, 15
- link-specific tools, 19, 169
- models, 14
- need for on MPLS VPNs, 548–550
- network expectations of end users, 9
- policies required on WAN aggregators, 448
- policing and markdown principles, 57–58
- porting software QoS to hardware, 223
- queuing and dropping principles, 58–60
- Scavenger class, 49–54
- simplifying, 19
  - AutoQoS, 24–26
  - cross-platform feature consistency, 24
  - default behavior, 21
  - MQC, 20
  - QoS Baseline, 20–22
- tool set, 17–18, 223
- upstream vs. downstream, 271
- video, 39
  - interactive, 39
  - streaming, 41
- VoIP, 33
  - bearer traffic, 34–38
  - Call-Signaling traffic, 38
- WAN edge link-specific
  - ATM, 488–497
  - ATM-FR SIW, 497–501
  - Frame Relay, 478–487
  - ISDN, 501–504
  - leased lines, 467–478
  - wireless LANs vs. wired LANs, 270
- QoS Baseline Model, 20–21, 463–465
  - class deployment, 55
  - QoS design principles, 55
  - recommendations, 22
- QoS basic service set (QBSS), 278
- qos dbl command, 367
- QoS Design Guide, 27
- QoS group placeholder, 568
- qos map dscp to tx-queue command, 367
- QoS Pre-Classify, 649
- QoS preclassify feature, 89
- queuing, 58–60, 133–134
  - algorithms
    - CBWFQ, 140
    - comparison, 138
    - PQ-WFQ, 139
    - priority queuing, 137
    - WFQ, 137
  - buffer space, 135
  - Catalyst 2950, 235
  - Catalyst 2950 switches, 322–323
    - show wrp-queue bandwidth command, 324
    - show wrp-queue cos-map command, 325
  - Catalyst 2970, 244–246, 351–356
  - Catalyst 3550, 240–241, 336–339
    - show mls qos interface buffers verification command, 340
    - show mls qos interface queuing verification command, 341
  - Catalyst 3750, 244–246
  - Catalyst 4500, 250–252, 366–370
    - show qos dbl command, 370
    - show qos interface command, 371–372
    - show qos maps dscp tx-queue command, 370–371
  - Catalyst 6500, 259–263, 391–394
    - 1P2Q1T queuing and dropping, 401–404
    - 1P2Q2T queuing and dropping, 405–408
    - 1P3Q1T queuing and dropping, 408–410
    - 1P3Q8T queuing and dropping, 411–414

- IP7Q8T queuing and dropping, 415–418
- 12Q2T queuing and dropping, 396–400
- line card queuing structures, 393–396
- Catalyst QoS models, 228, 230
- Cisco 12000 routers, 585
- default queue limits, 338
- Layer 2 queuing mechanisms, 150
- Layer 3 queuing mechanisms
  - CBWFQ, 139–140
  - legacy, 136–137
  - LLQ, 140–149
- LLQ, 652
- policies on routers, 549
- reducing queue limits, 657
- software (WAN aggregators), 448–449
- transmit ring (Tx-ring), 136
- Tx-ring, 152
- queuing tools, 133

## R

- radio downstream QoS, 271
- radio upstream QoS, 271
- RAI (resource activity indicator), 209
- random backoffs, 273
- random-detect command
  - ecn keyword, 165
- Real-Time class
  - admission criterion, 563–565
  - bandwidth provisioning, 449
- RED (Random Early Detection), 160
- re-marking
  - MPLS VPN CE QoS design considerations, 554–556
  - traffic, 304
- reservations, 196–197
- resource activity indicator (RAI), 209
- resource-based CAC tools, 209
- RFC 2205, 195
- RFC 2597, 58
- RFC 3168, 163
- RFC 3246, 36
- ROHC (robust header compression), 171
- routers
  - branch routers, 447
  - hub routers, 548
- P routers, 549
- policies, 549
- roles in WANs, 447
- WAN aggregators, 447
  - bandwidth provisioning, 449
  - distributed platform QoS, 453
  - IP RTP header compression, 451
  - link speeds, 452
  - PAK\_priority, 452
  - required QoS policies, 448
  - serialization, 450
  - software queuing, 448–449
  - Tx-ring tuning, 451
- routing
  - DDR, 503
  - packets-per-second capability, 651
- RPC DCOM/W32/MS Blaster, 531–532
- RSVP, 195
  - admission control, 197
  - CAC, 212
  - configuring, 196
  - cRTP, 180
  - interoperability, 213
  - LLQ, 199
  - overview, 196
  - scalability, 199
  - security, 213
  - service types, 197
  - VoIP CAC through RSVP, 215
- RSVP-DiffServ integration, 200
- RSVP PATH message, 196
- RSVP RESV message, 196
- RTP header compression (cRTP)
  - class-based header compression, 178–179
  - formats, 173
    - Cisco proprietary format, 173
    - IETF format, 174
    - IPHC, 173
  - formats and encapsulation summary, 177–178
  - Layer 2 encapsulation protocol support, 175
    - Frame Relay, 176
    - HDLC, 175
    - PPP, 175
  - policing and shaping, 180
  - tunnels, 180
- RTP payload classification, 77

**S**

- SAR (Segmentation and Reassembly) engine, 675
- SAs (security associations), 638
- Sasser worm, 532–533
- scalability
  - IPSec VPN QoS design case study, 686
  - RSVP, 199
- Scavenger class
  - DoS and worm mitigation, 50–54
  - QoS, 49
- Scavenger-class QoS strategy, 294
- SCCP (Skinny Call Control Protocol), 295
- scheduling tools, 133–134
- SCSP mutation maps (Catalyst 6500), 257
- security
  - RSVP, 213
  - worms, 50
- security associations (SAs), 638
- Serial Line IP (SLIP) protocol, 173
- serialization, 678
  - delay, 13
  - WAN aggregators, 450
- servers, 303
- service provider service-level agreements, 551
- service types (RSVP), 197
- service-policy, 20
- services for CallManagers, 295
- shapers, 103, 118
  - ATM networks, 121–122
  - class-based Frame Relay traffic shaping, 123–124
  - class-based shaping, 126–127
  - compared to policers, 104
  - cRTP, 180
  - distributed traffic shaping (DTS), 128
  - Frame Relay traffic shaping (FRTS), 122–123
  - Frame Relay voice-adaptive traffic shaping, 124
  - generic traffic shaping, 126
  - peak-rate shaping, 121
  - shaping algorithms, 120
- Short Pipe Mode, 569–573
- show atm bundle command, 493
- show atm pvc command, 489
- show atm vc command, 492
- show class-map verification command, 318
- show controllers command, 451
- show frame-relay fragment command, 482
- show ima interface atm command, 495
- show ip access-list command, 521
- show ip bgp vpnv4 all command, 615
- show ip nbar port-map command, 525
- show ip rsvp interface command, 599
- show ip rsvp neighbor command, 599
- show mls masks qos verification command, 319
- show mls qos command, 358
- show mls qos interface buffers verification command, 340
- show mls qos interface policers verification command, 318
- show mls qos interface queuing verification command, 341
- show mls qos interface statistics verification command, 329
- show mls qos interface verification command, 314
- show mls qos maps command, 356
- show mls qos maps dscp-output-q command, 356
- show mpls interface command, 600
- show mpls traffic-eng topology command, 614
- show mpls traffic-eng tunnels command, 601
- show mpls traffic-eng tunnels summary command, 600
- show policy command, 456
- show policy interface command
  - high-speed leased lines, 473
  - slow-speed leased lines, 469
- show policy interface verification command, 329
- show policy-map interface command, 178
- show policy-map verification command, 318
- show port qos commands, 376–377
- show ppp multilink command, 478
- show qos acl verification command (Catalyst 6500), 380
- show qos command, 358
- show qos info config 2q2 tx verification command, 398
- show qos info runtime verification command, 399–400
- show qos interface command, 371–372
- show qos maps dscp tx-queue command, 370–371
- show qos maps verification command (Catalyst 6500), 379

show qos policer verification command (Catalyst 6500), 381  
 show qos statistics verification command (Catalyst 6500), 382  
 show queuing interface verification command, 400  
 show wrt-queue bandwidth command, 324  
 show wrt-queue cos-map command, 325  
 SI (Standard Image), 232  
 SIFS, 272  
 site-to-site V3PN, 637
 

- headend VPN edge QoS options, 665–666
- IPSec transport mode (encrypting an IP GRE tunnel), 638
- IPSec tunnel mode (encrypting an IP GRE tunnel), 639–640
- IPSec tunnel mode (No IP GRE tunnel), 638
- QoS models
  - Eight-Class Site-to-Site V3PN Model, 660–664
  - Six-Class Site-to-Site V3PN Model, 658–659
- Six-Class Site-to-Site V3PN Model, 658–659
- Skinny Call Control Protocol (SCCP), 295
- SLIP (Serial Line IP) protocol, 173
- Slow Link-Speed QoS Class Models, 454
- slow-speed ATM links, 488–489
  - ATM PVC bundles, 490–492
    - show atm bundle command, 493
    - show atm vc command, 492
  - show atm pvc command, 489
  - Tx-rings, 490
- slow-speed Frame Relay links, 480–481
- slow-speed leased lines, 467–469
  - show interface command, 469
  - show policy interface command, 470
- slow-speed links (ATM-FR SIW), 499–501
- SMI (Standard Multilayer Software Image), 243
- SoftPhone, 315
- software queuing (WAN aggregators), 448–449
- source IP address classification, 520
- speed (links), 452
- split tunneling, 679–681
- SQL Slammer, 530
- Standard Image (SI), 232
- Standard Multilayer Software Image (SMI), 243
- state-machine synchronization, 212
- streaming video, 41, 557

strict-priority queuing rule, 59  
 sum of LLQs, 450  
 Supervisor 720, 253

## T

table map feature, 98  
 tail drops, 241  
 TCP
 

- global synchronization behavior, 159
- packet loss, 656
- and UDP, 553–554

 TCP/UDP classification, 522  
 TAM (time-division multiplexing), 105  
 teleworker V3PN QoS, 666–667
 

- asymmetric links and unidirectional QoS, 677
- bandwidth provisioning, 674
  - cable overhead, 676–677
  - DSL (AAL5 + PPPoE) overhead, 675–676
  - NAT transparency feature overhead, 675
- broadband serialization mitigation through TCP
  - maximum segment size tuning, 678–679
- broadband-access technologies, 671
  - cable, 673
  - DSL, 672
- business-ready teleworker design, 666

 Deployment Models, 667, 682
 

- Dual-Unit Model, 669
- Integrated Unit + Access Model, 669–670, 684–685
- Integrated Unit Model, 668
- Integrated Unit/Dual Unit Models, 682–684
- split tunneling, 679–681

 Three-Class (Voice and Data) Model, 454–456  
 Three-Class Provider-Core Model, 583  
 Three-Class Provider-Edge Model, 556–559, 563–564  
 time-division multiplexing (TDM), 105  
 token bucket algorithms, 105  
 topologies
 

- IPSec QoS design, 646
- split tunnel, 680

 ToS (type of service), 47
 

- byte preservation, 649
- reflection, 90

total drops statistics, 477

traffic

- branch-to-branch, 548
- campus networks, 339
- campus-to-branch, 548
- classification, 68–77
- conforming, 107
- data, 42
- defined by QoS Baseline, 21
- DLSw+, marking, 48
- exceeding, 107
- handoffs, 421
- horizontal separation of, 107
- IP, 48
- LLQ, 450
- marking/remarking, 68–69, 302–304
- out-of-profile, 227
- PAK\_priority, 153
- prioritization, 679
- Scavenger, 49
- Scavenger-class QoS strategy, 294
- unpoliced classes, 109
- vertical separation of, 107
- violating, 107
- worm mitigation in Scavenger class, 51–53

Transactional Data, 45

translating Layer 2 and Layer 3 packet markings, 90

- 802.1Q/p to and from DSCP, 92–93
- DHCP to Frame Relay DE bit, 94
- IP precedence to ATM/Frame Relay PVCs, 95–96

table map feature, 98

transmit queuing (Catalyst 6500), 392

transmit ring (Tx-ring), 136

troubleshooting

- class naming, 520
- DoS attacks (campus networks), 292–294
- worms (campus networks), 292–294

trust boundaries

- access-edge, 302
  - Conditionally Trusted Endpoint Models, 303, 307–312
  - Trusted Endpoint Models, 302–304, 314–315
  - Untrusted Endpoint Models, 304–307
- defined, 302

trust states, 225

configuring trust on Catalyst 6500, 255

trust-device command, 386

trusted endpoint models, 302–304, 314–315

Catalyst 2970/3750, 343–346

Catalyst 3550, 327

Catalyst 4500, 359

Catalyst 6500, 375

show port qos command, 376–377

trusted endpoints, connecting, 304

tunnel DiffServ, 566

tunneling

cRTP, 180

modes (MPLS DiffServ), 566

Pipe Mode, 573–582

Short Pipe Mode, 569–573

Uniform Mode, 567–569

split tunneling, 679–681

tx-queue command, 367

tx-ring-limit command, 490

Tx-rings (transmit rings), 136, 152

ATM, 489

tuning, 451

type of service (ToS), 47

---

## U

UBR (unspecified bit rate), 491

UDP and TCP, 553–554

underruns (jitter buffers), 14

unidirectional applications, 513–515

unidirectional QoS, 677

Uniform Mode, 567–569

unspecified bit rate (UBR), 491

Untrusted Endpoint Models (trust boundaries), 304–307

Untrusted Multiapplication Server Model, 315–318

show class-map and show policy-map verification commands, 318

show mls masks qos verification command, 319

show mls qos interface policers verification command, 318

Untrusted PC with SoftPhone Model

Catalyst 2950, 315

Catalyst 2970/3750, 344

Catalyst 3550, 327–329

Catalyst 4500, 359–360

- Catalyst 6500, 378–379
  - show qos acl verification command, 380–381
  - show qos maps verification command, 379–380
  - show qos policer verification command, 381–382
  - show qos statistics verification command, 382
- Untrusted Server Model
  - Catalyst 2970/3750, 345
  - Catalyst 3550, 330–331
  - Catalyst 4500, 360–362
  - Catalyst 6500, 383–386
- uplink connections (DSL and cable), 677
- upstream QoS, 271

## V

- variable network delay. *See* jitter
- VBR (variable bit-rate), 673
- verification command, 320
- verifying
  - ATM IMA group, 496
  - tag-switching configuration (MPLS per-VPN TE), 600
- vertical separation of traffic, 107
- very-high-speed ATM links, 496–497
- video
  - MPLS VPN CE QoS design considerations, 553
  - QoS, 39
    - Interactive-Video, 39
    - Streaming-Video, 41
  - Streaming-Video, protecting, 557
  - surveillance systems, 303
- videoconferencing
  - any-to-any, 548–549
  - gateways and systems, 303
  - videoconferencing rate, 40
- violating traffic, 107
- viruses, 526
- VoFR (Voice over Frame Relay), 149
- voice
  - gateway packet marking, 79–81
  - MPLS VPN CE QoS design considerations, 553
  - VVLANs, 314

- Voice and Data WAN Edge Model, 454
- Voice over Frame Relay (VoFR), 149
- voice VLANs (VVLANs), 314
- VoIP (Voice over IP), 33
  - bandwidth, 36–38
  - bandwidth provisioning, 646
  - Call-Signaling traffic, 38
  - campus networks, 291
  - header-compression techniques, 170
    - class-based header compression, 178–179
    - formats, 173–174
    - Layer 2 encapsulation protocol support, 175–176
    - RTP header compression (cRTP), 172
    - standards, 171
    - TCP header compression (cTCP), 171
  - LLQ, 141
  - over ATM, 91
  - over Ethernet to VoIP over a WAN, 91
  - over MPLS, 91
  - QoS
    - bearer traffic, 34–38
    - Call-Signaling traffic, 38
    - traffic, dominating links, 449
- VPNs (virtual private networks)
  - IPSec QoS design, 635
  - MPLS VPN QoS design, 547. *See also* MPLS VPN QoS design
- VVLANs (voice VLANs), 314

## W

- WAN aggregation router QoS design
  - case study, 505–507
- WAN aggregator/branch router handoff, 420–422
- WAN aggregators, 447, 548
  - bandwidth provisioning, 449
  - distributed platform QoS, 453
  - IP RTP header compression, 451
  - link speeds, 452
  - PAK\_priority, 452
  - required QoS policies, 448
  - serialization, 450
  - software queuing, 448–449
  - Tx-ring tuning, 451

## WAN Edge Classification and Provisioning Models

## High Link-Speed QoS Class Models, 459

- Distributed-Platform/Consistent QoS Behavior QoS Baseline Model, 465–466

- Eight-Class Model, 460–462

- QoS Baseline Model, 463–465

## Slow/Medium Link-Speed QoS Class Models, 454

- Five-Class Model, 456–459

- Three-Class (Voice and Data) Model, 454–456

## WAN edge link-specific QoS design

## ATM

- high-speed links, 494–495

- medium-speed links, 493

- slow-speed links, 488–493

- very-high-speed links, 496–497

## ATM-FR SIW, 497–501

## Frame Relay, 478

- Bc, 479

- Be, 480

- CIR, 479

- distributed platform links, 486–487

- high-speed links, 484–485

- medium-speed links, 482–484

- slow-speed links, 480–482

## ISDN

- CallManager CAC limitations, 503

- MLP packet reordering, 502

- variable bandwidth, 501

- voice and data on multiple ISDN B channels, 503–504

## leased lines, 467

- high-speed, 472–478

- medium-speed, 471

- slow-speed, 467–470

## WAN edge QoS design, 514–515

## WANs, 269, 548

- link fragmentation and interleaving, 181–183
- fragment sizes, 183–184

- Frame Relay fragmentation, 185, 188–189

- IPSec prefragmentation, 190

- Multilink PPP Link Fragmentation and Interleaving (MLP LFI), 183–185

- low link speeds, 450

- routers roles in, 447

- Weighted Random Early Detection. *See* WRED

## WFQ, 137

- wireless access points, 304

- wireless IP phones, 304

## WLANs (wireless LANs)

- basic service set information element, 278

- QoS, 270

## worms, 50

- campus network mitigation strategies, 292–294

- CodeRedv2, 527–528

- compared to viruses, 526

- mitigation in Scavenger class, 51–54

- mitigation principles, 61–62

- NIMDA, 529

- policing, 534–535

- preparing for future worms, 533–534

- RPC DCOM/W32/MS Blaster, 531–532

- Sasser, 532–533

- SQL Slammer, 530

- WRED (Weighted Random Early Detection), 159–164

- Catalyst 3550, 340

- DSCP-based WRED, 162–163

- ECN, 165

- enabling on the Best-Effort class, 457

- thresholds, 241

- WRED-drop thresholds (Catalyst 6500), 262

- wrr-queue bandwidth command, 322

- wrr-queue cos map command, 240

- wrr-queue dscp-map interface configuration command, 339

- wrr-queue queue-limit command, 240

- wrr-queue queue-limit interface command, 338