

Index

Symbols

- ! wildcard, 77, 82, 86
- # key, interdigit timeout, 88–89
- . wildcard, 105–106
- == operator, 108
- @ wildcard, 76, 104–105

Numerics

- 1:1 redundancy groups, 46
- 2:1 redundancy groups, 46
- 7-digit dialing, 115–117
- 10-10 dialing, 114
- 10-digit dialing, 116–117
- 900 numbers, blocking, 118–119, 216
- 911 emergency response
 - call routing, 243–245
 - calling search space configuration*, 246
 - partition configuration*, 246
 - route filter configuration*, 246
 - route group configuration*, 245
 - route list configuration*, 246
 - route pattern configuration*, 247
 - urgent call routing*, 93
 - CER, 782
- 30,000+ user deployment model, 49

A

- A bit, 325
- AAR (Automated Alternate Routing), 63
 - configuring, 234–236
- abandoned calls, associated CDR, identifying, 587–588

- AbbrDial (abbreviated dialing) feature, 276–278
 - configuring with CallManager User Options web page, 773
- access codes
 - adding to redialed numbers, 234
 - prepending to missed calls on Cisco IP Phones, 158–164
- accessing
 - CDRs from central database, 599–601
 - reports from Serviceability Reports Archive, 523–524
 - Terminal Services Client, 537
- ACK method (SIP), 376
- active calls, 263
- active connections, device registration process, 490–491
- Ad Hoc conferences, 278, 436
 - Confirm soft key, 678, 681
 - configuring, 437–438
 - Drop Any Party feature, 279
 - Drop Last Party feature, 279
 - example of, 595–597
 - service parameter, 438
 - streams, availability of, 439
- ADC (analog-to-digital conversion), 317
- adding
 - access codes to missed calls (Cisco IP Phones), 158–164
 - access codes to redialed numbers, 234
 - audio sources to MOH servers, 461
 - IP Phone services, 300
 - participants to conferences, 436
 - phones to existing CallManager systems, 499
 - with BAT*, 501
 - with CSV files*, 500

add-ins, Cisco CallManager Dialed Number Analyzer, 250, 253
address translation, 72
Administrative Reporting Tool (ART).
 See CAR (CDR Analysis and Reporting)
admission control, 57–58
Admission messages (H.225 RAS),
 UUIE fields, 801–803
admissions control
 H.323 gatekeeper, 64–66
 locations, 63–64
admissions requests, 352–355
Aggregator Layer (signaling), 40, 314
alarm definitions (Cisco CallManager Serviceability)
 configuring, 513
 viewing, 514
alerting names, configuring, 281
alerts, CAR, 511
algorithms
 call preservation, 487
 fallback, 488–489
ALI (automatic location identification), 243
allocating media resources
 conference bridge resources, 429
 MRGs, 415–416
 MRM, 418
analog interfaces, 317
 E&M signaling, 320
 FXS/FXO signaling, 317–319
analyzing trace information, 521
 SDI trace output, 516
annunciators, 474–475
 device control process, 475
 localization, 475
 performance counters, 477
 resources, 403
 servers configuration, 476

Answer/Release, 616
APDUs (application protocol data units), 336, 814
 delivery models, 337
 for call completion, 814
 for call diversion, 815
 for call transfer, 816–817
 for message waiting, 817
 for name services, 817
 for path replacement, 818
APIs (application programming interfaces), 304
 AXL SOAP API, 767–768
 Cisco IP Phones productivity services, 668
application layers external to CallManager, 304
 JTAPI, 306–307
 TAPI, 304–306
application protocols, JTAPI
 Call Center Capabilities package, 834–835
 Call Center Events package, 835–837
 Call Center package, 832–834
 Call Control Capabilities package, 839–840
 Call Control Events package, 841–842
 Call Control package, 837–839
 Capabilities package, 842
 Core package, 830–832
 Events package, 842–843
 Media Capabilities package, 844
 Media Events package, 845
 Media package, 843–844
 package support, 830
application solutions, 779
 call preservation support, 487
 Cisco AVVID IP Telephony
 Applications SDK, 779–780
 AST, 776
 BAT, 768

- Cisco CallManager Serviceability*, 770
- Cisco DPA voice mail gateways*, 763
- Cisco IP Phone Configuration Web page*, 771
- Cisco IP/VC*, 765
- Cisco IPCC*, 783
- CMI*, 775
- LDAP support*, 766, 775
- TAPS*, 743, 776
- Cisco CallManager Attendant Console, 781–782
- Cisco Emergency Responder, 782–783
- Cisco IP Communications system, 761
- Cisco IP Phone Address Book Synchronizer, 785
- Cisco IP Phone Services SDK, 785–786
- Cisco JTAPI Software, 780
- Cisco MeetingPlace, 786
- Cisco MeetingPlace Express, 786
- Cisco Personal Assistant, 787
- Cisco TAPI Software, 779
- Cisco Unity, 787
- Cisco Unity Express, 788
- Cisco WebDialer, 788–789
- IPCC, 783
- IPMA, 784
- applying**
 - dialing transformations, 124–126
 - outside dial tone, 95–99
- architectural layers, 40–42**
 - conference resources, 427
 - Protocol Layer*, 427
 - Supplementary Services Layer*, 427
 - CTI
 - application layers*, 304
 - CTI layer*, 307
 - MOH subsystem, 459
- area codes, metro dialing, 115–116. See also TLAs (Telealues)**
- AREA-CODE tag, 115**
- ARQ (Admission Request) messages, 352–355**
- ART (Administrative Reporting Tool). See CAR (CDR Analysis and Reporting)**
- assigning**
 - button templates, 276
 - gateways to route groups, 180–181
 - MOH stream sources, order of precedence, 468
 - MRGLs to endpoints, order of precedence, 417–418
 - priority values to calls, 101–102
 - resources to MRGs, 423–425
 - route groups to route lists, 181–183
 - route patterns, 76, 227
- AST (Admin Serviceability Tool). See RTMT (Real-Time Monitoring Tool)**
- Attendant Console, 781–782**
- Attendant DN, 137–138**
- AUCX (audit connection) command (MGCP), 367, 373–375**
- audio channel processing, 408**
- audio sources (MOH), 458–460**
 - adding to MOH servers, 461–462
 - audio source IDs, 459
 - play mode, configuring, 462–463
 - stream connection errors, 463
- Audio Translator service parameters, 462**
- AUEP (audit endpoint) command (MGCP), 367**
- Aupair, 558**
- authCodeDescription field (CDR), 576**
- authentication, 339**
- authorization, 340**
- AuthorizationLevel field (CDR), 576**
- Auto Answer feature, 282–283, 625**
- automatic gatekeeper discovery, 348**
- automatic location identification (ALI), 243**
- automatic report generation (CAR), 506**
- auto-registration, 433–434**
- availability**
 - of conference bridges, 428, 440
 - of conference servers, 432
 - of FXS/FXO interfaces on Cisco gateways, 319
 - of media processing resources, 438–439
 - of transcoders, 452–455
- available conference bridge resources, allocating, 429**
- AVC (Advanced Video Coding), 394**
- AVVID. See Cisco AVVID IP Telephony**
- AXL (AVVID XML Layer) API, 767–768**

B

- B bit, 325**
- B2BUA (back-to-back user agent), 374**

background noise, 395
backhaul, 315, 368–370
bandwidth, changing during H.323 calls, 356
bandwidth consumption of voice codecs, 393
Bandwidth messages (H.225 RAS), UUIE fields, 803–804
barge feature, 270–272
 built-in bridge support, 428–429
basic calls, 549
BAT (Bulk Administration Tool), 497–498, 634, 768
 adding users with CSV files, 500–501
 goal of using, 498
 managing established CallManager systems, 499
 misconfiguration of, 498–499
 phone certificates, updating, 501
 setting up CallManager database, 499
 TAPs, 501
billing, OnNet versus OffNet calls, 603
bit rates of voice codecs, 393
blind transfers, 745
block structure of CallManager, 388
blocking
 900 numbers, 118–119, 216
 international calls, 114
 long distance carrier selection, 114
BRI (Basic Rate Interface), 326, 329
 availability on Cisco gateways, 329–330
 ISDN Q.931 timers, 330–331
broadcast paging support, 633
BRQ (Bandwidth Request) messages, 356
built-in bridges
 resources, 404
 controlling allocation of, 412
 support on barge feature, 428–429
bulk transactions, performing with CSV files, 500–501
button templates. assigning, 276

C

CAC (call admission control)
 locations-based, 63
 message fields, 801–804
call appearances, 240

Call Center Capabilities package, Cisco JTAPI support, 834–835
Call Center Events package, Cisco JTAPI support, 835–837
Call Center package, Cisco JTAPI support, 832–834
call classification, 99
call completion APDUs (QSIG), 814
call control
 CallManager's role for station devices, 285
 processing gateway directory numbers, 603
Call Control Capabilities package, Cisco JTAPI support, 839–840
Call Control Events package, Cisco JTAPI support, 841–842
Call Control Layer (signaling), 42, 260, 314, 387–389
call control models, H.323, 343
Call Control package, Cisco JTAPI support, 837–839
call diversion APDUs (QSIG), 815
call establishment
 in circuit-switched networks, 9–10
 in Cisco AVVID IP Telephony networks, 33
 media exchange phase, 10
 on VoIP systems, 32–34
 session establishment, 9
Call Forward Busy, 643
Call Forward No Answer, 643
call forwarding
 Call Forward Busy, 643
 Call Forward No Answer, 643
 configuring with CallManager User Options web page, 773
 reason codes, 644
call forwarding calling search space, 196–197
call forwarding feature, UA
 accessibility to, 380
call hunting constructs, 74, 168
 hunt lists, 169–174
call leg IDs, 568
call legs, 397, 568
 precedence levels, 582
Call Management Records (CMRs), 547.
 See also CDR data; CDRs
Call Park, 645–646
Call Pickup, 646–647

call preservation, 371, 478–479, 648

- algorithms, 487
- examples, 483–485
- supported devices, 487

call processing video calls, 471

- performance monitoring, 471–473

call reports (CAR), 507**call routing, 80–86, 114–121**

- address translation, 72
 - by organization, 72, 188
 - by security level of user, 188
 - call hunting constructs, 74
 - calling search spaces, 75
 - delays, troubleshooting, 253
 - dialing behavior, 78–79
 - dialing transformations, 74
 - endpoint determination, 71
 - geographical routing, 220–232
 - individualized routing, 72
 - interdigit timeouts, 87
 - overlapped sending, 90–91
 - partitions, 75
 - pattern matching, 80–81
 - route filters, 74–75, 106, 110–113
 - for North American numbering plan, 113–114*
 - INTERNATIONAL-ACCESS DOES-NOT-EXIST, 114*
 - length limitations, 106*
 - toll-free numbers, 117*
 - route patterns, 74–76
 - . wildcard, 105–106*
 - @ wildcard, 104–105*
 - constraining, 113*
 - operators, 108–109*
 - tags, 107–108*
 - urgent calls, 93*
 - routing by class of calling user, 214–218
 - stages, 124–126
 - transformations, on terminating device, 142–146
 - translation patterns, 74, 146–148
- call signaling, 285, 300**
- between Cisco IP Phones, 822–829
 - Cisco IP Phones, 823, 826
 - H.225 messages, UUIE fields, 808–813
 - H.323, 812
 - call signaling phase, 342*
 - H.225, 356, 360–364*
 - RAS, 346–356*

- session establishment, 9–10

call transfer APDUs (QSIG), 816–817**CallDiagnosticsEnabled service****parameter, 554****called party transformations, 122, 184–186**

- applying, 124–126
- called party transformation mask, 141
- digit discarding instructions, 140
- masks, 140
- prefix digits, 141
- presentation settings, 127–129

caller ID, UA accessibility to, 381–382**Caller ID DN transformation, 143****callIdentifier field (CMR), 584****calling entities, 191–192****Calling Line ID Presentation****transformation, 144****Calling Party Number Screening Indicator****service parameter, 131–132****Calling Party Selection transformation, 144****calling party transformations, 121–123, 141, 184–186**

- masks, 142
- presentation settings, 127–129

calling search spaces, 75, 148, 188, 191–192, 685

- analogies to, 189
- behavior, 190
- call appearances, configuring, 240–243
- call forwarding, 196–197
 - manually configuring, 203*
- configuring, 196
- example of, 192–196
- interaction with unified messaging systems, 198–201
- QSIG, 210
 - call forward by rerouting, 211–213*
 - path replacement, 213–214*

callingPartyNumber field (CDR), 570**callingPartyNumberPartition field (CDR), 570****CallManager Administration**

- change notification, 628–629
- Phone Configuration page, 297
- plugins, CAR, 502

CallManager database

- performing bulk operations, 497–498
- purging, 511
- setting up with BAT, 499

CallManager list, 486

- CallManager Serviceability, 662, 770**
 - component version information, displaying, 524
 - Control Center, 522
 - QRT, 522
 - Service Activation, 522
- CallManager User Options web page, 771, 773–774**
- CallParkReversionTimeout service parameter, 646**
- calls**
 - less than 1 second, logging, 553
 - selecting, 265
- campus networks, CallManager deployment strategies, 50–51**
- Capabilities package, Cisco JTAPI support, 842**
- CAR (CDR Analysis and Reporting), 502, 769**
 - alerts, 511
 - call reports, 507
 - CDR data, loading, 505
 - conference bridge reports, 508–509
 - FAC/CMC reports, 510
 - features, 504
 - gateway reports, 508
 - goal of using, 502–503
 - malicious call detail reports, 510
 - precedence call summary reports, 510
 - pregeneration of reports, 506
 - QoS reports, 509
 - monthly summary reports, 503*
 - route plan reports, 508
 - system overview reports, 509
 - traffic summary reports, 507
 - user reports, 507
 - voice messaging reports, 509
- CAS (Channel Associated Signaling), 324**
 - interfaces, availability on Cisco gateways, 326
- case studies**
 - routing by class of calling user, 214–218
 - routing by geographic location, 220–232
- Catalyst 4000 conference bridges, mixed-mode conference bridge support, 430**
- Catalyst 6000 conference bridges, mixed-mode conference bridge support, 430**
- cBarge feature, 270–273**
- CBC (Cipher Block Chaining) symmetric encryption, 299**
- CCC (Cisco Conference Connection), 786**
- CCM MIB extension agent, updating, 542**
- CCM traces. *See* SDI tracing**
- CCS (Common Channel Signaling), 328**
- CDP (Cisco Discovery Protocol), 542**
- CDP MIB extension agent, 542**
- CDR data, 502, 547, 549. *See also* CDRs**
 - CMRs, field definitions, 584–585
 - format, 559–560
 - GCIDs, 566
 - examples of, 567–568*
 - generating, service parameters, 551–552
 - storing, 554–557
- CdrEnabled parameter, enabling/disabling CDR data generation, 552**
- CdrLogCallsWithZeroDurationFlag service parameter, 553–554**
- cdrRecordType field**
 - of CDRs, 570–576
 - of CMRs, 584–585
- CDRs (call detail records)**
 - abandoned calls, identifying, 587–588
 - accessing from central database, 599–601
 - associated CMRs, identifying, 586
 - calls between endpoints, identifying, 586
 - calls between IP phones, identifying, 587
 - comment field, 583
 - data types, 562
 - fields, 561, 569–575
 - call leg IDs, 568*
 - directory numbers, 568*
 - duration field, 569*
 - OnBehalfOf, 580–581*
 - partitions, 569*
 - unused, 562*
 - for zero duration calls, 588
 - IP Phone malfunctions, identifying, 588
 - maintaining
 - administrator's responsibility, 600–601*
 - storage limitations, 601*
 - malicious calls, identifying, 589
 - precedence calls, identifying, 589
 - processing guidelines, 602
 - redirected calls, identifying, 589
 - selecting storage location, 559–560
 - short calls, identifying, 588

- storage of
 - data types*, 563–564
 - troubleshooting*, 604
- transferred calls, identifying, 590
- unused fields, 562
- video calls, identifying, 589
- central CDR data store, 554**
 - loss of connectivity, contingencies, 557–558
- centralized call processing, 36**
- centralized system administration, 654**
- CER (Cisco Emergency Responder), 782–783**
- certified servers for CallManager installation, 20–22**
- CFwdAll soft key, 639–640**
- change notifications, 628–629**
- changing ring options, 268**
- circuit switched networks, 4**
 - analog interfaces, 317
 - E&M signaling*, 320
 - FXS/FXO signaling*, 317–319
 - call establishment, 9–10
 - digital interfaces, 317, 320–323
 - BRI*, 326, 329
 - CAS*, 324
 - framing bits*, 324
 - PRI*, 326, 329
 - QSIG*, 332–337
 - TDM*, 322–323
 - endpoints, 10
 - line cards, 8
 - PCM, 6
 - redirected call handling, 337–338
 - trunk cards, 8
 - versus packet switched, 6
- Cisco Applications SDK, 779–780**
- Cisco ATA (Analog Telephone Adaptors), 763**
- Cisco AVVID IP Telephony, 11**
 - applications
 - Applications SDK*, 779–780
 - AST*, 776
 - BAT*, 768
 - Cisco CallManager Serviceability*, 770
 - Cisco DPA voice mail gateways*, 763
 - Cisco IP Contact Center*, 783
 - Cisco IP Phone Configuration Web page*, 771
 - Cisco IP/VC*, 765
 - CMI*, 775
 - LDAP support*, 766, 775
 - TAPS*, 743, 776
 - call establishment, 33
 - clustering
 - centralized call processing*, 36
 - distributed call processing*, 36
 - Cisco-certified servers, 20–22
 - IP Telephony, Windows 2000 services, 23–24
 - QoS, 57
 - admission control*, 57–58
 - H.323 gatekeeper*, 64–66
 - IP precedence*, 59–60
 - locations*, 64
 - traffic classification*, 57
 - traffic prioritization*, 57
 - redundancy, 36–37, 43
 - reliability, 36
- Cisco CallManager releases, 11**
 - Multimedia Manager 1.0, 12
 - release 3.0, 14–15, 20
 - release 3.1, 15
 - release 3.2, 16
 - release 3.3, 16
 - release 4.0, 17–19
 - release 4.1, 19
 - Selsius-CallManager 1.0, 13
- Cisco CallManager Administration, MOH configuration, 465–467**
- Cisco CallManager Attendant Console, 781–782**
- Cisco CallManager Serviceability, 512, 770**
 - alarms
 - configuring*, 513
 - definitions, viewing*, 514
 - SDI tracing, 515–517
 - SDL tracing, 517
 - Trace Analysis, 521–522
 - traces, configuring, 517–520
- Cisco CallManager Trace Collection Tool, 789**
- Cisco Dialed Number Analyzer, 789**
- Cisco Discovery Protocol (CDP), 542**
- Cisco DPA voice mail gateways, 763**
- Cisco EGW (Enterprise Gateway), 769**
- Cisco gateways**
 - CAS interface support, 326
 - signaling connections to CallManager, security, 340

- Cisco IOS Telephony Services, CME (Cisco CallManager Express), 770**
- Cisco IP Communications network**
 - call establishment, 32–34
 - clustering, 35–36
 - ICCS, 40
- Cisco IP Communicator, 777**
- Cisco IP IVR (IP Interactive Voice Response), 790**
- Cisco IP Phone 7912G, 289**
- Cisco IP Phone 7914 Expansion Module, 291**
- Cisco IP Phone 7920G, 288**
- Cisco IP Phone 7935, 25**
- Cisco IP Phone 7940, 289**
- Cisco IP Phone 7940G, 289, 291**
- Cisco IP Phone 7941G, 289, 291**
- Cisco IP Phone 7905G, 289**
- Cisco IP Phone 7960, 25, 289, 291**
- Cisco IP Phone 7960G, 289, 291**
- Cisco IP Phone 7961G, 289, 291**
- Cisco IP Phone 7970G, 289, 291**
- Cisco IP Phone 7971G-GE, 289, 291**
- Cisco IP Phone 7985G, 291**
- Cisco IP Phone Address Book Synchronizer, 785**
- Cisco IP Phone Configuration web page, 662, 771**
- Cisco IP Phone Configuration web pages**
- Cisco IP Phone Productivity Services, 668**
- Cisco IP Phone Services SDK, 785–786**
- Cisco IP Phones**
 - Answer/Release, 616
 - call signaling, 300, 822–829
 - Cisco IP Communicator, 292
 - Cisco IP Conference Station 7936, 291
 - Cisco Wireless IP Phone 7920, 289
 - Confirm soft key, 436
 - Dial soft key, 157
 - EditDial soft key, 158
 - failure of, troubleshooting, 588
 - i button, context-sensitive help, 682
 - Missed Calls menu, 157–158
 - Placed Calls menu, adding access codes to redialed numbers, 234
 - Received Calls menu, 157–158
 - registration, 292–296
 - security, 296
 - configuration file security, 298–299*
 - configuring, 297–298*
 - device identity security, 298*
 - media privacy, 299*
 - services, 300–301
 - softkeys, 852
 - supported URIs, 855
 - Dial URI, 857*
 - EditDial URI, 858*
 - Init URI, 857*
 - Key URI, 855–856*
 - Play URI, 858*
 - QueryStringParam URI, 856*
 - RTP Streaming Control URIs, 856*
 - unregistration sequence requirements, 490
 - volume controls, 756
 - XML services, 785–786
 - XML support
 - CiscoIPPhoneDirectory data type, 850*
 - CiscoIPPhoneError data type, 854*
 - CiscoIPPhoneExecute data type, 853*
 - CiscoIPPhoneGraphicFileMenu data type, 850*
 - CiscoIPPhoneGraphicMenu data type, 849*
 - CiscoIPPhoneImage data type, 847–848*
 - CiscoIPPhoneImageFile data type, 848–849*
 - CiscoIPPhoneInput data type, 851–852*
 - CiscoIPPhoneMenu data type, 845*
 - CiscoIPPhoneResponse data type, 854*
 - CiscoIPPhoneStatus data type, 853*
 - CiscoIPPhoneText data type, 846*
 - IconMenu data type, 846*
- Cisco IP QM (IP Queue Manager), 790**
- Cisco IP SoftPhone, 668**
- Cisco IP Videoconferencing, 765**
- Cisco IP Voice Media Streaming App, 435**
- Cisco IP/VC (IP Videoconferencing), 765**
- Cisco IPCC (IP Contact Center), 783**
- Cisco JTAPI (Java Telephony Application Programming Interface) Software, 780**
- Cisco MCS 7800 series servers, 22–23**
- Cisco MeetingPlace, 786**
- Cisco MeetingPlace Express, 786**
- Cisco Personal Address Book, 669**
 - configuring with CallManager User Options web page, 774
- Cisco Personal Assistant, 787**
- Cisco PGW 2200 Softswitch, 769**

- Cisco TAPI (Telephony Application Programming Interface) Software, 779
- Cisco TSP (TAPI Service Provider), 779
- Cisco Unity, 787
- Cisco Unity Express, 788
- Cisco VG248, 764
- Cisco VT Advantage, 302, 778
- Cisco wave driver, 780
- Cisco WebAttendant, 658
- Cisco WebDialer, 788–789
- Cisco-certified servers for running AVVID, 20–22
- CiscoIPPhoneDirectory XML data type, 850
- CiscoIPPhoneError XML data type, 854
- CiscoIPPhoneExecute XML data type, 853
- CiscoIPPhoneGraphicFileMenu XML data type (XML), 850
- CiscoIPPhoneGraphicMenu XML data type, 849
- CiscoIPPhoneImage XML data type, 847–848
- CiscoIPPhoneImageFile XML data type, 848–849
- CiscoIPPhoneInput XML data type, 851–852
- CiscoIPPhoneMenu XML data type, 845
- CiscoIPPhoneResponse XML data type, 854
- CiscoIPPhoneStatus XML data type, 853
- CiscoIPPhoneText XML data type, 846
- Cisco Works, 538–539, 792
 - PathTool, 540
 - syslog analysis tools, 539–540
- Class 5 switches, 4
- class of service field (802.1Q packets), packet classification, 59–60
- CLID (calling line ID), 280), 649–651
- client devices
 - gateway devices, 26
 - media processing devices, 27
 - station devices, 25–26
- clientMatterCode field (CDR), 576
- clients of Cisco IP Communications system, 760
- clipping, 9
- closest match routing, 82–84, 239
 - blocking 900 numbers, 119
 - interdigit timeouts, 87
 - patterns, troubleshooting, 254
- Cluster Security Mode enterprise parameter, 298
- clustering, 11, 35–36
 - admissions control, H.323 gatekeeper, 64–65
 - central database, 555–557
 - centralized call processing, 36
 - communication between nodes, 39
 - device redundancy, 43
 - device registration, 433–434
 - distributed call processing, 36
 - enterprise deployment, 50
 - combined multiple-site model*, 57
 - multiple-site IP WAN model with distributed call processing*, 52–54
 - multiple-site model with centralized call processing*, 55
 - multiple-site model with independent call processing*, 53
 - single-site model*, 50–51
 - ICCS, 40
 - in fully meshed topologies, 38
 - inserting transcoders, rules, 452–454
 - intracluster communication, 42
 - media resources, organizing, 422–425
 - multitenant applications
 - calls between tenants*, 166–167
 - extension mapping*, 165
 - nodes, fault tolerance, 559
 - node-to-node communication
 - failure, handling, 483
 - over the WAN, 35
 - reliability of, 36–37
 - server deployment, 44–45
 - 10,000+ users*, 49
 - 1-1 redundancy groups*, 46
 - 2-1 redundancy groups*, 46
 - 2500 or less users*, 47
 - 30,000+ users*, 49
 - 5,000 to 10,000 users*, 48
- CMCs (client matter codes), 103–104
- CME (Cisco CallManager Express), 770
- CMI (Cisco Messaging Interface), 199–200, 775
- CMRs (Call Management Records), 547, 550.
 - See also CDR data*
 - associated CDRs, identifying, 586
 - enabling/disabling generation of, 554
 - field definitions, 584–585
 - unused fields, default value, 562

CNID (calling party name identification), 280, 652**codecs, 7, 322**

- high-bandwidth, 392
- low-bandwidth, 392
- mixed-mode conferences, 429
- transcoding, 397
- Video Codecs, 393–394
- video conferences, resource allocation, 431
- voice codecs, 391, 393–394

collecting traces, 533–535**combined multiple-site model, 57****comfort noise, 395****commands**

- grep, 78
- MGCP, 366–367
- mgcp package-capability srtp-package, 341

comment field (CDR), 575), 583**communication**

- between CallManager nodes, 39
- Cisco CallManager-to-device failure, handling, 482
- node-to-node failure, handling, 483

comparing

- call establishment on circuit-switched and packet-switched call models, 32, 34
- closest match routing and longest match routing, 82
- IP telephony and traditional telephone networks, 3–4, 7
- redundancy of traditional telephone systems and Cisco AVVID IP Telephony, 36–37

complex MOH configurations, 468**components of Cisco IP Communications****system**

- applications, 761
- clients, 760
- infrastructure solutions, 759–762
 - Cisco ATA*, 763
 - Cisco DPA gateways*, 763
 - Cisco IP/VC*, 765
 - Cisco VG248*, 764
 - SRST*, 766
- system tools, 761
- telephony services, 760

Computer Telephony Interface (CTI).**See CTI****conference bridges**

- availability, 438–440
- CAR reports, 508–509
- Cisco IP Voice Media Streaming Application, 435
- configuring, 434–435
- controlling server usage, 432
- DSP farms, 435
- mixed-mode conference support, 430
- registration, 432
- resources
 - allocating*, 429
 - availability*, 428
 - device control process*, 428
 - hardware-based, codec support*, 429

conference calls

- ad hoc, 278, 436
 - Conference button*, 678, 681
 - Drop Any Party feature*, 279
 - Drop Last Party feature*, 279
 - examples of*, 595–597
- CDRs, GCIDs, 567–568
- configuring, 437–438
- examples, 595–597
- maximum participation, 431
- Meet-Me calls, 436, 713
 - examples*, 597–598
 - features*, 437
- mixed-mode, 429
- on hold, 467
- participation, extending, 431
- resource limitations, 426–427
- service parameters, 438
- unicast, 751
- video, resource allocation, 431

conference controllers, 432, 436, 678**conference resources, architecture, 427****conference servers, 432****configuration file security, 298–299****configuring, 214–216, 218**

- AAR, 234–236
- Ad Hoc conferencing, 436
- annunciator servers, 476
- call appearances, 240–243
- call park, 645–646
- calling search spaces, 196
- CAR, alerts, 511
- CDR data transfer interval, 558
- codec packet generation, 391, 394

- conference bridges, 434–435
- conferencing, 437–438
- device registration, 433–434
- dialing alias, 150
- digital gateways, 138–139
- geographical routing, toll-bypass, 219–233
 - calling/called party transformations, applying*, 229
 - calling search spaces, configuring*, 230–231
 - configuring*, 219–233
 - External Route Plan Wizard*, 220
 - inbound dialing*, 231
 - outbound dialing*, 224
 - route groups, creating*, 224–227
 - route filters, creating*, 227–228
 - translation patterns, defining*, 231–232
- H.323
 - endpoints*, 310
 - gatekeeper*, 65
- hotlines, 151–153
- Meet-Me conferencing, 436
- MOH servers, 458–459
 - audio source play mode*, 462–463
 - examples*, 466–467
 - Multicast MOH*, 464–465
- MTPs, 455
- outside dial tone, 95–99
- phone options via Cisco CallManager User
 - Options web page, 773–775
- phone security options, 297–298
- PSTN fallback routing, 65
- time-of-day routing, 208–210
- tracing on CallManager Serviceability, 517–518
- transcoders, 455
- translation patterns, 147–148
- translations
 - on calls from CallManager to PSTN*, 160
 - on inbound calls*, 159
- user restrictions, 215–216
 - lobby phones*, 217–218
- Confrn soft key, 436**
- connected ID, UA accessibility to, 381–382**
- connections**
 - call legs, 397, 568
 - call preservation, 478–479
 - using transcoder, 408–411
- connectivity to central database, loss of, contingencies, 557–558**
- constraining route patterns, 113**
- consultation transfers, 745**
- context-sensitive help, 682**
- continuous play mode (MOH), configuring, 462**
- controlling**
 - allocation of media resources, 411
 - built-in bridge resource allocation*, 412
 - MRGs*, 415–416
 - MRM*, 418
 - CDR storage location, 559–560
 - conference bridge server usage, 432
 - silence suppression, 396
 - stored CDR data format, 559–560
- converting signed integer values to IP addresses, 563–565**
- Core package, Cisco JTAPI support, 830–832**
- corporate networks, call routing, 72**
- counters, 457**
 - descriptions, viewing, 528
 - annunciator-related, 477
 - hardware conference server-related, 443
 - MOH server-related, 469–470, 477–478
 - monitoring from RTMT, 528
 - MTP device-related, 456–457
 - transcoder-related, 456–457
 - unicast conference resources, 440–442
 - unicast software conference-related, 442–443
 - video call processing-related, 471–473
- CRCX (create connection) command, 367**
- creating**
 - CDR data, service parameters, 551
 - conference bridge resources, 427
 - conferences, resource availability, 438–439
 - route filters, 227
- CSA (Cisco Security Agent), 790–791**
- CSV (comma separated value) files**
 - adding users, 500
 - creating for bulk transactions, 500–501
- CTI (Computer Telephony Integration), 284–286**
 - application architecture, 303
 - application layers external to CallManager*, 304–307
 - CTI layer*, 307–308

CTIQBE, Cisco CallManager/Cisco TSP communication, 305
CTLs (Certificate Trust Lists), 298
customizing
 Microsoft Performance, 532
 traces, 517

D

DAC (digital-to-analog conversion), 317
data types, 562–564
database, 510
 automated change notification, 627
 CDR data transfer interval, configuring, 558
 CDRs
 accessing, 599–601
 data types, 562–564
 fields, 569–575
 centralized architecture, 555–557
 Publisher, 37
 purging, 511
 subscriber, 38
dateTimeDisconnect field (CDR), 575
dateTimeStamp field (CMR), 584
debug trace level settings, 517
dedicated servers, 22
default configuration
 of conference servers, 432
 of media resources, 412
default technology prefix, 355
delivering voicemail to correct mailbox number, 205
deploying
 CallManager in enterprise networks, 50
 combined multiple-site model, 57
 multiple-site IP WAN model with distributed call processing, 52–54
 multiple-site model with centralized call processing, 55
 multiple-site model with independent call processing, 52–53
 single-site model, 50–51
 servers within CallManager clusters, 44–45
 10,000+ users, 49
 1-1 redundancy group, 46
 2-1 redundancy group, 46
 2500 or less users, 47
 30,000+ users, 49
 5000 to 10,000 users, 48

destCallTerminationOnBehalfOf field (CDR), 573
destCause_location field (CDR), 574
 field definitions, 577
destCause_value field, field definitions, 578–580
destConversationId field (CDR), 573
destDeviceName field (CDR), 572
destinations (route patterns), selecting, 78–80
destIpAddr field (CDR), 573
destIpPort field (CDR), 573
destLegIdentifier field (CDR), 572
destMediaCap_g723BitRate field (CDR), 575
destMediaCap_maxFramesPerPacket field (CDR), 574
destMediaCap_payloadCapability field (CDR), 574
destMediaTransportAddress_IP field (CDR), 574
destMediaTransportAddress_Port field (CDR), 574
destNodeId field (CDR), 572
destVideoCap_Bandwidth field (CDR), 575
destVideoCap_Codec field (CDR), 575
destVideoCap_Resolution field (CDR), 575
destVideoTransportAddress_Ip field (CDR), 575
destVideoTransportAddress_Port field (CDR), 575
device control process, 428, 455, 475
device identity security, 298
device pools, 350, 684
device profile locale, configuring with CallManager User Options web page, 774
deviceName field (CMR), 584
devices
 call preservation support, 487
 calling search spaces, 191–192
 example, 192–196
 Cisco IP Phones, 287, 396
 Answer/Release, 616
 call signaling, 300, 822–829
 Cisco IP Communicator, 292
 Cisco IP Conference Station 7936, 291
 Cisco IP Phone 7905G, 289
 Cisco IP Phone 7912G, 289
 Cisco IP Phone 7914 Expansion Module, 291
 Cisco IP Phone 7920G, 288

- Cisco IP Phone 7940G*, 289, 291
- Cisco IP Phone 7941G*, 289, 291
- Cisco IP Phone 7960G*, 289, 291
- Cisco IP Phone 7961G*, 289, 291
- Cisco IP Phone 7970G*, 289, 291
- Cisco IP Phone 7971G-GE*, 289, 291
- Cisco IP Phone 7985G*, 291
- Cisco Wireless IP Phone 7920*, 289
- Confrn soft key*, 436
- registration, 292–296
- services, 300–301
- soft keys, 852
- Transit Logic Channel*, 396
- unregistration sequence
 - requirements, 490
 - XML data types, 845, 852
- clusters, registration, 433–434
- codecs, transcoding, 397
- conference bridges
 - availability, 438–440
 - Cisco IP Voice Media Streaming Application*, 435
 - configuring, 434–435
 - DSP farms, 435
 - registration, 432
- endpoints, handling failure of, 482
- gateway devices, 26, 261, 314
 - backhauling, 315
 - interaction with *CallManager*, 316
 - purpose of, 313
 - registration, 371
- H.323 endpoints, 286, 308–310
- inter-*CallManager* replication, 39
- intracluster communication, 42
- media processing devices, 27
 - handling failure of, 482
 - MOH resources, 28
 - MTP resources, 27
 - transcoding resources, 27
 - unicast conferencing devices, 27
- media resource registration sequence, 407
- MTPs, 400–401
- opening HTTP connections, 527
- recovering after failure, 486
- redundancy, 43
- registration, 455
 - during active connections, 490–491
 - fallback, 489
 - switchback, 488
 - switchover, 486
- route patterns, 75–76
- SCCP station devices, 286
- station devices, 25–26, 261
 - CallManager support*, 284
 - Cisco CallManager support*, 262
 - TFTP functionality, 295
- terminal endpoints, 261
- time-matching, 516
- transcoders, 397
 - as alternative to codecs, 450
 - availability, 452–455
 - configuring, 455
 - counters, 456–457
 - inserting into clusters, 452–454
 - logical connections between IP Phones, 408–411
- unicast conference bridges, 398
 - hardware-based, 400
 - software-based, 399
- voice codecs, 391, 394
 - bandwidth consumption, 393
- devices supported by *CallManager*, 126**
- device-to-device communication failure, handling, 483**
- diagnostics. *See* tracing; troubleshooting**
- dial plans**
 - address translation, 72
 - international, 249
 - U.K., 94–95
- Dial soft key (Cisco IP Phones), 157**
- dial tone, troubleshooting, 253**
- Dial URI support on Cisco IP Phones, 857**
- Dialed Number Analyzer, 250, 253**
- dialing behavior, 78–79**
 - aliases, configuring, 150
 - call classification, 99
 - enblock dialing, 136
 - MLPP precedence, 101
 - outside dial tone, 95–99
 - overlapped dialing, 136
 - urgent route patterns, 93
- dialing transformations, 74, 121**
 - applying, 124–126
 - masking, 127
 - on terminating device, 142–146
 - Caller ID DN*, 143
 - Calling Line ID Presentation*, 144
 - Calling Party Selection*, 144
 - service parameters, 130

- Calling Party Number Screening Indicator*, 131
 - Matching Calling Party Number With AttendantFlag*, 132
 - Numbering Plan Info*, 133–134
 - Overlap Receiving Flag For Pri*, 133
 - Strip # From Called Party Number*, 133
 - Unknown Caller ID*, 133
- Significant Digits, 138
 - versus translation patterns, 121
- DID (direct inward dial)**, 122, 686
- DiffServ**, 60
- digit discarding instructions**, 106, 114, 140
 - troubleshooting, 254
- digital gateways**, 138–139
- digital interfaces**, 317, 320–323
 - BRI, 326, 329–331
 - CAS, 324
 - framing bits, 324
 - interleaving, 317
 - PRI, 326
 - ISDN Q.931 timers*, 330–331
 - QSIG, 332
 - APDUs*, 336–337
 - connection establishment*, 336
 - FACILITY message*, 336
 - feature-to-feature communication*, 335–337
 - redirected call handling*, 337–338
 - vendor-specific features*, 334–335
 - TDM, 322–323
- digital signaling, PRI**, 329
- direct signaling model (H.323)**, 343–344
 - CallManager compliance, 345
- direct transfer feature**, 274
- Directories button (Cisco IP Phone 7960/7940)**, 687
- directories, specifying for MOH audio source file**, 461
- Directory data type (XML)**, 850
- Directory Number Configuration Screen**, 134
 - calling search space, 196
 - Display field, 121
 - Voice Message Box field, 204
- directory numbers**, 568
- directoryNum field (CMR)**, 584
- disabling**
 - CMR generation, 554
 - silence suppression, 396

- disconnect supervision**, 318
- Disengage messages (H.225 RAS), UUIE fields**, 805
- Display field (Directory Number Configuration screen)**, 121
- displaying**
 - alarm definitions, 514
 - component version information, 524
 - counter descriptions, 528
- distributed call processing**, 36
- distributed resource sharing**, 686
- distributing media processing load**, 421
- DLCX (delete connection) command (MGCP)**, 367
- DOD (Direct Outward Dial)**, 686
- DOES-NOT-EXIST operator**, 108
- dotted decimal notation**, 563
- downloading MIBs**, 542
- Drop Any Party feature**, 279
- Drop Last Party feature**, 279
- dropping conference participants**, 278–279
- DS0**, 323
- DS1**, 323
- DSPs (digital signal processors)**, 7
 - resources, transcoding, 426
- DTMF (dual-tone multifrequency) encoding**, 377
- duration field (CDR)**, 569, 575

E

- E&M signaling**, 320
- E911 solutions**, 689
- early dial tone, troubleshooting**, 253
- early media**, 359
- E-carrier system**, 321
- ECSs (empty capability sets)**, 444
- EditDial soft key (Cisco IP Phone)**, 158
- EditDial URI support on Cisco IP Phones**, 858
- EGW (Enterprise Gateway) 2200**, 769
- emergency services**
 - 911 call routing, 93
 - calling search space configuration*, 246
 - partition configuration*, 246
 - route filter configuration*, 246
 - route group configuration*, 245

- route list configuration*, 246
 - route pattern configuration*, 247
 - enhanced 911 support, 243–244
 - MLPP, 102
- empty capability sets**, 364, 446
- emulating PBXs**, 132
- enabling**
 - CDR data generation, 552
 - CMR generation, 554
- enbloc dialing**, 136
- encoding schemes, codecs**, 7
- endpoints**, 10
 - associating with media resources, 411–412
 - call legs, 397
 - H.323, 286
 - handling failure of, 482
 - logical channels, 390, 407–411
 - MRGLs, assigning, order of precedence, 417–418
 - originating, 407
 - selection process, 71–72
 - Tandberg SCCP video endpoints, 765
 - terminating, 407
 - toll restriction, 188
- endpoints (H.323)**, 343–344
- enhanced 911**, 243–244
 - calling search space configuration, 246
 - partition configuration, 246
 - route filter configuration, 246
 - route group configuration, 245
 - route list configuration, 246
 - route pattern configuration, 247
- enterprise deployment of CallManager clusters**, 50
 - combined multiple-site model, 57
 - multiple-site IP WAN model with distributed call processing, 52–54
 - multiple-site model with centralized call processing, 55
 - multiple-site model with independent call processing, 53
 - single-site model, 50–51
- enterprise numbering plans**, 211
- Enterprise Parameters, Cluster Security Mode**, 298
- ESF (Extended Superframe)**, 325
- establishing calls**
 - conference calls, 678
 - in circuit-switched networks, 9–10
 - in Cisco AVVID IP Telephony networks, 33
 - media exchange phase, 10
- Event Viewer**, 535–537
- Events package, Cisco JTAPI support**, 842–843
- examples**
 - of call preservation, 483–485
 - of conference calls
 - ad hoc*, 595–597
 - Meet-Me*, 597–598
 - of GCID usage in call transfer, 567–568
 - of held calls, 598
 - of MOH configuration, 466–467
 - of parked calls, 594
 - of route patterns, 79
 - closest match routing*, 82–84, 87
 - simple call routing*, 80–81
 - wildcards matching multiple digits*, 84–87
 - of shared lines, 265
 - executive support*, 266–267
 - small support groups*, 265
 - of transferred calls, 590–594
- exceeding maximum conference participation**, 439
- Excel spreadsheets, creating CSV files for bulk transactions**, 500–501
- EXISTS operator**, 108
- Expected Digits gateway setting**, 137
- exporting trace results to file**, 518
- extending**
 - conference participation, 431
 - conference resource availability, 439
- extension agents**, 541
 - CCM MIB, updating, 542
 - CDP MIB, 542
- extension mapping, multitenant applications**, 165
- extension mobility**, 690
- external access codes, adding to missed calls (Cisco IP Phones)**, 158–164
- external applications, gaining access to database tables**, 599
- external phone number masks**, 134–135
- External Route Plan Wizard**, 183, 692
 - fallback, 224
 - toll-bypass configuration, 220–221

F

FAC/CMC reports (CAR), 510
FACILITY messages (QSIG), 336
FACs (forced authorization codes), 103–104
failed devices, recovering, 486
failover, 292
failover, handling calls during, 490
fallback, 224, 292
 algorithms, 488–489
 External Route Plan Wizard, 224
 guard timers, 489
 handling calls during, 490
fallback routing, 238–239
fast connect, 359–360, 364
fast start, 359–360, 364
fault tolerance
 central database, 558
 nodes, 559
feature transparency, 332
features
 Answer/Release, 616
 ART, 654
 Auto Answer, 625
 automated change notification, 627
 BAT, 634
 broadcast paging support, 633
 call connection, 637
 call forward reason codes, 644
 call forwarding
 Call Forward Busy, 643
 Call Forward No Answer, 643
 Call Park, 645
 configuring, 645–646
 Call Pickup, 646–647
 call preservation, 648
 call status per line, 649
 call waiting/retrieve, 649
 calling search spaces, 685
 CDRs/CMRs, 638
 centralized system administration, 654
 Cisco IP Phone Configuration Web
 pages, 662
 Cisco IP SoftPhone support, 668
 Cisco Personal Address Book, 669
 Cisco WebAttendant, 658
 CLID, 649–651
 CNID, 652
 context-sensitive help, 682

device pools, 684
 Device wizard, 685
 DHCP IP address assignment, 685
 DID (Direct Inward Dial), 686
 directories, 687
 distinctive rings, 688
 distributed environment, 688
 distributed resource sharing, 686
 DOD (Direct Outward Dial), 686
 downloadable upgrades, 630, 683
 DSP resource alignment, 686
 E911 solutions, 689
 EndCall softkey, 690
 extension mobility, 690
 GSM-EFR/FR, 676
 H.232 supplementary services, 741
 Hold/Resume, 697, 743
 HTTPD server support, 698
 lines, 703
 Meet-Me conferencing, 713
 message waiting indicator, 714
 MOH, 719
 MRGL support, 712
 Mute button, 721
 New Call soft key (Cisco IP Phone 7940/
 7960), 712, 721
 of CAR, 504
 CDR data, loading, 505
 of Meet-Me conferences, 437
 of QSIG, 338–339
 of stations
 AbbrDial, 277–278
 alerting names, 281
 auto answer, 282–283
 barge, 271–272
 barge/cbarge, 270
 calling ID blocking, 268
 cbarge, 272–273
 configurable display of forwarded call
 information, 279–281
 configurable text label per line, 281
 direct transfer, 274
 distinctive ring per line, 267
 dropping conference participants,
 278–279
 iDivert, 275
 join, 274
 MCID, 269–270
 media termination at route points, 283

- privacy*, 270
- ring options*, 268
- service URLs*, 276
- speed dial*, 276
- off-hook dialing, 722
- overlap sending, 722
- paperless phone, 722
- partitions, 685
- performance monitoring, 723
- privacy, 723
- QoS statistics, 734
- redial, 736
- remote site survivability, 712, 737
- settings button, 738–739
- speakerphone, 740
- speed dial, 740
- TAPI/JTAPI redundancy, 742
- Tone on Hold, 743
- transfer, 745–746
- unicast conferences, 751
- zero cost phone moves/adds, 756
- field definitions**
 - call admission control messages, 801–804
 - destCause_location field, 577
 - destCause_value field, 578–580
 - directory numbers, 568
 - duration field, 569
 - H.225 RAS messages, 797
 - of CDRs, 561, 569–575
 - comment field*, 583
 - of CMRs, 584–585
 - OnBehalfOf, 580–581
 - origCause_location field, 577
 - origCause_value field, 578–580
 - registration request messages, 799
 - unregistration messages, 799–800
- file format of NANP, 248–249**
- files, adding to MOH audio sources, 461**
- filtering traces, 521**
- finalCalledPartyNumber field (CDR), 573**
- finalCalledPartyNumberPartition field (CDR), 574**
- Finnish numbering plans, TLAs, 89**
- firmware, upgrading, 630, 683**
- first-party call control, Cisco wave driver, 780**
- fixed data sources for MOH servers, 461**
- forwarded calls, configurable information display, 279–281**

- forwarding calling search spaces, manually configuring, 203**
- forwarding options**
 - for hunt lists, 175
 - for hunt pilots, 174
- ForwardMaximumHopCount service parameter, 640–642**
- frames, 322–324**
 - ESF formatting, 325
 - Superframe formatting, 325
- fully meshed topologies, clustering, 38**
- functionality of MCL, conferencing and transcoding DSP resources, 426–427**
- fundamentals of call routing, 72–75**
 - dialing behavior, 78–79
 - overlapped sending, 90–91
 - route filters, wildcards, 76–77
 - route patterns, 75–78
 - examples*, 84–86
- FXS/FXO interfaces, 317–318**
 - availability on Cisco gateways, 319
 - broadcast paging support, 633

G

- G.711 codecs, 393**
- G.723.1 codecs, 393**
- G.726 codecs, 393**
- G.728 codecs, 393**
- G.729a codecs, 393**
- G.729a voice codecs, 393**
- gaining access to database tables from external applications, 599**
- gatekeeper-routed call model (H.323), 343**
 - redundant routing information, 353
- gatekeepers, 343**
 - ARQ messages, 355
 - call admission, 352–353
 - default technology prefix*, 355
 - locating, 348
 - registering for H.323 sessions, 349–352
 - device pools*, 350
 - technology prefix*, 350
 - zone setting*, 349
- gateway devices, 26, 261**
- gateway endpoints, 180**
- gateway protocols, H.323, 342**
 - call signaling phase, 342

- endpoints, 343–344
- gatekeepers, 343
- H.225 protocol, 356, 360–364
- media control phase, 342
- media exchange phase, 342
- RAS, 346–356
- gateway reports (CAR), 508**
- gateways, 314, 763**
 - assigning to route groups, 180–181
 - backhauling, 315
 - digital, 138–139
 - directory numbers, processing, 603
 - fallback, 224
 - H.323
 - call signaling protocols, 812*
 - initialization, 372*
 - supplementary services, 741*
 - interaction with CallManager, 316
 - MGCP, 366
 - failover, 371–372*
 - MGC, 366*
 - overlapped dialing, 92*
 - registration during active connection, 491*
 - purpose of, 313
 - QSIG, 187
 - registration, 371
 - route lists, 74
- GCID (global call ID), 566–567**
- generation of CDR data**
 - service parameters, 551–552
 - troubleshooting, 604
- geographical routing, 219–221**
 - configuring, 232
 - inbound dialing, 231
 - outbound dialing, 224–230
 - troubleshooting, 221–224
- glare, 320**
- globalCallID_callId field , 566**
 - in CDR data, 570
 - in CMRs, 584
- globalCallID_callManagerId field**
 - in CDR data, 566
 - in CMRs, 584
- globalCallId_ClusterID field**
 - in CDR data, 570
 - in CMRs, 584
- graceful fallback algorithm, 489**
- graceful switchover algorithm, 487**

- GraphicMenu data type (XML), 849–850**
- Gratuitous ARP field (CallManager Administration>Phone Configuration page), 297**
- grep command, comparing to route patterns, 78**
- ground-start signaling, 319**
- GSM codecs, 393**
- GSM-EFR/FR (Groupe Speciale Mobile-Enhanced Full Rate/Full Rate), 676**
- guard timers, 489**
- guidelines for CDR processing, 602**

H

- H.225, 356, 360**
 - call signaling messages, 360–362, 810, 813
 - H.245, 362–364
 - RAS
 - admission messages, UUIE fields, 801–803*
 - bandwidth messages, UUIE fields, 803–804*
 - call admission control messages, 801–804*
 - call signaling messages, UUIE fields, 808–813*
 - disengage messages, UUIE fields, 805*
 - Information Request messages, UUIE fields, 806–807*
 - registration messages, 798*
 - terminal/gateway discovery messages, 797*
 - unregistration messages, 799–800*
- H.245, 362**
 - events, 360
 - fast start, 364
- H.261 video codecs, 394**
- H.263 video codecs, 394**
- H.264 video codecs, 394**
- H.320 video codecs, 395**
- H.323, 64–66, 310, 316, 796**
 - call control models, 343
 - call signaling protocol, 812
 - empty capability sets, 446
 - endpoints, 286, 308
 - gateway initialization, 372
 - H.225 protocol, 356, 360

- call signaling messages, 360–362*
 - H.245, 362–364*
 - load sharing algorithms, 351
 - nonredundant trunks, 350
 - RAS protocol, 346–356
 - bandwidth, changing, 356*
 - call admission, 352–355*
 - device pools, 350*
 - gatekeeper location, 348*
 - gatekeeper registration, 349–352*
 - messaging, 796*
 - technology prefix, 350*
 - redundant trunks, 351
 - supplementary services, 741
 - video codecs, 395
 - voice message box management, 204
 - H.323 protocol model, 342**
 - call signaling phase, 342
 - endpoints, 343–344
 - gatekeepers, 343
 - media control phase, 342
 - media exchange phase, 342
 - handling system failure**
 - Cisco CallManager-to-device communication, 482
 - endpoint failure, 482
 - media processing device failure, 482
 - node failure, 481–482
 - node-to-node communication, 483
 - hardware conference servers, counters, 443**
 - hardware-based conference bridges**
 - codec support, 429
 - registration during active connections, 490
 - Unicast, 400
 - hardware-based media processing resources, 405**
 - hardware-based MTPs, 401**
 - hardware-based videoconference bridges, 400**
 - headsets, auto answer feature, 282**
 - held calls**
 - examples, 598
 - hold feature, 263
 - hold types, 465
 - high order bit, 562**
 - high-bandwidth codecs, 392**
 - history of Cisco CallManager, 11**
 - Multimedia Manager 1.0, 12
 - release 3.0, 14–15, 20
 - release 3.1, 15
 - release 3.2, 16
 - release 3.3, 16
 - release 4.0, 17, 19
 - release 4.1, 19
 - Selsius-CallManager 1.0, 13
 - hold and resume feature, UA accessibility to, 379–380**
 - Hold button, 697, 743**
 - hotlines, configuring, 151–153**
 - HP Insight Agent MIB, 541**
 - HTTPD (HTTP Daemon), 698**
 - hub-and-spoke topologies, CallManager cluster deployment strategies, 55**
 - hunt groups, Attendant Console, 781**
 - hunt lists, 75, 169–170, 172–174**
 - forwarding options, 175
 - hunt pilots, 170, 174–176**
- I**
- i button, context-sensitive help, 682**
 - IBM Director Agents, 541**
 - ICCS (Intracluster Control Signaling), 40**
 - IconMenu data type (XML), 846**
 - identifying**
 - CDR-associated CMRs, 586
 - CDRs
 - abandoned calls, 587–588*
 - calls between endpoints, 586*
 - calls between IP phones, 587*
 - IP Phone malfunction, 588*
 - malicious calls, 589*
 - precedence calls, 589*
 - redirected calls, 589*
 - short calls, 588*
 - transferred calls, 590*
 - video calls, 589*
 - iDivert feature, 275**
 - IECs (interexchange carriers), 4**
 - immediate fallback algorithm, 489**
 - immediate switchover algorithm, 488**
 - inbound calls, configuring translations, 159**
 - inbound dialing, configuring, 231**
 - individualized routing, 72**
 - Information Request messages (H.225 RAS), UUIE fields, 806–807**
 - infrastructure of Cisco IP Communications system, 759–762**

- Cisco ATA, 763
- Cisco DPA gateways, 763
- Cisco IP/VC, 765
- Cisco VG248, 764
- SRST, 766
- Init URI support on Cisco IP Phones, 857**
- initial configuration, MOH, 467**
- initializing**
 - annunciator servers, 476
 - H.323 gateways, 372
 - MOH servers, 463
- Input data type (XML), 851–852**
- Insert Phones/Users screen, 499–500**
- inserting**
 - access codes in redialed numbers, 234
 - transcoders into clusters, rules, 452, 454
- insertion rules for MTPs, 454–455**
- installing**
 - CallManager, Cisco-certified servers, 20–22
 - Terminal Services Client, 537
- integrated solutions**
 - application solutions, 779
 - Cisco CallManager Attendant Console*, 781–782
 - Cisco Emergency Responder*, 782–783
 - Cisco IP Phone Address Book Synchronizer*, 785
 - Cisco IP Phone Services SDK*, 785–786
 - Cisco JTAPI Software*, 780
 - Cisco MeetingPlace*, 786
 - Cisco MeetingPlace Express*, 786
 - Cisco Personal Assistant*, 787
 - Cisco TAPI Software*, 779
 - Cisco Unity*, 787
 - Cisco Unity Express*, 788
 - Cisco WebDialer*, 788–789
 - IPCC*, 783
 - IPMA*, 784
 - infrastructure, 762
 - Cisco ATA*, 763
 - Cisco DPA gateways*, 763
 - Cisco IP/VC*, 765
 - Cisco VG248*, 764
 - SRST*, 766
 - telephony services, 767
 - AXL SOAP API*, 767–768
 - BAT*, 768
 - CallManager Serviceability*, 770
 - CallManager User Options web page*, 771, 773–774
 - CAR*, 769
 - Cisco EGW 2200*, 769
 - Cisco IP Communicator*, 777
 - Cisco VT Advantage*, 778
 - CME*, 770
 - CMI*, 775
 - LDAP support*, 775
 - RTMT*, 776
 - TAPS*, 776
 - third-party vendors, 759
- inter-CallManager replication, 39**
- intercluster trunks, 49, 345**
- interdigit timeouts, 87**
 - eliminating, 117
- interexchange carriers, 4**
- interleaving, 317**
- international calls, blocking, 114**
- international dial plans, 248–249**
 - TLAs, 89
- international fallback, 224**
- INTERNATIONAL-ACCESS DOES-NOT-EXIST route filters, 114**
- interrogation, 338**
- intertenant calls, 166–167**
- intracluster communication, 42**
- investment, 788**
- IP addresses, converting from signed integer values, 563–565**
- IP Centrex, 164**
- IP phone services, configuring with CallManager User Options web page, 773**
- IP Phones, 234, 287, 396**
 - Answer/Release, 616
 - call signaling, 300, 822–829
 - Cisco IP Phone 7905G, 289
 - Cisco IP Phone 7912G, 289
 - Cisco IP Phone 7920G, 288
 - Cisco IP Phone 7940, 289
 - Cisco IP Phone 7940G, 289, 291
 - Cisco IP Phone 7941G, 289, 291
 - Cisco IP Phone 7960, 289, 291
 - Cisco IP Phone 7960G, 289, 291
 - Cisco IP Phone 7961G, 289, 291
 - Cisco IP Phone 7970G, 289, 291
 - Cisco IP Phone 7971G-GE, 289, 291
 - Cisco Wireless IP Phone 7920, 289

- Confrn soft key, 436
- Dial soft key, 157
- EditDial soft key, 158
- failure, troubleshooting, 588
- Missed Calls menu, 157–158
- Received Calls menu, 157–158
- registration, 292, 294–296
- resource allocation, 415–417
- services, 300
 - configuring with CallManager User Options web page, 773*
 - phone-supported XML objects, 301*
- soft keys, 852
- Transit Logic Channel, 396
- unregistration sequence requirements, 490
- XML data types, 845, 852

IP precedence, 59–60

IP telephony, 3. *See also* Cisco AVVID IP Telephony

- packet-switching, 6
- versus traditional telephone networks, 3–4, 7

IPCC (Cisco IP Contact Center), 783

IPMA (Cisco IP Manager Assistant), 784

IPPhoneError XML data type, 854

IPPhoneExecute XML data type, 853

IPPhoneResponse XML data type, 854

IPPhoneStatus XML data type, 853

ISDN (Integrated Services Digital Network), 326

- digital gateways, 138–139

- Q.931 timers, 330–331

ITEM (CiscoWorks Internet Telephony Environment Monitor), 538, 791

ITU-T, H.323 recommendation, 342

J-K

jitter, 551

jitter field (CMR), 585

join feature, 274

JoinOnBehalfOf field (CDR), 572

JTAPI, 285, 304–307

- package support, 830

- for Call Center Capabilities package, 834–835*

- for Call Center Events package, 835–837*

- for Call Center package, 832–834*

- for Call Control Capabilities package, 839–840*

- for Call Control Events package, 841–842*

- for Call Control package, 837–839*

- for Capabilities package, 842*

- for Core package, 830–832*

- for Events package, 842–843*

- for Media Capabilities package, 844*

- for Media Events package, 845*

- for Media package, 843–844*

JVT (Joint Video Team), 394

key systems, 4

Key URI support on Cisco IP Phones, 855–856

L

large conference support, 431

lastRedirectDn field (CDR), 572

lastRedirectDnPartition field (CDR), 572

lastRedirectRedirectOnBehalfOf field (CDR), 572

lastRedirectRedirectReason field (CDR), 572

LATA (Local Access and Transport Area), 219

late dial tone, troubleshooting, 253

latency field (CMR), 585

layers of CallManager functionality, 40–42

LDAP directory support, configuring, 775

LECs (local exchange carriers), 4

length limitations on route filters, 106

limitations

- of barge feature, 271

- on conference participation, 431, 434

- on database record storage, 601

line appearance model, 263

- shared line appearance, remote-in-use, 263

line cards, 8

line groups, 169–172

- hunt options, 173–174

Link Layer, 40

loading CDR data with CAR, 505

load-sharing algorithms for H.323

- intercluster calls, 351**

lobby phones, 217–218

local calls

- 7-digit dialing, 115

- fallback, 224

LOCAL-AREA-CODE tag, 115
locales, 403
locating gatekeepers, 348
locations-based CAC, 63
logging calls less than 1 second, 553
logical channels, 390, 407–411
long distance and international fallback, 225
long distance carriers
 blocking selection of, 114
 IECs, 4
long distance fallback, 224
longest match routing, 82
loop-start signaling, 318
low-bandwidth codecs, 392
LSCs (Locally Significant Certificates),
 updating, 501

M

maintaining CDR/CMR records 554–555
 administrator's responsibility, 600–601
 storage limitations, 601
malfunctioning IP phones, identifying associated CDR, 588
malicious call detail reports (CAR), 510
malicious calls, identifying CDRs, 589
manageability tools
 BAT, 497
 adding users with CSV files, 500–501
 CallManager database, setting up, 499
 goal of using, 498
 managing established CallManager systems, 499
 misconfiguration, 498–499
 phone certificates, updating, 501
 TAPS, 501
 CAR, 502–503, 511
 automatic report generation, 506
 call reports, 507
 CDR data, loading, 505
 conference bridge reports, 508–509
 FAC/CMC reports, 510
 features, 504
 gateway reports, 508
 goal of using, 502–503
 malicious call detail reports, 510
 precedence call summary reports, 510
 QoS reports, 509
 route plan reports, 508
 system overview reports, 509
 traffic summary reports, 507
 user reports, 507
 voice messaging reports, 509
managing conference bridge resources, 427
manual gatekeeper discovery, 348
manually configuring forwarding calling search spaces, 203
mapping public phone numbers to internal numbering scheme, 153–156
masking, 127
 external phone number mask, 134–135
Matching Calling Party Number With Attendant Flag service parameter, 132
MatchingCgpnWithAttendantFlag service parameter, 132
MaxForwardsToDn service parameter, 640
maximum call capacity on shared lines, 265
maximum conference participation, 431
 exceeding, 439
MCID (Malicious Call Identification), 269–270
MCL (Media Control Layer), 389, 407–408
 annunciators, 474–475
 localization, 475
 audio channel processing, 408
 DSP resources, transcoding, 426
 functionality, conferencing and transcoding
 DSP resources, 426–427
 video channel processing, 410–411
MCU (multipoint conference units), 765
MDCX (modify connection) command (MGCP), 367
Media Capabilities package, Cisco JTAPI support, 843–844
media connections between VoIP endpoints, securing, 341–342
media control phase (H.323), 342
Media Events package, Cisco JTAPI support, 845
media exchange phase of H.323 call establishment, 10, 342
media privacy, 299
media processing, 389
 codecs, 391–392
 low-bandwidth, 392
 video codecs, 394
 conference resources, 427

- devices, handling failure of, 482
- distributing processing load, 421
- hardware-based resources, 404
- logical channels, 390
- MCL, 389
 - audio channel processing*, 408
 - video channel processing*, 410–411
- MTPs, 397, 444
 - allocation flowchart*, 450
 - ECSs*, 446
 - performance counters*, 457
 - transcoders*, 450
- redundancy, 486
- resource allocation
 - of built-in bridges, controlling*, 412
 - of MRGs*, 415–416
 - through MRM*, 418
- resources
 - annunciator resources*, 403
 - availability*, 438–439
 - built-in bridge resources*, 404
 - conference bridges, configuring*, 435
 - conference servers, default configuration*, 432
 - conferencing limitations*, 434
 - controlling allocation of*, 411–412
 - default configuration*, 412
 - device registration*, 433–434
 - hardware-based*, 405
 - MOH*, 28, 402
 - MRGs*, 413–414s, 418
 - MTPs*, 27, 400–401
 - Null MRGs*, 414
 - organizing allocation*, 422–425
 - registration*, 406
 - selecting*, 406, 418–421
 - software-based*, 404–406
 - transcoders*, 27, 397
 - types of*, 398, 404
 - Unicast conferencing resources*, 27, 398–399
 - video calls*, 471–473
- media streams, 392–394**
- media termination route points, 283**
- Meet-Me conferences, 436, 713**
 - configuring, 437–438
 - examples, 597–598
 - features, 437
 - service parameters, 438
 - streams, availability, 439
- membership to partitions, 191**
- message waiting APDUs (QSIG), 817**
- message waiting indicator, 205–208, 714**
 - configuring with CallManager User Options
 - web page, 774
- messages**
 - call admission control, 801–804
 - H.225 call signaling, 360–362, 810, 813
 - MGCP, 366–367
 - QSIG, APDUs, 814–818
 - registration request fields, 799
 - Resource Allocation Response, 419–420
 - SIP
 - request messages*, 818–821
 - response messages*, 819–822
 - SNMP traps, 541
 - unregistration fields, 799–800
- messaging systems**
 - CMI, 199–200
 - interaction with calling search spaces, 198–201
- methods (SIP), 375–376**
- metro dialing, 115–116**
- MGCP (Media Gateway Control Protocol), 316, 366**
 - CMRs, 550
 - gateway failover, 371–372
 - gateways, 366
 - registration during active connections*, 491
 - messages, 366–367
 - MGC, 366
 - overlapped dialing, 92
 - Q.931 backhaul, 368–370
- mgcp package-capability srtp-package command, 341**
- MGCs (Media Gateway Controllers), 366**
- MIBs (Management Information Bases), 541–542**
- Microsoft Event Viewer, 535–537**
- Microsoft Performance, 531–532**
- migrating users from another PBX, 238–239**
- misconfiguration of BAT, troubleshooting, 498–499**
- Missed Calls menu (Cisco IP Phones), 157–158**
- mixed-mode conferences, 429–430**

MLPP (Multilevel Priority and Preemption)

emergency calls, 102
precedence, 101

MOH, 458, 719

architecture, 459
Audio Translator, 461
complex configuration, 468
configuring with Cisco CallManager
Administration, 465–467
hold types, 465
initial configuration, 467
Network Stream Source, 468
placing conference participants on hold, 467
play mode configuration, 462–463
resources, 28, 402

servers

audio source, 458, 460
audio sources, adding, 461
capabilities summary, 464
configuring, 458–459
initialization, 463
Multicast configuration, 464–465
performance counters, 469–470,
477–478
service parameters, 462
summary of capabilities, 464

sources, 51, 402
stream connection errors, 463
stream source, selection process, 465
User Hold Stream Source, 468

monitoring. See also monitoring tools

performance counters, 532
MOH servers, 469–470, 477–478
MTPs, 456
transcoders, 456

Unicast conference resources, 440

monitoring tools

CDP, 542
Cisco CallManager Serviceability, 512
alarm configuration, 513
component version information,
displaying, 524
Control Center, 522
QRT, 522
SDI tracing, 515–517
SDL tracing, 517
Service Activation, 522
Trace Analysis, 521–522
trace configuration, 517–520

viewing alarm definitions, 514

CiscoWorks, 538–540
CiscoWorks2000, PathTool, 540
Microsoft Event Viewer, 535–537
Microsoft Performance, 531–532
RTMT, 524

Alert tab, 529–531

View tab, 525–527

SNMP, MIBs, 541–542
TCT, 533–535
Terminal Services Client, 537
VLT, 543–544
VNC Viewer, 538

MRGLs (Media Resource Group Lists),

413, 712

assigning to endpoints, order of precedence,
417–418

MRGs, selecting, 418

organizing resource allocation, 422–425

MRGs (Media Resource Groups)

device control process, 419

Null MRGs, 413

available resources, 414

organizing resource allocation, 422–425

resources, selecting, 418–421

selecting from MRGLs, 418

MRM (Media Resource Manager), 389, 417

media resource allocation, 418

Resource Allocation Response messages,
419–420

MTPs (media termination points), 364, 397,

400, 444–446

allocation flowchart, 450

availability, 452, 454–455

configuring, 455

hardware-based, 401

inserting in clusters, rules, 454–455

inserting into clusters

rules, 452–454

performance counters, 456–457

resources, 27

software-based, 401

transcoders, 450

Multicast MOH, configuring, 464–465**Multimedia Manager 1.0, 12****multiple call appearances, 240–241****multiple digit matches, 84–86****multiple line appearances, 263****multiple tenant applications, 192–196**

- multiple-site IP WAN model with distributed call processing, 52–54
- multiple-site model with centralized call processing, 55
- multiple-site model with independent call processing, 52–53
- multitenant applications, extension mapping, 165–167
- multitenant deployment, 164
- music stream source assignments (MOH), order of precedence, 468
- Mute buttons, 721
- MWI policy, configuring with CallManager User Options web page, 774
- My Fast Dials service, 278

N

- name services APDUs (QSIG), 817
- Network hold, 465
- Network Stream Source (MOH), 468
- Network Time Protocol Daemon (xNTPD), time-matching Cisco CallManager-related devices, 516
- New Call soft key, 712, 721
- NFAS (non-facility associated signaling), 329
- NMSs (network management systems), CiscoWorks, 538–540
- nodeId field (CMR), 584
- nodes, 21
 - active connections, device registration, 490
 - communication, regions, 61–62
 - conference bridge registration, 432
 - device registration, 455
 - failure, 481–482, 559
 - recovery objectives, 479–480
 - role in call preservation, 479
- node-to-node communication failure, handling, 483
- non-North American numbering plans, TLAs, 89
- non-QSIG route lists, 186–188
- nonredundant H.323 trunks, 350
- non-SMDI unified messaging systems, service parameters, 200
- North American numbering plan
 - @ wildcard, 248
 - 10-10 Dialing, 114

- 10-digit dialing, 116–117
- 7-digit dialing, 115–117
- digit discarding instructions, 140
- file format, 248–249
- metro dialing, 115–116
- route filters, 113–114
 - blocking 900 numbers, 118–121
 - blocking international calls, 114
 - blocking long distance carrier selection, 114
 - elimination of interdigit timing, 117
 - metro dialing, 115–116
 - routing only local numbers, 114–115
 - routing toll-free numbers, 117
- tags, 107–108

- NOT-SELECTED operator, 108
- Presentation and Restriction of Calling Line, Calling Name, Connected Line, and Connected Name feature, 381–382
- NTFY (notify) command (MGCP), 367
- Null MRGs, 413–414
- null partition, 191
- Num Digits gateway setting, 137
- numbering plans
 - international, 248
 - overlapped sending, 90–91
 - tags, 107
- numberOctetsReceived field (CMR), 585
- numberPacketsLoss field (CMR), 585
- numberPacketsReceived field (CMR), 585
- numberPacketsSent field (CMR), 584
- numeric data, storing in database, 562
- Nyquist's theorem, 322

O

- objectives for system failure recovery, 479–480
- objects, 532, 541–542
- ODN (original dialed number), 280
- off-hook dialing, 722
- office personnel, blocking 900 numbers, 216
- OffNet calls, processing, 603
- OnBehalfOf field definitions, 580–581
- one shot play mode (MOH), configuring, 463
- OnNet calls, processing, 603
- opening HTTP connections to devices (RTMT), 527

operators, 108–109
 configuring, 151
 stringing together, 109

options for line groups, 172
 hunt options, 173–174

organizing resource allocation, 422–425

origCalledPartyRedirectReason field (CDR), 573

origCallTerminationOnBehalfOf field (CDR), 572

origCause_location field (CDR), 571, 577

origCause_value field (CDR), 571, 578–580

origDeviceName field (CDR), 570

originalCalledPartyNumber field (CDR), 573

originalCalledPartyNumberPartition field (CDR), 573

originating device dialing transformations
 Attendant DN, 137–138
 Expected Digits, 137
 external phone number mask, 134–135
 Num Digits, 137
 prefix digits, 136
 Significant Digits, 138

originating endpoints, 407

origIpAddr field (CDR), 570

origIpPort field (CDR), 570

origLegCallIdentifier field (CDR), 570

origMediaCap_maxFramesPerPacket field (CDR), 571

origMediaCap_payloadCapability field (CDR), 571

origMediaTransportAddress_IP field (CDR), 571

origMediaTransportAddress_port field (CDR), 571

origNodeId field (CDR), 571

origSpan field (CDR), 571

outbound calls, routing, 237–238

outbound dialing, configuring, 224–230

outside dial tone
 configuring, 95–99
 suppressing, 99

overlapped dialing, 136

overlapped receiving, enabling, 133

overlapped sending, 90–92, 722

P

packages, Cisco JTAPI support, 830
 Call Center Capabilities package, 834–835
 Call Center Events package, 835–837
 Call Center package, 832–834
 Call Control Capabilities package, 839–840
 Call Control Events package, 841–842
 Call Controlpackage, 837–839
 Capabilities package, 842
 Core package, 830–832
 Events package, 842–843
 Media Capabilities package, 844
 Media Events package, 845
 Media package, 843–844

packet switching, 6
 codecs, 7
 softswitches, 10–11
 versus circuit switching, 6

packets, 6
 streams, 392–394
 transmission over codecs, configuring, 391, 394

paperless phone, 722

parameters
 for Audio Translator service, 462
 for ISDN Q.931 timers, 330–331
 for MOH servers, 462
 for SIP timers, 382–383

parked calls, examples, 594

participants, adding to conferences, 434–436

participation in conferences, extending/restricting, 431

partitions, 75, 190, 569, 685
 analogies to, 189
 calling search spaces, 191–192
 configuring call appearances, 240–243
 example, 192–196
 membership, 191

party classification, 99

party transform masks, 146

party transformations, 121

path replacement, 213–214

path replacement APDUs (QSIG), 818

pattern matching, 80–81
 . wildcard, 105–106
 @ wildcard, 104–105

- closest match routing, 82–84
 - interdigit timeouts*, 87
 - operators, 108–109
- PBXs (private branch exchanges), 4–5**
 - emulating, 132
- PC Port field (CallManager Administration>Phone Configuration page), 297**
- PC Voice VLAN Access field (CallManager Administration>Phone Configuration page), 297**
- PCM (pulse code modulation), 6**
- peer-to-peer call control model, CallManager compliance, 345**
- peer-to-peer model (H.323), 343**
 - redundant routing information, 353
- performance**
 - CDR processing, 600
 - monitoring, 723
 - Microsoft Performance*, 531–532
- performance counters**
 - descriptions, viewing, 528
 - annunciator-related, 477
 - hardware conference server-related, 443
 - MOH server-related, 469–470, 477–478
 - monitoring from RTMT, 528
 - MTP device-related, 456–457
 - transcoder-related, 456–457
 - Unicast conference resources, 440–442
 - Unicast software conference-related, 442–443
 - video call processing-related, 471–473
- performing bulk operations on CallManager database, 497–498**
- Personal Assistant, 787**
- PGW 2200 Softswitch, 769**
- phases of VoIP sessions, 340**
- phone certificates, updating, 501**
- phone locale, configuring with CallManager User Options web page, 774**
- phone options, configuring via Cisco CallManager User Options web page, 773, 775**
- pink noise, 395**
- PINX (Private Integrated Network Exchange), 332**
- Pkid field (CDR), 575**
- Placed Calls menu (Cisco IP Phones), inserting access codes in redialed numbers, 234**
- placing conference participants on hold, 467**
- PLAR (private line automatic ringdown), 136**
 - configuring, 151–153
- play mode, MOH configuration, 462–463**
- Play URI support on Cisco IP Phones, 858**
- plug-ins**
 - CAR, 502
 - Cisco Dialed Number Analyzer, 789
- plus sign, wildcards, 77**
- policies, QoS, 57**
 - H.323 gatekeeper, 64, 66
 - IP precedence, 59–60
 - locations, 63–64
 - regions, 61–62
- POTS**
 - circuit-switching, 4
 - call establishment*, 9–10
 - endpoints*, 10
 - Class 5 switches, 4
 - IECs, 4
 - PBXs, 4–5
 - PCM, 6
 - versus IP telephony, 3
- precedence calls**
 - CAR summary reports, 510
 - CDRs, identifying, 589
- precedence levels for call legs, 582**
- prefix digits, 136, 140–141**
- pregeneration of CAR reports, 506**
- prepending access codes to missed calls (Cisco IP Phones), 158–164**
- Presentation and Restriction of Calling Line, Calling Name, Connected Line, and Connected Name feature, 381–382**
- presentation settings, 127–129**
- PRI (Primary Rate Interface), 326**
 - availability on Cisco gateways, 329–330
 - ISDN Q.931 timers, 330–331
 - QSIG, 329
- primary CallManager, 486**
- priority values, assigning to calls, 101–102**
- privacy, 340, 723**
 - media privacy, 299
- privacy feature, 270**

processing

- CDRs, impact on system performance, 600
- gateway directory numbers, 603

processing load, distributing over media

- resource servers, 421

Protocol Layer (signaling), 40, 314, 427**proxy servers (SIP), 374****PSAPs (Public Safety Answering Points), 243****PSTNs (public switched telephone network)**

- analog interfaces, 317
- dialing plans, address translation, 72
- digital interfaces, 317
- fallback routing, configuring, 65

Publisher databases, 37**pulse code modulation, 6****purging CallManager database, 511****Q****Q.931 backhaul, 368–370****Q.931 signaling, 327****Q.931 Translator. See TripleCombo tool****QBE (Quick Buffer Encoding), 305****QoS (quality of service), 57**

- admissions control, 57–58
 - H.323 gatekeeper, 64–66*
- CAR reports, 503, 509
- DiffServ model, 60
- IP precedence, 59–60
- locations, 63–64
- regions, 61–62
- traffic classification, 57
- traffic prioritization, 57

QPM (CiscoWorks QoS Policy Manager), 791**QRT (Quality Reporting Tool), 522****QSIG, 313, 329, 332**

- APDUs, 336, 814
 - delivery models, 337*
 - for call completion, 814*
 - for call diversion, 815*
 - for call transfer, 816–817*
 - for message waiting, 817*
 - for name services, 817*
 - for path replacement, 818*
- calling search spaces, 210
 - call forward by rerouting, 211–213*
 - path replacement, 213–214*
- CallManager support of, 338–339

- connection establishment, 336

- FACILITY message, 336

- feature-to-feature communication, 335–337

- redirected call handling, 337–338

- route lists, 186, 188

- tunneling, 338

- vendor-specific features, 334–335

QueryStringParam URI support on Cisco IP**Phones, 856****question mark (?) wildcards, 77****R****range notation, 77****RAS (Registration, Admission, and Status)****protocol, 346–356, 796**

- bandwidth, changing, 356

- CAC messages, 801–804

- call admission, 352–355

- gatekeeper location, 348

- gatekeeper registration, 349–352

- device pools, 350*

- technology prefix, 350*

- zone setting, 349*

- registration messages, 798–799

- terminal/gateway discovery messages, 797

- unregistration messages, 799–800

- UUIE Fields, 796–797

RDN (redirected dialed number), 280**reason codes, call forwarding, 644****Received Calls menu (Cisco IP Phones),****157–158****records**

- call leg IDs, 568

CDRs

- abandoned calls, identifying, 587–588*

- accessing from central database, 599–601*

- associated CMR, identifying, 586*

- calls between endpoints,*

- identifying, 586*

- calls between IP phones,*

- identifying, 587*

- field definitions, 569–575*

- IP phone malfunctions,*

- identifying, 588*

- maintaining, 600–601*

- malicious calls, identifying, 589*

- precedence calls, identifying, 589*
- processing, 602*
- processing, impact on system performance, 600*
- redirected calls, identifying, 589*
- short calls, identifying, 588*
- storage limitations, 601*
- transferred calls, identifying, 590*
- video calls, identifying, 589*
- CMRs**
 - associated CDRs, identifying, 586*
 - field definitions, 584–585*
 - maintaining, 600–601*
 - storage limitations, 601*
- fields**
 - call leg identifiers, 568*
 - data type conversions, 563–565*
 - directory numbers, 569*
 - duration, 569*
 - GCIDs, 566*
 - partitions, 569*
- recovering failed devices, 486**
- recovery objectives after system failure, 479–480**
- Redial button, 736**
- redialed numbers, adding access codes, 234**
- redirect reason codes, 581–582**
- redirect servers, 374**
- redirected calls**
 - CDRs, identifying, 589*
 - handling on circuit-switched networks, 337–338*
- Redirector servlet, 788**
- redundancy**
 - CDR data storage, 555–557*
 - clustering, fully meshed topologies, 38*
 - in Cisco AVVID IP Telephony architecture, 43*
 - comparing with traditional telephone systems, 36–37*
 - TAPI/JTAPI, 742*
- redundant call processing, 486**
- redundant H.323 trunks, 351**
- regions, 61–62**
- registering**
 - Cisco IP Phones, 292, 294–296*
 - conference bridge servers, 427*
 - conference bridges, 432*
 - during active connections, 490–491*
 - gatekeepers for H.323 sessions, 349–352*
 - device pools, 350*
 - technology prefix, 350*
 - zone setting, 349*
 - gateways with CallManager, 371*
 - media processing resources, 406*
- registrars, 374**
- registration process, 455**
 - switchover, 486*
 - graceful switchover algorithm, 487*
 - immediate switchover algorithm, 488*
- registration message details, 798–799**
- registration request messages, fields, 799**
- releases, 11**
 - Multimedia Manager 1.0, 12*
 - Cisco CallManager release 3.0, 14–15, 20*
 - Cisco CallManager release 3.1, 15*
 - Cisco CallManager release 3.2, 16*
 - Cisco CallManager release 3.3, 16*
 - Cisco CallManager release 4.0, 17–19*
 - Cisco CallManager release 4.1, 19*
 - Selsius-CallManager 1.0, 13*
- reliability of Cisco AVVID IP Telephony, 36**
- remote site survivability, 712, 737**
- remote-in-use, 263**
- reports**
 - accessing from Serviceability Reports Archive, 523–524*
 - CAR**
 - call reports, 507*
 - conference bridge reports, 508–509*
 - FAC/CMC reports, 510*
 - gateway reports, 508*
 - malicious call detail reports, 510*
 - precedence call summary reports, 510*
 - pregeneration, 506*
 - QoS monthly summary reports, 503*
 - QoS reports, 509*
 - route plan reports, 508*
 - system overview reports, 509*
 - traffic summary reports, 507*
 - voice messaging reports, 509*
- request messages (SIP), 768, 818**
 - header fields, 820–821*
- required data for CDR processing, 602**
- resource allocation. *See also* resources**
 - MRM, 389*
 - of built-in bridges, controlling, 412*
 - on IP phones, 415–417*

Resource Allocation Response messages, 419–420**resources**

- conference resources, 427
- conference bridge resources
 - allocating, 429
 - availability, 428
 - configuring, 435
 - device control process, 428
 - hardware-based, 429
- DSP, transcoding, 426
- media processing, 398, 404
 - allocation, 415–416, 418
 - annunciator resources, 403
 - assigning to MRGs, 423–425
 - availability, 438–439
 - availability of conference servers, 432
 - built-in bridge resources, 404
 - conference servers, default configuration, 432
 - conferencing limitations, 434
 - controlling allocation of, 411–412
 - default configuration, 412
 - device registration, 433–434
 - distributing processing load, 421
 - hardware-based, 405
 - MOH, 402
 - MRGs, 413–414
 - MTPs, 400–401
 - Null MRGs, 414
 - organizing allocation, 422–425
 - selecting from MRGs, 418–419, 421
 - selecting MRGs from MRGLs, 418
 - software-based, 405–406
 - transcoders, 397
 - Unicast conferencing resources, 398–399
 - Unicast, monitoring, 440–442

response messages (SIP), 819–820

- header fields, 822

Resume softkey, 697, 743**retry counts, 382–383****ring settings**

- changing, 268
- configuring with CallManager User Options web page, 774

route filters, 74–75, 106, 110–113

- 7-digit dialing, 117
- creating, 227

- for North American numbering plan, 113–114

- 10-digit dialing, 116–117*
- blocking 900 numbers, 118–121*
- blocking long distance carrier selection, 114*
- blocking international calls, 114*
- elimination of interdigit timing, 117*
- metro dialing, 115–116*
- routing only local numbers, 114–115*
- routing toll-free numbers, 117*

INTERNATIONAL-ACCESS DOES-NOT-EXIST, 114

- length limitations, 106

LOCAL-AREA CODE tag, 115

- toll-free numbers, 117
- wildcards, 76–77

route groups

- 911 routing configuration, 245
- assigning gateways to, 180–181
- assigning to route lists, 181–183
- behavior, 177, 179

route lists

- 911 routing configuration, 245
- behavior, 177–179
- QSIG, 186–188
- route groups, assigning to, 181–183

Route Pattern Configuration screen (CallManager Administration), 73

- Urgent Priority check box, 93

route patterns, 74–76

- ! wildcard, 86
- . wildcard, 105–106
- @ wildcard, 104–105
- assigning, 227
- called party transformations, 184–186
- calling party transformations, 184–186
- closest matching patterns,
 - troubleshooting, 254
- constraining, 113
- destinations, selecting, 78–80
- examples, 79
 - closest match routing, 82–84, 87*
 - simple call routing, 80–81*
 - wildcards matching multiple digits, 84–87*
- filtering, 110–113
- hunt pilots, 174–176
- operators, 108–109

- overlapped sending, 92
- partitions, 190
- tags, 107–108
- urgent calls, 93
- versus translation patterns, 148–149
- wildcards, 76–77

route plan reports (CAR), 508**route-based calling, 184–186****routing**

- by class of calling user, case study, 214–218
- by geographic location, case study, 220–232
- organization, 188
- by security, 188

routing calls over a specific gateway, 237**routing loops, troubleshooting, 255****routing outbound calls, 237–238****routing-related service parameters, 130****RQNT (notification request) command (MGCP), 367****RSIP (restart in progress) command (MGCP), 367, 373–375****RTMT (Real-Time Monitoring Tool), 524, 776**

- Alert tab, 529, 531
- counters, 528
- opening HTTP connections to devices, 527
- View tab, 525–527

RTP Streaming Control URIs, support on Cisco IP Phones, 856**S****salt, 299****sample U.K. dialing plan, 94–95****sampling, 322****saving traces to file, 518****scalability, 34–36****SCCP (Skinny Client Control Protocol), 285**

- call signaling between Cisco IP Phones, 822–829
- messages, SDL message queues, 293
- station devices, 286

schedule-time fallback algorithm, 489**screening indicator field, specifying value of, 131****SDI tracing, 515–517****SDL (Signal Distribution Layer), 14**
message queues, 293**SDL (Specification and Description Language), 12****SDL tracing, 517****securing VoIP traffic**

- authentication, 339
- authorization, 340
- privacy, 340

security, 296

- configuration file security, 298–299
- configuring, 297–298
- device identity security, 298
- media privacy, 299
- of media connections between VoIP endpoints, 341–342
- of signaling connections from Cisco gateways to CallManager, 340
- salt, 299

Sedgley, Brian, 767**selecting**

- calls, 265
- CDR storage location, 559–560
- CDR storage method, 556
- media processing resources, 406
- MOH server as audio source file destination, 461
- MRGs from MRGLs, 418
- resources from MRGs, 418–421
- route pattern destinations, 78–80
- stored CDR data format, 559–560

Selsius-CallManager 1.0, 13**serialization rates for T1, 324****servers**

- annunciator, initialization, 476
- Cisco-certified for CallManager installation, 20, 22
- clustering, 11
- conference bridge servers, registration with CallManager, 427
- conference servers
 - availability, 432*
 - default configuration, 432*
- deployment within clusters, 44–45
 - 10,000+ users, 49*
 - 1-1 redundancy group, 46*
 - 2-1 redundancy group, 46*
 - 2500 or less users, 47*
 - 30,000+ users, 49*
 - 5000 to 10,000 users, 48*

- media resource, distributing processing load, 421
- MOH, 402
 - audio source*, 458, 460
 - Audio Translator*, 461
 - capabilities summary*, 464
 - complex configurations*, 468
 - configuring*, 458–459
 - configuring with Cisco CallManager Administration*, 465–467
 - hold types*, 465
 - initial configuration*, 467
 - initialization*, 463
 - multicast configuration*, 464–465
 - performance counters*, 469–470, 477–478
 - placing conference participants on hold*, 467
 - service parameters*, 462
 - stream connection errors*, 463
 - stream source selection process*, 465
- time-matching, 516
- trace configuration, 517
- Unicast conference, 398
- service parameters**
 - Call Forwarding-related, 615, 623–625, 633, 639, 679, 720
 - Call Park, 646–648
 - CallDiagnosticsEnabled, 554
 - CDR data-related, 551–552
 - CdrLogCallsWithZeroDurationFlag, 553–554
 - Cisco WebAttendant, 660
 - CLID-related, 651
 - conferencing-related, 438
 - controlling silence suppression, 396
 - dialing transformation-related, 130
 - Calling Party Number*
 - ScreeningIndicator*, 131
 - Matching Calling Party Number With Attendant Flag*, 132
 - MatchingCgpn With Attendant Flag*, 132
 - Numbering Plan Info*, 133–134
 - Overlap Receiving For Pri*, 133
 - Strip # From Called Party Number*, 133
 - Unknown Caller ID*, 133
 - MOH server-related, 462
 - StatisticsEnable, 529
 - Tone on Hold, 743
- service URLs, 276**
 - configuring with CallManager User Options web page, 773
- services**
 - adding, 300
 - phone-supported XML objects, 301
- sessions**
 - establishing, 9
 - H.245, events, 360
 - VoIP, 340
- setting up CallManager database with BAT, 499**
- Settings Access field (CallManager Administration>Phone Configuration page), 298**
- settings button (Cisco IP Phones 7910/7940/7960), 738–739**
- SGCP (Skinny Gateway Control Protocol), 316**
- shared line appearances, 263**
- shared lines**
 - barging into calls, 271
 - examples, 265
 - customer product groups*, 265
 - executive support*, 266–267
 - maximum call capacity, 265
- short calls, associated CDR, identifying, 588**
- sign bit, 562**
- signaling**
 - call legs, 397
 - CAS, availability on Cisco gateways, 326
 - Cisco gateways, securing connections to CallManager, 340
 - ground-start, 319
 - H.245, 360
 - intracluster communication, 42
 - loop-start, 318
- signaling layers**
 - Aggregator, 314
 - Call Control Layer, 314, 387–389
 - MCL, 407–408
 - media processing*, 410–411
 - transcoding DSP resources*, 426
 - Media Control Layer, 314, 387–389
 - Protocol, 314

signaling protocols, 795

H.323, 796

signed integer values, converting to IP addresses, 563–565**silence suppression, 395**

disabling, 396

simple call routing, 80–81**single-site model, 50–51****SIP (Session Initiation Protocol), 316,****372–373**

call flow, 374

methods, 375–376

MTP, 378

proxy servers, 374

redirect servers, 374

registrars, 374

request messages, 818

header fields, 820–821

response messages, 819–820

header fields, 822

timers, 382–383

UA-initiated features, 379–380

*call forwarding, 380**caller ID, 381–382**connected ID, 381–382**hold and resume, 380***Skinnny Protocol, voice message box management, 204****SMDI (Simple Message Desk Interface), 199****SNMP (Simple Network Management Protocol)**

MIBs, downloading, 541–542

traps, 541

softkeys

CFwdAll, 639–640

Cisco IP Phones, 852

Confrn, 436

End Call, 690

New Call, 712, 721

Resume, 697, 743

VidMode, 752

softswitches, 10–11**software, application solutions, 779**

Cisco CallManager Attendant Console, 781–782

Cisco Emergency Responder, 782–783

Cisco IP Phone Address Book

Synchronizer, 785

Cisco IP Phone Services SDK, 785–786

Cisco JTAPI Software, 780

Cisco MeetingPlace, 786

Cisco MeetingPlace Express, 786

Cisco Personal Assistant, 787

Cisco TAPI Software, 779

Cisco Unity, 787

Cisco Unity Express, 788

Cisco WebDialer, 788–789

IPCC, 783

IPMA, 784

software-based conference bridges

large conference support, 431

Unicast conference bridges, 399, 435

software-based media processing resources, 405–406**software-based MTPs, 401****source 51, 402****speakerphone feature, 740**

auto answer feature, 282

on Cisco IP Phone 7935, 25

special characters, # (pound sign), 88–89**specifications, H.323, 310****specifying**

directory path for MOH audio

source file, 461

value of screening indicator field, 131

speed dial, 276, 740. See also AbbrDial feature

Redial button, 736

spreadsheets, creating CSV files for bulk transactions, 500–501**SRST (Survivable Remote Site Telephony), 766****SRTP (secure Real-Time Transport Protocol), 296****stages of call routing, 124–126****state machines, 42**

intracluster communication, 42

states, 847**station devices, 25–26, 261, 313**

and users, 262

call control, 284

CallManager support, 284

CallManger support, 284

Cisco CallManager support, 262

Cisco IP Communicator, 292

Cisco IP Phones, 287

*Cisco IP Conference Station 7936, 291**Cisco IP Phone 7905G, 289**Cisco IP Phone 7912G, 289**Cisco IP Phone 7914 Expansion**Module, 291**Cisco IP Phone 7920G, 288*

- Cisco IP Phone 7940G*, 289, 291
- Cisco IP Phone 7941G*, 289, 291
- Cisco IP Phone 7960G*, 289, 291
- Cisco IP Phone 7961G*, 289, 291
- Cisco IP Phone 7970G*, 289, 291
- Cisco IP Phone 7971G-GE*, 289, 291
- Cisco IP Phone 7985G*, 291
- Cisco Wireless IP Phone 7920*, 289
- common line sharing, 264
- features
 - AbbrDial*, 277–278
 - alerting names, 281
 - auto answer, 282–283
 - barge, 271–272
 - barge/cbarge, 270
 - calling ID blocking, 268
 - cbarge, 272–273
 - configurable display of forwarded call information, 279–281
 - configurable text label per line, 281
 - direct transfer, 274
 - distinctive ring per line, 267
 - dropping conference participants, 278–279
 - iDivert*, 275
 - join, 274
 - MCID*, 269–270
 - media termination at route points, 283
 - privacy, 270
 - ring options, 268
 - service URLs, 276
 - speed dial, 276
- H.323 endpoints, 286, 308–310
- line appearance model, 263
- SCCP, 286
- shared line appearances, 263
- TFTP functionality, 295
- station-based conference bridges, 399**
- StatisticsEnable service parameter, 529**
- stored calls (Cisco IP Phones), prepending access codes, 157–164**
- storing records**
 - CDR data, 554–555
 - data types*, 562–564
 - central database*, 555–557
 - selecting method of*, 556
 - system limitations, 601
- streaming**
 - conferencing-related, 439
 - logical channels, 390, 407–411
 - MOH audio source
 - audio source IDs*, 459
 - connection errors*, 463
 - continuous play mode*, 462
 - fixed data sources*, 461
 - one shot play mode*, 463
 - order of precedence*, 468
 - MTPs, 397, 400–401
 - transcoders, 397
 - voice data streams, 392–394
 - codecs, bandwidth consumption*, 393
- streaming failure disconnect supervision, 492**
- subscriber databases, 38**
- summary of MOH server capabilities, 464**
- Superframe formatting, 325**
- Supplementary Services Layer, 42, 427**
- supported client devices, 28–29**
- supported devices, 126**
- supported international dial plans, 249**
- supported QSIG features (on CallManager), 338–339**
- suppressing outside dial tone, 99**
- switchback, 486**
- switchover, 486**
 - graceful switchover algorithm, 487
 - immediate switchover algorithm, 488
- symmetric encryption, CBC, 299**
- system administrator**
 - controlling media resources, 411–412
 - MRGs*, 415–416
 - MRM*, 418
 - maintaining CDR/CMR records, 600–601
- system failures**
 - call preservation, 478–479
 - Cisco CallManager-to-device
 - communication, handling, 482
 - endpoints, handling, 482
 - failed devices, recovering, 486
 - media processing devices, handling, 482
 - node failure, handling, 481–482
 - recovery objectives, 479–480
- system overview reports (CAR), 509**
- system tools**
 - Cisco CallManager Trace Collection Tool, 789
 - Cisco Dialed Number Analyzer, 789

- Cisco IP IVR, 790
- Cisco IP QM, 790
- CSA, 790–791
- for Cisco IP Communications system, 761
- ITEM, 791
- QPM, 791

T

- T.120 video codecs, 395**
- T1 serialization rates, 324**
- tags, 107–108**
 - AREA-CODE, 115
 - INTERNATIONAL ACCESS, 114
 - LOCAL-AREA-CODE, 115
- Tandberg SCCP video endpoints, 765**
- TAPI (telephony application programming interface), 304–306**
 - redundancy, 742
 - CTI, 285
- TAPS (Tool for Auto-Registered Phone Support), 501, 743, 776**
- T-carrier classifications, 321–323**
- TCP (Transmission Control Protocol), CallManager communication, 40**
- TCT (Trace Collection Tool), 533–535**
- TDM (Time-Division Multiplexing), 321–324**
- technology prefix, 349**
- telephony services, 767**
 - AXL SOAP API, 767–768
 - BAT, 768
 - CallManager Serviceability, 770
 - CallManager User Options web page, 771–774
 - CAR, 769
 - Cisco EGW 2200, 769
 - Cisco IP Communicator, 777
 - Cisco VT Advantage, 778
 - CME, 770
 - CMI, 775
 - LDAP support, 775
 - of Cisco IP Communications system, 760
 - RTMT, 776
 - TAPS, 776
- terminal endpoints, 261**
- Terminal Services Client, 537**
- terminal/gateway discovery messages, H.225 RAS, 797**

- terminating endpoints, 407**
- TFTP functionality for station devices, 295**
- third-party vendors for integrated solutions, 759**
- time-matching Cisco CallManager devices, 516**
- time-of-day routing, configuring, 208–210**
- timers, SIP, 382–383**
- TLAs (Telealues), 89**
- TLS (Transport Layer Security), 296**
- toll bypass, 72, 225**
 - calling/called party transformations, applying, 229
 - calling search spaces, configuring, 230–231
 - configuring, 219–233
 - External Route Plan Wizard, 220
 - inbound dialing, 231
 - outbound dialing, 224
 - route groups, creating, 224–227
 - route filters, creating, 227–228
 - translation patterns, defining, 231–232
- toll bypass fallback, 225**
- toll fraud, call classification, 99**
- toll restriction, 72, 188**
- toll-free numbers, 117**
- Tone on Hold, 467, 743**
- tools, 499. *See also* manageability tools; monitoring tools; system tools**
 - BAT, 497
 - managing established CallManager systems, 499*
 - misconfiguration, 498*
 - phone certificates, updating, 501*
 - phones, adding with CSV files, 501*
 - TAPS, 501*
 - CallManager Serviceability, 512
 - alarm configuration, 513*
 - component version information, displaying, 524*
 - Control Center, 522*
 - QRT, 522*
 - SDI tracing, 515–517*
 - SDL tracing, 517*
 - Service Activation, 522*
 - Trace Analysis, 521–522*
 - trace configuration, 517–518*
 - viewing alarm definitions, 514*

- CAR, 502
 - alerts, 511*
 - call reports, 507*
 - conference bridge reports, 508–509*
 - FAC/CMC reports, 510*
 - features, 504–505*
 - gateway reports, 508*
 - goal of using, 502–503*
 - malicious call detail reports, 510*
 - precedence call summary reports, 510*
 - QoS reports, 509*
 - route plan reports, 508*
 - system overview reports, 509*
 - traffic summary reports, 507*
 - user reports, 507*
 - voice messaging reports, 509*
- CiscoWorks, 538–539
 - syslog analysis tools, 539–540*
- Microsoft Event Viewer, 535, 537
- RTMT, 524
 - Alert tab, 529, 531*
 - View tab, 525, 527*
- TCT, 533–535
- Terminal Services Client, 537
- VLT, 543–544
- VNC Viewer, 538
- topologies, CallManager deployment strategies**
 - combined multiple-site model, 57
 - multiple-site IP WAN model with distributed call processing, 52–54
 - multiple-site model with centralized call processing, 55
 - multiple-site model with independent call processing, 52–53
 - single-site model, 50–51
- tracing**
 - collecting traces, 533–535
 - customization, 517
 - effect on performance, 522
 - filtering traces, 521
 - time-matching on Cisco CallManager devices, 516
- traditional telephone networks**
 - circuit-switching, 4
 - call establishment, 9–10*
 - endpoints, 10*
 - Class 5 switches, 4
 - comparing to IP telephony, 3–4, 7
 - IECs, 4
 - key systems, 4
 - packet-switching, codecs, 7
 - PBXs, 4–5
 - PCM, 6
 - redundancy, 36–37
- traffic classification methods, 57**
 - DiffServ model, 60
- traffic prioritization, 57**
- traffic summary reports (CAR), 507**
- transcoders, 27, 397**
 - as alternative to codecs, 450
 - availability of, 452–455
 - configuring, 455
 - DSP resources, 426
 - inserting in clusters, rules, 454–455
 - limitations on resources, 426–427
 - logical connection between IP Phones, 408–411
 - mixed-mode conferences, transcoding, 429
 - MOH audio sources, transcoding, 461
 - MTPs, 444
 - allocation flowchart, 450*
 - ECSSs, 446*
 - performance counters, 456–457
 - registration during active connection, 490
 - video conferences, resource allocation, 431
- Transfer button (Cisco IP Phone 12SP+), 745**
- transferred calls**
 - CDRs, identifying, 590
 - example, 590–594
- transformations, 121–124**
 - called party transformations, 122
 - masking, 127
 - on terminating device, 142–146
 - presentation settings, 127–129
 - service parameters, 132–134
 - Calling Party Number Screening Indicator, 131*
 - Matching Calling Party Number With Attendant Flag, 132*
 - Numbering Plan Info, 133*
 - Overlap Receiving For PRI, 133*
 - Strip # From Called Party Number, 133*
 - Unknown Caller ID, 133*

Transit Logic Channel, 396
TRANSIT-NETWORK-ESCAPE tag, 114
Translation Pattern Configuration screen, 75
translation patterns, 74, 146–148
 calling search space, 148
 dialing alias, configuring, 150
 hotlines, 151–153
 mapping public phone numbers to internal numbering scheme, 153–156
 mapping public phone numbers to private numbering scheme, 153–156
 versus dialing transformations, 121
 versus route patterns, 148–149

translations
 on inbound calls, configuring, 159
 on calls from CallManager to PSTN, configuring, 160

traps, 541
TripleCombo tool, 771
troubleshooting. *See also* tracing
 call delays, 253
 call routing loops, 255
 CDR data generation and storage, 604
 Cisco IP Phone failure, 588
 closest matching patterns, 254
 digit discarding instructions, 254
 geographical routing, 221–224
 outside dial tone, 98
early/late application of, 253

trunk cards, 8
trunks, 8
 BRI, 326, 329–331
 CAS, 324
availability on Cisco gateways, 326
 intercluster, 345
 PRI, 326, 330–331

type of service field (802.1Q packets), packet classification, 59–60

U

U.K. dialing plan, 94
UAs (user agents), 374
 accessible features
call forwarding, 380
caller ID, 381–382
connected ID, 381–382
hold and resume, 379–380

UDP (User Datagram Protocol), CallManager communication, 40
umbrella specifications, H.323, 342
 call signaling phase, 342
 endpoints, 343–344
 gatekeepers, 343
 H.225, 356, 360–364
 media control phase, 342
 media exchange phase, 342
 RAS protocol, 346–356

Unicast conference bridges, 389
 hardware-based, 400
 software-based, 399

Unicast conferencing, 751
 counters, 440–442
 devices, 27

unified messaging systems
 CMI, 199–200
 delivering voicemail to correct mailbox number, 205
 interaction with calling search spaces, 198–201
 methods of integration, mixing, 202
 non-SMDI, service parameters, 200
 voice mail profiles, 202–203

Unity, 787
Unity Express, 788
Universal Call Model, 769
UNIX, comparing grep command to route patterns, 78
UnknownCallerId service parameter, 650
UnknownCallerIdFlag service parameter, 650
UnknownCallerIdText service parameter, 650
unregistration message fields, 799–800
unregistration process
 fallback
algorithms, 488–489
guard timers, 489
 IP Phones, requirements for, 490
 switchback, 486

updating
 CCM MIB extension agent, 542
 CDP MIB extension agent, 542
 established CallManager systems, 499
 phone certificates, 501

upgrading firmware, 630, 683
uptime-delay fallback algorithm, 489
urgent route patterns, 93

URI support on Cisco IP Phones, 855

- Dial URI, 857
- EditDial URI, 858
- Init URI, 857
- Key URI, 855–856
- Play URI, 858
- QueryStringParam URI, 856
- RTP Streaming Control URIs, 856

**Use External Phone Number Mask
check box, 142****User hold, 465****User Hold Stream Source (MOH), 468****user reports (CAR), 507****user restrictions, configuring, 215–218****utilities. *See* tools****UUIE (user-user information element) fields,
360, 796–797, 808**

- of H.225 Call Signaling messages, 808–813
- of H.225 RAS Admission messages,
801–803
- of H.225 RAS Bandwidth messages,
803–804
- of H.225 RAS Disengage messages, 805
- of H.225 RAS Information Request
messages, 806–807
- registration details, 798–799

V**VAD (voice activity detect), 395****variable-length numbering plans, 89**

- overlapped sending, 90–91
- urgent route patterns, 94

video call processing, 471

- CDRs, identifying, 589
- performance monitoring, 471–473

video channel processing, 410–411**video codecs, 393–394****video conference bridges,**

- hardware-based, 400

video data streams, 394**video resolution values, 582****video telephony, Cisco VT Advantage, 302****videoconferencing**

- Cisco MeetingPlace, 786
- connections comparing with voice-
conference connections, 411
- resource allocation, 431

viewing

- alarm definitions (Cisco CallManager
Serviceability), 514
- descriptions of counters, 528

virtual endpoint determination, 71**VLT (Voice Log Translator), 543–544****VNC (Virtual Computer Networking)****Viewer, 538****voice codecs, 391, 394**

- bandwidth consumption, 393
- encoding, 7

voice data streams, 392, 394**voice mail**

- message waiting indicator, 205–208
- profiles, 202–203
- SDMI, 199

**Voice Message Box field (Directory Number
Configuration screen), 204****voice messaging reports (CAR), 509****voice streams, transcoding, 397****voicemail, delivering to correct mailbox
number, 205****voice-messaging systems, non-SMDI, 200****VoIP (Voice over IP), 6**

- call establishment, 32–34
- endpoints, securing media connections,
341–342
- logical channels, 390
- security
 - authentication, 339*
 - authorization, 340*
 - privacy, 340*
- sessions, 340

W**web pages, Cisco CallManager User Options****web page, 771–775****WebAttendant. *See* Attendant Console****WebDialer servlet, 788****white noise, 395****wideband codecs, 393****wildcards, 76–77**

- !, 77, 82
- ., 105–106
- @, 76, 104–105
- ?, 77
- +, 77

- multiple digit matches, 84–86
- range notation, 77
- set notation, 77
- X wildcard, 77

Windows 2000

- Microsoft Performance, 531–532
- services for Cisco IP Telephony, 23–24

wizards, 685

- External Route Plan Wizard, 692

X-Z**X wildcard, 77****XFER button (Cisco IP Phone 30VIP), 745****XML (Extensible Markup Language)**

- objects, 301
- services, Cisco IP Phone Services SDK, 785–786
- support on Cisco IP Phones, 845, 852
 - CiscoIPPhoneDirectory data type, 850*
 - CiscoIPPhoneError data type, 854*
 - CiscoIPPhoneExecute data type, 853*
 - CiscoIPPhoneGraphicFileMenu data type, 850*
 - CiscoIPPhoneGraphicMenu data type, 849*
 - CiscoIPPhoneImage data type, 847–848*
 - CiscoIPPhoneImageFile data type, 848–849*
 - CiscoIPPhoneInput data type, 851–852*
 - CiscoIPPhoneMenu data type, 845*
 - CiscoIPPhoneResponse data type, 854*
 - CiscoIPPhoneStatus data type, 853*
 - CiscoIPPhoneText data type, 846*
 - IconMenu data type, 846*

XML-formatted traces, 518**xNTPD (Network Time Protocol Daemon),
time-matching CallManager-related
devices, 516****zero duration calls, CDRs, 588****zip tones, 282**