

# INDEX

## A

- AAL5 over MPLS operation, 459–460
  - configuration, 462–463
  - flowchart configuration, 461
  - PE router, 461
  - provider router, 461
  - verification, 463–465
- AAL5 to VLAN Interworking, 515–517
- AC (Attachment Circuit), 452, 529
- address families, VPN routing, 86–90
- address-family ipv4 vrf command, 217
- addshelf command, 71
- adjacencies, 11
- administrative weights, constraint-based SPF, 389
- advertisement messages (LDP), 13
- aggregate labels, 17
- any to any interworking, AToM, 499
  - AAL5 to VLAN interworking, 515–517
  - bridged interworking mode, 499–500
  - Ethernet to VLAN interworking, 502–505
  - Frame Relay
    - AAL5 Interworking, 506–509
    - PPP Interworking, 509–512
    - VLAN Interworking, 512–514
  - L2 VPN Interworking, 501–502
  - routed interworking, 500–501
- Any Transport over MPLS. See AToM
- architectures
  - blocks, 6
  - CSC, 372
  - VPNs, 83–84
- ASBR routers (Autonomous System Boundary Routers), 272
- assignment of MPLS labels for data forwarding, 13
- ATM LSR
  - basic configuration, 50–51
  - cell-mode MPLS configuration, 59–61
  - flowchart, 48
- ATMs
  - cell-mode MPLS, 22–24, 46–47, 459
    - AAL5 over MPLS operation, 459–465
    - ATM cell relay over MPLS, 465–468
    - ATM LSR flowchart, 48
    - basic configuration steps, 49–51
    - control plane operation, 54–56
    - data forwarding operation, 56
    - device configuration, 57–58
    - Edge ATM LSR flowchart, 47
    - LSC (label switch controller), 66–76
    - OAM, 468–469
    - VC merge, 58–61
    - verification, 51–53
    - VP tunnels, 62–66
      - without VC merge, 61–62
  - cell-mode MPLS over VP tunnels, 62
    - ATM PVP configuration flowchart, 63
    - configuration steps, 63–64
    - device configuration, 65–66
    - Edge ATM LSR configuration flowchart, 63
      - verification steps, 64–65
  - cell relay over MPLS, 465–468
  - configuring switches, RFC 2684 routed PVCs, 43–44
  - modes, L2TPv3, 421–422
  - TE implementation, 376
  - VC-merge, 29–31
- AToM (Any Transport over MPLS), 449
  - any to any interworking, 499
    - AAL5 to VLAN, 515–517
    - bridged interworking mode, 499–500
    - Ethernet to VLAN, 502–505
    - Frame Relay to AAL5, 506–512
    - Frame Relay to VLAN, 512–514
    - L2 VPN, 501–502
    - routed interworking, 500–501
  - commands, 526–527
  - Layer 2 VPNs, 449–450
    - operation, 453–458
    - Pseudo Wire Reference Model, 450–452
    - terminology, 452–453
    - VPLS, 450
    - VPWS, 450
  - like to like circuits, 459
    - ATM over MPLS, 459–469
    - Ethernet over MPLS, 469–488
    - Frame Relay over MPLS, 496–499
    - HDLC mode, 492–495
    - PPP mode, 488–492

- local switching, 517
  - ATM to ATM, 522–524
  - Ethernet to Ethernet, 521–522
  - Ethernet to Frame Relay, 524–526
  - flowchart of configuration, 518
  - frame relay to frame relay, 519–521
- QoS implementation, 599–602
- Attachment Circuit (AC), 452, 529
- auto configuration, VPLS, 530
- auto-discovery, VPLS, 530
- automatic route filters, VPNs, 105–106
- Autonomous System Boundary Router (ASBR routers), 272
- autonomous-system command, 186
- available bandwidth (MPLS TE) versus maximum bandwidth, 386–387

## B

- backdoor links
  - EIGRP PE-CE routing protocol, SoO attribute, 201–202
  - OSPF PE-CE routing, 168–171
    - configuration, 172–180
    - flowchart of configuration, 171
- back-to-back VRF method, inter-provider VPN distribution, 273–274
  - configuration, 276–287
  - control plane forwarding, 274
  - data forwarding, 275
- backup tunnels, FRR operation, 409
- bandwidth command, 582
- BGP
  - communities, partitioning route-reflectors, 242–243
    - PE routers, 243–247
    - provider routers, 243–244
    - verification, 247
  - cost community, EIGRP PE-CE routing protocol, 199–200
  - CSC label exchange, 347
  - MPLS VPN superbackbone, 144–145
  - SoO (site of origin), 670
- BGP PE-CE routing, 213–215
  - commands, 269
  - Hub and Spoke environment

- same AS numbers, 266–268
    - unique AS numbers, 260–266
  - implementation flowchart, 216
  - route-reflectors, 225
    - confederations, 253–260
    - deployment methods, 225–231
    - partitioned, 236–247
    - peer groups, 248–253
    - RR configuration, 232–236
  - unique and same AS numbers, 217–218
    - CE routers, 218–219
    - configuration, 219–222
    - verification, 222–224
- BGP PE-PE routing, VPN configuration, 99–102
  - MP-iBGP neighbor verification, 103
  - PE1-AS1 and PE2-AS1 router, 102–103
- bgp rr-group command, 237
- both keyword, 98
- bottom-of-stack indicator, 9
- BPX+LSC
  - cell-mode MPLS verification, 73–76
  - configuring as ATM LSR, 67–68
    - BPX configuration, 69–71
    - Edge ATM LSR configuration, 73
    - LSC configuration, 72
- bridged interworking mode, AToM, 499–500

## C

- carrier supporting carrier. See CSC
- case studies
  - BGP SoO, 670
  - CBTS (class-based tunnel selection), 649
    - configuration, 651–653
    - implementation, 649
    - verification, 652
  - commands, 671–673
  - Dynamic Layer 3 VPNs, 642–644
    - configuration, 647
    - L3 VPN over mGRE tunnels, 644
    - verification, 647
  - Hub and Spoke with EIGRP Topology, 659–661
  - Hub and Spoke with OSPF Topology, 654–656
    - router configuration, 656–657
    - verification, 656–658

- inter-provider VPNs
  - multi-homed inter-AS provider network, 335–343
  - route-reflector and BGP confederation implementation, 328–335
- Layer 2 VPNs over Inter-AS topologies, 633–634
  - configuration, 636
  - pseudo-wire switching, 634–635
  - verification, 634
- Layer 3 VPNs over Layer 2 VPN topology, 637
  - configuration, 637–642
  - pseudo-wire redundancy, 640
  - verification, 640–641
- multicast VPNs, 609–610
  - configuration, 611
  - implementation, 613
  - operation, 610–611
  - verification, 615
- multi-VRF CE, 616–617
  - based on source IP address, 620–623
  - configuration, 619–620, 630–632
  - device configuration, 617–618
  - HSRP integration, 624–625
  - multicast support, 627–628
  - NAT integration, 625–626
  - verification, 629
- VPLS implementation with GSR 12000 series, 662
  - operation, 663–664
  - packet forwarding, 664–667
  - requirements, 667–669
- CBR (Constraint Based Routing), 379, 385–386
- CBTS (class-based tunnel selection), case study, 649
  - configuration, 651
  - final configuration, 653
  - implementation, 649
  - verification, 652
- CE routers (customer edge routers), 84
  - back-to-back VRF method, 277–278
  - BGP PE-CE routing
    - RR configuration, 233
    - unique and same AS numbers, 218–219
  - EIGRP PE-CE routing protocol, basic configuration, 191–195
  - OSPF PE-CE routing protocol, sham links, 176–180
  - RIPv2 PE-CE routing configuration, 124–125
  - static PE-CE routing, 115
  - VPLS
    - configuration, 565
    - Direct Attachment Architecture, 545–546, 555
    - H-VPLS, 565
    - VPNs, 84, 95
- CEF (Cisco Express Forwarding), 11, 35
- cell interleaving with VC-merge, implementation, 30–31
- cell-mode MPLS, 22–24
  - ATM VC-merge, 29–31
  - control VCs, 23
  - data plane forwarding operation, 25
  - enabling, 24–25
  - loop detection, 26–27
- cell-mode MPLS over ATM, 46–47
  - ATM LSR flowchart, 48
  - basic configuration steps
    - ATM LSR, 50–51
    - Edge ATM LSR, 49–50
  - control plane operation, 54–56
  - data forwarding operation, 56
  - device configuration, 57–58
  - Edge ATM LSR flowchart, 47
  - LSC (label switch controller), 66–67
    - BPX+LSC as ATM LSR, 67–73
    - verification with BPX+LSC, 73–76
- VC merge, 58
  - ATM LSR configuration, 59
  - ATM LSR verification steps, 61
  - configuration flowchart, 59
  - device configuration, 60
  - Edge ATM LSR configuration steps, 59
  - verification, 51–53
- VP tunnels, 62
  - ATM PVP configuration flowchart, 63
  - configuration steps, 63–64
  - device configuration, 65–66
  - Edge ATM LSR configuration flowchart, 63
  - verification steps, 64–65
  - without VC merge, 61–62
- Cisco website, 59
- class-based tunnel selection (CBTS), case study, 649
  - configuration, 651

- final configuration, 653
- implementation, 649
- verification, 652
- classification, QoS (quality of service), 570
  - DSCP, 570–573
  - IP precedence, 570–571
  - MPLS EXP bits, 573
  - ToS relationships, 570
- cnfqbin command, 71
- cnfrsrc command, 70
- commands, 35, 671–673
  - AToM, 526–527
  - basic configuration, 76–77
  - BGP PE-CE routing, 269
  - CSC, 373
  - EIGRP PE-CE routing protocol, 211
  - inter-provider VPNs, 343
  - L2TPv3, 446–447
  - mpls label protocol, 13
  - MPLS TE, 416–417
  - OSPF PE-CE routing protocol, 180
  - QoS, 605–607
  - RIP PE-CE routing, 138–139
  - static PE-CE routing, 120
  - VPLS configuration, 566–567
  - VPN configurations, 107–109
- confederations, BGP PE-CE routing, 253–254
  - implementation flowchart, 254
  - PE routers, 256–259
  - verification, 259–260
- configurations
  - AAL5 over MPLS operation, 462–463
  - BGP PE-CE routing
    - Hub and Spoke environment, 261–263
    - unique and same AS numbers, 219–222
  - CBTS (class-based tunnel selection), 651–653
  - cell-mode MPLS over ATM, 46–47
    - ATM LSR flowchart, 48
    - basic steps, 49–51
    - control plane operation, 54–56
    - data forwarding operation, 56
    - devices, 57–58
    - Edge ATM LSR flowchart, 47
    - LSC (label switch controller), 66–76
    - VC merge, 58–61
    - verification, 51–53
    - VP tunnels, 62–66
    - without VC merge, 61–62
  - CSC network deployment
    - carrier not running MPLS, 351–357
    - carrier providing MPLS VPN service, 367–370
    - carrier running MPLS, 360–363
  - dynamic Layer 3 VPNs, 647
  - EIGRP PE-CE routing protocol
    - networks using BGP cost community and SoO attribute, 205–209
    - no BGP cost community or SoO attribute, 203–204
    - SoO attribute, 202
    - verification of BGP cost community and SoO attribute, 209–211
    - with BGP cost community or SoO attribute, 204
  - frame mode MPLS, 35–36, 41–46
  - inter-provider VPNs
    - distribution, back-to-back VRF method, 276–287
    - non-VPN transit provider, 318–327
  - L2TPv3, 424–426, 437
  - Layer 2 VPNs over Inter-AS, 636
  - Layer 3 VPNs over Layer 2 VPN, 637–639, 642
  - MPLS TE, 393
    - dynamic and explicit paths, 397–400, 404–408
    - flowchart, 393–396
    - FRR (Fast ReRoute), 409–410
    - implementation of MPLS VPN over TE tunnels, 411–416
    - unequal cost load balancing, 408–409
    - verification of tunnel creation, 400–404
  - multicast VPNs, 611
  - multi-hop MP-eBGP method, 302
    - ASBRs, 304–305
    - flowchart, 302–304
    - verification, 305–307
  - multi-VRF CE, 619–620, 630–632
  - next-hop-self method, 291
    - ASBRs configuration, 291–293
    - verification, 293–294
  - OSPF PE-CE routing, 154
    - differing customer process ID, 155–166
    - differing process ID, 166–168
    - protocol, sham links, 172–180

- PPP over MPLS, 490
- redistribute connected method, 297–298
  - control plane forwarding, 299
  - routers, 298–299
  - verification, 299
- RIPv1 PE-CE routing, 135–136
- RIPv2 PE-CE routing, 122–124
  - CE routers, 124–125
  - PE routers, 125–128
- static PE-CE routing, 113–114
- VPNs, 95
  - BGP PE-PE routing, 99–103
  - CE routers, 95
  - forwarding on PE routers, 96–98
  - label verification, 104–105
  - PE1-AS1 router, 98–99
  - provider routers, 103–104
  - VRF verification on PE routers, 99
- congestion
  - avoidance, QoS queuing, 574
  - management, QoS queuing, 573
- Conservative Label Retention Mode, 16
- Constraint Based Routing, 379
- constraint-based SPF, MPLS TE operation, 388–390
- control planes, 6
  - AToM, 456–457
  - cell-mode MPLS configuration, 54–56
  - CSC network deployment
    - carrier not running MPLS, 350
    - carrier providing MPLS VPN service, 366–367
    - carrier running MPLS, 359–360
  - forwarding, inter-provider VPN distribution, 274
  - frame mode MPLS, 38–39
  - inter-provider VPN distribution, 308, 316
  - RIPv2 PE-CE routing, 129–132
  - transporting VPNv4
    - multi-hop MP-eBGP method, 301
    - next-hop-self method, 289
    - redistribute connected method, 295
    - redistributed connected method, 299
  - VPN routing, 91–93
- control VCs, 23
- control words, AToM operation, 457–458
- count to infinity, EIGRP PE-CE routing protocol, 197–198

- CSC (carrier supporting carrier), 345
  - architecture benefits, 372
  - basics, 345–347
  - commands, 373
  - deployment, 348
    - carrier not running MPLS, 348–358
    - carrier providing MPLS VPN service, 365–371
    - carrier running MPLS, 359–365
  - customer edge routers, 84
  - customer networks, VPNS, 80–83
  - customer sites, VPNS, 79–82

## D

- data forwarding
  - cell-mode MPLS configuration, 56
  - CSC network deployment
    - carrier not running MPLS, 350
    - carrier providing MPLS VPN service, 367
    - carrier running MPLS, 360
  - inter-provider VPN distribution, 275, 316
  - next-hop-self method, 289
  - redistribute connected method, 295
  - RIPv2 PE-CE routing, 132–133
- Data MDTs, 610
- data planes, 6, 11
  - AToM, 457
  - forwarding, frame mode MPLS, 39
  - LFIB, 11
  - operation in cell-mode MPLS, 25
  - PPP over MPLS, 492
  - transporting VPNv4, multi-hop MP-eBGP method, 301
  - VPN routing, 93–94
- dedicated PE peer-to-peer models, VPNS, 82
- dedicated routers, route-reflector deployment, 229–230
- Default MDTs, 610
- Demultiplexer Field, 453
- deployment
  - CSC, 348
    - carrier not running MPLS, 348–358
    - carrier providing MPLS VPN service, 365–371
    - carrier running MPLS, 359–365

- route-reflectors
  - dedicated routers, 229–230
  - partitioning, 230–231
  - PE routers, 225–227
  - provider routers, 227–228
- devices
  - cell-mode MPLS configuration, 57–58
    - over VP tunnels, 65–66
    - VC merge, 60
  - configuring RFC 2684 routed PVCs, 45–46
  - frame mode MPLS, 40–41
  - L2TPv3
    - dynamic tunnels, 435
    - static tunnel, 430
  - multi-VRF CE, 617–618
  - PPP over MPLS configuration, 490
  - static PE-CE routing
    - CE routers, 115
    - PE routers, 116–118
    - provider routers, 115–116
- Direct Attachment Architecture, VPLS, 535
  - dot1q tunnel mode and Layer 2 tunneling, 546–555
  - flowchart of configuration, 537–538
  - port and 802.1Q VLAN mode, 538–546
- disabling TTL propagation, 20
- discovery messages (LDP), 13, 35
- distributed keywords, 35
- domain-id command, 145
- dot1q Tunnel Mode, Ethernet over MPLS, 484–488
- downstream, 8, 15
- drop probability, DSCP, 570
- dspcds command, 69
- dsprsrc command, 70
- dsprks command, 69–71
- Dynamic Layer 3 VPNs, case study, 642–644, 647
- dynamic paths, configuring with MPLS TE, 397–400, 404–408
- dynamic tunnels, L2TPv3 configuration, 431–432
  - devices, 435
  - operation verification, 432–435

## E

---

- Edge ATM LSR
  - basic configuration, 49–50

- cell-mode MPLS
  - configuration, 59
  - over ATM, 73
- flowchart, 47
- EIGRP, hub and spoke topology, 659–661
- EIGRP PE-CE routing protocol, 180–181
  - BGP cost community feature, 199–200
  - command summary, 211
  - configuration
    - networks using BGP cost community and SoO attribute, 205–209
    - no BGP cost community or SoO attribute, 203–204
    - verification of BGP cost community and SoO attribute, 209–211
    - with BGP cost community or SoO attribute, 204
  - flowchart of configuration, 184–195
  - route propagation
    - AS same on PE routers, 182–183
    - differing AS on PE routers, 183–184
  - routing loops, 195
    - count to infinity, 197–198
    - multi-homed sites, 195–196
    - re-injecting multi-homed sites, 197
  - SoO attribute, 200
    - backdoor link, 201–202
    - configuration, 202
    - multi-homed sites, 201
    - suboptimal routing, 198
- E-LSRs (Edge-Label Switch Routers), 7
- Emulated VC, 452
- Emulated VC Encapsulation, 453
- enabling cell-mode MPLS, 24–25
- Ethernet
  - L2TPv3, 421
  - over MPLS, 469
    - dot1q Tunnel Mode, 484–488
    - port mode, 469–472
    - switch-based, 476–484
    - VLAN mode, 472–475
    - VLAN rewrite, 476
    - to VLAN interworking, 502–505
  - explicit paths, configuring with MPLS TE, 397–400, 404–408
  - EXPLICIT\_ROUTE object, 384
  - explicit-null labels, 17

Export Route Targets, VPN routing, 88  
 extended port command, 72  
 Extranet VPNs, 90

## F

Fast ReRoute, 409  
 FEC (forwarding equivalence path), 6  
 filters, partitioning route-reflectors, 237  
 flowchart (configuration flowchart), MPLS TE,  
 393–396  
 frame mode MPLS  
   configuration, 35–36  
   control plane, 38–39  
   data plane forwarding, 39  
   devices, 40–41  
   RFC 2684 routed PVCs, 41–43  
     configuration steps, 43  
     core ATM switches, 43–44  
     device configuration, 45–46  
     verification steps, 44–45  
   verification, 36–38  
 frame relay, L2TPv3, 421  
 Frame Relay over MPLS, AToM, 496–499  
 Frame Relay to AAL5 Interworking, 506–509  
 Frame Relay to PPP Interworking, 509–512  
 Frame Relay to VLAN Interworking, 512–514  
 frame-mode MPLS, 18–22  
 FRR (Fast ReRoute), 409–410

## H

HDLC mode, AToM, 492–495  
 headend routers (MPLS TE), 376, 380  
 hierarchical VPLS. See H-VPLS  
 HSRP support for MPLS VPN, 617  
 Hub and Spoke environments  
   BGP PE-CE routing  
     same AS numbers, 266–268  
     unique AS numbers, 260–266  
   EIGRP Topology, case study, 659–661  
   OSPF Topology, case study, 654–656  
     router configuration, 656–657  
     verification, 656–658

H-VPLS (hierarchical VPLS), 555–557  
   CE routers, 565  
   flowchart of configuration, 557  
   PE routers, 561–563  
   Q-in-Q mode, 558–559  
   service verification, 559–561  
   user PE routers, 563–565

## I

iBGP (Internal BGP), 87  
 IGP  
   CSC label exchange, 346  
   metric, constraint-based SPF, 389  
   routing protocol configuration, 35  
 implementation, QoS, 575–576  
 implicit-null labels, 17  
 Import Route targets, VPN routing, 88  
 inbound filters, partitioning route-reflectors,  
 237–239  
   BGP communities, 242–247  
   verification, 241–242  
 interfaces, LC-ATM, 23  
 Internal BGP (iBGP), 87  
 inter-provider VPNs  
   basics, 271–273  
   case studies  
     multi-homed inter-AS provider network,  
     335–343  
     route-reflector and BGP confederation  
     implementation, 328–335  
   commands, 343  
   distribution options  
     back-to-back VRF method, 273–287  
     MP-eBGP for VPNv4 method, 287–307  
     multi-hop MP-eBGP between , route-  
     reflectors method, 307–309  
     non-VPN transit provider, 315–327  
 Intranet VPNs, 90  
 IP, TE implementation, 375  
 ip multicast-routing vrf command, 611  
 ip route-cache cef command, 35  
 IP to Label TTL propagation, 20  
 IPv4, enabling MPLS, 36  
 IS-IS extensions, MPLS TE operation, 391–393

## J–L

- L2 VPN Interworking, 501–502
- L2TP Class, 426
- L2TPv2 (Layer 2 tunneling protocol version 2), 419
- L2TPv3 (Layer 2 tunneling protocol version 3)
  - basics, 419
    - header format, 424
    - modes of operation, 421–422
    - prerequisites, 422
    - server card on GSR 12000 series router, 422–424
    - services, 419–421
  - commands, 446–447
  - configuration, 424–426
  - dynamic tunnel configuration, 431–432
    - devices, 435
    - operation verification, 432–435
  - L3VPN implementation, 436–437
    - configuration, 437
    - PE router configuration, 442–446
    - verification, 440–441
  - QoS implementation, 604
  - static tunnel configuration, 426–429
    - devices, 430
    - operation verification, 429–430
- L3VPNs (layer 3 VPNs), 436
  - L2TPv3, 436–437
    - configuration, 437
    - PE router configuration, 442–446
    - verification, 440–441
  - over Layer 2 VPN topology, 637
    - configuration, 637–639, 642
    - pseudo-wire redundancy, 640
    - verification, 640–641
- label switch controller. See LSC
- Label VCs (LVCs), 66
- labels, 8–9
  - aggregate, 17
  - allocation process, 385
  - assignment, 13
  - bottom-of-stack indicator, 9
  - CSC, 346–347
  - distribution
    - downstream-on-demand, 15
    - penultimate hop popping, 17
    - unsolicited downstream, 15
  - explicit-null, 17
  - implicit-null, 17
  - imposition, 9
  - stack, 9
  - untagged, 17
  - VPN configuration, verification, 104–105
- Layer 2 tunneling protocol version 3. See L2TPv3
- Layer 2 VPNs
  - AToM, 449–450
    - any to any interworking, 499–517
    - commands, 526–527
    - like to like circuits, 459–499
    - local switching, 517–526
    - operation, 453–458
    - Pseudo Wire Reference Model, 450–452
    - terminology, 452–453
    - VPLS, 450
    - VPWS, 450
  - over Inter-AS topologies, 633–634
    - configuration, 636
    - pseudo-wire switching, 634–635
    - verification, 634
  - QoS, 599
    - AToM, 599–602
    - L2TPv3, 604
    - VPLS, 602–603
- Layer 3 VPNs,
  - L2TPv3, 436–437
    - configuration, 437
    - PE router configuration, 442–446
    - verification, 440–441
  - over Layer 2 VPN topology, 637
    - configuration, 637–639, 642
    - pseudo-wire redundancy, 640
    - verification, 640–641
- layer2vpn pseudowire switching, 633
- L-bit (RSVP path message), 384
- LC-ATM interfaces, 23
- LDP
  - label mapping, 454–456
  - message format, 27
  - router ID assignment, 35
  - session establishment, 13
- LFIB (Label Forwarding Information Base), 11
- LIB (Label Information Base), 11
- Liberal Label Retention Mode, 16

- like to like circuits, AToM, 459
    - ATM over MPLS, 459–469
    - Ethernet over MPLS, 469–488
    - Frame Relay over MPLS, 496–499
    - HDLC mode, 492–495
    - PPP mode, 488–492
  - link protection, FRR MPLS TE configuration, 409–410
  - LLC/SNAP encapsulation, 41
  - load balancing, unequal cost load balancing, 408–409
  - local switching, AToM, 517
    - ATM to ATM, 522–524
    - Ethernet to Ethernet, 521–522
    - Ethernet to Frame Relay, 524–526
    - flowchart of configuration, 518
    - frame relay to frame relay, 519–521
  - long pipe mode, QoS tunnel mode, 579–580
  - loops
    - detection, 26–27
    - prevention, with frame-mode MPLS, 20–22
  - LSC (label switch controller), 22, 66
    - cell-mode MPLS implementation, 66–67
      - BPX+LSC as ATM LSR, 67–73
      - verification with BPX+LSC, 73–76
  - LSPs (Label Switched Paths), 4, 7
  - LSRs (label switch routers), 6, 15
  - LVCs (Label VCs), 66
- ## M
- 
- MAC Addressing Learning, VPLS, 531, 533
  - MAC Addressing Withdrawal, VPLS, 533–534
  - marking, QoS (quality of service), 570
    - DSCP, 570–573
    - IP precedence, 570–571
    - MPLS EXP bits, 573
    - ToS relationships, 570
  - maximum bandwidth (MPLS TE) versus available bandwidth, 386–387
  - messages
    - implementation of RSVP for TE, 380
      - RSVP Error messages, 381–382
      - RSVP PATH message, 380, 383
      - RSVP RESERVATION messages, 381, 385
      - RSVP Tear messages, 382
    - LDP, 13, 27
    - modular QoS CLI (MQC), 581–584
    - MP-BGP (Multiprotocol BGP), 86–90
    - MP-eBGP (Multiprotocol eBGP), 272
      - inter-provider VPN distribution method, 287–288
        - multi-hop MP-eBGP between ASBRs, 301–307
        - next-hop-self method, 288–294
        - redistribute connected method, 294–299
    - MP-iBGP neighbors, verification, 103
    - MPLS, VPN superbackbone, 144–145
    - mpls atm control-vc command, 51
    - mpls atm vpi command, 73
    - mpls atm vp-tunnel vpi vc-range command, 63
    - MPLS EXP bits, QoS (quality of service), 573
    - mpls label protocol command, 13, 35
    - mpls ldp atm vc-merge command, 60
    - mpls ldp router-id command, 36
    - MPLS TE (MPLS Traffic Engineering), 375
      - commands, 416–417
      - configuration, 393
        - dynamic and explicit paths, 397–400, 404–408
        - flowchart, 393–396
        - FRR (Fast ReRoute), 409–410
        - implementation of MPLS VPN over TE tunnels, 411–416
        - unequal cost load balancing, 408–409
        - verification of tunnel creation, 400–404
      - theory, 377
        - CBR (Constraint Based Routing), 385–386
        - constraint-based SPF, 388–390
        - implementation of RSVP, 380–382
        - IS-IS extensions, 391–393
        - maximum versus available bandwidth, 386–387
        - OSPF extension, 390–391
        - overview, 377–380
        - RSVP operation, 382–385
    - mpls traffic-eng backup-path tunnel tunnel100 command, 410
    - MQC (modular QoS CLI), 581–584
    - multicast VPNs, 609–610
      - configuration, 611
      - implementation, 613
      - operation, 610–611
      - verification, 615

- multi-homed inter-AS provider networks, case studies, 335–343
- multi-homed sites, EIGRP PE-CE routing protocol
  - routing loops, 195–197
  - SoO attribute, 201
- multi-hop MP-eBGP method
  - inter-provider VPN distribution method, 307–309
  - transporting VPNv4, 301
    - configuring, 302–307
    - control plane forwarding, 301
    - data plane forwarding, 301
- Multiprotocol BGP (MP-BGP), 86–90
- Multiprotocol eBGP. See MP-eBGP
- multiprotocol label switching traffic, engineering, 375
- multi-VRF CE, 616–617
  - based on source IP address, 620–623
  - configuration, 619–620, 630–632
  - device configuration, 617–618
  - HSRP integration, 624–625
  - multicast support, 627–628
  - NAT integration, 625–626
  - verification, 629

## N

---

- NAT Integration with MPLS VPNs feature, 617
- neighbor as-override command, 266
- neighbor ip-address activate command, 101
- neighbor ip-address send-community both command, 101
- neighbor ip-address send-community extended command, 101
- network command, 114, 185
- network PE (n-PE), 555–556
- networks, VPNs, 80
- next-hop-self method, transporting VPNv4, 288–289
  - configuration, 291–294
  - control plane forwarding, 289
  - data forwarding, 289
  - flowchart for configuration, 290
- next-hop-self neighbor command, 101
- no auto-summary command, 185
- no ip vrf forwarding command, 98

- non-VPN transit provider, inter-provider VPN distribution method, 315–316
  - configuration, 318–327
  - control plane forwarding, 316
  - data forwarding, 316
  - flowchart of configuration, 318
- notification messages (LDP), 13
- n-PE (network PE), 555–556

## O

---

- OAM (Operations, Administration, and Maintenance), 468–469
- objects, RSVP operation in MPLS TE, 382–383
- Opaque LSAs, MPLS TE operation, 390–391
- Open Shortest Path First PE-CE routing protocol, 141
- Operations, Administration, and Maintenance (OAM), 468–469
- Organizational Unique Identifier (OUI), 540
- OSPF extension, MPLS TE operation, 390–391
- OSPF PE-CE routing protocol (Open Shortest Path First PE-CE routing protocol), 141–142
  - command summary, 180
  - configuration, 154
    - differing customer process ID, 155–166
    - differing process ID, 166–168
  - MPLS VPN superbackbone, 144–145
  - route propagation
    - domain ID different on PE routers, 148–149
    - domain ID same on PE routers, 147–148
    - impact of domain ID configuration, 149–150
  - routing loops, 150–151
    - down bit, 151–152
    - route tag, 152–154
  - sham links, 168–171
    - configuration, 172–180
    - flowchart of configuration, 171
  - traditional model, 142–143
- OUI (Organizational Unique Identifier), 540
- outbound filters, partitioning route-reflectors, 237
- outbound route files, VPNs, 105–106
- outgoing labels, 17
- overlay models, VPNs, 80

## P

- Packet Switched Network (PSN), 452, 530
- partitioned route-reflectors, 230–231, 236–247
- path vector TLVs, cell-mode MPLS loop detection, 27
- PDU (Protocol Data Units), 453
- PE routers (provider edge routers), 84
  - AAL5 over MPLS operation, 461
  - back-to-back VRF method, 278–285
  - BGP PE-CE routing
    - confederations, 256–259
    - partitioning route-reflectors, 243–247
    - RR configuration, 232–233
  - EIGRP PE-CE routing protocol, 182–184, 187–190
  - L2TPv3, L3VPN configuration, 442–446
  - OSPF PE-CE routing protocol, 157–162, 173–180
  - RIPv2 PE-CE routing configuration, 125–128
  - route-reflector deployment, 225–227
  - static PE-CE routing, 116–118
  - VPLS
    - Direct Attachment Architecture, 543–545, 551–555
    - H-VPLS, 561–565
  - VPN configuration, 84, 95
    - BGP PE-PE routing, 99–103
    - forwarding, 96–98
    - VRF verification, 99
  - VRFs (virtual routing and forwarding tables), 85–86
- PE to P tunnels, verification of MPLS TE over TE, 415–416
- PE to PE tunnels, verification of MPLS TE over TE, 414–415
- PE1-AS1 routers
  - BGP PE-PE routing, 102–103
  - VPN configuration, 98–99
- PE2-ASi routers, BGP PE-PE routing, 102–103
- PE-CE routing protocol
  - commands, 138–139
  - EIGRP PE-CE, 180–181
    - BGP cost community feature, 199–200
    - command summary, 211
    - configuration, 203–211
    - flowchart of configuration, 184–195
    - route propagation, 182–184
    - routing loops, 195–198
    - SoO attribute, 200–202
    - suboptimal routing, 198
  - OSPF (Open Shortest Path First), 141–142
    - command summary, 180
    - configuration, 154–168
    - MPLS VPN superbackbone, 144–145
    - route propagation, 147–150
    - routing loops, 150–154
    - sham links, 168–180
    - traditional model, 142–143
  - RIPv1, 133
    - configuration, 135–136
    - verification, 136–138
  - RIPv2, 121
    - configuration, 122–128
    - control plane forwarding operation, 129–132
    - data forwarding operation, 132–133
    - implementation flowchart, 122
    - verification, 128–129
  - static, 111–112
    - command reference, 120
    - configuration, 113–114
    - devices, 115–118
    - implementation flowchart, 112–113
    - verification, 118–120
- peer groups, route-reflectors, 248–249
  - provider routers, 249–251
  - verification, 251–253
- peer-to-peer models, VPNs, 81
- penultimate hop popping, 17–18
- per-VRF default MDTs, 610
- physical interfaces, 421
- pipe mode, QoS tunnel mode, 578
- police command, 582
- port mode, Ethernet over MPLS, 469–472
- PPP mode, AToM, 488–489
  - configuration, 490
  - data plane, 492
  - device configuration, 490
  - flowchart configuration, 489
  - verification, 490–492
- priority command, 582
- Protocol Data Units (PDUs), 453
- provider edge routers. *See* PE routers

provider networks, VPNs, 80, 84

provider routers, 80, 84

- AAL5 over MPLS operation, 461
- back-to-back VRF method, 278–285
- BGP PE-CE routing
  - partitioning route-reflectors, 243–244
  - peer groups, 249–251
  - RR configuration, 233–234
- OSPF PE-CE routing protocol, 157–162
- route-reflector deployment, 227–228
- static PE-CE routing, 115–116
- VPN configuration, 95, 103–104

Pseudo Wire Reference Model, Layer 2 VPN

- transport, 450–452

pseudowire classes, 426

pseudowire control encapsulation, 424

pseudo-wires

- redundancy, Layer 3 VPNs over Layer 2 VPN, 640
- switching, 634–635
- VPLS, 530

PSN (Packet Switched Network), 452, 530

PVCs, TE implementation with ATM, 376

## Q

Q-in-Q tunnels, H-VPLS, 556

QoS (Quality of Service), 569–570

- classification, 570
  - DSCP, 570–573
  - IP precedence, 570–571
  - MPLS EXP bits, 573
  - ToS relationships, 570
- commands, 605–607
- implementation, 575–576
- Layer 2 VPN, 599
  - AToM, 599–602
  - L2TPv3, 604
  - VPLS, 602–603
- marking, 570
  - DSCP, 570–573
  - IP precedence, 570–571
  - MPLS EXP bits, 573
  - ToS relationships, 570
- MQC (modular QoS CLI), 581–584
- queuing, 573–575

- topology, 585–586
  - short pipe mode implementation, 596–598
  - uniform mode implementation, 586–596
- tunnel modes, 576
  - long pipe, 579–580
  - pipe, 578
    - short pipe, 579
    - uniform, 577–578
- qualified learning, 533
- Quality of Service. See QoS
- queuing, QoS (quality of service), 573–575

## R

random-detect command, 582

raw mode, L2TPv3, 421

RECORD\_ROUTE object, 384

redistribute connected command, 114, 295

redistribute connected method, transporting VPNv4, 294

- configuration, 297–299
- control plane, 295
- data forwarding, 295
- flowchart for configuration, 296

resource reservation protocol, 380

RFC 2684 routed PVCs, frame mode MPLS, 41–43

- configuration steps, 43
- core ATM switches, 43–44
- device configuration, 45–46
- verification steps, 44–45

RIPv1 PE-CE routing, 133

- configuration, 135–136
- verification, 136–138

RIPv2 PE-CE routing, 121

- configuration, 122–124
  - CE routers, 124–125
  - PE routers, 125–128
- control plane forwarding operation, 129–132
- data forwarding operation, 132–133
- implementation flowchart, 122
- verification, 128–129

Route Distinguisher, VPN routing, 86–90

Route Targets, VPN routing, 86–90

routed interworking, AToM, 500–501

## route-reflectors

- BGP PE-CE routing, 225
  - confederations, 253–260
  - deployment methods, 225–231
  - partitioned, 236–247
  - peer groups, 248–253
  - RR configuration, 232–236
- multi-hop MP-eBGP inter-provider VPNs
  - distribution, 307–309

## routers

- E-LSRs, 7
- LSRs, 6
- provider, 80
- redistributed connected method, 298–299
- VPNs, 84
  - address families, 86–90
  - control plane operation, 91–93
  - data plane operation, 93–94
  - EIGRP PE-CE routing protocol, 180–211
  - MP-BGP, 86–90
  - OSPF PE-CE routing protocol, 141–180
  - PE-CE routing protocol, 111–139
  - Route Distinguisher, 86–90
  - Route Targets, 86–90
  - VRFs (virtual routing and forwarding tables), 85–86

## routing

- BGP PE-CE, 213–215
  - commands, 269
  - Hub and Spoke environment, 260–268
  - implementation flowchart, 216
  - route-reflectors, 225–260
  - unique and same AS numbers, 217–224
- CBR, operation in MPLS TE, 385–386
- contexts, 86
- routing loops, EIGRP PE-CE routing protocol, 195–198
- RSVP (resource reservation protocol), 380
  - Error messages, 381–382
  - operation in MPLS TE, 382–385
  - PATH messages, 380–383
  - RESERVATION messages, 381, 385
  - signaling with TE extensions, 380–385
  - Tear messages, 382

## S

- service provider (SP), 79
- session messages (LDP), 13
- sham links, OSPF PE-CE routing protocol, 168–171
  - configuration, 172–180
  - flowchart of configuration, 171
- shape command, 582
- short pipe mode
  - implementation, 596–598
  - QoS tunnel mode, 579
- show atm vc command, 47
- show atm vp command, 47
- show controllers vsi status command, 72
- show ip bgp neighbor command, 106
- show ip cef command, 36
- show ip route ospf command, 64
- show ip vrf command, 99
- show ip vrf interfaces command, 99
- show mpls atm-ldp bindings command, 54–56, 130–133
- show mpls interfaces command, 36
- show mpls ldp discovery command, 37, 51
- show mpls ldp neighbor command, 37, 52
- show mpls traffic-eng fast-reroute database detail command, 410
- show mpls traffic-eng tunnel brief command, 400
- show mpls traffic-eng tunnels destination command, 401
- signaling, RSVP with TE extensions, 380–382
  - RSVP Error messages, 381–382
  - RSVP PATH message, 380–383
  - RSVP RESERVATION messages, 381, 385
  - RSVP Tear messages, 382
- Site of Origin (SoO), 89, 670
  - attributes, EIGRP PE-CE routing protocol, 200
  - backdoor link, 201–202
  - configuration, 202
  - multi-homed sites, 201
- SoO (Site of Origin), 89, 670
  - attributes, EIGRP PE-CE routing protocol, 200
  - backdoor link, 201–202
  - configuration, 202
  - multi-homed sites, 201
- SP (service provider), 79
- SPF calculation, constraint-based MPLS TE operation, 388–390

- static PE-CE routing, 111–112
  - command reference, 120
  - configuration, 113–114
  - devices, 115–118
  - implementation flowchart, 112–113
  - verification, 118–120
- static tunnels, L2TPv3 configuration, 426–429
  - devices, 430
  - operation verification, 429–430
- suboptimal routing, EIGRP PE-CE routing protocol, 198
- Sub-TLV 6, 393
- Sub-TLV 8, 393
- Sub-TLV 9, 393
- Sub-TLV 10, 393
- switches, local, ATOM, 517–526

## T

- tailend routers, 380
- TE (traffic engineering), 375
  - basics, 375–377
  - implementation with ATM, 376
  - implementation with IP, 375
  - MPLS TE, 375
    - commands, 416–417
    - configuration, 393–416
    - theory, 377–393
- TE tunnels (Tunnel1 and Tunnel2), 378
  - configurations in implementation of MPLS VPN, 411–413
  - final configurations for dynamic and explicit paths, 404–408
  - unequal cost load balancing, MPLS TE configuration, 408–409
  - verification following MPLS TE configuration, 400–404
- TLV134, 392
- TLV135, 392
- TLV-22, 392
- topology, MPLS TE configuration, 397
- traceroutes, performing on MPLS domain, 21
- traffic engineering. *See* TE
- TTL
  - field, 9
  - propagation, disabling, 20

- Tunnel Header, 453
- tunnel labels, 453
- tunnel modes, QoS (quality of service), 576
  - long pipe mode, 579–580
  - pipe mode, 578
  - short pipe mode, 579
  - uniform mode, 577–578
- tunnel mpls traffic-eng fast-reroute command, 410
- Tunnel1, 378
- Tunnel2, 378
- tunneling, L2TPv3
  - basics, 419–424
  - commands, 446–447
  - configuration, 424–426
  - dynamic tunnel configuration, 431–435
  - L3VPN implementation, 436–437, 440–446
  - static tunnel configuration, 426–430
- tunnels (TE), verification following MPLS TE configuration, 400–404

## U

- unequal cost load balancing, MPLS TE configuration, 408–409
- uniform mode
  - implementation, 586–596
  - QoS tunnel mode, 577–578
- unqualified learning, 533
- unsolicited downstream label distribution, 15
- untagged labels, 17
- update-source command, 100
- u-PE (user facing PE), 555
- upstream, 8
- user facing PE (u-PE), 555

## V

- VC-FEC (Virtual-circuit FEC), 454
- VC-merge, 29–31
- VCS (virtual circuits), 46
  - cell-mode MPLS with merge, 58
  - ATM LSR configuration, 59
  - ATM LSR verification steps, 61
  - configuration flowchart, 59
  - device configuration, 60
  - Edge ATM LSR configuration steps, 59

- cell-mode MPLS without merge, 61–62
- label withdrawal procedure, 457
- Multiplexing, 41
- verification
  - AAL5 over MPLS operation, 463–465
  - BGP PE-CE routing
    - confederations, 259–260
    - Hub and Spoke environment, 264–268
    - inbound filters, 241–242
    - partitioning route-reflectors, 247
    - peer groups, 251–253
    - route-reflectors, 235–236
    - unique and same AS numbers, 222–224
  - CBTS (class-based tunnel selection), 652
  - cell-mode MPLS
    - configuration, 51–53
    - over VP tunnels, 64–65
  - CSC network deployment
    - carrier not running MPLS, 357–358
    - carrier providing MPLS VPN service, 370–371
    - carrier running MPLS, 363–365
  - EIGRP PE-CE routing protocol
    - basic configuration, 192–195
    - BGP cost community and SoO attribute, 209–211
  - frame mode MPLS, 36–38
  - H-VPLS, 559–561
  - inter-provider VPNs distribution, back-to-back
    - VRF method, 285–287
  - L2TPv3, L3VPN implementation, 440–441
  - Layer 2 VPNs over Inter-AS, 634
  - Layer 3 VPNs over Layer 2 VPN, 640–641
  - MPLS TE over TE
    - PE to P tunnels, 415–416
    - PE to PE tunnels, 414–415
  - multicast VPNs, 615
  - multi-VRF CE, 629
  - OSPF PE-CE routing, 162–166, 177–180
  - PPP over MPLS, 490–492
  - RFC 2684 routed PVCs, 44–45
  - RIPv1 PE-CE routing, 136–138
  - RIPv2 PE-CE routing, 128–129
  - static PE-CE routing, 118–120
  - transporting VPNv4, redistributed connected method, 299
  - VPLS, Direct Attachment Architecture, 541–543, 550–551
  - VFI (virtual forwarding instance), 531
  - virtual circuits. *See* VCs
  - virtual forwarding instance (VFI), 531
  - virtual path identifier/virtual channel identifier fields (VPI/VCI fields), 46
  - Virtual Private LAN Service. *See* VPLS
  - Virtual Private Wire Service (VPWS), 450
  - virtual routing and forwarding tables. *See* VRFs
  - virtual switch interface (VSI), 66, 531
  - Virtual-circuit FEC (VC-FEC), 454
  - VLANs
    - mode, Ethernet over MPLS, 472–475
    - rewrite, Ethernet over MPLS, 476
  - VP tunnels, cell-mode MPLS over ATM, 62
    - ATM PVP configuration flowchart, 63
    - configuration steps, 63–64
    - device configuration, 65–66
    - Edge ATM LSR configuration flowchart, 63
    - verification steps, 64–65
  - VPI/VCI fields (virtual path identifier/virtual channel identifier fields), 46
  - VPLS (Virtual Private LAN Service), 450
    - basics, 529
      - components, 529–531
      - MAC Address Learning, 531, 533
      - MAC Address Withdrawal, 533–534
    - CE configurations, 565
    - commands, 566–567
    - Direct Attachment Architecture, 535
      - dot1q tunnel mode and Layer 2 tunneling, 546–555
      - flowchart of configuration, 537–538
      - port and 802.1Q VLAN mode, 538–546
    - H-VPLS, 555–557
      - CE routers, 565
      - flowchart of configuration, 557
      - PE routers, 561–563
      - Q-in-Q mode, 558–559
      - service verification, 559–561
      - user PE routers, 563–565
    - implementation with GSR 12000 series, case study, 662–669
    - QoS implementation, 602–603
    - unifying Layer 2 and Layer 3 services, 450
  - VPN version 4 (VPNv4), 86
  - VPNs
    - architecture, 83–84
    - basic configuration, 95

- BGP PE-PE routing, 99–103
- CE routers, 95
- forwarding on PE routers, 96–98
- label verification, 104–105
- PE1-AS1 router, 98–99
- provider routers, 103–104
- VRF verification on PE routers, 99
- customer sites, 79–82
- inter-provider
  - basics, 271–273
  - case studies, 328–343
  - commands, 343
  - distribution options, 273–309, 315–327
- MPLS, implementation over TE tunnels, 411–416
- outbound route filters, 105–106
- PE-CE routing protocol
  - commands, 138–139
  - EIGRP PE-CE, 180–211
  - OSPF (Open Shortest Path First), 141–180
  - RIPv1, 133–138
  - RIPv2, 121–133
  - static, 111–120
- routing model, 84
  - address families, 86–90
  - control plane operation, 91–93
  - data plane operation, 93–94
  - MP-BGP, 86–90
  - Route Distinguisher, 86–90
  - Route Targets, 86–90
  - VRFs (virtual routing and forwarding tables), 85–86
- VPNv4 (VPN version 4), 86
- VPWS (Virtual Private Wire Service), 450
- VRFs (virtual routing and forwarding tables), 85
  - selection using policy based routing, 617
  - verification on PE routers, 99
- VPN routing, 85–86
- VSI (virtual switch interface), 66, 531

## W

---

- websites, Cisco, 59
- Weighted Random Early Detection (WRED), queuing, 574
- WRED (Weighted Random Early Detection), queuing, 574

## X–Z

---

- xconnect commands, 432
- XtagATM interface, 68