

# INDEX

## Symbols

---

- ! (exclamation point) character, 105
- # (pound sign) character, 105

## Numerics

---

- 10-Gigabit, 54
- 10-Mbps Ethernet, 48
- 802.1D, compatibility with RSTP, 230
- 802.1Q, 156–158
- 802.1X
  - configuration exercise, 663–669
  - network access security, 639–641

## A

---

- AAA
  - accounting, 625, 629
  - authentication, 173, 623–626
  - authorization, 624, 627
  - configuration exercise, 663–669
  - configuring, 630–631
- aaa authentication login command, 626
- aaa new-model command, 87, 626
- access
  - firewalls, 647–648
  - hopping attacks (VLAN), 660–661
  - physical, 619
  - unauthorized, 77
- access control lists. *See* ACLs
- access layer, 18
- access-layer switches, 50
- accounting, 625, 629
- ACLs (access control lists), 4, 618, 643
  - PACLs, 646
  - RACLs, 643
  - security, 642
  - VACLs, 644
  - vtv lines, 619
- active keyword, 513
- adding switches, 186
- Address Resolution Protocol. *See* ARP
- addresses
  - globally scoped, 484

- GLOP, 484–485
- IP multicast, 480
- limited-scope, 484
- MAC address notification, 317–318
- NAT, 649
  - reserved link local, 483–484
  - source-specific multicast, 484
  - virtual MAC, 573
- adjacencies, 393–394, 408
- ADSL (asymmetric digital subscriber line), 56
- agents, relay (DHCP), 379
- aggregate policers, 448
- Aggressive mode UDLD (A-UDLD), 336–338, 604
  - configuration exercises, 354
  - versus* Loop Guard, 272
- AppleTalk Remote, 624
- applications
  - Auto QoS, 463
  - Cisco AVVID, 16
  - statistics, 291
  - voice, 596
- Application-Specific Integrated Circuits. *See* ASICs
- applying ACLs, 643
- Architecture for Voice, Video and integrated Data.
  - See* Cisco AVVID
- ARP (Address Resolution Protocol), 12
  - DAI, 654–658
  - as a security feature, 658–659
  - throttling, 396–398
- ASICs (Application-Specific Integrated Circuits), 5–6, 275
- assured forwarding, 431–432
- asymmetric digital subscriber line (ADSL), 56
- attacks, 655, 660–661
- attenuation, 720
- A-UDLD (Aggressive mode UDLD), 336–338, 604
  - configuration exercises, 354
  - versus* Loop Guard, 272
- authentication, 173, 623–626
- authorization, 624, 627
- auth-proxy, 627
- Auto QoS, 463
- auto-negotiation, 53, 767
- Auto-RP, 494–495
- availability (VoIP), 4
- AVVID. *See* Cisco AVVID

**B**

---

- baby giants, 157, 326
- BackboneFast, 260
  - configuration.exe, 281–286
  - configuring, 264
  - link failures, 261
  - in RSTP, 227
- backup ports, 225
- backup root bridges, 211
- black holes, preventing, 269–271
- blocking state, 206
- boot system flash command, 102
- bootstrap router (BSR), 495–496
- BPDUs (Bridge Protocol Data Units), 203
  - filtering, 266
  - formats, 226–227
  - frames, 204
  - Guard, 258, 264
  - TCN, 213
  - timers, 204
- bridge IDs, 202
- Bridge Protocol Data Units. *See* BPDUs
- bridge virtual interface (BVI), 373
- bridging
  - backup/primary root, 211
  - loops, 198
    - building loop-free networks, 200
    - Loop Guard, 270
    - preventing, 199–200
    - troubleshooting, 277
  - signaling topology changes, 213–215
  - study tips, 240–241
- broadcasting
  - domains, 7
  - packets, 480
  - suppression, 324–325
- BSR (bootstrap router), 495–496
- building, 462
  - loop-free networks, 200
  - networks (Layer 3), 16–17
- Building Access submodule, 23, 26
- Building Distribution submodule, 23, 26
- burst size, 447
- BVI (bridge virtual interface), 373

**C**

---

- C, 39, 78
- cable plants, 597
- CallManager. *See* Cisco CallManager
- CAM (content addressable memory), 398
- Campus Backbone
  - layer, 66
  - submodule, 23, 26
- Campus Infrastructure module, 57
- campus networks, 19, 132–133
- Canonical Format Indicator (CFI), 156
- case studies
  - aggressive mode UDLD, 340–344
  - design (C language), 69–70
  - preventing VLAN hopping attacks, 660–661
- Catalyst 2950 switches, 696–697
  - power redundancy, 552
  - reflector ports, 738
  - WRR, 453
- Catalyst 2955 switches, 738
- Catalyst 2970 switches, 453–454
- Catalyst 3550 switches, 37–38, 694–696
  - power redundancy, 552
  - security, 38–39
  - updating software versions, 105
- Catalyst 3560 switches, 37–39, 69, 693–694
- Catalyst 3750 switches, 37–38, 691–693
  - security, 38–39
  - SRR, 453–454
- Catalyst 4500 switches, 550–552, 688–691
  - high availability, 535
  - redundancy, 534
  - security, 37
  - SSO, 540–544
- Catalyst 6500 modules, 686
- Catalyst 6500 switches, 77, 679–682, 687
  - configuring, 452
  - deployment scenarios, 687
  - features of, 34–35
  - high availability, 535

- hybrid-mode, 78
- line cards, 682
- redundancy, 534
- redundant power supplies, 550–552
- security, 36
- service modules, 681
- Supervisor Engine 720, 685
- Supervisor Engine I, 682
- Supervisor Engine II, 683–684
- VACL actions, 644
- Catalyst QoS trust concept, 437
- Catalyst switches, 540–542, 549
  - authorization, 624
  - BackboneFast, 263
  - bridge IDs, 202
  - Cisco IOS-based, 728
  - configuring
    - multilayer switching, 391
    - voice VLANs, 608–612
    - as VTP servers, 174
  - EtherChannel, 298
  - L2 traceroute availability, 746
  - multilayer, 369
  - policing, 448
  - pVLANs, 148
  - QoS fundamentals, 433–443
  - redundant Supervisor Engines, 533–542
  - RSPAN feature support, 738
  - security, 617
    - ACLs, 618
    - disabling, 620–621
    - passwords, 618
    - physical access, 619
  - software images, 96, 99–100
  - troubleshooting, 107
    - configuration commands, 109
    - connecting switches, 111
    - debug commands, impact and use, 109
    - IP connectivity, 112
    - show and debug commands, 108
  - updating software versions, 101–102, 105
  - VMPS support, 135
  - wavelengths, 718
- CDP (Cisco Discovery Protocol), 311, 314, 621
- CEF (Cisco Express Forwarding), 4, 391–395, 539
- CEF-based MLS, 391–395
  - ARP throttling, 396–398
  - centralized/distributed switching, 395–396
  - commands, 414
  - configuration, 404–406
    - adjacency tables, 408–411
    - CEF tables, 406
  - distributed switching, 396
  - load sharing, 404
  - sample operation, 402–403
  - study tips, 412–414
  - switching table architectures
    - CAM, 398
    - TCAM, 399, 401
  - troubleshooting
    - configuration exercise, 415–418
    - debugging CEF on Layer 3 Engine, 410
    - methodology, 411–412
    - verification, 405
- centralized switching, 395–396
- CFI (Canonical Format Indicator), 156
- channeling (EtherChannel), 298
- chromatic dispersion, 720
- Cisco AVVID, 15, 41
  - applications, 16
  - IP, 597
  - network topology, 16
  - supported components, 15
- Cisco CallManager, 165, 448, 596
- Cisco Catalyst switches. *See* Catalyst switches
- Cisco CatOS
  - compared to Cisco IOS (Native Mode), 78
  - configuring VLANs, 140
  - converting to Cisco IOS (Native Mode), 106
  - differences as compared to Cisco IOS, 79
  - feature parity with Cisco IOS, 78–79
  - MDGs, 316–317
  - switches, 82
    - configuration changes, 94
    - DNS lookup, 90
    - passwords, 86
    - Syslog destination, 91
    - time adjustments, 85
- Cisco CatOS-based switches
  - L2 traceroute command output, 748
  - SPAN configuration, 730
- Cisco Discovery Protocol (CDP), 311, 314, 621
- Cisco Express Forwarding. *See* CEF
- Cisco Firewall Services Module, 34

- Cisco IFS, 96
  - determining IFS size and contents, 98
  - formatting and copying images, 96
  - prefix descriptions, 97–98
- Cisco IOS, 163–164
  - Catalyst switches, 115–121
  - configuring AAA authorization, 628
  - debug command, 108
  - differences as compared to Cisco CatOS, 79
  - feature parity with Cisco CatOS, 78–79
  - file system, 96
    - determining size and contents, 98
    - image naming, 99–100
  - global configuration mode, 137–139
  - naming conventions, 100
  - show command, 108
  - switches
    - DNS lookup, 90
    - NTP settings, 85
    - Syslog destination, 91
    - time adjustments, 85
  - VLAN database configuration mode, 137
  - voice VLANs, 599
- Cisco IOS Server Load Balancing (SLB), 578–583
- Cisco IOS-based switches, SPAN configuration, 731
- Cisco IP Phones, 596
  - configuring, 599
  - daisy-chain topology, 598
- Cisco LRE (Long-Reach Ethernet), 55–56
- Cisco Metro solutions, 703–705
- classification, 444
- clear commands, 516
- clear vlan command, 141
- CLI (command-line interface), 77
- command-line interface (CLI), 77
- commands
  - bridging, 241
  - CEF-based MLS, 414
  - clear, 516
  - copy running-config startup-config, 102
  - debug ip cef, 411
  - enable secret, 618
  - encryption-type, 86
  - IP telephony, 607
  - line vty, 86
  - local SPN, 731
  - multicast traffic deployment, 518
  - performance management, 757
  - QoS, 465
  - redundancy, 584
  - RSPAN, 738
  - security, 663–664
  - show, 516
  - show catalyst6000 traffic-meter, 290
  - show interface, 83, 112
  - show ip mroute, 513–514
  - show ip route, 112
  - show logging, 288
  - show process cpu, 289
  - show running-config interface, 143
  - show system, 290
  - shutdown interface-level, 290
  - snmp-server user, 94
  - spanning-tree portfast, 285
  - srr-queue bandwidth shape, 454
  - srr-queue bandwidth share, 454
  - STP, 281
  - study tips, 114
  - switchport, 185
  - switchport host, 140
  - VLANs, 179, 381
  - vtp domain domain-name, 184
  - vtp mode, 184
  - vtp password, 184
  - vtp v2-mode, 174
- Common Spanning Tree (CST), 232
- community VLANs, 147
- comparing
  - PIM versions, 496–497
  - shared/source trees, 490–491
- compatibility of PIM, 496–497
- components
  - CEF, 393–395
  - Cisco AVVID, 15
  - Internet Connectivity module, 29
  - IP telephony, 595–596
  - Remote Access module, 30
  - VPN module, 30
- configuration exercises
  - 802.1X, 663, 665–669
  - AAA, 663–669
  - aggressive mode UDLD, 354
  - Cisco IOS-based Catalyst switches, 115–121

- configuring
  - BackboneFast, 281–286
  - QoS on Catalyst switches, 466–472
  - Root Guard, 285
  - RPR+, 586–588
  - spanning-tree, 242–248
  - UplinkFast, 284
  - VLANs, 181–185
  - voice VLANs, 608–612
- EtherChannel, 346–350
- HSRP, 589–591
- inter-VLAN routing, 385
- configuring, 115–121, 570, 653–654
  - AAA, 630–631
    - accounting, 629
    - authentication, 626
    - authorization, 627
  - aggressive mode UDLD, 343
  - Auto QoS, 463
  - baby giant and jumbo frame support, 329
  - BackboneFast, 264, 281–286
  - BPDU filtering, 266
  - broadcast and multicast suppression, 325
  - burst size, 447
  - CEF, 406
  - CEF-based MLS, 404–406
  - debounce timer feature, 323
  - DHCP snooping, 651
  - DNS lookup, 90
  - EtherChannel, 304–306
  - HSRP, 562–569
  - IEEE 802.1Q trunking, 162–163
  - IGMP snooping, 511
  - Interface FastEthernet, 611–612
  - inter-VLAN routing, 376
  - IP Phones, 599
  - IP telephony security, 603–604
  - ISL trunking, 161
  - LACP, 301
  - local SPAN, 731
  - loop-free networks, 200
  - MAC address notification, 318
  - MDGs, 317
  - MST, 236, 238–239
  - multilayer switching, 391
  - PACLs, 646
  - policers, 448
  - policy maps, 443
  - PortFast, 257, 285–286
  - protocol filtering, 320
  - PVST+
    - port cost, 220
    - root bridges, 219–220
  - Root Guard, 268, 285
  - RSPAN, 738
  - SNMP, 93–94
  - SPAN, 730
  - SRM, 547
  - SSO, 542
  - STP, 221–223, 244
  - switches for SSH, 88
  - Syslog destination, 91
  - UDLD, 338–339
  - UplinkFast, 259, 284
  - VACL with the capture option, 744
  - virtual servers (SLB), 582
  - VLANs, 138–139, 141
    - private VLANs, 148–151, 188–189
    - verifying configuration, 141–143
  - VSPAN, 732
  - VTP, 173–176
  - WRED, 460
  - WRR on Catalyst 6500 switches, 452
- connecting
  - IP telephony submodules, 604
  - redundancy, 290
- content addressable memory (CAM), 398
- control packets, prioritizing, 279
- converting Cisco CatOS to Cisco IOS (Native mode), 106
- copy command, 94
- copy running-config startup-config command, 102, 538
- copy tftp flash command, 101
- copying images on the Cisco IFS, 96
- core layer, 18
- count keyword, 514
- CQ (custom queuing), 456
- creating loop-free spanning trees, 208–211
- crypto key generate command, 87
- CST (Common Spanning Tree), 232
- current-generation network interface cards, 51
- custom queuing (CQ), 456
- CWDM modules, 720

**D**

DAI (Dynamic ARP inspection), 654–658

data paths, 682

data-link technologies, 47, 53

- 10-Gigabit Ethernet, 54
- 10-Mbps Ethernet, 48
- Fast Ethernet, 49
- GBICs, 55
- Gigabit Ethernet, 50–52
- LRE, 55–56

data-planes, 393

debounce timer feature, 322

- configuring, 323
- enabling, 322

debug all command, 110

debug command, 110

debug ip cef command, 411

default gateway router redundancy, 552, 555

- GLBP, 575
- HSRP, 556–560, 562–570
- IRDP, 554
- proxy ARP, 553
- VRRP, 571–574

deleting VLANs, 139

dense wavelength division multiplexing (DWDM)

- metro Ethernet, 714
- OADMs, 718
- optical multiplexers, 718
- wavelengths, 716

deploying IP telephony solutions, 604–605

designing

- loop-free networks, 200
- multilayer switched networks
  - case study, 69–70
  - Cisco Catalyst switches and data-link technologies, 57
  - data-link technologies, 47
  - large campus networks, 61–64
  - medium-sized campus networks, 60
  - selecting Layer 2 or Layer 3 switches, 58
  - Server Farm module, 64–67
  - small campus networks, 59
- networks, 596–603

devices, PDUs, 10

DFC (Distributed Forwarding Cards), 395

DHCP (Dynamic Handshake Challenge Protocol)

- enabling relay agents, 379
- snooping, 649–651

DHCP-based management IP configuration, 320–321

Differentiated Services Code Point (DSCP), 436

DiffServ model, 421, 428

- IP, 430
- packet, 429

disabling

- CDP, 621
- state, 206
- Telnet access, 121
- unnneeded or unused services, 620

disaster recovery, 3

discard adjacency, 408

disconnecting redundancy, 290

distance limitations, Ethernet wire, 50

Distributed Forwarding Cards (DFC), 395

distributed switching, 396

distribution layer, 18

distribution-layer switches, 50

DNS (Domain Name Service), 90

drop adjacency, 408

DSCP (Differentiated Services Code Point), 436

DTP (Dynamic Trunk Protocol), 620

duplex mismatch, 274

DVS (directed VLAN service), 710

DWDM (dense wavelength division multiplexing)

- metro Ethernet, 714
- OADMs, 718
- optical multiplexers, 718
- wavelengths, 716

Dynamic ARP inspection (DAI), 654–658

dynamic NAT, 649

Dynamic Trunk Protocol (DTP), 620

dynamic VLANs, 135

**E**

EDFAs (erbium doped fiber amplifiers), 718

egress queuing (SRR), 454–455

EIGRP (Enhanced Interior Gateway Routing Protocol), 63

electing a root bridge, 208

EMI (Enhanced Multilayer Image), 695

enable secret command, 618

- enabling
  - debounce timer feature, 322
  - DHCP relay agents, 379
  - NDE as source for NAM, 752
  - passwords, 86
  - VMPS, 135
- encapsulation dot1Q 1 native command, 375
- encryption (SNMP), 92
- encryption-type command, 86
- Enhanced Multilayer Image (EMI), 695
- Enhanced Interior Gateway Routing Protocol (EIGRP), 63
- enhancing network performance, 728, 736–737, 743–744
  - critical success tasks, 726
  - monitoring with RSPAN, 735, 739–740
  - SPAN, 727–730
  - VSPAN
    - configuration, 732
    - guidelines and rest, 730
- Enterprise Campus modules, 25–26
  - infrastructure, 22
  - meeting the needs of Enterprise networks, 25
- Enterprise Composite Network Model, 13, 18
  - Campus Infrastructure module, 57
  - Enterprise Campus, 22–25
  - Enterprise Edge, 20, 27
    - E-Commerce module, 28
    - Internet Connectivity module, 29
    - modules, 27
    - Remote Access module, 30
    - sample implementation, 31
    - VPN module, 30
    - WAN module, 30
  - Gigabit Ethernet, 51
  - IP, 604–605
  - overview, 19
  - sample implementation, 21
  - Service Provider Edge, 20, 31
    - ISP module, 31
    - PSTN module, 32
    - sample implementation, 33
- Enterprise Edge submodule, 4, 26, 68
  - E-Commerce module, 28
  - Internet Connectivity module, 29
  - modules, 27
  - Remote Access module, 30
  - sample implementation, 31
  - VPN module, 30
  - WAN module, 30
- enterprise MANs, 706
- enterprise network storage, 64
- erase startup-config command, 94
- erbium doped fiber amplifiers (EDFAs), 718
- error-disable feature, 329–333
- ESCON (Ethernet, Enterprise Systems Connection), 705
- EtherChannel, 298
  - configuration example, 303–306
  - configuration exercises, 346–350
  - guidelines, 302
  - LACP modes, 301–302
  - link redundancy, 532
  - load balancing, 309–311
  - PAgP modes, 300
- Ethernet, 49
  - baby giants, 326
  - Gigabit Ethernet, 51
  - jumbo frames, 327–329
  - metro Ethernet, 56, 706
    - CDWM, 718, 720
    - connectivity and transport, 707–710
    - DWDM, 715
    - optical distance challenges, 720–721
    - SONET, 711–713
    - WDM, 714
  - trunking modes, 160
  - wire standards and maximum distances, 50
- Ethernet, Enterprise Systems Connection (ESCON), 705
- EtherType(TPID), 156
- exclamation point (!) character, 105
- expedited forwarding, 432
- external routers, 373

---

## F

- Fast Ethernet, 49
- FCIP (Fibre Channel over IP), 4, 64
- FFI (Full Flow Information), 392
- FIB (forwarding information base), 393–394, 705
- Fibre Channel over IP (FCIP), 4, 64

- FIFO queuing, 450
- file systems, 96
- filtering
  - BPDUs, 266
  - DHCP snooping, 649
  - MAC addresses, 636
    - unicast, 637
- firewalls, 4, 647–648
- five nines uptime, 595
- flooding, 638–639
- flow control (IEEE 802.3), 334–335
- formatting images on the Cisco IFS, 96
- forwarding information base (FIB), 393–394, 705
- forwarding
  - loops, 269–271
  - state, 206
- Frame Relay, ATM, and PPP module, 32
- frames
  - baby giants, 157, 326
  - BPDUs, 204
  - corruption, 275
  - IEEE 802.1 Q, 156
  - ISL, 154
  - jumbo, 327, 329
- Full Flow Information (FFI), 392
- functional areas (Enterprise Composite Network Model), 21

## G

---

- Gateway Load Balancing Protocol (GLBP), 575
- GBICs (Gigabit Interface Converters), 55
- Gigabit Ethernet, 50, 55
  - auto-negotiation, 767
  - deployment strategies, 51
  - Fast Ethernet auto-negotiation, 53
- GLBP (Gateway Load Balancing Protocol), 575
- global configuration mode, 139
- globally scoped addresses, 484
- GLOP addresses, 484–485
- groups
  - multicast, 482
  - SNMP, 94

## H

---

- hardware, 290, 502–504
- hardware-switching, 5
- hello time timers, 206
- hierarchies, IP addresses, 365–366
- high availability, 529–530, 535, 602
- hopping attacks (VLAN), 660–661
- hosts, multicast groups, 480
- HSRP (Hot Standby Router Protocol), 4, 8, 570
  - configuration exercise, 589–591
  - virtual MAC address, 559
- Hybrid OS, 78
- hybrid-mode, 78

## I

---

- IEEE 802.1D, 202. *See also* STP
- IEEE 802.1Q, 153–158, 218
- IEEE 802.1Q-in-Q tunneling, 159
- IEEE 802.1w, 223. *See* RSTP
- IEEE 802.3 flow control feature, 334–335
- IGMP (Internet Group Management Protocol), 511
- images
  - loading on a Catalyst switch, 102
  - naming, 99–100
- implementing
  - ISL, 154
  - pVLANs, 147
  - SSO, 533, 540–542
- individual policers, 448
- infrastructure
  - Enterprise Campus, 22
  - IP telephony, 596
- inpkts keyword, 730
- inspection, DAI, 654–658
- integrated services model (IntServ model), 428
- Interface FastEthernet, configuring, 611–612
- interfaces
  - Catalyst 6500 switches, 681
  - DHCP snooping, 650
  - IPSG, 652–654
  - RACLs, 643
  - security, 621
- Internet service providers (ISPs), 6
- Internetwork Packet Exchange (IPX), 624



Inter-Switch Link (ISL), 153  
 inter-VLAN routing, 365–369  
     configuration exercise, 385  
     IP broadcasts, 378–379  
     multiple, 371–373  
     router on a stick, 373–375  
     study tips, 380–381  
     UDP, 379  
     verifying, 376  
 IntServ model, 428  
 IOS switches, configuring AAA, 630–631  
 IP (Internet Protocol), 279, 491, 507–508  
 IP addresses, 482–485  
     hierarchies, 365–366  
     multicast, 480  
 IP helper-address command, 379  
 IP Phones, configuring, 596–599  
 IP Source Guard (IPSG), 603, 652–654  
 IP telephony  
     commands, 607  
     components, 595–596  
     deployment best practices, 604–605  
     five nines uptime, 595  
     high availability, 602  
     network design, 596–597  
         bandwidth, 600  
         management, 602  
         power considerations, 601  
         QoS, 597  
         security, 603  
         voice (auxiliary), 598–599  
     security, 603–604  
     study tips, 605–606  
     submodules, 604  
 IPSG (IP Source Guard), 603, 652–654  
 IPX (Internetwork Packet Exchange), 624  
 ISL (Inter-Switch Link), 153–154  
 isolation  
     pVLANs, 148  
     VLANs, 147  
 ISPs (Internet service providers), 6  
 ITU grids, 717

## J - K

jitter, 425, 480  
 jumbo frames, 327–329

keywords  
     active, 513  
     count, 514  
     summary, 513

## L

L2 traceroute command  
     availability on Catalyst switches, 746  
     output from Cisco IOS-based switches, 747  
 LACP (Link Aggregation Control Protocol), 301–302  
 latency, 424  
 Layer 1, 201  
 Layer 2, 504–505  
     Cisco CatOS, 78  
     IPSG, 652–654  
     legacy switches, 7  
     loops, 286–292  
     multilayer switching, 13, 506–507  
     protocols  
         CDP, 311, 314  
         UDLD, 335  
     redundancy, 541  
     switching, 7, 10  
 Layer 3  
     entries, 392  
     marking, 443  
     multilayer switching, 13  
     networks, 16–17  
     protocol filtering, 319–320  
     routing protocol support, 369  
     switching, 8, 11, 15  
         ARP, 12  
         packet rewriting, 11  
     viewing, 406–408  
 Layer 4  
     performance, 9  
     QoS marking, 7  
     terminology, 9  
 layers  
     multiple, 6  
     Network Design Hierarchical Model, 18  
     PDUs, 10  
     Server Farm module, 66

- leaky token bucket algorithm, 446
- learning state, 206
- levels of SNMP, 92
- limited-scope addresses, 484
- line cards, Catalyst 6500 switches, 682
- line vty command, 86
- Link Aggregation Control Protocol (LACP), 301–302
- links
  - failures, 261
  - spanning-tree path cost, 202
- listening state, 206
- load balancing
  - EtherChannel, 309–311
  - HSRP, 560
- load sharing, CEF-based MLS, 404
- local SPAN, configuring, 731
- logging onto syslog servers, 91
- Loop Guard
  - versus* aggressive mode UDLD, 272
  - Root Guard, 271
- loop-free networks, building, 200
- loops
  - bridging, 198
  - building loop-free networks, 200
  - preventing, 199–200
  - Layer 2, 286–292

## M

- MAC (Media Access Control) addresses, 202, 317–318
- management
  - Catalyst switch configurations, 94
  - performance study tips, 756–757
- man-in-the-middle attacks, 655
- mapping
  - multicast IP-to-MAC, 485
  - policies, 443
  - VLANs, 158
- MDGs (Multiple Default Gateways), 316–317
- Media Access Control (MAC) addresses, 202, 317–318
- membership, multicast groups, 482
- memory, ASICs, 6

- merging, 643
- Metro Ethernet, 56, 706
  - CDWM, 718, 720
  - connectivity and transport, 707
    - DVS, 710
    - TLS, 708–709
  - DWDM, 715
  - optical distance challenges, 720–721
  - SONET, 711–713
  - WDM, 714
- MFIB (multicast forwarding information base), 504
- MFSC (Multilayer Feature Switch Card)
  - model, 106
- microflow policing, 448
- misconfiguring 802.1Q, 158
- MLS (multilayer switching), 4–5, 391
  - CEF-based MLS, 393–395
    - ARP throttling, 396–398
    - centralized/distributed switching, 395–396
    - configuration, 404–406
    - distributed switching, 396
    - load sharing, 404
    - sample operation, 402–403
    - study tips, 412–414
    - switching table architectures, 398–401
    - troubleshooting, 410–418
    - verification, 405
    - viewing, 406–409, 411
  - traditional MLS, 392
- mls nde sender command, 752
- MMLS (Multicast multilayer switching), 503
- mode rpr-plus command, 588
- models, SNMP, 92
- modes, SSO, 540–544
- modifying STP, 249–250
- modules
  - Catalyst 6500, 686–687
  - Cisco Firewall Services Module, 34
  - Enterprise Campus, 25–26
  - Network Management, 24
  - Server Farm, 24
- monitors, 735, 739–740
- moving configurations, 94
- MSFC (Multilayer Switch Feature Card), 77, 106

- MST (Multiple Spanning Tree), 231
  - 802.1Q, 232
  - configuring, 236, 238–239
  - IST instances, 234
  - instances, 236
  - PVST+, 232
  - regions, 233
- multicast forwarding information base (MFIB), 504
- multicast IP addresses, 480
- Multicast multilayer switching (MMLS), 503
- multicast suppression, 325
- multicast traffic, 479–481
  - deploying (study tips), 517–518
  - forwarding trees, 488–491
  - hardware switching, 502
    - CEF-based MMLS, 503
    - MFIB, 504
    - MMLS, 503
  - IP addresses, 482–485
  - IP protocols, 491, 507–508
    - configuring, 508–512
    - IGMP, 497–502
    - monitoring, 512–516
    - PIM, 491–497
  - Layer 2 protocols, 504–505
    - CGMP, 506–507
    - IGMP snooping, 505–506
  - MAC addresses, 485–486
  - reverse path forwarding, 486–488
- Multilayer Switch Feature Card (MSFC), 77, 106
- multilayer switched networks, 6, 303, 370, 618
  - Catalyst switch security, 617
  - Cisco AVVID, 15
    - applications, 16
    - supported components, 15
  - Cisco metro solutions, 704
  - data-link technologies, 47
    - 10-Gigabit Ethernet, 54
    - 10-Mbps Ethernet, 48
    - Fast Ethernet, 49, 53
    - GBICs, 55
    - Gigabit Ethernet, 50–52
    - LRE, 55–56
  - default gateway router redundancy, 552
    - GLBP, 575
    - HSRP, 556–560, 562–570
    - IRDP, 554
    - proxy ARP, 553
    - static default gateway configuration, 555
    - VRRP, 571–574
  - designing, 57
    - case study, 69–70
    - large campus networks, 61–64
    - medium-sized campus, 60
    - selecting, 58
    - Server Farm module, 64–67
    - small campus networks, 59
  - DHCP snooping, 651
  - disaster recovery, 4
  - Enterprise Composite Network Model, 13, 18, 28–33
  - Enterprise Edge, 68
  - hardware switching, 502
    - MFIB, 504
    - MMLS, 503
  - IP address hierarchies, 365–366
  - IP telephony security, 603–604
- Layer 2
  - CGMP, 506–507
  - design properties, 10
  - protocols, 504–506
  - switching, 7
- Layer 3, 11, 15
  - ARP, 12
  - packet rewriting, 11
  - switching, 8
- Layer 4
  - performance, 9
  - terminology, 9
- Layer 7 switching, 10
- multicast traffic, 479–488, 517–518
  - connections, 508–512
  - forwarding, 488–491
  - IP addresses, 482–485
  - IP protocols, 491–498, 500–508
  - MAC addresses, 485–486
  - monitoring, 512–516
- OSI reference model, 6
- QoS, 420–421, 460
  - assured forwarding, 431–432
  - Building Access submodule, 462
  - Building Distribution submodule, 462

- Campus Backbone, 463
- Catalyst fundamentals, 433–444
- congestion avoidance, 456–459
- congestion management, 449–456
- DiffServ model, 428–430
- expedited forwarding, 432
- IntServ model, 428
- jitter, 425
- latency, 424
- need for, 422–423
- packet loss, 426
- service models, 427
- traffic conditioning, 445–448
- trunking, 153
- multilayer switching. *See* MLS
- Multiple Default Gateways (MDG), 316–317
- Multiple Spanning Tree. *See* MST

## N

- NAM (Network Application Manager)
  - Catalyst 6500 switches, 748–753
  - versions, 748
- naming images, 99–100
- NAS (Network Area Storage), 4
- NAT (network address translation), 6, 649
- Native IOS, 78
- NBAR (Network Based Application Recognition), 441
- NDE (NetFlow Data Export), 750
  - enabling, 752
  - as a traffic source for NAM, 752
- NetFlow Data Export. *See* NDE
- network address translation (NAT), 6, 649
- Network Analysis Module, 748
- Network Application Manager (NAM)
  - Catalyst 6500 switches, 748–753
  - versions, 748
- Network Area Storage (NAS), 4
- Network Design Hierarchical Model, 18
- Network Management module, 24
- Network Management Processor (NMP), 683
- Network Time Protocol (NTP), 9
- networks
  - designing IP telephony, 596–603
  - enhancing performance
    - critical success tasks, 726
    - monitoring CPU interfaces, 733–734

- SPAN, 727–728, 730
- VSPAN, 730, 732
- Ethernet, 56
- FCIP, 64
- firewalls, 647–648
- high availability, 529–531
- Layer 3, 16–17
- loops, 290
- monitoring performance
  - RSPAN, 735–740
  - VACL, 743–744
- multilayer switched networks. *See* multilayer switched networks
- port security, 631–639
- security
  - ACLs, 642
  - network access (802.1X), 639–641
  - private VLANs, 658
  - QoS, 659
- VLANs, 131, 155, 158
  - configuring, 138–139, 141–151, 188–189
  - deleting, 139
  - dynamic, 135
  - implementing, 132–133
  - ranges, 136, 158
  - service provider-managed VLAN, 159
  - static, 134
  - study tips, 177–180
  - troubleshooting, 144–149
  - trunking, 152–154, 160–165
  - verifying configuration, 141–143
- NMP (Network Management Processor), 683
- no monitor session command, 737
- no switchport command, 304
- no switchport interface command, 370
- nonlinearities, 721
- NSF (Non-Stop Forwarding), 533, 543–544, 679
- NTP (Network Time Protocol), 9
- null adjacency, 408

## O

- OADM (optical add/drop multiplexers), 718–720
- OIR (Online Insertion and Removal) of, 537
- operating systems. *See* OS
- optical add/drop multiplexers (OADMs), 718

- OS (operating systems)
  - Catalysts 6500 switches, 78
  - Cisco CatOS, 78
  - Hybrid OS, 78
- OSI reference model, 6
- OSPF (Open Shortest Path First), 63

## P

- packets
  - broadcasting, 480
  - control, 279
  - loss, 102, 426
  - rewriting, 12
- PACLs (port access control lists), 646
- PAgP (Port Aggregation Protocol), 300, 620
- passwords, 86, 618
- PDU (protocol data units), 10
- Per VLAN Spanning Tree Plus. *See* PVST+, 215
- performance
  - enhancing, 727–730
  - Layer 4 switching, 9
  - management (study tips), 756–757
  - NAM (Catalyst 6500 switches), 748
    - autostart collections, 753
    - configuration, 749
    - data sources, 750
    - NDE as data source, 752
    - troubleshooting common problems, 755
    - verifying configuration, 754
- permanent filters, 637
- per-port VLAN ACL (PVACL), 652
- PFC (Policy Feature Card), 683
- PIM show commands, 516
- plain old telephone service (POTS), 55
- plants (cable), 597
- plug-n-play, 621
- Policy Feature Card (PFC), 683
- policy maps, configuring, 443
- populating Layer 3 entries, 392
- port access control lists (PACLs), 646
- Port Aggregation Protocol (PAgP), 300, 620
- PortFast, 256
  - configuration errors, 276
  - configuring, 257, 285–286
  - verifying, 285–286
- PortFast-enabled interfaces, 266
- ports
  - backup, 225
  - checking status, 279
  - cost, 220
  - EtherChannel, 302
  - reflector, 738
  - roles, 225
  - root, 212
  - Root Guard, 266–268
  - routed, 370
  - security, 639
    - blocking unicast flooding, 638–639
    - host MAC addresses, 632–635
    - restricting traffic, 636–637
  - source (RSPAN), 736
  - spanning-tree port states, 207
  - SSO, 541
  - uplink, 550
- POTS (plain old telephone service), 55
- pound sign (#) character, 105
- power supplies
  - redundancy, 550–552
  - UPS, 602
- preventing bridging loops, 199–200
- primary root bridges, 211
- prioritizing
  - control packets, 279
  - STP, 244–247
- priority queuing, 455
- priority values, 765
- private VLANs (pVLANs), 658
  - configuring, 148–151, 188–189
  - structure, 146
  - troubleshooting, 145–149
- protocol data units (PDUs), 10
- protocols
  - ARP, 396–398
  - DTP, 620
  - Layer 2, 311–314
  - MST, 239
  - PAgP, 620
  - SNMP, 91–94
  - SSO support, 541
  - STP, 197

- trunking, 154
  - IEEE 802.1 Q, 155–158
  - ISL, 154
  - VTP, 165–175
- UDLD, 335
- pruning, 169
- punt adjacency, 408
- PVACL (per-port VLAN ACL), 652
- pVLANs (private VLANs)
  - configuring, 148–151, 188–189
  - structure, 146
  - troubleshooting, 145–149
- PVST+ (Per VLAN Spanning Tree Plus), 215
  - configuring
    - port cost, 220
    - root bridges, 219–220
  - MAC addresses, 217
  - MST, 232

## Q

- QoS (quality of service), 5, 420–421, 659
  - ACLs, 642
  - Auto QoS, 463
  - Catalyst switches, 433–434
    - classification, 435–442
    - congestion avoidance, 456–459
    - congestion management, 449–456
    - marking, 443–444
    - traffic conditioning, 445–448
  - classification, 596
  - commands, 465
  - jitter, 425
  - latency, 424
  - Layer 2 switching, 7
  - marking in Layer 4, 7
  - multilayer switched networks, 460
    - Building Access submodule, 462
    - Building Distribution submodule, 462
    - Campus Backbone, 463
  - need for, 422–423
  - packet loss, 426
  - service models, 427
    - assured forwarding, 431–432
    - DiffServ model, 428
    - expedited forwarding, 432
    - IntServ model, 428
  - study tips, 464
- quality of service. *See* QoS
- queuing, egress, 454–455

## R

- RACLs (router access control lists), 642–643
- RADIUS AVPs, 625
- random early detection (RED), 458
- ranges
  - multicast IP addresses, 483
  - VLANs, 136, 158
- Rapid Spanning Tree Protocol.
  - See* RSTP
- rapid transition to forwarding, 227–228
- RED (random early detection), 458
- redundancy, 530, 553, 574
  - Catalyst 6500 switch SRM, 545
    - configuring, 547
    - displaying status, 548
    - failure scenario, 547
  - commands, 584
  - default, 554–560, 562–567
  - default gateway routers, 552
  - disconnecting, 290
  - Layer 2, 541
  - multilayer switched networks, 18
  - power supplies, 550–552
  - study tips, 583–586
  - Supervisor Engines, 549
  - switches, 533
- Redundant Power Systems (RPS), 552
- redundant Supervisor Engines, 37, 533–535
  - route processor redundancy,
    - 535–536
    - RPR+, 537–542
- redundant switched networks, 530
- reflector ports, 738
- relay agents (DHCP), enabling, 379
- remote RSPAN, 736–737
- reserved link local addresses,
  - 483–484
- resiliency (STP), 264
- restrictions, pVLANs, 148
- root bridges, 211
  - configuring, 219–220
  - election, 208
  - planning selection, 209–210
  - selection (sample selection), 212

Root Guard, 266–267, 604  
     configuration exercise, 285  
     configuring, 268  
     Loop Guard, 271  
 root ports, 212–213  
 router access control lists (ACLs), 642  
 routers  
     BSR, 495–496  
     redundancy, 545–548  
 routing  
     inter-VLAN routing, 365–368  
         bridge virtual interface, 373  
         IP broadcast forwarding, 378–379  
         multilayer Catalyst switches, 368–370  
         router on a stick, 373–375  
         switch virtual interface, 371–372  
         UDP broadcast forwarding, 379  
         verifying configuration, 376  
     protocols, 369  
 RPSs (Redundant Power Systems), 552  
 RSPAN  
     configuring, 738–740  
     guidelines and restrictions, 736–737  
     performance monitoring, 735  
     remote, 736–737  
     session support, 742  
 RSTP (Rapid Spanning Tree Protocol), 223  
     802.1D compatibility, 230  
     BackboneFast in RSTP, 227  
     BPDU format, 226–227  
     port roles, 225  
     rapid transition to forwarding, 227–228  
     topology change mechanism, 229–230

## S

S/D (Source and destination IP address), 392  
 SANs (storage-area networks), 64  
 secondary VLANs, types of, 147  
 Secure Shell (SSH), 4  
 Secure-HTTP (S-HTTP), 9  
 security, 603  
     AAA  
         accounting, 625, 629  
         authentication, 623–626

        authorization, 624, 627  
         configuring, 630–631  
 ACLs, 642  
 Catalyst 3550 switches, 38–39  
 Catalyst 3560 switches, 38–39  
 Catalyst 3750 switches, 38–39  
 Catalyst 4500 switches, 37  
 Catalyst 6500 switches, 36  
 Catalyst switch configurations, 617, 621  
     ACLs, 618  
     disabling unneeded services, 620  
     passwords, 618  
     physical access, 619  
 commands, 663–664  
 configuring, 639–641  
 DAI, 654–658  
 Enterprise Campus modules, 25  
 firewalls, 647–648  
 interfaces, 621  
 IP telephony, 603–604  
 Layer 3 networks, 16  
 multilayer switched networks, 4  
 NAT, 649  
 ports, 631–633, 639  
     blocking unicast flooding, 638–639  
     host MAC addresses, 632–635  
     restricting traffic, 636–637  
 private VLANs, 658  
 QoS, 424, 659  
 SNMP, 92, 622  
 STP, 623  
 study tips, 662–664  
 systems  
     logging, 622  
     warning banners, 620  
     vulnerabilities (SSH), 89  
 selecting root ports, 212  
 Server Farms, 24–26, 64–67  
 servers, logging, 91  
 service modules (Catalyst 6500 switches), 681–687  
 service provided-managed VLAN services, 159  
 service providers (metro Ethernet), 706  
 set boot system flash command, 102  
 shaped round robin (SRR), 453–455  
 Shared STP. *See* SSTP  
 shared trees, 489–491

- shortest path tree (SPT), 488
- show commands, 108, 516
  - show adjacency command, 409
  - show adjacency detail command, 409
  - show catalyst6000 traffic-meter command, 290
  - show current command, 238
  - show interface command, 83, 112
  - show interfaces command, 143
  - show IP cef command, 406
  - show ip cef detail command, 406
  - show ip mroute command, 513–514
  - show ip route command, 112
  - show logging command, 288
  - show mac address-table interface command, 143
  - show pending command, 238
  - show processes cpu command, 279, 289
  - show running-config command, 143
  - show running-config interface command, 143
  - show spanning-tree command, 222
  - show system command, 290
  - show vlan command, 141
  - show VTP domain command, 176
  - show vtp status command, 176
- S-HTTP (Secure-HTTP), 9
- shutdown interface-level command, 290
- Simple Network Management Protocol (SNMP), 91–94, 662
- Single Router Mode (SRM), 545–548
- size, Cisco IFS, 98
- SLB (Cisco IOS Server Load Balancing), 578–583
- slow throughput, 144
- SMI (Standard Multilayer Image), 695
- SNAP (Subnetwork Access Protocol), 311
- SNMP (Simple Network Management Protocol), 91–93, 622
- snmp-server user command, 94
- snooping, 650–651
  - DHCP, 649
  - IGMP, 511
- software, updating versions, 101–102, 105
- software-switching, 5
- SONET (metro Ethernet), 711–713
- Source and destination IP address (S/D), 392
- Source Guard, 603
- source ports (RSPAN), 736
- source trees, 488–491
- source-specific multicast addresses, 484
- SPAN (Switched Port Analyzer), 727
  - configuring, 730
  - guidelines and restrictions, 728
  - monitoring CPU interfaces, 733–734
  - session support, 742
  - troubleshooting, 735
- spanning tree protocol. *See* STP
- spanning-tree
  - path cost, 202, 220
  - port states, 204–207
  - portfast command, 285
- SPT (shortest path tree), 488
- SRM (Single Router Mode), 545–548
- SRR (shared round robin), 453–455
- srr-queue bandwidth shape command, 454
- srr-queue bandwidth share command, 454
- SSH (Secure Shell), 4
  - accessing switches during an upgrade, 102
  - configuring switches for, 88
  - software support, 87
  - study tips, 113
  - vulnerabilities, 89
- SSO (Stateful Switchover), 37, 533, 540–542, 680
  - configuring, 542
  - NSF, 543–544
  - verifying, 542
- SSTP (Shared STP), 218
- Standard Multilayer Image (SMI), 695
- Stateful Switchover (SSO), 37, 533, 540–542, 680
  - configuring, 542
  - NSF, 543–544
  - verifying, 542
- static default gateway configuration, 555
- static filters, 637
- static NAT, 649
- static VLANs, 134
- statistics, 291
- status (PortFast), 266
- steady state STP, 337
- storage-area networks (SANs), 64
- STP (spanning tree protocol), 197, 202
  - BackboneFast, 260
    - configuring, 264
    - link failures, 261
  - BPDUs, 203
    - frame format, 204
    - timers, 204



- bridge IDs, 202
- commands, 281
- configuring, 221–223, 244
- enhancements, 256
- events debug, 278
- IEEE 802.1Q trunks, 218
- Multiple Spanning Tree (MST), 231, 233
  - 802.1Q, 232
  - configuring, 236–239
  - IST instances, 234
  - instances, 236
  - PVST+, 232
  - regions, 233
- operation overview, 207–211
- overview, 197
- PortFast, 256–257
- PVST+. *See* PVST+
- resiliency, 264
  - BPDU filtering, 266
  - BPDU Guard, 264
  - Root Guard, 266–268
- RSTP, 223
  - BPDU format, 226–227
  - port roles, 225
  - rapid transition to forwarding, 227–228
  - topology change mechanism, 229–230
- sample election process scenario, 212–213
- security, 623
- spanning-tree
  - path cost, 202
  - port states, 204–207
- study tips, 280
- topologies
  - identifying changes in, 249–250
  - modifying, 213–215
- troubleshooting, 273
  - duplex mismatch, 274
  - frame corruption, 275
  - inappropriate STP diameter parameter tuning, 276
  - methodology, 277–279
  - PortFast configuration errors, 276
  - resource error, 275
  - unidirectional link failures, 274
- UplinkFast, 258, 280
- STS-1 (synchronous transport signal-level 1), 712
- study tips
  - bridging, 240–241
  - CEF-based MLS, 412–414
  - commands, 114
  - inter-VLAN routing, 380–381
  - IP telephony, 605–606
  - multilayered network switching, 40
  - performance management, 756–757
  - QoS, 464
  - redundancy, 583–584, 586
  - security, 662, 664
  - SSH, 113
  - STP, 280
  - switches
    - roles, 71
    - types, 698
  - VLANs, 177–180
- submodules
  - Enterprise Edge, 26
  - IP telephony, 604
- subnets
  - routing packets between, 8
  - troubleshooting IPs, 279
- Subnetwork Access Protocol (SNAP), 311
- summary keyword, 513
- Supervisor Engine, 549
  - OIR, 537
  - redundancy, 533
  - route processor redundancy, 535–537
  - RPF+, 539, 542
  - RPR+, 538
- Supervisor Engine 720, 69, 685
- Supervisor Engine I, 682
- Supervisor Engine II, 683–684
- Supervisor V-10GE Engine, 36
- support
  - GLBP, 575
  - uplink ports, 550
- suppression broadcast, 324–325
- SVI (switch virtual interface), 371
- switch virtual interface (SVI), 371
- Switched Port Analyzer. *See* SPAN
- switches, 535
  - access-layer, 50
  - adding, 186

- Auto QoS, 463
  - C, 108
  - Cat, 109
  - Catalyst 2950, 696–697
  - Catalyst 3550, 37–39, 694–696
  - Catalyst 3560, 37–38, 69, 693–694
  - Catalyst 3750, 37–38, 691–693
  - Catalyst 4500, 688–691
  - Catalyst 6500, 77, 679–682, 687
    - deployment scenarios, 687
    - features of, 34–35
    - hybrid-mode, 78
    - line cards, 682
    - security, 36
    - service modules, 681
    - Supervisor Engine 720, 685
    - Supervisor Engine I, 682
    - Supervisor Engine II, 683–684
  - Catalyst switches, 107
  - Cisco Catalyst switches
    - clocks, 83–85
    - configuring, 80–82
    - DNS, 90
    - managing configurations, 94
    - system switches, 91
    - telnet and SSH, 86–88
  - Cisco CatOS, 82
    - MDGs, 316–317
    - passwords, 86
  - Cisco IOS, 85
  - configuring for SSH, 88
  - distribution-layer, 50
  - high availability, 529–531
  - IOS, 630–631
  - legacy Layer 2 switches, 7
  - multilayer, 13
  - redundancy, 533
  - reflector ports, 738
  - role of (study tips), 71
  - Server Farm module, 65
  - SNMP, 91–94
  - SSO, 540–542
    - NSF, 543–544
    - verifying, 542
  - types (study tips), 698
  - unauthorized access, 77
  - VTP-transparent switches, 168
- switching
    - distributed, 396
    - hardware-switching, 5
    - Layer 2, 7, 10
    - Layer 3, 8, 11, 15
      - ARP, 12
      - packet rewriting, 11
    - Layer 4
      - performance, 9
      - terminology, 9
    - Layer 7, 10
    - software-switching, 5
    - terminology, 6
  - switching table architectures, 398–401
  - switchport command, 185, 304, 729
  - switchport host command, 140
  - synchronous data, 704
  - synchronous transport signal-level 1 (STS-1), 712
  - syslog servers, 91
  - system logging, 622
  - system names, configuring meaningful names, 80

---

## T

- TACACS+ AVPs, 625
- tail drop, 457
- TC (Topology Change), 213
- TCAM (ternary content addressable memory), 6
- Telnet
  - accessing switches during an upgrade, 102
  - disabling access, 121
  - establishing IP connections, 112
- terminology
  - Layer 4 switching, 9
  - switching, 6
- ternary content addressable memory (TCAM), 6
- TFTP (Trivial FTP) packet loss, 102
- throttling (ARP), 396–398
- TLS (transparent LAN service), 708–709
- topologies, 598
  - metro Ethernet, 57
  - multiple Ethernet technologies, 48
  - STP, 249–250
- topology change mechanism (RSTP), 229–230
- tracking, DHCP snooping, 650
- traffic
  - DHCP snooping, 650–651

- load balancing (EtherChannel), 309–311
- multicast, 479–481
  - CEF-based MMLS, 503
  - CGMP, 506–507
  - configuring IP, 508–512
  - deploying (study tips), 517–518
  - forwarding trees, 488–491
  - hardware switching, 502
  - IGMP snooping, 505–506
  - IP addresses, 482–485
  - IP protocols, 491–498, 500–508
  - Layer 2 protocols, 504–505
  - MAC addresses, 485–486
  - MFIB, 504
  - MMLS, 503
  - monitoring IP, 512–516
  - reverse path forwarding, 486–488
- TrafficDirector application, 748
- trees
  - shared, 489–491
  - source, 488–491
- Trivial FTP (TFTP) packet loss, 102
- troubleshooting
  - backup/primary root bridges, 211
  - building loop-free networks, 200
  - Catalyst 6500 switches using SPAN, 735
  - Catalyst switches, 107
    - configuration commands, 109
    - connecting to a switch, 111
    - debug commands, impact and, 109
    - IP connectivity, 112
    - show and debug commands, 108
  - CEF-based MLS, 410
    - configuration, 415–418
    - methodology, 411–412
  - forwarding loops and black holes, 269
  - IP subnets, 279
  - L2 traceroute command
    - availability on Catalyst switches, 746
    - output from Cisco IOS-based switches, 747
  - Layer 2 loops, 286–292
  - preventing bridging loops, 199–200
  - STP, 273
    - duplex mismatch, 274
    - frame corruption, 275
    - inappropriate STP, 276
    - methodology, 277–279

- PortFast configuration errors, 276
- unidirectional link failures, 274
- trunking, 165
- VLANs, 144
  - communication issues, 145
  - private VLANs, 145, 148–149
  - slow throughput, 144
- VTP, 177
- trunking
  - limiting connections, 622
  - protocols (VTP), 165–175
  - troubleshooting, 165
  - VLANs, 152
    - configuration, 161–163
    - IEEE 802.1 Q, 155–158
    - ISL, 154
    - modes and methods, 160
    - multilayer switched networks, 153
    - protocols, 154
    - verifying configurations, 163–165
- trusting DSCP, 436
- tunneling (IEEE 802.1Q-in-Q tunneling), 159

## U

- UDLD (Unidirectional Link Detection), 255, 335–338
  - case study, 342
  - configuring, 338–339
  - protocols, 335
- UDP (User Datagram Protocol)
  - broadcast forwarding, 379
  - multicast traffic, 481
- unauthorized access, 77
- unicast, 480
  - filtering, 637
  - flooding, 638–639
  - suppression, 325
- Unidirectional Link Detection. *See* UDLD
- unidirectional links
  - failures, 274
  - Loop Guard, 270
- uninterruptible power supply (UPS), 601–602
- unshielded twisted-pair (UTP), 49
- updating software versions on Catalyst switches, 101–105

- uplink port support, 550
- UplinkFast, 258, 280
  - configuration exercise, 284
  - configuring, 259
- UPS (uninterruptible power supply), 601–602
- User Datagram Protocol (UDP)
  - broadcast forwarding, 379
  - multicast traffic, 481
- UTP (unshielded twisted-pair), 49

## V

- VACLs (VLAN access control lists), 642
  - Capture option, 743–744
  - configuring, 663–669
- validating DAI, 654–658
- values, priority, 765
- verifying, 141, 143
  - CEF-based MLS, 405
  - PortFast, 285–286
  - SSO, 542
  - STP
    - bridges, 244–247
    - configuration, 221–223
  - VLAN, 187–188
  - VTP, 176, 187–188
- versions, PIM, 496–497
- virtual LANs. *See* VLANs
- virtual MAC addresses, 573
- virtual private networks. *See* VPNs
- Virtual Routers, 8
- Virtual Switched Port Analyzer. *See* VSPAN
- VLAN access control lists (VACLs), 642, 139
- VLAN management policy servers (VMPSs), 135
- VLANs (Virtual LANs), 8, 129
  - Cisco metro solutions, 710
  - commands, 381
  - configuring, 138–141
    - private VLANs, 148–151, 188–189
    - verifying configuration, 141–143
  - deleting, 139
  - dynamic, 135
  - hopping attacks, 660–661
  - IDs, 156
  - implementing in campus networks, 132–133
  - inter-VLAN routing, 365–368
    - IP broadcast forwarding, 378–379
    - multilayer Catalyst switches, 368–370
    - router on a stick, 373–375
    - study tips, 380–381
    - switch virtual interface, 371–373
    - UDP broadcast forwarding, 379
    - verifying configuration, 376
  - load balancing, 231
  - private VLANs as security feature, 658
  - propagated, 622
  - PVST+, 216
  - ranges, 136
  - ranges and mappings, 158
  - service provider-managed VLANs, 159
  - static, 134
  - study tips, 177, 179–180
  - troubleshooting, 144
    - communication issues, 145
    - private VLANs, 145–149
    - slow throughput, 144
  - trunking, 152
    - configuration, 161–163
    - IEEE 802.1 Q, 155–158
    - ISL, 154
    - modes and methods, 160
    - multilayer switched networks, 153
    - protocols, 154
    - troubleshooting, 165
    - verifying configurations, 163–165
  - verifying, 187–188
  - voice, 598
- VMPSs (VLAN management policy servers), 135
- voice
  - applications, 596
  - Auto QoS, 463
- VoIP (voice over IP), 3
- VPNs (virtual private networks), 3
- VRRP (Virtual Router Redundancy Protocol), 8, 573
- VSPAN
  - Virtual Switch, 727
  - configuration, 732
  - configuring, 732
  - guidelines and restrictions, 730

VTP (VLAN Trunking Protocol), 165–166  
  advertisements, 168  
  authentication, 173  
  configuring, 173–175  
  modes of operation, 167  
  pruning, 169  
  troubleshooting, 177  
  verifying, 187–188  
  versions, 170–172  
vtp domain domain-name command, 184  
vtp mode command, 184  
vtp password command, 184  
vtp v2-mode command, 174  
VTP-transparent switches, 168  
VTYs, securing access to, 619  
vulnerabilities (SSH), 89

## W

---

warning banners, 620  
Wave Division Multiplexing (WDM), 714–715  
wavelengths (electromagnetic spectrum), 716  
WDM (Wave Division Multiplexing), 714–715  
web interface security, 621  
weighted random early detection (WRED), 458  
weighted round robin (WRR), 451  
WRED (weighted random early detection), 458  
write erase command, 94  
WRR (weighted round robin), 451–454  
WS-SVC-NAM-1, 748  
WS-SVC-NAM-2, 748  
WS-X6380-NAM, 748