

Index

Numerics

802.11 channels/protocols

- 802.11a, 6–7
- 802.11b, 7
- 802.11g, 4–7, 194
- 802.11x, 5
- Aironet 1300, 10, 21
- Aironet 1400, 21
- Aironet Series 350, 16
- Cisco 1000 Series Lightweight APs, 17
- Cisco 3200 Series, 30
- IP phones, 31

802.1x authentication/protocols

- Cisco Wireless EAP, 72
- configuring, 89–92, 114
- EAP
 - Windows*, 117–118
 - EAP FAST*, 75–76
 - EAP-SIM*, 120
 - EAP-TLS*, 71–72, 119
 - host-based EAP*, 116
 - LEAP*, 72, 115–116
 - PEAP*, 119
- port access, 69

A

AAA clients, 152

access control, 131, 135

access control lists (ACLs), 69

access points (APs)

- Aironet series
 - 1100*, 4–5
 - 1130AG*, 6–7
 - 1200*, 7–9
 - 1230AG*, 9
 - 1300*, 9, 11
 - 350*, 16
 - SWAN*, 8
 - websites*, 33
- antenna placement, 92–93
- authenticators, 58
- beacon periods, 196–197
- bridges, wireless, 19
- cabling, 85
- categorizing, 181
- channels, 11–15
- checking, 222
- Cisco 1000 Series Lightweight, 16–17
- comparing devices, 11, 16
- configuring for RADIUS
 - connection, 152
- connecting to network
 - access control*, 135
 - address management*, 133–134
- data configuration
 - beacon period*, 196–197
 - data rates*, 192–195
 - data retries*, 198
 - DTIM*, 196–197
 - fragmentation threshold*, 198–199
 - RTS threshold*, 197
- data transfer speeds, 11–15, 192–195

- defective, 222, 237
 - Encryption Manager, 147
 - Ethernet, 69
 - Ethernet port, 95
 - faulty, 222, 237
 - filtering
 - IP filtering, 144–147*
 - IP phones, 32*
 - MAC filtering, 141–143*
 - fire codes, 82
 - friendly APs, 181
 - honeypots, 156–157
 - IP filtering, 144–147
 - IP phones, 32
 - MAC filtering, 141–143
 - managed APs, 181
 - misconfigured, 237
 - network standards, 11–15
 - power settings, 185, 187
 - problems, 221–222
 - radios, 95
 - range, 11–15, 19, 212
 - remote-edge APs, 17
 - repeater/parent data rates, 95
 - repeaters,
 - data rates, 95*
 - configuring, 95–97*
 - using CLI, 97–98*
 - rogue APs, 58, 181–182
 - root radio, 95
 - security, 11–15
 - Security Encryption Manager, 154
 - settings, 93–94
 - signal strength, 224
 - site surveys, 59, 81
 - speed, 11–15
 - SWAN, 56
 - troubleshooting,
 - checking APs, 221–222*
 - checklist, 234–235*
 - tuning radio parameters
 - power tuning, 185*
 - radio tuning, 188*
 - unmanaged APs, 181
 - VoIP, 11
 - WEP keys, 67
 - wireless bridges, 19
 - WLAN controllers, 17–19
- accounting, 131**
- ACLs (access control lists), 69**
- ACM (Aironet Client Monitor), 102–104**
- active profiles, 107–108**
- ACU (Aironet Client Utility), 101–102**
- ad hoc mode, 111–112**
- adapters**
See clients, adapters
- addresses,**
IP, 125
MAC
 - attacking with, 69*
 - Campus Manager, 159*
 - filtering, 141–143, 227–228*management, 133–134
security, 125, 159, 141
- ad-hoc topology, 128**
- ADU (Aironet Desktop Utility), 82, 101–102, 201–202**
- AES (Advanced Encryption Standard), 78–79**
- AirMagnet, 217–218**
- Aironet**
Aironet Client Monitor (ACM), 102–104
Aironet Client Utility (ACU), 101–102
Aironet Desktop Utility (ADU), 82, 101–102, 201–202
- antennas
 - 1130AG, 6*
 - 1200, 8*
 - 1300, 20*
 - 1400, 21*
 - models, 38–41*
- bridges, 19–21
- client adapters
 - 5 GHz 802.11a, 26–27*
 - 350, 24*

- 802.11a/b/g, 25–26
 - comparing*, 27–29
- comparing devices, 11, 16
- extensions, 187
- GUIs, 5, 9
- series
 - 350, 16
 - 1100, 4–5
 - 1130AG, 6–7
 - 1200, 7
 - 1230AG, 9
 - 1300, 9–11, 19–21
 - 1400, 21
- Alert view, Perfmon, 206–208**
- alignment, antennas, 48**
- amplification, 52**
- antennas**
 - Aironet, 38–41
 - 1130AG, 6
 - 1200, 8
 - 1300, 20
 - 1400, 21
 - beam width, 36
 - bridging, 49
 - Cisco 1000 Lightweight Series APs, 17
 - configuring, 195
 - defective, 237
 - dipole antennas, 37
 - directional, 35
 - diversity
 - configuring multiple*, 42–43
 - general*, 35
 - optimal placement*, 43–45
 - FCC, 50–52
 - Fresnel zone, 242–244
 - gain, 36–37
 - interference, 47
 - isotropic, 37
 - legalities, 50–52
 - line-of-sight, 242
 - material-density effects, 243
 - models
 - Cisco 2.4 GHz*, 38–39
 - Cisco 2.4 GHz bridge*, 40
 - Cisco 5 GHz bridge*, 40
 - modes, 111
 - multipath distortion, 194
 - offices, 49
 - omnidirectional, 35
 - parabolic dish antennas, 35, 49
 - patch antennas, 35
 - placement, 46–47
 - poles, 242
 - radiation patterns, 48
 - specialized, 9
 - tech specs, 36–37
 - towers, 242
 - upgrading
 - adding*, 45–46
 - aligning*, 48
 - placing*, 46–47
 - warehouses, 48
 - websites, 52, 244
 - WLANs, 126–127
 - Yagi antennas, 35
- Application panel, CiscoWorks LMS, 162**
- APs**
 - See* access points
- association tests, 229**
- asynchronous transfer mode (ATM), 159**
- attenuation, 92**
- authentication,**
 - 802.1x
 - configuring*, 114
 - EAP, Windows*, 117–118
 - EAP-SIM*, 120
 - EAP-TLS*, 119
 - general*, 86–92, 131, 151
 - host-based EAP*, 116
 - LEAP*, 115–116
 - PEAP*, 119
 - ACLs, 69
 - authenticators, 58

- bit significance, 86–87
- Cisco Wireless EAP, 72
- CLI, 88
- client certificates, 76
- comparing methods, 76
- credentials, 77
- database, 76
- defining, 154
- EAP, 70
- EAP FAST, 75
- EAP-TLS, 71
- IEEE 802.1x, 68
- methods, 76
- open authentication, 114
- operating systems, 76
- passwords, 77
- PEAP, 73–74
- problems, 238
- RADIUS servers, 151
- roaming, 77
- security, 141
- Security Encryption Manager, 154
- server certificates, 76
- servers, 76
- shared key authentication, 114
- single sign-on, 77
- tests, 229
- WPA, 77–78, 149

auto re-site survey, 178

B

- backward compatibility, 4**
- bandwidth, WLANs, 124–125**
- beacon frames, 187, 196–197**
- beacon periods, 112, 196–197**
- beam width, antennas, 36**
- BPDUs (bridge protocol data units), 129**
- bridges**
 - Aironet 1300, 21
 - antennas, 40, 49
 - channels, 24
 - Cisco 1300, 242

- distance, 240
- networks, 242
 - Fresnel zone, 242–244*
 - line-of-sight, 242*
- operations band, 24
- ranges, 19, 22–23
- security, 23
- speeds, 23
- topologies, 129–130
- websites, 33
- wireless
 - Aironet 1300 series, 19–20*
 - Aironet 1400 series, 21*
 - comparing devices, 22–24*
 - network standards, 22*
- workgroup bridges, 20

broadcast storms, 238

bulk import, CiscoWorks LMS, 166

C

- cabling**
 - coaxial cable, 93
 - fire codes, 82
 - hardware problems, 240
 - installation issues, 241
 - signal loss, 93
- CAM (constantly awake mode), 109**
- Campus Manager, CiscoWorks LMS**
 - discovering devices, 164
 - collecting data, 166
 - feature, 159
 - tracking users, 167
- campus networks, 10**
- card tests, 229**
- CardBus client adapters, 25–26**
- Catalyst 6500 series switches, 30**
- CCKM (Cisco Centralized Key Management), 136**
- CCX (Cisco Compatible Extensions), 32–33, 132**
- ceiling panels, 82**
- CEM (Client Encryption Manager), 104**

- Centrino mobile technology, 32**
- certificates, 70**
- certifications**
 - websites, 65
 - WLAN Design Specialist, 62–63
 - WLAN Sales Specialist, 63–64
 - WLAN Support Specialist, 64–65
- channels**
 - 802.11, 125
 - 802.11b, 241
 - 802.11g, 240–241
 - APs, 11–15
 - bridges, 24
 - changing, 224–225
 - optimal
 - determining, 188*
 - tuning, 189, 192*
 - overlap, 131
 - topologies, 130–131
 - United States, 130
- Chart view, Perfmon, 204–206**
- Cisco 2.4 GHz antennas**
 - AIR-ANT1728, 38
 - AIR-ANT1729, 39
 - AIR-ANT2012, 39
 - AIR-ANT2410Y-R, 39
 - AIR-ANT3213, 38
 - AIR-ANT3549, 39
 - AIR-ANT4941, 38
 - AIR-ANT5959, 38
- Cisco 2.4 GHz bridge antennas**
 - AIR-ANT1949, 41
 - AIR-ANT24120, 41
 - AIR-ANT2414S-R, 41
 - AIR-ANT2506, 40
 - AIR-ANT3338, 41
- Cisco 5 GHz bridge antennas**
 - AIR-ANT58G10SSA-N, 40
 - AIR-ANT58G28SDA-N, 40
 - AIR-ANT58G9VOA-N, 40
- Cisco 1000 Series Lightweight AP, 16–17**
- Cisco 3200 series routers, 30**
- Cisco Aironet Client Utility Site**
- Survey Utility, 224**
- Cisco CallManager, 31**
- Cisco Centralized Key Management (CCKM), 136**
- Cisco Compatible Extensions (CCX), 32–33, 132**
- Cisco EAP, 115–116**
- Cisco Structured Wireless-Aware Network**
 - See SWAN*
- Cisco Wireless 7920, 32**
- Cisco Wireless 7920 IP Phone, 31–32**
- Cisco Wireless EAP, 72**
- Cisco Wireless Security Suite, 5**
- CiscoView, 160**
- CiscoWorks LMS (LAN Management Solution)**
 - adding devices, 165
 - application tasks, 167–169
 - bulk import, 166
 - Campus Manager
 - collecting data, 166*
 - tracking users, 167*
 - CiscoView, 160
 - Common Services, 160
 - configuring, 161
 - DCA, 165
 - Device Troubleshooting panel, 162
 - DFM, 160, 168
 - discovering devices, 164
 - home page, 161
 - installing, 163–164
 - Internetwork Performance Monitor, 168–169
 - Management Server, 160
 - Product Updates panel, 163
 - Resources panel, 162
 - RME, 160, 167
 - upgrading, 163–164
 - websites, 169
- CiscoWorks Wireless LAN Solution Engine**
 - See WLSE*
- classified information, 79**

class-of-service (CoS) values, 214**clients**

adapters

- Aironet 350, 24*
- Aironet 5 GHz 802.11a, 26–27*
- Aironet 802.11a/b/g, 25–26*
- CardBus, 25–26*
- comparing devices, 27–29*
- form factors, 27*
- operations band, 29*
- PCI, 25–26*
- ranges, 28*
- security, 29*
- speed, 29*
- standards, 27*
- websites, 33*
- wireless medium, 29*

Aironet extensions, 187

authentication problems, 238

cards, 237

certificates, 76

connection problems, 221

configuring

- advanced ad hoc parameters, 111–112*
- advanced infrastructure, 110–111*
- changing channels, 223–225*
- checking SSID, 225*
- DHCP misconfiguration, 227*
- IP address duplication, 226–227*
- MAC filtering, 227–228*
- modes, 110*
- profiles, 106–107*
- security, 112–113*
- selecting active profiles, 107–108*
- setting system parameters, 108–109*
- signal strength, 223–224*
- WEP keys, 113–114, 225–226*
- WPA, 226*

conflict-resolution tools, 228–234

connection problems, 237

power settings, 187

site surveys, 81

tracking, 136

troubleshooting

- APs, 222*
- checklist, 234–235*
- prioritizing connections, 230–231*
- tools, 228–229*

utilities

- ACM, 102–104*
- ACU/ADU, 101–102*
- CEM, 104*
- LSM, 104*

websites, 235

Client Encryption Manager (CEM), 104**coaxial cable, 93****commands**

- configuring APs for RADIUS connection, 152
- enabling traps, 68
- defining EAP authentication, 155
- defining WEP encryption, 154
- ping, 222

Common Services panel, CiscoWorks LMS, 162**Common Services, CiscoWorks, 160****concrete, impacting signals, 243****conflict resolution, 228–234****connections**

- problems, 237
- prioritizing, 230–231

connectors, 51**constantly awake mode (CAM), 109****Content Services Gateways (CSG), 60****controllers, 17–19****CoS (class-of-service) values, 214****counters, alert, 206****CRC (cyclic redundancy checks), 78****credentials, 77****credentials, WLSE, 174****CSG (Content Services Gateway), 60****cyclic redundancy checks, 78**

D**dashboards**

- Sniffer Wireless, 219
- WLSE, 171–173

Data Encryption Standard (DES), 79**data**

- transfer rates
 - 802.11b vs. 802.11g*, 4
 - APs*, 11–15, 192–195
 - bridges*, 23
 - client adapters*, 29
 - repeater/parent APs*, 95
 - throughput problems*, 238–240
- transfer retries, 198

database authentication, 76**DCA (Device and Credential Admin), 165****decibel scale, 36–37, 187****decryption dictionaries, 68****defense agencies, 30****delivery traffic indication messages (DTIMs), 196–197****design**

- See* network design

Dell, 32**DES (Data Encryption Standard), 79****Device and Credential Admin (DCA), CiscoWorks LMS, 165****Device Troubleshooting panel, CiscoWorks LMS, 162****DFM (Device Fault Manager), 160, 168****DHCP (Dynamic Host Configuration Protocol)**

- misconfiguration, 227
- relay, 134
- servers, 133

dipole antennas, 37**directional antennas**

- alignment, 48
- function, 35
- remote sites, 49

discovery

- devices, CiscoWorks LMS, 164
- network, 105

distance, bridges, 240**distortion, multipath, 41, 194****diversity antennas**

- configuring multiple, 42–43
- function, 35
- optimal placement, 43–45

driver installation tests, 229**DTIMs (delivery traffic indication messages), 196–197****dual mode, 7****E****EAP (Extensible Authentication Protocol)**

- Aironet 1130AG, 7
- Cisco Wireless EAP, 72
- Cisco Wireless Security Suite, 5
- EAP FAST, 75–76
- EAP-GTC (EAP-Generic Token Card), 90
- EAP-MD5 (Message Digest 5), 5, 114
- EAP-SIM (EAP-Subscriber Identity Module), 90, 114, 120
- EAP-TLS (EAP with Transport Layer Security), 71–72, 90, 114, 119
- EAP-TTLS (EAP-Tunneled TLS), 90
- LEAP (Lightweight EAP), 72, 90, 115–116
- PEAP (Protected EAP), 73–75, 90, 114, 119
- Windows, 117–118

encryption

- AES, 78–79
- bit significance, 86–87
- CLI, 88
- DES, 79
- RC4, 78
- strong encryption, 79
- WPA, 78, 147

Encryption Manager, WPA, 147

Ethernet

- APs, 69
- devices, 20
- ports, 95
- switches, 69

Express Security Set-Up, 93–94**Extensible Authentication Protocol**

See EAP

F**Fast PSP (Power Save Protocol), 109****fast, secure roaming, 136****Fault Mediator, MWC, 60–61****FCC (Federal Communications****Commission)**

- amplification, 52
- power regulations, 51
- right antenna/right device, 50–51
- Rule 04-165, 50–51

fences, impacting signals, 243**filtering**

- IP filtering, 144, 146–147
- MAC addresses, 69
- MAC filtering, 141–143, 227–228

fire codes, 82**firmware, 238–239****form factors, client adapters, 27****fragmentation, 198–199****frame counters, 78****frequency**

- determining optimal, 188
- general, 240
- tuning optimal, 189, 192

Fresnel zone, 242–244**friendly APs, 181****G–H****gain, antennas, 36–37****Gateway GPRS Support Nodes
(GGSNs), 60****GUIs**

- Aironet 1100, 5
- Aironet 1200, 9

HA (home agents), 60**hardware problems**

- cable installation, 241
- cable type, 240
- configuration, 239–240
- firmware, 238–239
- signal problems, 240

Hewlett Packard, 32**home agents (HA), 60****homeland security, 30****honeypots, 156–157****host-based EAP, 116****hot standby, 5****hotspots, 10****HTTP mode, 161****I****I-beams, 47****ICMP, 160****IEEE 802.1x authentication,**

- Cisco Wireless EAP, 72
- EAP, 70–71
- EAP FAST, 75–76
- EAP-TLS, 71–72
- Lightweight EAP, 72
- port access, 68–69

infrastructure topology, 128–129**initialization vectors (IVs), 78****integration, wired/wireless LANs,
131–132****Intel, 32****interference,**

- antennas, 47
- detecting, 179
- effects, 59, 85, 224, 238–240
- microwave ovens, 243

**Internet Control Message Protocol
(ICMP), 160****Internetwork Performance Monitor,**

CiscoWorks LMS, 168–169
interoperability, 132
inventories, WLSE, 175
IP (Internet Protocol)
 addresses
 DHCP relay, 134
 DHCP servers, 133
 duplication, 226–227
 security, 125, 159, 141
 filtering, 144–147
 phones
 Cisco Wireless 7920, 31–32
 websites, 33
IVs (initialization vectors), 78

K–L

Kerberos, 70
kilomicroseconds, 196

LANs
 LAN emulation, 159
 LAN Port Access Control framework,
 69
 wired LANs, integrating, 3, 131–132
law, antennas, 50–52
Layer 2 networks, 159
LEAP (Lightweight EAP),
72, 90, 115–116
Lightweight Access Point Protocol
(LWAPP), 17
Linksys devices, 3
load balancing, 5
Log view, Perfmon, 208, 211
logging, 210
loops, 129
LWAPP (Lightweight Access Point
Protocol), 17

M

MAC (Media Access Control)
 addresses
 attacking with, 69
 Campus Manager, 159
 security, 141
 filtering, 141–143, 227–228
magnetic resonance imaging (MRI)
devices, 47
managed APs, 181
Management Information Base
(MIB), 160
Management Server, CiscoWorks,
160
man-in-the-middle attacks, 71
mesh fences, impacting signals, 243
message integrity checks (MICs), 78
metal, impacting signals, 243
microwave
 lighting, 47
 ovens, 47, 243
 paint dryers, 47
mid-span devices, 81
milliwatts, versus decibels, 187
misconfigurations, 237–238
mobility
 networks, 30
 routers, 30
 services, 59
 Mobile Wireless Center (WMC),
 59–60, 65
 users, 10, 135
modes
 ad hoc mode, 110–112
 antenna modes, 111
 ATM, 159
 dual mode, 7
 HTTP mode, 161
 infrastructure mode, 110
 power save mode, 109
 trimode, 7
MRI (magnetic resonance imaging)
devices, 47

multipath distortion, 41, 194
MWC (Mobile Wireless Center)
 Fault Mediator, 60–61
 Performance Mediator, 60–62
 Provisioning Manager, 60–61
 websites, 65

N–O

NetStumbler, 217
NetWare Directory Services login, 159
network design
 antennas, 126–127
 checklist, 127
 determining bandwidth, 124–125
 establishing size, 123–124
 organizational needs, 125
 physical constraints, 126
network discovery, 105
network tests, 229
network tuning
 Perfmon, 201–203
 Alert view, 206–208
 Chart view, 204–206
 Log view, 208, 211
 Report view, 211
 Qos, 211–215
 signal strength, 201–202
 third-party tools
 AirMagnet, 216–218
 NetStumbler, 217
 Sniffer Wireless, 218–219
nomadic users, 10, 135
NT login, 159

offices, antennas, 49
omnidirectional antennas
 alignment, 48
 dipole antennas, 37
 function, 35
 gain, 51
 offices, 49
 warehouses, 48

one-time passwords (OTPs), 70
open authentication, 114
operations band
 bridges, 24
 client adapters, 29
organizational needs, WLANs, 125
OTPs (one-time passwords), 70
outdoor access, 10
overlap, channels, 131

P

PAC (Protected Access Credential) files, 75
Packet Data Service Nodes (PDSNs), 60
packet services, 60
paper, impacting signals, 243
parabolic dish antennas, 35, 49
passwords, 77–78
patch antennas, 35
path trace tool, 159
PCI (Peripheral Component Interconnect), client adapters, 25–26
PCMCIA (Personal Computer Memory Card International) slots, 24
PDSNs (Packet Data Service Nodes), 60
PEAP (Protected EAP), 73–75, 90, 114, 119
Perfmon (Performance Monitor)
 Alert view, 206–208
 Chart view, 204–206
 feature, 203
 Log view, 208, 211
 Report view, 211
Performance Mediator, MWC, 60–62
Performance Monitor
See Perfmon
performance problems
 authentication/re-authentication, 238

- bridged networks, 242
 - Fresnel zone*, 242–244
 - line-of-sight*, 242
 - connections, 237
 - hardware issues, 238
 - cable installation*, 241
 - cable type*, 240
 - configuration*, 239–240
 - firmware*, 238–239
 - signal problems*, 240
 - slow throughput, 241
 - Peripheral Component Interconnect (PCI), client adapters, 24**
 - Personal Computer Memory Card International (PCMCIA) slots, 24**
 - physical constraints, WLANs, 126**
 - ping command, 222**
 - PoE (Power over Ethernet), 81, 85, 139**
 - point-to-multipoint bridging, antennas, 49**
 - point-to-point bridging, antennas, 49**
 - poles, antennas, 242**
 - policies, 215**
 - polling, ICMP, 160**
 - portability, 135**
 - power**
 - Aironet extensions, 187
 - general, 81, 85
 - legal regulations, 51–52
 - power injectors, 85**
 - Power over Ethernet (PoE), 81, 85, 139**
 - power save modes, 109**
 - Power Save Protocol (PSP), 109**
 - power settings, 185–187**
 - privacy, 131**
 - Product Updates panel, CiscoWorks LMS, 163**
 - profiles**
 - creating, 106–107
 - selecting active profiles, 107–108
 - Protected Access Credential (PAC) files, 75**
 - Protected EAP (PEAP), 73–75, 90, 114, 119**
 - Provisioning Manager, MWC, 60–61**
 - PSP (Power Save Protocol), 109**
 - public key authentication, 70**
 - public safety, 30**
-
- Q – R**
 - QoS (quality of service)**
 - configuring, 211–215
 - overview, 5, 212
 - policies, 215
 - radar, 47**
 - radiation**
 - characteristics, 43
 - patterns, 48
 - Radio Manager**
 - auto re-site survey, 178
 - detecting interference, 179
 - feature, 176
 - self healing, 178–179
 - radios**
 - 802.11a, 6
 - 802.11g, 6, 194
 - Aironet 1100, 4
 - Aironet 1130AG, 6
 - Aironet 1200, 7
 - Aironet 1230AG, 9
 - firmware problems, 238–239
 - parameters
 - power tuning*, 185–187
 - radio tuning*, 188–192
 - root radios, 95
 - tests, 229
 - WLSE, 176–177
 - RADIUS (Remote Authentication Dial-In User Service) servers**
 - 802.1x authentication, 89, 151
 - Aironet series, 21
 - APs, 152
 - configuring, 152

- EAP-TLS, 71
 - misconfigured, 237
 - range**
 - antennas, 46
 - APs, 11–15
 - bridges, 22–23
 - client adapters, 28
 - general, 19, 212
 - throughput, 238
 - RC4 encryption, 68, 78**
 - re-authentication problems, 238**
 - redundancy, 129**
 - relay, DHCP, 134**
 - Remote Authentication Dial-In User Service servers**
 - See* RADIUS
 - remote users, 135**
 - See also* mobility
 - repeaters, 95–98**
 - replay attacks, 78**
 - Report view, Perfmon, 211**
 - Request to Send (RTS) threshold, 197**
 - Resource Manager Essentials (RME), 160, 167**
 - Resources panel, CiscoWorks LMS, 162**
 - retries, data, 198**
 - RF (radio frequency)**
 - management, 58
 - reflective surfaces, 42
 - RME (Resource Manager Essentials), 160, 167**
 - roaming**
 - authentication, 77
 - fast, secure, 136
 - overview, 135
 - SWAN, 57–58
 - rogue APs, 181**
 - root radios, 95**
 - routers**
 - Cisco 3200 Series, 30
 - DHCP relay, 134
 - mobile, 30
 - public safety, 30
 - SWAN, 56
 - vehicles, 30
 - websites, 33
 - wireless, 30
 - RTS threshold, 197**
 - Rule 04-165, 50–51**
- ## S
- Secure Sockets Layer (SSL), 68**
 - security**
 - Aironet 1130AG, 7
 - APs, 11–15
 - authentication, 141
 - bridges, 23
 - Cisco Wireless Security Suite, 5
 - client adapters, 29
 - configuring, 112–113
 - WEP keys, 113–114*
 - Express Security Set-Up, 93–94
 - filtering, 141
 - homeland security, 30
 - honeypots, 156–157
 - integrating wired/wireless LANs, 131
 - IP addresses, 141
 - IVs, 78
 - LWAPP, 17
 - MAC addresses, 141
 - websites, 79
 - WEP keys, 67–68
 - WLSE
 - detecting/mitigating rogue APs, 181–182*
 - managing, 179–180*
 - WPA, 147, 149, 151
 - Security Encryption Manager, 154**
 - self healing, Radio Manager, 178–179**
 - server certificates, 76**
 - Service Selections Gateways (SSGs), 60**
 - service set identifiers (SSIDs), 109, 225, 240**
 - shared key authentication, 114**

signals

- directional antennas, 35
- diversity
 - configuring multiple antennas, 42–43*
 - optimal antenna placement, 43–45*
 - overview, 41*
- diversity antennas, 35
- loss, 93
- materials impacting, 243
- omnidirectional antennas, 35
- problems, 240
- strength, 201–202, 223–224

signal-to-noise ratio (SNR), 84**Simple Network Management****Protocol (SNMP), 160****single sign-on, 77****site surveys**

- analyzing site data, 84
- analyzing sites, 85
- AP location, 81
- assisted, 84
- CiscoWorks Wireless LAN Solution Engine, 84
- manual, 82–84
- overview, 59, 81–82, 241
- performing, 82–84
- signal strength, 223
- Site Survey tool, 82, 202

size, WLANs, 123–124**smart cards, 70****Sniffer Wireless, 218–219****SNMP (Simple Network Management Protocol), 160****SNR (signal-to-noise ratio), 84****spanning-tree topology, 129****spectrum analyzers, 85****speeds**

- 802.11b vs. 802.11g, 4
- APs, 11–15, 192–195
- bridges, 23
- client adapters, 29
- repeater/parent APs, 95
- throughput problems, 238

SSGs (Service Selections Gateways), 60**SSIDs (service set identifiers), 109, 225, 240****SSL (Secure Sockets Layer), 68****standards**

- APs, 11–15
- bridges, 22
- client adapters, 27
- IEEE 802.11
 - 802.11a, 6–7*
 - 802.11b, 7*
 - 802.11g, 4–7, 194*
 - 802.11x, 5*
 - Aironet 1300, 10, 21*
 - Aironet 1400, 21*
 - Aironet Series 350, 16*
 - Cisco 1000 Series Lightweight APs, 17*
 - Cisco 3200 Series, 30*
 - IP phones, 31*
- IEEE 802.1x
 - Cisco Wireless EAP, 72*
 - configuring, 114*
 - EAP, 70–71, 116–118*
 - EAP FAST, 75–76*
 - EAP-SIM, 120*
 - EAP-TLS, 71–72, 119*
 - LEAP, 72, 115–116*
 - port access, 68–69*
 - PEAP, 119*

vendor interoperability, 132

strong encryption, 79**SWAN (Structured Wireless-Aware Network)**

- Aironet 1230AG, 9
- overview, 55–59
- RF management, 58
- roaming, 57–58
- websites, 65
- WLSE, 171, 182
- WLSM, 30

switches

- Catalyst 6500 series, 30

- Ethernet, 69
- SWAN, 56
- System Monitor**
 - See Perfmon
- system parameters, 108–109**

T

- Temporal Key Integrity Protocol (TKIP), 77**
- throughput, 95, 238, 241**
- token cards, 70**
- topologies**
 - bridges, 129–130
 - channels, 130–131
 - spanning-tree topology, 129
 - WLAN, 128–129
- ToS (type-of-service) values, 213**
- Toshiba, 32**
- towers, antennas, 242**
- transport agencies, 30**
- transport layer security, 73**
- trimode, 7**
- troubleshooting**
 - 802.1x authentication, 226
 - APs, 221–222
 - checklist, 234–235
 - client configuration
 - changing channels, 224–225*
 - checking SSIDs, 225*
 - DHCP misconfiguration, 227*
 - IP address duplication, 226–227*
 - MAC filtering, 227–228*
 - signal strength, 223–224*
 - WEP keys, 225–226*
 - WPA, 226*
 - DHCP misconfiguration, 227
 - interference, 224
 - IP address duplication, 226–227
 - MAC filtering, 227–228
 - prioritizing connections, 230–231
 - Provisioning Manager, 61

- tools
 - resource conflict, 231, 234*
 - Troubleshooting Utility, 229*
- Troubleshooting Utility, 229**
- tuning, network**
 - See also Perfmon
 - QoS, 211–215
 - signal strength, 201–202
 - third-party tools, 216
 - AirMagnet, 217–218*
 - NetStumbler, 217*
 - Sniffer Wireless, 218–219*
- type-of-service (ToS) values, 213**

U–V

- UNII3 (Unlicensed National Information Infrastructure) band, 51**
- unmanaged APs, 181**
- vinyl, impacting signals, 243**
- virtual LANs (VLANS), 5, 131–132, 159**

W–Y

- wake duration, 112**
- warehouses, antennas, 48**
- WDS (Wireless Domain Services), 57, 136–139**
- websites**
 - AirMagnet, 219
 - antennas
 - Aironet, 33*
 - antennae calculation spreadsheet, 244*
 - Cisco, 52*
 - FCC rules, 52*
 - APs/bridges, 33
 - CCX, 33
 - certifications, 65
 - Cisco training courses, 62
 - CiscoWorks LMS, 169

- client adapters, 33
- client connection troubleshooting, 235
- Fresnel zone calculator, 244
- IP phones, 33
- MWC, 65
- National Institute of Standards and Technology, 79
- NetStumbler, 219
- PoE, 139
- Practically Networked, 235
- Radiolabs, 52
- security, 79
- site survey guides, 99
- Sniffer Wireless, 219
- SWAN, 65
- Tech Republic, 139
- training programs, 65
- WaveStumbler, 219
- Wi-Fi Alliance, 79, 235
- Window XP troubleshooting, 235
- wireless devices, 33
- WLAN Services Module, 33
- WEP (Wired Equivalent Privacy)**
 - authentication/encryption, 86
 - bit significance, 86–87
 - CEM, 104
 - CLI, 88
 - commands, 88
 - configuring, 113–114
 - CRCs, 78
 - keys, 67–68, 141, 225–226
 - timeouts, 72
 - WPA, versus, 77
- Wi-Fi Protected Access**
 - See* WPA
- wired LANs, integrating, 131–132**
- wireless**
 - bridges, 19–24
 - certifications
 - websites*, 65
 - WLAN Design Specialist*, 62–63
 - WLAN Sales Specialist*, 63–64
 - WLAN Support Specialist*, 64–65
 - medium, 29
 - routers, 30
 - See also* wireless LANs
- Wireless Domain Services (WDS), 57, 136–139**
- Wireless LAN Services Module (WLSM), 30**
- Wireless LAN Solution Engine (WLSE), 56, 171**
- wireless LANs (WLANs)**
 - APs, 3
 - controllers, 17–19, 84
 - design
 - antennas*, 126–127
 - checklist*, 127
 - determining bandwidth*, 124–125
 - establishing size*, 123–124
 - organizational needs*, 125
 - physical constraints*, 126
 - encryption, 79
 - integrating wired LANs
 - managing*, 171–173
 - configuring devices*, 174–175
 - overview*, 131–132
 - performance problems
 - authentication/re-authentication*, 238
 - bridged networks*, 242
 - cable installation*, 241
 - cable type*, 240
 - configuration, hardware*, 239–240
 - connections*, 237
 - firmware*, 238–239
 - Fresnel zone*, 242, 244
 - hardware issues*, 238
 - line-of-sight bridging*, 242
 - signals*, 240
 - slow throughput*, 241
 - special needs, 125–126
 - third-party tools
 - AirMagnet*, 216–217
 - NetStumbler*, 217
 - Sniffer Wireless*, 218
 - topologies, 128–129

- WLAN Design Specialist
 - certification, 62–63
- WLAN Sales Specialist certification, 63–64
- WLAN Services Modules, 33
- WLAN Support Specialist
 - certification, 64–65
- WLSM, 30
- WLSE (CiscoWorks Wireless LAN Solution Engine)**
 - credentials, 174
 - dashboard, 171–173
 - feature, 84, 188
 - inventories, 175
 - managing radios, 176–177
 - managing WLANs, 173–175
 - Radio Manager, 176–179
 - security
 - detecting/mitigating rogue APs, 181–182*
 - managing, 179–180*
- WLSM (Wireless LAN Services Module), 30**
- WMC (Mobile Wireless Center), 59–60, 65**
- wood, impacting signals, 243**
- workgroup bridges, 20**
- WPA (Wi-Fi Protected Access)**
 - Aironet 1130AG, 7
 - authentication, 77, 149
 - CCX, 32
 - Encryption Manager, 147
 - MIC, 78
 - overview, 7, 77–78, 90, 147–151, 226
 - WPA2, 78
- WSLE (Wireless Solutions Engine), 56**
- Yagi antennas, 35**