
Symbols

- *69, 17
- μ-law, 9, 151
 - converting to a-law, 10

Numerics

- 3PCCs (third-party call controllers), 283
- 23B+D, 68
- 64 kbps PCM, 9
- 800 call queries, example, 113–114
- 800 databases, 84
- 800 number services, 122
- 802.1x device authentication, 229–230
- 900 number services, 122

A

- AAA, 208–209
- access control lists. *See* ACLs
- access protocols, ISDN, 64
 - access interfaces, 66–68
 - call disconnect, 73
 - call setup, 71–72
 - L2/L3 specifications, 68–69
 - Q.931 messages, 69–71
 - services, 65
 - supplementary services, 65
- accessing Centrex services, 121
- accounting, 208
 - RADIUS, Cisco SPS interface, 215–217
- accumulated noise, 8
- ACD (automatic call distribution), 121
- ACK requests, 272
- acknowledgments, 199
- ACLs (access control lists), 184

- ACM (Address Complete Message), 16
- adaptive differential pulse code modulation (ADPCM), 151
- added number (POTS), 118
- address signaling
 - Bell System MF method, 57–58
 - CCITT No. 5 method, 60
 - service circuits, 55
- address translation, H.323, 248
- addressing
 - data link layer, 134
 - SIP, 271–272
- admission control
 - H.323, 248
 - RAS signaling, 253
- ADPCM (adaptive differential pulse code modulation), 151
- advanced call control commands (MGCP), 304
- advanced enterprise applications, 365–369
- Advanced Intelligent Network (AIN), 324
- AH (Authentication Header), 226
- AHT (average handle time), erlangs, 337
- AIN (Advanced Intelligent Network), 324
- a-law, 9, 151
- ALG (Application-Layer Gateways), 236
- A-links, 87
 - SS7 signaling traffic termination, 330
- Allow header (SIP), 292
- AMA (Automatic Messaging Accounting) records, 210
- analog signaling, 7
 - accumulated noise, 8
 - line noise, 7
 - lost tones, 11
 - PCM (pulse code modulation), 149
 - sampling, 149

analog trunks
R2 signaling, 61–62
supervision signaling, 56
TASI, CCITT No. 5 signaling, 58–59

ANFs (additional network features), QSIG, 74–75

ANM (Answer Message), 16

announcements, service circuits, 55

AORs, 285

APIs (application programming interfaces), VSC, 332

application layer (OSI Reference model), 130
networking protocols, 30

applications
enabled on packet voice network
architecture, 325
IP phones, 354
soft phone, 354
VSC, 332

architecture
OTP, 323
call-control plane, 324
packet voice networks, H.323 clients, 329
QSIG, 74

ARP (Address Resolution Protocol), IP network infrastructure, protecting, 231–232

ARS (Automatic Route Selection), 43

ASEs (Application Service Element), 110

ASR (application-specific routing), 249

associated signaling, 85

asymmetric keys, 222–223

ATIS (Alliance for Telecommunications Industry Solutions), 211

attributes of QSIG, 73

AUCX (AuditConnection) command, 309

audio codecs, H.323, 246

audiographics conferencing, 246

AUEP (AuditEndpoint) command, 308

authentication, 208
802.1x, 229–230
certificates, 224
digital signatures, 223
IPsec, 226
public-key cryptography, 222
asymmetric keys, 222–223
certificates, 224
digital signatures, 223
IPsec, 226
SRTP protocol, 227
TLS protocol, 224–225

RADIUS, 209–210
shared-key, 222

authenticity as security requirement, 221

authorization, 123, 208

automatic call distribution (ACD),

automatic callback, 17
CLASS, 119

automatic recall (CLASS), 119

availability, presence service, 297
related SIP extensions, 298

average rate (CAR), 188

B

B-links, 87

B channel, 12

B2BUA, server mode operation, 283–284

backbone, 197
high-speed transport, 197–198
routing protocols, 139

backbone QoS, 200

backhaul, 343

Backward Indicator Bits (BIBs), 92

backward messages, H.225, 254

Backward Sequence Number (BSN), 92**backward signaling**

- Bell System MF, 56
- inter-register signals, 64

bandwidth

- bursty protocols, 133
- wasted, 157

bandwidth consumption, IP Tax, 172**bandwidth control**

- H.323, 248
- RAS, 253

basic call control commands (MGCP), 303**basic MGCP call flow, 311–313****basic services, ISUP, 105****bearer, 324****bearer channel, 11–12****bearer control plane (Cisco Packet Telephony architecture), 324****bearer services, ISDN, 65****BECN-based throttling, 193****Bell, Alexander Graham, 5****Bell System MF signaling, 55**

- address signaling, 57–58
- digital trunks, 57
- supervision signals, 55–57

Bellcore (Bell Communications Research), 118**BGP (Border Gateway Protocol), 138****BIBs (Backward Indicator Bits), 92****billing**

- AMA records, 210
- CDRs, 210
- Cisco SPS case study, 213–217
- long distance services, 123
- mediation services, 218–219

bits, robbing, 57**blacklists, 216****blocking, 17, 194****Border Gateway Protocol (BGP), 138****BOWIE.net (case study), 356–357****BPDU Guard, protecting IP network infrastructure, 232–233****BRI (Basic Rate Interface), 11–12**

- reference points, 66–67

bridge links, 87**bridging, 132–134****broadcast packets, 133****BSN (Backward Sequence Number), 92****BT (British Telecom), E&M signaling, 50**

- Type I, 51
- Type II, 52
- Type III, 52
- Type IV, 53
- Type V, 54

burst size, defining, 188**bursty protocols, 133****business lines, 37–38****business services, 119**

- call centers, 121–122
- Centrex, 121

- Virtual Private Voice Networks, 120

busy-flash signals, 59**busy signal, automatic callback, 17****BYE requests, 272****C****C-links, 87****C reference point (QSIG), 74****cable headend, packet voice network architecture, 328****cabling**

- local loop, 10
- twisted copper pair, 11

calculating

- erlangs, 337
- packet fragmentation size, 194

call agents, 302**PGW2200, 326**

- CDRs, 341*
- check-pointing, 338*
- connection control, 331*
- core capabilities, 327*
- implementing, 337*
- inter-PGW2200 signaling, 330*
- NANP support, 334–336*
- optional elements, 327*
- required elements, 326*
- services control, 331*
- signaling termination, 329–330*
- supported protocols, 332*
- third-party application development tools, 332*
- XE, 333–334*

call blocking, 17**call centers, 121–122**

- call control, 351–353**
 - H.225 signaling, 254, 257
 - H.323, call-flow, 24–27
 - MGCP, 27
 - SGCP, 27
 - SIP, 29
- call control messages**
 - ISUP, 108–109
 - Q.931, 69–71
- call control plane, 31**
 - Cisco Packet Telephony architecture, 324
- call flow**
 - H.323, 260–262
 - PSTN, 15–16
 - comparing with IP, 164–166*
- call forwarding, 17**
 - POTS, 118
- call handling, Centrex, 121**
- Call Proceeding messages, 254**
- call return, 17**
- call screening (CLASS), 119**
- call setup**
 - ISUP, 106–107
 - QSIG, 76
- call waiting, 17**
 - POTS, 118
- caller/callee preferences (SIP), 293**
- calling cards, 17, 123**
 - prepaid, BOWIE.net case study, 356–358
- calling line ID blocking, 17**
- calling number blocking (CLASS), 119**
- calls, 303**
- CAM table overflow, protecting IP network infrastructure, 232**
- CANCEL requests, 272**
- Capability Exchange (H.245), 257**
- CAR (committed access rate), 187–188**
- CAS (channel-associated signaling), 50, 54**
 - address signaling, service circuits, 55
 - Bell System MF signaling, 55
 - address signaling, 57–58*
 - supervision signaling, 55–56*
 - CCITT No. 5 signaling, 58
 - address signaling, 60*
 - supervision signaling, 59*
 - R1 signaling, 60
 - R2 signaling, 60–61
 - inter-register signaling, 63–64*
 - supervision signaling, 61–62*
 - signaling traffic termination, 330
 - supervisions signals, 55
- case studies, 356–357**
 - Cisco SPS and billing, 213–218
- CBB (changeback buffer), 102**
- CBD (changeback declaration), 102**
- CB-WFQ (Class-Based Weighted Fair Queuing), 179**
- CC (Country Code), 19**
- CCITT No. 5 signaling, 58**
 - address signaling, 60
 - supervision signaling, 59
- CCS (common channel signaling), 49–50**
- CDRs (call detail records), 210, 341**
 - creation of
 - IPDR-based approach, 212*
 - OSP-based approach, 211*
 - RADIUS-based approach, 212*
 - telco approach, 210*
- CELP (code excited linear prediction compression), 152**
- central office switches, trunks, 10**
- centralized operator, 6**
- Centrex, 38–39, 121**
- certificates, 224**
- channel-associated signaling. See CAS**
- channels, ISDN, 11**
- check-pointing, 337**
 - between PGW2200s, 338
- CID (session context identifier), 174**
- circuit-switched long distance, 17**
- circuit switching, comparing to packet switching, 21**
- circuits. See also trunks**
 - dedicated, 11
 - glare, 13
- Cisco IP Phones, 365**
- Cisco MeetingPlace, 366–367**
- Cisco Packet Telephony architecture, 323–324**
- Cisco Port Security feature, protecting IP network infrastructure, 232**
- Cisco SPS**
 - billing, case study, 213–218
 - RADIUS interface, 215–217
- CLASS (Custom Local Area Signaling Services), 14**
 - custom features, 17
 - POTS, 118–119
- class 4 switches, 11**

- class 5 switches, 10**
- Class A networks, 135**
- Class B networks, 135**
- Class C networks, 135**
- Class D addresses, 136**
- Class E addresses, 136**
- classifying packets, 175, 180–184**
- clearing IP Precedence bits, 182**
- CLECs (Competitive LECs)**
 - Centrex lines, 38
 - simple business lines, 37
- click-to-dial applications, 369**
- COA (changeover acknowledgment), 101**
- codecs**
 - LBC, 152
 - MOS testing, 152–153
 - source codecs, 151
 - waveform codecs, 151
 - wideband, 370
- collaboration tools, 366–367**
- combined linksets, 88**
- commands**
 - fair-queue, 177
 - H.248-related, 317
 - ip rsvp bandwidth, 185
 - random-detect, 200
- commands (MGCP)**
 - advanced call control
 - NTFY (Notification)*, 308
 - RQNT (NotificationRequest)*, 305–307
 - basic call control
 - CRCX (CreateConnection)*, 304
 - DLCX (DeleteConnection)*, 305
 - MDCX (ModifyConnection)*, 305
 - management
 - AUCX (AuditConnection)*, 309
 - AUEP (AuditEndpoint)*, 308
 - EPCF (EndpointConfiguration)*, 310
 - RSIP (RestartIn-Progress)*, 309
- common channel signaling. See CCS**
- Common Object Request Broker Architecture. See CORBA**
- communication, states of presence, 367**
- comparing**
 - circuit and packet switching, 21
 - GTS and FRTS, 190
 - jitter and total delay, 148
 - meshed and hierarchical networks, 11
 - MF and DTMF, 14
 - PSTN and ET, 36–37
 - routed and routing protocols, 137
 - traffic-regulation tools, 187
- compression**
 - ADPCM, 151
 - CELP, 152
 - CID, 174
 - cRTP, 173–174
 - enabling, 174–175*
 - G.723.1, 152
 - need for, 175
 - tandem-compression, 159
 - waveform codecs, 151
- concealment strategy, 156**
- configuring**
 - CAR, 188–189
 - echo cancellation, 155
 - serial interfaces, MTU, 196
- conform actions, 187–188**
- congestion, onset of congestion alerts, 101**
- congestion avoidance**
 - TCP, flow control, 199
 - WRED, 199–200
- congestive-discard-threshold parameter (fair-queue command), 177**
- Connect messages, 255**
- connection control on PGW2200, 331**
- connectionless services, SCCP, 102–103**
- connection-oriented services, 102**
- connections (MGCP), 303**
- contact center applications, 369**
- contexts, 317**
- controlling**
 - bandwidth, H.323, 254
 - packet loss, 155–156
- convenience features, Centrex, 121**
- convergence**
 - DUAL (Diffusing Update Algorithm), 139
 - self-healing networks, 23
 - voice and data networks, 20–21
- Conversion Analyzer, 332**
- converting**
 - digital signals to analog, 158
 - PCM, μ -law to a-law, 10
- COO (changeover order), 101**
- CORBA (Common Object Request Broker Architecture), 340**
- cost-effectiveness of tie-lines, 43**
- Country Code (CC), 19**

CPU utilization on routers, 175
CQ (custom queuing), 177–178
CRC-16, 91
CRCs (cyclic redundancy checks), 186
CRCX (CreateConnection) command, 304
creation of CDRs
 IPDR-based approach, 212
 OSP-based approach, 211
 RADIUS-based approach, 212
 telco approach, 210
cRTP (RTP Header Compression), 162, 173–174
 CPU utilization, 175
 enabling, 174–175
CSS7, 84
CTI (computer telephony integration), 36
CUGs (Closed User Groups), 39
custom calling features
 POTS, 118
 PSTN
 call forwarding, 17
 call waiting, 17
 three-way calling, 17
custom dialing plans, Centrex, 121
Custom Local Area Signaling Services.
 See CLASS
custom queuing, 178
customizing CDRs, 341
custom-originated trace, 119

D

D channel, 12
D/A conversion, 158
D-links, 87
D/V/V integration, 21
DAI (Dynamic ARP Inspection), protecting IP network infrastructure, 231–232
DALs (Dedicated Access Lines), 120
data channel, 11–12
 H.323, 246
Data field (IP packets), 141
data layer, MTP, 91–92, 94–95
data link layer, OSI Reference model, 132–134
data networks, convergence with voice, 20–21
databases
 SPs, 122
 SS7, 84–85

DC (direct current) signaling, subscriber loop, 48
Dedicated Access Lines (DALs), 120
dedicated circuits, 11
dedicated tie-lines, 120
defining burst size (CAR), 188
delay, 146
 hangover, 157
“deny” statements, 184
designing dial plans, 162–164
Destination address field (IP packets), 141
Destination Point Code (DPC), 96
developing
 operational plans, 235–236
 VSC applications, 332
devices
 codecs
 MOS testing, 152–153
 source codecs, 151
 echo cancellers, 154
 echo suppressors, 154
 H.323
 gatekeepers, 247–248
 gateways, 247
 MCs, 248
 proxy servers, 249
 terminals, 245
 LAN switches, 134
 Layer 2, protecting IP network infrastructure, 230–233
 Layer 3, protecting IP network infrastructure, 233–234
 repeaters, 8
 switches, 6
 Class 5, 10
 dedicated circuits, 11
 end office switches, 8
 tandem, 11, 158–160
DHCP snooping
 database binding, 231
 IP infrastructure, protecting, 230
diagonal links, 87
dial plans
 designing, 162–164
 managing, 160
 Virtual Private Voice Networks, 120
dial-around numbers, 18
dialed digits, 82
dialogs (SIP), 278–279

DID (Direct-Inward-Dial), 65
 digit analysis for NANP call routing, 336
 digit maps (MGCP), 316
Digital Private Network Signaling System.
 See DPNSS
 digital signal level 0s (DS-0s), 90
digital signaling, 7
 ISDN BRI, 12
 lost tones, 11
 out-of-band, 12
 RBS, 13, 48
 repeaters, 8
digital signatures, 223
Digital Subscriber Signaling System No. 1 (DSS1), 68–69
digital trunks
 R2 signaling, 62
 supervision signaling, 57–58
Direct Endpoint Call Signaling, 255
Direct H.245 Control, 257
directory assistance, 123
disabling ports, 227
discrimination. *See* message discrimination
display features (CLASS), 119
displaying RSVP reservations, 186
distance vector routing protocols, 137–138
 EIGRP, 139
 IGRP, 139
 RIP, 140
Distributed CAR, configuring, 188–189
DLCX (DeleteConnection) command, 305
DNF (Do Not Fragment) bit, 197
DOCSIS (Data-over-Cable Service Interface Specifications), 328
DOD (Dial-Outward-Dial), 65
dotted decimal format, 136
DPC (Destination Point Code), 96
DPNSS (Digital Private Network Signaling System), 36, 77
DRR (Deficit Round Robin), 198
DS-0s (digital signal level 0s), 90
DSP (Digital Signal Processor), 146
DSS1 (Digital Subscriber Signaling System No. 1), 68–69
DTMF (Dual Tone Multi-Frequency), 11–12, 49. *See also* in-band signaling
DUAL (Diffusing Update Algorithm), 139
DUAL Gatekeeper, 249
dynamic access lists, 184

dynamic jitter buffers, 148–149
 dynamic queues, 149
 dynamic-queues parameter (fair-queue command), 177

E

E-ISUP (Enhanced ISUP), 330
E-links, 88
E&M signaling, 48
 Type I, 50–51
 Type II, 52
 Type III, 52
 Type IV, 53
 Type V, 54
E.164 numbers, 7
E.164 Recommendations (ITU-T), 19
echo, 154
 inverse speech, 155
 suppressing, 154
echo tail, 155
edge functions, 172
 traffic-shaping tools, 187
EGPs (Exterior Gateway Protocols), 138
EIA/TIA-232, 132
EIGRP (Enhanced IGRP), 139
embedded notification requests, 316–317
EMSS (Element Management Systems), 340
enabling
 cRTP, 174–175
 RSVP, 185
 traffic shaping, 191
 WFQ, 177
 WRED, 200
en-bloc address signals, 72, 108
end-loop signaling, 50
end office switches, 8
endpoints, 258, 302
 A-links, 87
 glare, 50
 load sharing, 88
 locating with RAS signaling, 252
 MCs, registration, 251
 MCU, 249
 predefined routes, 88
 provisioning, 97
end-to-end delay, 148, 171
end-to-end signaling, ISUP, 106

Enhanced ISUP (E-ISUP), 330
enhanced proxy routing, 291
enterprise applications
 Click-2-Dial, 353, 365
 IP phones, 354–365
 soft phones, 354, 365
Enterprise Telephony. See ET
EPCF (Endpoint Configuration) command, 310
erlangs, calculating, 337
ESF (Extended Superframe) framing
 format, 57
ESP (Encapsulation Security Payload), 226
ET (Enterprise Telephony)
 advanced features, 37
 Centrex lines, 39
 comparing to PSTN, 36
 dial plan, designing, 162–164
 PBX (Private Branch Exchange), 35
 private, 41
 tie-lines, 43–44
 simple business lines, 37–38
 VPNs, 39
ETSI (European Telecommunications Standards Institute), OSP, 247
European standards, a-law, 9
evaluating, voice quality, 152–153
events (MGCP), 315–316
examples
 of B2BUA servers, 283–284
 of SCCP connectionless services, 104
 of SIP proxy servers, 280–281
 of SIP redirect servers, 281
 of SS7
 800 queries, 113–114
 basic call setup and teardown, 112–113
exceed actions, 187–188
extended ACLs, 184
extended links, 88
extension negotiation mechanisms (SIP), 292
extensions (SIP), presence service-related, 298
external EMSs, 340

F

F-links, 88
 SS7 signaling traffic termination, 330
Facility messages, 255

fair-queue command, 177
Fast Connect, 258
faststart, 27, 258
fax messaging (POTS), 119
FCS (frame check sequence) field, FISU, 92
feature lines (Centrex), 121
features
 of ANFs, QSIG support, 75
 of Centrex, 121
 of POTS, 118
 CLASS, 118–119
 custom calling, 118
 voice mail, 119
FEC (forward error correction), 162
FIBs (Forward Indicator Bits), 92
fields
 of FISUs, 92
 of IP packets, 140
 of LSSUs, 93–94
 of MSUs, 95
 of TCP packets, 142
FIFO queuing, 175–176
filtering packets, route maps, 183
final SIP responses, 273, 275
Financial Enterprise Telephony, 37
FISUs (Fill-In Signal Units), 91–93
Flag field
 FISUs, 93
 IP packets, 141
flow control, 199
 sliding windows, 141
flows, queuing
 CB-WFQ, 179
 PQ, 178–179
 WFQ, 176
Floyd, Sally, 198
FMC (Consumer Fixed Mobile Convergence), 359–361
forking, 291
forward error correction (FEC), 162
Forward Indicator Bits (FIBs), 92
forward message, H.225, 254
Forward Sequence Number (FSN), 92
forward signals (inter-register signaling), 64
Forward-transfer signals, 59
four-telephone networks, 6
FR.12, 195
fragmentation, 193–194

Frame Relay

- FR.12, 195
- GTS, configuring, 191

- framing formats for T1 lines, 57

- FRF.12, 195

- front-end speech clipping, 157

- FRTS (Frame Relay Traffic Shaping), 189–193

- FSN (Forward Sequence Number), 92

- fully associated signaling, 330

- fully associated SS7, 84

- FX (Foreign Exchange), 65

G

- G.723.1 compression, 152

- G722.2 wideband codecs, 370

- Gatekeeper Routed H.245 Control, 257

- gatekeepers, H.323, 247–248

- gateway control protocols, MGCP, 301

- advanced call control commands, 305–308

- basic call control commands, 304–305

- basic call flow, 311–313

- call agents, 302

- calls, 303

- command-line format, 303

- connections, 303

- digit maps, 316

- embedded notification requests, 316–317

- endpoints, 302

- events and signals, 315–316

- management commands, 308–310

- response messages, 310–311

- trunking, 313–315

- gateway STPs (signal transfer points), 84

- gateways, H.323, 247

- Generic Functional Procedures (QSIG GF), 73–75

- GKRCS (Gatekeeper Routed Call Signaling), 248

- call signaling, 256

- glare, 13, 50

- global synchronization, 198

- global title translation, 82

- ground-start signaling, 50

- G-series recommendations (ITU-T), 152

- GTS (Generic Traffic Shaping), 189–191

- comparing to FRTS, 190

- syntax, 191–192

H

- H.225, 254, 257

- H.245, 257

- call termination, 259

- tunneling, 258

- H.248 connection model, 317. *See also* MEGACO

- H.323, 24–25, 217, 241–245

- call flow, 26, 260–262

- DUAL Gatekeeper, 249

- fast-start, 27

- gatekeepers, 247–248

- gateways, 247

- H.225, 254, 257

- H.245, 257

- MCU, 248

- protocol suite, 249

- proxy servers, 249

- RAS signaling, 250–251

- admissions*, 253

- bandwidth control*, 253

- endpoint location*, 252

- gatekeeper discovery*, 250–251

- registration*, 251

- status information*, 253

- RTP/RTCP, 259

- signaling traffic termination, 330

- SIP endpoint/client on packet voice network

- architecture, 329

- terminals, 245

- version 3, 247

- half-open connections, 234

- handling delay, 146

- hangover, 157

- Header checksum field (IP packets), 141

- headers

- compression, 174

- IP Tax, 172

- headers (SIP), 277–278

- hierarchical addressing, 134

- hierarchical networks, comparing to

- meshed, 11

- high-speed transport, 197–198

- HIPS (Host-based Intrusion Protection Systems), 228
 - history of PSTN, 5
 - HLR (Home Location Register), 84
 - homologation, 36
 - hoot-n-holler, 37
- I**
- IAM (Initial Address Message), 14
 - Identification fields (IP packets), 141
 - IGRP (Interior Gateway Routing Protocol), 139
 - IHL (IP header length) field, 140
 - IKE (Internet Key Exchange), 227
 - IM (instant messaging), 297
 - integrated IM clients, 354
 - implementing PGW2200, 337
 - implicit “deny” statements, 184
 - IMT (Inter-Machine Trunk), 28
 - IN (Intelligent Network), 14
 - in-band signaling, 11, 49
 - DTMF tones, 49
 - lost tones, 13
 - MF tones, 49
 - single-frequency tones, 49
 - inbound call centers, 37
 - infrastructure model, PSTN, 30, 32
 - integrated IM clients, 354
 - integrating disparate networks, 162–163
 - integrity as security requirement, 221
 - Interactive Voice Response (IVR), 122
 - intercept mode (routers), 234
 - interface configuration commands,
 - fair-queue, 177
 - interfaces
 - available for MNM, 340–341
 - high-speed transport, 197–198
 - packet voice networks, 329
 - connection control, 331
 - RSVP, enabling, 185
 - TCAP, 110
 - WFQ, enabling, 177
 - interference
 - accumulated noise, 8
 - line noise, 7–8
 - international STPs, 83
 - inter-packet arrival time. *See* jitter
 - inter-PGW2200 signaling, 330
 - inter-register signaling (R2 method), 63–64
 - inverse speech, 155
 - INVITE requests, 272
 - IP (Internet Protocol), 133–134
 - IP addressing
 - classes, 135–136
 - dotted decimal notation, 136
 - subnets, 136
 - IP call-flow, comparing to PSTN call-flow, 164–166
 - IP packets, 143
 - fields, 140
 - MTU (maximum transmission unit), configuring, 196
 - IP-PBXs, 354, 365
 - IP phones, 354, 365
 - IP Precedence, 181–183
 - ip rsvp bandwidth command, 185
 - IP Souce Guard, protecting IP network infrastructure, 231
 - “IP Tax,” 172
 - IPsec, 226
 - ISDN (Integrated Services Digital Network), 11, 64, 72
 - 23B+D, 68
 - access interfaces, 66
 - bearer services, 65
 - BRI, 12
 - reference points, 66–67
 - call disconnect, 73
 - L2/L3 specifications, 68–69
 - out-of-band signaling, 12
 - PRI, 68
 - Q.931 messages, 69–71
 - supplementary services, 65
 - teleservice, 65
 - ISDN User Part. *See* ISUP
 - IS-IS (Intermediate System to Intermediate System), 138
 - ISP case studies, BOWIE.net, 356–357
 - ISUP (ISDN User Part), 64, 89, 105–109
 - call setup and teardown, 106–107
 - end-to-end signaling, 106
 - messages
 - call control, 108–109
 - format, 107
 - services, 105

ITU-T (International Telecommunication Union Telecommunication Standardization Sector)

- E.164 recommendations, 19
- G.114 recommendations, 171
- G.726 recommendation, 151
- G-series recommendations, 152
- H.225, 254, 257
- H.245, 257
- H.323
 - gatekeepers*, 247–248
 - gateways*, 247
 - MCU*, 248
 - proxy servers*, 249
 - terminals*, 245
 - version 3*, 247
- international numbering plan, 19
- P.861 recommendation, PSQM, 154
- IUA (ISDN User Adaptation) specification, 343**
- IVR (Interactive Voice Response), 122**
- IWF (interworking functions), 358**
- IXCs (inter-exchange carriers)**
 - dial-around numbers, 18
 - services, 17

J-K

- Jacobson, Van, 198**
- jitter, 22–23, 148. *See also* echo**
 - comparing to total delay, 148
 - measuring, 149
- key-system, 38**

L

- L2/L3 specifications (ISDN), 68–69**
- lab testing QoS tools, 201–202**
- LAN switches, 134**
- LAPD (Link Access Procedures/D channel), 68–69**
- latency, 146**
- Layer 2 devices, protecting IP network infrastructure, 230–233**
- Layer 3 devices, protecting IP network infrastructure, 233–234**

layers

- of MTP (Message Transfer Part)
 - data layer*, 91–95
 - network layer*, 96–102
 - physical layer*, 90
- of OSI Reference model
 - application layer*, 130
 - comparing to SS7 protocol stack*, 89
 - data link layer*, 132
 - network layer*, 131–132
 - physical layer*, 132
 - presentation layer*, 130
 - session layer*, 131
 - transport layer*, 131, 140–143
- of packet-switching model, 22
- of SS7 protocol stack
 - ISUP*, 105–109
 - MTP*, 90–101
 - SCCP*, 102–104
 - TCAP*, 109–111
 - TUP*, 104

LBC (Internet Low Bitrate Codec), 152

LECs (Local Exchange Carriers)

- Centrex lines, 38
- simple business lines, 37

LI (Length Indicator) field of FISUs, 92–93

LIDB (Line Information Database), 84

limitations of DC signaling, 48

Line Information Database (LIDB), 84

line noise, 7–8

line signals, 55

link-state routing protocols, 137–138

- IS-IS, 138
- OSPF, 139

Link Status Signal Unit (LSSU), 91

links

- B-links, 87
- C-links, 87
- combined linksets, 88
- D-Links, 87
- endpoints, MCU, 249
- F-links, 88
- integrity of, verifying, 92
- signaling links
 - A-links*, 87
 - SS7*, 85
- T1, 90

LNP (Local Number Portability), 14

LNPDB (Local Number Portability Database), 84
load sharing, SS7, 88
local loop, 10
logging CDRs, 341
logical addressing, 134
Logical Channel Signaling, 258
long-distance services
 billing services, 123
 calling card services, 123
 circuit-switched, 17
 dial-around numbers, 18
 PCM, 10
loop-start signaling, 50
lossiness, 155–156
lost tones, 11–13
LSSU (Link Status Signal Unit), 91–94

M

MAC (Media Access Control) addresses, 134
man-in-the-middle attacks, 231
management commands, MGCP, 304
management functions, SCCP, 104
managing
 business services, Centrex, 121
 dial plans, 160
master-slave termination, 258
match clause feature, policy routing, 184
MCML PPP (Multi-Class Multilink Point-to-Point Protocol), 195
MCU (multipoint control unit), H.323, 248
MDCX (ModifyConnection) command, 305
MDRR (Modified Deficit Round Robin), 198
measuring jitter, 149
Media Gateways, 25
media transmission, H.323, 246
mediation services, 218–219
MEGACO (Media Gateway Control Protocol), 25, 29. See also H.248
meshed networks
 comparing to hierarchical, 11
 scalability, 10
message discrimination, 97
Message Signal Unit. See MSU
messages
 ACM, 16
 admissions, 253
 ANM, 16
 bandwidth control, 254
 Capability Exchange (H.245), 257
 COO, 101
 IAM, 14
 ISUP, 107
 call control, 108–109
 MTP3, format, 96
 network-user, 69
 Q.931, 69–71
 Q.932, call control signaling, 254
 RAS status information, 253
 registration (H.323), 251
 RELEASE, 16
 SIP
 headers, 277–278
 structure, 275–276
 TCAP, 110–111
 TFA (Transfer Allowed), 101
 UDTs, 103
 UDTSes, 103
 UPU, 98
 user network, 69
MF signaling systems, 13, 49, 55
 address signaling, 57–58
 supervision signaling, 55, 57
MFC (multi-frequency code), 60
MGs (media gateways) on packet voice network architecture, 327
MGC (Media Gateway Controller), 25
MGCP (Media Gateway Control Protocol), 25–27, 301
 advanced call control commands
 NTFY (Notification), 308
 RQNT (NotificationRequest), 305–307
 basic call control commands
 CRCX (CreateConnection), 304
 DLCX (DeleteConnection), 305
 MDCX (ModifyConnection), 305
 basic call flow, 311–313
 call agents, 302
 calls, 303
 command-line format, 303
 connection control, 331
 connections, 303
 digit maps, 316
 embedded notification requests, 316–317
 endpoints, 302
 events and signals, 315–316

- management commands
 - AUCX (AuditConnection)*, 309
 - AUEP (AuditEndpoint)*, 308
 - EPCF (EndpointConfiguration)*, 310
 - RSIP (RestartIn-Progress)*, 309
- Megaco architecture, 29
- packet voice networks, 331
- response messages, 310–311
- trunking, 313–315
- Microsoft Office Communicator Mobile**, 353
- middleware**, 218–219
- migrating to VoIP architecture**, 363–364
- missed calls, returning**, 17
- mitigation of DoS attacks as security requirement**, 221
- MNM (MGC Node Manager)**, 338–340
 - interfaces, 340–341
 - SP requirements, 341
- MOS (mean opinion score) tests**, 152–153
- MSU (Message Signal Unit)**, 91, 94–95
- MSW (Multiprotocol Signaling Switch)**, 359
- MTP (Message Transfer Part)**, 89
 - data layer, 91–95
 - network layer, 96–102
 - physical layer, 90
- MTP2**, 91
 - FISU, 91, 93
 - LSSU, 93–94
 - MSU, 94–95
- MTP3**, 96
 - message format, 96
 - routing, 98
 - SMH, 97
 - SNM, 98
 - changeover/changeback*, 101–102
 - congestion control*, 100–101
 - message structure*, 100
 - rerouting*, 101
- MTU (maximum transmission unit)**,
 - configuring, 196
- multicast packets**, 133
- multi-frequency code (MFC)**, 60
- multilink PPP, MCML**, 195
- mutual authentication mode (TLS)**, 225

N

- NANP (North American Numbering Plan)**, 18–19, 334
 - call rerouting, 336
 - digit analysis, 336
 - route analysis, 334–335
 - VSC, 334
- NANPA (North American Numbering Plan Association)**, 135
- NAPTR (Naming Authority Pointer)**, 285
- NAS (network access server)**, 209
- National Destination Code (NDC)**, 19
- National R2 signaling**, 62
- NDC (National Destination Code)**, 19
- NDM-U 2.5 (Network Data Management-Usage specification Version 2.5)**, 212
- negative acknowledgments**, 92
- Netmeeting**, 353, 365
- network layer**
 - MTP, 96–102
 - of OSI Reference model, 131–132, 135
- networks**
 - backbone, 197
 - edge, traffic-shaping tools, 187
 - ET. *See* ET
 - four-telephone, 6
 - packet voice. *See* packet voice network architecture
 - PSTN. *See* PSTN
 - self-healing, 23
 - subnetting, 136
 - telephony. *See* telephony networks
 - tie-line, 39–40
- network-to-network signaling**, 13–14
- network-user messages**, 69
- NIPS (Network-based Intrusion Prevention Systems)**, 233
- noise, accumulated**, 8
- nonassociated signaling**, 86, 330
- North American standards, μ -law**, 9–10
- notifications (SIP)**, 294
- NOTIFY method (SIP)**, 294–295
- NPA (Numbering Plan Areas)**, 135
- NTFY (Notification) command**, 308
- numbering plans, PSTN**
 - ITU-T, 19
 - NANP, 18–19
- Nyquist theorem**, 9, 149

O

- objective voice testing, 152–153
- on-hook/off-hook lead conditions, E&M
 - Types I through IV, 51–54
- onset of congestion alerts, 101
- OPC (Originating Point Code), 96
- operational plans, developing, 235–236
- operator services, SPs, 123
- OPT (Open Packet Telephony), 323
- Options field (IP packets), 141
- OPTIONS requests (SIP), 272, 292
- Originating Point Code (OPC), 96
- OSI Reference model
 - application layer, 130
 - comparing to SS7 protocol stack, 89
 - data link layer, 132
 - network layer, 131–132
 - physical layer, 132
 - presentation layer, 130
 - session layer, 131
 - transport layer, 131, 140
 - TCP, 141
 - UDP, 142–143
- OSP (Open Settlement Protocol), 247
- OSPF (Open Shortest Path First), 139
- out-of-band signaling, 11–12
- outbound call centers, 37
- overlap address signals, 108
- overlap signaling, 72

P

- P2P (Peer to Peer) networking, 25
- packet switching, 21–24
 - call-control layer, 24
 - call-control protocols, H.323, 25
 - standards-based infrastructure, 22–23
- packet voice network architecture
 - cable headend, 328
 - connection control, 331
 - H.232/SIP endpoint/client, 329
 - interfaces, 329
 - MG, 327
 - PGW2200 call agent, 326
 - CDRs, 341
 - check-pointing, 338
 - connection control, 331
 - core capabilities, 327
 - implementing, 337
 - inter-PGW2200 signaling, 330
 - NANP support, 334–336
 - optional elements, 327
 - required elements, 326
 - services control, 331
 - signaling termination, 329–330
 - supported protocols, 332
 - third-party application development tools, 332
 - XE, 333–334
 - residential gateway, 328
 - SCP, 328
 - signaling termination, 329
 - typical applications, 325

packets

- bandwidth consumption, IP tax, 172
- blocking, 194
- broadcast, 133
- burst size, defining, 188
- classifying, 180, 183–184
 - IP Precedence, 181–183
- congestion avoidance, 198
 - TCP, 199
 - WRED, 199
- end-to-end delay, 147
- filtering with route maps, 183
- FISU, 91
- fragmentation, 193–194
- handling delay, 146
- high-speed transport, 197–198
- IP, 140–143
- jitter, 22, 148
- lossiness, 155–156
- multicast, 133
- queuing, 175
 - CB-WFQ, 179
 - CQ, 177–178
 - delay, 147
 - PQ, 178–179
- rate-limiting, 187–188
- repeating, 134
- signal units, 91
- TCP, fields, 142
- timestamping, 22
- traffic shaping, FRTS, 192–193
- unicast, 133

packet-switching, call control protocols

SGCP, 27

SIP, 29

parallel forking, 291**parameters, fair-queue command, 177****PAs (presence agents), 298****pass-along method (end-to-end signaling), 106****PBXs (Private Branch Exchanges), 35–37,****41–43, 47**

CTI links, 36

E&M Type I, 51

E&M Type IV, 53

ground-start signaling, 50

IP-PBXs, 354, 365

tie-lines, 43–44

PCM (Pulse Code Modulation), 8, 149.*See also* ADPCM

μ-law, 9

a-law, 9

DS-0, 90

long-distance calls, 10

Nyquist Theorem, 9

peer-to-peer signaling, QSIG, 73**peering, 359****Perceptual Speech Quality Measurement (PSQM), 154****performance issues**

CPU utilization, 175

signaling links, 88

“permit” statements, 184**PGW Application Toolkit, 332****PGW2200, 335**

call agent, 326

*core capabilities, 327**optional elements, 327**required elements, 326*

CDRs, 341

check-pointing, 338

connection control, 331

implementing, 337

inter-PGW2200 signaling, 330

NANP support

*call rerouting, 336**route analysis, 334–335*

services control, 331

signaling termination, 329–330

supported protocols, 332

third-party application development

tools, 332

XE, 333

*available services, 333–334**NANP support, 334, 336***phone lines, 10****physical layer**

of MTP, 90

of OSI Reference model, 132–134

PINs (personal identification numbers), 123**point code, 80****policing, 229**

CAR, 187–188

policy routing, 182–184**polite blocking, 297****ports, disabling, 227****post-paid calling cards, 17****POTS (plain old telephone service), 117**

CLASS features, 118–119

custom calling features, 118

voice mail, 119

PQ (priority queuing), 178–179**precedence, rate-limiting traffic, 187–188****predefined signaling routes, 88****pre-paid calling cards, 17**

BOWIE.net case study, 356–358

presence, 297, 367

related SIP extensions, 298

various states of, 367

presence-aware services, 298, 368–369**presentation layer (OSI Reference model), 130****presentity, 298****PRI (primary rate interface), 12, 68**

signaling traffic termination, 330

primitives, SCPs (Service Control Points), 84–85**privacy as security requirement, 221****Private Branch Exchanges. *See* PBXs****private ETs, 41**

PBXs, 41–43

private leased lines, 18**processing delay, 146****propagation delay, 146****protocol extensions, 209****Protocol field (IP packets), 141****protocol stack**

QSIG, 75

SS7, 89

*ISUP, 105–109**MTP, 90–102*

SCCP, 102–104

TCAP, 109–111

TUP, 104

protocol supervisory messages, 338

protocols

bursty, 133

call-control, H.323, 24–25

call flows, 260–262

H.225, 254, 257

H.245, 257

RAS signaling, 250–253

registration, 251

RTP/RTCP, 259

provisional SIP responses, 273–275

provisioning signaling endpoints, 97

proxy servers

H.323, 249

SIP, 29

example of, 280–281

PSQM (Perceptual Speech Quality Measurement), 154

PSS1 (Private Signaling System No. 1).

See **QSIG**

PSTN (Public Switched Telephone Network), 47

advanced features, 37

business services, 119–120

call centers, 121–122

Centrex, 121

call-control plane, 31

call flow, 15–16, 164–166

Centrex lines, 39

CLASS, 14

comparing to ET, 36

CUGs, 39

custom calling features, 17

dedicated tie-lines, 120

devices, homologation, 36

history, 5

network infrastructure model, 30–32

numbering plans

ITU-T, 19

NANP, 18–19

over IP, 344–346

IUA, 343

SCTP, 342–343

SIGTRAN, 341–342

signaling methods, 11–16

simple business lines, 38

SPs, 122–123

voice and data convergence, 20–21

VPNs, 39–40

public-key cryptography, 222

asymmetric keys, 222–223

certificates, 224

digital signatures, 223

IPsec, 226

SRTP, 227

TLS protocol, 224–225

Public Switched Telephone Network.

See **PSTN**

Pulse Code Modulation. *See* **PCM**

Q

Q reference point, 74

Q.931 messages, 69–71

Q.932 messages, 254

QoS (quality of service), 201

backbone, 200

queuing, 175

CB-WFQ, 179

CQ, 177–178

custom queuing, 178

PQ, 178–179

WFQ, 176–177

testing, 201

weighting techniques, 180

IP Precedence, 181–183

policy routing, 183–184

RSVP, 184–186

QSIG, 36, 73

ANFs, 75

architecture, 74

attributes, 73

call setup, 76

Generic Functional Procedures, 73–75

protocol stack, 75

reference points, 74

services, 74

quad-play offerings, 353

quality of service. *See* **QoS**

quasi-associated signaling, 86

queuing, 175

CB-WFQ, 179

CQ, 177–178

delay, 147

PQ, 178–179
 tail-drops, 199
 traffic shaping, 190–191
 weighting techniques, RSVP, 184–186
 WFQ, 176–177

R

- R reference point, 67**
- R1 signaling, 60**
- R2 signaling, 60–61**
 - inter-register signaling, 63–64
 - supervision signaling
 - analog trunks, 61*
 - digital trunks, 62*
- RADIUS (Remote Authentication Dial-In User Service), 209–210**
 - server accounting, 215–217
- random-detect command, 200**
- RAS (Registration, Admission and Status) signaling**
 - admissions, 253
 - bandwidth control, 253
 - endpoint location, 252
 - gatekeeper discovery, 250–251
 - registration, 251
 - status information, 253
- rate-limiting tools, CAR, 187–188**
- RBS (Robbed Bit Signaling), 13**
- recommendations, ITU-T. *See* ITU-T**
- RED (Random Early Detection), 198**
- redirect servers (SIP), example of, 281**
- REFER requests (SIP), 296**
- reference points, 67**
 - BRI, 66–67
 - QSIG, 74
- REGISTER requests, 273**
- registration process**
 - RAS signaling, 251
 - SIP, 285–286
 - state changes during, 295*
- Release Complete messages, 255**
- RELEASE message, 16**
- Release-guard signals, 59**
- reliability of routing protocols, 137**
- Reliable User Data Protocol. *See* RUDP**
- removing echo, 155**
- repeaters, 8, 134**
- requests (SIP)**
 - handling preferences, specifying, 293
 - NOTIFY, Subscription-State header, 295
 - REFER, 296
- Require header (SIP), 292**
- rerouting calls on PGW2200 for NANP, 336**
- reservable-queues parameter (fair-queue command), 177**
- reservations (RSVP), displaying, 186**
- resetting IP Precedence, 182**
- residential gateways on packet voice network architecture, 328**
- response messages (MGCP), 310–311**
- responses (SIP), 273, 276**
- restrictions on DC signaling, 48**
- retransmission messages, SS7, 91**
- returning missed calls, *69, 17**
- RFC 3841, caller/callee preferences, 293**
- ring-down circuits, 5**
- RIP (Routing Information Protocol), 140**
- robbed-bit signaling, 48**
 - digital trunks, 57
- root bridge, 232**
- Root Guard, IP network infrastructure, protecting, 232–233**
- Round-Trip Delay (H.245), 258**
- route analysis for NANP call routing, 334–335**
- route maps, 183**
- routed protocols, comparing to routing protocols, 137**
- routers, CPU utilization, 175**
- routesets, 88**
- routing**
 - ASR, 249
 - MTP3, 98
- routing protocols, 137**
 - BGP, 138
 - distance vector, 138
 - EIGRP, 139*
 - RIP, 140*
 - IGRP, 139
 - IS-IS, 138
 - link-state, 138–139
- routing tables, 138**
- RQNT (NotificationRequest) command, 305–307**
- RSIP (RestartIn-Progress) command, 309**
- RSVP (Resource Reservation Protocol), 184–186**

RTCP (RTP Control Protocol), 161
RTCP XR (RTP Control Protocol Extended Reports), 162
RTP (Real-time Transport Protocol), 22, 227
RTP (Reliable Transport Protocol), 161–162
RTP Control Protocol (RTCP), 161
RUDP (Reliable User Data Protocol), 162, 330

S

S/T reference points, 67
sampling
 Nyquist theorem, 9, 149
 voice samples per frame, effect on voice quality, 150
satellite networks, sampling, 150
SBCs (session border controllers), 346–348, 358
SCAI (Switch-Computer Applications Interface), 122
scalability
 meshed telephone networks, 10
 RSVP, 186
SCCP (Signaling Connection Control Part), 89
 connection-oriented services, 102
 connectionless services, 102–103
 example, 104
 management functions, 104
SCNs (switched circuit networks), gateways, 247
scoring MOS tests, 152–153
SCPs (Service Control Points), 24, 84–85, 324
 on packet voice network architecture, 328
SCTP (Stream Control Transmission Protocol), 342–343
security
 authorization services, 123
 Centrex features, 121
 H.323 call authorization, 248
 layering, 230
 operational plans, developing, 235–236
segment sequence number, 199
segmentation, 228
selecting dial-plan design, 163
self-healing networks, 23, 137
sequential forking, 291
serial interfaces, configuring MTU, 196

serialization delay, 146
server-auth mode (TLS), 225
service circuits, 55
Service Control Points. *See* SCPs
service plane (Cisco Packet Telephony architecture), 324
service providers
 call control, 351–353
 case studies, BOWIE.net, 356–357
 Vonage, wide-scale deployment, 354–355
services
 business services, 119
 call centers, 121–122
 Centrex, 121
 Virtual Private Voice Networks, 120
 CLASS, 17
 connection-oriented, 102
 connectionless, SCCP, 102–103
 controlling on PGW2200, 331
 disabling, 227
 ISUP, 105
 IXCs, 17
 POTS, 117
 CLASS features, 118–119
 custom calling features, 118
 features, 118
 voice mail, 119
 PSTNs
 Centrex lines, 39
 simple business lines, 38
 VPNs, 39–40
 QSIG, 74
 SPs
 database services, 122
 operator services, 123
session context, 174
Session layer (OSI Reference model), 131
setup messages, 14, 254
SF (Super Frame) framing format, 57
SGCP (Simple Gateway Control Protocol), 27
 packet voice networks, 331
shaping traffic, 189–190
 FRTS, 192–193
 GTS, 191
shaping tools, 187
shared secrets, 209
shared-key authentication, 222
SIB (Status Indicator Busy), 94
SIE (Status Indicator Emergency), 94

SIF (Service Information Field), MSUs, 95**signal units, 91**

FISUs, 91–93

LSSUs, 93–94

MSUs, 94–95

signaling

address signals, 55

analog, 7–8

backhaul, 28

CAS, 50, 54

R1, 60*R2*, 60–64

CCITT No. 5, 58

address signaling, 60*supervision signaling*, 59

CCS, 49–50

CLASS, 14

DC, subscriber loop, 48

digital, 7–8

DPNSS, 77

E&M

Type I, 50*Type II*, 52*Type III*, 52*Type IV*, 53*Type V*, 54

en-bloc, 72

end-loop, 50

ET, comparing to PSTN, 36

ground-start, 50

H.225, 254, 257

in-band, 11, 49

ISDN, 64

BRI, 66*call disconnect*, 73*call setup*, 71*L2/L3 specifications*, 68*PRI*, 68–70*Q.931 messages*, 69–70

line signals, 55

Logical Channel, 258

lost tones, 11

MF, 55

address signaling, 57–58*supervision signals*, 55–57

network-to-network, 13

out-of-band, 12

overlap signaling, 72

peer-to-peer, 73

PSTN

call flow, 15–16

CLASS, 14

glare, 13*lost tones*, 13*network-to-network*, 14

QSIG

architecture, 74*call setup*, 76*protocol stack*, 75*reference points*, 74*services*, 74*T reference point*, 74

R2, 60–61

inter-register signaling, 63–64*supervision signaling*, 61–62

RAS, 250–251

admissions, 253*bandwidth control*, 253*endpoint location*, 252*gatekeeper discovery*, 250–251*registration*, 251*status information*, 253

RBS, 13, 48

Single Frequency, 49, 56

SS7, 13–14

associated signaling, 85*C-links*, 87*combined linksets*, 88

CSS7, 84

databases, 84*E-links*, 88*F-links*, 88*nonassociated signaling*, 86*quasi-associated signaling*, 86*specifications*, 115

supervision signals, 55

user-to-network, 11

signal-to-noise threshold, 157**SIGTRAN (Signaling Transport), 28, 341–342****simple business lines, 37–38****SIN (Status Indicator Normal), 94****Single Frequency signaling, 49, 56****SIO (Status Indicator Out-of-Alignment), 94****SIOS (Status Indicator Out-of-Service), 94****SIP (Session Initiation Protocol)**

addressing, 271–272

dialog, 278–279

enhanced proxy routing, 291

- extension negotiation mechanism, 292
- forking, 291
- headers, 277–278
- notifications, 294
- NOTIFY method, 294–295
- OPTIONS requests, 292
- presence service, 297–298
- provisional responses, 273–275
- proxy servers, 29
 - example of*, 280–281
- redirect servers, *example of*, 281
- registration procedure, 285–286
 - state changes during*, 295
- requests
 - handling preferences, specifying*, 293
 - REFER, 296
 - structure of*, 275–276
- responses, 273
 - final*, 273–275
 - structure of*, 276
- RFC 3841, caller/callee preferences, 293
- signaling, supported transport layer
 - protocols, 280
- transactions, 278–279
- user mobility, 285

SIPO (Status Indicator Processor Outage), 94

SIP-T, 331

sliding windows, 141

SLT (Signaling Link Terminal), 28

SMH (Signaling Message Handling), 97

SN (Subscriber Number), 19

SNA (Systems Network Architecture), 155, 182

SNM (Signaling Network Management), 98

- changeover/changeback, 101–102
- congestion control, 100–101
- message structure, 100
- rerouting, 101

soft phones, 354, 365

softswitches, 24–29

- PSTN signaling over IP, 342

Source address field (IP packets), 141

source codecs, 151

specifications

- FR.12, 195
- ITU-T, H.323, 241–248
- SS7, 115

specifying SIP request handling preferences, 293

speed dialing, POTS, 118

SPF (shortest path first) algorithm, 139

SPs (service providers)

- business services, 119
 - call centers*, 121–122
 - Centrex, 121
 - Virtual Private Voice Networks*, 120
- database services, 122
- operator services, 123
- POTS, 117
 - CLASS features*, 118–119
 - custom calling features*, 118
 - features*, 118
 - voice mail*, 119

SRTP (Secure Real-time Transport Protocol), 227

SS6, 50

SS7 (Signaling System 7)

- A-links, 87
- ACM, 16
- ANM, 16
- associated signaling, 85
- C-links, 87
- combined linksets, 88
- CSS7, 84
- databases, 84
- D-links, 87
- E-links, 88
- examples
 - 800 queries*, 113–114
 - basic call setup and teardown*, 112–113
- F-links, 88
- fully associated, 84
- global title translation, 82
- ISUP, 105–109
 - call control messages*, 108–109
 - call setup and teardown*, 106–107
 - end-to-end signaling*, 106
 - message format*, 107
 - services*, 105
- message structure, 91
- MNM, 338–340
 - interfaces*, 340–341
 - SP requirements*, 341
- MTP, 89
 - data layer*, 91–95
 - network layer*, 96–102
 - physical layer*, 90

- nonassociated signaling, 86
- point code, 80
- protocol stack, 89
- quasi-associated signaling, 86
- RELEASE message, 16
- retransmission messages, 91
- SCCP, 102–104
- SCPs, 84–85
- signaling links, 85
 - performance*, 88
- signaling traffic termination, 329
- specifications, 115
- SSP, 81
- STP, 82
 - global title translation*, 82
 - hierarchical structure*, 83–84
- TCAP, 109–111
- TUP, 104
- SSPs (Service Switching Points), 81**
- standards, G-series recommendations, 152**
- standards-based packet infrastructure, 22–23**
- states of presence, 367**
- static jitter buffers, 148**
- Status field (LSSUs), 93**
- Status Indicator Processor Outage (SIPO), 94**
- status information (RAS), obtaining, 253**
- STP (Switching Transfer Point), 28**
- STPs (Signal Transfer Points), 82**
 - A-links, 87
 - global title translation*, 82
 - hierarchical structure*, 83–84
- streams, RTP, 22**
- structure of SIP requests/responses, 275–276**
- subinterfaces (Frame Relay), GTS**
 - configuration, 191**
- subjective voice testing, 152–153**
- subnets, 136**
 - broadcast packets, 134
- SUBSCRIBE method (SIP), 294–295**
- subscriber loop, 48**
- Subscriber Number (SN), 19**
- supervision signaling, 55**
 - Bell System MF digital trunks, 57
 - CCITT No. 5 method, 59
 - R2
 - analog trunks*, 61
 - digital trunks*, 62
 - Single Frequency signaling, 56

- supplementary services**
 - ISDN, 65
 - ISUP, 105
- Supported header (SIP), 292**
- supported protocols on PGW2200, 332**
- Switch-Computer Applications Interface (SCAI), 122**
- switches, 6, 134**
 - Class 5, 10
 - dedicated circuits, 11
 - end office, 8
 - hierarchical structure, 11
 - tandem, 158–160
 - trunks, 10
- System Control Unit (H.323), 246**
- Systems Network Architecture (SNA), 155, 182**

T

- T reference point (QSIG), 74**
- T1 lines, 90**
 - 23B+D, 68
 - framing format, 57
- T1 links**
- tail-drops, 199**
- tandem-compression, 159**
- tandem switches, 11, 84, 158**
- TASI (Time Assignment Speech Interpolation), 58–59**
- TCAP (Transaction Capabilities Applications Part), 89, 102, 109–111**
- TCP (Transmission Control Protocol), 141, 199**
- TCP header compression, 173**
- TCP intercept, 234**
- TCP/IP, 22**
 - toll-bypass, 353
- TDM (time-division multiplexing), 176**
- telephony networks**
 - business services, 119
 - call centers*, 121–122
 - Centrex*, 121
 - four-telephone networks, 6
 - line noise, 8
 - meshed, scalability, 10
 - phone lines, 10
 - POTS, 117–119

- PSTN, history of, 5
 - ring-down circuits, 5
 - signaling, 7
 - SPs
 - database services*, 122
 - operator services*, 123
 - terminals, H.323, 245**
 - testing**
 - QoS tools, 201–202
 - voice quality, 152–153
 - TFA messages (Transfer Allowed), 101**
 - third-party application development tools for PGW2200, 332**
 - three-way calling, 17**
 - POTS, 118
 - throttling, BECN-based, 193**
 - tie-lines, 39–40, 43–44**
 - Time Assignment Speech Interpolation (TASI), 58–59**
 - Time To Live fields (IP packets), 141**
 - time-division multiplexing (TDM), 176**
 - timestamping, 22**
 - RTP, 149
 - TLS (Transport Layer Security), 224–225**
 - tooggling BIB/FIB values, 92**
 - toll-bypass, 353, 364**
 - toll operators, 123**
 - tones (in-band signaling), 49**
 - tools**
 - cRTP, 173–174
 - QoS, 169
 - lab testing*, 201–202
 - total delay, comparing to jitter, 148**
 - Total length field (IP packets), 141**
 - traffic. *See also* traffic shaping**
 - burst size, defining, 188
 - classifying, 175, 179–180, 183–184
 - IP Precedence*, 181–183
 - congestion avoidance, 198
 - TCP*, 199
 - WRED*, 199
 - high-speed transport, 197–198
 - onset of congestion alerts, 101
 - policing, 229
 - queuing, 175
 - CB-WFQ*, 179
 - CQ*, 177–178
 - PQ*, 178–179
 - WFQ*, 176
 - rate-limiting, 187–188
 - repeating, 134
 - segmentation, 228
 - traffic shaping**
 - enabling, 191
 - FRTS, 192–193
 - GTS, 191
 - transaction capabilities application part. *See* TCAP**
 - transactions**
 - MGCP, 303
 - SIP, 278–279
 - Transfer Allowed (TFA) messages, 101**
 - transitive trust, 235**
 - transport layer (OSI Reference model), 131**
 - RTP, 161–162
 - SIP signaling support, 280
 - TCP, 141
 - UDP, 142–143
 - transport mode (IPsec), 226**
 - trunks, 10, 313–315**
 - IMT (Inter-Machine Trunk), 28
 - signaling
 - E&M*, 50
 - Type I*, 51
 - supervision signaling
 - analog*, 56
 - digital*, 57–58
 - tunnel mode (IPsec), 226**
 - tunneling, H.245, 258**
 - TUP (Telephone User Part), 89, 104**
 - Type I interfaces (E&M signaling), 50**
 - Type II interfaces (E&M signaling), 52**
 - Type III interfaces (E&M signaling), 52**
 - Type IV interfaces (E&M signaling), 53**
 - Type V interfaces (E&M signaling), 54**
 - Type of service fields (IP packets), 140**
- ## U
- U reference point, 67**
 - UA (user agents)**
 - dialog, 278–279
 - SIP registration process, 285–286
 - UDP (User Data Protocol), 22, 142–143**
 - RUDP, 330
 - UDTs (Unidata Messages), 103**
 - UDTSes (Unidata Service Messages), 103**

- unicast packets, 133
- unused ports, disabling, 227
- UPU (User Part Unavailable) messages, 98
- user-network messages, 69
- user-to-network signaling, 11
- utilities, cRTP, 173–174

V

- VAD (voice activity detection), 157
- VCs (virtual circuits), 18
- verifying signaling elements, integrity, 92
- Versatile Interface Processor Distributed CAR (VIP-DCAR), 188
- Version field (IP packets), 140
- video codecs, H.323, 246
- VIP-DCAR (Versatile Interface Processor Distributed CAR), 188
- virtual circuits (VCs), 18
- Virtual Private Networks (VPNs), 18, 39–40
- Virtual Private Voice Networks, 120
- VLR (Visitor Location Register), 85
- voice activity detection (VAD), 157
- voice mail, POTS, 119
- voice messaging, 119
- voice networks, convergence with data networks, 20–21
- VoIP-based toll-bypass, 364
- Vonage, wide-scale deployment, 354–355
- VPNs (Virtual Private Networks), 18, 39–40
- VSAs (vendor-specific attributes), 210
- VSC (virtual switch controller), 27, 325
 - CDRs, 341
 - packet voice networks, 329
 - XE, 334

W

- WANs, edge functions, 172
- wasted bandwidth, utilizing, 157
- waveform codecs, 151
- web-based collaboration tools, 366–367
- web sites, Frame Relay Technical Forum, 195
- weighted random early detection (WRED), 199–200

- weighting techniques, 180
 - IP Precedence, 181–183
 - policy routing, 183–184
 - RSVP, 184–186
- WFQ (weighted fair queuing), 175–177
- whitelists, 216
- wideband codecs, 370
- Wi-Fi-enabled phones, 370
- Winchester Blocks, 132
- WRED (weighted random early detection), 199–200

X-Y-Z

- XE (Execution Environment), available services, 333–334
- zone management, H.323, 248