



INDEX

A

AA (Auto Attendant)

- SRST (Survivable Remote Site Telephony), 390–391
- Tcl application, 442

aaa preauth command, 109

address identifiers, ISDN, 139–140

address resolution, 9

address signaling, 115

- E&M (Ear and Mouth), 126
- FXS/FXO, 118–119

advanced busyout (AVBO), 346

alias command, 398

allow-connections command, 65, 110, 397, 556

allow-connections h323 to h323 command, 65

allow-connections h323 to sip command, 65

allow-connections sip to h323 command, 65

analog circuits, 116

- E&M (Ear and Mouth), 123
 - address signaling, 126
 - Type I signaling, 124
 - Type II signaling, 124
 - Type III signaling, 124
 - Type IV signaling, 125
 - Type V signaling, 125

FXO (Foreign Exchange Office), 117

- address signaling, 118–119
- caller ID, 120–121

CAMA (Centralized Automated Message Accounting), 122–123

FXS-DID service, 119

informational signaling, 119–120

power failover, 117

supervisory disconnect, 121–122

supervisory signaling, 117–118

FXS (Foreign Exchange Service), 117

- address signaling, 118–119
- caller ID, 120–121

CAMA (Centralized Automated Message Accounting), 122–123

DID service, 119

informational signaling, 119–120

supervisory disconnect, 121–122

supervisory signaling, 117–118

analog connections, trunk circuits, 146

analog phones, call flow, 33–35

analog ports, local identifier, 28

Analog Telephone Adapter (ATA), 13

ANI (automatic number identification), 116

ani mapping command, 155

application MGCPAPP command, 38

application mgcpapp command, 39, 49

application session command, 98

architectures, IPIPGW (Multiservice IP-to-IP gateway), 553–554

ATA (Analog Telephone Adapter), 13

audio files, Tcl, 450

AuditConnection (AUCX) command, 31

authentication

- gatekeeper security, 483
- IPIPGW (Multiservice IP-to-IP gateway), 562–563

authentication username command, 109

auto attendant. *See* AA

automatic number identification (ANI), 116

AutoQoS, IP WAN QoS, 248–249

AVBO (advanced voice busyout), 346

B

back-to-back user agent (B2BUA), SIP (Session Initiation Protocol), 81

bandwidths

- control, 9
- IP WAN design, 221

Basic ACD, Tcl application, 443

battery-reversal command, 121

BGP (Border Gateway Protocol), 236

billing, IPIPGW (Multiservice IP-to-IP gateway), 568

bind command, SIP voice service configuration, 101

blocking calls, voice translation profiles, 315–316

Border Gateway Protocol (BGP), 236

BRI interface, MGCP backhaul configuration, 39

busyout action graceful command, 337

busyout monitor gatekeeper command, 337

C

CAC (Call Admission Control), 66, 221, 334, 565

- call route selection, 334–336
 - local*, 336–337
 - measurement-based*, 337–346
 - resource-based*, 346–348
 - RSVP*, 348–359
- gatekeepers, 472–475, 496–498
- IP WAN design, 221
- IPIPGW (Multiservice IP-to-IP gateway), 565
 - carrier ID*, 565–566
 - maximum connections*, 565
 - resource thresholds*, 566–567
 - RSVP*, 565

Call Admission Control. See CAC

- call application alternate default command, 39**
- call application voice command, 72, 445, 448**
- call-block disconnect-cause command, 316**
- call-block translation-profile incoming command, 316**
- call command, H.323 voice class option, 62**
- call control agents**
 - CallManager, 14
 - CME (CallManager Express), 14–15
 - EGW (Enterprise Gateway), 15
 - PBX toll bypass, 15
 - SIP proxy server, 15
- call control signaling, optional routing, 9**
- call fallback commands, 344–345**
- call flow**
 - H.323 protocol, 56–58
 - MGCP (Media Gateway Control Protocol), 33
 - analog phones*, 33–35
 - fallback*, 37
 - ISDN connections with backhaul*, 35–36
 - SIP (Session Initiation Protocol), 88
 - Cisco CallManager 5*, 93–95
 - multiple servers*, 92–93
 - proxy server*, 90–92
 - two SIP gateways*, 88–90
- call-forward command, 392–393**
- call forwarding, SRST (Survivable Remote Site Telephony), 392–393**
- call legs, dial peers, 284–285**
- call-manager-fallback command, 383**
- call preservation, remote sites, 398–399**

call route selection

- CAC (Call Admission Control), 334–336
 - local*, 336–337
 - measurement-based*, 337–346
 - resource-based*, 346–348
 - RSVP*, 348–359
- case study, 360–362
- hunt groups, 328
 - digit manipulation*, 330–332
 - huntstop command*, 329–330
 - preference command*, 328–329
- POTS-to-POTS considerations, 359–360
- TEHO (Tail-End Hop-Off), 333–334
- troubleshooting gatekeepers, 505–508
- trunk groups, 332–333
- call service stop command, SIP voice service configuration, 101**
- call signaling, ISDN, 136–137**
- call transfers, SRST (Survivable Remote Site Telephony)**
 - consultative transfers, 392
 - transfer-pattern, 391–392
- call treatment cause-code command, 567**
- caller ID, 116**
 - FXS/FXO, 120–121
 - manipulation, 317–318
- caller-id enable command, 149, 185**
- calling-info command, SIP UA commands, 98**
- calling line identification (CLID), 116**
- calling number identification (CNID), 116**
- calling privileges, COR (Class of Restrictions)**
 - basics, 365–366
 - case study, 374–378
 - implementation, 367–370
 - inbound call restriction, 372–374
 - list assignment with CallManager Express, 371–372
 - list assignment with SRST, 370–371
 - operation, 366–367
- CallManager**
 - call control agents, 14
 - configuration, MGCP (Media Gateway Control Protocol), 40–46
 - deployment scenarios
 - multisite with centralized call control*, 17

- multisite with distributed call control*, 17–18
 - single site deployment*, 16
- gatekeepers, 481, 508–512
- H.323 protocol, 67–69
- registration
 - MGCP (Media Gateway Control Protocol)*, 31–32
 - SIP (Session Initiation Protocol)*, 102–107
- RSVP, 352–353
- SIP (Session Initiation Protocol), 93–95
- SRST (Survivable Remote Site Telephony), 386
- versus dial peers, 295–298
- CallManager Express**
 - COR list assignment, 371–372
 - DSPs transcoding, 434–435
- CAMA (Centralized Automated Message Accounting), 122, 146**
 - FXS/FXO, 122–123
 - POTS trunks, PSTN (public switched telephone network), 154–157
 - signaling format, 146
- carrier IDs, CAC (call admission control), 565–566**
- CAS (channel-associated signaling), 129, 206**
 - PBX connection, 206
 - ports, 7
 - T1 circuits, 129
- cas-custom command, 170**
- case studies**
 - call route selection, 360–362
 - COR (Class of Restrictions), 374–378
 - dial plans, 298–300
 - digit manipulation, 321–323
 - DSPs, 435–437
 - gatekeeper configuration, 536–545
 - H.323 protocol, 73–75
 - introduction, 18–19
 - IPIPGW (Multiservice IP-to-IP gateway), 570–574
 - MGCP (Media Gateway Control Protocol), configuration, 49–51
 - PBX connection, 213–217
 - PSTN (public switched telephone network) connections, 179–180
 - SIP (Session Initiation Protocol), 111–113
 - SRST (Survivable Remote Site Telephony), 405–408
 - study site descriptions, 20
 - Tcl, 451–454
- CC (country code), 140**
- ccm-compatible command, H.323 voice class option, 62**
- ccm-manager fallback-mgcp command, 404**
- ccm-manager music-on-hold command, 40**
- ccm-manager redundant-host command, 45**
- Centralized Automated Message Accounting. See CAMA**
- channel-associated signaling. See CAS**
- circuits**
 - analog, 116
 - E&M (Ear and Mouth)*, 123–126
 - FXO (Foreign Exchange Office)*, 117–123
 - FXS (Foreign Exchange Service)*, 117–123
 - digital, 126–127
 - E1*, 131
 - echo cancellation*, 141–142
 - ISDN*, 134–141
 - R2 signaling*, 131–133
 - T1*, 127–131
 - signaling methods, 115–116
- Cisco CallManager, 5**
 - call control agents, 14
 - configuration, MGCP (Media Gateway Control Protocol), 40–46
 - SIP (Session Initiation Protocol), 93–95
- Cisco CallManager Express (CME), 14–15**
- Cisco Enterprise Gateway (EGW), call control agents, 15**
- Cisco gateways, protocols, 6**
- Cisco proprietary method, sending tones, 70**
- Cisco Voice Portal (CVP), 444**
- class maps**
 - classifying traffic, 222
 - Layer 2*, 226–227
 - Layer 3*, 225–226
 - Layer 4*, 222–225
 - MPLS, 232–239
- Class of Restrictions. See COR**
- clear-channel mode, 207**
- CLID (calling line identification), 116, 317**
- clock source internal command, 193, 215**
- clock source line command, 192**

clock source line primary command, 194, 215
clocking, digital trunks, 191–195
clustering, gatekeeper redundancy, 516–522
CME (Cisco CallManager Express), 14–15
CNID (calling number identification), 116
codec clear-channel command, 210
codec command, 343
codec complexity command, 419–420
codec G711ulaw command, 557
codec-interval, 343
codec-numpackets, 343
codec preference command, 62
codec transparent command, 561
codec-size, 343
codexes
 configuring complexity, 419–420
 DSP voice termination, 418–419
complexity
 codec, 419–420
 flex, 420–421
components, networks, 54–56
compression, IP WAN QoS, 246–248
conference bridges, DSPs, 423–424
conferencing
 DSPs
 configuration, 425–427
 enhanced, 429–432
 SRST (Survivable Remote Site Telephony), 391
configuration
 gatekeepers, 485
 CAC (Call Admission Control), 496–498
 CallManager, 508–512
 case study, 536–545
 dial peers, 490–493
 directory gatekeepers, 500–502
 dynamic prefix registration, 494–496
 gateways, 487–489
 multiple configurations, 498–500
 redundancy, 513–527
 security, 528–536
 technology prefix, 489
 troubleshooting, 503–508
 zone prefix, 490–493
 zones, 486–487
 IPIPGW (Multiservice IP-to-IP gateway),
 556–560
connection plar command, 149–151

connections
 IP WANs, 266
 business application, 219–220
 design, 220–221
 fax services, 249–258
 modems, 249–250, 258–260
 QoS (quality of service), 221–249
 security, 260–266
 MGCP (Media Gateway Control Protocol), 28
 PSTN (public switched telephone network)
 case study, 179–180
 digital trunks, 158–178
 POTS trunks, 147–157
 trunk circuits, 145–147
controller E1 command, 159
controller T1 command, 159
COR (Class of Restrictions), 365
 basics, 365–366
 case study, 374–378
 implementation, 367–370
 inbound call restriction, 372–374
 list assignment with CallManager Express,
 371–372
 list assignment with SRST, 370–371
 operation, 366–367
corlist incoming command, 370
corlist outgoing command, 369
country code (CC), 140
cptone command, 120
cptone GB command, 169
cptone locale command, 185
CreateConnection (CRCX) command, 30
csim start command, 73
CVP (Cisco Voice Portal), Tcl application, 444

D

database url command, 400
debug cch323 h225 command, 73
debug cch323 h245 command, 73
debug ccsip command, 111
debug commands, IPIPGW (Multiservice IP-to-IP gateway), 569–570
debug ephone command, 405
debug fax relay t30 command, 255
debug gatekeeper gup asn1 command, 521–522

- debug h225 asn1 command, 506–507**
- debug h225 command, 73**
- debug h245 command, 73**
- debug ip tcp transaction command, 73**
- debug isdn q921 command, 199–200**
- debug isdn q931 command, 200**
- debug voice ccapi inout command, 405**
- debug voice dial peer command, 405**
- debug voice translation command, 316**
- debug voip ccapi inout command, 73**
- debug voip vtsp session command, 190**
- debug vpm all command, 150, 154–156**
- debug vpm signal command, 172, 190**
- debug vpm signaling, 190**
- debug vtsp all command, 172**
- debugging**
 - gatekeepers, 482–483
 - configuration, 528–530*
 - troubleshooting, 530–536*
 - gateways
 - H.323 protocol, 72*
 - MGCP (Media Gateway Control Protocol), 47*
 - IP WANs, 260–261
 - design, 221*
 - firewalls, 265–266*
 - NAT, 265*
 - V3PN, 264–265*
 - voice media, 261–264*
 - IPIPGW (Multiservice IP-to-IP gateway)
 - H.323 network deployment, 562*
 - HTTP digest authentication, 562–563*
 - TLS (Transport Layer Security), 562*
 - SIP (Session Initiation Protocol), 109–110
 - SRST (Survivable Remote Site Telephony), 399–403
- delay-start operation, address signaling, 126**
- DeleteConnection (DLCX) command, 30**
- deployment**
 - CallManager scenarios
 - multisite with centralized call control, 17*
 - multisite with distributed call control, 17–18*
 - single site deployment, 16*
 - gatekeepers, 476
 - directory gatekeeper, 479*
 - RAI (Resource Availability Indicator), 478–479*
 - redundancy, 476–478*
- designs, IP WANs, 220–221**
- dest-ipaddr command, 343**
- dest-port command, 343**
- dial-peer cor custom name label command, 367**
- dial peer hunt command, 293, 328**
- dial peers, 283–284**
 - call matching
 - inbound, 285–287*
 - operation status, 294–295*
 - outbound, 288–289*
 - outbound targets, 291–293*
 - POTS versus VoIP, 293–294*
 - verification, 289–290*
 - versus CallManager, 295–298*
 - configuration, SIP (Session Initiation Protocol), 98
 - gatekeeper configuration, 490–493
 - gateways, 477
 - H.323 configuration, 62–63
 - inbound versus outbound, 284–285
 - virtual, 384–385
- dial plans, 275**
 - case study, 298–300
 - dial peer matching, 283–284
 - dial peer verification, 289–290*
 - inbound, 284–287*
 - operation status, 294–295*
 - outbound, 288–289*
 - outbound targets, 291–293*
 - POTS versus VoIP, 293–294*
 - versus CallManager, 295–298*
 - distribution, 283
 - H.323 protocol, 60–61
 - MGCP (Media Gateway Control Protocol), 37
 - number plans, 276
 - private, 276–277*
 - PSTN, 278–281*
 - overlapping number plans, 281–282
 - scalable, 283
 - SIP (Session Initiation Protocol), 96–97
 - SRST (Survivable Remote Site Telephony), 387
 - configuring patterns, 389–390*
 - direct extension dialing, 389*
 - H.323 gateways, 388*
 - MGCP gateways, 388–389*

dialed number identification service (DNIS), 116
dialplan-pattern command, 390, 398

DID (direct inward dialing)

FXS (Foreign Exchange Service), 119
 POTS trunk, PSTN (public switched telephone network), 152–154
 signaling format, 146

digest authentication, IPIPGW (Multiservice IP-to-IP gateway), 562–563

digit manipulation

basics, 303–304
 prefix, 306
 stripping, 304–305
 caller ID, 317–318
 case study, 321–323
 forward digits, 305–306
 hunt groups, 330–332
 number expansion, 306–307
 operation order, 318–320
 troubleshooting, 320–321
 voice translation profiles, 307–308
 application, 314–315
 blocking calls, 315–316
 creating, 314
 creating voice rules, 308–309
 regular expressions, 309–314
 testing rules, 316

digit-strip command, 305

digital circuits, 126–127

E1, 131
 echo cancellation, 141–142
 ISDN, 134
 address identifiers, 139–140
 call signaling, 136–137
 IE (Information Elements), 138–139
 NFAS (Non-Facility Associated Signaling), 140
 QSIG (Q Signaling), 141
 switch configuration, 134–136
 R2 signaling, 131
 inter-register signaling, 132–133
 line signaling, 131–132
 T1, 127–129
 CAS (channel-associated signaling), 129
 E&M signaling, 129–130
 FGD (feature group D), 130–131

digital connections, trunk circuits, 147

digital interfaces, local identifier, 29

digital signal level zero, 127

Digital Signal Processors. See DSPs

digital trunks

PBX connection
 E1/T1 physical layer connections, 190–196
 ISDN PRI trunks, 196–205
 tie trunks, 206
 PSTN (public switched telephone network), 158
 E1 R2 trunks, 168–172
 E1/T1 connection, 158–161
 ISDN BRI trunks, 175–178
 ISDN PRI trunks, 162–168
 T1 CAS trunks, 172–175

direct extension dialing, SRST (Survivable Remote Site Telephony), 389

direct-inward-dial command, 288–289

direct inward dialing (DID), FXS (Foreign Exchange Service), 119

directory gatekeepers, 479, 500–502

directory services, PSTN numbering plans, 278

DNIS (dialed number identification service), 116

downloads, Tcl scripts, 444–445

ds0-group command, 209

dscp-based command, 230

dspfarm command, 424

DSPs (digital signal processors), 16, 411

CallManager Express transcoding, 434–435
 case study, 435–437
 configuring resources, 424–425
 enhanced transcoding and conferencing, 429–432
 transcoding and conferencing configuration, 425–427
 function in gateways, 411–412
 resource requirement determination, 412
 conference bridge, 423–424
 sharing, 421–422
 transcoding, 422–423
 various models, 413–414
 voice termination, 414–421

DTMF (Dual-tone Multifrequency), 283

inter-register signaling, 133

IPIPGW (Multiservice IP-to-IP gateway), 563–564

dtmf h245-alphanumeric command, 557
DTMF Relay
 configuration, MGCP (Media Gateway Control Protocol), 46
 H.323 protocol, 70–71
 SIP (Session Initiation Protocol), 107–109
dtmf-relay command, 71, 108
dtmf-relay rtp-nte command, 557
Dual-tone Multifrequency. See DTMF
dynamic prefixes, registration, 494–496

E

E&M (Ear and Mouth), 116
 analog circuits, 123
 address signaling, 126
 Type I signaling, 124
 Type II signaling, 124
 Type III signaling, 124
 Type IV signaling, 125
 Type V signaling, 125
 ports, 7
 signaling
 format, 146
 T1 circuits, 129–130
 trunks, PBX connection configuration, 187–190
e&m-delay-dial signaling, 130
e&m-fgd signaling, 130
e&m-immediate-start signaling, 130
e&m-wink-start signaling, 130
E.164 number resolution, gatekeepers, 469–470
 call routing process, 472
 technology prefixes, 471
 zone prefixes, 470–471
E1 circuits, 131
E1 connections, digital trunks, 190–191
 clocking, 191–195
 verification, 195–196
E1 digital circuit, digital trunks, 158–161
E1 R2, signaling format, 147
E1 R2 trunks, PSTN (public switched telephone network) connection, 168–171
 MGCP, 171
 verification, 171–172
Ear and Mouth. See E&M
echo cancellation, digital circuits, 141–142

EEM (Embedded Event Manager), Tcl application, 444
EGW (Enterprise Gateway), 15
Embedded Event Manager (EEM), 444
emergency services, PSTN numbering plans, 278
encoding command, H.323 voice class option, 62
EndpointConfiguration (EPCF) command, 31
endpoints, MGCP (Media Gateway Control Protocol), 28
Enterprise Gateway (EGW), 15
events, MGCP (Media Gateway Control Protocol), 28
EVM-HD-8FXS/DID model, 153
extension dialing, SRST (Survivable Remote Site Telephony), 389

F

fair-queue command, 230
fallback
 call flow, MGCP (Media Gateway Control Protocol), 37
 MGCP, 39, 403–404
 SRST (Survivable Remote Site Telephony), 382–383
Fast Start, H.323 protocol, 56, 58
fault tolerances, 283
Fax Detect script, Tcl application, 443
fax-relay ecm disable command, 251
fax-relay sg3-to-g3 command, 255
faxes
 IP WANs, 249–255
 Cisco fax relay, 251–252
 passthrough configuration, 256–258
 IPIPGW (Multiservice IP-to-IP gateway), 564
feature group D (FGD), T1 circuits, 130–131
FGD (feature group D), T1 circuits, 130–131
fgd-eana signaling, 130
fgd-os signaling, 130
firewalls, IP WAN security, 265–266
flex complexity, voice termination, 420–421
Foreign Exchange Office. See FXO
Foreign Exchange Station. See FXS
forward digits, manipulation, 305–306
forward-digits 4 command, 67

forward-digits command, 305
forward-digits extra inband command, 395
forwarding calls, SRST (Survivable Remote Site Telephony), 392–393
frame forwarding mode, 207
frame relay
 FRF.12 fragmentation, 242–244
 MLPoFR fragmentation, 244–245
framing command, 159
FRF.12 fragmentation, 242–244
FXO (Foreign Exchange Office), 116, 146
 analog circuits, 117
address signaling, 118–119
caller ID, 120–121
CAMA (Centralized Automated Message Accounting), 122–123
FXS-DID service, 119
informational signaling, 119–120
power failover, 117
supervisory disconnect, 121–122
supervisory signaling, 117–118
 POTS trunk, PSTN (public switched telephone network), 147–151
 signaling format, 146
FXO ports (Foreign Exchange Office ports), 7, 184–186
FXS (Foreign Exchange Station), 116, 146
 analog circuits, 117
address signaling, 118–119
caller ID, 120–121
CAMA (Centralized Automated Message Accounting), 122–123
DID service, 119
informational signaling, 119–120
supervisory disconnect, 121–122
supervisory signaling, 117–118
 signaling format, 146
FXS ports (Foreign Exchange Station ports), 7, 184–186

G

gatekeeper command, 486
Gatekeeper Transaction Message Protocol (GKTMP), 469

Gatekeeper Update Protocol (GUP), 468–469
gatekeepers
 basics, 459–461
 CAC (Call Admission Control), 472–475
 CallManager, 481
 CallManager deployment scenarios
multisite with centralized call control, 17
multisite with distributed call control, 17–18
single site deployment, 16
 clustering, 478
 configuration, 485
CAC (Call Admission Control), 496–498
CallManager, 508–512
case study, 536–545
dial peers, 490–493
directory gatekeepers, 500–502
dynamic prefix registration, 494–496
gateways, 487–489
multiple configurations, 498–500
redundancy, 513–527
security, 528–536
technology prefix, 489
troubleshooting, 503–508
zone prefix, 490–493
zones, 486–487
 deployment models, 476
directory gatekeeper, 479
RAI (Resource Availability Indicator), 478–479
redundancy, 476–478
 E.164 number resolution, 469–470
call routing process, 472
technology prefixes, 471
zone prefixes, 470–471
 H.323 protocol, 12, 55
 role, 8–9
 security, 482–483
 signaling, 461
GKTMP (Gatekeeper Transaction Message Protocol), 469
GUP (Gatekeeper Update Protocol), 468–469
RAS signaling, 461–468
 tokenless call authentication, 483
gateway command, 487

gateways

- call control agents
 - CallManager*, 14
 - CME (CallManager Express)*, 14–15
 - EGW (Enterprise Gateway)*, 15
 - PBX toll bypass*, 15
 - SIP proxy server*, 15
- CallManager deployment scenarios
 - multisite with centralized call control*, 17
 - multisite with distributed call control*, 17–18
 - single site deployment*, 16
- dial peers, 477
- gatekeeper configuration, 487–489
- H.323 protocol, 12, 61
 - CallManager*, 67–69
 - case study*, 73–75
 - DTMF Relay*, 70–71
 - network components*, 55
 - redundancy*, 69–70
 - security*, 72
 - toll bypass*, 65–67
 - troubleshooting*, 72–73
 - voice class configuration*, 62–64
 - voice service commands*, 64–65
- MGCP (Media Gateway Control Protocol)
 - CallManager configuration*, 40–42, 45–46
 - configuration*, 38
 - configuring fallback*, 39
 - DTMF Relay configuration*, 46
 - music on hold enabling*, 40
 - PRI and BRI backhaul configuration*, 39
 - security*, 47
 - source IP address assignment*, 39
- role, 5–7
- SIP (Session Initiation Protocol)
 - call flow*, 88–90
 - CallManager registration*, 102–107
 - dial peer configuration*, 98
 - DTMF Relay*, 107–109
 - security*, 109–110
 - SIP UA configuration*, 98–100
 - toll bypass*, 102
 - voice service configuration*, 101–102
- SRST (Survivable Remote Site Telephony), 383–385

- types, 7
 - routers*, 7
 - standalone voice gateways*, 7–8
 - switch modules*, 8
- GKTMP (Gatekeeper Transaction Message Protocol), 469**
- ground-start signaling, 118**
- group command, 109**
- GUP (Gatekeeper Update Protocol), 468–469**

H

- H.225 specification, H.323 protocol, 53**
- H.235 specification, H.323 protocol, 54**
- H.245 Alphanumeric method, sending tones, 70**
- H.245 Signal method, sending tones, 70**
- H.245 specification, H.323 protocol, 54**
- H.261 specification, H.323 protocol, 54**
- H.263 specification, H.323 protocol, 54**
- H.320 specification, H.323 protocol, 54**
- H.323 networks**
 - gatekeeper signaling, 466–468
 - IPIPGW (Multiserver IP-to-IP gateway), 555, 562
- H.323 protocol, 6, 12, 53, 61**
 - call flow, 56–58
 - CallManager*, 67–69
 - case study*, 73–75
 - cons, 59
 - dial plan, 60–61
 - DTMF Relay*, 70–71
 - fax services passthrough, 257–258
 - gateway security, 72
 - network components, 54
 - gatekeepers*, 55
 - gateways*, 55
 - MCU (multipoint control units)*, 56
 - proxy servers*, 56
 - terminals*, 55
 - pros, 58–59
 - redundancy, 69–70
 - SIP (Session Initiation Protocol) connections, 110
 - specifications, 53–54
 - SRST (Survivable Remote Site Telephony), 388
 - toll bypass, 65–67

- troubleshooting, 72–73
- voice class configuration, 62–64
- voice service commands, 64–65
- when to use, 59–60
- H.450 specification, H.323 protocol, 54**
- H225 command, H.323 voice class option, 62**
- H245 command, H.323 voice class option, 62**
- h323-gateway voip bind sradddr command, 68**
- h323-gateway voip interface command, 487**
- hierarchical gatekeeper implementation, 479**
- hierarchical numbering plans, 283**
- Hot Standby Routing Protocol. *See* HSRP**
- HSRP (Hot Standby Routing Protocol), 477, 513–516**
- HTTP, digest authentication, 562–563**
- hunt groups, call route selection, 328**
 - digit manipulation, 330–332
 - huntstop command, 329–330
 - preference command, 328–329
- huntstop channel command, 391**
- huntstop command, hunt groups, 329–330**

I

- IE (Information Elements), ISDN, 138–139**
- immediate-start operation, address signaling, 126**
- inbound calls, COR restriction, 372–374**
- inbound dial peers, 284–287**
- incoming called-number command, 63**
- Information Elements (IE), ISDN, 138–139**
- information services, PSTN numbering plans, 278**
- informational signaling, 116, 119–120**
- interface bri command, 176**
- interleave, IP WAN QoS, 239–240**
 - frame relay FRF.12 fragmentation, 242–244
 - frame relay MLPoFR, 244–245
 - MLPoATM, 245–246
 - multilink PPP, 240–242
- international calls, PSTN numbering plans, 278**
- Internet Protocol Device Control (IPDC), 25**
- Internet Telephony Service Provider. *See* ITSP**
- inter-register signaling, R2 signaling, 132–133**
- IP addresses**
 - IPIPGW (Multiserver IP-to-IP gateway), 561
 - MGCP source assignment, 39

- ip sla responder command, 341**
- ip source address command, 402**
- IP Telephony Service Providers (ITSP), 10, 80**
- IP WANs, 266**
 - business application, 219–220
 - design, 220–221
 - fax services, 249–251, 254–255
 - Cisco fax relay, 251–252*
 - passthrough configuration, 256–258*
 - T.38 for MGCP gateways, 252*
 - modems, 249–250, 258
 - modem relay, 258–259*
 - passthrough, 259–260*
 - QoS (quality of service), 221–222
 - AutoQoS, 248–249*
 - classifying traffic using class maps, 222–227*
 - compression, 246–248*
 - link fragmentation and interleave, 239–246*
 - MPLS class mapping, 232–239*
 - policy maps, 227–232*
 - security, 260–261
 - firewalls, 265–266*
 - NAT, 265*
 - V3PN, 264–265*
 - voice media, 261–264*
- IPDC (Internet Protocol Device Control), 25**
- IPIPGW (Multiservice IP-to-IP gateway), 551**
 - basics, 551–552
 - architecture, 553–554*
 - H.323 networks, 555*
 - media-handling modes, 554–555*
 - protocol interworking, 556*
 - SIP networks, 555*
 - case study, 570–574
 - configuration, 556–560
 - supported features, 560
 - billing, 568*
 - CAC (call admission control), 565–567*
 - debug commands, 569–570*
 - DTMF interworking, 563–564*
 - faxes, 564*
 - hidden IP addresses, 561*
 - QoS (quality of service), 565*
 - security, 562–563*
 - show commands, 569*

- Tcl scripts*, 568
- transcoding*, 568
- video support*, 560–561
- VSML (voice XML)*, 568
- IPsec, IP WAN security**, 263
- IP-to-IP gateways, role**, 10–11
- ISDN**
 - digital circuits, 134
 - address identifiers*, 139–140
 - call signaling*, 136–137
 - IE (Information Elements)*, 138–139
 - NFAS (Non-Facility Associated Signaling)*, 140
 - QSIG (Q Signaling)*, 141
 - switch configuration*, 134–136
 - PRI trunks, 196–198
 - MGCP*, 201–202
 - QSIG protocol*, 204–205
 - troubleshooting*, 203–204
 - verification*, 198–201
- isdn bchan-number-order command**, 163
- isdn bind-l3 ccm-manager command**, 39, 165, 201
- ISDN BRI, signaling format**, 147
- ISDN BRI ports**, 7
- ISDN BRI trunks, PSTN (public switched telephone network) connection**, 175–177
 - MGCP*, 177–178
 - verification*, 178
- ISDN connections, call flow**, 35–36
- isdn incoming-voice voice command**, 177
- ISDN PRI, signaling format**, 147
- ISDN PRI trunks, PSTN (public switched telephone network)**, 162–164
 - MGCP*, 164–165
 - verification*, 165–168
- isdn protocol-emulate command**, 135
- isdn protocol-emulate network command**, 196
- isdn spid1 command**, 176
- isdn spid2 command**, 177
- isdn switch-type command**, 135, 162, 176
- isdn switch-type primary-qsig command**, 205
- ITSP (Internet Telephony Service Provider)**, 10, 80

J–L

- limit-dn command**, 385
- line signaling, R2 signaling**, 131–132
- linecode command**, 159
- link fragmentation, IP WAN QoS**, 239–240
 - frame relay FRF.12*, 242–244
 - frame relay MLPoFR*, 244–245
 - MLPoATM*, 245–246
 - multilink PPP*, 240–242
- load balancing, gatekeeper redundancy**, 520–521
- local CAC, call route selection**, 336
 - DS0 limitations*, 336
 - LVBO (local voice busyout)*, 337
 - maximum connections*, 336
- local calls, PSTN numbering plans**, 278
- local voice busyout (LVBO)**, 337
- location servers, SIP (Session Initiation Protocol)**, 81
- long distance calls, PSTN numbering plans**, 278
- loop-start signaling**, 118
- lrq forward-queries command**, 501
- lrq reject-resource-low command**, 479
- LVBO (local voice busyout)**, 337

M

- Malicious Call ID (MCID)**, 443
- match ip rtp 16383 2000 command**, 224
- max-conferences command**, 391
- max-conn command**, 336
- max-dn command**, 384
- max-ephones command**, 384
- max-forwards command, SIP UA commands**, 98
- MCID (Malicious Call ID), Tcl application**, 443
- MCUs (multipoint control units)**, 12
 - H.323 protocol*, 12
 - network components, H.323 protocol*, 56
- measurement-based CAC**, 337
 - AVBO (advanced voice busyout)*, 346
 - configuring IP SLA*, 340–342
 - IP Service Assurance Agent and Response Time Reporter*, 342–344
 - IP SLA network monitoring*, 338
 - probable voice quality estimates*, 338–340
 - PSTN fallback*, 344–346

- media, IPIPGW (Multiservice IP-to-IP gateway), 554–555**
 - media flow-through/flow-around command, 556**
 - Media Gateway Control Protocol. *See* MGCP**
 - media termination point (MTP), 16**
 - messages**
 - MGCP (Media Gateway Control Protocol), 29–31
 - SIP (Session Initiation Protocol), 82–88
 - metacharacters, 309**
 - MGCP (Media Gateway Control Protocol), 6, 11, 25–26**
 - basics, 26–27
 - cons*, 28
 - pros*, 27
 - call flow, 33
 - analog phones*, 33–35
 - fallback*, 37
 - ISDN connections with backhaul*, 35–36
 - CallManager configuration, 40–42, 45–46
 - case study, 49–51
 - configuring fallback, 39
 - dial plan, 37
 - DTMF relay configuration, 46
 - E1 R2 trunks, 171
 - fallback, 403–404
 - fax services passthrough, 256–257
 - FXO and FXS ports, 186
 - FXO POTS trunk connection, 151
 - gateway configuration, 38
 - ISDN BRI trunks, 177–178
 - ISDN PRI trunk connection, 164–165
 - ISDN PRI trunks, 201–202
 - music on hold enabling, 40
 - operation, 28–29
 - CallManager registration*, 31–32
 - messages*, 29–31
 - PRI and BRI backhaul configuration, 39
 - PSTN (public switched telephone network),
 - FXO POTS trunk connection, 150–151
 - securing gateways, 47
 - source IP address assignment, 39
 - SRST (Survivable Remote Site Telephony), 388–389
 - T1 CAS trunks, 174
 - troubleshooting, 47–49
 - mgcp call-agent command, 45, 201**
 - mgcp command, 38**
 - mgcp modem passthrough command, 256, 259**
 - mgcp modem passthrough mode command, 256**
 - mgcp modem passthrough voip redundancy command, 256**
 - mgcp package-capability command, 26**
 - mgcp tse payload command, 256**
 - MIME (Multipurpose Internet Mail Extension), 80**
 - min-se command, SIP voice service configuration, 101**
 - MLPoATM, link fragmentation and interleave, 245–246**
 - mobiles, PSTN numbering plans, 278**
 - modems, IP WANs, 249–250, 258**
 - modem relay, 258–259
 - passthrough, 259–260
 - ModifyConnection (MDCX) command, 30**
 - modules, switch gateways, 8**
 - moh filename command, 396**
 - moh-live command, 396**
 - MPLS (Multiprotocol Label Switching), 18, 232–239**
 - MTP (media termination point), 16**
 - MTP resources, transcoding, 422–423**
 - multicast discovery, 465**
 - multilink PPP, link fragmentation and interleave, 240–242**
 - multipoint control units. *See* MCUs**
 - Multiprotocol Label Switching (MPLS), 18, 232–239**
 - Multipurpose Internet Mail Extension (MIME), 80**
 - Multiservice IP-to-IP gateway. *See* IPIPGW**
 - music on hold**
 - enabling, MGCP (Media Gateway Control Protocol), 40
 - SRST (Survivable Remote Site Telephony), 396
 - mutual authentication, 562**
-
- N**
-
- namespaces, Tcl gateway configuration, 446–448**
 - NANP (North American Numbering Plan), 279**
 - NAT, IP WAN security, 265**
 - nat command, SIP UA commands, 99**

National (Significant) Number (N(S)N), 140
National Destination Code (NDC), 140
NDC (National Destination Code), 140
network-clock-participate command, 192
network-clock-participate wic 2 command, 416
network-clock-select command, 192
networks
 components, H.323, 54–56
 VoIP. *See* VoIP networks
NFAS (Non-Facility Associated Signaling), 140
no auto grant command, 401
no call service stop command, 65
no mgcp command, 38
Non-Facility Associated Signaling (NFAS), 140
North American Numbering Plan (NANP), 279
NPI (number plan identification), ISDN address identifiers, 139–140
number plan identification (NPI), ISDN address identifiers, 139–140
numbering plans, 276
 overlapping, 281–282
 private, 276–277
 PSTN, 278–279
 NANP (North American Numbering Plan), 279
 UK NNP (UK National Numbering Plan), 279–281
numbers, expansion, 306–307
num-exp command, 307

O

optional call management, 9
optional routing, call control signaling, 9
optional security, 9
Ousterhout, Dr. John, Tcl script, 439
outbound dial peers, 284–285, 288–289
overlapping numbering plans, 281–282

P

paramspace command, 447
passthrough method, 249
 fax services configuration
 H.323, 257–258

IP WAN, 256–257
 SIP, 257–258
 modem services, 259–260
path selection
 CAC (Call Admission Control), 334–336
 local, 336–337
 measurement-based, 337–346
 resource-based, 346–348
 RSVP, 348–359
 case study, 360–362
 hunt groups, 328
 digit manipulation, 330–332
 huntstop command, 329–330
 preference command, 328–329
 POTS-to-POTS considerations, 359–360
 TEHO (Tail-End Hop-Off), 333–334
 trunk groups, 332–333
pattern command, 395
PBX (private branch exchange), 5
 case study, 213–217
 digital trunks
 EI/TI physical layer connections, 190–196
 ISDN PRI trunks, 196–205
 tie trunks, 206
 POTS (plain old telephone service), 184
 configuring FXO and FXS port connections, 184–186
 E&M trunk connection, 187–190
 T-CCS (transparent common channel signaling), 207–213
 toll bypass, 15
physical connections, digital trunks, 190–191
 clocking, 191–195
 verification, 195–196
plain old telephone service. See POTS
policy maps, IP WAN QoS, 227–232
post dial delays, 283
POTS (plain old telephone service), 184
 call route selection, 359–360
 dial peers, 293–294
 PBX connection, 184
 configuring FXO and FXS port connections, 184–186
 E&M trunk connection, 187–190

POTS trunks, PSTN (public switched telephone network), 147

- CAMA connections, 154–157
- DID connection configuration, 152–154
- FXO connection configuration, 147–151

preference command, hunt groups, 328–329**prefix command, 306****prefix digits, manipulation, 306****premium calls, PSTN numbering plans, 278****presence servers, SIP (Session Initiation Protocol), 13, 81****PRI interface, MGCP backhaul configuration, 39****PRI trunks, digital trunks, 196–198**

- MGCP, 201–202
- QSIG protocol, 204–205
- troubleshooting, 203–204
- verification, 198–201

pri-group command, 135, 163**pri-group timeslots command, 39****priority command, 229****private branch exchange. See PBX****private numbering plans, 276–277****protocols**

- H.323, 12, 53, 61
 - call flow*, 56–58
 - CallManager*, 67–69
 - case study*, 73–75
 - cons*, 59
 - dial plan*, 60–61
 - DTMF Relay*, 70–71
 - gateway security*, 72
 - network components*, 54–56
 - pros*, 58–59
 - redundancy*, 69–70
 - specifications*, 53–54
 - toll bypass*, 65–67
 - troubleshooting*, 72–73
 - voice class configuration*, 62–64
 - voice service commands*, 64–65
 - when to use*, 59–60
- IPIPGW (Multiservice IP-to-IP gateway), 555–556
- MGCP (Media Gateway Control Protocol), 11, 25–26
 - basics*, 26–28
 - call flow*, 33–37
 - CallManager configuration*, 40–42, 45–46

case study, 49–51

configuring fallback, 39

dial plan, 37

DTMF Relay configuration, 46

gateway configuration, 38

music on hold enabling, 40

operation, 28–32

PRI and BRI backhaul configuration, 39

securing gateways, 47

source IP address assignment, 39

troubleshooting, 47–49

RTP (Real-Time Transport Protocol), 14

SCCP (skinny client control protocol), 13

SIP (Session Initiation Protocol), 12–13, 79

allowing H.323 connections, 110

basics, 79–88

call flow, 88–95

CallManager registration, 102–107

case study, 111–113

cons, 96

dial peer configuration, 98

dial plan, 96–97

DTMF Relay, 107–109

pros, 95

security, 109–110

SIP UA configuration, 98–100

toll bypass, 102

troubleshooting, 110–111

voice service configuration, 101–102

when to use, 96

proxy command, 398**proxy servers**

- network components, H.323 protocol, 56
- SIP (Session Initiation Protocol), 13
 - call flow*, 90–92
 - functional components*, 81

PSTN (public switched telephone network), 5, 145

case study, 179–180

digital trunks, 158

E1 R2 trunks, 168–172

E1/T1 connection, 158–161

ISDN BRI trunks, 175–178

ISDN PRI trunks, 162–168

T1 CAS trunks, 172–175

fallback, measurement-based CAC, 344–346

numbering plans, 278–281

POTS trunks, 147
 CAMA connections, 154–157
 FXO connection configuration, 147–154
 trunk circuits, 145–147

public switched telephone network. *See* PSTN

PVDM versus PVDM2, 414

PVDM2 versus PVDM, 414

Q

Q Signaling. *See* QSIG

QoS (quality of service), 221

IP WAN design, 221

IP WANs, 221–222

AutoQoS, 248–249

classify traffic using class maps, 222–227

compression, 246–248

link fragmentation and interleave,
 239–246

MPLS class mapping, 232–239

policy maps, 227–232

IPIPGW (Multiservice IP-to-IP gateway), 565

QSIG (Q Signaling), 141

ISDN digital circuits, 141

PRI trunks, 204–205

quality of service. *See* QoS

R

R2 signaling, 131

inter-register signaling, 132–133

line signaling, 131–132

R2-Compelled inter-register signaling, 133

R2-Noncompelled inter-register signaling, 133

R2-Semi-compelled inter-register signaling, 133

RAI (Resource Availability Indication), 348, 478

gatekeeper deployment models, 478–479

gatekeeper redundancy, 522–527

resource-based CAC, 348

random-detect command, 230

random-detect dscp-based command, 230

RAS signaling, gatekeeper signaling, 461–464

discovery, 464–465

H.323 call flow, 466–468

Real-Time Transport Control Protocol (RTCP),
 14

Real-Time Transport Protocol (RTP), 6, 14

redirect contact order command, SIP voice

service configuration, 101

redirect ip2ip command, 98, 101

redirect servers, SIP (session initiation protocol),
 13, 81

redundancy

CallManager, MGCP (Media Gateway Control
 Protocol), 45–46

gatekeeper configuration

clustering, 516–520

HSRP (Hot Standby Routing Protocol),
 513–516

load balancing, 520–521

RAI (Resource Availability Indication),
 522–527

troubleshooting gatekeeper cluster,
 521–522

gatekeeper deployment models, 476–478

H.323 protocol, 69–70

register servers, SIP (Session Initiation Protocol),
 81

registrar command, SIP UA commands, 99

registrar server command, 101, 397

registrar servers, SIP (session initiation protocol),
 13

registration, troubleshooting gatekeepers,
 503–505

regular expressions, voice translation profiles,
 309

changing call type or numbering plan, 313–314

deleting specific digits, 312

rerouting call over PSTN, 310–312

sets and replacement digits, 312–313

relay method, 249

remote sites

call preservation, 398–399

MGCP gateway fallback, 403–404

SRST (Survivable Remote Site Telephony).

See SRST

residential gateways, 26

Resource Availability Indication. *See* RAI

resource-based CAC, call route selection, 346

gatekeeper zone bandwidth, 347

local system resources, 346–347
 RAI (Resource Availability Indication), 348
Response Time Reporter (RTR), 342–344
restoral time, SRTS (Survivable Remote Site Telephony), 383
retry command, SIP UA commands, 99
ring number command, 148
routers, gateway type, 7
RSVP
 call route selection, 348–349
 agent configuration, 354–358
 CallManager controlled, 352–353
 configuring gateway controlled RSVP, 351–352
 gateway controlled RSVP, 349–350
 IntServ/DiffServ model, 358
 voice network incorporation, 358–359
 IPIP GW (Multiservice IP-to-IP gateway), 565
RTCP (Real-Time Transport Control Protocol), 14
RTP (Real-Time Transport Protocol), 6, 14
RTP-NTE method, sending tones, 70
RTR (Response Time Reporter), 342–344

S

SAA (Service Assurance Agent), 342–344
SBC (Session Border Controller), 551
 IPIP GW (Multiservice IP-to-IP gateway)
 basics, 551–556
 case study, 570–574
 configuration, 556–560
 supported features, 560–570
scalable dial plans, 283
SCCP (Skinny Client Control Protocol), 6, 13
scripts
 Tcl application, 446
 Tcl download, 444–445
 Tcl implementation, 448–450
secondary-dialtone digit command, 390
secure RTP, IP WAN security, 261–263
Secure versions of RTP (SRTP), 14
security
 gatekeepers, 482–483
 configuration, 528–530
 troubleshooting, 530–536

gateways
 H.323 protocol, 72
 MGCP (Media Gateway Control Protocol), 47
 IP WANs, 260–261
 design, 221
 firewalls, 265–266
 NAT, 265
 V3PN, 264–265
 voice media, 261–264
 IPIP GW (Multiservice IP-to-IP gateway)
 H.323 network deployment, 562
 HTTP digest authentication, 562–563
 TLS (Transport Layer Security), 562
 SIP (Session Initiation Protocol), 109–110
 SRST (Survivable Remote Site Telephony), 399–403
security password level command, 72
security token required-for registration command, 72
serialization delay, 239
Service Assurance Agent (SAA), 342–344
service mgcp command, 39
service-policy command, 222
service voip configuration mode, 556
Session Border Controller. See SBC
Session Initiation Protocol. See SIP
Session protocol command, 557
session protocol sipv2 command, 557
session target command, 557
session target ras command, 490
session transport command, 98, 101
SGCP (Simple Gateway Control Protocol), 25
sharing DSPs, 421–422
show atm vc command, 246
show ccm-manager backhaul command, 39
show ccm-manager command, 47–48, 203–204
show class-map command, 226, 232
show commands, 519, 569
show controller command, 195–196
show controller e1 command, 161
show dial-peer voice command, 384
show dial-peer voice summary command, 72
show dialplan number command, 73, 307
show ephone command, 405
show frame-relay fragment command, 244
show gatekeeper calls command, 493

- show gatekeeper endpoints command, 488, 503
- show gatekeeper zone prefix command, 490
- show gatekeeper zone status command, 497
- show h323 gateway command, 73
- show interface multilink 1 command, 241
- show ip sla statistics command, 341
- show isdn status command, 39, 135, 178, 198–199, 203
- show mgcp command, 49, 253
- show mgcp endpoint command, 49
- show network-clocks command, 191
- show policy interface command, 230–232, 243–244
- show policy-map command, 232
- show policy-map interface command, 246
- show queuing command, 232
- show run command, 71
- show sip-ua command, 110
- show sip-ua statistics command, 111
- show sip-ua status command, 100–102
- show voice call summary command, 171, 175, 213
- show voice dsp voice command, 415–417
- show voice port command, 49, 149, 154–156, 188–189
- show voice port summary command, 149, 154, 171, 174, 185, 213
- show voice translation-profile command, 316
- show voice translation-rule command, 316
- signal cama command, 155
- signal did command, 153
- signal encryption, 562
- signal type subcommand, 185
- signaling
 - circuits, 115–116
 - gatekeepers, 461
 - GKTMP (*Gatekeeper Transaction Message Protocol*), 469
 - GUP (*Gatekeeper Update Protocol*), 468–469
 - RAS, 461–468
 - sides, 187
- signals, MGCP (*Media Gateway Control Protocol*), 28
- Simple Gateway Control Protocol (SGCP), 25
- SIP (*Session Initiation Protocol*), 6, 12–13, 79
 - allowing H.323 connections, 110
 - basics, 79–81
 - functional components*, 81–82
 - messages*, 82–88
 - call flow, 88
 - Cisco CallManager 5*, 93–95
 - multiple servers*, 92–93
 - proxy server*, 90–92
 - two SIP gateways*, 88–90
 - CallManager registration, 102–107
 - case study, 111–113
 - cons, 96
 - dial peer configuration, 98
 - dial plan, 96–97
 - DTMF Relay, 107–109
 - fax services passthrough, 257–258
 - pros, 95
 - proxy server, call control agents, 15
 - security, 109–110
 - SIP UA configuration, 98–100
 - toll bypass, 102
 - troubleshooting, 110–111
 - voice service configuration, 101–102
 - when to use, 96
- SIP ACK message, 88
- sip command, 101
- SIP INVITE message, 85–86
- SIP networks, IPIPGW (*Multiservice IP-to-IP gateway*), 555
- SIP OK responses, 87–88
- SIP Ringing responses, 87
- SIP SDP message, 86
- sip-server command, SIP UA commands, 99
- SIP SRST gateways, 397
 - SIP registrar server configuration, 397
 - voice register pool, 397–398
- SIP Trying responses, 87
- sip-ua command, 98
- SIP UA configuration, SIP (*Session Initiation Protocol*), 98–100
- sip-ua configuration mode, 563
- Skiny Client Control Protocol (SCCP), 6, 13
- SN (*Subscriber Number*), 140
- source-ipaddr command, 343
- source-port, 343
- specifications, H.323 protocol, 53–54
- SRST (*Survivable Remote Site Telephony*), 27, 381
 - basics, 381–382
 - fallback*, 382–383
 - restoral time*, 383
 - case study, 405–408

- configuration
 - CallManager*, 386
 - gateway*, 383–385
- COR list assignment, 370–371
- dial plan, 387
 - configuring patterns*, 389–390
 - direct extension dialing*, 389
 - H.323 gateways*, 388
 - MGCP gateways*, 388–389
- features
 - AA (Auto Attendant)*, 390–391
 - call transfers*, 391–392
 - conferencing*, 391
 - forwarding calls*, 392–393
 - maximum line appearances*, 391
 - music on hold*, 396
 - voice-mail*, 393–396
- security, 399–403
- SIP SRST gateway, 397
 - SIP registrar server configuration*, 397
 - voice register pool*, 397–398
- troubleshooting, 404–405
- SRTP (Secure versions of RTP), 14**
- standalone voice gateways, 7–8**
- station-id command, 121**
- station ID commands, caller ID manipulation, 318**
- station-side connections, 184**
- stripping, digit manipulation, 304–305**
- Subscriber Number (SN), 140**
- subscription maximum command, SIP voice service configuration, 101**
- supervisor disconnect command, 150**
- supervisory disconnect, FXS/FXO, 121–122**
- supervisory signaling**
 - circuits, 115
 - FXS/FXO, 117–118
- Survivable Remote Site Telephony. See SRST**
- switches, gateway modules, 8**

T

- trunks, PSTN (public switched telephone network) connection, 172–175
- T1 circuits, 127–129**
 - CAS (channel-associated signaling), 129
 - E&M signaling, 129–130
 - FGD (feature group D), 130–131
- T1 connections, digital trunks, 190–191**
 - clocking, 191–195
 - verification, 195–196
- T1 digital circuits, digital trunks, 158–161**
- T1/E1 PRI ports, 7**
- T-CCS (transparent common channel signaling), 207–213**
- Tail-End Hop-Off (TEHO), 333–334**
- Tcl (Toolkit Command Language), 439**
 - applications
 - AA (auto attendant)*, 442
 - Basic ACD*, 443
 - CVP (Cisco Voice Portal)*, 444
 - EEM (Embedded Event Manager)*, 444
 - Fax Detect script*, 443
 - MCID (Malicious Call ID)*, 443
 - T.37 Store and Forward Fax*, 443
 - audio files, 450
 - basics, 439–442
 - case study, 451–454
 - configuring gateway, 445
 - initializing and specifying parameters*, 445
 - packages and parameter namespaces*, 446–448
 - script application*, 446
 - downloading scripts from Cisco, 444–445
 - restrictions, 451
 - script implementation, 448–450
- Tcl scripts (Toolkit Command Language scripts), 568**
- technology prefixes**
 - configuration, 489
 - E.164 number resolution, 471
- TEHO (Tail-End Hop-Off), 333–334**
- telephony-service command, H.323 voice class option, 62**
- terminals, H.323 protocol, 12, 55–56**
- test voice translation-rule command, 316**
- T.37 Store and Forward Fax, Tcl application, 443**
- T.120 specification, H.323 protocol, 54**
- T1 CAS**
 - signaling format, 147

timers command, SIP UA commands, 99**TLS**

- IP WAN security, 263–264
- IPIPGW (Multiservice IP-to-IP gateway) security, 562

toll bypass

- configuration, SIP (Session Initiation Protocol), 102
- H.323 protocol, 65–67
- PBX, 15

toll calls, PSTN numbering plans, 278**toll-free calls, PSTN numbering plans, 278****TON (type of number), ISDN address identifiers, 139–140****Toolkit Command Language. See Tcl****Toolkit Command Language scripts (Tcl scripts), 568****traffic, classifying using class maps, 222**

- Layer 2, 226–227
- Layer 3, 225–226
- Layer 4, 222–225

transcoding, 411

- DSPs
 - CallManager Express*, 434–435
 - configuration*, 425–427
 - enhanced*, 429–432
- IPIPGW (Multiservice IP-to-IP gateway), 568

transfer-pattern command, 391–392**transfer-system command, 392****translation-profile command, 315****translation profiles, voice, 307–308**

- application, 314–315
- blocking calls, 315–316
- creating, 314
- creating voice rules, 308–309
- regular expressions, 309–314
- testing rules, 316

translation rules, 307**transparent common channel signaling (T-CCS), 207–213****transport switch udp tcp command, SIP voice service configuration, 101****troubleshooting**

- digit manipulation, 320–321
- gatekeeper clustering, 521–522
- gatekeeper security, 530–536

gatekeepers, 503

- call routing issues*, 505–508

- registration issues*, 503–505

gateways, H.323 protocol, 72–73

- MGCP (Media Gateway Control Protocol), 47–49

- PRI trunks, 203–204

- SIP (Session Initiation Protocol), 110–111

- SRST (Survivable Remote Site Telephony), 404–405

trunk circuits, PSTN (public switched telephone network), 145–146

- analog connections, 146

- digital connections, 147

trunk groups

- call route selection, 332–333

- outbound dial peer targets, 291–292

trunk sides, 187**trunking gateways, 26****trunks, PSTN (public switched telephone network)**

- digital, 158–178

- POTS, 147–157

Type I signaling, E&M (Ear and Mouth), 124**Type II signaling, E&M (Ear and Mouth), 124****Type III signaling, E&M (Ear and Mouth), 124****Type IV signaling, E&M (Ear and Mouth), 125****Type V signaling, E&M (Ear and Mouth), 125****type jitter command, 343****type of number (TON), ISDN address identifiers, 139–140****U****UACs (user agent clients), 81****UAs, SIP (Session Initiation Protocol), 81****UASs (user agent servers), 81****UDP (User Datagram Protocol), 14****udp-jitter command, 340****UK National Numbering Plan (UK NNP), 279–281****UK NNP (UK National Numbering Plan), 279–281****unicast discovery, 464****user agent clients (UACs), 81****user agent servers (UASs), 81**

user agents, SIP (session initiation protocol), 13
 User Datagram Protocol (UDP), 14

V

V3PN, IP WAN security, 264–265
 VIA zones (Voice Infrastructure and Applications zones), 10
 VIC (voice interface cards), 125
 VIC-2CAMA interface module, 155
 VIC-2DID model, 153
 VIC-4FXS/DID model, 153
 VIC2-2FXO interface module, 155
 VIC2-4FXO interface module, 155
 video, IPIPGW (Multiservice IP-to-IP gateway), 560–561
 vm-integration command, 394
 voice class codec command, 62
 voice class h323 10 command, 62
 voice class h323 10 command, 70
 voice-class sip transport switch udp tcp command, 98
 voice classes, H.323 protocol, 62–64
 voice gateways. *See* gateways
 Voice Infrastructure and Applications zones (VIA zones), 10
 voice interface cards (VIC), 125
 voice-mail, SRST (Survivable Remote Site Telephony)
 centralized voice-mail system, 393–396
 CUE integration, 393
 voice media, IP WAN security, 261
 IPsec, 263
 secure RTP, 261–263
 TLS, 263–264
 Voice over IP networks. *See* VoIP networks
 voice-port command, 148, 185
 voice register dn command, 372
 voice register pool configuration command, 372
 voice register pools, SIP SRST gateways, 397–398
 voice rules, creating, 308–309
 voice service command, 64
 voice service commands, H.323 protocol, 64–65
 voice service voip command, 65, 101, 397
 voice service voip configuration mode, 556

voice services, configuration, 101–102
 voice termination, DSPs, 411, 414–418
 codecs, 418–419
 configuring codec complexity, 419–420
 flex complexity, 420–421
 voice translation-profile command, 314
 voice translation-rule command, 308
 voices, translation profiles, 307–308
 application, 314–315
 blocking calls, 315–316
 creating, 314
 creating voice rules, 308–309
 regular expressions, 309–314
 testing rules, 316
 VoiceXML, 439–442
 VoIP, dial peers, 293–294
 voip-incoming translation-profile command, 315
 VoIP networks (Voice over IP networks), 5
 gatekeepers role, 8–9
 gateways
 role, 5–7
 types, 7–8
 IP-to-IP gateways role, 10–11
 protocols
 H.323, 12
 MGCP (*Media Gateway Control Protocol*), 11
 RTP (*Real-Time Transport Protocol*), 14
 SCCP (*skinny client control protocol*), 13
 SIP (*session initiation protocol*), 12–13
 Vonage, 80
 VSML, IPIPGW (Multiservice IP-to-IP gateway), 568

W

WANs
 business application, 219–220
 design, 220–221
 fax services, 249–251, 254–255
 Cisco fax relay, 251–252
 passthrough configuration, 256–258
 T.38 for MGCP gateways, 252
 modems, 249–250, 258
 modem relay, 258–259
 passthrough, 259–260

- QoS (quality of service), 221–222
 - AutoQoS*, 248–249
 - classifying traffic using class maps*, 222–227
 - compression*, 246–248
 - link fragmentation and interleave*, 239–246
 - MPLS class mapping*, 232–239
 - policy maps*, 227–232
- security, 260–261
 - firewalls*, 265–266
 - NAT*, 265
 - V3PN*, 264–265
 - voice media*, 261–264

wink-start operation, address signaling, 126

Z

zone cluster command, 517

zone local command, 486

zone management, 9

zone prefixes

- gatekeeper configuration, 490–493
- gatekeeper E.164 number resolution, 470–471

zones

- gatekeeper configuration, 486–487
- IPIPGW (Multiservice IP-to-IP gateway), 558–560