

Cisco Systems



# A

- ABR (Area Border Router), 206, 216
- access, dedicated networks, 23
- access layer, three-layer hierarchical design model, 6
- access lists, scalable networks, 20
- accessibility, scalable networks, 16, 23
- acknowledgment packets, EIGRP, 141
- ACLs (Access Control Lists), 20
- AD (advertised distance), 139
- adaptability of scalable networks, 15, 22
- addresses
  - IP, 33
    - CIDR, 42–43
    - Class A, 36
    - Class B, 37
    - Class C, 38
    - Class D, 38
    - discontiguous subnets*, 54–55
    - management*, 33
    - private*, 54
    - route aggregation*, 43–45
    - structure*, 34
    - subnetting*, 39–41
    - supernetting*, 43–46
    - troubleshooting*, 41
  - IPv4, 34
    - architecture*, 34–35
    - classes*, 35–39
    - subnet masks*, 39–41
- IS-IS, 256–263
- ISO, 260
- Layer 2 multicast, 279
- loopback, 188
- MAC, 260
- next-hop, 109
- NSAPs, 256, 258
- adjacencies
  - IS-IS, 279
  - OSPF
    - databases*, 171
    - establishing*, 179
- administrative distance, 84, 338–341
- advertised distance (AD), 139
- advertisements
  - loopback addresses, 189
  - LSAs, 88
  - supernets, 397
- AFI (Authority and Format Identifier), 256–258
- aggregate-address command, 397
- aggregation, 43–45, 112
- Aggregator attribute, 398
- algorithms
  - Bellman-Ford, 85. *See also* distance vector routing protocols
  - Dijkstra's, 87. *See also* link-state routing protocols
- DUAL, 132
- SPF, 169, 291

- allocation  
  AFI, 258  
  IP addresses, 42  
  supernetting, 45–46
- alternative paths, scalable networks, 17
- AppleTalk routing protocols, 82
- architecture  
  IPv4 addressing, 34–35  
  IS-IS, 250–255
- Area Border Router (ABR), 206, 216
- area stub command, 224
- areas  
  backbone router requirements, 229  
  OSPF, 169  
    *adding*, 354  
    *configuring*, 186–188  
    *multiarea operation*, 203–220  
    *types of*, 208
- AS (autonomous system), 17, 334, 383
- AS\_Path attribute 394
- ASBR (Autonomous System Boundary Router), 206, 217
- assignments, IS-IS, 261
- Atomic Aggregate attribute, 397
- attributes  
  Aggregator, 398  
  AS\_Path, 394  
  Atomic Attribute, 397  
  BGP, 390–404  
  Local Preference, 398  
  MED, 401  
  Next Hop, 391  
  Origin, 404  
  paths, 374–375  
  scalable internetwork design, 15–24  
  Weight, 401
- authentication  
  OSPF, 191  
  RIPv2, 106, 109, 114–121
- Authority and Format Identifier (AFI), 256
- auto-cost reference-bandwidth command, 190
- automatic route summarization, 120
- autonomous system (AS), 17, 334, 383
- Autonomous System Boundary Router (ASBR), 206, 217
- autonomous systems (BGP), 361–363  
  multihomed nontransit, 364  
  multihomed transit, 365  
  single-homed, 363–364  
  usage selection, 366–367
- autosummarization, EIGRP, 157
- availability of scalable networks, 15–17

## B

- backbone routers  
  area requirements, 229  
  connections, 281  
  IS-IS, 278  
  OSPF, 206, 254
- backup, dial, 18
- backup designated router (BDR), 170, 176, 180
- bandwidth  
  command, 153  
  EIGRP, 132  
  OSPF, 167
- bandwidth-percent command, 154, 155
- BDR (backup designated router), 170, 176 180
- Bellman-Ford algorithm, 85. *See also* distance vector routing protocols

- 
- BGP (Border Gateway Protocol), 361
    - attributes, 390–404
    - autonomous systems, 361–363
      - multihomed nontransit*, 364
      - multihomed transit*, 365
      - single-homed*, 363–364
      - usage selection*, 366–367
    - commands
      - bgp always-compare-med router command*, 402
      - bgp default local-preference command*, 399
    - configuring, 375–376
      - clearing tables*, 380–381
      - continuity inside AS*, 383–384
      - peering*, 381–383
    - decision process, 404
    - default routing, 415–417
    - EBGP multihop, 379–380
    - filtering, 405–412
    - FSM, 371
    - load balancing, 412–414, 417
    - multihomed connections, 418–420
    - operation, 367
      - messages*, 369–371
      - monitoring*, 384–386
      - neighbors*, 368–369, 371–373
      - NLRI*, 373
      - path attributes*, 374–375
      - routing updates*, 367
    - OSPF case study, 466–467
    - redistribution, 421–425
    - redundancy, 412–414
    - routing, 386–388
      - controlling*, 390
      - policies*, 388–390
    - routing policies, 405–412
  - sessions, 377–379
  - symmetry, 412–414, 417
  - bidirectional communication, 172
  - Border Gateway Protocol (BGP)
    - attributes, 390–404
    - autonomous systems, 361–363
      - multihomed nontransit*, 364
      - multihomed transit*, 365
      - single-homed*, 363–364
      - usage selection*, 366–367
    - configuring, 375–376
      - clearing tables*, 380–381
      - continuity inside AS*, 383–384
      - peering*, 381–383
    - decision process, 404
    - default routing, 415–417
    - EBGP multihop, 379–380
    - filtering, 405–412
    - FSM, 371
    - load balancing, 412–414, 417
    - multihomed connections, 418–420
    - operation, 367
      - messages*, 369–371
      - monitoring*, 384–386
      - neighbors*, 368–369, 371–373
      - NLRI*, 373
      - path attributes*, 374–375
      - routing updates*, 367
    - OSPF case study, 466–467
    - redistribution, 421–425
    - redundancy, 412–414
    - routing, 386–388
      - controlling*, 390
      - policies*, 388–390
    - routing policies, 405–412
    - sessions, 377–379
    - symmetry, 412–414, 417

bounded updates, EIGRP, 132  
 broadcasts, helper addresses, 64–67  
 building IP forwarding tables, 301

## C

calculation of routes, 96–99  
 case studies  
   BGP/OSPF routing, 466–467  
   EIGRP, 463–464  
   OSPF, 464–466  
 Catalyst 2950 Series access layer switches, 15  
 Catalyst 3550 Series core layer switches, 12  
 Catalyst 4500 Series core layer switches, 12  
 Catalyst 6500 Series core layer switches, 12  
 CIDR (classless interdomain routing)  
   IP addresses, 42–43  
   link-state routing protocols, 88  
 Cisco 4000 Series Distribution Layer Router, 8  
 Cisco routers. *See also* routers  
   helper addresses, 64–67  
   ISO addressing, 260  
   NETs, 258  
   OSPF, 166–171  
     *adjacencies*, 179  
     *BDR/DR election*, 180–182  
     *commands*, 188–194  
     *configuring*, 186–188  
     *Hello protocol*, 176–179  
     *multiarea operation*, 203–220  
     NBMA, 194–203  
     *network types*, 174–176  
     NSSA, 225–229  
     *operation*, 179  
     *route discovery*, 182–183  
     *route selection*, 183  
   routing information, 184–185  
   states, 171–174  
   stubby areas, 221–224  
   virtual links, 229–233  
 Class A IP addresses, 36  
 Class B IP addresses, 37  
 Class C IP addresses, 38  
 Class D IP addresses, 38  
 Class E IP addresses, 38  
 classes, IPv4 addressing, 35–39  
 classful routing protocols, VSLM, 49–50  
 classless interdomain routing (CIDR)  
   IP addresses, 42–43  
   link-state routing protocols, 88  
 classless route lookups, 112  
 classless routing, 113  
   contiguous subnets, 120  
   VSLM, 49–50  
 clear commands, OSPF, 193  
 clearing BGP tables, 380–381  
 CLNP (Connectionless Network Protocol), 249  
 CLNS (Connectionless Network Service), 247  
 code values, IS-IS PDUs, 266  
 commands  
   *aggregate-address*, 397  
   *area stub*, 224  
   *auto-cost reference-bandwidth*, 190  
   *bandwidth*, 153  
   *bandwidth-percent*, 154, 155  
   bgp  
     *bgp always-compare-med router*, 402  
     *bgp default local-preference*, 399  
   clear, 193  
   debug  
     *EIGRP*, 158  
     *isis adj-packet*, 316

*OSPF*, 193  
*RIP*, 121  
**default**  
*default-information originate*, 91  
*default-metric*, 342, 349  
DHCP servers, 62  
distance, 340  
distance, 95 OSPF configuration, 340  
**distribute-list**, 331–333, 407  
ebgp-multihop 2, 382  
frame relay  
*frame-relay interface-dlci*, 317  
*frame-relay map ip*, 202  
ip, 80  
*ip bandwidth-percent eigrp*, 155  
*ip classless*, 93  
*ip classless global*, 112  
*ip default-network*, 91, 92  
*ip helper-address*, 64, 65  
*ip ospf cost*, 190  
*ip ospf message-digest-key*, 191  
*ip ospf priority*, 189  
*ip prefix-list*, 410, 411  
*ip rip receive version*, 118  
*ip rip send version*, 118  
*ip route*, 80, 334  
*ip subnet-zero*, 47, 113  
*ip summary-address eigrp*, 157  
*ip unnumbered e0*, 57  
isis priority, 248, 316  
is-type, 277  
maximum-paths, 417  
neighbor, 197  
network, 81, 376  
*network 0.0.0.0*, 91  
*network 10.0.0.0*, 327  
*network area*, 187, 188  
no hello padding, 270  
no-auto-summary, 120  
OSPF, 188–194  
passive-interface, 111, 328  
**redistribute**  
*redistribute rip*, 343  
*redistribute rip subnets*, 217  
*redistribute static*, 329  
route-map, 334, 388  
service dhcp, 61  
**show**  
*EIGRP*, 158  
*OSPF*, 193  
*RIP*, 121  
*show clns neighbor*, 319  
*show clns routes*, 299  
*show clns traffic*, 311  
*show frame-relay map*, 315  
*show ip bgp neighbor*, 382  
*show ip bgp neighbors*, 386  
*show ip ospf interface*, 189  
*show ip route*, 77, 131  
*show ip routes*, 301  
*show isis database*, 310  
*show isis routes*, 299  
*show isis topology*, 297  
timers spf, 184  
which-route, 299  
**compatibility**  
EIGRP/IGRP, 130  
RIPv2, 111, 118  
**Complete Sequence Number PDU (CSNP)**, 265  
**components, EIGRP**, 140–148  
**compression, WAN**, 21

**configuration**

- ABR, 216
- ASBR, 217
- authentication (OSPF), 191
- BGP, 375–376
  - clearing tables*, 380–381
  - continuity inside AS*, 383–384
  - EBGP multihop*, 379–380
  - EBGP/IBGP sessions*, 377–379
  - peering*, 381–383
- DHCP, 61
- distance vector routing protocols, 85–86
- dynamic routing, 82–85
- EIGRP, 89, 151–158
  - components*, 140–148
  - design*, 132–133
  - features*, 133–139
  - monitoring*, 158–159
  - operation*, 148–151
- IGRP, 131
- inbound route filters, 332
- integrated IS-IS, 302–312
- IP
  - forwarding tables*, 301
  - helper addresses*, 65
  - unnumbered interfaces*, 57
- link-state routing protocols, 87–89
- loopback addresses, 188
- MED, 403
- one-way route redistribution, 342–346
- OSPF, 186–188
  - commands*, 188–194
  - IS-IS, 254
  - multiarea operation*, 203–220
- NBMA, 194–203
- NSSA, 225–229
- stubby areas*, 221–224
- virtual links*, 229–233
- outbound route filters, 331–333
- passive EIGRP interfaces, 333
- passive interfaces, 328–330
- RIP route redistribution, 351–355
- IPv2, 118–121
- route summarization, 218
- scalable internetworks, 3
  - attributes*, 15–24
  - hierarchical*, 3–15
- static routing, 79, 81, 90
- subinterfaces, 198
- supernet advertisements, 397
- timers, 192
- two-way route redistribution, 346–348

**connected routes, redistributing**, 348–350

**Connectionless Network Protocol (CLNP)**, 249

**Connectionless Network Service (CLNS)**, 247

**connections**

- backbones, 281
- multihomed (BGP), 418–420

**continuity inside AS, BGP**, 383–384

**controlling**

- BGP routing, 390
- routing updates, 327–328

**convergence**, 95–96, 167

- EIGRP, 132, 148, 149
- IS-IS, 247

**core layer, three-layer hierarchical design model**, 5–6

**cost of OSPF**, 170

**CSNP (Complete Sequence NUmber PDU)**, 265

**D**

- data flow, IS-IS, 283  
databases, OSPF, 169  
DDR (dial-on-demand routing), 21  
debug commands. *See also* troubleshooting  
    EIGRP, 158  
    isis adj-packet command, 316  
    OSPF, 193  
    RIPv2, 121–124  
decision processes, BGP, 404  
DECnet Phase V, 252  
dedicated access, scalable networks, 23  
default metrics, IS-IS, 289  
default routing, 89–94, 415–417  
default-information originate command, 91  
default-metric command, 342, 349  
delivery, RTP, 135  
design  
    ABR, 216  
    ASBR, 217  
    authentication (OSPF), 191  
    BGP, 375–376  
        *clearing tables*, 380–381  
        *continuity inside AS*, 383–384  
        *EBGP multihop*, 379–380  
        *EBGP/IBGP sessions*, 377–379  
        *peering*, 381–383  
    DHCP, 61  
    distance vector routing protocols, 85–86  
    dynamic routing, 82–85  
    EIGRP, 89, 151–158  
        *components*, 140–148  
        *design*, 132–133  
        *features*, 133–139  
        *monitoring*, 158–159  
        *operation*, 148–151  
    IGRP, 131  
    inbound route filters, 332  
    integrated IS-IS, 302–312  
    IP  
        *forwarding tables*, 301  
        *helper addresses*, 65  
        *unnumbered interfaces*, 57  
    link-state routing protocols, 87–89  
    loopback addresses, 188  
    MED, 403  
    one-way route redistribution, 342–346  
    OSPF, 186–188  
        *commands*, 188–194  
        *IS-IS*, 254  
        *multiarea operation*, 203–220  
        *NBMA*, 194–203  
        *NSSA*, 225–229  
        *stubby areas*, 221–224  
        *virtual links*, 229–233  
    outbound route filters, 331–333  
    passive EIGRP interfaces, 333  
    passive interfaces, 328–330  
    RIP route redistribution, 351–355  
    RIPv2, 118–121  
    route summarization, 218  
scalable internetworks, 3  
    *attributes*, 15–24  
    *hierarchical*, 3–15  
static routing, 79, 81, 90  
subinterfaces, 198  
supernet advertisements, 397  
timers, 192  
two-way route redistribution, 346–348  
designated intermediate system (DIS), 248  
designated router (DR), 170, 176, 180  
detection of mismatched interfaces, 319

DHCP (Dynamic Handshake Challenge Protocol), 58–64

DHCPOPACK unicast, 60

DHCPOFFER unicast, 60

DHCPREQUEST broadcast, 60

dial backup, 18

dial up access, scalable networks, 23

dialer map statements, 312

dial-on-demand routing (DDR), 21

Diffusing Update Algorithm (DUAL), 132

Dijkstra’s algorithm, 87. *See also* link-state routing protocols

DIS (designated intermediate system), 248

discontiguous subnets, 54–55, 120

discovery

- distance vector networks, 86
- EIGRP, 134
- routes, 173, 182–183

distance commands

- distance, 95 OSPF configuration command, 340
- distance command, 340

distance vector paths, OSPF, 166

distance vector routing protocols, 85–86

distribute-list command, 331–333, 407

distribution layer, three-layer hierarchical design model, 6

Domain-Specific Part (DSP), 256

dotted-decimal notation, 44

Down state, OSPF, 172

DR (designated router), 170, 176, 180

DSP (Domain-Specific Part), 256

DUAL (Diffusing Update Algorithm), 132

DUAL finite-state machine (FSM), 135

dual IS-IS, 252. *See also* IS-IS

dynamic routing, 82–85. *See also* routing

## E

Easy IP, 58–64

EBGP (Enhanced BGP)

- configuring, 377–379
- multihop, 379–380

ebgp-multihop 2 command, 382

efficiency

- bandwidth (EIGRP), 132
- scalable networks, 15, 20

EGPs (Exterior Gateway Protocols), 82, 334

EIGRP (Enhanced Interior Gateway Routing Protocol), 89, 129–132

- case study, 463–464
- components, 140–148
- configuring, 151–158
- convergence, 148
- debug commands, 158
- design, 132–133
- features, 133–139
- IGRP compatibility, 130
- monitoring, 158–159
- operation, 148–151
- packets, 140
- passive interfaces, 333
- route tagging, 147
- show commands, 158
- summarization, 156
- tables, 142, 144

End System Hello (ESH) packets, 251

End System-to-Intermediate System (ES-IS), 250

Enhanced BGP (EBGP)

- configuring, 377–379
- multihop, 379–380

Enhanced Interior Gateway Routing Protocol. *See* EIGRP

- ESH (End System Hello) packets, 251  
 ES-IS (End System-to-Intermediate System), 250  
 event-driven updates, 98  
 Exchange state, OSPF, 174  
 ExStart state, OSPF, 173  
 extended metrics, IS-IS, 290  
 Exterior Gateway Protocols (EGPs), 82, 334  
 external route summarization, 218
- F**
- FD (feasible distance), 139  
 features  
   EIGRP, 133–139  
   RIPv2, 109  
 fields  
   OSPF packet headers, 177  
   TLVs, 262  
 filtering  
   BGP, 405–412  
   routing updates, 331–333  
 finite-state machine (FSM), 371  
 flapping routes, 52  
 floating static routes, 94–95  
 flooding  
   LSPs, 284  
   LSUs, 213, 215  
 formatting  
   ABR, 216  
   ASBR, 217  
   authentication (OSPF), 191  
   BGP, 375–376  
     *clearing tables*, 380–381  
     *continuity inside AS*, 383–384  
     *EBGP multihop*, 379–380  
   *EBGP/IBGP sessions*, 377–379  
   *peering*, 381–383  
 DHCP, 61  
 distance vector routing protocols, 85–86  
 dynamic routing, 82–85  
 EIGRP, 89, 151–158  
   *components*, 140–148  
   *design*, 132–133  
   *features*, 133–139  
   *monitoring*, 158–159  
   *operation*, 148–151  
 IGRP, 131  
 inbound route filters, 332  
 integrated IS-IS, 302–312  
 IP  
   *forwarding tables*, 301  
   *helper addresses*, 65  
   *unnumbered interfaces*, 57  
 IPv6 addresses, 69  
 link-state routing protocols, 87–89  
 loopback addresses, 188  
 LSPs, 270  
 MED, 403  
 messages, 109  
 one-way route redistribution, 342–346  
 OSPF, 186–188  
   *commands*, 188–194  
   *IS-IS*, 254  
   *multiarea operation*, 203–220  
   *NBMA*, 194–203  
   *NSSA*, 225–229  
   *stubby areas*, 221–224  
   *virtual links*, 229–233  
 outbound route filters, 331–333  
 passive EIGRP interfaces, 333  
 passive interfaces, 328–330

- RIP route redistribution, 351–355  
 RIPv2, 118–121  
 route summarization, 218  
 scalable internetworks, 3  
   *attributes*, 15–24  
   *hierarchical*, 3–15  
 static routing, 79, 81, 90  
 subinterfaces, 198  
 supernet advertisements, 397  
 timers, 192  
 two-way route redistribution, 346–348  
**forwarding helper addresses**, 64–67  
**forwarding tables**, 301  
**Frame Relay**  
   commands  
     *frame-relay interface-dlci command*, 317  
     *frame-relay map ip command*, 202  
   full-mesh, 197  
   integrated IS-IS, 313–321  
   partial-mesh, 198  
**FSM (finite-state machine)**, 371  
**full adjacency**, 174  
**full-mesh Frame Relay, OSPF**, 197  
   *filtering*, 405–412  
   *FSM*, 371  
   *load balancing*, 412–414, 417  
   *monitoring*, 384–386  
   *multihomed connections*, 418–420  
   *operation*, 367–375  
   *OSPF case study*, 466–467  
   *redistribution*, 421–425  
   *redundancy*, 412–414  
   *routing*, 386–390  
   *routing policies*, 405–412  
   *sessions*, 377–379  
   *symmetry*, 412–414, 417  
   default routing, 89–94  
   EIGRP, 129–132  
     *components*, 140–148  
     *configuring*, 151–158  
     *design*, 132–133  
     *features*, 133–139  
     *monitoring*, 158–159  
     *operation*, 148–151  
**GOSIP (Government OSI Profile)**, 258  
**groups, OSPF**, 167  
**guidelines for route redistribution**, 341–342

**G**

- gateways**  
 BGP, 361  
   *attributes*, 390–404  
   *autonomous systems*, 361–367  
   *configuring*, 375–384  
   *decision process*, 404  
   *default routing*, 415–417  
   *EBGP multihop*, 379–380

**H**

- headers, packets**, 177  
**Hello messages, IS-IS**, 267  
**hello packets, EIGRP**, 140  
**Hello PDUs**, 256  
**Hello protocol, OSPF**, 176–179  
**helper addresses, IPv4**, 64–67  
**hierarchical design models**, 7–14  
   access layer, 14  
   core layer, 10–12

- distribution layer, 13–14  
routers, 7–9  
three-layer, 4
- hierarchies, routing OSPF**, 204
- high level views, IS-IS operations, 264
- HODSP (High-Order Domain-Specific Part)**, 257
- hub-and-spoke topology, OSPF, 199
- hybrid routing protocols, EIGRP, 89
- I**
- IANA (Internet Assigned Numbers Authority)**, 362
- IBGP (Internal BGP)**, 366, 377–379
- IDI (initial domain identifier)**, 256
- IDP (Interdomain Part)**, 256
- IDRP (Interdomain Routing Protocol)**, 293
- IETF (Internet Engineering Task Force)**, 252
- IGPs (Interior Gateway Protocols)**, 82
- IGRP (Interior Gateway Routing Protocol)**, 129
- default routing, 91
  - EIGRP, 130
- implementation**
- ABR, 216
  - ASBR, 217
  - authentication (OSPF), 191
  - BGP, 375–376
    - clearing tables*, 380–381
    - continuity inside AS*, 383–384
    - EBGP multihop*, 379–380
    - EBGP/IBGP sessions*, 377–379
    - peering*, 381–383
  - DHCP, 61
  - distance vector routing protocols, 85–86
  - dynamic routing, 82–85
  - EIGRP, 89, 151–158
    - components*, 140–148
- design*, 132–133
  - features*, 133–139
  - monitoring*, 158–159
  - operation*, 148–151
- IGRP, 131
- inbound route filters, 332
- integrated IS-IS, 302–312
- IP
- forwarding tables*, 301
  - helper addresses*, 65
  - unnumbered interfaces*, 57
- link-state routing protocols, 87–89
- loopback addresses, 188
- MED, 403
- one-way route redistribution, 342–346
- OSPF, 186–188
  - commands*, 188–194
  - IS-IS*, 254
  - multiarea operation*, 203–220
  - NBMA, 194–203
  - NSSA, 225–229
  - stubby areas*, 221–224
  - virtual links*, 229–233
- outbound route filters, 331–333
- passive EIGRP interfaces, 333
- passive interfaces, 328–330
- RIP route redistribution, 351–355
- RIPv2, 118–121
- route summarization, 218
- routing policies, 407
- scalable internetworks, 3
  - attributes*, 15–24
  - hierarchical*, 3–15
- static routing, 79, 81, 90
- subinterfaces, 198
- supernet advertisements, 397

- timers, 192
  - two-way route redistribution, 346–348
  - inbound filtering, BGP**, 406
  - inbound route filters, configuring**, 332
  - incremental updates, scalable networks, 22
  - Init state, OSPF**, 172
  - initial domain identifier (IDI)**, 256
  - initiation of routing updates, 98
  - injecting routes**, 422
  - input policy engines**, 387
  - Integrated IS-IS**, 253. *See also* IS-IS
    - configuring, 302–312
    - Frame Relay, 313–321
    - IP routing with, 292–301
    - WANs, 312–313
  - interarea route summarization**, 218
  - Interdomain Part (IDP)**, 256
  - Interdomain Routing Protocol (IDRP)**, 293
  - interfaces**
    - detecting, 319
    - IP unnumbered, 57
    - IS-IS, 261
    - multipoint, 316
    - passive, 328–330
    - summarization, 157
  - Interior Gateway Protocols (IGPs)**, 82
  - Interior Gateway Routing Protocol (IGRP)**, 129
    - default routing, 91
    - EIGRP, 130
  - Intermediate System Hello (ISH) packets**, 251
  - Intermediate System-to-Intermediate System (IS-IS)**, 247
    - addressing, 256–263
    - adjacencies, 279
    - architecture, 250–255
    - assigning, 261
  - configuring, 302–312
  - data flow, 283
  - ES-IS. *See also* ES-IS, 251
  - Frame Relay, 313–321
  - Hello messages, 267
  - IP routing with integrated, 292
  - LSP formats, 270
  - metrics, 289
  - networks, 290
  - operations, 263
  - OSI protocols, 248–250
  - overview of, 247–248
  - PDUs, 266
  - routing levels, 275
  - WANs, 312–313
- Internal BGP (IBGP)**, 366, 377–379
- internal routers, OSPF**, 206
- International Telecommunication Union Telecommunication Standardization Sector (ITU-T)**, 248
- Internet Assigned Numbers Authority (IANA)**, 362
- Internet Engineering Task Force (IETF)**, 252
- Internet Protocol. *See* IP**
- Internetwork Packet Exchange (IPX)**, 82
- internetworks**
  - autonomous systems, 361–363
    - multihomed nontransit*, 364
    - multihomed transit*, 365
    - single-homed*, 363–364
      - usage selection*, 366–367
  - floating static routing, 94–95
  - scalable
    - attributes*, 15–24
    - hierarchical design models*, 3–15
      - overview of*, 3
  - static routing, 79–82

**IOS DHCP servers, configuring**, 61

**IP (Internet Protocol)**

addresses

*CIDR*, 42–43

*Class A*, 36

*Class B*, 37

*Class C*, 38

*Class D*, 38

*discontiguous subnets*, 54–55

*management*, 33

*private*, 54

*route aggregation*, 43–45

*structure*, 34

*subnetting*, 39–41

*supernetting*, 43–46

*troubleshooting*, 41

*unnumbered*, 56–58

commands

*ip bandwidth-percent eigrp command*, 155

*ip classless command*, 93

*ip classless global command*, 112

*ip default-network command*, 91, 92

*ip helper-address command*, 64, 65

*ip ospf cost command*, 190

*ip ospf message-digest-key command*, 191

*ip ospf priority command*, 189

*ip prefix-list command*, 410, 411

*ip rip receive version command*, 118

*ip rip send version command*, 118

*ip route command*, 80, 334

*ip subnet-zero command*, 47, 113

*ip summary-address eigrp command*, 157

*ip unnumbered e0 command*, 57

EIGRP, 151

forwarding tables, 301

routing with integrated IS-IS, 292–301

routing protocols, 83

**IPv4 (Internet Protocol version, 4)**

addressing, 34

*architecture*, 34–35

*classes*, 35–39

*subnet masks*, 39–41

DHCP, 58–64

discontiguous subnets, 54–55

Easy IP, 58–64

helper addresses, 64–67

NAT, 55–56

route summarization, 51

VSLM, 46

*routing protocols*, 49–50

*subnet masks*, 46–49

**IPv6 (Internet Protocol version 6)**, 68–71

**IPX (Internetwork Packet Exchange)**, 82

**ISH (Intermediate System Hello) packets**, 251

**IS-IS (Intermediate System-to-Intermediate System)**, 247

addressing, 256–263

adjacencies, 279

*architecture*, 250–255

assigning, 261

configuring, 302–312

data flow, 283

ES-IS, 251

Frame Relay, 313–321

Hello messages, 267

IP routing with integrated, 292

LSP formats, 270

metrics, 289

networks, 290

operations, 263

OSI protocols, 248–250  
 overview of, 247–248  
 PDUs, 266  
 routing levels, 275  
 WANs, 312–313  
**isis priority command**, 248, 316  
**is-type command**, 277  
**ITU-T (International Telecommunication Union Telecommunication Standardization Sector)**, 248

**K**

**keywords**  
 mask, 376  
 no-summary, 222  
 summary-only, 397

**L**

**L2 SPF tree calculations**, 293  
**Layer 2 multicast addresses, IS-IS**, 279  
**layers**  
 access  
*hierarchical design models*, 14  
*three-layer hierarchical design model*, 6  
 core  
*hierarchical design models*, 10–12  
*three-layer hierarchical design model*, 5, 6  
 distribution  
*hierarchical design models*, 13–14  
*three-layer hierarchical design model*, 6  
**NLRI**, 373  
**Level 2 routing**, 248  
**levels, routing (IS-IS)**, 275  
**limitations of RIPv2**, 117  
**links**, 168, 229–233

**link-state advertisements (LSAs)**, 88  
 opaque, 215  
**OSPF**, 207, 255  
**link-state PDUs (LSPs)**, 254  
 flooding, 284  
**IS-IS**, 270  
**link-state routing protocols**, 87–89, 165  
*adjacencies*, 179  
*BDR/DR election*, 180–182  
*commands*, 188–194  
*configuring*, 186–188  
*Hello protocol*, 176–179  
*multiarea operation*, 203–220  
*NBMA*, 194–203  
*network types*, 174–176  
*NSSA*, 225–229  
*operation*, 179  
*overview of*, 166–171  
*route discovery*, 182–183  
*route selection*, 183  
*routing information*, 184–185  
*states*, 171–174  
*stubby areas*, 221–224  
*virtual links*, 229–233  
**lists, access**, 20  
**load balancing**  
 BGP, 412–414, 417  
 scalable networks, 18  
**Loading state, OSPF**, 174  
**Local Preference attribute**, 398  
**lookups, classless route**, 112  
**loopback addresses**  
*configuring*, 188  
*IP addresses (IS-IS)*, 260

loops (EIGRP), 129–132  
 components, 140–148  
 configuring, 151–158  
 design, 132–133  
 features, 133–139  
 monitoring, 158–159  
 operation, 148–151  
**LSAs (link-state advertisements)**, 88  
 opaque, 215  
 OSPF, 207, 255  
**LSPs (link-state PDUs)**, 254  
 flooding, 284  
 IS-IS, 270

## M

**MAC (Media Access Control) addresses**, 260  
**management of IP addresses**, 33  
**mask keyword**, 376  
**maximum transmission unit (MTU)**, 343  
**maximum-paths command**, 417  
**MED (Multiple Exit Discriminator) attribute**, 401  
**Media Access Control (MAC) addresses**, 260  
**members**, OSPF, 167  
**memory**  
 floating static routing, 94–95  
 static routing, 79–82  
**messages**  
 BGP, 369–371  
 Hello, 267  
 RIPv2  
*formatting*, 110  
*multicasting*, 109  
**metrics**  
 IS-IS, 289

routing, 99  
**mismatched interfaces, detecting**, 319  
**mixing nonroutable/routable protocols**, 22  
**models**, BGP routing process, 387. *See also BGP modification*  
 ABR, 216  
 ASBR, 217  
 authentication (OSPF), 191  
 BGP, 375–376  
*clearing tables*, 380–381  
*continuity inside AS*, 383–384  
*EBGP multihop*, 379–380  
*EBGP/IBGP sessions*, 377–379  
*peering*, 381–383  
 DHCP, 61  
 distance vector routing protocols, 85–86  
 dynamic routing, 82–85  
 EIGRP, 89, 151–158  
*components*, 140–148  
*design*, 132–133  
*features*, 133–139  
*monitoring*, 158–159  
*operation*, 148–151  
 IGRP, 131  
 inbound route filters, 332  
 integrated IS-IS, 302–312  
**IP**  
*forwarding tables*, 301  
*helper addresses*, 65  
*unnumbered interfaces*, 57  
 link-state routing protocols, 87–89  
 loopback addresses, 188  
 MED, 403  
 one-way route redistribution, 342–346  
 OSPF, 186–188  
*commands*, 188–194

*IS-IS*, 254  
*multiarea operation*, 203–220  
*NBMA*, 194–203  
, 225–229  
*stubby areas*, 221–224  
*virtual links*, 229–233

outbound route filters, 331–333  
passive EIGRP interfaces, 333  
passive interfaces, 328–330  
RIP route redistribution, 351–355  
RIPv2, 118–121  
route summarization, 218  
routers, 189  
routing policies, 407  
scalable internetworks, 3  
  *attributes*, 15–24  
  *hierarchical*, 3–15  
static routing, 79, 81, 90  
subinterfaces, 198  
supernet advertisements, 397  
timers, 192  
two-way route redistribution, 346–348

**modules**, PDMs, 139  
monitoring BGP, 384–386  
**MTU** (maximum transmission unit), 343  
**multiarea integrated IS-IS configuration**, 305  
**multiarea OSPF operation**, 203–220  
**multicast updates**, RIPv2, 106  
**multicasting**  
  Layer 2 addresses, 279  
  RIPv2, 109

**multihomed connections**, BGP, 418–420  
**multihomed nontransit autonomous systems**, 364  
**multihomed transit autonomous systems**, 365  
**multihop**, EBGP, 379–380

**Multiple Exit Discriminator (MED) attribute**, 401  
**multiple routes**, calculating, 97  
**multipoint interfaces**, Frame Relay, 316

## N

**NAT (Network Address Translation)**  
  IPv4, 55–56  
  private addressing, 54  
**negotiation**, 371–373  
**neighbors**  
  BGP, 368–369, 371–373  
  command, 197  
  EIGRP, 134, 142  
  LSAs, 88  
  OSPF, 194  
  RTP, 135  
**NET (network entity title)**, 250, 258  
**network commands**  
  network 0.0.0.0 command, 91  
  network 10.0.0.0 command, 327  
  network area command, 187, 188  
  network command, 81, 376  
**network entity title (NET)**, 250, 258  
**Network Layer Reachability Information (NLRI)**, 373  
**network service access point (NSAP)**, 250  
**networks**  
  autonomous systems, 361–363  
    *multihomed nontransit*, 364  
    *multihomed transit*, 365  
    *single-homed*, 363–364  
    *usage selection*, 366–367  
  commands. *See* network commands  
  configuring. *See* configuration

- 
- helper addresses, 64–67
  - IP, 151
  - IS-IS, 290
  - non-IP protocols, 83
  - OSPF
    - adjacencies*, 179
    - BDR/DR election*, 180–182
    - commands*, 188–194
    - configuring*, 186–188
    - Hello protocol*, 176–179
    - multiarea operation*, 203–220
    - NBMA, 194–203
    - NNSA, 225–229
    - operation*, 179
    - overview of*, 166–171
    - route discovery*, 182–183
    - route selection*, 183
    - routing information*, 184–185
    - states, 171–174
    - stubby areas*, 221–224
    - types*, 174–176
    - virtual links*, 229–233
  - point-to-multipoint, 200
  - protocols
    - distance vector routing protocols*, 85–86
    - EIGRP, 89
    - link-state routing protocols*, 87–89
  - RIP route redistribution, 351–355
  - routing
    - default*, 89–94
    - dynamic*, 82–85
    - floating static*, 94–95
    - static*, 79–82
  - scalable internetworks
    - attributes of*, 15–24
    - hierarchical design models*, 3–15
  - overview of*, 3
  - WANs
    - compression*, 21
    - integrated IS-IS*, 312–313
    - passive interfaces*, 329
    - private addresses*, 53
  - new features, RIPv2, 109
  - Next Hop attribute, 391
  - next-hop addresses, RIPv2, 109
  - NLRI (Network Layer Reachability Information), 373
  - no auto-summary command, 120
  - no hello padding command, 270
  - non-IP network protocols, 83
  - nonroutable protocols, mixing, 22
  - no-summary keyword, 222
  - notation, dotted decimals, 44
  - not-so-stubby areas, OSPF, 221–224
  - NSAP (network service access point), 250, 258
  - NSAP selector (N-selector), 257
- O**
- one-way route redistribution, configuring, 342–346
  - opaque LSAs, 215
  - Open Shortest Path First. *See* OSPF
  - Open System Interconnection (OSI), 247–250
  - operations
    - BGP, 367
    - messages*, 369–371
    - monitoring*, 384–386
    - neighbors*, 368–373
    - NLRI, 373
    - path attributes*, 374–375
    - routing updates*, 367
  - DHCP, 60

- EIGRP, 148–151
- IS-IS, 263
- OSPF, 179
- RIPv2, 106–107
- optimization**
  - ABR, 216
  - ASBR, 217
  - authentication (OSPF), 191
  - BGP, 375–376
    - clearing tables*, 380–381
    - continuity inside AS*, 383–384
    - EBGP multihop*, 379–380
    - EBGP/IBGP sessions*, 377–379
    - peering*, 381–383
  - DHCP, 61
  - distance vector routing protocols, 85–86
  - dynamic routing, 82–85
  - EIGRP, 89, 151–158
    - components*, 140–148
    - design*, 132–133
    - features*, 133–139
    - monitoring*, 158–159
    - operation*, 148–151
  - IGRP, 131
  - inbound route filters, 332
  - integrated IS-IS, 302–312
  - IP
    - forwarding tables*, 301
    - helper addresses*, 65
    - unnumbered interfaces*, 57
  - link-state routing protocols, 87–89
  - loopback addresses, 188
  - MED, 403
  - one-way route redistribution, 342–346
  - OSPF, 186–188
    - commands*, 188–194
  - IS-IS, 254
  - multiarea operation*, 203–220
  - NBMA, 194–203
  - NSSA, 225–229
  - stubby areas*, 221–224
  - virtual links*, 229–233
  - outbound route filters, 331–333
  - passive EIGRP interfaces, 333
  - passive interfaces, 328–330
  - RIP route redistribution, 351–355
  - RIPv2, 118–121
  - route summarization, 218
  - routing policies, 407
  - scalable internetworks, 3
    - attributes*, 15–24
    - hierarchical*, 3–15
  - static routing, 79, 81, 90
  - subinterfaces, 198
  - supernet advertisements, 397
  - timers, 192
  - two-way route redistribution, 346–348
- Origin attribute**, 404
- OSI (Open System Interconnection)**, 247–250
- OSPF (Open Shortest Path First)**, 165
  - adjacencies, 179
  - areas, 354
  - authentication, 191
  - BDR/DR election, 180–182
  - BGP case study, 466–467
  - case study, 464–466
  - clear commands, 193
  - commands, 188–194
  - configuring, 186–188
  - debug commands, 193
  - full-mesh Frame Relay, 197
  - Hello protocol, 176–179

- 
- hub-and-spoke topology, 199
  - IS-IS, 254
  - LSAs, 207, 255
  - multiarea operation, 203–220
  - NBMA, 194–203
  - network types, 174–176
  - NSSA, 225–229
  - operation, 179
  - overview of, 166–171
  - packet headers, 177
  - partial-mesh Frame Relay, 198
  - point-to-multipoint, 200
  - RIP, 351
  - route discovery, 182–183
  - route selection, 183
  - routers types of, 206
  - routing
    - hierarchies*, 204
    - information*, 184–185
  - show commands, 193
  - states, 171–174
  - stubby areas, 221–224
  - timers, 192
  - updates, 186
  - virtual links, 229–233
- outbound filtering, BGP**, 406
- outbound route filters, configuring**, 331–333
- output policy engines**, 388
- 
- ## P
- packets**
    - EIGRP, 140
    - ESH, 251
    - ISH, 251
    - OSPF, 172, 177
  - routing, 77–79
  - RTP, 135
  - scalable networks, 23
- Partial Sequence Number PDU (PSNP)**, 265
- partial updates, EIGRP**, 132
- partial-mesh Frame Relay, OSPF**, 198
- passive EIGRP interfaces, configuring**, 333
- passive interfaces, configuring**, 328–330
- passive-interface command**, 111, 328
- passwords, IS-IS**, 304
- paths**
  - attributes, 374–375
  - OSPF, 166
  - scalable networks, 17
- PDMs (protocol-dependent modules)**, 139
- PDU (protocol data unit)**, 264–266
- peers**
  - BGP, 381–383
  - routes, 387
- point-to-multipoint OSPF**, 200
- point-to-multipoint WANs**, 312
- point-to-point networks, creating**, 198
- point-to-point serial links, VSLM**, 48
- point-to-point WANs**, 312
- policies**
  - BGP, 405–412
  - routing, 334–336, 388–390
- prioritization, traffic**, 19
- priority, OSPF routers**, 189
- private addressing**, 54
- processing**
  - floating static routing, 94–95
  - static routing, 79–82
- protocol data unit (PDU)**, 264–266
- protocol-dependent modules (PDMs)**, 139

**protocols**

- BGP, 361
  - attributes*, 390–404
  - autonomous systems*, 361–367
  - configuring*, 375–384
  - decision process*, 404
  - default routing*, 415–417
  - EBGP multihop*, 379–380
  - filtering*, 405–412
  - FSM, 371
    - load balancing*, 412–414, 417
    - monitoring*, 384–386
    - multihomed connections*, 418–420
    - operation*, 367–375
  - OSPF case study*, 466–467
  - redistribution*, 421–425
  - redundancy*, 412–414
  - routing*, 386–390
    - routing policies*, 405–412
    - sessions*, 377–379
    - symmetry*, 412–414, 417
- CLNP, 249
  - dynamic routing*, 82–85
- EGPs, 82, 334
  - EIGRP, 129–132
    - case study*, 463–464
    - components*, 140–148
    - configuring*, 151–158
    - convergence*, 148
    - debug commands*, 158
    - design*, 132–133
    - features*, 133–139
    - IGRP compatibility*, 130
    - monitoring*, 158–159
  - PSNP (Partial Sequence Number PDU)*, 265
- IGPs, 82
  - IP. *See IP*
  - IS-IS, 247
    - non-IP networks*, 83
    - nonroutable/routable/routable*, 22
    - OSI, 248–250
    - OSPF, 165
    - RIPv2, 105–118
      - configuring*, 118–121
      - verifying*, 121–124
    - routing*
      - AppleTalk*, 82
      - classless*, 113
      - distance vector routing protocols*, 85–86
      - EIGRP*, 89
      - IP*, 83
      - IPX*, 82
      - link-state routing protocols*, 87–89
      - route calculation*, 96–99
      - VSLM*, 49–50
    - RTMP, 17
    - RTP, 135
    - scalable routing*, 17
    - tunnels*, 18

**Q**

query packets, EIGRP, 142

**R**

rapid convergence, EIGRP, 132

reachability, NLRI, 373

reconfiguration of timers, 280. *See also* configuration

recovery, EIGRP, 134

**redistribute commands**

redistribute rip command, 343

redistribute rip subnets command, 217

redistribute static command, 329

**redistribution**

BGP, 421–425

routes, 336–338

*administrative distance*, 338–341

*connected/static*, 348–350

*guidelines*, 341–342

*one-way configuration*, 342–346

*RIP configuration*, 351–355

*two-way configuration*, 346–348

*verifying*, 350–351

**redundancy**, BGP, 412–414

**relationships**, OSPF, 171–174

**reliability**, scalable networks, 17

**Reliable Transport Protocol (RTP)**, 135

**reply packets**, EIGRP, 142

**requirements**, backbone routers, 229

**responsiveness**, scalable networks, 15, 19

**RFC 1918**, 53

**RIB (Routing Information Base)**, 283

**RIP (Routing Information Protocol)**, configuring, 351–355

**RIPv2 (Routing Information Protocol version 2)**,

105–118

configuring, 118–121

verifying, 121–124

**routable protocols**, mixing, 22

**route switch modules (RSMs)**, 11

**route-map command**, 334, 388

**routers**, 7–14

helper addresses, 64–67

ISO addressing, 260

NETs, 258

OSPF, 166–171

*adjacencies*, 179

*BDR/DR election*, 180–182

*commands*, 188–194

*configuring*, 186–188

*Hello protocol*, 176–179

*multiarea operation*, 203–220

NBMA, 194–203

*network types*, 174–176

NSSA, 225–229

*operation*, 179

*route discovery*, 182–183

*route selection*, 183

*routing information*, 184–185

*states*, 171–174

*stub areas*, 221–224

*virtual links*, 229–233

**routes**

aggregation (IP addresses), 43–45

calculation, 96–99

classless lookups, 112

discovery, 173, 182–183

filtering, 405–412

injecting, 422

peers, 387

redistribution, 336–338  
*administrative distance*, 338–341  
*connected/static*, 348–350  
*guidelines*, 341–342  
*one-way configuration*, 342–346  
*RIP configuration*, 351–355  
*two-way configuration*, 346–348  
*verifying*, 350–351

selection, 183  
states, 146  
successors, 148  
summarization, 120, 218  
    *flapping*, 52  
    *IPv4*, 51  
    *scalable networks*, 22  
tags, 147  
withdrawn, 373

**routing, 77–79**

BGP, 386–388  
    *attributes*, 390–404  
    *autonomous systems*, 361–367  
    *configuring*, 375–384  
    *decision process*, 404  
    *default routing*, 415–417  
    *EBGP multihop*, 379–380  
    *filtering*, 405–412  
    *FSM*, 371  
    *load balancing*, 412–414, 417  
    *monitoring*, 384–386  
    *multihomed connections*, 418–420  
    *operation*, 367–375  
    *OSPF case study*, 466–467  
    *redistribution*, 421–425  
    *redundancy*, 412–414  
    *routing*, 386–390  
    *routing policies*, 405–412

*sessions*, 377–379  
    *symmetry*, 412–414, 417

CIDR, 42–43  
classless, 120  
convergence, 95–96  
DDR, 21  
default, 89–94  
distance vector routing protocols, 85–86  
dynamic, 82–85

EIGRP, 89, 129–132  
    *case study*, 463–464  
    *components*, 140–148  
    *configuring*, 151–158  
    *convergence*, 148  
    *debug commands*, 158  
    *design*, 132–133  
    *features*, 133–139  
    *IGRP compatibility*, 130  
    *monitoring*, 158–159  
    *operation*, 148–151  
    *packets*, 140  
    *passive interfaces*, 333  
    *route tagging*, 147  
    *show commands*, 158  
    *summarization*, 156  
    *tables*, 142, 144

information, 184–185  
IP, 292–301  
IS-IS, 247  
Level 2, 248  
levels, 275  
link-state routing protocols, 87–89  
metrics, 99  
OSPF hierarchies, 204  
passive interfaces, 328–330  
policies, 334–336, 405–412

protocols  
*AppleTalk*, 82  
*classless*, 113  
*IP*, 83  
*IPX*, 82  
*route calculation*, 96–99  
*VSLM*, 49–50  
scalable protocols, 17  
snapshot, 21  
static, 79–82  
    *defaults*, 90  
    *floating*, 94–95  
tables, 83  
    *EIGRP/IGRP*, 131  
    *OSPF*, 170  
    *updates*, 186, 215  
updates  
    *BGP*, 367  
    *controlling*, 327–328  
    *filtering*, 331–333  
**Routing Information Base (RIB)**, 283  
**Routing Information Protocol**. *See RIP*  
**Routing Information Protocol version 2**. *See RIPv2*  
**Routing Table Maintenance Protocol (RTMP)**, 17  
**RSMs (route switch modules)**, 11  
**RTMP (Routing Table Maintenance Protocol)**, 17  
**RTP (Reliable Transport Protocol)**, 135

## S

**scalability**, IS-IS, 247  
**scalable internetworks**  
    attributes of, 15–24  
    hierarchical design models, 3–15  
    overview of, 3  
**scalable networks**, 18, 21

**scalable routing protocols**, 17  
**schemes**, IPv4, 34–35  
**security**  
    authentication, 191  
    scalable networks, 16, 23  
**selection of routes**, 183  
**servers**, IOS DHCP, 61  
**service dhcp command**, 61  
**sessions (BGP)**  
    configuring, 377–379  
    peering, 381–383  
**shortest path first (SPF) algorithm**, 87, 169, 291.  
*See also link-state routing protocols*  
**show commands**  
    *EIGRP*, 158  
    *OSPF*, 193  
    *RIPv2*, 121–124  
    *show clns neighbor command*, 319  
    *show clns routes command*, 299  
    *show clns traffic command*, 311  
    *show frame-relay map command*, 315  
    *show ip bgp neighbor commands*, 382  
    *show ip bgp neighbors command*, 386  
    *show ip ospf interface command*, 189  
    *show ip route command*, 77, 131  
    *show ip routes command*, 301  
    *show isis database command*, 310  
    *show isis routes command*, 299  
    *show isis topology command*, 297  
**single areas**, OSPF, 186–188  
**single autonomous systems**, 363–364  
**SMDS (Switched Multimegabit Data Service)**, 194  
**snapshot routing**, 21  
**speed of OSPF**, 167  
**SPF (shortest path first) algorithm**, 87, 169, 291.  
*See also link-state routing protocols*  
**stability of networks**, EIGRP, 132

**statements, dialer map**, 312

**states**

EIGRP, 146

OSPF, 171–174

**static routes, redistributing**, 348–350

**static routing**, 79–82

defaults, 90

floating, 94–95

**structure of IP addresses**, 34, 39–41

**stubby areas, OSPF**, 221–224

“stuck in active” state routes, EIGRP, 146

**subinterfaces**. *See also interfaces*

hub-and-spoke topology, 200

point-to-point networks, 198

**subnet masks**

discontiguous, 54–55, 120

IPv4 addressing, 39–41

private addresses (with NAT), 54

RIPv2, 109

VSLM, 46–49

**suboptimal IS-IS routing**, 294

**successors, EIGRP**, 145, 148

**summarization**

classless route lookups, 112

EIGRP, 156

interfaces, 157

routes, 120, 218

*flapping*, 52

*IPv4*, 51

*scalable networks*, 22

**summary-only keyword**, 397

**supernetting**, 112

advertisements, 397

allocation, 45–46

IP addresses, 43–45

**Switched Multimegabit Data Service (SMDS)**, 194

**switches**

access layer, 15

Catalyst 2950 Series access layer switches, 15

Catalyst 3550 Series core layer switches, 12

Catalyst 4500 Series core layer switches, 12

Catalyst 6500 Series core layer switches, 12

core layer, 12

**switching scalable networks**, 23

**symmetry, BGP**, 412–414, 417

**synchronization**, 284

## T

**tables**

adjacencies, 279

BGP, 380–381

EIGRP, 142, 144

routing, 77–79, 83

*distance vector routing protocols*, 85

*static*, 81

**tags, routes**, 147

**TCP/IP (Transmission Control Protocol/Internet Protocol)**, 249

**technologies, EIGRP**, 134. *See also EIGRP*

**three-layer hierarchical design model**, 4

**timed updates**, 98

**timers**

OSPF, 192

reconfiguring, 280

**timers spf command**, 184

**TLVs (Type, Length, and Value)**, 262, 270

**topological databases, OSPF**, 169

**topologies**

hub-and-spoke, 199

OSPF, 180

tables, 144

totally stubby areas, OSPF, 221–224  
traffic, prioritization, 19  
troubleshooting  
    BGP, 412–414  
    convergence, 95–96  
    default routing, 93  
    interfaces, 319  
    IP addresses, 41  
        CIDR, 42–43  
        *route aggregation*, 43–45  
        *supernetting*, 45–46  
    IPv6, 68  
    RIPv2, 116–117, 121–124  
    successors, 148  
    “stuck in active” states, 146  
tunnels, protocols, 18  
two-tuple length, prefixes, 373  
two-way route redistribution, configuring, 346–348  
two-way state, OSPF, 172  
Type, Length, and Value (TLVs), 262, 270  
types  
    of areas, 207–208  
    of messages, 369–371  
    of networks  
        IS-IS, 290  
        OSPF, 174–176  
    of packets  
        EIGRP, 140  
        OSPF, 172  
    of routers, 206

**U**  
UDP (User Datagram Protocol), 65  
unnumbered IP addressing, 56–58  
updates  
    BGP, 367  
    incremental, 22  
    OSPF, 186  
    packets (EIGRP), 142  
    passive interfaces, 328–330  
    RIPv2, 106  
    route calculation, 96–99  
    routing  
        *controlling*, 327–328  
        *filtering*, 331–333  
        *tables*, 186, 215  
usage selection, BGP, 366–367

**V**  
values  
    AFI, 259  
    IS-IS PDUs, 266  
variable-length subnet masking (VLSM), 86  
verification  
    BGP, 384–386  
    EIGRP, 158–159  
    multiarea OSPF operation, 220  
    RIPv2, 121–124  
    route redistribution, 350–351  
virtual links, OSPF, 229–233  
VLSM (variable-length subnet masking)  
supernetting, 86  
IPv4, 46  
    *routing protocols*, 49–50  
    *subnet masks*, 46–49  
OSPF, 167  
RIPv2, 106

## **W**

### **WAN (wide area networks)**

- compression, 21
  - integrated IS-IS, 312–313
  - passive interfaces, 329
  - private addresses, 53
- Weight attribute**, 401
- which-route command**, 299
- withdrawn routes**, 373