



INDEX

A

access

- Catalyst 1900 switches, 74–75
- console ports, 41–44
- lists, 35–36
 - command, 317
 - configuring, 315–324
 - extended, 313–314
 - standard, 313–314
- networks, 346–353
- remote users, 361–366
- routers, 366–376
- Telnet
 - configuring vty lines, 50–52
 - creating host tables, 101–103
 - terminal servers, 46–54

adding

- frame-relay map statements, 131
- network, 201–208

addresses

- EA, 457
- IP, 30
 - assigning, 48, 59, 472
 - BRIO interfaces, 249–252
 - Catalyst 1900 switches, 78–81
 - interfaces, 115–116
 - management consoles, 78–81
 - mapping, 118
- loopback, 203
- MAC
 - switching, 70
 - transparent bridging, 69
- summary, 204
- administrative distances by routing protocols, 224
- advertisement receipts, confirming, 165
- algorithms, 187–192, 288
- analysis, routers, 167–168
- ANSI (American National Standards Institute), 450
- applications, 6
 - Cisco IOS
 - backing up, 337–338, 492
 - executing, 330
 - loading, 329
 - searching, 329

- upgrading, , 338–341, 493–494
- HyperTerminal, 43. *See also* HyperTerminal
- Notepad. *See* Notepad
- applying ping command, 354–360
- ARP (Address Resolution Protocol), 118
- AS (autonomous system), 191, 197
- assignment of
 - BRIO interfaces, 249–252
 - IP addresses, 48, 59, 472
- asynchronous lines, 62
 - clearing, 64
 - Telnet, 61
- autosummary, disabling, 204
- AUX (auxiliary), 15

B

backing up

- Cisco IOS software
 - diagrams, 492
 - image files, 337–338
 - configuration files, 342–343
 - router diagrams, 494
- banner motd command, 97
- basic scripts, writing, 103–104, 108–113
- BECN (backward-explicit congestion notification), 453, 457
- bits
 - buckets, 206
 - C/R, 457
- Black Box ISDN Simulator, 27, 497–498
- boot sequences, routers, 329–337
- boot system flash command, 331
- bootstrap code, loading, 329
- BRI (Basic Rate Interface), 239
- bridging, 69
- brief option, 277
- BRIO interfaces
 - IP addresses, 249–252
 - PPP encapsulation, 252–253
- broadcast option, 130
- buckets, 206

C

- C/R bits, 457
- cables
 - connecting, 41–44
 - terminal servers, 56–58
- CAB-OCTAL-ASync cables, 56
- calculations, inverse masks, 314
- Catalyst 1900 switches
 - accessing, 74–75
 - configuring, 73–91, 471
 - diagrams, 478
 - FastForward, 71
 - IP addresses, 78–81
 - naming, 75–76
 - passwords, 77–78
 - Reverse Telnet, 66–67
- CCITT (Consultative Committee on International Telephone and Telegraph), 449
- CDP (Cisco Discovery Protocol), 148–149
- CIDR (classless interdomain routing), 201, 223
- circuits
 - Frame Relay, 451
 - DLCIs, 452
 - PVCs, 452
 - SVCs, 451
 - PVCs, 451
 - SVCs, 451
- Cisco Discovery Protocol (CDP), 148–149
- Cisco IOS software
 - backing up, 337, 492
 - executing, 330
 - loading, 329
 - searching, 329
 - upgrading, 338, 493–494
- clear frame-relay inverse arp command, 130
- clearing asynchronous lines, 64
- CLI (command-line interface), 73
- clock rate command, 463
- COM ports, selecting, 45
- command-line interfaces, routers, 15–22
- commands
 - %Ambiguous, 21
 - access-list, 317
 - banner motd, 97
 - boot system flash, 331
 - clear frame-relay inverse arp, 130
 - clock rate, 463
 - configure, 20
 - configure terminal, 100
 - copy, 52, 342
 - copy flash tftp, 337
 - copy running startup, 342
 - copy running-config startup-config, 52
 - debug dialer packets, 363
 - debug ip igrp, 182
 - debug ip igrp transactions, 183
 - debug ip rip, 167–168
 - description, 123
 - dialer-group, 246
 - enable secret, 16
 - encapsulation frame-relay, 128
 - exec-timeout, 51
 - exec-timeout 0 0, 100
 - exec-timeout 10 5, 100
 - frame-relay lmi-type, 128
 - hostname, 48
 - interface, 119
 - ip access-group, 315–317
 - ip default-network, 232
 - ip host, 62
 - ip subnet-zero, 143
 - mistyped, 99
 - network, 159
 - no auto-summary, 210
 - no exec-timeout, 100
 - no ip domain-lookup, 99
 - notepad, 103
 - passive-interface, 165–170, 183
 - ping, 126
 - applying, 354–360
 - EIGRP, 208
 - IGRP, 184
 - interfaces, 220
 - IPX, 279–291
 - loopback networks, 223
 - verifying interconnectivity, 166–167
 - ping 192.169.2.2, 159
 - ping ipx, 304–307
 - redistribute, 220–222
 - redistribute connected, 254
 - redistribute static, 255
 - router igrp, 178
 - router rip, 159

- show cdp interface serial 0, 148
- show dialer, 263
- show flash, 337–338
- show frame-relay lmi, 122
- show frame-relay map, 123–131, 353
- show frame-relay pvc, 122, 278, 350
- show frame-relay route, 464–466
- show interface, 249
- show interface bri0, 362
- show interface ethernet 0, 281
- show interface ethernet0, 49
- show interface loopback0, 60
- show interface serial 0, 137
- show interfaces serial 0, 135
- show ip eigrp, 357
- show ip eigrp neighbors, 195
- show ip eigrp topology, 213
- show ip interface brief, 347
- show ip protocols, 163, 209–210
- show ip route, 156, 363
- show ip route 192.168.3.0, 356
- show ipx eigrp neighbors, 300
- show ipx interface, 277, 301
- show ipx interface brief, 284, 300
- show ipx interface Ethernet 0, 301
- show ipx route, 300
- show ipx servers, 304
- show ipx traffic, 302–303
- show isdn active, 266
- show isdn status, 248, 361
- show running-config, 52, 60, 211–212
- show sessions, 65
- show version, 330
- Start menu, HyperTerminal, 43
- transport input telnet, 61
- transport input x, 61
- components
 - EIGRP, 188–189
 - Frame Relay, 117–118
 - ISDN, 240–241
 - routers, 13
 - interfaces, 15–22
 - memory, 13–15
 - ports, 15
- concepts, EIGRP, 189–192
- configuration
 - access lists, 315–324
 - Black Box ISDN Simulator, 497–498
 - Catalyst 1900 switches, 29, 73–91, 471
 - consoles
 - passwords, 96
 - ports, 100–101
 - default routes, 224
 - dialer idle-timeouts, 264–268
 - dialer lists, 258–261
 - DLL, 37
 - EIGRP, 192–193, 195–213
 - enable passwords, 96
 - Ethernet interfaces, 138–143
 - extended access lists, 474
 - files, 342–343
 - Frame Relay interfaces, 118–132
 - gateways, 78–81
 - host names, 94, 96
 - IGRP, 179–185
 - IPX
 - EIGRP, 292–298
 - RIP, 289–292
 - route redistribution, 299–300
 - routing, 288
 - verifying, 300–306
 - ISDN switches, 246–248
 - loopback interfaces, 145–148
 - MOTD banners, 97–98
 - network layers, 38
 - networks, 494
 - numbers that routers call from, 261–263
 - OSI reference model, 5–8
 - physical layers, 37
 - point-to-point serial interfaces, 132–138
 - Reverse Telnet, 65
 - RIP, 155–163, 163–172
 - routers, 29, 37, 382, 400–409, 411–415, 417–429, 431–441, 443–445, 471
 - backing up, 494
 - diagrams, 476–487
 - Frame Relay switches, 460–466
 - IPX, 274–285
 - loading, 329
 - searching, 329
 - running configurations, 52
 - standard access lists, 474
 - static routes, 254–258
 - summary addresses, 204

- switches, 449–450
- terminal servers, 28, 54–67, 381–382, 470
 - saving, 62–63
 - Telnet, 46–54
 - testing, 62–63
- Token Ring interfaces, 143–145
- virtual terminal lines, 50–52
- VLAN, 81–91
- vty passwords, 96
- configure command, 20
- configure terminal command, 100
- confirmation of advertisement receipts, 165
- congestion. *See also* troubleshooting
 - BECN, 453
 - FECN, 453
 - Frame Relay, 453
- connections
 - console ports, 41–44, 100–101
 - Frame Relay switches, 460
 - ISDN simulators, 497
 - naming, 44
 - physical, 26–27
 - point-to-point, 132–138
 - Reverse Telnet, 58–66
 - VLANs, 71–72
- connectivity
 - interfaces, 115–116
 - IPX, 300–306
 - OSI reference model, 5–8
 - terminal servers, 57
 - troubleshooting, 305
 - verifying, 50, 354
- consoles, 15
 - management
 - configuring gateways/IP addresses, 78–81
 - gateways/IP addresses, 78–81
 - passwords, 96
 - ports
 - accessing, 41–44
 - configuring, 100–101
- context-sensitive help, 18, 20–21
- copy command, 52, 342
- copy flash tftp command, 337
- copy running startup command, 342
- copy running-config startup-config command, 52
- copying
 - Cisco IOS software image files, 337–338

- Notepad, 106
- CPE (customer premises equipment), 240
- CRC (cyclic redundancy check), 454
- customizing, 81
- cut-through switching, 70

D

- data link layer, 8
- DCE (data circuit-terminating equipment), 450
- DDR (dial-on-demand routing), 32, 239, 473
- DE (discard eligibility), 453
- debug dialer packets command, 363
- debug ip igrp command, 182
- debug ip igrp transactions command, 183
- debug ip rip command, 167–168
- default gateways, 78–81
- default routes, configuring, 224
- description command, 123
- devices, Frame Relay, 450
- diagrams
 - Catalyst switches, 478
 - Frame Relay, 479
 - IP/IPX routing tables, 488–492
 - labs, 476–487
 - master, 445
 - router configuration. *See* configuration
 - terminal servers, 47, 476
 - VLANs, 72
- dial strings, specifying, 261–263
- dialer lists, configuring, 258–261
- dialer-group command, 246
- dialers, configuring, 264–268
- direct access, console ports, 41–44
- disabling
 - autosummary, 204
 - DNS lookups, 98–99
 - split horizons, 292–298
- disconnections, Reverse Telnet, 63–66. *See also* connections; troubleshooting
- DLCI (data-link connection identifier), 117, 451–459
- DLL (Data Link Library), configuring, 37
- DNS (Domain Name Service), enabling, 98–99

domains
 IGRP routing, 185
 RIP routing, 172
 routing, 218
 DRAM (dynamic random-access memory), 13
 DTE (data terminal equipment), 450
 DUAL (Diffusing Update Algorithm), 187–192, 288

E

EA (Extended Address), 457
 editing
 mistyped commands, 99
 Notepad, 106
 EIGRP (Enhanced Interior Gateway Routing Protocol), 288, 472
 AS 100, 197
 components, 188–189
 concepts, 189–192
 configuring, 192–193, 195–208
 features, 187–188
 IPX, 34, 288–298, 473
 route redistribution, 217–218, 220–234
 scaling, 288
 troubleshooting, 213, 357
 verifying configuration, 208–213
 Enable mode, 48
 enable passwords, configuring, 96
 enable secret command, 16
 enabling
 DNS lookups, 98–99
 global configuration mode, 246–248
 IGRP, 177–179
 IPX routing, 274–275
 split horizons, 292
 encapsulation
 naming, 272
 PPP, 252–253
 SNAP, 148
 encapsulation frame-relay command, 128
 EPROM (erasable programmable read-only memory), 14
 equipment, labs, 9–10
 errors. *See* troubleshooting

Ethernet
 access, 346–353
 connectivity, 354
 IP addresses, 48
 IPX, 280–284
 verifying, 49
 EXEC levels, 16
 EXEC sessions, 46
 exec-timeout 0 0 command, 100
 exec-timeout 10 5 command, 100
 exec-timeout command, 51
 execution of
 bootstrap code, 329
 Cisco IOS software, 330
 extended access lists, 36, 313–324, 474
 external routes, 191

F

fast convergence, 288
 FastForward switching, 71
 FCS (frame check sequence), 71, 456
 feasible successors, IGRP, 190
 features of EIGRP, 187–188
 FECN (Forward-explicit congestion notification), 453, 457
 files
 configuration, 342–343
 image
 backing up, 337–338
 upgrading, 338–341
 flags, 457
 Flash, 14
 formats
 EIGRP packets, 190
 Frame Relay frames, 456–459
 FragmentFree switching, 71
 Frame Relay
 congestion-control mechanisms, 453
 CRC, 454
 DE, 453
 devices, 450
 diagrams, 479
 frame formats, 456–459
 interfaces, 117

- components, 117–118
- configuring, 118–132
- mapping IP addresses, 118
- IPX, 276–280
- LMI, 454, 456
- routers, 460–466
- switch router, 27
- switches, 449, 459–460
- virtual circuits, 451
 - DLCIs, 452
 - PVCs, 452
 - SVCs, 451
- frame-relay lmi-type command, 128
- frame-relay map statement, 126, 131, 280, 351, 353
- frames, formats, 456–459

G

- gateways, configuring, 78–81
- global configuration mode, 52, 246–248
- GNS (Get Nearest Server), 272

H

- help, context-sensitive, 18–21
- hierarchies, IOS, 16
- hold-down timers, 154
- hop counts
 - limitations, 155
 - RIP. *See* RIP
- hostname command, 48
- hosts
 - names
 - configuring, 94
 - mapping, 62
 - modifying, 48
 - tables, 62, 101–103
- hot keys, CLI, 21
- HyperTerminal, 42
 - command (Start menu), 43
 - starting, 43

I-K

- IGRP (Interior Gateway Routing Protocol), 31, 175, 472
 - configuring, 177–179
 - metrics, 176
 - route redistribution, 217–220, 229–234
 - scalability, 176
 - updates, 175
 - verifying configuration, 179–185
- image files
 - backing up, 337–338
 - upgrading, 338–341
- I-masks, 314
- interconnectivity, 166–167. *See also* connections
- interfaces
 - access lists
 - extended, 313–314
 - standard, 313–314
 - BRI/PRI, 239
 - BRIO
 - assigning IP addresses, 249–252
 - specifying PPP encapsulation, 252–253
 - command, 119
 - connectivity, 115–116
 - Ethernet, 138–143
 - Frame Relay, 117
 - components, 117–118
 - configuring, 118–132
 - IPX, 276–280
 - mapping IP addresses, 118
 - hot keys, 21
 - IP addresses, 115–116
 - LMI, 118, 450–459
 - loopback
 - configuring, 145–148
 - creating, 59–60, 201
 - preventing RIP updates, 168–170
 - ping command, 220
 - point-to-point serial, 132–138
 - routers, 15–22
 - split horizons, 154
 - Token Ring, 143
- Intermediate System-to-Intermediate System (IS-IS), 287
- internal routes, 191
- internetworks, OSI reference model, 5–8

- inventories, 26–27
 - Inverse ARP, 118. *See also* ARP
 - inverse masks, 314
 - IOS
 - executing, 330
 - hierarchies, 16
 - loading, 329
 - searching, 329
 - IP (Internet Protocol)
 - access lists, 313–314
 - addresses
 - assigning, 48, 59, 472
 - BRIO interfaces, 249–252
 - Catalyst 1900 switches, 78–81
 - interfaces, 115–116
 - management consoles, 78–81
 - mapping, 118
 - addressing, 30
 - host tables, 62, 101–103
 - remote users, 361–366
 - resources, 354–360
 - routing tables, 225, 488–492
 - ip access-group command, 315, 317
 - ip default-network command, 232
 - ip default-network statement, 233
 - ip host command, 62
 - ip subnet-zero command, 143
 - IPX (Internetwork Packet Exchange), 33, 271–273, 473
 - EIGRP, 34, 288, 473
 - ping command, 280
 - RIP, 35, 287–288, 474
 - routing, 287
 - configuring, 274–288
 - EIGRP, 292–298
 - redistribution, 299–300
 - RIP, 289–292
 - tables, 431–433, 435–445, 488–492
 - verifying configuration, 300–306
 - ISDN (Integrated Services Digital Network), 32, 239–246
 - Black Box ISDN Simulator, 497–498
 - BRI/PRI, 239
 - components, 240–241
 - DDR, 32, 473
 - dial strings, 261–263
 - dialer idle-timeouts, 264–268
 - Frame Relay, 449
 - legacy DDR, 242–243
 - PPP, 252–253
 - static routes, 254–258
 - switches, 246–248
 - traffic, 258–261
 - IS-IS (Intermediate System-to-Intermediate System), 287
 - ITU-T (International Telecommunications Union-Telecommunications Sector), 450
-
- ## L
-
- labs
 - access lists, 315–324
 - diagrams, 476–487
 - EIGRP, 192–208
 - equipment, 9–10
 - extended access lists, 474
 - IP addresses, 472
 - IPX, 273, 473
 - EIGRP, 292–298, 473
 - RIP, 289–292, 474
 - route redistribution, 299–300
 - routing, 288
 - verifying configuration, 300–306
 - ISDN, 32, 244–246, 473
 - objectives, 27
 - access lists, 35–36
 - Cisco Catalyst switch configuration, 29
 - EIGRP, 31
 - IGRP, 31
 - IP addressing, 30
 - IPX, 33
 - IPX EIGRP, 34
 - IPX RIP, 35
 - ISDN DDR, 32
 - operations, 36
 - RIP, 30
 - route redistribution, 32
 - router configuration, 29
 - terminal server configuration, 28
 - R1, 26–27
 - RIP, 155–163
 - route redistribution, 218–221, 223–234, 473

- routers
 - configuring, 471
 - operations, 327–339, 341–343, 474
- standard access lists, 474
- terminal servers, 470
 - accessing, 43–44
 - configuring, 54–56, 58–67
- LAN (local area network)
 - terminal servers, 53–54
 - VLAN, 71–72
- layers, OSI reference model, 6–8
- legacy DDR, 242–243
- levels, EXEC, 16
- limitations
 - hop counts, 155
 - RIP, 154
- lines
 - asynchronous, 61
 - configuring, 51–52
 - vty, 50–52
- links, 258–261
- lists
 - access, 35–36
 - dialers, 258–261
- LMI (Local Management Interface), 118, 454–459
- loading
 - bootstrap code, 329
 - Cisco IOS software, 329
 - configurations, 329
- logical diagrams, terminal servers, 47
- login, Telnet, 51. *See also* access
- lookups, DNS, 98–99
- loopback interfaces
 - configuring, 145–148
 - creating, 59–60, 201
 - RIP updates, 168–170
- loopback networks, 223
- loops, split horizons, 154

M

- MAC (Media Access Control) addresses
 - switching, 70
 - transparent bridging, 69

- management consoles, 78–81
- manual mappings, 118, 130
- mapping
 - host names, 62
 - IP addresses, 118
 - MAC addresses, 69
 - static, 118
- masks, 314
- master diagrams, 445
- MAU (media attachment unit), 27
- mechanisms
 - Frame Relay congestion-control, 453
 - RIP, 154
- memory, routers, 13–15
- messages, MOTD, 97–98
- metrics
 - IGRP, 176
 - RIP, 153–154
- mistyped commands, troubleshooting, 99
- models, OSI reference, 5–8
- modes
 - Enable, 48
 - EXEC, 16
 - global configuration, 52
 - interface configuration, 249–252
 - line configuration, 51
 - ROM Monitor, 14
 - Shutdown, 48
- modification
 - host names, 48
 - passwords
 - Catalyst 1900 switches, 77
 - troubleshooting, 366–376
- monitoring ROM MONitor mode, 14
- MOTD (message of the day) banners, configuring, 97–98

N

- naming. *See also* resolution
 - Catalyst 1900 switches, 75–76
 - connections, 44
 - encapsulation types, 272
 - hosts
 - configuring, 94–96

- mapping, 62
 - modifying, 48
 - VLAN 1, 83
 - VLAN 2, 85
 - VLAN 3, 87
 - VLAN 4, 89
 - navigation
 - Catalyst 1900 switches, 79
 - hot keys, 21
 - neighbors
 - EIGRP, 195
 - tables, 189
 - networks, 7, 38, 161
 - access, 346–353
 - command, 157
 - configuring, 494
 - ISDN, 239
 - lab equipment, 9–10
 - loopback, 223
 - OSI reference model, 5–8
 - private enterprise, 456
 - PSN, 451
 - public carrier provided, 456
 - symptoms, 354–360
 - next-hop routers, 254, 256–258
 - NLSP (Network Link Services Protocol), 287
 - no auto-summary command, 210
 - no exec-timeout command, 100
 - no ip domain-lookup command, 99
 - Notepad, writing scripts, 103–113
 - notification
 - BECN, 453
 - congestion, 453
 - FECN, 453
 - NT1 (network termination type 1), 240
 - numbers, configuring, 261–263
 - NVRAM (nonvolatile random-access memory), 14
- O**
-
- objectives
 - access lists, 315–324
 - Catalyst switches, 471
 - EIGRP, 192–193, 195–208, 472
 - extended access lists, 474
 - IGRP, 472
 - IP addresses, 472
 - IPX, 273, 473
 - EIGRP, 292–298, 473
 - RIP, 289–292, 474
 - route redistribution, 299–300
 - routing, 288
 - verifying configuration, 300–306
 - ISDN, 32, 244–246, 473
 - labs, 27
 - access lists, 35–36
 - Cisco Catalyst switch configuration, 29
 - EIGRP, 31
 - IGRP, 31
 - IP addressing, 30
 - IPX, 33
 - IPX EIGRP, 34
 - IPX RIP, 35
 - ISDN DDR, 32
 - operations, 36
 - RIP, 30
 - route redistribution, 32
 - router configuration, 29
 - terminal server configuration, 28
 - RIP, 155–163, 472
 - route redistribution, 218, 220–234, 473
 - routers
 - configuring, 471
 - operations, 327–339, 341–343, 474
 - standard access lists, 474
 - terminal servers, 54–56, 58–67, 470
 - operations
 - EIGRP, 208–213
 - IGRP, 179–185
 - IPX, 300–306
 - RIP, 163–172
 - routers, 36, 327–334, 336–343, 474, 492–494
 - options, 81
 - brief, 277
 - broadcast, 130
 - subnet masks, 81
 - transactions, 182
 - OSI
 - application layer, 6
 - data link layer, 8
 - network layer, 7
 - physical layer, 8

- presentation layer, 6
- reference models, 5–8
- session layer, 7
- transport layer, 7
- output. *See also* commands
 - show ip interface brief, 347
 - show frame-relay map command, 350
 - show frame-relay pvc, 350

P-Q

-
- packets
 - EIGRP formats, 190
 - ping, 263
 - RIPs, 154
 - partial updates, IPX EIGRP, 288
 - passive-interface command, 165, 168–170, 183
 - passwords
 - Catalyst 1900 switches, 77–78
 - configuring, 96
 - Telnet, 51
 - troubleshooting, 366–376
 - pasting scripts, 107
 - PBX (private branch exchange), 15
 - PC (personal computer), accessing over LAN/WAN, 53–54
 - physical connections, 26–27. *See also* connections
 - Frame relay switches, 460
 - ISDN simulators, 497
 - physical layers, 8, 37
 - ping 192.169.2.2 command, 159
 - ping command, 126, 263
 - applying, 354–357, 359–360
 - EIGRP, 208
 - IGRP, 184
 - interfaces, 220
 - IPX, 279, 289, 291
 - loopback networks, 223
 - routers, 166–167
 - ping ipx command, 304–307
 - point-to-point serial interfaces, 132–138
 - poison reverse, 155
 - ports
 - COM, 45
 - consoles
 - accessing, 41–44
 - configuring, 100–101
 - routers, 15
 - VLANs, 71–72
 - POPOST (power-on-self-test), 13, 329
 - PPP (Point-to-Point Protocol), 252–253
 - presentation layer, 6
 - prevention of RIP updates, 168–170
 - PRI (Primary Rate Interface), 239
 - private enterprise networks, 456
 - protocols
 - ARP, 118
 - CDP, 148–149
 - EIGRP, 31, 187, 472
 - components, 188–189
 - concepts, 189–192
 - configuring, 192–193, 195–208
 - features, 187–188
 - verifying configuration, 208–211, 213
 - IGRP, 31, 175, 472
 - configuring, 177–185
 - metrics, 176
 - scalability, 176
 - updates, 175
 - IPX, 274–285, 473
 - configuring routing, 288
 - EIGRP, 288–298, 473
 - redistribution, 299–300
 - RIP, 287–292, 474
 - routing, 287
 - verifying configuration, 300–306
 - NLSP, 287
 - RIP, 30, 153
 - configuring, 155–163
 - labs, 472
 - metrics, 153–154
 - scalability limitations, 154
 - stability, 154
 - verifying configuration, 163–172
 - SAP, 272
 - SLARP, 330
 - SNAP, 148
 - Spanning-Tree, 72
 - transporting, 61
 - UDP, 153
 - PSN (packet-switched network), 451

PSTN (Public Switched Telephone Network), 239
 public carrier provided networks, 456
 PVCs (permanent virtual circuits), 118, 451

R

RAM (random-access memory), 13
 redistribute command, 220, 222
 redistribute connected command, 254
 redistribute static command, 255
 redistribution of routes, 32, 229, 473
 IPX, 299–300
 RIP, 217–228
 reference points
 ISDN networks, 241
 OSI reference model, 5–8
 remote users, troubleshooting, 361–366
 resolution, 99. *See also* DNS
 resources
 access, 346–353
 IP, 354–360
 restoration of configuration files, 342–343
 Reverse Telnet, 58
 Catalyst 1900 switches, 66–67
 configuring, 65
 creating IP host tables, 62
 troubleshooting, 63–66
 RIP (Routing Information Protocol), 472
 configuring, 155–163, 163–172
 IPX, 35, 287–292, 474
 lab objectives, 155–163
 metrics, 153–154
 scalability limitations, 154
 stability, 154
 updates, 153
 RIP-1 (RIP Version 1), 154
 RIP-2 (RIP Version 2), 154
 rollover cables, 41. *See also* cables
 ROM (read-only memory), 13
 router igrp command, 178
 router rip command, 159
 routers
 access, 366–376
 analyzing, 167–168
 boot sequences, 329–337

 components, 13
 interfaces, 15–22
 memory, 13–15
 ports, 15
 configuration. *See* configuration
 console ports, 41–44
 diagrams, 476–487
 DNS lookups, 98–99
 Ethernet interfaces, 138–143
 Frame Relay switches, 27, 460–466
 host
 names, 94, 96
 tables, 101–103
 interconnectivity, 166–167
 interfaces, 115–116
 IPX, 274–285
 loopback interfaces, 145–148
 next-hop, 254–258
 numbers, 261–263
 operations, 36, 327–339, 341–343, 474, 492
 point-to-point connections, 132–138
 redistribution, 32
 routing tables, 219
 scripts, 103–104, 108–113
 Token Ring, 145
 troubleshooting, 474–475
 routes
 configuring, 224
 external, 191
 internal, 191
 redistribution, 217–221, 223–234, 473. *See also*
 redistribution of routes
 states, 190
 static, 254, 256–258
 summaries, 223
 summary, 201
 routing
 CIDR. *See also* CIDR
 configuring, 38
 DDR, 32, 239
 domains, 218
 EIGRP domains, 201–208
 hold-down timers, 154
 IGRP domains, 185
 IPX, 287
 configuring, 288
 EIGRP, 288–298

- enabling, 274–275
- redistribution, 299–300
- RIP, 287–292
- verifying configuration, 300–306
- poison reverse, 155
- RIP domains, 172
- split horizons, 154
- tables
 - diagrams, 488–492
 - IP, 225, 431–445
 - IPX, 431–445
 - troubleshooting, 356
- running configurations, saving, 52

S

- SAP (Service Advertisement Protocol), 272
- saving. *See also* backing up
 - Cisco IOS software image files, 337–338
 - RIP configurations, 171–172
 - running configurations, 52
 - terminal server configurations, 62–63
- scalability
 - IGRP, 176
 - EIGRP, 288
 - RIP, 154
- scripts, writing, 103–113
- searching
 - Cisco IOS software, 329
 - configurations, 329
- security
 - access lists, 313
 - extended, 314
 - standard, 313–314
 - Catalyst 1900 switches, 77–78
 - passwords, 366–376
- selection of COM ports, 45
- sequences, 329–337
- servers
 - terminal
 - configuring, 28, 381–382, 470
 - diagrams, 476
 - TFTP
 - backing up configuration files, 342–343
 - upgrading, 338–341
- sessions
 - EXEC, 16, 46
 - layers, 7
 - Telnet. *See* Telnet
- show cdp interface serial 0 command, 148
- show dialer command, 263
- show flash command, 337–338
- show frame-relay lmi command, 122
- show frame-relay map command, 123–131, 350
- show frame-relay pvc command, 122, 278, 350
- show frame-relay route command, 464, 466
- show interface bri0 command, 362
- show interface command, 249
- show interface ethernet 0 command, 281
- show interface ethernet0 command, 49
- show interface loopback0 command, 60
- show interface serial 0 command, 137
- show interfaces serial 0 command, 135
- show ip eigrp interfaces command, 357
- show ip eigrp neighbors command, 195
- show ip eigrp topology command, 213
- show ip interface brief command, 347
- show ip protocols command, 163, 209–210
- show ip route 192.168.3.0 commands, 356
- show ip route command, 156, 363
- show ipx eigrp neighbors command, 300
- show ipx interface brief command, 284, 300
- show ipx interface command, 277, 301
- show ipx interface Ethernet 0 command, 301
- show ipx route command, 300
- show ipx servers command, 304
- show ipx traffic command, 302–303
- show isdn active command, 266
- show isdn status command, 248, 361
- show running-config command, 52, 60, 211–212
- show sessions command, 65
- show version command, 330
- Shutdown mode, 48
- SIMMs (single in-line memory modules), 14
- simulators, Black Box ISDN Simulator, 497–498
- SLARP (Serial Line Address resolution Protocol), 330
- SNAP (Subnetwork Access Protocol), 148
- Spanning-Tree Protocol, 72
- specifying
 - PPP encapsulation, 252–253
 - traffic, 258–261

split horizons, 154
 disabling, 292–298
 EIGRP, 202
 IPX RIP, 292

stability of RIP, 154

standard access lists, 35, 313–321

Standard Frame Relay frames, 456–458

Start menu commands, HyperTerminal, 43

statements
 frame-relay map, 126, 131, 280, 351–353
 ip default-network, 233
 manual map, 130
 network, 161

states, routes, 190

static mappings, 118

static routes, configuring, 254–258

store-and-forward switching, 71

strings, specifying, 261–263

subnet masks, 81

summaries, 201–204, 223

supernetting, 223

SVCs (switched virtual circuits), 451

switches
 Catalyst 1900, 29, 66–67
 configuring, 471
 console ports, 41–44
 diagrams, 478
 Frame Relay, 27, 459–466
 ISDN, 246–248
 VLANs, 71–72, 81–91

switching MAC addresses, 70

symptoms. *See* troubleshooting

T

tables
 creating, 62, 101–103
 neighbors, 189
 routing, 219
 diagrams, 488–492
 IP, 225, 431–445
 IPX, 431–445
 troubleshooting, 356
 topologies, 189–190

TE (terminal equipment), 240

TE1 (terminal equipment type 1), 240

TE2 (terminal equipment type 2), 240
 access, 101–103
 asynchronous lines, 61
 Reverse, 58
 Catalyst 1900 switches, 66–67
 creating IP host tables, 62
 troubleshooting, 63–66
 scripts, 103–113
 terminal servers, 46–54
 virtual terminal lines, 50

terminal adapters (TAs), 240

terminal servers, 62–63
 configuring, 28, 54–67, 381–382, 470
 console ports, 43–44
 diagrams, 476
 host names, 62
 PC over LAN/WAN, 53–54
 saving, 62–63
 Telnet, 46–54

testing, 62–63

TFTP (Trivial File Transfer Protocol)
 Cisco IOS software files, 338–341
 configuration files, 342–343

timers, hold-down, 154

Token Ring
 interfaces, 143–145
 IPX, 280–284

topologies, 189–190

traffic, triggering links, 258–261

transactions option, 182

transmissions, CRC, 454

transparent bridging, 69

transport
 protocols, 61
 Telnet, 61

transport input telnet command, 61

transport input x command, 61

transport layers, 7

triggering links, 258–261

troubleshooting, 474–475
 context-sensitive help, 18–21
 EIGRP, 213
 Frame Relay, 454
 IP resources, 354–360
 mistyped commands, 99
 network access, 346–353

- remote users, 361–366
- Reverse Telnet, 63–66
- router access, 366–376
- routing tables, 356
- show frame-relay map, 123–125
- terminal servers, 62–63

types

- of encapsulation, 272
- of memory, 14
- of switching, 70, 246–248

U

UDP (User Datagram Protocol), 153

updates, 288

- hold-down timers, 154
- HyperTerminal, 42
- IGRP, 175
- RIP, 153, 168–170

upgrades

- Cisco IOS software, 493–494
- image files, 338–341

users, troubleshooting, 361–366

V

verification

- connectivity, 50, 354
- EIGRP configuration, 208–213
- Ethernets, 49
- IGRP configuration, 179–185
- IPX configuration, 284–285, 300–306
- network symptoms, 354–360
- Reverse Telnet, 63–66
- RIP configuration, 163–172
- VLAN configurations, 90

virtual circuits, 451–452

virtual terminal lines, configuring, 50

VLAN (virtual LAN), 71–72, 81–91

VLSM (variable-length subnet masking), 154

VSM (Visual Switch Manager), 73

vty passwords, configuring, 96

W

WAN (wide area networks), accessing, 53–54

wildcard masks, 314

writing scripts, 103–113

X-Z

XNS (Xerox Network System), 271