

## Symbols

---

? (question mark), CLI help system 35

## Numerics

---

10Base specifications 163  
 10Base2 Ethernet 151, 153  
 10Base5 Ethernet 151, 153  
 10BaseT Ethernet 153  
   full-duplex 156  
   half-duplex 153, 155  
 10-Mbps Ethernet 151–157  
 1900 series switches 179  
   configuring, 179, 188, 196  
   default settings 180  
   ports, numbering 180  
 2-wire circuits 575  
 4-wire circuits 575  
 802.1Q, VLAN tagging 237, 250

## A

---

access layer 573–574  
 access links 610  
 access lists 489  
   controlling vty access 515–516  
   deny statements 496, 517  
   displaying details for all protocols 499, 504, 519  
   extended IP 494, 497, 503–505, 512, 516  
     displaying details of 499, 504, 519  
     example 506–512  
     filtering IPX traffic 715–718  
     filtering logic 505–506  
     matching options 505  
     packet matching criteria 507–508  
     placement of 507–508  
   extended IPX 718  
     matching parameters 715, 731  
     socket parameter 716  
 filtering logic 710  
 functionality of 494

hands-on lab exercises 842–844  
 matching logic 496–497  
 named IP 512–515  
 named IPX 724  
 permit statements 496, 517  
 SAP filters 721, 733, 802  
   configuration 767–768  
   matching parameters 720, 733  
   versus IPX packet filters 720  
 standard IP 494, 503, 516  
   configuring 498–503, 767–768  
   controlling vty port access 516  
   displaying details of 499, 504, 519  
   features 495–496  
   matching options 504  
   planning 802  
 standard IPX 707–715  
   configuration 767–768  
   filtering SAP traffic 718–720  
   matching parameters 715, 731  
   statements 505  
   wildcard masks 497–498  
 access-class command 499  
 accessing CLI 32–34  
 access-list command 707, 722, 729, 733  
 ACK field, TCP connection establishment 283  
 acknowledgement numbers, error recovery 100  
 active configuration 44  
 Address Mask Request/Reply ICMP message 288  
 addresses, 107–108  
   addressing schemes 119  
   AppleTalk addresses  
     grouping 118  
     structure 120, 129  
   broadcast addresses 128, 297, 375  
   burned-in addresses 108, 127  
   IP, 297–298, 375–376  
     calculating 474, 485–486  
     classes of 299–302  
     displaying 179, 195  
     format 309  
   Frame Relay hybrid full/partial mesh  
     networks 642  
   grouping 118  
   host portion 298, 309, 376  
   hostnames, displaying 343, 380  
   interfaces, displaying 343, 380

- mapping to MAC addresses
- network masks 298, 376
- network portion 298, 309, 376
- planning 797
- prefix notation 339
- setting 179, 195
- structure 120, 129
- subnet masks 298, 376
- subnet portion 298, 306, 376
- subnets, calculating 393, 398–399
- translating for invalid hosts with NAT 342
- wildcard masks 497, 518
- IPX addresses 683, 725, 741, 751–752
  - displaying for neighboring routers 818
  - features 684, 725
  - Frame Relay hybrid full/partial mesh networks 642
  - grouping 118
  - node portion 697
  - secondary addresses 805
  - structure 120, 129
- MAC addresses 157, 185–186
  - BIAs 158
  - broadcast addresses 158
  - components 158
  - dynamic 183
  - features 158, 189
  - functional addresses 158
  - LAN card addressing 158
  - mapping to IP addresses 286–287
  - multicast addresses 158
  - OUI 158
  - permanent 184
  - restricted-static entries 184
  - switches, setting permanent 179, 195
  - switches, setting restricted 179, 195
  - tables, displaying 180, 195
  - unicast 157
- network layer 118–119
- multicast addresses 128
- network layer addresses 123, 136, 142
- switch port violations 186
- unicast addresses 127
- address-violation command 180, 186, 195
- adjacent layer interaction (OSI model) 90–97
- administrative distance 459–460
- advanced RIP-2 features 443–446
- advertisements, VTP 237–238
- ANSI (American National Standards Institute) 162, 191
- AppleTalk
  - addresses
    - grouping 118
    - structure 120, 129
  - cable ranges 118
- application layer (OSI reference model) 84–85, 88, 124
- applying access lists to vty ports 515–516
- arbitration 106–107
  - Ethernet 106
  - Token Ring 106
- architected field specifications 540
- ARP (Address Resolution Protocol) 116, 272, 274, 286. *See also* Inverse ARP
  - broadcast 274
  - cache, displaying 343, 381
- ARPA IPX Ethernet encapsulation 688, 726
- asynchronous data links 539
- asynchronous serial leased lines 539, 575
- ATM (Asynchronous Transfer Mode)
  - CCNA exam coverage 572
  - strengths/weaknesses 573, 584
- authentication
  - CHAP 557–558
  - PAP 557–558
- auto summarization (IP routes) 452, 465
- autonegotiation
  - Ethernet 162
  - switches 182
- autosummarization 446–451
- auxiliary ports 34

---

## B

- balanced hybrid routing protocols 414–416, 462
- bandwidth command 628
- BCRAN (Building Cisco Remote Access Networks) 6

BECN (backward explicit congestion notification) 611  
 behavior of distance vector routing protocols 416–417  
 BIAs (burned-in addresses) 158  
 binary conversion table 933–941  
 binary network numbers 301  
 binary values, converting to decimal and hexadecimal values 307–309, 933, 941  
 Blocking state (Spanning Tree) 229, 250  
 Boolean AND 309  
 boot field 54  
 boot sequence (Cisco IOS) 53–55, 57  
 boot system command 55  
 boot system flash command 55, 63  
 boot system rom command 55, 63  
 boot system tftp command 55, 63  
 BPDUs (bridge protocol data units) 220, 224  
 BRI (Basic Rate Interface), ISDN 548–549  
   DDR 560–562, 583  
   features 578  
   information, displaying 583  
 bridging  
   IDs 224  
   transparent 165–169  
 broadcast addresses 108, 128, 297, 375  
   MAC addresses 158  
 broadcast command 567  
 broadcast domains 173–174, 193  
   VLANs 230, 232–233  
     configuring 241–248  
     implementing 233–234  
     ISL trunking 235–236  
     trunking 234  
     VTP 237–238  
 broadcast firewalls 174, 177  
 broadcast handling, Frame Relay 625–626  
 BSCN (Building Scalable Cisco Networks) 6  
 buffering 103  
 Building Cisco Remote Access Networks (BCRAN) 6  
 burned-in addresses 108, 127  
 burst rate 611

## C

cable ranges (AppleTalk) 118  
 cabling  
   Fast Ethernet 161  
   WANs 546–547  
 Can't Fragment code (Destination Unreachable ICMP message) 290  
 carrier sense multiple access collision detect. *See* CSMA/CD 106  
 CBPDUs (Configuration Bridge Protocol Data Units) 220, 224, 249  
 CCDA (Cisco Certified Design Associate) 6–7  
 CCDP (Cisco Certified Design Professional) 5–6  
   prerequisite certification 5  
   specialization certifications 7  
   WAN certification 7  
 CCIE (Cisco Certified Internetworking Expert) 4  
   prerequisite certification 5  
   WAN certification 7  
 CCIP (Cisco Certified Internetworking Professional) 6  
 CCNA certification  
   course associations 6  
   exam requirements 6  
   recommended training path 17–18  
   topics covered 8–15  
     cross reference to chapters 16–17  
     study tips 19–21  
   training path recommended for 16–17  
 CCNP (Cisco Certified Network Professional) 5–6  
   prerequisite certification 5  
   specialization certifications 7  
   WAN certification 7  
 CDP (Cisco Discovery Protocol) 370–372, 779  
 cdp enable command 371  
 cdp run command 371  
 certification  
   CCDP 7  
   CCIE 4  
     prerequisite certification 5  
     WAN certification 7  
   CCNA  
     preparing for 22–24  
     recommended training path 17–18  
     topics covered 8–15, 19–21  
     training path recommended for 16–17

- CCNP
  - prerequisite certification 5
  - specialization certifications 7
- reseller requirements 4
- routing and switching 5
- testing locations 3
- WANs 7
- Challenge Handshake Authentication. *See* CHAP
- channels, ISDN 548–549
- CHAP (Challenge Handshake Authentication) 543, 557–558, 578
- CID (Cisco Internetwork Design) 7
- CIDR (classless interdomain routing) 338–339
- CIR (committed information rate) 611
- Cisco Certified Design Associate. *See* CCDA
- Cisco Certified Design Professional. *See* CCDP
- Cisco Certified Internetworking Expert. *See* CCIE
- Cisco Certified Network Professional. *See* CCNP
- Cisco Discovery Protocol. *See* CDP
- Cisco Internetwork Design (CID) 7
- Cisco Internetwork Troubleshooting (CIT) 6
- Cisco IOS
  - boot sequence 53–55, 57
  - CLI 32
    - accessing 32–34
    - configuration mode 39
    - help system 35–36
    - setup mode 46–50
  - configuration files
    - erasing from NVRAM 46
    - managing 44–45
    - updating 39
  - example configuration 40–42
  - privileged exec mode 34
  - user exec mode 34
- Cisco Networking Academy, post-exam strategies 22–23
- Cisco Systems training partners 17
- CIT (Cisco Internetwork Troubleshooting) 6
- Class A networks 302
  - IP addresses 300
  - masks 298, 376
  - network numbers 302
  - subnetting 306
- Class B networks 302
  - IP addresses 300
  - IP subnet design 396, 399
  - masks 298, 376
  - network masks 303
  - network numbers 302
  - subnetting 306
- Class C networks 302
  - IP addresses 300
  - IP subnet design 397, 402, 405
  - masks 298, 376
  - network masks 303
  - network numbers 302
  - subnetting 306
- classes of networks 300–302
- classful routers 368
- classless interdomain routing. *See* CIDR
- classless routers 368
- CLI (command-line interface) 27, 39, 59, 179
  - 1900 series switch, hands-on lab 831–836
  - accessing 33
  - commands, recalling 36
  - configuration mode 39–40
  - hands-on lab 827–831
  - help system 35–36
  - password recovery 56
  - privileged exec mode
- commands 628
  - access-class 499
  - access-list 707, 722, 729, 733
  - address-violation 180, 186, 195
  - bandwidth 628
  - boot system 55
  - boot system flash 55, 63
  - boot system ROM 55, 63
  - boot system tftp 55, 63
  - broadcast 567
  - cdp enable 371
  - cdp run 371
  - clock rate 547
  - compress 541, 546, 577
  - configuration mode end 40
  - configure terminal 179, 182
  - confreg 57
  - context-sensitive help 795
  - copy 45, 60
  - copy nvram tftp 187–188, 196
  - copy running-config startup-config 188, 196
  - copy startup-config tftp 187–188, 196
  - copy tftp flash 51–53, 819

- debug 37
  - output 435–437
- debug dialer 562, 583
- debug dialer events 571
- debug dialer packets 571
- debug ip icmp 353
- debug ip igmp event 438–439
- debug ip igmp transaction 437–439, 787, 795
- debug ip packet 343, 350–351, 381
- debug ip rip 430, 435, 440, 447–449, 464, 771, 778
- debug ip rip event 770, 778
- debug ipx routing 694, 729
- debug ipx routing activity 698–700, 705–707, 769, 778, 786
- debug ipx routing event 705–707, 769
- debug ipx sap 694, 729
- debug ipx sap activity 699–700, 706, 769, 778, 786, 807
- debug ipx sap event 707, 769, 778
- debug isdn q921 562, 583
- debug isdn q931 562, 571, 583
- delete nvram 188, 196
- delete vtp 241, 251
- dialer fast-idle 568
- dialer idle-timeout 568
- dialer in-band 565
- dialer load-threshold 559, 567
- dialer map 566–567
- dialer string 561, 566, 582
- dialer-group 561, 565, 582
- editing in CLI 36
- enable 795
- enable secret 795
- encapsulation 236, 541, 577
- encapsulation hdlc 542
- erase startup-config 46, 188, 196
- frame-relay interface-dlci 628
- frame-relay lmi-type 628
- global commands 40
- hostname 40
- interface 40
- interface ethernet 0 40
- interface serial 628
- ip access-group 499, 503, 513, 518–520
- ip access-list extended 513, 520
- ip access-list standard 513, 520
- ip address 40, 179, 195, 343, 380
- ip classless 343, 365–370, 380
- ip default-gateway 179, 195
- ip default-network 343, 368, 380
- ip domain-lookup 343, 362, 380
- ip domain-name 362
- ip host 343, 362, 380
- ip maximum-paths 452
- ip mtu 361
- ip name-server 343, 362, 380
- ip netmask-format 343, 380
- ip rip send version 445
- ip route 367, 566
- ip routing 343, 380
- ipx access-group 708, 722, 730, 733
- ipx access-list 708, 730
- ipx access-list extended 722, 733
- ipx access-list sap 722, 733
- ipx access-list standard 722, 733
- ipx delay 700
- ipx input-sap-filter 708, 722, 730, 733
- ipx maximum-paths 693, 700, 729
- ipx network 693, 696, 703, 729
- ipx output-sap-filter 708, 722, 730, 733
- ipx per-host-load-share 701
- ipx routing 693, 696–698, 703, 729
- isdn answer1 560, 582
- isdn answer2 560, 582
- isdn spid1 560, 582
- isdn spid2 560, 582
- isdn switch-type 560–561, 569, 582
- keepalive 628
- key commands, Ctrl+z 40
- line aux 33, 58
- line console 33, 58
- line vty 33–34, 58
- logging buffered 37
- logging host 38
- logging synchronous 37
- login 34
- mac-address-table permanent 179, 184, 195
- mac-address-table restricted 184
- mac-address-table restricted static 179, 195
- mtu 361
- network 430–432, 464
- no address-violation 186

- no cdp enable 371
- no cdp run 371
- no debug all 37, 438
- no ip classless 368
- no ip domain-lookup 362
- no keepalive 795
- no router rip 439
- output, comment lines 40
- ping 275, 289, 350–355, 546, 694, 729, 776, 793
- port secure 180, 185–186, 195
- ppp multilink 559
- recalling 36, 59
- resume 365
- router igrp 430, 464
- router rip 430, 464
- setup 47
- show access-list 499, 708, 730, 769
- show cdp entry 371
- show cdp interface 372
- show cdp neighbor 371
- show cdp neighbor detail 371, 806
- show compress 546, 577
- show controllers bri 561, 583
- show debug 353
- show dialer interface bri 561, 569, 583
- show flash 52
- show frame-relay lmi 793, 813
- show frame-relay map 791, 793, 815
- show frame-relay pvc 791, 819–820
- show hosts 343–344, 380–381
- show interface 349, 772, 788
- show interfaces 179, 182, 195, 343, 380
- show interfaces bri 561–562, 569, 583
- show ip 179, 182, 195
- show ip arp 350, 775, 778, 792
- show ip host 362
- show ip interface 343, 348, 380, 499
- show ip interface brief 343, 347, 380, 768, 786, 795, 806
- show ip protocol 430, 438–439, 464, 773, 789, 795
- show ip route 346–348, 351–352, 434, 437–439, 441, 447, 449, 460, 775–778, 792, 795
  - options 453–459
- show ipx access-list 708, 730
- show ipx interface 693, 696–697, 708, 729–730
- show ipx interface brief 773, 786, 789
- show ipx route 693, 698–700, 729, 773, 778, 790, 795
- show ipx servers 694, 698–700, 706, 729, 774, 778, 790, 793–795, 807
- show ipx traffic 694, 729
- show isdn 561, 583
- show isdn active 570
- show isdn status 570
- show mac-address-table 180, 184–185, 195
- show process 546
- show running-config 179–181, 346–347, 350, 774, 791
- show spantree 248
- show trunk 247
- show version 180, 188, 195–196
- show vlan 243
- show vlan-membership 241, 247, 251
- show vtp 241, 247, 251
- subcommands 40
- telnet 362
- terminal history size 36
- terminal ip netmask 350
- terminal ip netmask-format 343, 346, 381
- trace 291, 776–778, 793
- traffic-share 430, 464
- traffic-share balanced 452
- trunk 241, 244, 251
- undebg all 769
- variance 430, 452, 464
- vlan 242
- vlan-membership 242
- vtp 241–242, 247, 251
- vtp trunk pruning-disable 241, 251
- write erase 46, 188, 196
- write terminal 350
- comment lines, command output 40
- comparing
  - distance vector routing protocols 428–429
  - routing and routed protocols 122–123
  - WAN options 571–574
  - WAN protocols 540–541
- compress command 541, 546, 577
- compression
  - data-link protocol configuration 544–546
  - synchronous serial leased lines 544, 546

- Configuration Bridge Protocol Data Units. *See* CBPDUs 220, 249
- configuration files
  - copying 45–46
  - erasing from NVRAM 46
  - managing 44–45
  - routers
    - copying to TFTP servers 188, 196
    - erasing at reload time 188, 196
    - updating at reload time 188, 196
  - storing 44
  - switches
    - copying from TFTP servers 180, 195
    - copying to TFTP servers 187
    - displaying version information 180, 195
    - erasing at reload time 188, 196
    - managing 187–188, 196
    - saving to TFTP servers 180, 195
    - updating at reload time 188, 196
  - updating 39
- configuration mode (Cisco IOS CLI) 39–40
- configuration mode end command 40
- configuration register 55–54, 63
- configuration revision number, VTP advertisements 238
- configure terminal command 179, 182
- configuring
  - access lists
    - extended IP 503–505
    - extended IPX 718
    - hands-on lab exercises 842–844
    - named IP 515
    - named IPX 724
    - standard IPX 712, 715
  - CHAP 557
  - Cisco IOS, example 40–42
  - data-link protocols, compression 544–546
  - DDR
    - connection termination, determining 568
    - determining the subset of packets that trigger dialing 565
    - dialing 567
  - default routing 365–370
  - Frame Relay 203–206, 210, 257–258, 628–629
    - fully-meshed 629–636
    - hybrid 641–646
    - partial-meshed 637–641
    - with point-to-point subinterfaces 805
    - without subinterfaces 783–785
  - HDLC 541–542
  - IGRP 429–434
  - IP addresses 342–354
    - naming 361–362
    - with Frame Relay subinterfaces 357–360
  - IPX 693–701
    - access lists 709–710
    - Frame Relay networks with point-to-point subinterfaces 701–703
    - multiple Ethernet encapsulations 703–704
    - multiple networks 689–690
    - named access lists 721–724
    - standard access lists 711–714
  - IPX networks 802–805
  - ISDN 555–556, 569
    - authentication 557–558
    - DDR 560–562
  - legacy DDR 563, 567–568
    - sample configurations 568–571
    - signaling 565–567
    - triggering the dial 563–565
  - MAC address table entries 183, 186
  - named IP access lists 512–515
  - Novell IPX, hands-on lab exercises 848–849
  - point-to-point leased lines 597–603
  - routers
    - for ISL encapsulation 236
    - IGRP 459
    - IP 355, 471, 474, 480, 485, 783–785
    - IPX 707, 747–748, 752–754
    - RIP 429–432, 459, 767–768
    - RIP-2 443, 446
    - setup mode 46–50
  - secondary IP addressing 356–357
  - standard access lists 498–503
  - switches 179, 188, 196
    - as VTP client/servers 246
    - 1900 series, default settings 180
    - IP support 181–183
    - methods of 179
  - trunks 241, 247, 251
  - VLANs 241
    - multiple switch configuration 244–248
    - single switch configuration 242–244
  - VTP 247
  - WANs, hands-on lab exercises 844–848

confreg command 57  
 congestion avoidance 103–104  
     buffering 103  
     congestion avoidance 103–104  
     flow control 102  
     windowing 104  
 connectionless protocols 98–99, 126  
 connection-oriented protocols 98–99, 126  
 connections  
     TCP 282–284  
     telnet, suspended 365  
 console ports, routers 34  
 contiguous networks 448  
 convergence 414, 462–463  
     distance vector routing protocols 462–463  
     STP 227–229  
 converting  
     decimal to binary 933–941  
     decimal to hex 933–941  
 copy command 45, 60  
 copy nvram tftp command 187–188, 196  
 copy running-config startup-config command 188, 196  
 copy startup-config tftp command 187–188, 196  
 copy tftp flash command 51, 53, 819  
 copying  
     configuration files 45–46  
     from TFTP servers 180, 195  
     images into Flash memory 50–53  
 core layer 573–574  
 count-to-infinity 422, 426, 434  
 courses  
     BCMSN 6  
     BCRAN 6  
     BSCN 6  
     CID 7  
     CIT 6  
     DCN 6  
     ICND 6, 17–18  
     ITM 17  
 CRC (cyclical redundancy check) 109  
 creating subnet charts 316–320, 334–337  
 criteria  
     for standard access lists 500–502  
     for STP forwarding state activation 223–224  
 CSMA/CD 106, 152  
 Ctrl+z key sequence 40  
 cut-through processing 174–175

## D

data connection process, FTP 295  
 data link layer (OSI reference model) 84–89, 105, 124  
     addressing 107–108  
     arbitration 106–107  
     encapsulated data, identifying 109, 113  
     encapsulation 94  
     error detection 109  
     error recovery 92  
     functionality 114, 128  
     identifying encapsulated data 109–114  
     ISDN specifications 550  
     summary of functions 113  
 Data Services Unit/Channel Services Unit.  
     *See* DSU/CSU  
 datagrams 97  
 data-link encapsulation (IPX) 687  
 data-link protocols  
     comparing 540–541  
     compression 544–546  
     configuring 541–542  
     error-recovery 540  
     LCP 542  
     PPP  
         error detection 543–544  
         looped link detection 543–544  
         LQM 544  
         magic numbers 543  
         Protocol Type field 540–541  
 DCE (data communications equipment) 609  
 DCN (Designing Cisco Networks) 6  
 DDR (dial-on-demand routing) 555  
     configuring over ISDN BRI 560–562  
     connection termination, determining 568  
     dialing 567  
         triggers 565  
     legacy configuration 563  
         connection termination 567–568  
         sample configurations 568–571  
         signaling 565–567  
         triggering the dial 563–565  
 DE (discard eligibility) 611  
 debug command 37  
     output 435–437  
 debug dialer command 562, 583



- debug dialer events command 571
- debug dialer packets command 571
- debug ip icmp command 353
- debug ip igrp event command 438–439
- debug ip igrp transaction command 437–439, 787, 795
- debug ip packet command 343, 350–351, 381
- debug ip rip command 430, 435, 440, 447–449, 464, 771, 778
- debug ip rip event command 770, 778
- debug ipx routing activity command 698–700, 705–707, 769, 778, 786
- debug ipx routing command 694, 729
- debug ipx routing event command 705–707, 769
- debug ipx sap activity command 699–700, 706, 769, 778, 786, 807
- debug ipx sap command 694, 729
- debug ipx sap event command 707, 769, 778
- debug isdn q921 command 562, 583
- debug isdn q931 command 562, 571, 583
- decimal-to-binary conversion 307–309, 933–941
- default port costs, STP 226
- default routing 365–370
- delay 690
- delete nvram command 188, 196
- delete vtp command 241, 251
- deny statements (access lists) 496, 517
- deploying networks
  - configuration 766–768
  - Frame Relay networks
    - configuration 783–785
    - planning phase 780–782
    - verifying configuration 785–796
  - IPX networks
    - configuration 802–805
    - planning phase 797–802
    - planning phase 762–766
    - verifying configuration 768–779, 806–820
- designated bridge 223
- designated port 223, 226
- Designing Cisco Networks (DCN) 6
- Destination Unreachable ICMP message 288, 290
- Destination Unreachable messages 289–291
- devices
  - hubs 152–153
  - TE2 552
  - telnetting between 362–365
- DF (Don't Fragment) bits 354
- dialer fast-idle command 568
- dialer groups (ISDN), enabling 561, 582
- dialer idle-timeout command 568
- dialer in-band command 565
- dialer load-threshold command 559, 567
- dialer map command 566–567
- dialer string command 561, 566, 582
- dialer-group command 561, 565, 582
- dial-on-demand routing. *See* DDR
- Dijkstra SPF algorithm 414–415
- directly connected routes, routing table updates 418
- directly connected subnets 416
- disabling debug options 37
- discontiguous networks 448
- discovering neighbor devices 370–372
- displaying
  - running configuration 46
  - syslog messages 37
- distance vector routing protocols 412–413, 416, 462–463
  - administrative distance 459–460
  - autosummarization 446–451
  - comparing 428–429
  - equal-cost routes 420–421
  - IGRP
    - configuring 429–433
    - equal-cost routes 452
    - metrics, configuring 434
  - loop avoidance 419, 422 462–463
  - count to infinity 422
  - hold-down timers 426–428
  - poison reverse 425
  - route poisoning 428
  - split horizon 423–425
  - triggered updates 428
- RIP
  - advanced features 443–446
  - configuring 429–432
  - debug command output 435–437
  - hop count 418–419
  - migration from RIP-1 to RIP-2 445
  - migration to IGRP 437–439
  - route aggregation 446–451
  - routing behavior 416–417
  - routing tables 417–418
  - routing update timers 419
- distance-vector routing protocols
- distribute lists 718
- distribution layer 573–574

DIX Ethernet 106  
DLCI (data-link connection identifier) 109, 610–611, 616–620

- global addressing 618–620
- local addressing 617

DNS (Domain Name System), 274, 285  
Domain Name System. *See* DNS  
domains, broadcast 174, 193  
Don't Fragment (DF) bits 354  
DRAM (dynamic random-access memory) 43, 59.  
*See also* RAM  
DSAP (destination service access point) 110  
DSU/CSU (Data Services Unit/Channel Services Unit) 539 547, 575  
DTE (data terminal equipment) 107, 609  
DUAL (Diffusing Update Algorithm) 414–415  
dynamic MAC addresses 183  
dynamic random-access memory. *See* DRAM

## E

---

E1 lines 539, 576  
Echo ICMP message 288–289  
Echo Request/Reply messages 289  
editing commands in CLI 36  
EIA/TIA 232 WAN cabling standard 547  
EIA/TIA 449 WAN cabling standard 547  
EIA/TIA 530 WAN cabling standard 547  
EIGRP (Enhanced Interior Gateway Routing Protocol) 415–416, 462

- auto summarization 452, 465
- equal-cost routes 452
- equal-metric routes 452
- route aggregation 451–452, 465

electing root bridge (STP) 224–225  
enable command 795  
enable secret command 795  
encapsulation 94–97

- data link layer processes 94
- forward acknowledgment 100–101
- identifying encapsulated data 113
- IPX 687, 783–785
- OSI layer processes 93
- switches
  - 802.10 237, 250
  - 802.1Q 237, 250
  - ISL 236–237, 250
  - LANE 237, 250
- encapsulation command 236, 541, 577
- encapsulation frame-relay command 628
- encapsulation hdlc command 542
- Enhanced IGRP. *See* EIGRP
- enterprise network layers 573–574
- equal-cost routes 420–421, 452
- erase startup-config command 46, 188, 196
- erasing configuration files 46
- error detection 543–544
  - at data-link layer 109
  - PPP 543–544, 577–578
  - versus error recovery 99–100
- error recovery
  - acknowledgement numbers 100
  - at data link layer 92
  - example 101
  - LLC2 102, 127
  - procedures 102, 127
  - SPX 102, 127
  - TCP 102, 127, 277, 280, 796
  - versus error detection 99–100
  - WAN protocols 540

E-series ISDN protocols 549, 578  
EtherChannel 215  
Ethernet 105, 108, 163

- 10Base2 151, 153
- 10Base5 151, 153
- 10BaseT 153
  - full-duplex 156
  - half-duplex 153–155
- 10-Mbps 152–157
- arbitration 106
- CSMA/CD 106, 152
- DIX Ethernet 106
- encoding 113
- Fast Ethernet 161–163
- Gigabit Ethernet 161–163
- hubs 153
- IEEE standards 162–163, 191
- IPX encapsulation 688–689, 726
- multicast addresses 108, 128
- Ethernet\_802.2 encapsulation 688
- Ethernet\_802.3 encapsulation 688
- Ethernet\_II encapsulation 688
- Ethernet\_SNAP encapsulation 688

evolution of OSI reference model 84–85  
 exam (CCNA), topics covered 8–15, 19–21  
 example configuration, Cisco IOS 40–42  
 extended IP access lists 494–505, 512, 516  
   example 506–512  
   filtering logic 505–506  
   matching options 505  
   matching packet filtering criteria 507–508  
   placement of 507–508  
 extended IPX access lists 715–718  
   configuring 715–718  
   matching 715, 731  
   socket paramet 716  
 exterior routing protocols 414

## F

Fast Ethernet 161–162  
   online resources 163  
 FCS (frame check sequence) 99, 109, 540  
 FDDI (Fiber Distributed Data Interface)  
   ANSI standards 162, 191  
   IPX encapsulation 688–689, 727  
 FECN (forward explicit congestion notification) 611  
 filtering packets  
   extended IP access lists 503–505  
     example 506–512  
     placement of 507–508  
   named IP access lists 512–515  
   SAP updates 718–720  
   standard access lists 494  
     configuring 498–503  
     features 495–496  
   matching logic 496–497  
   wildcard masks 497–498  
 FIN field, TCP connection establishment 283  
 Flash memory  
   read-only mode 53  
   routers 43, 60  
   storing IOS images 50–53  
   verifying contents of 52  
 flow control 102–103  
   buffering 103  
   congestion avoidance 103–104  
   TCP 281–282  
   terminology 105  
   windowing 104  
 forward acknowledgment 100–101  
   TCP 280  
 Forward Delay Timer (Spanning Tree) 227, 250  
 forwarding state (Spanning Tree) 223–224, 229, 250  
   lowest-cost hello, calculating 226  
 four-wire circuits 539  
 fragmentation 360–361  
   SAR 572  
 FragmentFree processing 175  
 frame check sequence. *See* FCS  
 Frame Relay 572, 609  
   broadcast handling 625–626  
   configuration 203–206, 210, 257–258  
     with point-to-point subinterfaces 805  
     without subinterfaces 783, 785  
   configuring 628–629  
   DLCI 616–620  
   encoding 113  
   full-mesh, configuring 629–636  
   hybrid full/partial mesh networks  
     configuring 641–646  
     IP addresses 642  
     IPX addresses 642  
   IP addressing, configuring 357–360  
   Layer 3 addressing 621–625  
     Layer 2 address mappings 632–636  
   LMI 614–616  
   maps, static 783, 785  
   network deployment  
     configuration 783–785  
     planning 780–783  
     verification 785–796  
   partial-mesh, configuring 637–641  
   Protocol Type field, lack of 615  
   split horizon 626–627  
   strengths/weaknesses 573, 584  
   VCs 108, 610, 612–614  
 frame-relay interface-dlci command 628  
 frame-relay lmi-type command 628  
 frames 107, 158–160  
   latency, decreasing with switch processing 174  
 framing 538  
 FTP 294–295  
   control connections 294  
   data connection process 295

full-duplex 10BaseT Ethernet 156  
fully-meshed Frame Relay networks, configuring  
613, 629–636  
function groups, ISDN 551–555

## G

---

gateway of last resort 368  
gateways, setting default 179, 195  
Gigabit Ethernet 161–163  
global addressing 618–620  
global commands 40  
GNS (Get Nearest Server) requests 691–693,  
728, 779  
GOSIP (Government OSI Profile) 85  
Government OSI Profile (GOSIP) 85  
group addresses 158

## H

---

half-duplex 10BaseT Ethernet 153–155  
half-duplex switch ports 181–183  
hands-on lab exercises 823  
    access list configuration 842–844  
    IP routing configuration 840–842  
    Novell IPX configuration 848–849  
    router CLI familiarization 827–831  
    router IP configuration and management  
        navigation 838–840  
    switch CLI familiarization 831–836  
    VLANs, trunks, and STP 836–838  
    WAN configuration 844–848  
HDLC 106–107, 541, 572, 576  
    compression 544–546  
    configuring 541–542  
    encoding 113  
    strengths/weaknesses 572, 583  
headers  
    encapsulation 93–97  
    forward acknowledgment 100–101  
    TCP 278  
    trunking 234

hello BPDUs 224  
Hello time timer (STP) 250  
    Spanning Tree  
    STP 227  
help system, CLI 35–36, 59  
hexadecimal values, converting to decimal and  
    binary values 933–941  
history buffer (CLI), recalling commands 36  
hold-down timers 422–423, 426–428  
home-based ISDN 554  
hop count 418–419  
host addresses. *See* IP addresses  
Host Unreachable code (Destination Unreachable  
    ICMP message) 290  
hostname command 40  
hostnames, mapping to IP addresses 362  
hubs 152  
    Ethernet 153  
    full-duplex 10BaseT Ethernet 156  
    half-duplex 10BaseT Ethernet 153–155  
    shared Ethernet 153  
“Hurry up and wait” 104  
hybrid Frame Relay networks, configuring 641–646

## I

---

ICMP (Internet Control Message Protocol) 272,  
275–276, 287  
    echo messages, sending/receiving 430, 464  
    functions of 288  
    messages  
        Address Mask Request/Reply 288  
        Code field 288  
        Destination Unreachable 288–291  
        Echo 288–289  
        Echo Request/Reply 289  
        Parameter Problem 288  
        Redirect 288, 293  
        Router Advertisement and Selection 288  
        Source Quench 288  
        Time Exceeded 288, 291–293  
        Timestamp 288  
        Type field 288

- ICND 6, 17
  - course summary 17–18
- identifying
  - encapsulated data at data link layer 109–114
  - IP address structure 311–315
- IEEE 802.1Q, VLAN trunking 235
- IEEE 802.3. *See* Ethernet
- IEEE 802.5. *See* Token Ring
- IEEE standards
  - group addresses 158
  - LANs 162, 191
- IGRP (Interior Gateway Routing Protocol) 407, 416, 462
  - auto summarization 452, 465
  - CCNA exam coverage 415–416
  - configuring 429–433, 459
  - equal-cost routes 452
  - features 429, 463
  - metrics 434
  - migration from RIP 437–439
  - packets, displaying log messages 430, 464
  - route aggregation 452, 465
  - subnet masks 440–442
  
  - updates, displaying log messages 430, 464
  - versus RIP 429, 463
- image files (IOS) 50
  - storing in Flash memory 50–53
  - upgrading into Flash memory 61
- implementing VLANs with multiple switches 233–234
- infinite-distance routes 424
- interaction between OSI layers
  - adjacent layers 90–93
  - same layers 93–94
- interesting packets 564
- interface command 40
- interface ethernet 0 command 40
- interface serial command 628
- interfaces. *See also* ports
  - displaying information for 179, 195
  - IP parameters, displaying settings 343, 380
  - routers 43–44
  - statistics, displaying 343, 380
  
  - summary information, displaying 343, 380
  - switches, numbering 180
- Interior Gateway Routing Protocol. *See* IGRP
- interior routing protocols 414
- internal switch processing 174–175
- International Telecommunications Union. *See* ITU
- Internetworking Technology Multimedia. *See* ITM
- Inter-Switch Link. *See* ISL
- Inverse ARP 634–636, 796
- IOS 32
  - CLI 27, 179
    - accessing 33
    - configuration mode 40
    - privileged exec mode 39–40, 59
    - user exec mode 39, 59
  - configuration file
    - managing 44
    - storing 44
  - distribute lists 718
  - image files
    - storing in Flash memory 50–53
    - upgrading into Flash memory 61
- IP access lists
  - extended 512
    - displaying details of 499, 504, 519
    - matching options 505
  - standard 494, 503
    - configuration 767–768
    - controlling vty port access 516
    - displaying details of 499, 504, 519
    - matching options 504
    - planning 802
- IP addresses 297–298, 375–376
  - address classes 299–302
  - ARP cache, displaying 343, 381
  - calculating 474, 485–486
  - CIDR 338–339
  - configuring 342–355, 471, 474, 480, 485, 783–785
    - on switches 181–183
  - connectivity, verifying 818
  - displaying 179, 195
  - format 309

- Frame Relay hybrid full/partial mesh
    - networks 642
  - grouping 118
  - host portion 298, 309, 376
  - hostnames, displaying 343, 380
  - identifying address structure 311–315
  - interfaces, displaying 343, 380
  - naming configuration 361–362
  - NAT 338–342
  - network masks 298, 376
  - network numbers 300–301
  - network portion 298, 309, 376
  - planning
  - prefix notation 339
  - Private Addressing 338–340
  - secondary addresses 355–357
  - structure 120, 129
  - subnetting 303–306
    - binary conversion 307–309
    - deriving subnet broadcast address 327–333
    - deriving subnet number 321–327
    - masks 298, 376
    - practice questions 943–988
    - subnet chart, creating 316–320
  - Telnet sessions 694
  - test preparation 310
  - translating for invalid hosts with NAT 342
  - wildcard masks 497, 518
- IP RIP**
- configuration 767–768
  - versus IPX RIP 690, 727
- IP routes**
- aggregating 452, 465
  - auto summarization 452, 465
  - equal-cost 452
  - metrics, displaying 778
  - static routes 785
  - troubleshooting 460
- IP routing protocols 412**
- interior 462
  - routing tables, displaying 430, 464
- ip access-group command 499, 503, 513, 518–520**
- ip access-list extended command 513, 520**
- ip access-list standard command 513, 520**
- ip address command 40, 179, 195, 343, 380**
- ip classless command 343, 365–370, 380**
- ip default-gateway command 179, 195**
- ip default-network command 343, 368, 380**
- ip domain-lookup command 343, 362, 380**
- ip domain-name command 362**
- ip host command 343, 362, 380**
- ip maximum-paths command 452**
- ip mtu command 361**
- ip name-server command 343, 362, 380**
- ip netmask-format command 343, 380**
- ip rip send version command 445**
- ip route command 367, 566**
- ip routing command 343, 380**
- IPX (Internetwork Packet Exchange) 684**
- access lists, SAP filters 721, 733
  - addresses 741, 751–752
    - displaying for neighboring routers 818
    - features 684, 725
    - Frame Relay hybrid full/partial mesh networks 642
    - node portion 697
    - secondary addresses 805
    - structure 120, 129, 683, 725
  - addressing 683–687
  - configuring 693–701, 747–754, 783–785
    - hands-on lab exercises 848–849
    - multiple networks on same link 689–690
    - on Frame Relay networks with point-to-point subinterfaces 703
    - on networks with multiple Ethernet encapsulations 707
  - connectivity, verifying 818
  - enabling on routers 696
  - encapsulation 687, 783–785
    - accommodating multiple types 805
  - extended access lists, 718
    - configuring 715–718
    - filtering logic 710
    - matching parameters 715, 731
    - socket parameter 716
  - Frame Relay with point-to-point subinterfaces
    - configuring 701–702
  - GNS requests 691–693, 728, 779
  - interface parameter settings, displaying 693, 729
  - multiple Ethernet encapsulations,
    - configuring 703–704
  - named access lists, configuring 721–724
  - network deployment
    - configuration 802–805

- planning 797–802
  - verifying configuration 806–820
- network numbers, creating 696
- packets
  - filtering 707–709
  - sending to verify connectivity 694, 729
- RIP 690–691
  - versus IP RIP 727
- router configuration 707
- routing 684–687
  - updates, displaying 694, 729
- routing tables, displaying 693–694, 729
- SAP 691–693
  - filters, configuring 718–720, 733, 767–768
  - tables, displaying 694, 729
  - updates, displaying 694, 729
- secondary addressing 689–690
- standard access lists
  - configuring 709–715, 767–768
  - filtering logic 710
  - matching parameters 715, 731
  - versus SAP filters 720
- traffic, displaying statistics on 694, 729
- ipx access-group command 708, 722, 730, 733
- ipx access-list command 708, 730
- ipx access-list extended command 722, 733
- ipx access-list sap command 722, 733
- ipx access-list standard command 722, 733
- IPX addresses
  - grouping 118
- ipx delay command 700
- ipx input-sap-filter command 708, 722, 730, 733
- ipx maximum-paths command 693, 700, 729
- ipx network command 693, 696, 703, 729
- ipx output-sap-filter command 708, 722, 730, 733
- ipx per-host-load-share command 701
- ipx routing command 693, 696–698, 703, 729
- ISDN (Integrated Services Digital Network) 820
  - backup usage 555
  - BRI 548–549
    - DDR parameters, displaying 562, 583
    - features 578
    - information, displaying 583
  - channels 548
  - CHAP 557–558
    - configuring 555–556
  - DDR 555, 560–562
    - connection termination, determining 568
    - determining the subset of packets that trigger dialing 565
    - dialing 567
    - legacy configuration 563–569, 571
  - dial in/dial out capabilities, enabling 561, 582
  - dial strings, defining 582
  - dialer groups, enabling 561, 582
  - function groups 551–555
  - home-based 554
  - incoming call numbers, defining 560, 582
  - interesting packets 582–583
  - LAPD 550
  - Layer 2 messages, displaying 562, 583
  - Layer 3 messages, displaying 562, 583
  - modems 554
  - Multilink PPP, configuring 558–559
  - out-of-band signaling 550
  - PAP 557–558
  - PPP 551
  - PRI 548–549
  - protocols 549–551
  - reference points 551–555
  - SBus 554–555
  - SBus topology 554
  - signaling 562
  - specifications 551
  - SPIDs 551
    - defining 560, 582
    - subaddresses 555
  - status information, displaying 561, 583
  - switches
    - configuration 569
    - defining to router 560, 582
- isdn answer1 command 560, 582
- isdn answer2 command 560, 582
- isdn spid1 command 560, 582
- isdn spid2 command 560, 582
- isdn switch-type command 560–561, 569, 582
- I-series ISDN protocols 549, 578

ISL (Inter-Switch Link) 236  
 tagging  
   configuring routers for 236  
   VLANs 236–237, 250  
 trunking 235–236  
   VTP pruning 239–240  
 ITM (Internetworking Technology Multimedia) 17  
 ITU (International Telecommunications Union)  
 547–549

## J-K-L

keepalive command 628  
 key sequences, Ctrl+z 40

LAN addresses. *See* MAC addresses  
 LAN Emulation. *See* LANE 237, 250  
 LANE (LAN Emulation) 237, 250  
 LANs

  collision domains 154  
   Ethernet  
     10-Mbps 151–157  
     CSMA/CD 152  
   frames 158–160

  segmenting  
     with bridges 165–169, 177  
     with routers 177  
     with switches 170–174, 177  
   switching, internal processing 174–175  
   VLANs 230, 232–233  
     configuring 241–248  
     implementing 233–234  
     ISL trunking 235–236  
     trunking 234  
     VTP 237–238

LAPB (Link Access Procedure Balanced) 541, 572,  
 576  
   HDLC 539  
   strengths/weaknesses 572, 583  
 LAPD (Link Access Procedure on the D  
 channel) 541, 576  
   ISDN 550  
 LAPF (Link Access Procedure Frame Bearer  
 Services) 611, 615  
 LAT (Local Area Transport) 121

latency, decreasing with switch processing 174  
 Layer 1. *See* physical layer  
 Layer 2. *See* data link layer  
 Layer 3 addressing. *See also* network layer  
   Frame Relay 621–625  
   fully-meshed networks, Frame Relay  
     configuration 629–632  
   hybrid networks, Frame Relay configuration  
     641–646  
   Layer 2 address mappings 632–636  
   partially-meshed networks, Frame Relay  
     configuration 637–641  
 Layer 3 processes 97  
 Layer 3 protocols 97  
 Layer 4. *See* transport layer  
 layers of OSI model 85–88  
   concepts 89–90  
   data link layer 105  
     addressing 107–108  
     arbitration 106–107  
     error detection 109  
     identifying encapsulated data 109–114  
   encapsulation 94–97  
   interaction between 90–94  
   network layer  
     addressing 118–119  
     routing 114–118  
   Transport layer 98  
 LCP (Link Control Protocol) 542–543, 578  
 Learning state (Spanning Tree) 229, 250  
 leased lines  
   synchronous serial leased lines 546  
   versus packet-switching 572–573  
 legacy DDR configuration 563  
   connection termination 567–568  
   sample configurations 568–571  
   signaling 565–567  
   triggering the dial 563–565  
 line aux command 33, 58  
 line console command 33, 58  
 line vty comand 33–34, 58  
 Link Access Procedure on the D channel.  
   *See* LAPD  
 Link Quality Monitoring. *See* LQM  
 link state routing protocols 414–415  
 link-state routing protocols 415–416, 462  
 Listening state, (Spanning Tree) 229, 250



- LLC (Logical Link Control) Type 2 106, 109
  - error recovery 102, 127
- LMI (Local Management Interface) 609, 611–616, 796
- local addressing 617
- logging buffered command 37
- logging host command 38
- logging synchronous command 37
- Logical Link Control. *See* LLC 106
- login command 34
- loop avoidance
  - detecting with LCP 577
  - distance vector protocol features 419, 422, 462–463
    - hold-down timers 426–428
    - poison reverse 425
    - route poisoning 428
    - split horizon 423–425
    - triggered updates 428
  - split horizon over Frame Relay 626–627
- STP 220–223
  - convergence 227–229
  - designated port 226
  - forwarding state 223–224
  - root bridge election 224–225
  - timers 227
  - troubleshooting 423
- looped link detection, PPP 543–544
- lower layers of OSI reference model 85–86, 88
- LQM (Link Quality Monitoring) 543–544, 577
  - switches, 179, 195
  - tables, displaying 180, 195
  - unicast 157
- mac-address-table permanent command 179, 184, 195
- mac-address-table restricted command 184
- mac-address-table restricted static command 179, 195
- magic numbers 543
- managing configuration files 44–45
- masks 298, 376
  - Class A networks 298, 376
  - Class B networks 298, 303, 376
  - Class C networks 298, 303, 376
  - subnet masks 298, 306, 376
    - display types, setting 344, 381
    - RIP-1/IGRP issues 440, 442
- matching packet filtering criteria
  - extended IP access lists 504–508
  - standard access lists 500–502
- MaxAge timer (STP) 227, 250
- maximum transmission unit. *See* MTU
- MD5 (Message Digest 5) 557
- Media Access Control. *See* MAC
- memory 43
  - Flash 43
    - read-only mode 53
    - routers 60
    - storing IOS images 50–53
    - verifying contents of 52
  - NVRAM 43, 60
  - RAM 43, 59
  - ROM 43, 59
- Message Digest 5. *See* MD5
- messages, ICMP 287
  - Destination Unreachable 289–291
  - Echo Request/Reply 275, 289
  - Redirect 293
  - Time Exceeded 291–293

## M

- MAC (Media Access Control) 105, 157, 714
  - BIAs 158
  - broadcast addresses 158
  - components 158
  - dynamic 183
  - features 158, 189
  - functional addresses 158
  - LAN card addressing 158
  - mapping to IP addresses 286–287
  - multicast addresses 158
  - OUI 158
  - permanent 184
  - restricted-static entries 184
- metrics 416
  - administrative distance 459–460
  - equal-cost routes 452
  - hop count 418–419
  - IGRP 434
  - IP routes, displaying 778
  - IPX routes, displaying 778
  - ticks 690

migrating to IGRP 437–439  
 modems, ISDN 554  
 MTU (maximum transmission unit) 160, 360–361  
 mtu command 361  
 multiaccess Frame Relay networks 609
 

- broadcast handling 625–626
- configuring 628–646
- DLCI 616–620
- Layer 3 addressing 621–625
- LMI 614–616
- MAC addresses 158
- split horizon 626–627
- VCs 610, 612–614

 multicast addresses 108, 128  
 Multilink PPP 558–559  
 multiple IPX network configuration 689–690  
 multiple switch VLAN configuration 244–248  
 multiplexing 276–277
 

- TCP 278–280
- T1 mux 539
- UDP 285

## N

named IP access lists 512–515
 

- comparing to numbered access lists 513–514

 named IPX access lists 724
 

- configuring 721–724
- versus standard and extended IPX access lists 721–722, 733

 naming
 

- IP addresses 361–362
- VLANs 241–242, 251

 NAT (Network Address Translation) 338–342  
 NBMA (nonbroadcast multiaccess) 611, 796  
 neighboring devices, discovery 370–372  
 NetBEUI 121  
 NetBIOS 121  
 NetWare versus OSI and TCP/IP 97–98  
 Network Address Translation. *See* NAT  
 network address. *See* network numbers  
 network command 430–432, 464  
 Network File System. *See* NFS

network layer (OSI reference model Layer 3) 84–89, 124
 

- addressing 118–119, 123, 136, 142
- ISDN specifications 550
- routing 114–118

 network masks 298, 376  
 network numbers 297, 300–301, 375
 

- aggregating with CIDR 338–339
- Class A networks 299–302
- Class B networks 299–302
- Class C networks 299–302
- IPX
  - creating 696
  - planning 797

 network service access point. *See* NSAP  
 Network Unreachable code (Destination Unreachable ICMP message) 290  
 networks 375. *See also* subnets
 

- Class A 302
  - IP addresses 300
  - masks 298, 376
  - network numbers 302
  - subnetting 306
- Class B 302
  - IP addresses 300
  - IP subnet design 396, 399, 402
  - masks 298, 303, 376
  - network numbers 302
  - subnetting 306
- Class C 302
  - IP addresses 300
  - IP subnet design 397, 402, 405
  - masks 298, 303, 376
  - network numbers 302
  - subnetting 306

 contiguous 448  
 Frame Relay 609
 

- broadcast handling 625–626
- configuring 628–646, 783–785
- DLCI 616–620
- IP addressing 357–360
- Layer 3 addressing 621–625
- LMI 614–616
- planning 780–783
- split horizon 626–627
- VCs 610, 612–614
- verifying configuration 785–796

- IPX
    - configuring 802–805
    - planning phase 797–802
    - verifying configuration 806–820
  - planning 762, 766
  - private Internets 340
  - Next-Hop Routers, routing table entries 418
  - NFS (Network File System) 88, 285
  - no address-violation command 186
  - no cdp enable command 371
  - no cdp run command 371
  - no debug all command 37, 438
  - no ip classless command 368
  - no ip domain-lookup command 362
  - no keepalive command 795
  - no router rip command 439
  - nonroutable protocols 120–121
  - nonvolatile random-access memory (NVRAM) 43, 60
  - Novell IPX
    - addressing 683–684, 686–687
    - configuring 693–701
    - encapsulation 687
    - Frame Relay with point-to-point subinterfaces 701–702
    - GNS requests 691–693
    - multiple Ethernet encapsulations 703–704
    - multiple networks on same link, configuring 689–690
    - RIP 690–691
    - routing 684, 686–687
    - SAP updates 691
      - filtering 718–720
    - secondary addressing 689–690
    - standard access lists, configuring 709–714
  - Novell NetWare. *See* NetWare
  - Novell-ether IPX Ethernet encapsulation 688, 726
  - Novell-fddi encapsulation 688, 727
  - NSAP (network service access point) 79
  - NT1 (Network Termination Type 1) 796
    - ISDN function group 553, 580
  - NT1/NT2 (Network Termination Type 1/Network Termination Type 2) ISDN function group 553, 580
  - NT2 (Network Termination Type 2) ISDN function group 553, 580
  - numbered IP access list, versus named IP access lists 513–514
  - numbering
    - router interfaces 44
    - switch ports 180
  - NVRAM (nonvolatile RAM) 43, 60
    - configuration files, erasing 46
    - routers 43, 60
- 
- O**
- 
- Open Systems Interconnection reference model. *See* OSI reference model
  - operating systems, categories of 54
  - ordered data transfer 284
  - Organizationally Unique Identifier. *See* OUI
  - OSI (Open Systems Interconnection) reference model 79
    - application layer 85, 88, 124
    - benefits of layered model 125
    - current usage 85
    - data link layer 85, 89, 105, 124
      - addressing 107–108
      - arbitration 106–107
      - error detection 109
      - identifying encapsulated data 109–114
      - ISDN specifications 550
    - encapsulation 94–97
    - evolution of 84–85
    - interaction between layers 90–94
    - justification for 79
    - layers 85–90
    - network layer 85, 89, 124
      - addressing 118–119
      - ISDN specifications 550
      - routing 114–118
    - origin/evolution 85
    - physical layer 85, 89, 124
      - ISDN specifications 550
    - presentation layer 85, 88, 124
    - session layer 85, 88, 124
    - transport layer 85, 89, 98, 124
    - versus NetWare and TCP/IP protocol suites 97–98

OSPF (Open Shortest Path First) 415–416, 462  
    auto summarization 452, 465  
    route aggregation 452, 465  
OUI (Organizationally Unique Identifier)  
    108, 158, 127  
out-of-band signaling, ISDN 550  
output (commands), comment lines 40

## P

---

packet filtering  
    extended IP access lists 503–505  
        example 506–512  
        placement of 507–508  
    named IP access lists 512–515  
    standard access lists 494  
        configuring 498–503  
        features 495–496  
        matching logic 496–497  
        wildcard masks 497–498  
packets 97. *See also* datagrams  
    default routing 365–370  
    encapsulation 94–97  
    flow control 102  
        buffering 103  
        congestion avoidance 103–104  
        windowing 104  
    fragmentation 360–361  
    IGRP log messages, displaying 430, 464  
    interesting 564, 583  
    IP  
        filtering 494  
        log messages, displaying 343, 381  
    IPX  
        encapsulation 687  
        filtering 707–718  
        sending to verify connectivity 694, 729  
    MTU 360–361  
    multiplexing 276–277  
packet-switching  
packet-switching services 572  
    ATM, strengths/weaknesses 573, 584  
    Frame Relay, strengths/weaknesses 573, 584  
    versus leased line technologies 572–573  
    X.25, strengths/weaknesses 573, 584  
PAP (Password Authentication Protocol) 543,  
    557–558, 578  
Parameter Problem ICMP message 288  
partial mesh networks 613–614  
    configuring 637–641  
Password Authentication Protocol. *See* PAP  
passwords  
    accessing CLI 34  
    recovery 56  
periodic updates 417  
permanent MAC addresses 184  
permit statements (access lists) 496, 517  
physical layer (OSI reference model) 84–89, 95, 124  
    ISDN specifications 550  
ping command 275, 289, 350–355, 546, 694, 729,  
    776, 793  
placement of extended IP access lists 507–508  
planning phase, network deployment 762–766  
    IPX networks 797–802  
point-to-point data link protocols 546  
point-to-point leased lines 591, 597–603  
point-to-point serial links, compression 544–546  
poison reverse 423  
port secure command 180, 185–186, 195  
Port Unreachable code (Destination Unreachable  
    ICMP message) 290  
ports 279. *See also* interfaces  
    console ports 34  
    switches  
        address violations 186  
        assigning to VLANs 241–242, 251  
        full-duplex 181, 183  
        half-duplex 181, 183  
        IP configuration, verifying 182–183  
        MAC addresses, limiting associations with  
            185–186  
        numbering 180  
        security, setting 180, 185–186, 195  
        VLAN membership, displaying 241, 251  
    vty ports, controlling access with IP access  
        lists 515–516  
        well-known numbers 280  
PPP (Point-to-Point Protocol), 538–541, 572, 576  
    compression 544–546  
    configuration 768  
    configuring 541–542  
    error detection 543–544

- ISDN 551
- LCP 542–543, 578
- looped link detection 543–544
- LQM 544
- magic numbers 543
- strengths/weaknesses 572, 583
- ppp multilink command 559
- Predictor (compression software) 578
- preparing for exam
  - guidelines 22–24
  - IP addressing 310
    - creating subnet chart 316–320
    - deriving subnet broadcast address 327–333
    - deriving subnet number 321–327
    - identifying address structure 311–315
- presentation layer (OSI reference model Layer 6) 84–88, 124
- preventing routing loops
  - hold-down timers 426–428
  - poison reverse 425
  - route poisoning 428
  - split horizon 423–425
  - STP 222–223
    - convergence 227–229
    - designated port 226
    - forwarding state 223–224
    - root bridge election 224–225
    - timers 227
  - triggered updates 428
- PRI (Primary Rate Interface) 548–549
- Private Addressing 338–340
- private Internets 340
- privileged exec mode (Cisco IOS) 34, 39, 59
- processors 43
- Protocol Type field 540–541
- Protocol Unreachable code (Destination Unreachable ICMP message) 290
- protocols
  - connectionless 99, 126
  - connection-oriented 99, 126
  - ISDN 549–551
  - MAC105
  - nonroutable protocols 121
  - routed 123, 412
  - routing 123, 412
    - comparison of 413, 416, 462
    - definition of 413
    - distance vector routing protocols 412

- goals of 413
- troubleshooting 460
- pruning
  - VLANs 241, 251
  - VTP trunks 239–240
- PVCs (permanent virtual circuits) 610–620

## Q-R

- Q-series ISDN protocols 549, 578
- R ISDN reference point 554, 580
- RAM (random-access memory) 43, 59
  - routers 43, 59
- random-access memory. *See* RAM
- read-only memory. *See* ROM
- read-only mode, Flash memory 53
- recalling commands 36
- recommended CCNA training path 17–18
- recommended study guidelines 22–24
- recovering passwords 56
- Redirect ICMP message 288, 293
- Redirect messages 293
- redundancy. *See* routing loops
- reference points, ISDN 551–555
- reliability of TCP 280
- removing configuration files from NVRAM 46
- resellers, required certification 4
- restricted-static MAC address entrie 184
- resume command 365
- RIP (Routing Information Protocol) 407, 415
  - CCNA exam coverage 415–416
  - configuration 460
  - configuring 429–432
    - debug command output 435–437
  - enabling on IPX networks 703
  - features 429, 463
  - hop count 418–419
  - IP
    - configuration 767–768
    - versus IPX 690, 727
  - IPX 690–691
  - migration to IGRP 437–439
  - subnet masks, absence of in routing updates 440–442
  - updates, displaying log messages 430, 464
  - versus IGRP 429, 463

- RIP-1 416, 462
  - auto summarization 452, 465
  - migrating to RIP-2 445
  - route aggregation 452, 465
  - subnet mask issues 440–442
- RIP-2 416, 443, 446, 462, 464
  - advanced features 443–446
  - auto summarization 452, 465
  - configuration 443, 446
  - migration from RIP-1 445
  - route aggregation 452, 465
- ROM (read-only memory) 43, 59
- root bridge election process 224–225, 249
- root port 223–225, 249, 777
- route aggregation 446–451
- route poisoning 422–423, 426–428
- routed protocols 412
  - versus routing protocols 122–123
- Router Advertisement and Selection ICMP message 288
- router igrp command 430, 464
- router rip command 430, 464
- routers 818
  - auxiliary connections 33, 58
  - CLI
    - hands-on lab 827–831
    - versus switch CLI 179
  - configuration
    - for ISL encapsulation 236
    - IGRP 460
    - IP 355, 471, 474, 480, 485, 783–785
    - IP RIP 767–768
    - IPX 707, 747–748, 752–754, 783–785
    - RIP 460
    - RIP-2 443, 446
  - configuration files
    - copying 45–46, 188, 196
    - erasing at reload time 188, 196
    - updating at reload time 188, 196
  - configuration register 55, 63
  - configuring with setup mode 46–50
  - console connections, configuring 33, 58
  - interfaces 43–44
  - IPX
    - enabling 696
    - parameter settings, displaying 693, 729
  - ISDN backup connections 555
  - memory 43
    - Flash 43, 60
    - NVRAM 43, 60
    - RAM 43, 59
    - ROM 43, 59
  - multiple Telnet connections 34
  - neighboring devices, discovery 370–372
  - Next-Hop routing table entries 418
  - OS categories 54
  - ports 34
  - processors 43
  - running configuration, viewing 46
  - Telnet connections, configuration 33, 58
  - telnetting, suspend function 362–365
  - version information, displaying 188, 196
  - versus bridges and switches 177
- routes
  - counting to infinity 434
  - IP
    - aggregating 452, 465
    - auto summarization 452, 465
    - equal-cost 452
    - static 785
    - troubleshooting 460
  - split horizon 434
  - troubleshooting multiple routes to the same subnet 420
- routing
  - address resolution 118
  - at network layer 114–118
  - IPX 686–687
    - updates, displaying 694, 729
  - loops, troubleshooting 423
  - protocol flows 175, 177
- routing and switching certifications 5
- Routing Information Protocol. *See* RIP
- routing loops (STP) 220–223
  - convergence 227–229
  - designated port 226
  - forwarding state 223–224
  - root bridge election 224–225
  - root ports 225
  - timers 227
- routing protocols 120, 123, 412–414
  - balanced hybrid routing protocols 415–416, 462
  - comparison of 413, 416, 462
  - definition of 413

- distance vector 412–413, 416, 462
    - autosummarization 446–451
    - comparing 428–429
    - convergence 422, 462–463
    - equal-cost routes 420–421
    - hold-down timers 426–428
    - IGRP 433–434
    - loop avoidance 419, 422, 462–463
    - poison reverse 425
    - route aggregation 446–451
    - route poisoning 428
    - routing behavior 416–417
    - split horizon 423–425
    - triggered updates 428
  - goals of 413
  - link-state protocols 415–416, 462
  - terminology 414
  - troubleshooting 460
  - versus routing protocols 122–123
  - routing tables 122–123, 137
    - displaying 343, 381
    - distance vector protocols 417–418
    - IP, displaying 430, 464
    - IPX, displaying 693, 729
  - routing updates
    - absence of subnet masks, troubleshooting 440–442
    - timers 419
  - running configuration 44
    - viewing 46
- S**
- 
- S ISDN reference point 554, 580
  - S/T ISDN reference point 554, 580
  - same-layer interaction (OSI model) 93–94
  - sample TCP/IP network 272–273
  - SAP (Service Advertisement Protocol) 110, 407, 691, 707, 718
    - enabling on IPX networks 703
    - encapsulation 688–689
    - filters 721, 733
      - configuration 767–768
      - matching parameters 720, 733
      - versus IPX packet filters 720
    - packets, internetwork transactions 718
      - tables, displaying 778
      - timers 718
      - updates, filtering 707–709, 718–721, 733
    - SAP IPX Ethernet encapsulation 688, 727
    - SAP IPX FDDI encapsulation 727
    - SAP IPX Token Ring encapsulation 727
    - SAR (segmentation and reassembly) 572
    - saving switch configuration files to TFTP servers 180, 195
    - SBus topology (ISDN) 554–555
    - scenarios, network deployment
      - configuration 766–768
      - planning phase 762–766
      - verification 768–779
    - SDLC (Synchronous Data Link Control) 540–541, 576
    - secondary addresses
      - IP 355–357
      - IPX 689–690
    - security
      - authentication
        - CHAP 557–558
        - PAP 557–558
      - extended IP access lists 497, 503–505
        - example 506–512
      - named IP access lists 512–515
      - passwords, accessing CLI 34
      - standard access lists 494
        - configuring 498–503
        - features 495–496
        - hands-on lab exercises 842–844
        - matching logic 496–497
        - wildcard masks 497–498
      - switch ports, setting 180, 195
    - segmenting LANs
      - with transparent bridges 165–169
      - with switches 170–174
    - sending syslog messages 38
    - serial WAN cabling 546–547
    - servers (TFTP), copying switch configuration files from 180, 195
    - Service Advertising Protocol. *See* SAP
    - session layer (OSI reference model) 84–88, 124
    - setup command 47
    - setup mode, router configuration 46–50
    - shared Ethernet 153
    - show access-list command 499, 708, 730, 769

- show cdp entry command 371
- show cdp interface command 372
- show cdp neighbor command 371
- show cdp neighbor detail command 371, 806
- show compress command 546, 577
- show controllers bri command 561, 583
- show debug command 353
- show dialer interface bri command 561, 569, 583
- show flash command 52
- show frame-relay lmi command 793, 813
- show frame-relay map command 791–793, 815
- show frame-relay pvc command 791, 819–820
- show hosts command 343–344, 380–381
- show interface command 349, 772, 788
- show interfaces bri command 561–562, 569, 583
- show interfaces command 179, 182, 195, 343, 380
- show ip arp command 350, 775, 778, 792
- show ip command 179, 182, 195
- show ip host command 362
- show ip interface brief command 343, 347, 380, 768, 786, 795, 806
- show ip interface command 343, 348, 380, 499
- show ip protocol command 430, 438–439, 464, 773, 789, 795
- show ip route command 346, 348, 351–352, 434, 437, 439, 441, 447, 449, 460, 775, 778, 792, 795
  - options 453–459
- show ipx access-list command 708, 730
- show ipx interface brief command 773, 786, 789
- show ipx interface command 693, 696–697, 708, 729–730
- show ipx route command 693, 698, 700, 729, 773, 778, 790, 795
- show ipx servers command 694, 698, 700, 706, 729, 774, 778, 790, 793, 795, 807
- show ipx traffic command 694, 729
- show isdn active command 570
- show isdn command 561, 583
- show isdn status command 570
- show mac-address-table command 180, 184–185, 195
- show process command 546
- show running-config command 179–181, 346–347, 350, 774, 791
- show spantree command 248
- show trunk command 247
- show version command 180, 188, 195–196
- show vlan command 243
- show vlan-membership command 241, 247, 251
- show vtp command 241, 247, 251
- signaling, ISDN 562–567
- single switch VLAN configuration 242–243
- sliding windows 281
- SNAP (Subnetwork Access Protocol) 110
- SNAP IPX Ethernet encapsulation 688–689, 727
- SNAP IPX FDDI encapsulation 727
- SNAP IPX Token Ring encapsulation 727
- sockets 278–280
- Source Quench ICMP message 288
- Spanning Tree 220–223
  - blocking state 224, 249
  - building initially 249
  - CBPDUs 224, 249
  - configuration status
    - displaying for switches 248
  - convergence 227–229
  - designated port 224–226, 249
  - election process 777
  - features of 230
  - forwarding state 223–226, 249, 778
  - functions of 229–230
  - hands-on lab exercises 836–838
  - learning state 778
  - listening state 778
  - port states 226
  - root bridges, electing 224–225, 249
  - root ports 225, 777
  - timers
    - Forward Delay 227, 250
    - Hello time 227, 250
    - MaxAge 227, 250
  - VLAN information, displaying 241, 251
- SPF (shortest path first) algorithm 415
- SPIDs (service profile identifiers) 551
  - defining 560, 582
  - subaddresses 555
- split horizon 422–425, 434
  - over Frame Relay 626–627
  - with poison reverse 422, 425
- SPX (Sequence Packet Exchange), error recovery 102, 127
- STAC 543, 578
- standard IP access lists 494, 503, 516
  - applying to vty ports 515–516
  - configuring 498–503, 767–768
  - displaying 499, 504, 519



- features 495–496
  - matching logic 496–497, 504
  - planning 802
- standard IPX access lists 715
  - configuring 711–714, 767–768
  - matching 715, 731
- startup configuration 44
- static Frame Relay maps 783, 785
- static IP routes 785
- store-and-forward processing 174–175, 193
- storing IOS images in Flash memory 50–53
- subaddresses, ISDN SPIDs 555
- subcommands 40
- subinterfaces 624
- subnet masks 298, 306, 308–309, 376
  - binary conversion 314
  - display types, setting 344, 381
  - RIP-1/IGRP issues 440, 442
- subnet numbers 297, 375
  - displaying 818
- subnets 118, 303–306, 375
  - absence of in routing updates, troubleshooting 440–442
  - binary conversion 307–309
  - contiguous 448
  - deriving from IP address information 474, 485–486
  - deriving subnet broadcast address 327–333
  - deriving subnet number 321–327
  - designing for Class B IP networks 396, 399, 402
  - designing for Class C IP networks 397, 402, 405
  - directly connected 416
  - equal-cost routes 420–421, 452
  - list chart, creating 316–320, 334–337
  - practice questions 943–988
- supernetting 451
- suspend function (Telnet) 362–365
- SVCs (switched virtual circuits) 610–613
- switches
  - 1900 series 179
  - address violations 180, 195
  - autonegotiation 182
  - CLI 179
    - hands-on lab 831–832, 834–836
    - versus router CLI 179
  - configuring 179, 188, 196
    - as VTP clients 246
    - as VTP servers 246
    - duplex 181, 183
    - IP support 181, 183
    - methods of 179
  - configuration files
    - copying from TFTP servers 180, 195
    - copying to TFTP servers 187
    - displaying version information 180, 195
    - erasing at reload time 188, 196
    - managing 187–188, 196
    - saving to TFTP servers 180, 195
    - updating at reload time 188, 196
  - cut-through processing 174–175, 193
  - encapsulation
    - 802.10 237, 250
    - 802.1Q 237, 250
    - ISL 236–237, 250
    - LANE 237, 250
  - fragment-free processing 174–175, 193
  - internal logic 171
  - ISDN
    - configuration 569
    - defining to router 560, 582
  - ISL trunks 235
  - LANs 170–175
  - logic behind 170
  - MAC address tables
    - configuration 183, 186
    - displaying contents 183, 186
  - neighboring devices
    - discovery 370–372
    - learning about via CDP 372
  - ports
    - address violations 186
    - assigning to VLANs 241–242, 251
    - duplex settings, verifying in 182–183
    - full-duplex 181, 183
    - half-duplex 181, 183
    - IP configuration, verifying 182–183
    - MAC addresses, limiting associations with 185–186
    - numbering 180
    - security, setting 180, 185–186, 195
    - VLAN membership, displaying 241, 251
  - Spanning Tree configuration status, displaying 248
  - store-and-forward processing 174–175, 193
  - system files, managing 187–188, 196
  - trunks, hands-on lab 836–838

- version information, displaying 188, 196
- VTP configuration information 237, 247
- SYN field, TCP connection establishment 283
- Synchronous Data Link Control. *See* SDLC
- synchronous serial data-link protocols,
  - comparing 540–541
- synchronous serial leased lines 538, 572, 575
  - clock source 575
  - compression 544, 546
  - HDLC 540, 572, 583
  - LAPB 540, 572, 583
  - PPP 540, 572, 583
- syntax
  - extended IP access lists 507
  - named IP access lists 513–514
  - standard access lists 499–500
- syslog messages 37
  - sending 38
  - viewing 37

## T

---

- T ISDN reference point 554, 580
- T/1 lines 539, 575
- T1 mux 539, 575
- TA (Terminal adapter) ISDN function group 553, 580
- TCP (Transmission Control Protocol) 98, 272, 277, 819
  - connections 282–284
  - error recovery 102, 127, 280, 796
  - features of 277
  - flow control 281–282
  - forward acknowledgment 280
  - functions of 284, 374
  - headers 278
  - multiplexing 278–280
  - ordered data transfer 284
  - sockets, connections 278–280
  - versus UDP 284–286
  - well-known port numbers 279
- TCP/IP (Transport Control Protocol/Internet Protocol) 98, 267
  - ARP 286
  - ARP Broadcast 274
  - DNS 274
  - FTP 294–295
  - ICMP 287–288
    - Address Mask Request/Reply message 288
    - Code field 288
    - Destination Unreachable messages 288–291
    - Echo message 288–289
    - Echo Request/Reply messages 289
    - Parameter Problem message 288
    - Redirect message 288, 293
    - Router Advertisement and Selection message 288
    - Source Quench message 288
    - Time Exceeded messages 288, 291–293
    - Timestamp message 288
    - Type field 288
  - IP addressing 299
    - address classes 299–302
    - CIDR 338–339
    - configuring 342–354
    - deriving subnet broadcast address 327–333
    - deriving subnet number 321–327
    - identifying address structure 311–315
    - naming configuration 361–362
    - NAT 340–342
    - network numbers 300–301
    - over Frame Relay subinterfaces 357–360
    - private addressing 339–340
    - secondary addresses 355–357
    - subnet chart, creating 316–320
    - subnet list chart, creating 334–337
    - subnets 303–309
    - test preparation 310
  - sample network 272–273
  - TCP 277, 819
    - connection establishment/termination 282–284
    - error recovery 280
    - features of 277
    - flow control 281–282
    - forward acknowledgement 280
    - functions of 284, 374
    - headers 278
    - multiplexing 278–280

- ordered data transfer 284
- sockets 278–280
- versus UDP 284, 286
- TFTP 295–296
- UDP 819
  - data transfer 285
  - DNS 285
  - functions of 285, 374
  - multiplexing 285
  - NFS 285
  - versus TCP 284, 286
  - versus OSI and NetWare 97–98
- TE1 (Terminal Equipment 1) ISDN function group 553, 579–580
- TE2 (Terminal Equipment 2) ISDN function group 553, 579
- TE2 (Terminal Equipment 2) devices 552
- telco 539, 575
- Telnet sessions
  - router connections, configuring 33–34, 58
  - multiple, resuming 365
  - suspend function 362–365
- telnet command 362
- terminal history size command 36
- terminal ip netmask command 350
- terminal ip netmask-format command 343, 346, 381
- terminating TCP connections 283
- terminology, routing protocols 414
- testing locations 3
- TFTP (Trivial File Transfer Protocols) 180, 195, 295–296
- TIA (Telecommunications Industry Association), WAN cabling standards 547
- ticks 690
- Time Exceeded ICMP message 288, 291–293
- timers
  - routing update timers 419
  - SAP 718
  - STP 227
- Timestamp ICMP message 288
- Token Ring 105–108
  - arbitration 106
  - encoding 113
  - functional addresses 128, 158
  - IEEE standards 162, 191
  - IPX encapsulation 688–689, 727
- topics covered on CCNA 8–15
  - cross reference to chapters 16–17
  - study tips 19–21
- trace command 291, 776, 778, 793
- traffic
  - filtering with access lists 494–496
    - IP 494
    - SAP updates 707–720
  - flow control 102
    - buffering 103
    - congestion avoidance 103–104
    - windowing 104, 281–282
  - interesting 582
  - IPX, displaying statistics on 694, 729
- traffic-share balanced command 452
- traffic-share command 430, 464
- trailers 93
- training path for CCNAs 17–18
- Transmission Control Protocol. *See* TCP
- transparent bridging 165–169
- transparent VTP mode, enabling 239, 242
- Transport Control Protocol/Internet Protocol. *See* TCP/IP
- transport layer (OSI reference model Layer 4) 84–89, 124
  - connection-oriented/connectionless protocols 98, 126
  - error recovery 99, 127
  - flow control 102, 105
- triggered updates 422, 428
- troubleshooting
  - distance vector routing protocols 453–460
  - IP routes 460
  - multiple routes to the same subnet 420
  - non-transmission of subnet masks 440–442
  - routing protocols 460
- trunk command 241, 244, 251
- trunks 215, 234
  - configuration 241, 247, 251
  - hands-on lab exercises 836–838
  - ISL 235–236
  - status, displaying 241, 251
  - verifying configuration 248
  - VTP 237–238
- two-wire circuits 539

## U

---

- U ISDN reference point 554, 580
- UAAs (Universally Administered Addresses) 158
- UDP (User Datagram Protocol) 272, 284, 819
  - data transfer 285
  - DNS 285
  - functions of 285, 374
  - multiplexing 285
  - NFS 285
  - versus TCP 284–286
- undebug all command 769
- unicast addresses 127
- unicast MAC addresses 157
- Universally Administered Addresses (UAAs) 518
- unreachable codes (ICMP) 290
- updating configuration files 39
- upgrading images into Flash memory 50–53
- upper layers of OSI reference model 85–86, 88
- User Datagram Protocol. *See* UDP
- user exec mode, IOS CLI 34, 39, 59

## V

---

- V.35 WAN cabling standard 547
- variance command 430, 452, 464
- VCs (virtual circuits) 108, 610–620
- verifying IPX network configuration 806–820
- viewing
  - running configuration 46
  - syslog messages 37
- virtual LANs. *See* VLANs
- vlan command 242
- vlan-membership command 242
- VLANs (virtual LANs) 230–233, 243
  - configuring 241
    - for multiple switches 244–248
    - for single switch 242–243
  - defining 241, 251
  - hands-on lab exercises 836–838
  - implementing 233–234
  - membership, displaying 241, 251
  - naming 241–242, 251
  - numbering 242

- parameters, verifying 243
- pruning 239–241, 251
- Spanning Tree information, displaying 241, 251
- summary information, displaying 241, 251
- switch ports, assigning to 241–242, 251
- tagging 234
  - 802.10 237, 250
  - 802.1Q 237, 250
  - ISL 236–237, 250
  - LANE 237, 250
- trunking 235–236
  - configuration 241, 247, 251
  - status, displaying 241, 251
  - verifying configuration 248
- VTP 237
  - advertisements 237–238
  - client mode 238–239, 251
  - clients, configuring switches as 246
  - configuring 247
  - mechanics of 237–239, 251
  - modes of operation 238
  - parameters, resetting to defaults 241, 251
  - pruning 239–240
  - server mode 238–239, 251
  - servers, configuring switches as 246
  - status, displaying 241, 251
  - transparent mode 238–242, 251
- VLSM (variable-length subnet mask) 315
- VTP (VLAN Trunking Protocol) 215, 237
  - advertisements 237–238
  - client mode 238–239, 251
  - configuration, displaying 247
  - mechanics of 237, 239, 251
  - modes of operation 238
  - parameters, resetting to defaults 241, 251
  - pruning 239–240
  - server mode 238–239, 251
  - servers 237
  - status, displaying 241, 251
  - transparent mode 238–242, 251
- vtp command 241–242, 247, 251
- vtp trunk pruning-disable command 241, 251
- vty ports
  - access lists, applying 515–516
  - controlling access with IP access lists 515–516

---

## W

---

### WANs

- 2-wire circuits 575
- 4-wire circuits 575
- asynchronous serial leased lines 539, 575
- cabling standards 546–547
- comparing 571–574
- data-link protocols
  - comparing 540–541
  - configuring 541–542
  - Protocol Type field 540–541
- DSU/CSU 575
- error recovery 540
- four-wire circuits 539
- Frame Relay 609
  - broadcast handling 625–626
  - configuring 628–646
  - DLCI 616–620
  - Layer 3 addressing 621–625
  - LMI 614–616
  - split horizon 626–627
  - VCs 610, 612–614
- HDLC protocol, compression 544, 546
- ISDN 548
  - channels 548
  - CHAP 557–558
  - configuring 555–556
  - DDR 560–562
  - function groups 551–554
  - home-based 554
  - legacy DDR configuration 563–571
  - multilink PPP 558–559
  - out-of-band signaling 550
  - PAP 557–558
  - protocols 549–550
  - reference points 551–554
  - SPIDs 551
- LAPB protocol, compression 544, 546
- layers 573–574
- packet-switching services 572
- PPP 541
  - compression 544–546
  - error detection 543–544
  - LCP 542–543, 578
  - looped link detection 543–544

### protocols

- HDLC 539, 576
  - LAPB 539, 576
  - LAPD 541, 576
  - PPP 539, 576
  - SDLC 540–541, 576
  - synchronous links 538
  - synchronous serial leased lines 538, 572, 575
  - two-wire circuits 539
- well-known port numbers 279–280
- wildcard masks 497–498
  - extended IPX access list concerns 717
  - IP addresses 497, 518
  - standard IPX access lists 713–714
- windowing, TCP flow control 281–282
- write erase command 46, 188, 196
- write terminal command 350

---

## X-Y-Z

---

- X.21 WAN cabling standard 547
- X.25 572–573, 584