



Numerics

- 10,000-Mbps Ethernet, 322
- 1000-Mbps Ethernet, 322
- 100-Mbps Ethernet, 320–321
- 10-Mbps Ethernet, 318–320
- 1900 switches
 - accessing, 369
 - HTTP, 190
 - passwords, 378
 - testing, 375
- 2900 switches
 - configuring, 372
 - passwords, 379
 - ping command, 376
 - testing, 375
- 3512XL switches
 - configuring, 370
 - password, 378
 - testing, 371
 - troubleshooting, 370
- 3600 series routers, 77
- 3-way handshake sequences, 171
- 802.2 SAP headers, Ethernet frame format, 331–333

A

- above baselines, building, 691
- access
 - lists, 641
 - methods, 32
 - switches, 369
- Access Control Lists (ACLs), 18, 95
- access layer, 46
- accounting, managing, 108
- acknowledgments (acks), 16
- ACLs (Access Control Lists), 18, 95
- active monitors, 37
- adding
 - routing protocols, 70
 - static Frame Relay maps, 510
- Address Resolution Protocol (ARP), 13, 306
- addresses
 - broadcast, 198
 - Ethernet, 335–336
 - Frame Relay, 523–528
 - IP, 193–194
 - subnets, 194–199
 - summarization, 199–202
 - local multicast, 170
 - MAC, 13, 167
 - NAT, 199
 - Novell, 276–277
- administration, shut down, 599
- Advanced Search Tool (TAC), 105
- advantages of VLANs, 434
- advertisements
 - CDP, 67
 - loopbacks in EIGRP, 593
- algorithms
 - DUAL, 208
 - SPF, 209
- American Wire Gauge (AWG), 40
- analyzing
 - 3-way handshake sequences, 171
 - BPDU, 389–391
 - host-to-host connectivity, 159
 - IP headers, 165
 - IPX
 - client startup, 274
 - headers, 267
 - RIP headers, 268
 - protocols, 115–122, 156
 - RConsole SPX packets, 273
 - RIP packets, 169
 - routes, 156
 - SPAN, 362
 - Telnet, 171
- Application Layer (Layer 7), 14
- applications
 - Novell, 254
 - Internet Layer, 261–272
 - Transport Layer, 272–273
 - upper-layer, 274–276
 - port numbers, 175
 - TCP/IP, 160–162
 - Internet Layer, 162–167
 - Transport Layer, 168–176
 - upper-layer, 176–192
 - Telnet, 176
- application-specific integrated circuits (ASICs), 382
- applying
 - routers as Frame Relay switches, 503–512
 - Sniffer Pro, 118–122

architecture
 Cat5000/Cat6000, 400–404
 selecting, 9–20
ARP (Address Resolution Protocol), 13
 clear arp-cache command, 167
 inverse ARP, 524–526
 show arp command, 72
 no ip proxy-arp command, 174
 tables, 306
ASICs (application-specific integrated circuits), 382
authentication, 608, 610
auto frame-type detection, 260
automatic summarization, closing, 158
autonegotiation hierarchy, 342
AWG (American Wire Gauge), 40

B

back-to-back configuration (Frame Relay), 497–503
Backup
 configuration, 240
 dial, 644–652
 interfaces, 644, 647
 Trouble Tickets, 712–717
backward explicit congestion notification (BECN), 514, 516
baseband signaling, 319
baselining, 138
 IPX, 231
 troubleshooting, 56–57
 WANDL, 113
Basic Rate Interface (BRI), 146, 616–620, 628
BEC (Gigabit EtherChannel), 448
BECN (backward explicit congestion notification), 514, 516
BGP (Border Gateway Protocol), 210–212, 543
big-endian systems, 34
binary place values, 22–23
bindery, 258, 275
bits
 C/R, 517
 EA, 518
 Frame Relay, 514
blades, routers, 470
boot helper (rxboot) mode, 241
BOOTP (Bootstrap Protocol), 191
Border Gateway Protocol (BGP), 210–212, 543
bouncing interfaces, 442
BPDU analysis, 389–391
BRI (Basic Rate Interface), 146, 616–620, 628
bridges, 380–382, 433
broadband networks, 319
broadcast addresses, 198
broadcast domains, 36, 384, 432–435
 configuring, 435–439
 traffic types, 435
 VMPS, 439
building Layer 2 baselines, 685

C

C/R (Command/Response) bit, 517
cables, 40
 straight-through, 368
 unplugging, 63
caches, clear arp-cache command, 167
calculating binary place values, 22
CAM (content addressable memory), 376
canonical names, 35
capturing
 packets, 162
 Syslog, 713
carrier sense (CS), 319
carrier sense multiple access collision detect (CSMA/CD), 33
Cat5000/Cat6000 architecture, 400–404
CatOS
 switches, 395–400, 687
 troubleshooting, 362–379
 VTP statistics, 458
CCP (Cisco Control Protocol), 609
CD (collision detection), 319
CDaemon Syslog, 699
CDP (Cisco Discovery Protocol), 67, 277
CDPD (cellular digital packet data), 42
CEF (Cisco Express Forwarding), 17, 472–473
cellular digital packet data (CDPD), 42
central office (CO), 597
CHAP (Challenge Handshake Authentication Protocol), 610
characters
 ping command output, 84
 traceroute command, 87
checklists, troubleshooting, 139

- chesapeakebay switch, documentation, 701
- CIC (Cisco Info Center), 189
- CIDR (Classless Interdomain Routing), 20
- CIR (Committed Information Rate), 513, 515
- Cisco approach to troubleshooting, 47–55
- Cisco Control Protocol (CCP), 609
- Cisco Discovery Protocol (CDP), 67, 277
- Cisco Express Forwarding (CEF), 17, 472–473
- Cisco Info Center (CIC), 189
- Cisco Marketplace, 101
- Cisco Website (CCO), 99–100
- CiscoWorks, 109–112, 189
- CiscoWorks for Switched Internetworks (CWSI), 109
- classes, 21, 193
- Classless Interdomain Routing (CIDR), 20
- clear arp-cache command, 72, 167
- clear counters command, 64
- clear frame-relay-inarp command, 508
- clear ip route command, 71
- clear trunk vlan# command, 458
- clearing
 - 2900 switches, 372
 - counters, 598
 - existing switch configurations, 369
 - normal call clearing, 637
- CLI (command-line interface), 394
 - CatOS-based switches, 395–400
 - IOS-based switches, 400
- clients, NetWare, 260
- CLNS (Connectionless Network Protocol), 210
- clock rate
 - command, 63
 - statement, 528
- closing automatic summarization, 158
- CO (central office), 597
- code, ICMP, 97
- collision detection (CD), 319
- collisions
 - bridges, 380–382
 - domains, 36, 384
- Command/Response (C/R) bit, 517
- commands, 67, 192
 - backup interface, 644
 - clear arp-cache, 72, 167
 - clear counters, 64
 - clear frame-relay inarp, 508
 - clear ip route, 71
 - clear trunk vlan#, 458
 - clock rate, 63
 - config-register, 241
 - configure terminal, 142
 - copy tftp flash, 241
 - debug, 94–98
 - debug dialer, 643
 - debug dialer events, 640
 - debug frame-relay events, 525
 - debug frame-relay lmi, 501, 508, 519
 - debug frame-relay packet, 526
 - debug ip bgp, 211
 - debug ip icmp, 96
 - debug ip ospf, 209
 - debug ip packet, 96
 - debug ip packet detail, 97
 - debug ip rip events, 204
 - debug ipx packet, 261, 265
 - debug isdn q921, 633, 635
 - debug ppp authentication, 610
 - debug ppp negotiation, 609
 - debug serial interface, 603
 - debug service timestamps, 499
 - dialer map, 625
 - dialer-group, 643
 - dialer-list 1 protocol ip permit global, 641
 - dialer-list protocol ip permit, 625
 - display networks, 258
 - enable, 142
 - encap frame-relay, 498
 - erase startup-config, 177
 - frame relay route, 505
 - frame-relay intf-type dce, 499
 - frame-relay local-dlci, 498
 - Hayes, 8
 - hostname, 368
 - interface vlan #, 372
 - ip classless, 156
 - ip http server, 365
 - ipx network, 272
 - ipx routing, 235
 - load monitor, 257
 - logging
 - IOS troubleshooting tools, 92–94
 - show logging, 92
 - synchronous, 530
 - no auto-summary, 158, 303, 594
 - no ip access-group ftp out, 52
 - no ip http server, 365

- no ip proxy-arp, 174
 - no logging, 93
 - no shut, 66, 147, 600
 - no synchronization, 543
 - ping, 695
 - 2900 switches, 376
 - character output, 84
 - Ethernet, 304
 - extended, 85
 - hostnames, 159
 - IOS troubleshooting tools, 84–87
 - IP, 149
 - IPX, 231, 261
 - testing, 374
 - user-mode, 84
 - port monitor, 389
 - reload, 242, 406
 - set spantree mode mst, 450
 - set trunk mod#/port#, 446
 - set trunk mod#/port# mod, 445
 - set vtp domain vtpname, 454
 - sh int switching, 107
 - show
 - IOS troubleshooting tools, 62–84
 - ISDN, 637
 - show access-lists, 52
 - show arp, 72
 - show buffers, 80
 - show cdp neighbors, 68
 - show cdp neighbors detail, 263
 - show controllers, 63, 148, 499
 - show debug, 97
 - show frame-relay lmi, 508, 519
 - show frame-relay map, 502, 527
 - show frame-relay route, 531
 - show frame-relay traffic, 537
 - show hosts, 187
 - show interfaces, 63
 - show interfaces bri0 1 2, 628
 - show interfaces ethernet0, 66
 - show interfaces serial 0, 598
 - show interfaces serial0, 64
 - show ip bgp, 211
 - show ip bgp summary, 210
 - show ip interface brief, 66
 - show ip interface s0, 52
 - show ip ospf, 209
 - show ip protocols, 69
 - show ipx interface ethernet 0, 248
 - show ipx route, 276
 - show ipx servers, 276
 - show isdn history, 634
 - show isdn status, 631
 - show logging, 92
 - show mac address, 690
 - show memory, 78–79
 - show module, 448
 - show port, 389, 403
 - show protocols, 69, 692
 - show run interface bri0, 639
 - show running-config, 690
 - show spanning-tree, 450
 - show stacks, 80
 - show start, 76
 - show startup-config, 75, 372
 - show tech-support, 82, 105
 - show version, 73
 - show vlan, 449
 - show vmps, 439
 - spanning-tree vlan 1, 719
 - switchport mode trunk IOS, 442
 - terminal monitor (term mon), 602
 - trace
 - IOS troubleshooting tools, 87–91
 - logging, 88
 - traceroute, 30, 695
 - characters, 87
 - extended, 90
 - tracert, 695
 - write memory, 77
 - write-erase, 177
- committed burst, 515
 - Committed Information Rate (CIR), 513, 515
 - Common Spanning Tree (CST), 450
 - communication protocols, 9
 - comparisons, models, 46
 - components, ISDN, 617
 - compression, 609
 - config-register command, 241
 - configuration
 - 2900 switches, 372
 - 3512XL switch, 370
 - ANSI LMI, 520
 - back-to-back (Frame Relay), 497–503
 - Backup, 240
 - BPDU, 389–391
 - BRI, 628
 - copying, 179, 702

EtherChannel, 448
 Ethernet, 297
 Frame Relay switches, 504
 HSRP, 471
 interfaces, 313
 IP parameters, 365
 IPX, 248
 logging, 93
 lower-layer discovery, 682
 management, 108
 routers, 374, 532
 scenario host, 368
 SPIDs, 626
 static maps, 528, 535
 subnets (Frame Relay), 506
 switches, 362–379
 terminal servers, 138
 upper-layer discovery, 682
 VLANs, 435–439
 configure terminal command, 142
 Connectionless Network Protocol (CLNS), 210
 connection-oriented Data Link Layer technology, 516
 connections, 40
 end-to-end, 305
 Frame Relay, 506
 frames, 508
 host-to-host, 159
 ISDN, 630. *See also* ISDN
 PPP, 607
 layers, 607–610
 troubleshooting, 610–615
 serial 0/0, 148
 connectors, RJ-45, 39
 contacting TAC, 105
 content addressable memory (CAM), 376
 controllers, testing, 590
 copy tftp flash command, 241
 copying configurations, 179, 702
 Core Layer, 46
 costs, paths, 387
 counters, clearing, 598
 CPE (customer premises equipment), 516
 crab routers, documentation, 700
 CRC (cyclical redundancy check), 445
 crossover cables, 40
 crossover Category 5 in-line couplers, 148
 CS (carrier sense), 319
 CSMA/CD (carrier sense multiple access collision detect), 33
 CST (Common Spanning Tree), 450

customer premises equipment (CPE), 516
 CWSI (CiscoWorks for Switched Internetworks), 109
 cyclical redundancy check (CRC), 445

D

D Channel, verifying, 628
 DA (destination address), 13
 dampening, 544
 Data Carrier Detect (DCD), 600
 Data Link Layer (Layer 2), 30
 Data Set Ready (DSR), 600
 datagrams, IP headers, 163, 169
 data-link connection identifier (DLCI), 514
 DCD (Data Carrier Detect), 600
 DDR (dialer-on-demand routing), 641–644
 DDR (dial-on-demand routing), 270, 629
 DE (Discard Eligible), 514–515
 debug dialer command, 643
 debug dialer events command, 640
 debug frame-relay events command, 525
 debug frame-relay lmi command, 501, 508, 519
 debug frame-relay packet command, 526
 debug ip bgp? command, 211
 debug ip icmp command, 96
 debug ip ospf ? command, 209
 debug ip packet command, 96
 debug ip packet detail command, 97
 debug ip rip events command, 204
 debug ipx packet command, 261, 265
 debug isdn q921 command, 633, 635
 debug ppp authentication command, 610
 debug ppp negotiation command, 609
 debug serial interface command, 603
 debug service timestamps command, 499
 debugging
 ACLs, 95
 IOS troubleshooting tools, 94–98
 packets, 204
 serial interfaces, 603
 Time Stamps, 95
 defaults
 interfaces, 313
 switches, 364
 desktop tools, 124–128
 destination address (DA), 13
 detection, 609
 auto frame-type, 260
 errors, 609

devices, testing, 590
 dial backup, 644–652
 dial strings, ISDN, 629
 dialer map command, 625
 dialer map-class statements, 651
 dialer-group command, 643
 dialer-list 1 protocol ip permit command, 625
 dialer-list 1 protocol ip permit global command, 641
 dialer-on-demand routing (DDR), 641–644
 dialers

- lists, 641
- troubleshooting, 638

 dial-on-demand routing (DDR), 270, 629
 did connections, 173
 Diffusing Update algorithm (DUAL), 208
 Digital Intel Xerox (DIX), 30
 Digital Subscriber Lines (DSL), 597
 disabled states, 387
 Discard Eligible (DE), 514–515
 discontinuous subnets, 155
 discovery labs, Trouble Tickets, 681–695
 DISL (Dynamic Inter-Switch Link), 445
 display networks command, 258
 Distribution Layer, 46
 DIX (Digital Intel Xerox), 30, 327–330
 DLCI (data-link connection identifier), 514. *See also*

- Frame Relay, addresses

 DNS (Domain Name System), 73
 documentation, 91

- CD-ROM, 100–101
- labs, 695–705
- routers, 308
- troubleshooting, 56–57

 DoD TCP/IP suite, troubleshooting, 45–47
 Domain Name System (DNS), 73
 domains

- broadcast, 36, 384, 432–435
- collision, 36, 380–384
- set vtp domain vtpname command, 454
- TDR, 37

 dot1Q (IEEE 802.1Q), 447
 drivers, loading, 258
 DSL (Digital Subscriber Lines), 597
 DSR (Data Set Ready), 600
 DUAL (Diffusing Update algorithm), 208
 duck routers

- building Layer 3 baselines, 691
- documentation, 698

dumps, memory, 703
 Dynamic Inter-Switch Link (DISL), 445

E

EA (Extension) bits, 518
 Echo Reply packets, 165
 Echo Request packets, 165
 ECN (explicit congestion notification), 518
 editors, RFC, 8
 EIGRP (Enhanced IGRP), 157, 206–208

- Frame Relay, 539
- loopbacks, 593
- Novell, 278–279
- redistribution, 708–712

 electrostatic discharge (ESD), 405
 enable command, 142
 encaps frame-relay command, 498
 encapsulation, 12

- Frame Relay, 516
- HDLC, 598–601
 - layers, 602
 - troubleshooting, 602–607
- IP/IPX, 255
- ISL, 447
- mismatches, 600
- Novell, 257
- PPP, 609–610

 end-system data flow, 12
 end-to-end connectivity, 305
 Enhanced IGRP. *See* EIGRP
 erase startup-config command, 177
 errors, 609
 ESD (electrostatic discharge), 405
 EtherChannel, 448–449
 Ethernet, 33, 295, 318

- 10,000-Mbps, 322
- 1000-Mbps, 322
- 100-Mbps, 320–321
- 10-Mbps, 318–320
- addressing, 335–336
- configuring, 297
- frame format, 34
- frames, 325
 - 802.2 SAP headers, 331–333
 - Ethernet II formats, 327–330
 - raw (Novell 802.3) headers, 330–331
 - SNAP headers, 333–335

- IEEE 802.3 evolution, 323–324
- IP hosts, 302
- Physical Layer, 337
- transparent bridging, 381
- Trouble Tickets, 343–357
- troubleshooting, 296–317, 337–343
- wireless, 323
- evolution of IEEE 802.3 Ethernet, 323–324
- excess burst, 515
- explicit congestion notification (ECN), 518
- extended ping command, 85
- extended traceroute command, 90
- Extension (EA) bits, 518

F

- factory defaults, resetting switches, 364
- Fast EtherChannel (FEC), 448
- fast switching, 17
- fault management, 108
- FCS (frame check sequence), 13
- FDDI (Fiber Digital Device Interface), 34
- Feature Navigator, 238
- FEC (Fast EtherChannel), 448
- FECN (forward explicit congestion notification), 514, 516
- ferry routers, documentation, 700
- fields, show port command, 403
- File Transfer Protocol (FTP), 183
- files, 187
 - hosts (Windows 2000), 188
 - isdn ending configs, 652
 - running-config, 595
- filters
 - routes, 18
 - SAP, 271
- Flash
 - IOS versions, 236
 - memory, 236
 - upgrading, 237
- floating static routes, 646
- Fluke handheld devices, 113
- formats
 - Ethernet II (DIX Ethernet), 327–330
 - frames, 34
 - PPP frames, 608
- forward explicit congestion notification (FECN), 514, 516

- forwarding states, 387
- FQDN (fully qualified domain names), 189
- frame check sequence (FCS), 13
- Frame Relay
 - addresses, 523–528
 - applying routers as switches, 503–512
 - back-to-back configuration, 497–503
 - BGP, 543
 - frames, 516–523
 - history of, 512–516
 - inverse ARP, 524–526
 - IS-IS, 541
 - loopback testing, 544–546
 - OSPF, 540
 - Physical Layer, 528–536
 - routing protocols, 538–544
 - standards, 512
 - static maps
 - adding, 510
 - statements, 569
 - subinterfaces, 529
 - terminology, 514
 - topologies, 529
 - Trouble Tickets, 546–579, 712–717
 - troubleshooting, 496–497, 536–546
- frame relay route commands, 505
- frame-relay interface-dlci dlci# command, 536
- frame-relay intf-type dce command, 499
- frame-relay local-dlci command, 498
- frames, 34
 - auto frame-type detection, 260
 - connections, 508
 - Ethernet, 325
 - 802.2 SAP headers, 331–333
 - Ethernet II (DIX Ethernet) formats, 327–330
 - raw (Novell 802.3) headers, 330–331
 - SNAP headers, 333–335
 - Frame Relay, 516–523. *See also* Frame Relay maps, 498
 - PPP formats, 608
 - tagging, 447
 - types, 162, 254–261
- FTP (File Transfer Protocol), 183
- fully qualified domain names (FQDN), 189

G

GD (General Deployment), 73, 238
 Get Nearest Server (GNS), 261
 Gigabit EtherChannel (BEC), 448
 Gigabit Ethernet, 321
 global positioning system (GPS), 42
 GNS (Get Nearest Server), 261
 goose routers, documentation, 700
 GPS (global positioning system), 42

H

hard code speed, 384
 hardware
 support, 102
 tools, 113
 Hayes command, 8
 HDLC (High-Level Data Link Control), 68, 235, 498, 598–601
 layers, 602
 troubleshooting, 602–607
 headers
 Frame Relay, 517–519
 IP, 163, 165
 IPX, 266
 layers, 13
 heron router documentation, 699
 hex place values, 35
 hierarchies, autonegotiation, 342
 High Speed Study Group (HSSG), 322
 High-Level Data Link Control. *See* HDLC
 High-Speed Serial Interface (HSSI), 64
 history of Frame Relay, 512–516
 hops, TTL, 87
 hosta
 CDaemon Syslog, 699
 testing, 379
 hosta IP configuration, 376
 hostnames
 command, 368
 ping command, 159
 hosts, 21–22, 187
 2900 switch ping command, 376
 routes, 596
 scenario configuration, 368
 subnets, 198
 Windows 2000, 188

host-to-host connectivity, testing, 159
 host-to-host delivery, 15
 HSRP (Hot Standby Router Protocol), 470–471
 HSSG (High Speed Study Group), 322
 HSSI (High-Speed Serial Interface), 64
 HTTP (Hypertext Transport Protocol), 190, 365
 hubs, 36, 380, 532
 hybrid back-to-back configuration, 502

I

IAB (Internet Architecture Board), 8
 IANA (Internet Assigned Numbers Authority), 8
 ICMP type values and codes, 97
 IDB (Interface Description Block), 592
 IEEE 802.1Q, 447
 IEEE 802.3 Ethernet evolution, 323–324
 IESG (Internet Engineering Steering Group), 8
 IETF (Internet Engineering Task Force), 8
 IGRP (Interior Gateway Routing Protocol), 206–208
 infrastructure, 113
 Integrated Services Digital Network. *See* ISDN
 Interface Descriptor Block (IDB), 592
 interface vlan # command, 372
 interfaces
 backup, 644, 647
 bouncing, 442
 BRI, 628
 CLI, 394
 CatOS-based switches, 395–400
 IOS-based switches, 400
 default settings, 313
 HSSI, 64
 IP, 145
 ISDN BRI, 616–620
 layers, 620–637
 troubleshooting, 637–641
 MII, 337
 NIC, 10
 normal, 649
 serial
 debugging, 603
 keepalives, 603
 Trouble Tickets, 680–681
 viewing, 598
 shut down, 599
 Sniffer Pro, 115
 applying, 118–122
 starting, 116–117

- statistics, 310
- switches, 364
- targets, 339
- testing, 590
- troubleshooting, 146
- WAN, 586
- Interior Gateway Routing Protocol (IGRP), 206–208
- Intermediate System-to-Intermediate System (IS-IS), 158, 209–210, 541
- International Organization for Standardization (ISO), 108
- Internet Architecture Board (IAB), 8
- Internet Assigned Numbers Authority (IANA), 8
- Internet Engineering Steering Group (IESG), 8
- Internet Engineering Task Force (IETF), 8
- Internet Layer
 - Novell, 261–272
 - TCP/IP, 162–167
- Internet Network Information Center (InterNIC), 8
- Internet Protocol. *See* IP
- Internet Research Task Force (IRTF), 8
- Internet service providers (ISPs), 8
- Internet Society (ISOC), 8
- Internetwork Packet Exchange. *See* IPX
- InterNIC (Internet Network Information Center), 8
- Inter-Switch Link (ISL), 8, 342
- inter-VLAN routing, 460–471
- Inverse ARP, 502, 524–526
- IOS (Internet Operating System)
 - Configuration Backup, 240
 - Flash, 236
 - life cycle, 74
 - switches, 400
 - building Layer 2 baselines, 690
 - troubleshooting, 362–379
 - tools
 - debug commands, 94–98
 - logging commands, 92–94
 - ping commands, 84–87
 - show commands, 62–84
 - trace commands, 87–91
 - troubleshooting, 62
 - upgrading, 241
- IP (Internet Protocol), 135
 - addresses, 193–194
 - subnets, 194–199
 - summarization, 199–202
 - headers, 163, 165
 - hosta configuration
 - configuration
 - hosta IP, 376
 - hosts, 302
 - IPX encapsulation, 255
 - MAC addresses, 167
 - parameters, 365
 - ping command, 149
 - routes, 302
 - routing, 212
 - testing, 145
 - troubleshooting, 136–160
- ip classless command, 156
- ip default-gateway statement, 241
- ip http server command, 192, 365
- ip helper-address, 192
- IPX (Internetwork Packet Exchange)
 - addressing, 276–277
 - binding, 258
 - clients, 274
 - configuration, 248
 - encapsulation, 255
 - headers, 266
 - Novell. *See* Novell
 - SAP filters, 271
 - testing, 252
 - troubleshooting, 230–253
 - verifying, 304
- ipx network commands, 272
- IPX RIP protocol, 277–278
- ipx routing command, 235
- IRTF (Internet Research Task Force), 8
- ISDN (Integrated Services Digital Network), 712–717
- ISDN BRI (Integrated Services Digital Network Basic Rate Interface), 616–620
 - layers, 620–637
 - troubleshooting, 637–641
- isdn ending configs file, 652
- IS-IS (Intermediate System-to-Intermediate System), 158, 209–210
 - Frame Relay, 541
- ISL (Inter-Switch Link), 8, 342, 445–447
- ISO (International Organization for Standardization)
 - network management, 108
- ISPs (Internet service providers), 8

K

keepalives, 603
kentnarrows switch, documentation, 701
Kermit protocol, 8
keywords, logging, 92

L

LAN Management Solution (LMS), 109
LANE (LAN Emulation), 109
LAPD (Link Access Procedure D), 620
LAPD (Link Access Protocol), 512
Layer 1, 36
Layer 2, 30, 685
Layer 3, 16, 691
Layer 4, 15
Layer 5, 15
Layer 6, 14
layers
 Access, 46
 Application, 14
 Core, 46
 Data Link, 30
 discovery labs, 682
 Distribution, 46
 Ethernet, 297
 HDLC, 602
 headers, 13
 Internet (Novell), 261–272
 ISDN BRI, 620–637
 Network, 16
 OSI, 11. *See also* OSI
 Physical, 36
 Ethernet, 337
 Frame Relay, 528–536
 PPP, 607–610
 Presentation, 14
 Session, 15
 TCP/IP, 160–162
 Internet, 162–167
 Transport, 168–176
 upper-layer, 176–192
 Transport, 15, 272–273
 troubleshooting, 44–45
 Upper (Novell), 274–276
LDN (local directory number), 625

leaks, memory, 79
learning states, 388
least significant bit (LSB), 35
LECs (Local Exchange Carrier), 528
LEDs (light emitting diodes), 405
levels, logging, 92
life cycles, IOS, 74
like devices, 40
line termination (LT), 618
Link Access Protocol Channel D (LAPD), 512, 620
link-state advertisement (LSA), 209
listening states, 387
lists
 access, 641
 ACL. *See* ACL
 dialers, 641
little-endian systems, 34
LLC (Logical Link Control), 30
LMI (Local Management Interface), 515, 519–523
LMS (LAN Management Solution), 109
load monitor command, 257
loading drivers, 258
local directory number (LDN), 625
Local Exchange Carrier (LEC), 528
Local Management Interface (LMI), 515, 519–523
local multicast addresses, 170
logging
 commands, 92, 530
 configuring, 93
 keywords, 92
 levels, 92
 trace commands, 88
logical bridges
 VLANs, 433
logical bus networks, 319
Logical Link Control (LLC), 30
logon, Microsoft Client, 260
loopbacks
 EIGRP
 advertising, 593
 Frame Relay, 544–546
 troubleshooting, 594
 viewing, 595
lower-layer discovery configuration, 682
LSA (link-state advertisement), 209
LSB (least significant bit), 35
LT (line termination), 618

M

MA (multiple access), 319
 MAC (Media Access Control), 13, 30, 167
 Main Serial0 Interface, 533
 management
 networks
 CiscoWorks, 109–112
 ISO, 108
 WANDL, 113
 VLANs, 449–459
 Management Information Base (MIB), 189
 maps
 frames, 498
 ISDN, 629
 static, 535
 static Frame Relay, 510
 static statements, 527–528
 Marketplace, 101
 masks, 21, 193
 maximum transmission unit (MTU), 13
 Media Access Control (MAC), 13, 30, 167
 media testers, 113
 medium-independent interface (MII), 337
 memory
 CAM, 376
 dumps, 703
 leaks, 79
 routers, 236
 mess topology, 37
 messages, monitoring, 455
 methods
 access, 32
 troubleshooting, 10, 55
 trunking, 449
 MIB (Management Information Base), 189
 Microsoft Challenge Handshake Authentication Protocol (MSCHAP), 608
 Microsoft Client, NetWare, 260
 MII (medium-independent interface), 337
 mismatches, encapsulation, 600
 MISTP (Multiple Instance STP), 393
 MLS (multilayer switching), 473–474
 MLSP (Multilayer Switching Protocol), 473
 models
 comparing, 46
 OSI, 5, 10–24. *See also* OSI
 troubleshooting, 10, 55
 modification of physical topologies, 362–379

monitoring
 active monitors, 37
 networks, 114
 ports, 389
 SPAN, 362
 VTP messages, 455
 most significant bit (MSB), 35
 MPPP (Multilink Point-to-Point Protocol), 609
 MSB (most significant bit), 35
 MSCHAP (Microsoft Challenge Handshake Authentication Protocol), 608
 MTU (maximum transmission unit), 13
 multicast addresses, 170
 multilayer switching (MLS), 473–474
 Multilayer Switching Protocol (MLSP), 473
 Multilink Point-to-Point Protocol (MPPP), 609
 multiple access (MA), 319
 Multiple Instance STP (MISTP), 393
 multiple switches, 512
 multipoint subinterfaces, 530, 543–546, 582

N

names
 canonical, 35
 management, 108
 resolution, 188
 NAT (Network Address Translation), 20, 199
 NCP (NetWare Core Protocol), 274
 NDS (Novell Directory Service), 275
 negotiation of paths, 275
 NetBIOS (Network Basic Input/Output System), 276
 Netsys Baseline (WANDL), 113
 NetWare
 display networks command, 258
 Microsoft Client, 260
 NetWare Core Protocol (NCP), 274
 Netware Link Services Protocol (NLSP), 278
 NetWare Loadable Module (NLM), 232
 Network Address Translation (NAT), 20, 199
 network architecture, selecting, 9–20
 Network Basic Input/Output System (NetBIOS), 276
 network interface card (NIC), 10
 Network Layer (Layer 3), 16
 network management systems (NMS), 48
 network operating system (NOS), 229
 Network Time Protocol (NTP), 48, 95, 602

Networking Professionals Connection, 104
networks, 21
 ISDN, 712–717
 ISDN BRI, 616–620
 layers, 620–637
 troubleshooting, 637–641
 management
 CiscoWorks, 109–112
 ISO, 108
 WANDL, 113
 media testers, 113
 monitors, 114
 segmentation, 380
 bridges, 380–382
 repeaters (hubs), 380
 routers, 384–385
 switches, 382–383
 WAN
 HDLC, 598–601
 layers, 602
 terminology, 596–598
 Trouble Tickets, 652–672
 troubleshooting, 586–596, 602–607
next-hop-self concept. r1, 544
NIC (network interface card), 10, 258
NLM (NetWare Loadable Module), 232
NLSP (NetWare Link Services Protocol), 278
NMS (network management system), 48
no auto-summary command, 158, 303, 594
no ip access-group ftp out command, 52
no ip access-group statement, 54
no ip http server command, 365
no ip proxy-arp command, 174
no logging console command, 93
no shut command, 66, 147, 600
no synchronization command, 543
nonlinear path costs, 387
non-root bridges, 387
normal call clearing, 637
normal interfaces, verifying, 649
NOS (network operating system), 229
Novell
 addressing, 276–277
 EIGRP, 278–279
 encapsulation, 257
 IPX RIP protocol, 277–278
 packets, 253–261
 protocols, 253–254
 frame types, 254–261
 Internet Layer, 261–272

 Transport Layer, 272–273
 upper-layer, 274–276
 Trouble Tickets, 280–289
 troubleshooting, 232
Novell Directory Service (NDS), 275
Novell Network Registry, 277
NTP (Network Time Protocol), 48, 95, 602, 702
numbers, application ports, 175

O

Open Shortest Path First. *See* OSPF
Open System Interconnection (OSI), 5
optimization of STP, 391–393
Organizationally Unique Identifier (OUI), 31
OSI (Open System Interconnection), 5
 Application Layer, 14
 Data Link Layer, 30
 Network Layer, 16
 Physical Layer, 36
 Presentation Layer, 14
 Session Layer, 15
 Transport Layer, 15
 troubleshooting, 10–24
 troubleshooting. *See also* OSI
OSPF (Open Shortest Path First), 138, 208–209
 Frame Relay, 540
 lab Trouble Tickets, 705–708
 redistribution, 708–712
osprey routers, documentation, 700
OUI (Organizationally Unique Identifier), 31
output, ping command, 84
Output Interpreter, 104

P

packets
 capturing, 162
 debug ip packet command, 96
 debug ip packet detail command, 97
 Echo Reply, 165
 Echo Request, 165
 IP headers, 163
 IPX RIP, 268
 MLSP, 473
 Novell, 253–261
 protocol analyzers, 115–122
 protocols, 160

- RConsole SPX, 273
- RIP
 - analyzing, 169
 - debugging, 204
 - switching, 17
- parameters, configuring, 365
- passwords, 247. *See also* security
 - 1900 switches, 378
 - 2900 switch, 379
 - 3512XL switches, 378
- paths
 - costs, 387
 - negotiating, 275
- PBXs (private branch exchanges), 617
- PCL (printer control language), 8
- PDUs (protocol data units), 11
- performance, management of, 108
- permanent virtual circuit (PVC), 515, 520
- permit statement, 54
- permit tcp statements, 52
- Physical Layer (Layer 1), 36
 - Ethernet, 337
 - Frame Relay, 528–536
- physical topology switches, 362–379
- ping command, 695
 - 2900 switches, 376
 - character output, 84
 - Ethernet, 304
 - extended, 85
 - hostnames, 159
 - IOS troubleshooting tools, 84–87
 - IP, 149
 - IPX, 261
 - routers, 374
 - user-mode, 84
- ping ipx command, 231
- Please Do Not Threaten Support People Again, 11
- Point of Presence (POP), 322
- Point-to-Point Protocol. *See* PPP
- poison reverse, 208
- policies, VMPS, 439
- POP (Point of Presence), 322
- POP (Post Office Protocol), 185
- port monitor command, 389
- ports
 - application numbers, 175
 - monitoring, 389
 - root, 387
 - show port command, 403
 - SPAN, 362
 - states, 388
- Post Office Protocol (POP), 185
- PPP (Point-to-Point Protocol), 607
 - layers, 607–610
 - troubleshooting, 610–615
- Predictor, 609
- Presentation Layer (Layer 6), 14
- printer control language (PCL), 8
- private branch exchanges (PBXs), 617
- process switching, 17
- Project DOTU, 106–108
- protocol data units (PDUs), 11
- protocols
 - analyzers, 115–122
 - ARP, 13, 306
 - BOOTP, 191
 - CCP, 609
 - CDP, 67, 277
 - CHAP, 610
 - CLNS, 210
 - communications, 9
 - DoD TCP/IP suite, 45–47
 - EIGRP, 157
 - HSRP, 470–471
 - HTTP, 190
 - ICMP type values and codes, 97
 - IP
 - addresses, 193–194
 - routing, 212
 - subnets, 194–202
 - troubleshooting, 136–160
 - Kermit, 8
 - LAPD, 512
 - MLSP, 473
 - MPPP, 609
 - MSCHAP, 608
 - NCP, 274
 - NLSP, 278
 - Novell, 253–254
 - frame types, 254–261
 - Internet Layer, 261–272
 - Transport Layer, 272–273
 - upper-layer, 274–276
 - NTP, 48, 702
 - packets, 160

- POP, 185
- PPP, 607
 - layers, 607–610
 - troubleshooting, 610–615
- PUP, 203
- RIP, 136, 189
 - IPX headers, 268
 - redistribution, 708–712
 - testing, 156
- routing, 16, 18, 277
 - adding, 70
 - BGP, 210–212
 - EIGRP, 278–279
 - Frame Relay, 538–544
 - IGRP/EIGRP, 206–208
 - IPX RIP, 277–278
 - IS-IS, 209–210
 - NLSP, 278
 - OSPF, 208–209
 - RIP, 202–206
 - testing, 70
- RSTP, 387
- RTP, 208
- SLP, 270
- SMTP, 185
- SNAP, 445
- STP, 362, 385–388
 - BPDU analysis, 389–391
 - optimizing, 391–393
 - port monitoring, 389
 - RSTP, 393–394
 - Trouble Tickets, 717–719
 - VLANs, 450–453
- suites, 9
- TCP/IP, 160–162
 - Internet Layer, 162–167
 - Transport Layer, 168–176
 - Upper-Layer Layer, 176–192
- testing, 156
- TFTP
 - copying configurations, 702
 - memory dumps, 703
- troubleshooting, 6–10
- VTP, 453–459
- Xmodem, 8
- proxy ARPs, 174
- pruning VTP, 458–459
- pseudo frame switches, 498

- PumpKin, 177
- PUP (Xerox PARC Universal Protocol), 203
- PVC (permanent virtual circuit), 515, 520

Q-R

- QoS (quality of service), 383
- RAM (random access memory)
 - routers, 236
 - upgrading, 237
- Rapid Spanning Tree Protocol (RSTP), 387, 393–394
- raw (Novell 802.3) headers, Ethernet frame formats, 330–331
- RConsole SPX packets, analyzing, 273
- redistribution, Trouble Tickets, 708–712
- release designations, IOS life cycles, 74
- Reliable Transport Protocol (RTP), 208
- reload command, 242, 406
- reloading routers, 178
- Remote Monitoring (RMON), 109
- repeaters, 380
- replies, Echo Reply packets, 165
- Request For Comments (RFCs), 8
- requests
 - Echo Request packets, 165
 - GNS, 261
 - TOS, 209
- resetting
 - counters, 64
 - switches, 364
- resolution, names, 188
- Resource Manager Essentials (RME), 110
- resources
 - desktops, 124
 - troubleshooting, 98
 - Cisco.com, 99–100
 - documentation CD-ROM, 100–101
 - Marketplace, 101
 - Project DOTU, 106–108
 - TAC, 101–106
- restrictions, trunking, 446
- reviewing routing tables, 158, 594
- RFCs (Request For Comments), 8

- RIP (Routing Information Protocol), 136, 189, 202–206
 - analyzing, 169
 - IPX packets, 268
 - IPX RIP protocol, 277–278
 - redistribution, 708–712
 - testing, 156
 - RJ-45 connectors, 39
 - RME (Resource Manager Essentials), 110
 - RMON (Remote Monitoring), 109
 - root ports, 387
 - ROTB (router out of the box), 179
 - router out of the box (ROTB), 179
 - router-on-a-stick scenario, 460–469
 - routers, 384–385
 - 3600 series, 77
 - baselines, 685
 - blades, 470
 - configuring, 374
 - documentation, 308, 698
 - Frame Relay, 503–512
 - HSRP, 470–471
 - Layer 3, 691
 - memory, 236
 - multipoint subinterfaces, 532
 - reloading, 178
 - testing, 374
 - tracing, 707
 - Trouble Tickets, 680–681
 - trunking, 440–445
 - dot1Q, 447
 - EtherChannel, 448–449
 - ISL, 445–447
 - methods, 449
 - VLANs, 426–432
 - routes
 - filters, 18
 - hosts, 596
 - IP, 302
 - searching, 303
 - server summarization, 200
 - static, 506, 646
 - switch technologies, 472
 - CEF, 472–473
 - MLS, 473–474
 - testing, 156
 - routing, 17
 - CIDR, 20. *See also* CIDR
 - DDR, 270, 629, 641–644
 - inter-VLAN, 460–471
 - IP, 212
 - protocols, 16, 18, 277
 - adding, 70
 - BGP, 210–212
 - EIGRP, 278–279
 - Frame Relay, 538–544
 - IGRP/EIGRP, 206–208
 - IPX RIP, 277–278
 - IS-IS, 209–210
 - NLSP, 278
 - OSPF, 208–209
 - RIP, 202–206
 - testing, 70
 - tables, 150
 - reviewing, 158, 594
 - viewing, 594
 - Routing Information Protocol. *See* RIP
 - RSM/MSFC (router blades), 470
 - RSTP (Rapid Spanning Tree Protocol), 387, 393–394
 - RTP (Reliable Transport Protocol), 208
 - running-config file, 595
 - rxboot mode, 241
- ## S
-
- SA (source address), 13
 - SAP (service access points), 16, 30, 271
 - scenarios
 - host configuration, 368
 - router-on-a-stick, 460–469
 - searching routes, 303
 - security
 - management, 108
 - passwords, 247
 - segmentation, 380
 - bridges, 380–382
 - repeaters (hubs), 380
 - routers, 384–385
 - switches, 382–383
 - Sequenced Packet Exchange (SPX), 254
 - serial 0/0 connections, 148
 - serial interfaces
 - debugging, 603
 - keepalives, 603
 - Trouble Tickets, 680–681
 - viewing, 598
 - Server Message Block (SMB), 275

servers

- FTP, 183
- route summarization, 200
- terminal configuration, 138
- TFTP
 - copying configurations, 702
 - PumpKin, 177
 - VMPS, 439
- service access points (SAPs), 16, 30, 271
- service level agreement (SLA), 513, 516
- Service Location Protocol (SLP), 270
- Service Profile Identifiers (SPIDs), 619
- Session Layer (Layer 5), 15
- sessions, TCP disconnections, 173
- set spantree mode mst command, 450
- set trunk mod#/port# ? command, 446
- set trunk mod#/port# mode command, 445
- set vtp domain vtpname command, 454
- sh int switching commands, 107
- shared media access methods, 319
- shooting trouble. *See* troubleshooting
- Shortest Path First (SPF), 209
- show access-lists command, 52
- show arp command, 72
- show buffers command, 80
- show cdp neighbors command, 68
- show cdp neighbors detail command, 263
- show commands
 - IOS troubleshooting tools, 62–84
 - ISDN, 637
- show controllers command, 63, 499
- show controllers commands, 148
- show debug command, 97
- show frame-relay lmi command, 508, 519
- show frame-relay map command, 502, 527
- show frame-relay route command, 531
- show frame-relay traffic command, 537
- show hosts command, 187
- show interfaces bri0 1 2 command, 628
- show interfaces command, 63
- show interfaces ethernet0 command, 66
- show interfaces serial 0 command, 598
- show interfaces serial0 command, 64
- show ip bgp ? command, 211
- show ip bgp summary command, 210
- show ip interface brief command, 66
- show ip interface s0 command, 52
- show ip ospf ? command, 209
- show ip protocols command, 69
- show ipx interface ethernet 0 command, 248
- show ipx route command, 276
- show ipx servers command, 276
- show isdn history command, 634
- show isdn status command, 631
- show logging command, 92
- show mac address command, 690
- show memory command, 78–79
- show module command, 448
- show port command, 403
- show port monitor command, 389
- show process command, 79
- show protocols command, 69, 692
- show run interface bri0 command, 639
- show running-config command, 690
- show spanning-tree ? command, 450
- show stacks command, 80
- show start command, 76
- show startup-config command, 75, 372
- show tech-support command, 82, 105
- show version command, 73
- show vlan command, 449
- show vmpls command, 439
- shut down, 599
- signaling Frame Relay, 519–523
- Signaling System 7 (SS7), 620
- Simple Mail Transfer Protocol (SMTP), 185
- SLA (service level agreement), 513, 516
- SLP (Service Location Protocol), 270
- SMB (Server Message Block), 275
- SMTP (Simple Mail Transfer Protocol), 185
- SNAP (Subnetwork Access Protocol), 445, 333–335
- Sniffer Pro, 115
 - applying, 118–122
 - packets, 162
 - starting, 116–117
- software support, 102
- source address (SA), 13
- SPAN (Switched Port Analyzer), 362
- Spanning Tree Protocol (STP), 362, 385–388
 - BPDU analysis, 389–391
 - optimizing, 391–393
 - port monitoring, 389
 - RSTP, 393–394
 - Trouble Tickets, 717–719
 - VLANs, 450–453
- spanning-tree vlan 1 command, 719

- SPF (Shortest Path First), 209
- SPIDs (Service Profile Identifiers), 619, 626
- split horizons, 208
- spoke routers, multipoint subinterfaces, 532
- spoofing, 629
- SPX (Sequenced Packet Exchange), 254
- SS7 (Signaling System 7), 620
- Stacker, 609
- stacks, testing, 592
- standards. *See also* protocols
 - Frame Relay, 512
 - troubleshooting, 6–10
- star topologies, 37
- starting
 - IPX clients, 274
 - Sniffer Pro, 116–117
- statements
 - clock rate, 528
 - dialer map-class, 651
 - ip default-gateway, 241
 - no ip access-group, 54
 - permit, 54
 - permit tcp, 52
 - static maps, 527–528
- states
 - ports, 388
 - PVC, 520
- static Frame relay maps, adding, 510
- static maps
 - configuring, 535
 - statements, 527–528
- static routes, 506, 646
- statistics
 - interfaces, 310
 - ISDN interfaces, 627
 - LMI, 523
 - VTP, 458
- STP (Spanning Tree Protocol), 362, 385–388
 - BPDU analysis, 389–391
 - optimizing, 391–393
 - port monitoring, 389
 - RSTP, 393–394
 - Trouble Tickets, 717–719
 - VLANs, 450–453
- straight-through cables, 40, 368
- strings, ISDN, 629
- subinterfaces (Frame Relay), 529
- subnets, 194–199
 - discontiguous, 156
 - Frame Relay
 - configuring, 506
 - troubleshooting, 511
- Subnetwork Access Protocol (SNAP), 445
- suites, protocols, 9
- summarization, 158
 - closing, 158
 - IP addresses, 199–202
 - VLSM, 199–202, 212, 215, 225
- support
 - desktops, 124
 - hardware, 102
 - software, 102
 - technology, 102
- swan routers, documentation, 700
- Switched Port Analyzer (SPAN), 362
- switches, 382–383
 - 1900, 190
 - accessing, 369
 - Cat5000/Cat6000 architecture, 400–404
 - CatOS, 395–400, 687
 - configuring, 369
 - documentation, 701
 - Frame Relay, 503–512
 - hosta, 379
 - IOS, 400, 690
 - ISDN, 619
 - multiple, 512
 - pseudo frame, 498
 - resetting, 364
 - route technologies, 472
 - CEF, 472–473
 - MLS, 473–474
 - Trouble Tickets, 406–421
 - troubleshooting, 362–379, 405–406
 - trunking, 440–445
 - dot1Q, 447
 - EtherChannel, 448–449
 - ISL, 445–447
 - methods, 449
 - VLANs, 426–435
 - configuring, 435–439
 - traffic types, 435
 - VMPS, 439
- switching, 17, 107
- switchport mode trunk IOS command, 442
- synchronization of Frame Relay, 543
- Syslog, capturing, 713

T

- T/L (type or length field), 13
- tables
 - ARP, 306
 - IDB, 592
 - routing, 150
 - reviewing, 158, 594
 - viewing, 594
- TAC (Technical Assistance Center), 80, 101–106
- tagging frames, 447
- targets, interfaces, 339
- TCP (Transmission Control Protocol)
 - 3-way handshake sequences, 171
 - disconnections, 173
- TCP/IP (Transmission Control Protocol/Internet Protocol) layers, 160–162
 - Internet Layer, 162–167
 - Transport Layer, 168–176
 - upper-layer, 176–192
- TDM (time-division multiplexing), 617
- TDR (time domain reflectometer), 37
- TE (terminal endpoint), 632
- Technical Assistance Center (TAC), 80, 101–106
- Technical Service Bulletins (TSBs), 39
- technology support, 102
- TEIs (terminal endpoint identifiers), 632
- Telecommunications Act of 1996, 596
- Telnet
 - analyzing, 171
 - applications, 176
 - testing, 379
- terminal endpoint (TE), 632
- terminal endpoint identifiers (TEIs), 632
- terminal monitor (term mon), 206, 602
- terminal servers, configuring, 138
- terminology
 - Frame Relay, 514
 - WAN, 596–598
- testing
 - 1900 switch, 375
 - 2900 switches, 375
 - 3512XL switches, 371
 - ANSI LMI, 520
 - back-to-back configuration, 497–503
 - backup interfaces, 647
 - controllers, 590
 - devices, 590
 - end-to-end connectivity, 305
 - Ethernet, 304
 - Frame Relay, 506, 544–546
 - host-to-host connectivity, 159
 - interfaces, 145, 590
 - IP, 149
 - IPX, 252
 - media, 113
 - protocols, 156
 - routers, 374
 - routes, 156
 - routing protocols, 70
 - stacks, 592
 - Telnet, 379
- TFTP (Trivial File Transfer Protocol)
 - Configuration Backup, 240
 - copying configurations, 702
 - memory dumps, 703
 - PumpKin, 177
- time domain reflectometer (TDR), 37
- Time Stamps, debug command, 95
- time-division multiplexing (TDM), 617
- timers, STP, 388
- time-to-live (TTL), 87, 267
- Token Ring, 33
- tools
 - desktop, 124–128
 - hardware, 113
 - IOS
 - debug commands, 94–98
 - logging commands, 92–94
 - ping commands, 84–87
 - show commands, 62–84
 - trace commands, 87–91
 - troubleshooting, 62
 - Novell, 254
 - Internet Layer, 261–272
 - Transport Layer, 272–273
 - upper-layer, 274–276
 - TAC, 103
 - WANDL, 113
- topologies, Frame Relay, 529
- TOS (type of service), 209
- trace command
 - IOS troubleshooting tools, 87–91
 - logging, 88
- traceroute command, 30, 695
 - characters, 87
 - extended, 90

- tracert command, 695
 - tracing routers, 707
 - traffic
 - protocol analyzers, 115–122
 - show frame-relay traffic command, 537
 - VLANs, 435
 - translators, 14
 - transparent bridging, 381
 - transparent mode, 443
 - Transport Layer
 - Novell, 272–273
 - TCP/IP, 168–176
 - Transport Layer (Layer 4), 15
 - Trivial File Transfer Protocol. *See* TFTP
 - Trouble Tickets, 51, 213–225
 - discovery labs, 681–695
 - documentation labs, 695–705
 - Ethernet, 343–357
 - Frame Relay, 546–579, 712–717
 - Novell, 280–289
 - OSPF labs, 705–708
 - redistribution, 708–712
 - routers, 680–681
 - serial interfaces, 680–681
 - STP, 717–719
 - switches, 406–421
 - VLAN, 717–719
 - VLANs, 476–490
 - WAN, 652–672
 - troubleshooting, 5, 55
 - 3512XL switch, 370
 - baselining, 56–57
 - BGP, 210
 - CatOS, 362–379
 - checklists, 139
 - Cisco approach to, 47–55
 - desktops, 124
 - dialers, 638
 - documentation, 56–57
 - DoD TCP/IP suite, 45–47
 - encapsulation, 600
 - Ethernet, 296–317, 337–343
 - Frame Relay, 496–497, 536–546
 - applying as switches, 503–512
 - back-to-back configuration, 497–503
 - subnets, 511
 - frames, 508
 - HDLC, 602–607
 - infrastructure, 113
 - interfaces, 146
 - IOS, 62
 - debug commands, 94–98
 - logging commands, 92–94
 - ping commands, 84–87
 - show commands, 62–84
 - switches, 362–379
 - trace commands, 87–91
 - IP, 136–160
 - IPX, 230–253
 - ISDN BRI, 637–641
 - keepalives, 603
 - layers, 44–45
 - loopbacks, 594
 - methods, 10, 55
 - models, 10, 55. *See also* OSI
 - networks, 114
 - Novell, 232
 - PPP, 610–615
 - protocols, 6–10, 115–122
 - resources, 98
 - Cisco.com, 99–100
 - documentation CD-ROM, 100–101
 - Marketplace, 101
 - Project DOTU, 106–108
 - TAC, 101–106
 - switches, 405–406
 - VLANs, 426–432, 474–476
 - WAN, 586–596
 - Troubleshooting Assistant, 104
 - trunking, 440–445
 - ISL, 445–449
 - methods, 449
 - restrictions, 446
 - TSBs (Technical Service Bulletins), 39
 - TTL (time-to-live), 87, 267
 - type of service (TOS), 209
 - type or length field (T/L), 13
 - types
 - frames, 162, 254–261
 - ICMP, 97
 - VLANs, 435
-
- U**
- UDP (User Datagram Protocol), 168
 - unlike devices, 40

- unplugging cables, 63
- upgrading
 - IOS, 241
 - RAM, 237
- upper-layer, 274–276
- upper-layer discovery configuration, 682
- upper-layer, TCP/IP, 176–192
- User Datagram Protocol (UDP), 168
- user-mode ping command, 84
- utilities (TCP/IP), 160–162
 - Internet Layer, 162–167
 - Transport Layer, 168–176
 - upper-layer, 176–192

V

- values, 97
 - binary place, 20
 - ICMP, 97
- variable-length subnet masking (VLSM), 158
- verification of
 - D Channel, 628
 - Frame Relay switches, 505
 - IP routes, 302
 - IPX, 304
 - multipoint subinterfaces, 534
 - normal interfaces, 649
 - PPP encapsulation, 609
 - VLANs, 443
- viewing
 - backup interfaces, 645
 - frame maps, 498
 - host routes, 596
 - LMI statistics, 523
 - loopbacks, 595
 - multipoint subinterfaces, 533
 - NTP, 702
 - routing tables, 594
 - serial interfaces, 598
 - static maps, 528
 - VLANs, 444
- virtual LANs. *See* VLANs
- VLANs (virtual LANs), 425–435
 - configuring, 435–439
 - inter-VLAN routing, 460–471
 - managing, 449–459
 - STP, 450–453
 - traffic types, 435

- Trouble Tickets, 476–490, 717–719
- troubleshooting, 474–476
- trunking, 440–445
 - dot1Q, 447
 - EtherChannel, 448–449
 - ISL, 445–447
 - methods, 449
- verifying, 443
- viewing, 444
- VMPS, 439
- VTP, 453–458459
- VLSM (variable-length subnet masking), 158. *See also* subnets
- VMPS (VLAN Membership Policy Server), 439
- VTP (VLAN Trunking Protocol), 453–459

W-X

- WAN (wide-area network)
 - HDLC, 598–601
 - layers, 602
 - troubleshooting, 602–607
 - terminology, 596–598
 - troubleshooting, 586–596
 - Trouble Tickets, 652–672
- WANDL (Netsys Baseline), 113
- WC3 (World Wide Web Consortium), 8
- Windows 2000 hosts file, 188
- wireless Ethernet, 323
- Wireless Troubleshooting Center, 104
- World Wide Web Consortium (WC3), 8
- write memory command, 77
- write-erase command, 177
- Xerox Network Systems (XNS), 203, 229
- Xerox PARC Universal Protocol (PUP), 203
- Xmodem protocol, 8
- XNS (Xerox Network Systems), 203, 229