



Numerics

1000BASE-LX/LH (WS-G5486), 9
 1000BASE-SX (WS-G5484), 9
 1000BASE-T (WS-G5483), 9
 1000BASE-ZX (WS-G5487), 9
 1024-bit RSA public/private key pair, 623
 802.1Q-tagged Ethernet frames, 170
 802.1x authentication, 650, 656–660

A

AAA (authentication, authorization, and accounting)
 clients

creating, 634
 verifying, 636

configuring, 606–607, 647
 management access, 639
 optimizing, 626–633
 servers, 620
 support, 634, 637
 switches, 638

aaa accounting command, 633

aaa authentication command, 632

aaa authentication dot1x command, 653

aaa authorization command, 633

accelerated CEF (aCEF), 468. *See also* CEF

access

confirming, 669

devices, 648–654, 654–660

interfaces (VLANs), 156

management, 605–606

AAA, 606–607, 639

configuring, 46–76

protocols, 608–609

reducing vulnerabilities, 609

restricting, 608, 614

networks, 610

ports, 620

Telnet

restricting, 622, 624

testing, 647

traffic filtering, 610–611

VLANs, 146, 667

Access layer, 6, 391

configuring, 414–415, 840–841, 902–906

QoS, 702–712

switches, 398–399

Access port (VLAN), 151

accounting, planning, 628

aCEF (accelerated CEF), 468. *See also* CEF

ACLs (Access Control Lists), 448

adding

static routes, 669

USA, 590

addresses

BIA, 410

GDA, 590

IP

12trace command, 742

configuring, 52

load sharing, 180

MAC

12trace command, 741

enabling reduction, 163–165

load sharing, 180

multicast, 510

adjacency tables, 467, 477

administration, VLAN, 160–162

administrative groups, 229

advertisements, VTP, 175, 177

agents, mapping, 568

aggregate basis, 687

aggregate policers, creating, 709

aggregation

bandwidth, 167, 178–182

PAgP, 182, 745

aging, 125

algorithms

STA, 248

transparent bridging, 133–139

allocation of internal bandwidth, 90

applications

prerequisites, 77–98

QoS, 673–674

DiffServ model, 675

functions, 680

implementing, 681–688

models, 674

application-specific integrated circuits (ASICs), 342, 427

architecture

Catalyst 4000 router module, 375

Catalyst 6000/6500 switches, 434–443

collapsed backbone, 345–347

inter-VLAN routing, 340–343

Layer 3

hardware-based, 433–434

MLS, 446

point-to-point architecture, 6–16, 516–524, 730–

738, 828–833

router-on-a-stick, 340–341

selecting, 6–16

ASICs (application-specific integrated circuits), 342, 427

asserts, PIM dense mode, 526

- assignment
 - ports (VLAN), 151
 - router ports, 591
- asymmetric routing, 730. *See also* routing
- attacks, 194
- audio (multicast routing), 509–510
 - addressing, 510
 - forwarding, 516–518
 - IGMP, 512
 - IP, 513–515
 - LAN, 519–520, 570–576
- auditing exec events, 644
- authentication
 - 802.1x
 - configuring, 656–660
 - planning, 650
 - login, 51, 613
 - NTP, 105
 - planning, 627
 - switches, 638
 - user-level, 615
- authentication, authorization, and accounting. *See* AAA
- authorization
 - levels, 616
 - planning, 628
 - privilege levels, 625
 - TACACS+ servers, 643
 - testing, 647
- auto mode, 182
- auto-negotiation, 80, 744
 - Ethernet delays, 745
 - trunking, 171–172
- Auto-RP, configuring, 565–569
- autosensing, 845
- availability
 - collapsed backbone architecture, 346
 - EtherChannel, 181
 - LAN, 344
 - multilayer LAN, 349

B

- IGMP, 512
- IP, 513–515
- LAN, 519–520, 570–576
- banner command, 615
- banners
 - configuring, 621
 - login
 - configuring, 613
 - creating, 615
- basic ping, 727. *See also* ping utility
- BDR (backup designated router), 405
- BIA (burned-in address), 410
- binding QoS policy, 708
- bits, DF, 728
- blocking states, 243, 247
- boot environment variables, 777, 789, 799
- booting
 - bypassing startup files, 768
 - failures, 792
 - hybrid mode, 482
 - native mode, 483, 488
 - operating systems, 775
 - parameters, 494
 - ROMMON mode, 487
 - switches, 797
- BPDU (bridge protocol data units), 197, 243, 756
 - Filter, 305–307
 - port priority, 276
 - PortFast, 302–305
 - troubleshooting, 333
- breaking loops, 331
- bridge protocol data units (BPDUs), 197, 243, 756
- bridges, 121–125
 - designating, 248
 - LAN segmentation, 125–129
 - root bridges
 - configuring, 254–272
 - placement, 256–259, 275
 - secondary placement, 260
 - spanning trees, 243
 - STP. *See* STP
 - tables, 122
 - configuring entries, 137
 - viewing, 135
 - viewing on Switch-B, 137
 - transparent, 133–139
 - viewing, 267
- broadcast domains, 126
- building
 - SPT from source to RP, 550
 - trees (PIM sparse mode), 547–556
- bundles. *See also* EtherChannel
 - configuring, 227
 - STP, 290
- burned-in address (BIA), 410
- bypassing startup files, 768

C

- cabling, testing, 110
- caches, 434, 463
- candidate RPs, configuring, 567
- capture, traffic, 800–806, 828
- Catalyst 2900XL/3500XL switches, 681
- Catalyst 2950 switches, 7
- Catalyst 2950/3550 switches, 682
- Catalyst 3550 multilayer switches, 372–374
- Catalyst 3550 switches, 10
- Catalyst 3750 switches, 13
- Catalyst 4000 router module, 374–375
- Catalyst 4000 series of switches, 684
- Catalyst 4000/4500 switches, 14
- Catalyst 6000/6500 switches, 20, 686
 - architecture, 434–443
 - CEF-based Layer 3 switching, 465–478
 - configuring, 497–505
 - MLS, 444–465
 - operating systems, 444
 - upgrading, 479–497
- Catalyst Layer 3 switches, multicasting, 520
- Catalyst switches, 4–7, 582, 597
 - connections, 726–742
 - errDisable status, 755–765
 - file management, 771–799
 - installing, 27–46
 - operating systems, 25–27
 - platforms, 7–25
 - VLAN
 - CatOS, 132
 - implementing, 131–132
- CatOS. *See also* operating systems
 - 12trace command, 741
 - adjacency tables, 477
 - commands, 612
 - configuring, 209
 - disabling DTP/PAGP, 746
 - EtherChannel, 229–233
 - FIB, 476
 - file management, 774
 - flow control, 94
 - hard coding speed and duplex settings, 745
 - IP addressing, 56
 - NTP, 104, 107
 - password recovery, 765–768
 - passwords, 50
 - ping utility, 728
 - PortFast, 749
 - RSPAN, 821
 - secure management protocols, 609
 - set port host macro, 749
 - SNMP, 66
 - SPAN, 815
 - spanning tree delays, 748
 - switches, 621
 - SYSLOG, 74
 - transparent bridging, 134
 - VLAN, 132, 152–154
- CDP (Cisco Discovery Protocol), 117, 196, 734
- CEF (Cisco Express Forwarding), 343, 466
 - Layer 3
 - operating in native mode, 497–505
 - switching, 465–478
 - verifying, 476
- CGMP (Cisco Group Management Protocol), 520
 - configuring, 588–602
 - local leave processing, 595
- cgmp holdtime global configuration command, 601
- cgmp leave-processing global configuration command, 601
- cgmp option, 584
- channel groups, 229
- channel-group command, 387
- channel-group interface configuration command, 400
- chassis
 - Catalyst 4000/4500 switches, 14
 - Catalyst 6000/6500 switches, 20
- checksums, CRC, 169
- Cisco Discovery Protocol (CDP), 117, 196, 734
- Cisco Express Forwarding. *See* CEF
- Cisco Group Management Protocol (CGMP), 520
- Cisco IOS, 205
 - EtherChannel, 228–229
 - transparent bridging, 137–139
 - VLAN, 154–158
 - VTP, 133, 146–148
- Cisco PVST+ (Per-VLAN spanning tree), 252
- CiscoSecure ACS, 634
- class maps, creating, 707
- Class of Service (CoS), 135, 677
- clear cam command, 137
- clear spantree root vlan-id command, 265
- clear spantree uplinkfast command, 314
- clear trunk command, 210
- clear vlan command, 159
- clear vtp pruneeligible command, 216
- clients
 - AAA
 - creating, 634
 - verifying, 636
 - VTP, 189
- collapsed backbone architecture, 345–347
- collisions, domains, 126
- commands, 614
 - 12trace, 741
 - aaa accounting, 633
 - aaa authentication, 632
 - aaa authentication dot1x, 653
 - aaa authorization, 633
 - banner, 615
 - CatOS, 612
 - cgmp holdtime global configuration, 601

- cgmp leave-processing global configuration, 601
- channel-group, 387
- channel-group interface configuration, 400
- clear cam, 137
- clear spantree root vlan-id, 265
- clear spantree uplinfast, 314
- clear trunk, 210
- clear vlan, 159
- clear vtp pruneeligible, 216
- configure, 41
- configure terminal, 41
- copy, 778
- copy running-config startup-config, 43
- copy startup-config running-config, 45
- debug dtp, 212
- debug dtp packets, 212
- debug ip igmp, 560
- debug ip packet, 365, 367
- debug ip pim, 545, 560
- debug standby events, 418
- delete, 782
- dot1x port-control, 654
- enable, 60
- encapsulation dot1q x, 364
- exec-timeout, 616
- exit, 42, 385
- format, 492
- hostname global configuration, 41
- interface FastEthernet 0/0.x, 363
- interface global configuration, 161
- interface range, 84, 499
- interface vlan 1 global configuration, 161
- interface VLAN 200, 373
- interface VLAN 300, 373
- interface vlan global configuration, 381
- interface VLAN x global configuration mode, 373
- IOS, 614
- ip default-gateway, 362
- ip default-gateway global configuration, 362
- ip domain-lookup, 55
- ip igmp join-group, 541
- ip igmp snooping global configuration, 584, 587
- ip multicast-routing global configuration, 557
- ip name-server, 55
- ip pim dense-mode, 537
- ip pim interface configuration, 536, 564
- ip pim rp-address, 557
- ip pim send-rp-announce global configuration, 567
- ip pim send-rp-discovery global configuration, 568
- ip route global configuration, 365
- ip routing, 362
- line vty, 48
- login line configuration, 48
- login local, 615
- mac-address table static global configuration, 575
- management interface configuration, 162
- maximum-paths, 409
- no ip igmp snooping global configuration, 575
- no ip routing global routing, 362
- no shutdown, 381
- no shutdown interface configuration mode, 161, 363
- no switchport interface configuration, 381
- password, 48
- ping, 367
 - interfaces, 669
 - starting, 542
- ping ip, 727
- pings, 84
- port-channel load-balance global configuration
 - mode, 234
- privilege, 616
- QoS, 692
- radius-server, 631
- root macro, 264
- router eigrp 1, 388
- session, 384, 473
- set accounting, 631
- set authentication, 630
- set authentication login, 613
- set authorization, 630
- set banner motd, 613
- set BAUD, 792
- set boot config-register, 488
- set crypto key rsa, 614
- set dot1x, 653
- set enablepass, 50
- set igmp enable, 583
- set igmp fastleave enable, 587
- set interface sc0, 161
- set interface sc0 configuration, 57
- set ip permit, 614
- set logout, 614
- set password, 50
- set port channel, 231
- set port dot1x, 653
- set port duplex, 85
- set port security, 651
- set pvlan, 662
- set radius server, 629
- set security acl, 663
- set spantree macreduction, 163, 268
- set spantree portcost mod/port cost cost, 287
- set spantree portpri mod/port cost, 289
- set spantree portvlancost, 287
- set spantree root, 265
- set spantree root secondary, 264
- set spantree uplinkfast disable, 314
- set system name, 42
- set tacacs server, 629
- set trunk, 209
- set vlan, 152, 210
- set vlan vlan-id pvlan-type, 662
- set vtp, 190
- set vtp pruneeligible, 216
- set vtp pruning, 216
- show arp, 414

- show bootvar, 494
- show cam dynamic, 134, 136
- show cam permanent, 137, 575
- show cam static, 137
- show cdp neighbors, 736
- show cdp neighbors detail, 736
- show cgmp, 602
- show channel group, 230
- show channel traffic, 238
- show clock, 101
- show etherchannel port, 236
- show interface, 227
- show interface switchport, 208
- show interface trunk, 209, 217
- show interfaces port-channel 1, 387
- show ip igmp snooping mrouter, 585
- show ip mroute, 540
- show ip mroute active, 544
- show ip ospf, 403
- show ip ospf neighbor, 407
- show ip pim neighbor, 538
- show ip pim rp mapping, 569
- show ip route, 364, 366
- show ip rpf, 539
- show mac-address-table dynamic, 137
- show mac-address-table multicast, 576, 585
- show mac-address-table static, 139
- show mls cef mac, 501
- show module, 40
- show multicast, 583
- show multicast group, 584
- show port, 115
- show port capabilities, 225, 687
- show port mod/port, 227
- show port negotiation, 88
- show spanning-tree active, 291
- show spanning-tree blockedports, 291
- show spanning-tree bridge, 267
- show spanning-tree interface, 271
- show spanning-tree root, 271
- show spanning-tree summary, 398
- show spanning-tree uplinkfast, 314
- show spantree 1, 272
- show spantree uplinkfast, 313
- show standby, 421
- show standby brief, 413
- show startup-config, 45
- show trunk, 211, 218, 380
- show version, 37, 385
- show vlan, 154, 158, 192
- show vlan internal usage, 165
- show vtp domain, 188, 193
- show vtp status, 148, 188
- spanning-tree cost cost interface configuration, 286
- spanning-tree extend system-id global configuration, 163
- spanning-tree vlan 1 root, 268
- spanning-tree vlan interface configuration, 286
- squeeze, 782
- standby 1 ip 192.168.1.10, 412
- standby track, 412
- switchpoint mode access, 156
- switchport interface configuration, 156
- switchport security, 652
- switchport trunk interface configuration, 206
- switchport trunk pruning interface configuration, 216
- tacacs-server, 631
- telnet, 60
- traceroute mac, 740
- traceroute mac ip, 740
- tracert, 416
- username, 615
- vlan database, 146
- vlan vlan-id global configuration mode, 155
- vtp global configuration, 189
- vtp pruning, 215
- vtp VLAN configuration, 189
- Common Spanning Tree (CST), 197, 252
- communication
 - MLS, 450
 - VLAN, 129–131
- compatibility, trunking modes, 200
- components
 - CEF, 467
 - layer 3 switches, 373
 - Supervisor 720 engine, 443
- CONFIG_FILE environment variable, 488
- configuration, 634, 841
 - 802.1x authentication, 656–660
 - AAA, 606–607
 - confirming, 647
 - management access, 639
 - support, 637
 - switches to use AAA, 638
 - Access layer, 414–415, 840–841
 - Auto-RP, 565–569
 - backing up, 484
 - banners, 621
 - BOOT environment variables, 799
 - booting parameters, 494
 - BPDU, 243
 - bridge table entries, 137
 - candidate RPs, 567
 - Catalyst 4000 router module, 374–375
 - Catalyst 6000/6500 switches, 497–505
 - MLS, 444–465
 - CatOS, 209, 229–233
 - CGMP, 588–602
 - Cisco IOS, 205, 228–229
 - CiscoSecure ACS, 634
 - class maps, 707
 - core, 399
 - core layer, 840
 - dates and time, 99
 - default gateways, 362

- DHCP server support, 699
- directory numbers, 701
- Distribution layer, 405, 840–841
- DNS, 52
- dynamic routing, 402–409
- EtherChannel, 219–238
 - bundles, 227
 - Layer 2, 835
 - planning, 219–223
 - support, 223–225
 - tasks, 225–238
 - verifying, 235–237
- Ethernet, 76–98
- flow control, 88
- groups, 640
- high-speed band rates, 793
- hosts, 40, 361–362
- HSRP, 410–413
- identity, 40
- idle session timeouts, 624
- IGMP snooping, 576–588
- inter-VLAN Layer 2 infrastructure, 837
- inter-VLAN routing, 358–359, 361–370
 - Switch-A/Switch B, 380–389
- IP, 52, 355, 370
- ip routing command, 362
- jumbo frames, 94
- Layer 2 infrastructure, 834–839, 843
 - connecting, 843–844
 - interfaces, 499
 - inter-VLAN routing, 868–870
 - management, 870–875
 - parameters, 360–361, 377–380, 393
 - ports, 845–849
 - QoS, 875–882
 - security, 870–875
 - spanning tree, 857–867
 - VLAN, 849–857
- Layer 3
 - interfaces, 499
 - routing, 500
 - switching, 370–371
- login, 613, 615
- loop-free topologies, 242–251
- management of Layer 2 infrastructure, 838
- mapping agents, 568
- minimum flow mask, 457
- MLS-RP, 454
- MLS-SE, 456
- MSFC, 472
- MSFC-2, 473
- multicast routing, 841
- multilayer, 839, 841, 897
 - access layer, 902–906
 - core layer, 897–902
 - distribution layer, 902–906
 - routing, 907–914
 - multilayer LAN design, 344–353
 - network management access, 46–76
- NTP, 101
- passwords, 48, 637, 771
- permit lists, 623
- PFC, 475
- physical port parameters, 225–227
- PIM dense mode, 521–522
 - neighbor discovery, 523
 - tasks, 533–546
 - trees, 523–530
 - unicasting, 522
- PIM sparse mode, 546–547
 - tasks, 556–563
 - trees, 547–556
- PIM sparse-dense mode, 564
- ports
 - Gigabit Ethernet, 86
 - Layer 2, 835
- prerequisites, 77–98
- privilege levels, 625
- prune eligible lists, 216
- pruning VTP, 213–218
- QoS, 688–693
 - Access layer, 702–712
 - connecting, 693–699
 - Distribution layer, 712–722
 - IOS IP telephony service, 699–702
 - Layer 2 infrastructure, 839
- restoring, 770
- RP, 556
- RSPAN, 817–825
- routed interfaces, 399–402, 405–407
- routers, 362–367, 386, 664
- saving, 42, 770
- scheduling, 716
- security, 610, 648–660
 - LAN segments, 660–663
 - Layer 2 infrastructure, 838
 - management interfaces, 617–626
 - ports, 654–656
 - protocols, 638
- SNMP, 61–67
- SPAN, 809–816
- spanning tree, 837
- static IP routing, 366
- STP
 - BackboneFast, 317–325
 - BPDU Filter, 305–307
 - BPDU, 302–305
 - load sharing, 272–293
 - multilayer design, 326–328
 - PortFast, 298–302
 - root bridges, 254–272
 - root guard, 293–298
 - troubleshooting, 328–335
 - UplinkFast, 307–317

- switches, 882–894
 - Access layer, 398–399
 - Distribution layer, 394–398
 - self-study labs, 914–930
 - SYSLOG, 67–76
 - system names, 664
 - system time, 98–108
 - TFTP servers, 796
 - trunk mode (DTP), 199
 - trunking
 - between switches, 194–213
 - encapsulation, 195
 - Layer 2, 835
 - trunks, 619, 695
 - unicasting, 534
 - VACLs, 825–829
 - VLAN, 146, 148–160, 665
 - access, 667
 - extended-range VLANs, 162–165
 - Layer 2 infrastructure, 835–836
 - management, 160–162
 - VTP, 139–148, 183–194, 456
 - WRED, 715
 - configure command, 41
 - configure terminal command, 41
 - confirming
 - AAA configuration, 647
 - access, 669
 - connections, 665
 - connections, 834
 - Catalyst switches, 4–7
 - installing, 27–46
 - operating systems, 25–27
 - platforms, 7–25
 - confirming, 665
 - Ethernet, 76–98
 - hosts (AAA servers), 620
 - IP, 59
 - LAN, 742–755
 - Layer 1, 110
 - Layer 2
 - troubleshooting, 116
 - verifying, 114
 - Layer 3, 119
 - management
 - MSFC, 472
 - Switch-B, 385
 - networks
 - Layer 2, 843–844
 - Layer 2 infrastructure, 834
 - ping, 364, 368
 - QoS, 693–699
 - routers, 664
 - Telnet, 464
 - tools, 726–742
 - troubleshooting, 108–119
 - trunking, 168–172
 - UplinkFast, 307–317
 - verifying, 367–370, 389, 501, 619
 - Content switching module (WS-SVC-CSG-1), 24
 - contiguous ports, 225
 - continuous ping commands, starting, 542
 - control, confirming access, 669
 - control plane, 428, 431
 - convergence, 326–328
 - conversions, Flash file systems to native mode, 492
 - copy command, 778
 - copy running-config startup-config command, 43
 - copy startup-config running-config command, 45
 - copying
 - files, 788
 - native mode, 493
 - operating system files, 778
 - Core layer, 6, 391
 - core layer configuration, 399, 840, 897–902
 - corrupt operating system images, recovering, 790
 - corrupted frames, 334
 - CoS (Class of Service), 135, 677
 - CoS-to-DSCP map, 713
 - costs
 - LAN, 344
 - Layer 3 switching, 426
 - multilayer LAN, 349
 - ports, 281–285
 - STP, 245
 - CPUs (central processing units), 242
 - CRC (cyclic redundancy check), 169
 - CST (Common Spanning Tree), 197, 252
-
- ## D
-
- data plane, 428, 431
 - databases, VLAN, 146. *See also* VLAN
 - dates, configuring, 99. *See also* time
 - dCEF (distributed CEF), 468. *See also* CEF
 - debug dtp command, 212
 - debug dtp packets command, 212
 - debug ip igmp command, 560
 - debug ip packet command, 365, 367
 - debug ip pim command, 545, 560
 - debug standby events command, 418
 - debugging
 - BackboneFast, 322
 - PIM dense mode, 545
 - PIM sparse mode, 560
 - STP, 332
 - DEC (Digital Equipment Corporation), 241
 - default gateways, 350–351, 362
 - default port startup delays, measuring, 750
 - defining authorization levels, 616
 - delays
 - DTP, 746
 - Ethernet auto-negotiation, 745
 - forward delay, 747

- forward delay timer, 249
- PAGP, 221, 746
- port startup, 743, 750
- protocol negotiation, 744–746
- delete command, 782
- deleting
 - files, 782
 - operating system files, 778
 - VLANs, 159–160
- denial-of-service (DoS) attacks, 194
- density of ports (Layer 3 switching), 426
- design, 634, 841
 - 802.1x authentication, 656–660
 - AAA, 606–607
 - confirming, 647
 - management access, 639
 - support, 637
 - switches to use AAA, 638
 - Access layer, 414–415, 840–841
 - Auto-RP, 565–569
 - backing up, 484
 - banners, 621
 - BOOT environment variables, 799
 - booting parameters, 494
 - BPDU, 243
 - bridge table entries, 137
 - candidate RPs, 567
 - Catalyst 4000 router module, 374–375
 - Catalyst 6000/6500 switches, 497–505
 - MLS, 444–465
 - CatOS, 209, 229–233
 - CGMP, 588–602
 - Cisco IOS, 205, 228–229
 - CiscoSecure ACS, 634
 - class maps, 707
 - core, 399
 - core layer, 840
 - dates and time, 99
 - default gateways, 362
 - DHCP server support, 699
 - directory numbers, 701
 - Distribution layer, 405, 840–841
 - DNS, 52
 - dynamic routing, 402–409
 - EtherChannel, 219–238
 - bundles, 227
 - Layer 2, 835
 - planning, 219–223
 - support, 223–225
 - tasks, 225–238
 - verifying, 235–237
 - Ethernet, 76–98
 - flow control, 88
 - groups, 640
 - high-speed band rates, 793
 - hosts, 40, 361–362
 - HSRP, 410–413
 - identity, 40
 - idle session timeouts, 624
 - IGMP snooping, 576–588
 - inter-VLAN Layer 2 infrastructure, 837
 - inter-VLAN routing, 358–359, 361–370
 - Switch-A/Switch B, 380–389
 - IP, 52, 355, 370
 - ip routing command, 362
 - jumbo frames, 94
 - Layer 2 infrastructure, 834–839, 843
 - connecting, 843–844
 - interfaces, 499
 - inter-VLAN routing, 868–870
 - management, 870–875
 - parameters, 360–361, 377–380, 393
 - ports, 845–849
 - QoS, 875–882
 - security, 870–875
 - spanning tree, 857–867
 - VLAN, 849–857
 - Layer 3
 - interfaces, 499
 - routing, 500
 - switching, 370–371
 - login, 613, 615
 - loop-free topologies, 242–251
 - management of Layer 2 infrastructure, 838
 - mapping agents, 568
 - minimum flow mask, 457
 - MLS-RP, 454
 - MLS-SE, 456
 - MSFC, 472
 - MSFC-2, 473
 - multicast routing, 841
 - multilayer, 839, 841, 897
 - access layer, 902–906
 - core layer, 897–902
 - distribution layer, 902–906
 - LAN design, 344–353
 - routing, 907–914
 - network management access, 46–76
 - NTP, 101
 - passwords, 48, 637, 771
 - permit lists, 623
 - PFC, 475
 - physical port parameters, 225–227
 - PIM dense mode, 521–522
 - neighbor discovery, 523
 - tasks, 533–546
 - trees, 523–530
 - unicasting, 522
 - PIM sparse mode, 546–547
 - tasks, 556–563
 - trees, 547–556
 - PIM sparse-dense mode, 564
 - ports
 - Gigabit Ethernet, 86
 - Layer 2, 835

- prerequisites, 77–98
- privilege levels, 625
- prune eligible lists, 216
- pruning VTP, 213–218
- QoS, 688–693
 - Access layer, 702–712
 - connecting, 693–699
 - Distribution layer, 712–722
 - IOS IP telephony service, 699–702
 - Layer 2 infrastructure, 839
- restoring, 770
- RP, 556
- RSPAN, 817–825
- routed interfaces, 399–402, 405–407
- routers, 362–367, 386, 664
- saving, 42, 770
- scheduling, 716
- security, 610, 648–660
 - LAN segments, 660–663
 - Layer 2 infrastructure, 838
 - management interfaces, 617–626
 - ports, 654–656
 - protocols, 638
- SNMP, 61–67
- SPAN, 809–816
- spanning tree, 837
- static IP routing, 366
- STP
 - BackboneFast, 317–325
 - BPDU Filter, 305–307
 - BPDU, 302–305
 - load sharing, 272–293
 - multilayer design, 326–328
 - PortFast, 298–302
 - root bridges, 254–272
 - root guard, 293–298
 - troubleshooting, 328–335
 - UplinkFast, 307–317
- switches, 882–894
 - Access layer, 398–399
 - Distribution layer, 394–398
 - self-study labs, 914–930
- SYSLOG, 67–76
- system names, 664
- system time, 98–108
- TFTP servers, 796
- trunk mode (DTP), 199
- trunking
 - between switches, 194–213
 - encapsulation, 195
 - Layer 2, 835
- trunks, 619, 695
- unicasting, 534
- VACLs, 825–829
- VLAN, 146, 148–160, 665
 - access, 667
 - extended-range VLANs, 162–165
 - Layer 2 infrastructure, 835–836
 - management, 160–162
 - VTP, 139–148, 183–194, 456
 - WRED, 715
- designated router (DR), 523
- desirable mode, 182
- destination MAC addresses, 181
- detection
 - UDLD, 222, 756
 - unidirectional, 333
 - WRED, 684, 715
- devices
 - access, 648–654, 654–660
 - CDP, 734
 - Ethernet, 76–98
 - Flash, 776
 - VLAN, 129–131, 149
- DF (don't fragment) bit, 728
- DFC (Distributed Feature Card), 441
- DHCP server support, 699
- dia parameter, 265
- DiffServ (Differentiated Services) model, 675
- Digital Equipment Corporation (DEC), 241
- direct failures, STP, 250
- directory numbers, configuring, 701
- disabling
 - DTP, 746, 753
 - PAgP, 746, 752
 - ports, 247, 331
 - unnecessary services, 609
 - VTP, 146–148
- disconnections. *See also* connections
 - idle sessions, 614, 616
- DISL (Dynamic Inter-Switch Link), 172
- distributed CEF (dCEF), 468. *See also* CEF
- Distributed Feature Card (DFC), 441
- distributed switching environments, 173
- Distribution layer, 6, 391
 - configuring, 405
 - QoS, 712–722
 - switches, 394–398
- distribution layer configuration, 840–841, 902–906
- DMZ segments, optimizing, 660–663
- DNS (Domain Name Service), configuring, 52
- domains
 - broadcast, 126
 - collisions, 126
 - Layer 2, 345–347, 394
 - Layer 3, 394
 - VTP, 142, 175
- don't fragment (DF) bit, 728
- DoS (denial-of-service) attacks, 194
- dot1x port-control command, 654
- downloading
 - files, 793
 - operating system images, 798
- DR (designated router), 523
- drop adjacency, 502

DTP (Dynamic Trunking Protocol), 153, 172, 379, 744
 disabling, 753
 negotiation delays, 746
 SYSLOG, 213
 dummy multicasts, 310
 duplex, 78, 83, 333
 dynamic desirable mode, 156
 Dynamic Inter-Switch Link (DISL), 172
 dynamic routing, configuring, 402–405, 407, 409
 Dynamic Trunking Protocol (DTP), 153, 172, 379, 744

E

egress queuing, 716
 EMI (Enhanced Multilayer Image), 10, 371
 enable command, 60
 enable secret password, 609
 enabling
 BackboneFast, 320
 event logging, 332
 IGMP
 fast-leave processing, 586
 Querier, 587
 snooping, 583–584
 MAC address reduction, 163–165
 MLS, 454, 456
 port security, 651
 PortFast, 748, 752
 BPDU Filter, 306
 BPDU Guard, 303
 root guard, 295
 SSH support, 623
 SYSLOG, 213
 TACACS+, 640
 UplinkFast, 311
 user-level authentication, 615
 voice prioritization, 703
 VTP pruning, 215
 encapsulation
 configuring, 195
 trunk, 169–171
 encapsulation dot1q x command, 364
 encryption. *See also* security
 passwords, 609
 engines, switching, 686
 enhanced image, 8
 Enhanced Multilayer Image (EMI), 10, 371
 errDisable status, troubleshooting, 755–765
 EtherChannel, 167
 bundles
 configuring, 227
 STP, 290
 Switch-B, 384
 configuring, 219–238
 planning, 219–223
 support, 223–225
 tasks, 225–238
 verifying, 235–237

Layer 2, 835, 845–849
 load sharing, 222–223
 misconfiguration, 756
 negotiation, 182
 PAgP, 220–222
 performance, 180
 redundancy, 181
 Ethernet
 802.1Q-tagged frames, 170
 auto-negotiation delays, 745
 bridging, 122–125
 connections, 76–98
 LAN segmentation, 125–129
 multicast addressing, 511
 MTU, 170
 VLAN parameters, 151
 events
 exec, 644
 STP, 332
 Exclusive OR (XOR), 181
 exec events, 644
 EXEC mode, 148
 EXEC sessions, 605
 exec-timeout command, 616
 exit command, 42, 385
 extended ping, 727. *See also* ping utility
 extended-range VLANs, configuring, 162–165

F

fabric-enabled card, 441
 fabric-only card, 441
 facility tags, SYSLOG, 70
 failures
 BackboneFast, 317–325
 STP, 250
 Uplinkfast, 307–317
 Fast Link Pulse (FLP), 80
 fast-leave processing, enabling, 586
 FIB (Forwarding Information Base), 467, 476
 fields
 CoS, 677
 ToS, 676
 files
 copying, 788
 deleting, 782
 downloading, 793
 management, 771–799
 operating systems
 backing up, 484
 copying/deleting, 778
 native mode, 485
 restoring, 785
 startup, 768
 transferring (TFTP), 775

filtering, 125
 PortFast BPDU, 305–307
 traffic, 610–611

firewall services module (WS-SVC-FWM-1-K9), 24

Flash file systems
 converting to native mode, 492
 formatting, 798
 mounting, 769

flexibility of Layer 3 switching, 426

flow control, 78
 CatOS, 94
 configuring, 88
 Gigabit Ethernet, 86
 IOS, 93

flow entry, 434

flow packets, inter-VLAN routing, 356–357, 375–376

flow-based caching mechanisms, 467

flows, MLS, 448

FLP (Fast Link Pulse), 80

format command, 492

formats, native mode, 492

formatting
 class maps, 707
 Flash file systems, 798
 login banners, 615
 passwords, 637
 public/private keys, 614

forward delay timers, 249, 747

forwarding, 125
 CEF, 466. *See also* CEF
 DFC, 441
 multicasting, 516–518, 571
 RPF, 517

Forwarding Information Base (FIB), 467

forwarding states, 243
 ports, 249
 transitions, 247

frames
 802.1Q-tagged Ethernet, 170
 corrupted, 334
 oversized support, 95
 PAGP, 182

full flow masks, 458

functions. *See also* commands
 QoS, 680

G

gateways
 default, 350–351, 362
 virtual default, 351

GDA (Group Destination Address), 590

Generic VLAN Registration Protocol (GVRP), 173

Gigabit Ethernet ports, configuring, 86

gigabit ports, Switch-B, 384

GigaStack (WS-X3500-XL), 9

global configuration mode, VLANs, 155

grafting PIM dense mode, 529

Group Destination Address (GDA), 590

group-list keyword, 567

groups
 CGMP, 520, 588–602
 configuring, 640
 IGMP, 512
 memberships, 581, 596
 multicast, 541
 receivers
 adding, 577, 593
 deleting, 579, 595

guards
 PortFast BPDU, 302–305
 root, 293–298

GVRP (Generic VLAN Registration Protocol), 173

H

hard coding speed and duplex settings, IOS, 745

hardware
 ASICs, 342
 prerequisites, 77–98

hardware-based Layer 3 switching architectures, 433–434

hello parameter, 265

Hello timer, 249

high availability, EtherChannel, 181

high-speed band rates, configuring, 793

hopping, VLAN, 197

host-based authentication, 608

hostname global configuration command, 41

hosts, 361
 AAA servers, 620
 configuring, 361–362
 connecting, 697
 names, 40

Hot Standby Router Protocol (HSRP), 328, 349–353, 482

hybrid mode
 CEF-based Layer 3 switching, 465–478
 upgrading, 479–497

hyper terminals, 793

I

identifying loops, 329

identity, 40

idle sessions
 disconnecting, 614, 616
 timeouts, 624

IEEE 802.1d version of STP, 241. *See also* STP

- IGMP (Internet Group Management Protocol)
 - fast-leave processing, 580, 586
 - Membership Report message, 578
 - multicasting, 512
 - Querier, 587
 - snooping, 520, 576–588
- images, 8
 - EMI, 10
 - operating systems
 - downloading, 798
 - recovering corrupt, 790
 - upgrading, 775
 - SMI, 10
- implementation
 - CEF, 470
 - control planes, 431
 - data planes, 431
 - QoS, 681–688
 - redundant multilayer topology, 390–421
 - VLAN
 - Catalyst switches, 131–132
 - CatOS, 132
- implementing VLAN, 131–132
- in-band management interfaces, 160
- indirect failures, STP, 250
- infrastructure
 - Layer 2
 - configuring, 843
 - connecting, 843–844
 - inter-VLAN routing, 868–870
 - management, 870–875
 - ports, 845–849
 - QoS, 875–882
 - security, 870–875
 - spanning tree, 857–867
 - switching, 834–839
 - VLAN, 849–857
 - switching, 606. *See also* security
 - VLAN, 129–131
- ingress port queues, viewing, 687
- installing Catalyst switches, 27–46
- instances, CST, 197
- interconnections. *See also* connections
 - switches, 619, 695
 - trunking, 168–172
 - VTP, 173–178
- interface FastEthernet 0/0.x command, 363
- interface global configuration command, 161
- interface range command, 84, 499
- interface vlan 1 global configuration command, 161
- interface VLAN 200 command, 373
- interface VLAN 300 command, 373
- interface vlan global configuration command, 381
- interface VLAN x global configuration mode command, 373
- interfaces
 - Cisco IOS, 154–158
 - in-band management, 160
- IOS
 - disabling, 146–148
 - verifying transparent bridging, 137–139
 - VLAN, 133
 - Layer 2 configuration, 499
 - Layer 3 configuration, 499
 - management, 796
 - MLS, 455
 - out-of-band management, 160
 - physical, 372
 - ping command, 669
 - ping connectivity, 367–370
 - ranges, 157
 - routers, 399–402, 405–407
 - sc0, 161
 - security, 611–617
 - configuring, 617–626
 - optimizing AAA, 626–633
 - SVI, 52, 161, 372
 - SVU, 473
 - Switch-A, 381
 - switchport interface configuration, 156
 - VLANs, 156
- internal bandwidth allocation, 90
- interoperability, snooping, 597
- Inter-Switch Link. *See* ISL
- interswitch trunks, configuring, 205
- interval keyword, 567
- inter-VLAN routing
 - architecture, 340–343
 - configuring, 358–359, 361–370
 - Layer 2 configuration, 837, 868–870
 - packet flow, 356–357, 375–376
 - Switch-A/Switch-B, 380–389
- Intrusion detection system module (WS-SVC-IDS2BUNK9), 24
- IOS, 83, 614
 - disabling DTP/PAGP, 746
 - DNS configuration, 52, 56
 - EtherChannel, 228–229
 - file management, 773
 - flow control, 93
 - Gigabit Ethernet, 87
 - hard coding speed and duplex settings, 745
 - IP addressing configuration, 52
 - IP telephony service, 699–702
 - NTP, 103, 106
 - passwords
 - configuring, 48
 - recovery, 768–771
 - PortFast, 748
 - RSPAN, 818
 - secure management protocols, 609
 - SNMP, 63
 - SPAN, 810
 - spanning tree delays, 747
 - speed, 83
 - switch security, 623

- switchport host interface configuration macro, 749
- SYSLOG, 71
- traceroute mac command, 740
- traceroute mac ip command, 740
- transparent bridging, 137–139
- VLAN, 133
- VTP, 146–148
- IP (Internet Protocol), 52
 - addresses (l2trace command), 742
 - connections, 59
 - IOS telephony service, 699–702
 - multicast addressing, 510
 - multicasting, 513–515
 - parameters, 664
 - routing
 - configuring, 355
 - MSFC, 474
 - Switch-A, 382
 - routing tables, 366
 - tools, 726–742
 - CDP, 734
 - Layer 2 traceroute, 737–742
 - ping utility, 727
 - traceroute, 729–733
- ip default-gateway command, 362
- ip default-gateway global configuration command, 362
- ip domain-lookup command, 55
- ip igmp join-group command, 541
- ip igmp snooping global configuration command, 584, 587
- ip multicast-routing global configuration command, 557
- ip name-server command, 55
- IP Phones
 - connecting, 697
- ip pim dense-mode command, 537
- ip pim interface configuration command, 536, 564
- ip pim rp-address command, 557
- ip pim send-rp-announce global configuration command, 567
- ip pim send-rp-discovery global configuration command, 568
- ip route global configuration command, 365
- ip routing command, 362
- IPSec virtual private network (VPN) services module (WS-SVC-IPSEC-1), 24
- ISL (Inter-Switch Link), 169

J

- JAM signals, 126
- join messages, VTP, 214
- joining multicast groups, 541
- jumbo frames, 97
 - configuring, 94
 - Gigabit Ethernet, 86

K

- keys, creating, 614
- keywords
 - group-list, 567
 - interval, 567
 - mrouter learn, 584
 - override, 557
 - permanent, 137
 - secondary, 264
 - static, 137

L

- l2trace utility, 737
- lack of resources, 334
- LAN (local area network)
 - bandwidth aggregation, 179
 - Catalyst switches, 4–7
 - installing, 27–46
 - operating systems, 25–27
 - platforms, 7–25
 - collapsed backbone architecture, 345–347
 - multicasting, 519–520, 570–576
 - multilayer design, 344–353
 - redundant topologies, 738
 - segmentation, 125–129
 - segment security, 660–663
 - tools, 726–742
 - topologies (multiple VLANs), 149
 - transparent bridging, 122–125, 133–139
- Layer 1 connections, verifying, 110
- Layer 2
 - collapsed backbone design, 345–347
 - connections, 114
 - domains, 394
 - infrastructure
 - configuring, 843
 - connecting, 843–844
 - inter-VLAN routing, 868–870
 - management, 870–875
 - ports, 845–849
 - QoS, 875–882
 - security, 870–875
 - spanning tree, 857–867
 - VLAN, 849–857
 - interfaces, 499
 - multicasting, 571
 - parameters, 360–361, 377–380, 393
 - switching, 834–839
 - switching engines, 686
 - traceroute utility, 737–742
 - troubleshooting, 116

Layer 3

- connections, 119
- domains, 394
- interfaces, 499
- multicasting, 520
- routing, 500
- switches, 343
- switching, 426–433
 - CEF-based, 465–478
 - configuring, 370–371
 - hardware-based architecture, 433–434
- switching engines, 686
- topologies, 391

layers, 6

- Access, 391
 - configuring, 414–415
 - QoS, 702–712
 - switches, 398–399
- Core, 391
- Distribution, 391
 - configuring, 405
 - QoS, 712–722
 - switches, 394–398
- multilayer configuration, 897
 - access layer, 902–906
 - core layer, 897–902
 - design, 326–328
 - distribution layer, 902–906
 - routing, 907–914
- multi configuration, 839, 841
- leaf switches, Uplinkfast, 307–317
- learning, spanning tree, 746–749
- Learning phase, spanning-tree topology, 249
- LEDs (light emitting diodes), 112
- levels
 - authorization, 616
 - privilege, 625
- limitations
 - of native mode, 481
 - of RSPAN/SPAN, 805
- line cards, 23
- line vty command, 48
- links
 - bandwidth aggregation, 178–182
 - DISL, 172
 - ISL, 169
 - UDLD, 222
 - unidirectional, 333
- listening, spanning tree, 746–749
- Listening state, 248
- lists, configuring prune eligible, 216
- load sharing, 353
 - configuring, 272–293
 - EtherChannel, 222–223
 - MAC addresses, 180
- local area networks. *See* LANs
- local leave processing, 595
- lockout parameters, 621

- logical components, Layer 3 switches, 373
- login
 - authentication, 51, 613
 - banners
 - configuring, 613
 - creating, 615
 - parameters, 621
- login line configuration command, 48
- login local command, 615
- logs, STP events, 332
- lookup tables, routes, 434
- loops
 - breaking, 331
 - identifying, 329
 - routing, 730
 - spanning tree listening/learning, 746–749
 - Spanning-tree, 196
 - STP. *See* STP

M

- MAC (Media Access Control), 180
 - 12trace command, 741
 - enabling reduction, 163–165
- mac-address-table static global configuration command, 575
- macros, 749
 - interface range, 157
 - switchport host interface configuration, 749
 - WORKSTATION-PORTS, 84
- management
 - access, 605–606
 - AAA, 606–607, 639
 - configuring, 46–76
 - protocols, 608–609
 - reducing vulnerabilities, 609
 - restricting, 608, 614
 - CGMP, 520, 588–602
 - collapsed backbone architecture, 346
 - connections
 - MSFC, 472
 - Switch-B, 385
 - files, 771–799
 - interfaces
 - configuring, 796
 - configuring security, 617–626
 - optimizing AAA, 626–633
 - security, 611–617
 - LAN, 344
 - Layer 2 configuration, 838, 870–875
 - multilayer LAN, 349
 - VLAN, 160–162
 - VTP, 173–178
- management interface configuration command, 162
- manual configuration, Ethernet, 80
- manual root bridge configuration, 266

- mapping agents, configuring, 568
 - maps
 - class, 707
 - CoS-to-DSCP, 713
 - threshold, 719
 - VACLs, 827
 - max age timer, 249
 - maximum devices per VLAN, 149
 - maximum transmission unit (MTU), 170
 - maximum-paths command, 409
 - measurements, default port startup delays, 750
 - memberships, groups, 581, 596
 - memory, TCAM, 436
 - messages
 - CDP propagation, 734
 - IGMP Membership Report, 578
 - join, 214
 - state refresh (PIM), 530
 - SYSLOG, 758. *See also* SYSLOG
 - microflow basis, 687
 - minimum flow mask, configuring, 457
 - misconfiguration. *See also* configuration; troubleshooting
 - EtherChannel, 756
 - MLS (multilayer switching), 343, 434
 - Catalyst 6000/6500 switches, 444–465
 - platform support, 451
 - verifying, 459
 - MLS protocol (MLSP), 445
 - MLS Route Processor (MLS-RP), 445
 - MLS Switching Engine (MLS-SE), 445
 - MLSP (MLS protocol), 445
 - MLS-RP (MLS Route Processor), 445, 454
 - MLS-SE (MLS Switching Engine), 445, 456
 - models
 - DiffServ, 675
 - QoS, 674
 - modes
 - auto, 182
 - configuration, 187
 - desirable, 182
 - trunk, 172, 199
 - VTP, 142, 175, 176
 - modification
 - boot environment variables, 789
 - STP timers, 265
 - Supervisor engines, 496
 - modules
 - routers
 - configuring, 386
 - testing, 385
 - switching, 19, 23
 - monitoring
 - connections, 108–119
 - STP, 328–335
 - mounting Flash file systems, 769
 - moving files, 788
 - mrouter learn keywords, 584
 - MSFC (multilayer switching feature card), 22, 686
 - Catalyst 6000/6500 switches, 435
 - configuring, 472
 - MSFC-2, configuring, 473
 - MST (Multiple Spanning Tree), 252
 - MTU (maximum transmission unit), 170
 - multicast routing, configuring, 841
 - multicasting, 509–510
 - Auto-RP, 565–569
 - addressing, 510
 - CGMP, 588–602
 - configuration, 89, 907–9147
 - access layer, 902–906
 - core layer, 897–902
 - distribution layer, 902–906
 - routing, 907–914
 - forwarding, 516–518
 - IGMP, 512, 576–588
 - IP, 513–515
 - LAN, 519–520, 570–576
 - PIM dense mode
 - configuring, 521–522
 - neighbor discovery, 523
 - tasks, 533–546
 - trees, 523–530
 - unicasting, 522
 - PIM sparse mode
 - configuration tasks, 556–563
 - configuring, 546–547
 - trees, 547–556
 - PIM sparse-dense mode, 564
 - VTP, 177
 - multilayer configuration, 839, 841
 - multilayer design, 326–328
 - multilayer LAN design, 344–353
 - multilayer switch feature card (MSFC), 686
 - multilayer switches, Catalyst 3550, 372–374
 - multilayer switching. *See* MLS
 - multilayer switching feature card (MSFC), 22
 - Catalyst 6000/6500 switches, 435
 - Multiple Spanning Tree (MST), 252
 - multiple virtual routers, 353
 - multiple VLANs, 149
- ## N
-
- names
 - hosts
 - configuring, 40
 - system, 618
 - configuring, 664
 - NAS (network attached storage), 94
 - native mode
 - booting, 488
 - CEF-based Layer 3 switching, 497–505
 - operating system files, 485
 - upgrading, 479–497

native VLANs, 196. *See also* VLANs

negotiation

- DTP, 153, 172, 746
- EtherChannel, 182
- PAgP, 220–222, 746
- ports, 86
- protocols, 744–746
- trunking, 171–172

neighbors

- PIM dense mode, 523
- viewing, 538

NetFlow statistics, 504

Network analysis module (WS-SVC-NAM-x), 25

network architecture. *See also* architecture

- network attached storage (NAS), 94
- point-to-point architecture, 6–16, selecting, 6,

Network Time Protocol (NTP), 101

networks

- access, 610
- connections
- LAN
 - multicasting, 519–520, 570–576
 - multilayer design, 344–353
- Layer 2 infrastructure, 834
- management access, 46–76
- QoS, 673–674
 - DiffServ model, 675
 - functions, 680
 - implementing, 674, 681–688
- STP, 264–272
- VLANs, 149–150

no ip igmp snooping global configuration command, 575

no ip routing global configuration command, 362

no shutdown command, 381

no shutdown interface configuration mode command, 161, 363

no switchport interface configuration command, 381

non fabric-enabled card, 441

non-silent PAgP operation, 222

NTP (Network Time Protocol), 101, 107

O

O IA designations, 408

operating systems

- backing up, 484
- Catalyst 6000/6500 switches, 444
- Catalyst switches, 25–27
- CatOS
 - creating VLANs, 152–154
 - EtherChannel, 229–233
 - verifying transparent bridging, 134
 - VLAN, 132
- files
 - copying/deleting, 778
 - restoring, 785

images

- downloading, 798
- recovering corrupt, 790
- native mode, 485
- recovery, 791, 794
- upgrading, 775, 786

optical time domain reflector (OTDR), 112

optimization

- AAA, 626–633
- EtherChannel, 180
- load sharing, 326–328
- route lookup tables, 434
- security (DMZ segments), 660–663
- STP, 251–254

options

- cgmp, 584
- pimdvmrp, 584

Organizational Unique Identifier (OUI), 512

OTDR (optical time domain reflector), 112

OUI (Organizational Unique Identifier), 512

out-of-band management interface, 160

override keyword, 557

oversized frame support, 95

P

packets

- flow, 356–357, 375–376
- unicast, 509

PAgP (Port Aggregation Protocol), 182, 745

- disabling, 752
- negotiation, 220–222
- negotiation delays, 746

parameters

- booting, 494
- dia, 265
- hello, 265
- IP configuration, 664
- Layer 2 configuration, 360–361, 377–380, 393
- lockout, 621
- login, 621
- MLS configuration, 457
- physical ports, 225–227
- portvlancost, 287
- QoS configuration, 694
- secondary, 264
- security configuration, 618
- timeout, 614
- VLAN, 151

passwords. *See also* AAA; security

- configuring, 48, 771
- creating, 637
- encryption, 609
- recovery, 765–771
- VTP, 194

- paths. RPF, 517
- peers. PAgP, 182
- performance. *See also* optimization
 - collapsed backbone architecture, 346
 - EtherChannel, 180
 - LAN, 344
 - Layer 3 switching, 426
 - multilayer LAN, 349
 - segmentation, 125–129
- permanent keyword, 137
- permit lists, configuring, 623
- Per-VLAN spanning tree (Cisco PVST +), 252
- PFC (policy feature card), 22
 - Catalyst 6000/6500 switches, 435
 - configuring, 475
- physical interfaces, 372, 381, 384
- physical site surveys. *See also* architecture
 - performing, 6–16,
 - physical trunks, 384
- PIM dense mode configuration, 521–522
 - neighbor discovery, 523
 - tasks, 533–546
 - trees, 523–530
 - unicasting, 522
- PIM sparse mode configuration, 546–547
 - tasks, 556–563
 - trees, 547–556
- PIM sparse-dense mode, configuring, 564
- pimdvmrp option, 584
- ping command, 84, 367, 727
 - connectivity
 - testing, 364, 368
 - verifying, 367–370
 - interfaces, 669
 - starting, 542
- ping ip command, 727
- placement
 - root bridge, 256–259, 275
 - secondary, 260
- planning
 - 802.1x authentication, 650
 - accounting, 628
 - authentication, 627
 - authorization, 628
 - EtherChannel configuration, 219–223
 - inter-VLAN routing configuration, 358–359, 361–370
 - port security, 649
 - trunk configuration, 195–204
 - VTP configuration, 184
- platforms
 - Catalyst switches, 7–25
 - MLS support, 451
- point-to-point architecture, 6–16, 516–524, 730–738, 828–833
- policies, QoS, 708. *See also* QoS
- policy feature card. *See* PFC
- Port Aggregation Protocol. *See* PAgP
- port-channel load-balance global configuration mode
 - command, 234
- PortFast, 748
 - BPDU Filter configuration, 305–307
 - BPDU guard configuration, 302–305
 - configuring, 298–302
 - enabling, 752
- ports
 - access, 620
 - auto-negotiation, 171–172
 - cost, 281–285
 - density (Layer 3 switching), 426
 - designating, 248
 - disabling, 247, 331
 - errDisable status, 755–765
 - forwarding state, 249
 - gigabit (Switch-B), 384
 - Gigabit Ethernet configuration, 86
 - ingress queues, 687
 - Layer 2
 - configuring, 845–849
 - infrastructure, 835
 - LEDs, 112
 - physical parameters, 225–227
 - priorities, 276–281
 - router assignment, 591
 - security, 757
 - configuring, 654–656
 - enabling, 651
 - planning, 649
 - spanning tree
 - listening/learning, 746–749
 - states, 246
 - startup delays, 743, 750
 - VLAN assignment, 151
- portvlancost value, 287
- prerequisite configuration, 77–98
- priorities, ports, 276–281
- private keys, creating, 614
- private VLANs, configuring, 665
- privilege command, 616
- privileged access mode, 770
- privileges, configuring levels, 625
- propagation of CDP messages, 734
- protocols
 - CDP, 117, 196, 734
 - CGMP, 520, 588–602
 - DISL, 172
 - DTP, 153, 172, 379, 744
 - GVRP, 173
 - HSRP, 328, 349–353, 410–413, 482
 - IGMP
 - multicasting, 512
 - snooping, 520, 576–588
 - IP
 - multicast addressing, 510
 - multicasting, 513–515
 - management access, 608–609

- MLSP, 445
- negotiation delays, 744–746
- NTP, 101
- PAGP, 182, 745
- RSTP, 251
- security configuration, 638
- SNMP, 47
- STP, 241–242
 - BackboneFast, 317–325
 - BPDU Filter, 305–307
 - BPDUs, 302–305
 - configuring root bridges, 254–272
 - creating loop-free topologies, 242–251
 - load sharing, 272–293
 - multilayer design, 326–328
 - new features, 251–254
 - PortFast, 298–302
 - root guard, 293–298
 - troubleshooting, 328–335
 - Uplinkfast, 307–317
- SYSLOG configuration, 67–76
- TFTP, 775
- VRRP, 353
- VTP, 139–148, 173–178, 360
- proxy reporting, 579
- prune eligible lists, configuring, 216
- pruning
 - PIM dense mode, 526
 - VTP, 213–218
- pruning trunks, 178
- public keys, creating, 614
- punt adjacency, 502

Q

- QoS (quality of service), 673–674
 - commands, 692
 - configuring, 688–693
 - Access layer, 702–712
 - connecting, 693–699
 - Distribution layer, 712–722
 - IOS IP telephony service, 699–702
 - functions, 680
 - implementing, 681–688
 - Layer 2
 - configuring, 875–882
 - infrastructure, 839
 - models, 674, 675
 - quality of service. *See* QoS
 - Querier (IGMP), 587
 - queuing, egress, 716

R

- RADIUS servers, defining IP addresses, 629
- radius-server command, 631
- ranges
 - extended-range VLANs, 162–165
 - interfaces, 157
- Rapid Spanning Tree Protocol (RSTP), 251
- rebooting switches, 497. *See also* booting
- receivers
 - groups
 - adding, 577, 593
 - deleting, 579, 595
 - SPT from source to all, 553
- recommendations
 - trunking modes, 200
 - VTP configuration, 193–194
- recovery. *See also* troubleshooting
 - corrupt operating system images, 790
 - operating systems, 791, 794
 - passwords, 765–771
- reduction, enabling MAC addresses, 163–165
- redundancy, EtherChannel, 181
- redundant LAN topologies, 738
- redundant multilayer topologies, 390–421
- registration, GVRP, 173
- remote EXEC access, 47
- remote SPAN. *See* RSPAN
- renaming startup configuration files, 769
- rendezvous point (RP), 547
 - Auto-RP configuration, 565–569
 - configuring, 556
 - SPT, 550
- reports, proxy reporting, 579
- requirements
 - native mode, 480
 - switching self-study lab, 833–834
- reserved multicast addresses, 511
- resetting passwords, 770
- resources, lack of, 334
- restoring
 - configurations, 770
 - operating system files, 785
- restricting
 - access (Telnet), 622, 624
 - management access, 608, 614
- reverse path forwarding (RPF), 517
- rolling back operating system images, 775
- ROMMON
 - booting, 487
 - management interface, 796
- root bridges
 - configuring, 254–272
 - placement, 256–260, 275
 - selecting, 245
- root guard, configuring, 293–298
- root macro command, 264

- roots, spanning trees, 242
- round robin, 685
- route, 434
- Route Processor Redundancy Plus (RPR+), 481
- routed interfaces, configuring, 399–402, 405–407
- router eigrp 1 command, 388
- Router-A, configuring, 362–367
- Router-B, configuring, 362–367
- router-on-a-stick, 340–341
- routers, 361
 - BDR, 405
 - Catalyst 4000 router module, 374–375
 - configuring, 362–367, 664
 - connecting, 664, 697
 - DR, 523
 - HSRP, 349–353
 - modules
 - configuring, 386
 - testing, 385
 - multiple virtual, 353
 - port assignment, 591
 - VRRP, 353
- routes
 - cached, 434
 - lookup tables, 434
 - static, 669
- routing
 - configuring, 841, 907–914
 - dynamic configuration, 402–409
 - inter-VLAN. *See also* inter-VLAN routing
 - configuring, 358–359, 361–370
 - packet flow, 356–357, 375–376
 - Switch-A/Switch-B, 380–389
 - IP
 - configuring, 355, 370
 - MSFC, 474
 - Switch-A, 382
 - Layer 3
 - configuring, 500
 - switches, 343
 - loops, 730
 - multicasting, 509–510
 - addressing, 510
 - Auto-RP, 565–569
 - building trees (PIM dense modes), 523–530
 - CGMP, 588–602
 - configuring (PIM dense mode), 521–522
 - configuring (PIM sparse mode), 546–547
 - forwarding, 516–518
 - IGMP, 512, 576–588
 - IP, 513–515
 - LAN, 519–520, 570–576
 - neighbor discovery, 523
 - PIM sparse-dense mode, 564
 - tasks (PIM dense mode configuration), 533–546

- tasks (PIM sparse mode configuration), 556–563
- trees (PIM sparse mode), 547–556
- unicasting, 522
- static IP configuration, 366
- tables
 - verifying, 366
 - viewing, 364
- unicast configuration, 534
- verifying, 366
- RP (rendezvous point), 547
 - Auto-RP configuration, 565–569
 - configuring, 556
 - SPT, 550
- RPF (reverse path forwarding), 517
- RPR+ (Route Processor Redundancy Plus), 481
- RSPAN (remote SPAN), 799, 802
 - configuring, 817–825
 - limitations, 805
- RSTP (Rapid Spanning Tree Protocol), 251

S

- SAN (storage area networking), 94
- saving
 - configuration, 42, 770
 - files, 778
- sc0 (virtual management interface), 161
- scalability, 20
 - collapsed backbone design, 347
 - LAN, 344
 - multilayer LAN, 349
- scheduling configuration, 716
- secondary parameters, 264
- secondary placement, root bridges, 260
- security, 178
 - CatOS switches, 621
 - device access, 648–654, 654–660
 - interfaces, 611–617
 - configuring, 617–626
 - optimizing AAA, 626–633
 - IOS switches, 623
 - LAN segments, 660–663
 - Layer 2
 - configuring, 870–875
 - infrastructure, 838
 - management access, 605–606
 - AAA, 606–607
 - protocols, 608–609
 - reducing vulnerabilities, 609
 - restricting, 608
 - networks, 610
 - password recovery, 765–771
 - ports, 757
 - configuring, 654–656
 - enabling, 651
 - planning, 649

- protocol configuration, 638
- SYSLOG, 70. *See also* SYSLOG
- traffic filtering, 610–611
- VTP, 194
- segmentation
 - LAN, 125–129
 - security, 660–663
- selecting
 - number of VLANs needed, 149–150
 - root bridges, 245
- self-study labs
 - multilayer configuration, 897
 - access layer, 902–906
 - core layer, 897–902
 - distribution layer, 902–906
 - routing, 907–914
 - switch configurations, 882–894, 914–930
 - switching
 - Layer 2 infrastructure, 834–839
 - multilayer configuration, 839, 841
 - requirements, 833–834
- servers
 - AAA, 620
 - DHCP support, 699
 - NTP, 103
 - RADIUS, 629
 - TACACS+
 - authorization, 643
 - defining IP addresses, 629
 - enabling, 640
 - TFTP configuration, 796
 - VTP configuration, 186
- services
 - disabling, 609
 - QoS, 673–674
 - DiffServ model, 675
 - functions, 680
 - implementing, 681–688
 - models, 674
 - telephony (IOS IP), 699–702
- session command, 384, 473
- sessions
 - EXEC, 605
 - idle
 - configuring timeouts, 624
 - disconnecting, 614, 616
 - timeout, 621
- set accounting command, 631
- set authentication command, 630
- set authentication login command, 613
- set authorization command, 630
- set banner motd command, 613
- set BAUD command, 792
- set boot config-register command, 488
- set crypto key rsa command, 614
- set dot1x command, 653
- set enablepass command, 50
- set igmp enable command, 583
- set igmp fastleave enable command, 587
- set interface sc0 command, 161
- set interface sc0 configuration command, 57
- set ip permit command, 614
- set logout command, 614
- set password command, 50
- set port channel command, 231
- set port dot1x command, 653
- set port duplex command, 85
- set port host, 749
- set port host marco, 749
- set port security command, 651
- set pvlan command, 662
- set radius server command, 629
- set security acl command, 663
- set spantree macreduction command, 163, 268
- set spantree portcost mod/port cost cost command, 287
- set spantree portpri mod/port priority cost command, 289
- set spantree portvlancost command, 287
- set spantree root command, 265
- set spantree root secondary command, 264
- set spantree uplinkfast disable command, 314
- set system name command, 42
- set tacacs server command, 629
- set trunk command, 209
- set vlan command, 152, 210
- set vlan vlan-id pvlan-type command, 662
- set vtp command, 190
- set vtp pruneeligible command, 216
- set vtp pruning command, 216
- SFM (switch fabric module), 440–441
- shared trees, 515, 548
- sharing (load), 353
 - EtherChannel, 222–223
 - MAC addresses, 180
 - STP, 272–293
- shortest path tree (SPT), 514, 547
 - from source to RP, 550
 - troubleshooting, 553
- show arp command, 414
- show bootvar command, 494
- show cam dynamic command, 134, 136
- show cam permanent command, 137, 575
- show cam static command, 137
- show cdp neighbors command, 736
- show cdp neighbors detail command, 736
- show cgmp command, 602
- show channel group command, 230
- show channel traffic command, 238
- show clock command, 101
- show etherchannel port command, 236
- show interface command, 227
- show interface switchport command, 208
- show interface trunk command, 209, 217
- show interfaces port-channel 1 command, 387
- show ip igmp snooping mrouter command, 585
- show ip mroute active command, 544

- show ip mroute command, 540
- show ip ospf neighbor command, 403, 407
- show ip pim neighbor command, 538
- show ip pim rp mapping command, 569
- show ip route command, 364, 366
- show ip rpf command, 539
- show mac-address-table dynamic command, 137
- show mac-address-table multicast command, 576, 585
- show mac-address-table static command, 139
- show mls cef mac command, 501
- show module command, 40
- show multicast group command, 584
- show multicast router command, 583
- show port capabilities command, 225, 687
- show port command, 115
- show port mod/port command, 227
- show port negotiation command, 88
- show spanning-tree active command, 291
- show spanning-tree blockedports command, 291
- show spanning-tree bridge command, 267
- show spanning-tree detail command, 271
- show spanning-tree interface command, 271
- show spanning-tree root command, 271
- show spanning-tree summary command, 398
- show spanning-tree uplinkfast command, 314
- show spantree 1 command, 272
- show spantree uplinkfast command, 313
- show standby brief command, 413
- show standby command, 421
- show startup-config command, 45
- show trunk command, 211, 218, 380
- show version command, 37, 385
- show vlan command, 154, 158, 192
- show vlan internal usage command, 165
- show vtp domain command, 188, 193
- show vtp status command, 148, 188
- silent PAgP operation, 222
- Simple Network Management Protocol (SNMP), 47, 61–67
- site surveys, 6–16, 516–524, 730–738, 828–833
- SMI (Standard Multilayer Image), 10, 371
- SNMP (Simple Network Management Protocol), 47, 61–67
- snooping
 - IGMP, 520, 576–588
 - interoperability, 597
- software prerequisites, 77–98. *See also* applications
- source trees, 514
- SPAN (switch port analyzer), 799, 801
 - configuring, 809–816
 - limitations, 805
- Spanning Tree Protocol. *See* STP
- spanning trees
 - CST, 197
 - Layer 2
 - configuring, 857–867
 - infrastructure, 837
 - listening/learning, 746–749
 - loops, 196
 - PortFast, 748
 - Spanning-Tree Algorithm (STA), 248
 - spanning-tree cost cost interface configuration command, 286
 - spanning-tree extend system-id global configuration command, 163
 - spanning-tree vlan 1 root command, 268
 - spanning-tree vlan interface configuration command, 286
 - specifications, STP, 251–254
 - speed, 78, 83
 - duplex auto-negotiation, 744
 - high-speed band rates, 793
 - SPT (shortest path tree), 514, 547
 - from source to RP, 550
 - troubleshooting, 553
 - squeeze command, 782
 - SSH (Secure Shell). enabling support, 623
 - STA (Spanning-Tree Algorithm), 248
 - Standard Multilayer Image (SMI), 10, 371
 - standards image, 8
 - standby 1 ip 192.168.1.10 command, 412
 - standby track command, 412
 - starting continuous ping commands, 542
 - startup
 - files, 768
 - port delays, 750
 - renaming configuration files, 769
 - troubleshooting, 742–755
 - state refresh messages, PIM, 530
 - states
 - blocking, 243, 247
 - forwarding, 243
 - ports, 249
 - transitions, 247
 - Listening, 248
 - spanning tree
 - port, 246
 - verifying, 272
 - static bridge table entries, 572
 - static IP routing, configuring, 366
 - static keyword, 137
 - static routes, adding, 669
 - statistics, NetFlow, 504
 - storage area networking (SAN), 94
 - STP (Spanning Tree Protocol), 241–242
 - BackboneFast configuration, 317–325
 - BPDU Filter configuration, 305–307
 - BPDU configuration, 302–305
 - load sharing configuration, 272–293
 - loop-free topologies, 242–251
 - multilayer design configuration, 326–328
 - new features, 251–254
 - PortFast configuration, 298–302
 - root bridges configuration, 254–272
 - root guard configuration, 293–298
 - troubleshooting, 328–335
 - UplinkFast configuration, 307–317

- strict priority, 683, 685
- Supervisor 1A option, Catalyst 6000/6500 switches, 437
- Supervisor engines, 17, 22
 - Catalyst 6000/6500 switches, 435. *See also* Catalyst 6000/6500 switches
 - modifying, 496
 - Supervisor 720, 443
 - viewing, 494
- Supervisor 1 module, Catalyst 6500/6000 switches, 436
- Supervisor 2 module, Catalyst 6000/6500 switches, 438
- Supervisor 3 module (Catalyst 4000 switches), 685
- support
 - AAA configuration, 634, 637
 - baby giants, 96
 - DHCP servers, 699
 - EtherChannel, 223–225
 - oversized frame, 95
 - platforms (MLS), 451
 - SNMP configuration, 61–67
 - SSH, 623
 - SYSLOG configuration, 67–76
- SVI (switched virtual interface), 52, 161, 372, 473
- switch fabric module (SFM), 440–441
- switch port analyzer feature. *See* SPAN
- switch processors, 479
- Switch-A, 154
 - bridge tables
 - configuring entries, 137
 - viewing, 135
 - extended-range VLANs, 164
 - inter-VLAN routing configuration, 380–389
 - IP routing, 382
 - Layer 2 parameters configuration, 377
 - trunking, 378
 - VLANs, 153, 378
- Switch-B, 384
 - bridge tables, 137
 - extended-range VLANs, 165
 - gigabit ports, 384
 - inter-VLAN routing configuration, 380–389
 - Layer 2 parameters configuration, 379
 - MAC address reduction, 163
 - management connections, 385
 - management interfaces, 162
 - VLANs, 379
 - creating, 155
 - verifying, 158
 - VTP
 - disabling, 147
 - verifying, 148
- switched virtual interfaces. *See* SVIs
- switches
 - AAA
 - configuring, 638
 - support, 637
 - Access layer configuration, 398–399
 - booting, 797
 - bridges, 122–129
 - Catalyst, 4–7, 131–132
 - CatOS, 132
 - installing, 27–46
 - operating systems, 25–27
 - platforms, 7–25
 - catalyst 2900XL/3500XL, 681
 - Catalyst 2950/3550, 682
 - Catalyst 3550 multilayer, 372–374
 - Catalyst 4000 series of, 684
 - Catalyst 6000/6500, 686
 - architecture, 434–443
 - configuring, 497–505
 - configuring MLS, 444–465
 - operating systems, 444
 - upgrading, 479–497
 - CatOS security, 621
 - CGMP, 597
 - configuring, 882–894, 914–930
 - connections, 726–742
 - DISL, 172
 - Distribution layer configuration, 394–398
 - errDisable status, 755–765
 - EtherChannel
 - configuring, 219–238
 - planning, 219–223
 - support, 223–225
 - tasks, 225–238
 - file management, 771–799
 - IGMP snooping, 582
 - interconnecting, 619, 695
 - interfaces
 - configuring security, 617–626
 - optimizing AAA, 626–633
 - security, 611–617
 - IOS security, 623
 - ISL, 169
 - Layer 3 routing, 343
 - multicasting, 520
 - network management access, 46
 - parameter configuration, 664
 - password recovery, 765–768
 - QoS
 - Access layer, 702–712
 - configuring, 688–693
 - connecting, 693–699
 - Distribution layer, 712–722
 - implementing, 681–688
 - IOS IP telephony service, 699–702
 - rebooting, 497
 - security, 610
 - SYSLOG, 213
 - traffic filtering, 610–611
 - transparent bridging, 133–139
 - trunking, 168–172, 194–213
 - two-LAN internetworks, 130
 - VLAN, 129–131, 151. *See also* VLAN
 - VTP, 173–178. *See also* VTP

- switching
 - distributed environments, 173
 - engines, 686
 - Layer 3, 426–433
 - CEF-based, 465–478
 - configuring, 370–371
 - hardware-based architecture, 433–434
 - MLS, 343, 434
 - modules, 19, 23
 - multicast routing, 509–510
 - addressing, 510
 - CGMP, 588–602
 - forwarding, 516–518
 - IGMP, 512
 - IGMP snooping, 576–588
 - IP, 513–515
 - LAN, 519–520, 570–576
 - security, 606. *See also* security
 - self-study lab
 - Layer 2 infrastructure, 834–839
 - multilayer configuration, 839, 841
 - requirements, 833–834
 - switchport host interface configuration macro, 749
 - switchport interface configuration command, 156
 - switchport mode access command, 156
 - switchport security command, 652
 - switchport trunk interface configuration command, 206
 - switchport trunk pruning interface configuration command, 216
 - symmetric routing, 730. *See also* routing
 - SYSLOG
 - configuring, 67–76
 - enabling, 213
 - messages, 758
 - system logging (SYSLOG), 47
 - system name configuration, 664
 - system settings, Catalyst 6000/6500 switches, 498
 - system time configuration, 98–108
 - systems, names, 618
- ## T
-
- tables, 366
 - adjacency, 467, 477
 - bridges, 122
 - configuring entries, 137
 - viewing on Switch-B, 137
 - lookup routes, 434
 - multicast routing, 516
 - routing, 364
 - static bridge entries, 572
 - TACACS+ servers
 - authorization, 643
 - enabling, 640
 - IP addresses, 629
 - tacacs-server command, 631
 - tagged traffic, 677, 684
 - tail drop, 684
 - tasks
 - configuration
 - CGMP, 598–602
 - IGMP snooping, 583–597
 - LAN, 574
 - PIM dense mode, 533–546
 - PIM sparse mode, 556–563
 - root guard, 295
 - STP, 264–272
 - EtherChannel, 225–238
 - trunk configuration, 204–213
 - VTP
 - configuration, 185–193
 - pruning configuration, 215–218
 - TCAM (ternary content addressable memory), 436
 - telephony service, IOS IP, 699–702
 - Telnet
 - access restriction, 622, 624
 - connections, 464
 - testing, 647
 - VLAN2 traffic, 828
 - telnet command, 60
 - ternary content addressable memory (TCAM), 436
 - testing
 - authorization, 647
 - BackboneFast, 322
 - cabling, 110
 - login authentication, 51
 - NTP, 107
 - PIM sparse mode, 560
 - ping connectivity, 364, 368
 - POM dense mode, 540
 - port LEDs, 112
 - PortFast BPDU Guard, 304
 - root guard, 297
 - router modules, 385
 - Telnet, 647
 - UplinkFast, 315
 - TFTP (Trivial File Transfer Protocol), 775, 785, 796
 - threshold maps, 719
 - time, configuring, 98–108
 - timeout
 - idle sessions configuration, 624
 - parameters, 614, 621
 - timers
 - MLS configuration, 458
 - spanning-tree, 249, 747
 - STP modification, 265
 - time-to-live (TTL), traceroute utility, 730
 - timing startup delays, 752–753
 - tools
 - 12trace utility, 737
 - IP, 726–742
 - CDP, 734

- Layer 2 traceroute, 737–742
 - ping utility, 727
 - traceroute, 729–733
 - LAN, 726–742
 - ping utility, 727
 - topologies
 - EtherChannel, 219
 - inter-VLAN routing, 376
 - Layer 3, 391
 - loop-free, 242–251
 - redundant LAN, 738
 - redundant multilayer, 390–421
 - ToS (type of service) fields, 676
 - traceroute mac commands, 740
 - traceroute mac ip command, 740
 - traceroute utility, 729–733, 737–742
 - tracert command, 416
 - tracert utility, 370
 - traffic
 - auto-negotiation, 171–172
 - capture, 800–806, 828
 - filtering, 610–611
 - multicast, 509
 - router-on-a-stick architecture, 340–341
 - tagged, 677, 684
 - trunking, 168–172
 - unicast, 509
 - verifying, 670
 - transferring files (TFTP), 775
 - transitions
 - PortFast, 298–305
 - STP states, 247
 - transparent bridging, 122–125, 133–139
 - transparent mode, VTP, 176
 - trees
 - PIM dense mode, 523–530
 - PIM sparse mode, 547–556
 - shared, 515, 548
 - source, 514
 - spanning trees, 242
 - SPT, 514, 547
 - troubleshooting
 - 12trace utility, 737
 - BackboneFast, 322
 - BPDU, 333
 - CDP, 734
 - connections, 108–119, 726–742
 - delays, 744–746
 - errDisable status, 755–765
 - Layer 2 connections, 116
 - PIM dense mode, 540
 - PIM sparse mode, 560
 - PortFast BPDU Guard, 304
 - root guard, 297
 - SPT, 553
 - STP, 250, 328–335
 - traceroute utility, 729–733, 737–742
 - UplinkFast, 315
 - workstations, 742–755
 - Trunk port (VLAN), 151
 - trunking, 167–172
 - DTP, 153, 379, 744
 - encapsulations, 169–171, 195
 - Layer 2
 - configuring, 845–849
 - infrastructure, 835
 - modes, 172, 199
 - negotiation, 171–172
 - pruning, 178
 - Switch-A, 378
 - switches, 194–213
 - verifying, 212, 380
 - VTP, 173–178, 360. *See also* VLAN; VTP
 - trunks
 - configuring, 619, 695
 - router-on-a-stick, 341
 - TTL (time-to-live), traceroute utility, 730
 - two-LAN internetworks, 127, 130
 - type of service (ToS) fields, 676
-
- ## U
-
- UDLD (Unidirectional Link Detection), 222, 756
 - Unicast Source Address (USA), 590
 - unicasting
 - configuring, 534
 - PIM dense mode, 522
 - traffic, 509
 - unidirectional links, 333
 - untagged traffic, 684
 - upgrading
 - Catalyst 6000/6500 switches, 479–497
 - operating system images, 775
 - operating systems, 786
 - UplinkFast, configuring, 307–317
 - USA (Unicast Source Address), 590
 - user-level authentication, enabling, 615
 - username command, 615
 - utilities. *See* tools
-
- ## V
-
- VACLs (VLAN access control lists), 799, 805, 825–829
 - values, portvlancost, 287
 - verification
 - AAA clients, 636
 - CEF, 476
 - connections, 501

- connectivity, 367–370, 389, 619
- egress queuing, 716
- EtherChannel configuration, 235–237
- IP
 - connectivity, 59
 - routing tables, 366
 - unicast routing, 534
- Layer 1 connections, 110
- Layer 2 connections, 114
- Layer 3 connections, 119
- load sharing (STP), 291–293
- MLS, 459
- multicast routers, 583
- native mode, 487
- operating system boot settings, 775
- PIM dense mode multicast routing, 538
- PIM sparse mode, 559
- PortFast, 302
- ports (EtherChannel), 230
- QoS policy, 708
- RSPAN, 822
- spanning tree states, 272
- STP, 328–335
- traffic, 670
- transparent bridging
 - CatOS, 134
 - Cisco IOS, 137–139
- trunking, 208, 212, 380
- UplinkFast, 313
- VLANs, 667
 - Switch-A, 154
 - Switch-B, 158
- VTP, 191
 - Switch-B, 148
 - pruning, 217
- video (multicast routing), 509–510
 - addressing, 510
 - forwarding, 516–518
 - IGMP, 512
 - IP, 513–515
 - LAN, 519–520, 570–576
- viewing
 - adjacency tables, 477
 - boot environment variables, 777
 - bridge IDs, 267
 - bridge tables (Switch-B), 135, 137
 - default Flash devices, 776
 - extended-range VLANs, 164
 - FIB, 476
 - ingress port queues, 687
 - PIM neighbors, 538
 - routing tables, 364
 - statistics (NetFlow), 504
 - Supervisor engines, 494
 - tables, 135
 - violation actions, 651
 - virtual default gateways, 351
 - virtual LANs. *See* VLANs
 - virtual management interface (sc0), 161
 - Virtual Router Redundancy Protocol (VRRP), 353
 - VLAN (virtual LANs), 129–131
 - access, 667
 - bridge IDs, 267
 - Catalyst switches
 - CatOS, 132
 - implementing, 131–132
 - CatOS, 152–154
 - Cisco IOS, 154–158
 - configuring, 148–160, 665
 - deleting, 159–160
 - extended-range, 162–165
 - GVRP, 173
 - hopping, 197
 - interfaces, 156
 - inter-VLAN routing. *See* inter-VLAN routing
 - IOS
 - interfaces, 133
 - verifying transparent bridging, 137–139
 - Layer 2
 - configuration, 849–857
 - infrastructure, 835–836
 - management, 160–162
 - native, 196
 - parameters, 151
 - ports assignment, 151
 - RSPAN, 817
 - Switch-A, 378
 - Switch-B, 379
 - verifying, 154, 667
 - voice prioritization, 703
 - VTP, 173–178
 - configuring, 187
 - pruning, 213–218
 - VLAN access control lists. *See* VACLs
 - vlan database command, 146
 - VLAN trunking protocol. *See* VTP
 - vlan vlan-id global configuration mode command, 155
 - voice prioritization, enabling, 703
 - VRRP (Virtual Router Redundancy Protocol), 353
 - VTP (VLAN Trunking Protocol), 173–178, 360
 - configuring, 139–148, 183–194, 456
 - pruning, 213–218
 - vtp global configuration command, 189
 - vtp pruning command, 215
 - vtp VLAN configuration command, 189
 - vulnerabilities, reducing, 609

W

Weighted Random Early Detection (WRED), 684
weighted round robin (WRR), 683, 685
WORKSTATION-PORTS macro, 84
workstations, troubleshooting, 742–755
WRED (Weighted Random Early Detection), 684, 715
WRR (weighted round robin), 683, 685

X-Z

XMODEM, 793
XOR (Exclusive OR), 181