

## Numerics

---

- 3DES (triple DES), 378
- 75-ohm coaxial cable, 54. *See also* cables

## A

---

- AAA (authentication, authorization, and accounting), 345–347
  - broadcast accounting, 357, 360
  - configuring, 348–360
  - ISDN callback with TACACS+, 366–370
- Access Control Server (ACS), 346
- access servers, 28
- access VPNs, 384
- access-list-number arguments, 127
- accounting
  - broadcast, 357, 360
  - configuring, 356
  - failed login, 359
  - full resource, 360
  - records, 359
  - resource failure stop, 359
  - TACACS+, 365–366
- accounting, 346. *See also* AAA
- ACLs (access control lists), configuring DDR with, 129–132
- ACS (Access Control Server), 346
- addresses
  - helper, 59
  - IP, 59
- NAT, 319–321
  - applying, 323–324
  - configuring, 321–329
  - dynamic, 336–341
  - order of operation, 322–323
  - overlapping, 335–336
  - overloading, 334
  - static, 333–334
  - TCP load distribution, 336
  - topologies, 330–333
- PPP, 99
  - private, 410–417
  - translating, 326–327
- ADSL (Asymmetric DSL), 7, 177
  - interference, 178–179
  - modulation, 178
  - overview of, 177–178
- AES (Advanced Encryption Standard), 378
- AH (authentication header), 375–377
- AHDLC (Asynchronous High-Level Data Link Control), 84
- algorithms
  - DES, 376
  - Diffie-helman, 376
  - SHA, 376
- analog connections, 6
- anti-replay, 375
- applying NAT, 323–324
- ARAP (AppleTalk Remote Access Protocol), 34, 351
- architecture
  - DSL, 186–194
  - IPSec, 375–376
    - 3DES, 378
    - AES, 378
    - AH, 377

- DES, 378
- ESP, 377
- IKE, 378–380
  - transform sets, 381–382
  - transport mode, 380
  - tunnel mode, 381
- arguments, methods, 349
- assignment
  - custom queues to interfaces, 305
  - dialer lists, 127
  - priority lists to interfaces, 302
- Asymmetric DSL. *See* ADSL
- asynchronous callbacks, configuring, 102
- asynchronous calls, configuring, 166–169
- asynchronous communications, 16–17
- asynchronous group interfaces, configuring, 167
- Asynchronous High-Level Data Link Control (AHDLC), 84
- asynchronous interfaces, 99
- asynchronous lines, 37–40
- asynchronous links, 98–102
- AT command, 30
- attribute-value (AV) pairs, 346
- authentication. *See also* AAA
  - ARAP, 351
  - CHAP, 88
  - LCP, 86
  - method lists, 348
  - NASI, 351
  - PAP, 87
  - PPP, 102
    - configuring, 350
    - ISDN, 130
    - unidirectional, 137
  - RADIUS, 362
  - TACACS+, 361

- authentication header (AH), 375–377
- authorization. *See also* AAA
  - disabling, 355
  - reverse-Telnet, 355
  - TACACS+, 363–365
  - types of, 353
- autoconfiguration of modems, 33–37. *See also* configuration
- autosensing, enabling, 98
- AUX (auxiliary port), 28
- AV (attribute-value) pairs, 346
- avoidance, congestion, 389

---

## B

- backup
  - dial
    - load sharing, 273–280
    - primary line failures, 268–273
  - dialer profiles, 280–286
  - interfaces, 139–146, 263–267
  - primary links, 286–291
- bandwidth. *See also* connections
  - ISDN, 116–118
  - management, 388
  - WFQ, 294–295
- BAP (Bandwidth Allocation Protocol), 93
- Basic Rate Interface (BRI), 5, 142–146
- binding dialer profiles, 153–154
- bit rates, 182

- branch offices, 3
  - analog connections, 6
  - cable modems, 8
  - DSL, 6–8
  - Frame Relay, 4
  - ISDN, 4–6
  - serial links, 4
- BRI (Basic Rate Interface), 5, 142–146
- Bridge Group Virtual Interface (BVI), 187
- bridging, configuring, 64–68
- broadcast accounting, configuring, 360
- building labs
  - asynchronous communication, 16–17
  - LANs, 12
  - WANs, 13–16
- bundling MPPP, 92
- BVI (Bridge Group Virtual Interface), 187

## C

- CA (certification authority), 376
- cables. *See also* connections
  - modems, 8, 53–54
    - bridging/routing configuration, 64–68
    - Cisco CMTS configuration, 57–64
    - DOCSIS hardware, 55–56
    - downstream/upstream, 54
    - modulation, 55
    - spectrums, 55
    - troubleshooting, 68–77
  - RJ-45, 22
- call setup, ISDN, 122–123

- callback
  - asynchronous, 102
  - ISDN/TACACS+, 366–370
  - PPP, 89
- caller identification, 137
- CAP (Carrier Amplitude and Phase), 178
- CAR (Committed Access Rate), 390
- Carrier Detect (CD), 29
- Carrierless Amplitude and Phase (CAP), 178
- carrier-to-noise ratio (CNR), 60
- CCM (Cisco CallManager), 329
- CCP (Compression Control Protocol), 90
- CD (Carrier Detect), 29
- CDSL (Consumer DSL), 7
- central offices
  - analog connections, 6
  - DSL, 6–8
  - Frame Relay, 4
  - ISDN, 4–6
  - serial links, 4
- central-site modems, configuring, 40–45
- certification authority (CA), 376
- channels
  - bandwidth, 61
  - ISDN, 116–118
- CHAP (Challenge Handshake Authentication Protocol), 87
- chat scripts, configuring, 32
- chat-script command, 32
- check bytes, 183
- Cisco 6160 DSLAM system, 179–184
- Cisco 6400 UAC, 184–186
- Cisco CallManager (CCM), 329
- Cisco CMTS, configuring, 57–64

Cisco VPN 3000 client, 434–437. *See also* VPNs

class-based WFQ, 388

classification of packets, 387–388

clearing IKE connections, 386

clients

    Cisco VPN 3000, 384, 434–437

    NAT/preshared keys, 425–430

    VPNs, 425–430

clock rate command, 13

CNR (carrier-to-noise ratio), 60

commands

    AT, 30

    cable modems, 68–77

    chat-script, 32

    clock rate, 13

    custom queuing, 303

    dialer, 104

    global configuration, 355

    ISDN, 123–129

    line, 29

    modem autoconfigure, 34

    priority queuing, 301

    show controller, 13

    show line, 29

    show modemcap, 35

    telnet, 27

    transport input, 27

    variance, 267

Committed Access Rate (CAR), 390

communication. *See also* connections

    between DTE devices, 20

    DCE-to-DCE, 20–21

components

    Cisco 6160 DSLAM system, 179–184

    Cisco 6400 UAC, 184–186

    dialer profiles, 152–153

    ISDN, 115–116

    compression, 24–26, 305

        link, 307

        PPP, 90

        ratios, 25

    Compression Control Protocol (CCP), 90

    CON (console port), 28

    confidentiality, 375

    configuration

        AAA, 345–360, 366–370

        accounting, 356, 365–366

        asynchronous groups, 167

        asynchronous interfaces, 99

        asynchronous lines, 37–40

        authentication

            ARAP, 351

            RADIUS, 362

            TACACS+, 361

        authorization

            TACACS+, 363–365

            types of, 353

        backup dialer profiles, 280–286

        bridging, 64–68

        broadcast accounting, 360

        central-site modems, 40–45

        channels, 61

        chat scripts, 32

        Cisco 6160 DSLAM system, 179–184

        Cisco 6400 UAC, 184–186

        clockrates, 13

        compression, 305–307

        dialers

            profiles, 155–162, 169–173

            rotary groups, 156, 162–165

        dynamic translation, 325

        firewalls, 430–433

        frequencies, 57

- interfaces
  - downstream, 63
  - modems, 29
- internal modem lines, 168
- IPSec router-to-router, 395–398
- IRB over DSL, 194–196
- ISDN, 123–129
  - call setup and teardown, 122–123
  - DDR, 129–132
  - identification, 136–137
  - interfaces, 139
  - PRI, 132–136
  - routing, 138–139
- LANs, 12
- line types, 28
- local interface addressing, 99
- modemcap database, 35
- modems
  - autoconfiguration, 33–37
  - DCE, 26–33
- NASI, 351
- NAT, 319–321
  - applying, 323–324
  - dynamic, 336–341
  - order of operation, 322–323
  - overlapping, 335–336
  - overloading, 334
  - routers, 321–329
  - static, 333–334
  - TCP load distribution, 336
  - topologies, 330–333
- PIX firewalls, 430–437
- PPP, 94–96
  - asynchronous links, 98–102
  - enabling DDR, 104–110
  - initializing access servers, 97–98
  - interfaces, 102–104
  - PPPoA over DSL, 198–201, 204–217
  - PPPoE over DSL, 201–204
  - PRI, 166–169
  - priority queuing, 307–316
  - QoS for VPN support, 392
  - queuing
    - custom, 303–305, 310–313
    - priority, 300–302
    - WFQ, 298–300
  - RBE over DSL, 196–198
  - reverse-Telnet, 27, 355
  - RFC 1483 bridging over DSL,
    - 217–222
  - routing, 64–68
  - serial interfaces, 37–40
  - spectrum management, 62
  - SPIDs, 130
  - static routes, 165
  - static translation, 324
  - upstream input power level, 59
  - WANs, 13–16
- congestion. *See also* troubleshooting
  - avoidance, 389
  - queuing, 294
    - custom queuing, 297–298
    - priority queuing, 295–296, 307–316
    - WFQ, 294–295
- connections
  - ADSL modulation, 178
  - analog, 6
  - cables
    - bridging/routing configuration, 64–68
    - Cisco CMTS configuration, 57–64

- DOCSIS, 55–56
- downstream/upstream, 54
- modems, 8, 53–54
- modulation, 55
- spectrums, 55
- troubleshooting, 68–77
- DCE
  - configuring modems, 26–33
  - modem autoconfiguration, 33–37
- DSL, 6–8
  - ADSL overview, 177–178
  - interference, 178–179
  - IRB over, 194–196
  - PPPoA over, 198–201, 204–217
  - PPPoE over, 201–204
  - RBE over, 196–198
  - RFC 1483 bridging over, 217–222
- DTE-to-DCE wiring, 23–24
- DTE-to-DTE wiring, 22–23
- forward/reverse, 26
- Frame Relay, 4, 13–16
- IKE, 386
- ISDN, 4–6, 115–116
  - bandwidth/channels, 116–118
  - BRI, 118–119, 142–146
  - call setup and teardown, 122–123
  - configuring, 123–129
  - DDR, 119–120, 129–132
  - dialing out with, 140–142
  - identification, 136–137
  - interfaces, 139
  - Layer 1, 121
  - Layer 2, 121
  - Layer 3, 122
  - layers, 120
  - PRI, 132–136
  - routing, 138–139
  - modems, 19–21
  - point-to-multipoint, 4
  - PPP, 83
    - asynchronous links, 98–102
    - configuring, 94–96
    - enabling DDR, 104–110
    - frames, 84, 94
    - initializing access servers, 97–98
    - interfaces, 102–104
    - LCP, 86–94
    - negotiation phases, 84–86
  - reverse Telnets, 41
  - serial links, 4
  - Telnet, 27. *See also* Telnet
- connectors, RJ-45, 22
- Consumer DSL (CDSL), 7
- control
  - errors, 24–26
  - modem functions, 21
- corporate users, 3
- CPU utilization, IPSec, 385
- CQ (custom queuing), 297–298, 303–313, 390–391
- customization
  - AAA, 345–360, 366–370
  - accounting, 356, 365–366
  - asynchronous groups, 167
  - asynchronous interfaces, 99
  - asynchronous lines, 37–40
  - authentication
    - ARAP, 351
    - RADIUS, 362
    - TACACS+, 361
  - authorization
    - TACACS+, 363–365
  - types of, 353

- backup dialer profiles, 280–286
- bridging, 64–68
- broadcast accounting, 360
- central-site modems, 40–45
- channels, 61
- chat scripts, 32
- Cisco 6160 DSLAM system, 179–184
- Cisco 6400 UAC, 184–186
- clockrates, 13
- compression, 305–307
- dialers
  - profiles, 155–162, 169–173
  - rotary groups, 156, 162–165
- dynamic translation, 325
- firewalls, 430–433
- frequencies, 57
- interfaces
  - downstream, 63
  - modems, 29
- internal modem lines, 168
- IPSec router-to-router, 395–398
- IRB over DSL, 194–196
- ISDN, 123–129
  - call setup and teardown, 122–123
  - DDR, 129–132
  - identification, 136–137
  - interfaces, 139
  - PRI, 132–136
  - routing, 138–139
- LANs, 12
- line types, 28
- local interface addressing, 99
- modemcap database, 35
- modems
  - autoconfiguration, 33–37
  - DCE, 26–33
- NASI, 351
- NAT, 319–321
  - applying, 323–324
  - dynamic, 336–341
  - order of operation, 322–323
  - overlapping, 335–336
  - overloading, 334
  - routers, 321–329
  - static, 333–334
  - TCP load distribution, 336
  - topologies, 330–333
- PIX firewalls, 430–437
- PPP, 94–96
  - asynchronous links, 98–102
  - enabling DDR, 104–110
  - initializing access servers, 97–98
  - interfaces, 102–104
- PPPoA over DSL, 198–201, 204–217
- PPPoE over DSL, 201–204
- PRI, 166–169
- priority queuing, 307–316
- QoS for VPN support, 392
- queuing
  - custom, 303–305, 310–313
  - priority, 300–302
  - WFQ, 298–300
- RBE over DSL, 196–198
- reverse-Telnet, 27, 355
- RFC 1483 bridging over DSL,
  - 217–222
- routing, 64–68
- serial interfaces, 37–40
- spectrum management, 62
- SPIDs, 130
- static routes, 165
- static translation, 324
- upstream input power level, 59
- WANs, 13–16

**D**

- data communications equipment, 13. *See* DCE
- data compression, 24–26
- Data Encryption Standard (DES), 376–378
- Data Link Connection Identifier (DLCI), 4
- Data Over Cable Service Interface Specifications (DOCSIS), 53, 65
- data terminal equipment, 13. *See* DTE
- databases, configuring, 35
- DC (Demand Circuit), 138
- DCE (data communications equipment)
  - DTE-to-DCE wiring, 23–24
  - modems
    - autoconfiguration, 33–37
    - configuring, 26–33
- DDR (dial-on-demand routing)
  - dialer profiles, 151–152
    - binding, 153–154
    - components, 152–153
    - configuring, 155, 157–162, 169–173
    - limitations, 154–155
  - dialer rotary groups, 155–156, 162–165
  - ISDN, 119–120, 129–132
  - PPP, 104–110
  - triggering, 169
- debugging. *See also* troubleshooting
  - PPP, 107
- dedicated PPP sessions, configuring, 104
- defining
  - custom queue lists, 303
  - IKE parameters, 393–394
  - interesting traffic, 163
  - interesting traffic patterns, 105
  - IPSec transform sets, 394
  - method lists for authentication, 348
  - passive interfaces, 165
  - priority lists, 301
- Demand Circuit (DC), 138
- deployment of NAT, 329
- DES (Data Encryption Standard), 376–378
- devices
  - AAA, 348–360
  - DCE, 23–24
  - DTE, 22–23
  - modem connections, 19–21
- D-H (Diffie-Hellman) algorithm, 376
- dial in/dial out, 110
- dial number identification service (DNIS), 360
- dialer commands, 104
- dialer lists, assigning, 127
- dialer maps, configuring, 126
- dialer pool interfaces
  - backup, 263
  - triggering, 264–267
- dialer profiles, 151–152
  - backup, 280–286
  - binding, 153–154
  - components, 152–153
  - configuring, 155–162, 169–173
  - limitations, 154–155
- dialer rotary groups, 155–156, 162–165
- dialer-group-numbers, 127
- dialing in, dialer profile sequences, 153
- dialing out
  - dialer profile binding sequences, 153
  - with ISDN, 140–142
- dial-on-demand routing. *See* DDR
- differentiating forward/reverse connections, 26
- Diffie-Hellman (D-H) algorithm, 376
- Diffserv (DS), 390



digital modulation, 55

Digital Subscriber Line. *See* DSL

disabling
 

- AAA, 348
- authorization, 355

distribution, TCP load, 327–328

DLCI (Data Link Connection Identifier), 4

DMT2 (Discreet MultiTone 2 - Issue 2), 178

DNA (DoNotAge) bit, 138

DNIS (dialed number identification service), 360

DOCSIS (Data Over Cable Service Interface Specifications), 53, 65

downstream, 54
 

- ADSL, 178
- interfaces, 63

DS (DiffServ), 390

DSL (digital subscriber line), 6–8, 177
 

- ADSL
  - modulation, 178
  - overview of, 177–178
- architectures, 186–194
- interference, 178–179
- IRB, 194–196
- PPPoA, 198–201, 204–217
- PPPoE, 201–204
- profiles, 181
- protocols, 186–194
- RBE, 196–198
- RFC 1483 bridging, 217–222

DSLAM (DSL Access Multiplexer), 177–184

DTE (data terminal equipment), 13. *See also* connections
 

- DTE-to-DCE wiring, 23–24
- DTE-to-DTE wiring, 22–23

dynamic NAT, 320, 336–341

dynamic translation, 324–325

## E

EIA/TIA-232 serial interface (COM port), 25

EIGRP (Enhanced IGRP), load backup feature, 267

enabling
 

- AAA, 348
- autosensing, 98
- backup for primary links, 286–291
- DDR, 104–110
- encapsulation, 99
- full resource accounting, 360
- password protection, 352
- ports, 58
- resource failure stop accounting, 359

Encapsulating Security Payload (ESP), 375–377

encapsulation, enabling PPP, 99

encryption
 

- AES, 378
- DES, 376
- IPSec/GRE with NAT, 417–425
- packets, 347

error control, 24–26. *See also* troubleshooting

ESF (Extended Super-Frame), 118

ESP (Encapsulating Security Payload), 375, 377

EXEC-stop records, 359

extranet VPNs, 384

## F

failed login, generating accounting records for, 359

fields, PPP frames, 94

firewalls
 

- Cisco PIX 500 series, 383
- configuring, 430–433

flags, PPP, 98

- floating static routes, 138, 266
- flow-based WFQ, 388
- formatting frames (PPP), 94
- forward connections, 26
- forward path, 54
- Frame Relay, 4, 13–16
- Frame Relay Traffic Shaping (FRTS), 392
- frames
  - ESF, 118
  - PPP, 84, 94
  - SF, 118
- frequencies, configuring, 57
- FRTS (Frame Relay Traffic Shaping), 392
- full resource accounting, enabling, 360
- functional groups
  - BRI, 118
  - reference points, 119
- functionality, disabling AAA, 348
- functions, 21. *See also* commands

## G

---

- generation of interim accounting records, 359
- global configuration commands, 355
- GRE (Generic Routing Encapsulation), 417–425
- groups
  - BRI functional, 118
  - dialer rotary, 155–156, 162–165
- GTS (Generic Traffic Shaping), 389

## H

---

- hardware
  - Cisco 6160 DSLAM system, 179
  - DOCSIS, 55–56
- HDC (Hybrid Fiber Coax), 54
- HDSL (High Bit rate DSL), 7
- helper addresses, Cisco CMTS configuration, 59
- hosts, naming, 130
- hubs, IPSec router-to-router hub and spoke, 404–410

## I-K

---

- ICMP (Internet Control Message Protocol), 109
- IDB (interface description block), 155
- identification, configuring, 136–137
- idle timers, configuring, 126
- IDSL (ISDN DSL), 7
- IGRP (Interior gateway Routing Protocol), 267
- IKE (Internet Key Exchange), 376–380
  - parameters, 393–394
  - troubleshooting, 386
- Integrated Services Digital Network DSL (IDSL), 7
- initializing cable modems, 73
- input
  - login, 352
  - power level configuration, 59
- inside global addresses, 321, 325
- inside local addresses, 321
- inside source addresses, 324–325
- Integrated Routing and Bridging, 177, 194–196
- Integrated Services Digital Network. *See* ISDN
- integrity, 375
- interactive PPP sessions, configuring, 104

- interesting traffic
  - DDR, 119
  - defining, 163
  - ISDN, 127
  - parameters, 105
- interface description block (IDB), 155
- interfaces
  - asynchronous
    - configuring, 99
    - groups, 167
  - backup, 263–267
  - BVI, 187
  - Cisco 6160 DSLAM system, 180
  - clockrates, 13
  - custom queues, 297–298
    - assigning to, 305
    - configuring, 303–313
  - dialer, 152
    - configuring, 158
    - creating, 168
    - formatting rotary groups, 163
  - downstream, 63
  - ISDN, 123–129, 139
  - method lists, 352
  - modems, 29
  - NASI, 351
  - passive, 165
  - PPP, 102–104
  - PRI
    - calls, 166–169
    - configuring, 132–136
  - priority lists, 302
  - priority queuing, 295–302
  - serial, 37–40
  - WFQ, 298–300
- interference ADSL, 178–179
- interim accounting records, generating, 359
- interleaving delay parameter, Cisco 6160 DSLAM system, 183
- internal modem lines, configuring, 168
- Internet Key Exchange (IKE), 376–380
  - parameters, 393–394
  - troubleshooting, 386
- Internet Protocol Security. *See* IPSec
- Internet Security Association and Key Management Protocol (ISAKMP), 376
- IP (Internet Protocol) addresses, 59
- IP PHONE, deploying NAT, 329
- IPSec (Internet Protocol Security). *See also* security
  - 3DES, 378
  - AES, 378
  - AH, 377
  - architecture, 375–376
  - CPU utilization, 385
  - DES, 378
  - ESP, 377
  - GRE with NAT, 417–425
  - IKE, 378–380
  - L2TP over, 439–443
  - maintenance, 385–386
  - memory, 385
  - monitoring, 385–386
  - private addresses, 410–417
  - router-to-router
    - configuration, 395–398
    - hub and spoke, 404–410
  - three full-mesh routers, 398–404
  - transform sets, 381–382, 394
  - transport mode, 380
  - tunnel mode, 381VPNs, 384

IRB (Integrated Routing and Bridging), 177, 194–196

ISAKMP (Internet Security Association and Key Management Protocol), 376

ISDN (Integrated Services Digital Network), 4–6, 115–116

- bandwidth/channels, 116–118
- BRI, 142–146
  - functional groups, 118
  - reference points, 119
- call setup and teardown, 122–123
- callback, 366–370
- configuring, 123–129
- DDR, 119–120, 129–132
- dialing out with, 140–142
- identification, 136–137
- interfaces, 139
- layers, 120
  - Layer 1, 121
  - Layer 2, 121
  - Layer 3, 122
- PRI, 132–136, 166–169
- routing, 138–139

- Layer 2, ISDN, 121
- Layer 2 Tunneling Protocol (L2TP) over IPsec, 439–443
- Layer 3 ISDN, 122
- LCP (Link Control Protocol), 86–94
- legacy DDR, advantages of dialer profiles over, 151
- limitations of dialer profiles, 154–155
- lines
  - applying method lists to, 352
  - cards, 181
  - command, 29
  - types, 29
- link compression, 306–307
- Link Control Protocol (LCP), 86–94
- list-names, 349
- lists
  - custom queues, 303
  - methods
    - AAA, 347. *See also* AAA
    - applying to interfaces/lines, 352
    - defining, 348
    - priority, 301
- load backup features, routing, 266
- load distribution, 327–328, 336
- load sharing, configuring dial backup, 273–280
- local area networks (LANs), creating, 12
- local interface addressing, configuring, 99
- login
  - authentication, 349
  - accounting records, 359
  - input, 352

---

## L

L2TP (Layer 2 Tunneling Protocol) over IPsec, 439–443

labs
 

- asynchronous communication, 16–17
- LANs, 12
- WANs, 13–16

LANs (local area networks), creating, 12

Layer 1, ISDN, 121

## M

---

MAC (Media Access Control), 4

maintenance. *See also* troubleshooting

- IPSec, 385–386
- NAT, 329
- QoS for VPNs, 393

management

- bandwidth, 388
- spectrums, 62

maps

- classes, 152, 160
- dialer, 126

margins, Cisco 6160 DSLAM system, 182

MD5 (Message Digest 5), 376

Media Access Control (MAC), 4

memory, IPSec, 385

method lists

- AAA, 347. *See also* AAA
- arguments, 349
- defining, 348
- interfaces/lines, 352

modem autoconfigure command, 34

modemcap database, configuring, 35

modems. *See also* connections

- AT commands, 30
- AUX port for EXEC dial-in connectivity, 45
- cable, 53–54
  - bridging/routing configuration, 64–68
  - Cisco CMTS configuration, 57–64
  - DOCSIS hardware, 55–56
  - downstream/upstream, 54
  - modulation, 55
  - spectrums, 55
  - troubleshooting, 68–77

- central-site, 40–45
- compression, 24–26
- connections, 19–21
- DCE
  - autoconfiguration, 33–37
  - configuring, 26–33
- error control, 24–26
- internal lines, 168
- modulation standards, 24
- nonstandard commands, 31
- speed, 25

modifying translation timeouts, 328

modulation, 55

- ADSL, 178
- QAM, 55
- standards, 24

modules

- AAA, 345–347
- configuring, 348–360

monitoring, 385–386

- IPSec, 385–386
- NAT, 329
- QoS VPN, 393

MPPC (Microsoft Point-to-Point Compression), 306

MPPP (Multilink PPP), 91. *See also* PPP

multiple routers, IPSec, 410–417

## N

---

named method lists

- accounting, 357
- authorization, 354

naming hosts, 130

NASI (NetWare Asynchronous Services Interface), 351

NAT (Network Address Translation), 319–321

- applying, 323–324
- configuring, 321–329
- dynamic, 336–341
- IPSec with GRE, 417–425
- maintenance, 329
- monitoring, 329
- order of operation, 322–323
- overlapping, 335–336
- overloading, 334
- static, 333–334
- TCP load distribution, 336
- topologies, 330–333

negotiation phases, PPP, 84–86

NetWare Asynchronous Services Interface (NASI), 351

Network Address Translation. *See* NAT

NETWORK records, 359

networks

- AAA, 348–360
- IPSec, 375
  - 3DES, 378
  - AES, 378
  - AH, 377
  - architecture, 375–376
  - DES, 378
  - ESP, 377
  - IKE, 378–380
  - transform sets, 381–382
  - transport mode, 380
  - tunnel mode, 381
- LANs, 12
- VPNs, 382
- WANs, 13–16

nonstandard modem commands, 31

NULL, suppressing, 359

numbering interfaces, 180

---

## O

---

O4, 349–350

optimization

- AAA, 345–360, 366–370
- accounting, 356, 365–366
- asynchronous groups, 167
- asynchronous interfaces, 99
- asynchronous lines, 37–40
- authentication
  - ARAP, 351
  - RADIUS, 362
  - TACACS+, 361
- authorization
  - TACACS+, 363–365
  - types of, 353
- backup dialer profiles, 280–286
- bridging, 64–68
- broadcast accounting, 360
- central-site modems, 40–45
- channels, 61
- chat scripts, 32
- Cisco 6160 DSLAM system, 179–184
- Cisco 6400 UAC, 184–186
- clockrates, 13
- compression, 305–307
- dialers
  - profiles, 155–162, 169–173
  - rotary groups, 156, 162–165
- dynamic translation, 325
- firewalls, 430–433

- frequencies, 57
  - interfaces
    - downstream, 63
    - modems, 29
  - internal modem lines, 168
  - IPSec router-to-router, 395–398
  - IRB over DSL, 194–196
  - ISDN, 123–129
    - call setup and teardown, 122–123
    - DDR, 129–132
    - identification, 136–137
    - interfaces, 139
    - PRI, 132–136
    - routing, 138–139
  - LANs, 12
  - line types, 28
  - links, 307
  - local interface addressing, 99
  - modemcap database, 35
  - modems
    - autoconfiguration, 33–37
    - DCE, 26–33
  - NASI, 351
  - NAT, 319–321
    - applying, 323–324
    - dynamic, 336–341
    - order of operation, 322–323
    - overlapping, 335–336
    - overloading, 334
    - routers, 321–329
    - static, 333–334
    - TCP load distribution, 336
    - topologies, 330–333
  - PIX firewalls, 430–437
  - PPP, 94–96
    - asynchronous links, 98–102
    - enabling DDR, 104–110
    - initializing access servers, 97–98
    - interfaces, 102–104
  - PPPoA over DSL, 198–201, 204–217
  - PPPoE over DSL, 201–204
  - PRI, 166–169
  - priority queuing, 307–316
  - QoS for VPN support, 392
  - queuing
    - custom, 303–305, 310–313
    - priority, 300–302
    - WFQ, 298–300
  - RBE over DSL, 196–198
  - reverse-Telnet, 27, 355
  - RFC 1483 bridging over DSL,
    - 217–222
  - routing, 64–68
  - serial interfaces, 37–40
  - spectrum management, 62
  - SPIDs, 130
  - static routes, 165
  - static translation, 324
  - traffic, 293–294
  - upstream input power level, 59
  - WANs, 13–16
- origin authentication, 375
  - OSPF (Open Shortest Path First)
    - Demand Circuit, 138
    - load backup feature, 266
  - outside global addresses, 321
  - outside local addresses, 321
  - outside source lists, dynamic NAT, 336–341

## overlapping

- addresses, 326–327
- NAT, 335–336

## overloading

- inside global addresses, 325
- NAT, 334

---

**P**

---

## packets

- classification, 387–388
- encryption, 347
- NAT, 321

## PAP (Password Authentication Protocol), 87

## parameters

- IKE, 393–394
- interfaces, 102–104
- security protocols, 348

## passive interfaces, 165

## passwords, enabling protection, 352

payload compression, 306. *See also* compression

## physical interfaces

- backup, 263–267
- dialer profiles, 153, 161
- dialer rotary groups, 165

## PIX firewalls

- Cisco VPN 3000 clients, 434–437
- configuring, 430–433

## platforms, Cisco VPN 3000 series concentrators, 383–384

## point-to-multipoint connections, 4

Point-to-Point Protocol. *See* PPPPoint-to-Point Protocol over ATM. *See* PPPoAPoint-to-Point Protocol over Ethernet. *See* PPPoE

## policers, traffic, 389

## pools, dialer, 152

## ports, enabling upstream, 58

## PPP (Point-to-Point Protocol), 83

- AAA, 350
- authentication, 102
  - ISDN, 130
  - unidirectional, 137
- configuring, 94–96
  - asynchronous links, 98–102
  - enabling DDR, 104–110
  - initializing access servers, 97–98
  - interfaces, 102–104
- frames, 84, 94
- LCP, 86–94
- negotiation phases, 84–86
- troubleshooting, 95, 107
- verification, 95, 106

## PPPoA (Point-to-Point Protocol over ATM), 177

- DSL, 190
- configuring over, 198–201, 204–217

## PPPoE (Point-to-Point Protocol over Ethernet), 177, 192, 201–204

## PQ (priority queuing), 295–302, 391

## preshared keys

- NAT, 425–430
- VPNs, 430–433

## preventing routing updates, 169

## PRI (Primary Rate Interface), 5

- asynchronous calls/ISDN calls, 166–169
- ISDN, 132–136

## primary line failures, configuring dial backup, 268–273

## primary links, enabling, 286–291

## prioritizing traffic, 293–294



- private addresses, IPSec, 410–417
- privileged levels, enabling passwords, 352
- profiles
  - dialer
    - binding, 153–154
    - components, 152–153
    - configuring, 155–162, 169–173
    - DDR, 151–152
    - limitations, 154–155
  - DSL, 181
- protection, enabling passwords, 352
- protocols
  - AAA, 346
  - ARAP, 351
  - BAP, 93
  - CCP, 90
  - CHAP, 87–88
  - DSL, 186–194
  - IDSN layers, 120
    - Layer 1, 121
    - Layer 2, 121
    - Layer 3, 122
  - IKE, 376
  - IPSec, 375
    - 3DES, 378
    - AES, 378
    - AH, 377
    - architecture, 375–376
    - DES, 378
    - ESP, 377
    - IKE, 378–380
    - transform sets, 381–382
    - transport mode, 380
    - tunnel mode, 381
  - ISAKMP, 376
  - PAP, 87

- PPP, 83
  - asynchronous links, 98–102
  - configuring, 94–96
  - enabling DDR, 104–110
  - frames, 94
  - framing, 84
  - initializing access servers, 97–98
  - interfaces, 102–104
  - LCP, 86–94
  - negotiation phases, 84–86
  - security parameters, 348
- SLIP, 84
- WFQ, 294–295

## Q

---

- QAM (Quadrature Amplitude Modulation), 55
- QoS (Quality of Service)
  - VPNs, 387
    - bandwidth management, 388
  - CAR, 390
  - configuring, 392
  - congestion avoidance, 389
  - CQ, 390–391
  - DS, 390
  - FRTS, 392
  - monitoring, 393
  - packet classification, 387–388
  - PQ, 391
  - traffic shaping, 388–389
  - tunnels, 389
- QPSK (Quadrature Phase Shift Keying), 55

queuing, 297–298  
  CQ, 390–391  
  custom, 303–313  
  operations, 294  
    custom queuing, 297–298  
    priority queuing, 295–296, 307–316  
  PQ, 391  
  priority, 300–302  
  WFQ, 388  
    configuring, 298–300  
    operations, 294

## R

---

RADIUS (Remote Authentication Dial-in User Service), 362. *See also* AAA  
RADSL (Rate-Adaptive DSL), 7  
ratios, compression, 25  
RBE (Routed Bridge Encapsulation), 177, 188, 196–198  
records  
  accounting  
    generating interim, 359  
    suppressing, 359  
  EXEC-stop, 359  
  NETWORK, 359  
  start-stop, 360  
reference points, ISDN BRI, 119  
remote office/branch office (ROBO), 5  
reports, accounting, 356. *See also* AAA  
resource failure stop accounting, enabling, 359  
return paths, 54  
reverse connections, 26  
reverse paths, 54  
reverse Telnet connections, 41  
  authorization, 355  
  configuring, 27  
RFC 1483 bridging, 186, 217–222  
RJ-45 connectors, 22  
ROBO (remote office/branch office), 5  
Routed Bridge Encapsulation. *See* RBE  
routers. *See also* connections  
  AAA, 345–347  
  asynchronous interfaces, 99  
  back-to-back connections through AUX ports, 47  
  configuring, 348–360  
  dial in/dial out, 110  
  interfaces, 37–40  
  ISDN  
    configuring, 123–129, 138–139  
    DDR, 129–132  
    identification, 136–137  
    interfaces, 139  
    PRI, 132–136  
  NAT  
    applying, 323–324  
    configuring, 321–329  
    dynamic, 336–341  
    order of operation, 322–323  
    overlapping, 335–336  
    overloading, 334  
    static, 333–334  
    TCP load distribution, 336  
    topologies, 330–333  
  three full-mesh IPSec, 398–404  
  VPNs, 383, 425–430  
  WANs, 13–16

router-to-router configuration

IPSec, 395–398

hub and spoke, 404–410

routes

floating static as backups, 266

static, 165

routing

configuring, 64–68

ISDN, 138–139

load backup, 266

updating, 169

RSA signatures, 376

## S

SAs (Security Associations), IPSec, 385–386

scripts, configuring chat, 32

SDSL (Symmetric DSL), 7, 177

Secure Hash Algorithm (SHA), 376

security

AAA, 345–347

configuring, 348–360

firewalls (Cisco PIX 500 series), 383

IPSec, 375

3DES, 378

AES, 378

AH, 377

architecture, 375–376

DES, 378

ESP, 377

IKE, 378–380

transform sets, 381–382

transport mode, 380

tunnel mode, 381

protocols, 348

sequences, binding dialer profiles, 153–154

serial interfaces, configuring, 37–40

Serial Line Internet Protocol (SLIP), 84

serial links, 4

servers

access, 28

ACS, 346

NAT, 319–321

applying, 323–324

configuring, 321–329

dynamic, 336–341

order of operation, 322–323

overloading, 334–336

static, 333–334

TCP load distribution, 336

topologies, 330–333

RADIUS, 362

TACACS+

accounting, 365–366

authentication, 361

authorization, 363–365

ISDN callback, 366–370

services, configuring AAA, 348–360

sessions

accounting records, 359

PPP, 104

reverse-Telnet, 27, 41, 355

SF (Super-Frame), 118

SHA (Secure Hash Algorithm), 376

shaping traffic, 388–389, 392

sharing spectrums, 55

show controller command, 13

show line command, 29

show modemcap command, 35

signals, CD, 29

- site-to-site VPNs, 384
- SLIP (Serial Line Internet Protocol), 84
- SNR (signal-to-noise) ratio, 182
- SOHO (small office/home office), 5
- sp autoconfiguration, 36
- spectrums
  - configuring, 62
  - sharing, 55
- speed, modems, 25
- SPIDs (Service Profile Identifiers), 130
- spokes, 404–410
- standards, modem modulation, 24
- start-stop records, 360
- static NAT, 333–334. *See also* NAT
- static routes, configuring, 165
- static translation, 324
- Super-Frame (SF), 118
- suppressing accounting records, 359
- switches
  - AAA, 345–347, 348–360
  - types, 124
  - VPNs, 383
- Symmetric DSL. *See* SDSL
- system components, Cisco 6160 DSLAM system, 179

## T

---

- TACACS+
  - accounting, 365–366
  - authentication, 361
  - authorization, 363–365
  - ISDN callback, 366–370
- TCP (Transmission Control Protocol)
  - headers, 306
  - load distribution, 327–328
  - NAT, 336
- TDM (time-division multiplexing), 55
- TDMA (time-division multiple access), 55
- teardown, ISDN, 122–123
- technologies, 3
  - analog connections, 6
  - cable modems, 8
  - DSL, 6–8
  - Frame Relay, 4
  - ISDN, 4–6
  - serial links, 4
- telecommuters, 3
- Telnet, reverse connections, 41
  - authorization, 355
  - configuring, 27
- telnet command, 27
- testing ICMP, 109
- three full-mesh IPSec routers, 398–404
- time-division multiple access (TDMA), 55
- time-division multiplexing (TDM), 55
- timeouts, modifying, 328
- timers, configuring idle ISDN, 126
- topologies, NAT, 330–333
- tracking AAA, 356
- traffic
  - custom queuing, 297–298
  - DDR, 119
  - interesting
    - defining, 163
    - ISDN, 127
  - interesting patterns, 105
  - policers, 389

- prioritizing, 293–294
- priority queuing, 295–296
- shaping, 388–392
- WFQ, 294–295
- training modes, Cisco 6160 DSLAM
  - system, 184
- transform sets, 381–382, 394
- translation
  - addresses, 326–327
  - NAT. *See* NAT
  - timeouts, 328
- transport input command, 27
- transport mode, 380
- triggering DDR calls, preventing routing updates
  - from, 169
- triggering dial backup, 264–267
- triple DES (3DES), 378
- troubleshooting
  - autoconfiguration, 36
  - backup
    - dialer profiles, 280–286
    - load sharing, 273–280
    - primary line failures, 268–273, 286–291
  - cable modems, 68–77
  - compression, 305–307
  - congestion
    - custom queuing, 297–298
    - PQ, 295–296
    - priority, 307–316
    - queuing, 294
    - WFQ, 294–295
  - DSL interference, 178–179
  - error control, 24–26
  - IKE, 386

- interfaces
  - backup, 263
  - triggering backup, 264–267
- IPSec, 385–386
- NAT, 329
- PPP, 95, 107
- QoS for VPNs, 393
- traffic prioritization, 293–294
- TTY (asynchronous port), 28
- tunnels
  - GRE, 417–425
  - L2TP over IPSec, 439–443
  - modes, 381
  - QoS for VPN, 389
- types
  - of authorization, 353
  - of switches, 124
  - of users, 3

## U

- UAC (Universal Access Concentrator), 177, 184–186
- UARTs (Universal Asynchronous Receiver Transmitters), 25
- unidirectional PPP authentication, 137
- uninteresting traffic, DDR, 119
- updating routing, preventing, 169
- upstream, 54
  - ADSL, 178
  - channel bandwidth configuration, 61
  - frequencies, 57
  - input power level configuration, 59
  - ports, 58
- users, types of, 3

## V

---

- value flags, PPP, 98
- variance command, 267
- VDSL (Very High Bit Rate DSL), 7
- verification
  - ISDN configuration, 134
  - PPP, 95, 106
  - PPP configuration, 101
- VPNs (virtual private networks), 382
  - Cisco PIX 500 series firewalls, 383
  - Cisco VPN 3000 client, 384
  - Cisco VPN 3000 series concentrators,  
383–384PIX firewalls, 430–433
- QoS, 387
  - bandwidth management, 388
  - CAR, 390
  - configuring, 392
  - congestion avoidance, 389
  - CQ, 390–391
  - DS, 390
  - FRTS, 392
  - monitoring, 393
  - packet classification, 387–388
  - PQ, 391
  - traffic shaping, 388–389
  - tunnels, 389
- routers, 383
- switches, 383
- vty (virtual terminal), 28

## W-Z

---

- WANs (wide area networks)
  - compression, 305–307
  - creating, 13–16
- WFQ (Weighted Fair Queuing), 294–300, 388
- wireless communications, 3
- wiring. *See also* cables
  - DTE-to-DCE, 23–24
  - DTE-to-DTE, 22–23