



# INDEX

## A

- ABRs (Area Border Routers), 292
  - LSA propagation, 294
- Access layer, hierarchical designs, 42
- access lists. *See also* IP access lists
  - BGP-4, 557
  - controlling terminal access, 51–52
  - guidelines for writing, 48
  - prioritization, 54–55
  - security, 51
  - writing guidelines for, 49
- accessibility, network requirements, 34
- ACRC (Advanced Cisco Router Configuration), 5, 17
- AD (advertised distance), 439
- adaptability, network requirements, 34
- adding networks to topology tables, 443
- addresses
  - classes of, 92
  - Internet, 92
  - Integrated IS-IS, 354–355
    - NETs, 356–357
    - NSAPs, 356
  - IP addresses. *See* IP addresses
  - major, 92
  - network, 89–92
  - NIC addresses, 91
  - summarization, 113
  - supernet addresses, 92
  - translating, 125–126
  - VLSM addresses, allocating, 107
- addressing schemes, case studies, 88
- adjacencies
  - Integrated IS-IS, 345, 361–362
    - establishing on broadcast links, 362
    - establishing on NBMA links, 363
    - establishing on point-to-point links, 362
  - OSPF, 180, 217
- administrative distance
  - configuring, 619–620
  - path selection between routing protocols, 181–183, 610–612
- Advanced Cisco Router Configuration. *See* ACRC
- advantages
  - of CIDR, 101–103
  - of OSPF neighbors, 218
  - of policy routing, 637–638
  - of summarization, 112, 132
  - of VLSM, 104
    - bit allocation, 107
    - VLSM addresses, 107
- advertised distance, 439
- advertising routes
  - from BGP-4 to IGP, 571–572
  - from IGP to BGP-4, 571
- aggregate-address command, 571
- aggregated routes, 109
  - autonomous systems, 509
- Aggregator attribute (BGP-4), 502
- alleviating network congestion, 43
- allocating VLSM addresses, 107
- alternatives
  - to connecting to ISP, 512–513
  - to summarization, 115
- answers
  - to scenario 11-1, 671–673
  - to scenario 11-2, 673–674
  - to scenario 11-3, 675, 677
  - to scenario 11-4 Part A, 683, 685–686
  - to scenario 11-4 Part B, 688–689
  - to scenario 11-4 Part C, 720, 722–724
  - to scenario 11-5 Part C, 766–768
  - to scenario 11-5 Part A, 726–728
  - to scenario 11-5 Part B, 728, 730–731
  - to scenario 11-5 Part C, 765–769
- AppleTalk. EIGRP configuration, 461
- applications, delays in, 40
- Area 0, 292
- Area Border Routers. *See* ABRs
- area boundaries, multiple areas, 290
- area range command, 304–305
- area routing, 358–360
- areas., 297–299, 345
  - backbone areas, 298
  - design considerations, 377–378
  - NSSAs, 298
  - stubby areas, 298
- AS external ASBR summary link, LSAs, 294
- AS\_Path attribute (BGP-4), 502

ASBRs (Autonomous System Boundary Routers), 292

- LSA propagation, 294
- OSPF summarization command, 305

assigning IP VLSM subnets to WAN connections, 116–117

Atomic Aggregate attribute (BGP-4), 502

attributes

- BGP-4
  - local preference, 565
  - policy routing, 500–503
  - verifying configurations, 567, 569–570
  - weight, 564
- OSPF, 180

automatic summarization, 113

autonomous switching, 171

Autonomous System Boundary Routers. *See* ASBRs

autonomous systems, 176

- configuring, 507
- defined, 490
- defining networks to be advertised, 508
- identifying neighbors and peer groups, 508
- Next-Hop addresses, forcing, 508
- routes, aggregating, 509
- routing processes, starting, 508
- synchronization, disabling, 509

avoiding routing loops, 612–614

## B

backbone areas, 292, 298

backbone routers, 292

backup designated routers, 218

bandwidth, configuring over NBMA, 457–458

bandwidth command, 239, 456–457

- using in WANs with EIGRP, 457

bandwidth-percent command, 459

baselines, 49

best path selection, Integrated IS-IS, 375–376

BGP-4, 483, 488–489

- access lists, 557
- advertising routes
  - from BGP-4 to IGP, 571–572
  - from IGP to BGP-4, 571
- attributes
  - local preference, 565
  - verifying configurations, 567–570
  - weight, 564

- autonomous systems, 490
- case studies, 488–489, 544
- characteristics of, 491
- CIDR, 496
- commands for tuning, 564
- configuring default metrics, 617
- controlling traffic, 556
- designing networks, 545
- determining paths by tuning attributes, 564
- distribute lists, 557
- external BGP-4, 492
- fully meshed networks, 546
- internal BGP-4, 492
- key features of, 515–520
- message types, 492
- Next Hop attribute, 503, 505
- operations overview, 491
- policy routing, 490
  - attributes, 500–503
  - disadvantages of, 499
  - rules of, 497
- prefix lists, 557–558
- redistributing between IGP, 570
- route aggregation, 496–497
- route maps, 557
- route selection, 505–507
- synchronization, 494
- verifying configurations, 510–511
- when not to use, 511

bit allocation

- network addresses, 94
- VLSM, 107

Border Gateway Protocol 4. *See* BGP-4

broadcast mode, OSPF, 244

broadcast multiaccess

- OSPF network topologies, 214
- Next Hop attribute, 505

BSCI (Building Cisco Scalable Internetworks), 5–6

- how to use this book if you have taken this course, 17
- prerequisites for, 5

Building Cisco Scalable Internetworks. *See* BSCI

building OSPF routing tables, 221–222

## C

calculating cost of path selection, 296–297

case studies

addressing schemes, 88

BGP-4, 488–489, 544

EIGRP, 429

inadequate networks, 32–33

OSPF, 211

in multiple area networks, 289

redistribution, 599

examples of, 627–633

routing protocols, 162

VLSM, 105–107

CBWFQ (class-based weighted fair queuing), 55

CCDP (Cisco Certified Design Professional), 3

CCIE (Cisco Certified Internetworking Expert), 6–7

CCNA/CCDA certification, 7

CEF (Cisco Express Forwarding), 171

certifications, 6–7

CCIE, 6–7

CCNA/CCDA, 7

CCNP/CCDP, 7

exams, 9

routing and switching career tracks, 7

changing default metrics with cost command, 238–239

characteristics

of BGP-4, 491

of Layer 3 addresses, 90

of policy routing, 637

of route maps, 634–635

of route reflectors, 549–550

Charter List, BGP-4 attributes, 503

checking

OSPF configurations in multiarea networks, 315

show ip ospf border-routers command, 316

show ip ospf virtual-links command, 317–318

OSPF configurations on a single router, 246, 250

show ip ospf command, 247

show ip ospf database command, 248

show ip ospf interface command, 250–252

show ip ospf neighbor command, 252–254

show ip protocols command, 255–256

show ip route, 257

choosing

successors, 442–443

topologies, OSPF, 232

CIDR (classless interdomain routing), 98, 496

advantages of, 101–103

BGP-4, 496

definition of, 98

example of, 100–101, 131

example of use in case study, 101

IP addressing and the Internet, 99

summary of, 130

circuits, 345

Cisco Certified Design Professional. *See* CCDP

Cisco Certified Internetworking Expert. *See* CCIE

Cisco Express Forwarding (CEF), 58, 171

Cisco Networking Academy Courses, study

guidelines upon completion, 17–18

Cisco routers. *See also* routers, 43

alleviating congestion with IP access lists, 43

routing/switching relationships, 170–171

Cisco Technical Assistance Center. *See* TAC

class-based weighted fair queuing (CBWFQ), 55

classes of IP addresses, 92–93

classful IP routing protocols, 171

classful routing, 97, 171

classless interdomain routing. *See* CIDR

classless routing protocols, 171–172

clients

placement of for controlling network traffic, 59

unable to connect to network resources, 40

CLNP (Connectionless Network Protocol), 345

CLNS (Connectionless Network Service), 346

CLV (Code/Length/Value), 345

commands, 316

access-class, 52

access-group, 52

access-list, 45–46

aggregate-address, 571

area range, 304

auto-cost, 239

auto-cost reference-bandwidth, 239

bandwidth, 239, 456–458

bandwidth-percent, 459

cost, 238–239

debug, 401–402

debug commands for EIGRP, 465

debug ip bgp, 510

debug IP OSPF adjacency, 222

debug ip policy, 646

default metric, 618

- deny any, 45, 49
  - distance, 631
  - distribute-list, 627
  - for configuring multiarea OSPF networks, 302
    - area range command, 304–305
    - network command, 302–303
    - summarization command, 305
  - for configuring OSPF on internal routers, 234
  - for monitoring policy routing, 645
  - for tuning BGP-4, 564
  - ip access-group, 45
  - ip classless, 632
  - ip forward-protocol, 60
  - ip helper-address, 60
  - ip ospf cost, 239
  - ip ospf network, 242
  - ip ospf network non-broadcast, 244
  - ip unnumbered, 113
  - match route map, 634
  - neighbor, 244
  - no ip address, 245
  - no-summary, 308
  - ospf auto-cost, 239
  - ospf neighbor, 243
  - passive interface, 622
  - priority, 55, 240
  - redistribute, 617
  - redistribute connected subnets, 236
  - route-map, 635
  - router ospf process number, 235
  - set route map, 634
  - show buffers, 35
  - show clns interface, 393–395
  - show clns neighbors, 391–393
  - show cpu process, 291
  - show interface, 35, 457
  - show ip bgp, 510, 567
  - show ip bgp neighbors, 510
  - show ip bgp paths, 510
  - show ip bgp summary, 510
  - show ip eigrp neighbors, 462
  - show ip eigrp topology, 462–464
  - show ip eigrp topology all, 462
  - show ip eigrp traffic, 462–464
  - show ip ospf, 246–248
  - show ip ospf border-routers, 315–317
  - show ip ospf command, 247
  - show ip ospf database, 246–250
  - show ip ospf interface, 246, 250–252
  - show ip ospf neighbor, 222, 246, 252–254
  - show ip ospf virtual-links, 315–318
  - show ip prefix-list, 559–560
  - show ip protocols, 246, 255–256
  - show ip route, 167–168, 246, 257
  - show ip route eigrp, 465
  - show ipx route, 462
  - show isis database, 396–397
  - show isis database detail, 397–399
  - show isis spf-log, 400–401
  - show memory, 291
  - show queuing, 35
  - stop telnet, 48
  - sub net zero, 107
  - summarization, 305
  - summary-only, 509
  - syntax conventions, 20
  - traceroute, 644
  - tunnel interface, 63
  - variance, 454–456
  - vtv commands, 52
- Community attribute (BGP-4), 503
- configuring
    - administrative distance, 619–620
    - autonomous systems, 507
    - bandwidth over NBMA clouds, 457–458
    - default metrics, 617–618
    - EIGRP, 451
      - for AppleTalk, 461
      - for IPX, 459–461
      - optional commands, 454–459
      - required commands, 452–453
  - Integrated IS-IS, 380–381
    - NMBA, 386–388
    - routing level, 381–383
    - summarization, 384–386
  - multiple routing protocols, problems with, 607
  - null interfaces, 55
  - OSPF, 234
    - area range command, 304–305
    - in broadcast mode, 244
    - in multiarea networks, 302, 314
    - in NBMA mode, 242–243
    - in point-to-multipoint mode, 244
    - in point-to-point mode on a Frame Relay subinterface, 245
    - network command, 302–303
    - on internal routers, 234–240

- on a single router, 240
  - stub areas, 307
  - summarization command, 305
  - totally stubby areas, 308
  - virtual links, 311
- prefix lists
  - BGP-4, 558
  - verifying configurations, 559–560
- redistribution, 615–617
- route maps for policy routing, 640
- router ID, 238
- virtual links, 312
- contents of BSCI exam, 9–12
- controlling
  - BGP-4 traffic, 556
  - network traffic
    - CEF, 58
    - design of client/server network, 59
    - EIGRP, 60
    - IP helper address, 59
    - silicon switching, 58
    - tunneling into IP, 61–62
    - with CPUs, 58
  - routing updates
    - redistribution, 601–602
    - with filtering, 625–627
  - terminal access, 51–52
- conventions for command syntax, 20
- convergence, 183
  - EIGRP, 184
  - IGRP, 184
  - OSPF, 185
  - RIPv1, 183
- Core layer, 42
- cost, 238–239
  - of path selection, calculating (OSPF), 297
- count to infinity, RIPv1, 177
- CPUs, controlling network traffic, 58
- creating
  - networks, 40
    - hierarchical designs, 41
    - scaling, 41
  - prefix lists, 558
- CSNP (complete sequence number packet), 345
- custom queuing, 54

## D

- debug command, 401–402
  - BGP-4, 510
- debug commands, 465
- debug ip bgp, 510
- debug ip ospf adjacency, 222
- debug ip policy, 646
- decision process (Integrated IS-IS), 375–376
- default metric command, 618
- default metrics, configuring, 238, 617–618
- default routes, 164, 601
  - EIGRP, 624
  - IGRP, 624
  - redistribution, 623–624
  - when to use, 624
- delays, 40
- designated routers
  - backup designated routers, 218
  - determining with priority command, 240
  - electing, 219–221
  - OSPF, 219–221
  - OSPF neighbors, 218
  - purpose for, 219
- designing
  - BGP-4 networks, 545
  - client server networks, controlling network traffic, 59
  - Integrated IS-IS areas, 377–378
  - IP networks, 118–123
    - private addresses, 124–125
  - OSPF networks in multiple areas, 299
- destination address rotary translation, NAT, 127
- determining
  - area boundaries, 290
  - BGP-4 paths by tuning attributes, 564
  - designated router with priority command, 240
  - policy-based routes, 638
- DHCP (Dynamic Host Configuration Protocol), 89, 123
- Diffusing Update Algorithm. *See* DUAL
- Dijkstra algorithm, 185, 226
- DIS (designated intermediate system), 346
- disabling synchronization, 509
- disadvantages
  - of fully meshed networks, 546
  - of OSPF in a single area, 290
  - of policy routing, 499, 638

- discontinuous networks, summarization, 114–115
- discovering OSPF routes, 224–226
- distance command, 631
- distance vector protocols, 172–173
  - EIGRP, 173
  - IGRP, 178–179
  - metrics, 173
  - routing loops, 173
- distribute lists, 53, 625
  - BGP-4, 557
- distribute-list command, 627
- Distribution layer, 42
- distribution lists, controlling routing updates, 602
- DNS (Domain Name System), 123
- dotted decimal form, 95
- down state, 223
- DUAL (Diffusing Update Algorithm), 173
  - EIGRP, 439
    - updating routing tables in active mode, 441–443, 445–446, 449
    - updating the routing table in passive mode, 440
- Dual IS-IS. *See* Integrated IS-IS
- Dynamic Host Configuration Protocol. *See* DHCP
- dynamic routes, 164
- dynamic source address translation, NAT, 127

## E

---

- efficient networks, criteria for, 34
- EGP (External Gateway Protocol), configuring
  - default metrics, 617
- EIGRP (Enhanced Interior Gateway Routing Protocol), 423, 429
  - administrative distance, configuring, 620
  - autonomous system number, 452
  - bandwidth command, using in WANs, 457
  - case studies, 429
  - choosing successors, 442–443
  - configuring, 451
    - for AppleTalk, 461
    - for IPX, 459, 461
    - optional commands, 454–459
    - required commands, 452–453
  - configuring default metrics, 618
  - controlling network traffic, 60
  - convergence, 184
  - default routes, 624
  - defaults in bandwidth utilization, 456
  - defined, 429
  - distance vector protocols, 173
  - DUAL, 439
    - updating routing tables in active mode, 441–449
    - updating routing table in passive mode, 440
  - finding alternative paths to remote networks, 446, 449
  - hello protocol, 434
    - neighbor tables, 434–435
    - neighbors, 434
    - topology tables, 436–438
  - load balancing, 454
  - metrics, 438–439
  - operation of, 430–431
  - scaling, 449–450
    - solutions to issues, 450–451
  - summarization, 454, 727
  - terminology, 432–433
  - verifying operations, 462
    - debug commands, 465
    - show ip eigrp neighbors command, 462
    - show ip eigrp topology command, 463
    - show ip eigrp traffic command, 464
- electing designated routers, 219–221
- enabling OSPF routing protocol, 235
- Enhanced Interior Gateway Routing Protocol.
  - See* EIGRP
- examples
  - of prefix lists, 559
  - of redistribution, 627–633
- exams (certification), strategies for taking, 21–22
- exchange process, finding OSPF neighbors, 222–223
- exchange state, 224
- exstart state, 224
- extended IP access lists, 46–48
- extended ping, 645
- exterior routing protocols, 176
- external BGP-4, 492
- external link LSAs, 294
- external summarization, 300

---

## F

- fast switching, 171
  - policy-routed traffic, 643
- FC (feasibility condition), 442
- FD (feasible distance), 439
- feasible successors, 442
- features
  - of NAT, 127–128
  - of redistribution, 604
    - default redistribution between routing protocols, 604–606
    - multiple protocols, 606–607
- filter configuration, verifying, 49
- filtering routing updates, 625–627
- finding alternative paths to remote networks, 446, 449
- first octet rule, 96
- floating static routes, 183
- flooding, 91
- format of Hello packets (Integrated IS-IS), 365–366
  - LSPs, 367–368
  - NSPs, 368–369
- forwarding databases. *See* routing tables
- forwarding process (Integrated IS-IS), 377
- Frame Relay, OSPF topologies
  - NBMA, 232
  - point-to-point mode, 245
- full state, 224
- fully meshed IBGP-4 networks, route reflectors, 546–548

---

## G

- goals of this book, 4
- guidelines
  - for avoiding routing loops, 614
  - for writing access lists, 48–49

---

## H

- hello packets
  - Integrated IS-IS, 364–366
  - OSPF, 216–217

- hello protocol, 214
  - EIGRP, 434
    - becoming neighbors, 434
    - neighbor tables, 434–435
    - topology tables, 436–438
- hiding network summarization changes, 112
- hierarchical designs
  - creating networks, 41
  - networks, 41
    - Access layer, 42
    - Core layer, 42
    - creating, 41
    - design rules for layers, 42
    - Distribution layer, 42
- holddown, RIPv1, 177
- hops, 173
- host addressing
  - IP addresses, 92

---

## I-J

- IANA (Internet Assigned Numbers Authority), 93
- IBGP-4 fully meshed networks, 547
- ICANN (Internet Corporation for Assigned Names and Numbers), 93
- ICND (Interconnecting Cisco Network Devices), 6, 27
- ICRC (Introduction to Cisco Router Configuration), 6
- identifying neighbors within autonomous systems, 508
- IGP (interior gateway protocol), 292
  - advertising routes from BGP-4 to IGP, 571–572
  - advertising routes from IGP to BGP-4, 571
  - redistributing between BGP-4, 570
- IGRP (Interior Gateway Routing Protocol), 178–179
  - configuring default metrics, 618
  - convergence, 184
  - default routes, 624
- implementing IP access lists, 44
- init state, 223
- Integrated IS-IS, 346
  - adjacencies, 361–362
    - establishing on broadcast links, 362
    - establishing on NBMA links, 363
    - establishing on point-to-point links, 362
  - area routing, 358–360



- configuring, 380–381
- decision process, 375–376
- design considerations, 377–378
- forwarding process, 377
- ISO addressing, 354–355
  - NETs, 356–357
  - NSAPs, 356
- L1 routers, 357
- L2 routers, 358
- Level 1-2 routers, 358
- neighbors, 360
- NMBA, configuring, 386–388
- packet types, 364–366
  - LSPs, format, 367–368
  - NSPs, format, 368–369
- receive process, 377
- route summarization, 379
- routing level, configuring, 381–383
- summarization, configuring, 384–386
- TLVs, 369–371
- troubleshooting, 399–402
- update process, 372–374
- verifying operation, 389–390
- versus OSPF, 350–353
- interarea routers, 357
- interarea summarization, 300
- Interconnecting Cisco Network Devices. *See* ICND
- interdomain routing, 98
- interior gateway protocol. *See* IGP
- interior routing protocols, 176
- intermittent connectivity, 40
- internal BGP-4, 492
- internal routers, 291
- Internet
  - and IP addresses, 92–94
    - fixing problems with CIDR, 99
    - multiple connections to, 560–562
- Internet Assigned Numbers Authority (IANA), 93
- Internet Corporation for Assigned Names and Numbers (ICANN), 93
- Introduction to Cisco Router Configuration (ICRC), 6
- IP access lists, 45. *See also* access lists
  - alleviating network congestion with Cisco routers, 43
  - extended IP access lists, 46, 48
  - implementing, 44
  - standard IP access lists, 45–46
  - uses of, 51
- ip access-group command, 45
- IP addresses, 91
  - and the Internet, 99
  - bit allocation, 94
  - classes, 93
  - controlling network traffic, 44, 61–62
  - host addressing, 92
  - Internet, 92–94
  - Internet authoritative bodies, 93
  - Internet masks, 92
  - networks, 92
  - optimizing, 116–118
  - private addresses, 124–125
  - subnet masks, 94, 98
    - logical AND, 95–96
    - network boundaries, 94
    - rules, 97
    - rules for IP subnetting, 96–97
  - summary of, 130
- ip classless command, 632
- ip forward-protocol command, 60
- IP helper addresses, controlling network traffic, 59–60
- IP networks, designing, 118–123
- ip ospf cost, 239
- ip ospf network, 242
- ip ospf network non-broadcast, 244
- ip unnumbered command, 113
- IP VLSM subnets, assigning to WAN connections, 116–117
- IPX (Internetwork Packet Exchange), configuring
  - EIGRP for, 459–461
- ISO addressing, 354–355
  - NETs, 356–357
  - NSAPs, 356
- ISPs, connecting to, 512–513

---

## K-L

- keepalives, BGP-4 message types, 492
- L1 routers, 347, 357
- L1-2 routers, 347
- L2 routers, 347, 358
- LAN Hello packets, 366
- Layer 3 addresses, 89
  - need for, 88–89
  - network characteristics of, 90
- layers, design rules for, 42

Level 1-2 routers, 358  
 link-state advertisements. *See* LSAs  
 link-state routing protocols, 174–175  
   networks, 175  
   path selection, 176  
   updating local network tables, 176  
 LLQ (low-latency queuing), 55  
 load balancing  
   EIGRP, 454  
   RIPv1, 178  
 loading state, 224  
 local preference attribute, 502  
   BGP-4, tuning, 564–565  
 logical AND, 95–96  
 Logical Hop field, 166  
 loopback interfaces, 238  
   configuring OSPF on internal routers, 237  
 low-latency queuing (LLQ), 55  
 LSAs (links-state advertisements), 176  
   OSPF, 293–294  
   propagating, 294–295  
 LSPs (link-state packets), 347

## M

maintaining  
   redistribution, 644  
   topology databases, 227  
   topology tables, 436  
 major addresses, 92  
 managing  
   BGP-4 configurations, 510–511  
   IP network congestion, 44  
 manual summarization, 113  
 match commands, policy routing with route maps,  
   634, 640–643  
 match route map command, 634  
 MED (Multiple Exit Discriminator) attribute, 502  
 message types, BGP-4, 492  
 Metric field, 165  
 metrics  
   default metrics, 617–618  
   distance vector metrics, 173  
   EIGRP, 438–439  
   routing metrics, 608  
   seed metrics, 617  
 monitoring policy routing, commands for, 645

multihoming, 560  
 multiple areas  
   area boundaries, 290  
   OSPF, 289  
     design considerations, 299, 302  
   NBMA, 301  
   path selection, 295  
   summarization, 300  
   virtual links, 300  
 Multiple Exit Discriminator (MED) attribute, 502  
 multiple Internet connections, 561–562

## N

NAT (Network Address Translation), 125–126  
   features of, 127–128  
 NBMA (nonbroadcast multiaccess)  
   configuring bandwidth over, 457  
   OSPF, 231  
     choosing topologies, 232  
     Cisco-specific, 231  
     configuring, 242–243  
     Frame Relay topologies, 232  
     in multiple areas, 301  
     network topologies, 215  
     RFC-complaint, 231  
     subinterfaces, 232–233  
 neighbor command, 244  
 neighbors, 360  
   EIGRP, hello protocol, 434–435  
   identifying autonomous systems, 508  
   OSPF, 214  
     adjacent neighbors, 217  
     designated routers, 218–219, 221  
     finding with exchange process, 222–223  
     hello packets, 216–217  
 Net Flow, 58  
 NETs (network entity titles), 347, 356–357  
 network addresses, 92–94  
 network command, OSPF, 234–237  
   configuring multiarea networks, 302–303  
   configuring on internal routers, 235  
 network congestion, 35. *See also* networks  
   alleviating with Cisco routers, 43  
   dropped packets, 37  
   excessive traffic, 36  
   IP, managing, 44  
   network design, 35

- retransmission of packets, 37
- routing tables, 37
- runaway congestion, 39
- scaling networks, 41
- server lists, 38
- Spanning-Tree Protocol, 38–39
- symptoms of, 39–40
- traffic analysis, 35

Network field, routing tables, 164–165

network summary link, LSAs, 294

network traffic. *See also* network congestion

networks

- adding to topology tables, 443
- address translation, 125–126
- addressing, 89–91
- as defined by Layer 3, 89
- broadcast multiaccess networks, Next Hop attribute, 505
- case studies, 32–33
- creating, 40
  - hierarchical designs, 41
  - scaling to reduce congestion, 41
- defining to be advertised, 508
- definitions of, 90
- discontiguous, 114
- fully meshed networks, BGP-4, 546
- hiding changes, summarization, 112
- hierarchical designs, 41
  - Access layer, 42
  - Core layer, 42
  - Distribution layer, 42
  - rules for each layer, 42
- IP addresses, 92
- IP boundaries, 94
- link-state routing protocols, 175
- nonbroadcast multiaccess networks, Next Hop attribute, 505

OSPF, 214

- broadcast multiaccess, 214
- multiple area networks 289
- NBMA, 215
- point-to-point, 215
- point-to-multipoint, 215
- virtual links, 216

redistribution, 613–614

requirements of, 33

- accessibility/security, 34
- adaptability/serviceability, 34
- efficiency, 34

- increasing network traffic, 35
- reliability, 33
- responsiveness, 33

traffic, controlling

- Cisco express forwarding, 58
- design of client/server network, 59
- EIGRP, 60
- IP helper address, 59
- null interfaces, 55–56
- placement of clients/servers, 59
- silicon switching, 58
- tunneling into IP, 61–62
- with CPUs, 58

Next Hop attribute (BGP-4), 502–505

Next Logical Hop field, routing tables, 166–167

Next-Hop addresses, forcing, 508

NIC address, 91

no ip address, 245

nonbroadcast multiaccess. *See* NBMA

no-summary command, 308

not so stubby areas. *See* NSSAs

notification, BGP-4 message types, 492

NPDU (network protocol data units), 347

NSAPs (network service access points), 348, 356

NSEL (network selector), 348

NSSAs (not so stubby areas), 298

- external LSAs, 294

null interfaces

- controlling routing updates, 601
- internet example, 55
- intranet example, 56
- reducing network traffic, 55–56

---

## O

OL (Overload) bit, 348

open messages (BGP-4), 492

Open Shortest Path First. *See* OSPF

optimizing IP address space, 116, 118

options for configuring OSPF on internal routers, 237–240

Origin attribute (BGP-4), 501

- Originator ID, 503

OSPF (Open Shortest Path First)), 44, 179

- attributes of, 180
- case studies, 211

- checking configurations in multiarea networks
    - show ip ospf border-routers
      - command, 316
    - show ip ospf virtual-links
      - command, 317–318
  - checking configurations on a single router, 246
    - show ip ospf command, 247
    - show ip ospf database command, 248
    - show ip ospf interface command, 250, 252
    - show ip ospf neighbor command, 252, 254
    - show ip protocols command, 255–256
    - show ip route command, 257
  - checking configurations on a single server,
    - show ip ospf database command, 250
  - checking configurations on multiarea networks, 315
  - configuring, 234
    - default metric, 617
    - in broadcast mode, 244
    - in NBMA mode, 242–243
    - in point-to-multipoint mode, 244
    - in point-to-point mode on a Frame Relay subinterface, 245
    - on a single router, 240
    - on internal routers, 234, 238
    - over NBMA topology, 242
    - virtual links, 311
  - convergence, 185
  - designs, router types, 291
  - designs within areas, 291
  - hello protocol, 214
  - in multiple areas
    - area boundaries, 290
    - design considerations, 299
    - NBMA, 301
    - summarization, 300
    - virtual links, 300
  - in single areas, disadvantages of, 290
  - LSAs, 293–294
  - multiarea networks, 302
    - area range command, 304–305
    - commands for stub areas, 307
    - network command, 302–303
    - OSPF command for the cost of default routes propagated to the area, 309
    - summarization command, 305
    - totally stubby areas, 308
    - working configurations, 314
  - NBMA
    - choosing topologies, 232
    - Cisco-specific, 231
    - Frame Relay topologies, 232
    - RFC-compliant, 231
    - subinterfaces, 232–233
  - neighbors, 214
    - adjacent neighbors, 217
    - designated routers, 218–219, 221
    - finding with exchange process, 222–223
    - hello packets, 216–217
  - network topologies, 214
    - broadcast multiaccess, 214
    - NBMA, 215
    - point-to-multipoint, 215
    - point-to-point, 215
    - virtual links, 216
  - path selection
    - between areas, 295
    - calculating cost, 296–297
  - router types, 291–292
  - routes, discovering, 224
  - routing protocol, enabling, 235
  - routing tables
    - building, 221–222
    - building routing tables on new OSPF routers, 222
    - building SPF, 231
    - choosing SPF, 230
    - learning new routes, 227–228
    - maintaining, 227
    - topology databases, 226
    - updating topology tables, 226
  - routing tables codes and associated LSAs, 297
  - terminology, 212–213
  - topology databases, maintaining, 227
  - types of areas, 297–299
  - versus Integrated IS-IS, 350–353
- ospf auto-cost command, 239
  - ospf neighbor command, 243
  - Outgoing Interface field, routing tables, 165
  - overview of IP access lists, 45
- ## P-Q
- 
- packets
    - ensuring they are switched at speed, 643
    - Integrated IS-IS, 364–366
    - LSPs, format, 367–368
    - network congestion, 37
    - retransmitting, 37
    - NSPs, format, 368–369

passive interface command, 622

passive interfaces, 601

- redistribution, 621

PAT (port address translation), 127

path selection

- between routing protocols, 181, 610
- calculating cost, 296
- link-state routing protocols, 176
- OSPF
  - between areas, 295
  - calculating cost of, 297
- routing protocols, administrative distance, 181–183
- routing tables, 608–609
- within routing protocols, 608

paths, removing from topology tables, 444

peer groups, 508

ping, extended ping, 645

point-to-multipoint

- OSPF network topologies,

point-to-multipoint OSPF topologies, 215

- configuring, 244

point-to-point OSPF network topologies, 215

Point-to-point Hello packets, 366

policy routing

- advantages of, 637–638
- BGP-4, 490, 497
  - attributes, 500–503
  - disadvantages of, 499
  - rules of, 497
- characteristics of, 637
- commands for monitoring, 645
- configuring route maps, 640
- disadvantages of, 638
- route maps, 633, 636–638
  - match commands, 640–643

port address translation. *See* PAT

prefix lists, 576–577

- BGP-4, 557
  - configuring, 558
  - creating, 558
- examples of, 559
- verifying configurations, 559–560

prefix routing. *See* CIDR, 98

prerequisites for BSCI course, 5

prioritization, access lists, 54–55

priority, 55

priority command, 240

priority queuing, 54

private addresses, 124–125

problems

- with IP addressing and the Internet, 99
- with OSPF in a single area, 290
- with redistribution and network convergence, 613

process ID, 235

processing prefix lists, 558

professional-level certifications, 3

propagating LSAs, 294–295

proprietary Cisco solutions for alleviating network congestion, 44

protocols

- definition of, 163
- distance vector protocols. *See* distance vector protocols
- IGP, 292
- link-state routing protocols. *See* link-state routing protocols
- routing protocol. *See* routing protocols

pseudonodes, 349

PSNP (partial sequence number packet), 348

purpose of routing protocols, 163

## R

reasons for controlling routing updates, 602–603

receive process (Integrated IS-IS), 377

redistribute command, 617

redistribute connected subnets, 236

redistribution, 181, 599

- administrative distance, configuring, 619–620
- avoiding routing loops, 612
- between IGP and BGP-4, 570
- between routing protocols, 599, 601
- case studies, 599
- configuring, 615
  - configuration syntax, 615–616
  - default metrics, 617
- configuring multiple routing protocols, 607
- controlling routing updates, 601
- controlling routing updates with filtering, 625
- default metrics, 617
- default routes, 623–624
- examples of, 627–633
- features of, 604
  - default redistribution between routing protocols, 604–606
  - multiple protocols, 606–607

- network convergence, 613–614
- passive interfaces, 621
- path selection between routing protocols, 608–610
- reasons for using on routing protocol, 607
- routing updates, controlling, 602
- seed metrics, 617
- static routes, 621–623
- verifying, 644
  - extended ping, 645
  - traceroute, 644
- reducing
  - network traffic, 55–56
  - size of routing tables, 112
- reliability, network requirements, 33
- remote networks, finding alternative paths to, 446, 449
- removing paths or routers from topology tables, 444
- requirements of networks, 33–34
  - accessibility/security, 34
  - efficiency, 34
  - increasing network traffic, 35
  - reliability, 33
  - responsiveness, 33
- responsiveness, requirements of networks, 33
- RFC-compliant NBMA, 231
- RIPv1 (Routing Information Protocol version 1), 177–178
  - configuring default metrics, 617
  - convergence, 183
- route aggregation, BGP-4, 496–497
- route map command syntax, 635
- route maps
  - BGP-4, 557
  - characteristics of, 634–635
  - controlling routing updates, 602
  - policy routing, 633–638
    - match commands, 640–643
  - statements, 639
  - uses for, 634
- route reflectors, 575–576
  - characteristics of, 549–550
  - fully meshed IBGP-4 networks, 547–548
  - rules for propagating updates, 550–556
- route selection, BGP-4, 505–507
- route summarization, Integrated IS-IS, 379
- route switching, 643
- routed protocols versus routing protocols, 163–164
- route-map command, 635
- router ID, 235
  - configuring, 237–238
- router link LSAs, 293
- router ospf process number command, 235
- routers. *See* Cisco routers
  - designated routers, OSPF, 218–221, 291–292
  - removing from topology tables, 444
- routes
  - autonomous systems, aggregating, 509
  - OSPF, discovering, 224, 226
- routing
  - policy-based routing. *See* policy routing
  - SIN routing, 604
  - versus switching, 169
- Routing and Switching career tracks, 7
- Routing Domains, 349
- BSCI exam, 3–4
  - contents of, 9–12
- routing function, 169
- Routing Information Protocol version 1. *See* RIPv1
- routing loops, 173, 612–614
- routing metrics, 608
- routing protocols
  - case studies, 162
  - definition of, 163
  - exterior routing protocols, 176
  - IGRP, 178–179
  - interior routing protocols, 176
  - link-state routing protocols. *See* link-state protocols
  - OSPF, 179
    - attributes of, 180
    - enabling, 235
  - path selection, 181, 608–610
    - administrative distance, 181–183
  - purpose of, 163
  - redistribution, 599–601
  - RIPv1, 177–178
  - types of, 171
    - classful routing protocols, 171
    - classless routing protocols, 171–172
  - versus routed protocols, 163–164
  - VLSM, 103–104
- routing tables
  - keeping current and correct, 168–169
  - Metric field, 165
  - network congestion, 37

- Network field, 164–165
  - Next Logical Hop field, 166–167
  - OSPF
    - building, 221–222
    - building routing tables on new OSPF routers, 222
    - building SPF, 231
    - choosing SPF, 230
    - learning new routes, 227–228
    - maintaining, 227
    - topology databases, 226
    - updating topology tables, 226
  - Outgoing Interface field, 165
  - path selection, 608–609
  - reducing size of, summarization, 112
  - updating in active mode with DUAL, 442–449
  - routing updates, controlling, 52–54, 602
    - reasons for , 602–603
    - redistribution, 601
    - with filtering, 626–627
  - routing/switching relationships in Cisco routers, 170–171
  - rules
    - for propagating updates, 550–556
    - for VLSM, 132
    - IP addresses, subnets, 97
    - of policy routing, 497
    - of VLSM, 104
  - runaway congestion, 37–39
- ## S
- 
- scaling
    - EIGRP, 449–451
    - networks, 41
  - scenario 11-1, 667
    - answers to, 671–673
  - scenario 11-2, 668–669
    - answers to, 673–674
  - scenario 11-3, 669–670
    - answers to, 675–677
  - scenario 11-4
    - part A, 678–682
      - answers to, 683–686
    - part B, 687
      - answers to, 688–689
    - part C, 689–704, 706–709, 711–714, 716–720
      - answers, 720–724
    - scenario 11-5, 724
      - part A, 726
        - answers, 726–728
      - part B, 728
        - answers, 728–731
      - part C, 731, 733–765
        - answers, 765–769
    - security, access lists, 51–52
    - seed metrics, 617
    - server lists, network congestion, 38
    - servers, placement of in controlling network traffic, 59
    - serviceability, network requirements, 34
    - set command, 638
    - set route map command, 634
    - ships in the night (SIN) routing, 604
    - shortest path first. *See* SPF
    - show buffers, 35
    - show clns interface command, 393–395
    - show clns neighbors command, 391–393
    - show cpu process command, 291
    - show interface command, 35, 457
    - show ip bgp command, 510, 567
    - show ip bgp neighbors command, 510
    - show ip bgp paths command, 510
    - show ip bgp summary command, 510
    - show ip eigrp neighbors command, 462
    - show ip eigrp topology command, 462–464
    - show ip eigrp topology all command, 462
    - show ip eigrp traffic command, 462–464
    - show ip ospf command, 246
    - show ip ospf border-routers command, 315–317
    - show ip ospf command, 247–248
    - show ip ospf database command, 246–250
    - show ip ospf interface command, 246, 250–252
    - show ip ospf neighbor command, 222, 246, 252–254
    - show ip ospf virtual links command, 315–318
    - show ip prefix-list command, 559–560
    - show ip protocols command, 246, 255–256
    - show ip route command, 167–168, 246, 257
    - show ip route eigrp command, 465
    - show ipx route command, 462
    - show isis database command, 396–397
    - show isis database detail command, 397–399
    - show isis spf-log command, 400–401
    - show memory command, 291
    - show queuing command, 35
    - silicon switching command, 58, 171
    - SIN (ships in the night) routing, 604

SNP (Sequence number PDU), 349  
 SNPA (subnetwork point of attachment), 350  
 Spanning-Tree Protocol, network congestion, 38–39  
 SPF (shortest path first), 226  
   building routing tables, 230–231  
 split horizon rule, 173, 177  
 split horizon with poison reverse, 177  
 starting routing processes, autonomous systems, 508  
 statements, route maps, 639  
 static addressing, NAT, 127  
 static routes, 164, 601  
   redistribution, 621–624  
   VLSM, 104  
 stop telnet, 48  
 strategies for exam day, 21–22  
 stub area, 298  
   OSPF commands, 307–308  
 study strategies, 17–19  
 sub net zero, 107  
 subinterfaces, OSPF  
   configuring in point-to-point mode, 245  
   NBMA, 232–233  
 subnet masks  
   IP addresses, 94, 98  
   logical AND, 95–96  
   network boundaries, 94  
   rules, 97  
   subnetting, 96  
   VLSM. See VLSM  
 subnet rules, 97, 107  
 subnetwork dependent layer, 349  
 subnetwork independent layer, 350  
 successors, choosing, 442–443  
 summarization, 109  
   address exhaustion, 113  
   advantages of, 112, 132  
   alternatives to, 115  
   automatic summarization, 113  
   discontiguous networks, 114–115  
   EIGRP, 454, 727  
   IP address space, optimizing, 116–118  
   manual summarization, 113  
   OSPF in multiple areas, 300  
 summarization command, 305  
 summary-only command, 509  
 supernet addresses, 92  
 supernets, 109  
 switching versus routing, 169  
 switching function, 170

symptoms of network congestion, 39–40  
 synchronization  
   autonomous systems, disabling, 509  
   BGP-4, 494  
 syntax of route map command, 635

## T

terminal access, controlling, 51–52  
 terminology of EIGRP, 432–433  
 TLV (Type/Length/Value), 350, 369–371  
 topologies, OSPF NBMA, 232  
 topology tables, 435  
   adding to networks, 443  
   EIGRP, hello protocol, 436, 438  
   maintaining, 227, 436  
   OSPF, routing tables, 226  
   removing paths or routers, 444  
 totally stubby areas, OSPF commands, 308–309  
 traceroute command, verifying redistribution, 644  
 traffic  
   controlling in BGP-4, 556  
   network congestion, 36  
   route switching, 643  
 traffic analysis, network congestion, 35  
 traffic control, routing updates, 52, 54  
 translating addresses, 125–126  
 triggered update  
   RIPv1, 177  
   with poison reverse, 183  
 troubleshooting  
   Integrated IS-IS, 399–402  
   redistribution, 644  
 tunnel interface, 63  
 tunneling into IP, controlling network traffic, 61–62  
 two-way state, 223  
 types  
   of OSPF areas, 297, 299  
   of routing protocols  
     classful routing protocols, 171  
     classless routing protocols, 171–172



## U

---

- underruns, 702
- update messages, BGP-4 message types, 492
- update process (Integrated IS-IS), 372–374
- updates, rules for propagating, 550, 552–554, 556
- updating
  - local network tables, link-state routing protocols, 176
  - routing tables, 168–169
    - in active mode with DUAL, 441–449
    - in passive mode with DUAL, 440

## V

---

- variable-length subnet masks. See VLSM
- variance command, 454–456
- verifying
  - BGP-4 attribute configurations, 510–511, 567–570
  - EIGRP operations, 462
    - debug commands, 465
    - show ip eigrp neighbors, 462
    - show ip eigrp topology, 463
    - show ip eigrp traffic, 464
  - filter configuration, 49
  - Integrated IS-IS operation, 389–390
  - prefix lists configurations, 559–560
  - redistribution, 644
    - extended ping, 645
    - traceroute, 644
- virtual links (OSPF)
  - configuring, 312
  - in multiarea networks, 300, 311
  - network topologies, 216
- virtual terminal line, 51
- VLANs, 89
- VLSMs (variable-length subnet masks), 103
  - address allocation, 107
  - advantages of, 104
    - allocating VLSM addresses, 107
    - bit allocation, 107
  - case studies, 105–107

- example of, 103
- routing protocols, 103
- rules for, 132
- rules of, 104
- static routes, 104
- vty (virtual terminal line), 51–52

## W-Z

---

- WANs
  - assigning IP VLSM subnets, 116–117
  - bandwidth command and EIGRP, 457
- Weight attribute (BGP-4), 503, 564
- writing access lists, guidelines for, 48–49