

Index

Numerics

- 1900 series switches
 - configuration, 577, 587
 - default settings, 578–579
 - ports, numbering, 579
- 802.1Q, 73
 - versus ISL, 74–75
- 802.1w. *See* RSTP

A

- access links, 378, 599
- access lists, **xxi**
 - controlling vty access, 446
 - deny statements, 429
 - displaying details for all protocols, 433, 440
 - extended IP, 427, 430, 437
 - displaying details of*, 433, 440
 - example*, 440–442
 - filtering logic*, 439
 - matching options*, 438, 450
 - functionality of, 427
 - matching logic, 429–430
 - named IP, 443–444, 448
 - permit statements, 429
 - SAP filter, 478
 - standard IP, 427
 - configuring*, 432–435
 - displaying details of*, 433, 440
 - features*, 429
 - matching options*, 438, 450
 - planning*, 478
 - statements, 438–439, 451
 - wildcard masks, 430–431
- access-class command, 433
- address classes, 102–103
- address violations, switch ports, 585
- addresses, 232
 - IP addresses
 - displaying*, 16, 578
 - planning*, 474
 - setting*, 14, 578
 - translating for invalid hosts with NAT*, 269
 - IPX addresses
 - displaying for neighboring routers*, 489
 - secondary addresses*, 464, 481
 - MAC addresses, 583, 585
 - broadcast addresses*, 10
 - dynamic*, 582
 - LAN card addressing*, 10
 - multicast addresses*, 10
 - restricted-static entries*, 582
 - switches, setting permanent*, 578
 - switches, setting restricted*, 578
 - tables, displaying*, 16, 578
- address-violation command, 578, 585
- administrative distance, 176–177
- advertisements, VTP, 76
- AMI (Alternate Mark Inversion), 335
- applying access lists to vty ports, 446
- architected field specifications, 309
- areas (OSPF), 195, 197
- ARP (Address Resolution Protocol), 473
- authentication, 313
 - CHAP, 314–315
 - PAP, 314–315
- autonegotiation, switches, 580
- autosummarization, 233–237

B

- B8ZS (Binary 8 with Zero Substitution), 335
- backup ports, 51
- balanced hybrid routing protocols, 178, 575
 - EIGRP, 198–199
 - configuring*, 209–211
 - features*, 201
 - loop avoidance*, 199–200
- bandwidth command, 395
- BECN (backward explicit congestion notification), 599
- behavior of distance vector routing protocols, 150
- binary values, converting to decimal and hexadecimal values, 107–109, 555, 559
- blocking state (Spanning Tree), 45, 63
- Boolean AND operation, 109–111
 - identifying subnet number in subnet masks, 116–117
- BPDU (bridge protocol data units), 36, 39, 47
- BRI (Basic Rate Interface), 327
 - DDR, 336–338
- bridge IDs, 40
- bridge priority, manipulating, 58–60
- bridge tables, 11
- broadcast addresses
 - deriving without using binary, 121–127
 - MAC addresses, 10
- broadcast command, 344
- broadcast domains, 71
 - VLANs
 - configuring*, 587–595
 - ISL trunking*, 289–290, 295
 - VTP*, 76–77
- broadcasts, Frame Relay handling, 392–393
- burst rate, 599

C

- calculating number of hosts per subnet, 112–115
- Can't Fragment code (Destination Unreachable ICMP message), 279
- CBPDUs (Configuration Bridge Protocol Data Units), 39
- certification, reseller requirements, x
- Challenge Handshake Authentication Protocol (CHAP), 314–317, 535
- channel-group command, 61
- channels, ISDN, 327
- CHAP (Challenge Handshake Authentication Protocol), 314–317, 535
- CIDR (classless interdomain routing), 257–259
- CIR (committed information rate), 600
- circuit-switched WANs, 305
- Cisco 2950 switches
 - basic operation, 16–20
 - configuring, 14–16, 20–25
 - port security*, 25–27
 - single switch trunk configuration*, 81–88
 - STP
 - configuring*, 56–57
 - show commands*, 57–58
- classes of networks, 102–103
- classful routing protocols, 233
 - autosummarization, configuring, 234–237
- classless interdomain routing (CIDR), 257–259
- classless routing protocols, 233, 242–244
- clock rate command, 307
- clock sources, 308
- collision domains, 71

- commands, 395–396
 - access-class, 433
 - address-violation, 578, 585
 - bandwidth, 395
 - broadcast, 344
 - channel-group, 61
 - clock rate, 307
 - compress, 310
 - configure terminal, 580
 - controller t1, 337
 - copy nvram tftp, 586–587
 - copy running-config startup-config, 587
 - copy startup-config tftp, 586–587
 - debug, output, 168–170
 - debug dialer, 338
 - debug dialer events, 350
 - debug dialer packets, 351
 - debug ip igrp event, 172–173
 - debug ip igrp transaction, 171–173, 473
 - debug ip igrp transactions, 466
 - debug ip rip, 161, 168, 202, 210
 - debug isdn q921, 338
 - debug isdn q931, 338, 350
 - delete nvram, 587
 - delete vtp, 80, 588
 - dialer fast-idle, 337, 345
 - dialer idle-timeout, 345
 - dialer load-threshold, 361
 - dialer string, 343
 - dialer-group, 337, 342
 - dialer-list, 337
 - encapsulation, 290, 310
 - encapsulation frame-relay, 398
 - encapsulation hdlc, 311
 - erase startup-config, 587
 - frame-relay interface-dlci, 396
 - frame-relay lmi-type, 395
 - framing sf, 338
 - interface serial, 396
 - ip access-group, 432, 440
 - ip address, 14, 578
 - ip classless, 239–242
 - ip default-gateway, 14, 578
 - ip default-network, 240
 - ip mtu, 289
 - ip route, 240
 - ip route, 240
 - isdn answer1, 337
 - isdn caller, 337
 - isdn spid1, 336–337
 - isdn spid2, 337
 - isdn switch-type, 337
 - keepalive, 396
 - linecode ami, 338
 - mac-address-table permanent, 578, 583
 - mac-address-table restricted, 583
 - mac-address-table restricted static, 578
 - mtu, 289
 - network, 161–163
 - ping, 146–149, 278–280, 471
 - port secure, 584–585
 - ppp multilink, 361
 - pri-group timeslots, 338
 - router igrp, 161, 202, 209, 269
 - router rip, 161, 202, 209, 269
 - show access-lists, 433
 - show cdp neighbor detail, 481
 - show controllers bri, 338
 - show dialer interface bri, 338, 349
 - show frame-relay lmi, 472, 485
 - show frame-relay map, 469, 471, 487
 - show frame-relay pvc, 469, 490
 - show interface, 467
 - show interfaces, 578, 581
 - show interfaces bri, 338, 348
 - show ip, 16, 578, 581
 - show ip arp, 471
 - show ip interface, 433
 - show ip interface brief, 466, 473, 481
 - show ip protocol, 161, 172–173, 202, 210, 469, 473
 - show ip route, 146–148, 166, 171–173, 471
 - show isdn, 338
 - show isdn active, 349
 - show isdn status, 350
 - show mac-address-table, 578, 583–584
 - show running-config, 470, 579
 - show spantree, 595
 - show trunk, 594–595
 - show version, 16, 578, 587
 - show vlan, 590
 - show vlan-membership, 588, 595
 - show vtp, 588, 594
 - STP-related show commands, 57–58
 - trace, 281, 471
 - traffic-share, 161, 209
 - variance, 161, 176, 209
 - vlan-membership, 589

- vtp, 588–589, 594
- vtp trunk pruning-disable, 588
- write erase, 587
- comparing**
 - link-state and distance vector protocols, 160, 197–198
 - WAN protocols, 305, 308
- components of point-to-point leased lines, 306–307**
- compress command, 310**
- configuration files**
 - routers, 587
 - switches
 - copying from TFTP servers, 578*
 - copying to TFTP servers, 586*
 - displaying version information, 16, 578*
 - erasing at reload time, 587*
 - managing, 586–587*
 - saving to TFTP servers, 578*
 - updating at reload time, 587*
- configuration revision number, VTP advertisements, 77**
- configure terminal command, 580**
- configuring**
 - CHAP, 315–317, 535
 - Cisco 2950 switches, 20–27
 - DDR, dialer profiles, 344, 354, 356–359
 - default routes with ip default-network command, 240–242
 - default routing, 239–242
 - EIGRP, 209–211
 - extended IP access lists, 437
 - example, 440–442*
 - Frame Relay, 395–396
 - fully-meshed, 397–404*
 - hybrid, 410–412*
 - partial-meshed, 404–409*
 - point-to-point subinterfaces, 481*
 - without subinterfaces, 464*
 - HDLC, 310–311
 - IGRP, 161–164, 204, 210
 - metrics, 166*
 - IP addresses, 147–148
 - IPX networks, 479–481
 - ISDN
 - authentication, 315*
 - DDR, 336–338*
 - PRI, 352–354*
 - legacy DDR, 339, 345
 - sample configurations, 345, 348*
 - signaling, 342–344*
 - triggering the dial, 340–342*
 - MAC address table entries, 582, 585
 - named IP access lists, 443–444, 448
 - NAT, 269
 - dynamic NAT, 272–275*
 - static NAT, 270–271*
 - OSFP, 201–202
 - multiple area configuration, 204–209*
 - single-area configuration, 202–204*
 - PAT, 275–277
 - RIP, 161–163, 204, 210
 - debug command output, 168–170*
 - route summarization, 224–232
 - secondary IP add, 285
 - standard IP access lists, 432–435
 - static default routing, 239–240
 - STP, 56–57
 - bridge priority, 58–60*
 - EtherChannel, 60–61*
 - port cost, 58–60*
 - switches, 577, 587
 - as VTP clients/servers, 593*
 - Cisco 2950 switches, 14–16
 - default settings for 1900 series, 578–579*
 - IP support, 580–582*
 - trunks, 80, 588, 594
 - VLANs, 587
 - multiple switch configuration, 591–595*
 - single switch configuration, 588–590*
 - trunking, 79–88*
 - VLSM, 228–229
 - VTP, 594
- contiguous networks, 236**
- controller t1 command, 337**
- convergence, 179, 575**
 - of RSTP, 52–55
 - STP, 43–45, 62
- converting decimal-to-hexadecimal-to-binary values, 555, 559**
- copy nvram tftp command, 586–587**
- copy running-config startup-config command, 587**

- copy startup-config tftp command, 586–587
- copying switch configuration files from TFTP servers, 578
- count to infinity, 154, 167, 179
 - hold-down timers, 158
- creating subnet list charts, 130–136
- criteria
 - for standard access lists, 434–436
 - for STP forwarding state activation, 38–39, 62

D

- data connection process, FTP, 287
- data link layer, ISDN specifications, 329, 363
- data-link protocols
 - comparing, 308
 - configuring, 310–311
 - error-recovery, 309
 - for point-to-point leased lines, 307–308
 - PPP
 - error detection*, 312
 - looped link detection*, 312
 - LCP*, 311
 - LQM*, 313
 - magic numbers*, 313
 - Protocol Type field, 309
- DCE (data communications equipment), 376
- DDR (Dial On-Demand Routing)
 - configuring over ISDN BRI, 336–338
 - dialer profiles, configuring, 338–339, 354–359
 - dialer watch, 338
 - dialing, 344
 - legacy configuration, 339
 - connection termination*, 345
 - sample configurations*, 345, 348
 - signaling*, 342–344
 - triggering the dial*, 340–342
- DE (discard eligibility), 601
- dead interval, 194
- debug command, output, 168, 170
- debug dialer command, 338
- debug dialer events command, 350
- debug dialer packets command, 351
- debug ip igrp event command, 172–173
- debug ip igrp transaction command, 171–173, 473
- debug ip igrp transactions command, 466
- debug ip rip command, 161, 168, 202, 210
- debug isdn q921 command, 338
- debug isdn q931 command, 338, 350
- decimal values, converting to hexadecimal
 - and binary values, 555–559
- default port costs, STP, 42, 62
- default routes, configuring, 240–242
- delete nvram command, 587
- delete vtp command, 80, 588
- deny statements (access lists), 429
- deploying
 - Frame Relay networks
 - configuring*, 464–466
 - planning phase*, 462–463
 - verify*, 466–473
 - IPX networks
 - configuring*, 479–481
 - planning phase*, 474–478
 - verifying configuration*, 481–490
- deriving subnet numbers without binary conversion, 121–127
- designated ports, 39–41
- Destination Unreachable messages, 277–280, 295
- devices, TE2, 332
- dialer fast-idle command, 337, 345
- dialer groups (ISDN), enabling, 337
- dialer idle-timeout command, 345
- dialer load-threshold command, 361
- dialer profiles, configuring, 338–339, 354–359
- dialer string command, 343
- dialer watch, 338
- dialer-group command, 337, 342
- dialer-list command, 337
- Dijkstra SPF algorithm, 178, 575
- directed broadcast address, identifying, 118–119
- directly connected routes, routing table updates, 151
- directly connected subnets, 150
- discontiguous networks, 236
- distance vector routing protocols, 153, 567
 - administrative distance, 176–177
 - autosummarization, 236
 - comparing, 160
 - equal-cost routes, 173–176

IGRP
 configuring, 161–164, 204, 210
 metrics, 166

loop avoidance, 153, 179
 count to infinity, 154, 179
 hold-down timers, 158–159
 poison reverse, 157
 route poisoning, 154
 split horizon, 155–157
 triggered updates, 160

RIP
 configuring, 161–163, 204, 210
 debug command output, 168, 170
 hop count, 152–153
 migration to IGRP, 170–173

route aggregation, 236
 routing behavior, 150
 routing tables, 151, 198, 213

DLCI (data-link connection identifier), 378, 383–387, 602
 global addressing, 385–387
 local addressing, 384

DTE (data terminal equipment), 376
 DUAL (Diffusing Update Algorithm), 179, 575

dynamic MAC addresses, 582
 dynamic NAT, 264–265
 configuring, 272–275

E

Echo ICMP message, 277–278, 295
 Echo Request/Reply messages, 278
 edges, 50

EIGRP (Enhanced IGRP), 198–199
 configuring, 209–211
 features of, 201
 loop avoidance, 199–200

electing root bridge (STP), 40–41
 encapsulation, IPX, 464
 encapsulation command, 290, 310
 encapsulation frame-relay command, 395–396, 398
 encapsulation hdlc command, 311
 equal-cost routes, 173, 175–176
 erase startup-config command, 587

error detection, 312
 error recovery, WAN protocols, 309
 E-series ISDN protocols, 328
 ESF (Extended Super Frame), 336
 EtherChannel, 47
 configuring, 60–61
 Ethernet edges, 50
 extended IP access lists, 427, 430, 437
 example, 440–442
 filtering logic, 439
 matching options, 438, 450
 exterior routing protocols, 178, 575

F

FCS (frame check sequence), 309
 features of EIGRP, 201
 FECN (forward explicit congestion notification), 603

filtering packets
 extended IP access lists, 437
 example, 440–442
 named IP access lists, 443–444, 448
 standard access lists, 427
 configuring, 433–435
 features, 429
 matching logic, 429–430
 wildcard masks, 430–431

filtering process of switches, 11

flash updates, 160

Forward Delay Timer, STP, 43

forwarding, 36, 47

 unknown unicast frames on switches, 13

forwarding process of switches, 11

forwarding state (STP), 38–39, 45, 62–63
 lowest-cost hello, calculating, 41

fragmentation, 288

Frame Relay, xxii, 376

 broadcast handling, 392–393
 configuring, 395–396

fully-meshed, 397–404

hybrid, 410–412

partial-meshed, 404–409

point-to-point subinterfaces, 481

without subinterfaces, 464

 DLCI, 383–387

- Layer 2 address mappings, 399–404
- Layer 3 address mappings, 388–391, 415
- LMI, 381–383
- maps, static, 464
- network deployment
 - planning*, 462–463
 - verification*, 466–473
- partial-mesh, configuring, 404–409
- Protocol Type field, lack of, 383
- VCs, 377–381

- frame-relay interface-dlci command**, 396
- frame-relay lmi-type command**, 395
- framing**, 307, 335–336
- framing sf command**, 338
- FRF.5**, 394
- FRF.8**, 394
- FTP (File Transfer Protocol)**, 286–287
 - data connection process, 287
- FTP control connections**, 286
- fully-meshed Frame Relay networks**, 380
 - configuring, 397–404
- function groups, ISDN**, 331, 333–334

G

- gateway of last resort, 240
- gateways, default, 14, 578
- global addressing, 385, 387
- group addresses, 10

H

- half-duplex switch ports, 580, 582
- HDB3 (High-Density Bipolar 3)**, 335
- HDLC (High-Level Data Link Control)**,
 - configuring, 310–311
- hello BPDUs, 40
- Hello packets (OSPF), 193
- Hello timer, STP, 43
- hexadecimal values, converting to decimal
 - and binary values, 555–559
- hold-down timers, 154, 158–159, 179
- home-based ISDN, 334
- hop count, 152–153
- Host Unreachable code (Destination Unreachable ICMP message), 279
- hybrid Frame Relay networks, configuring, 410–412

I-J

ICMP (Internet Control Message Protocol) messages

- Destination Unreachable, 277–280, 295
- Echo, 277–278, 295
- Echo Request/Reply, 278
 - sending/receiving*, 161, 202, 269
- Parameter Problem, 277, 295
- Redirect, 277, 283, 295
- Source Quench, 277, 295
- Time Exceeded, 277, 280–283, 295

identifying

- subnet broadcast address, 118–119
- subnet number in subnet masks, 116–117
- valid IP address range in subnets, 119–121
- valid subnets based on network number, 130–133

IEEE 802.1Q, 73

- versus ISL, 74–75

IEEE 802.1w. *See* RSTP

IGRP (Interior Gateway Routing Protocol)

- administrative distance, 176–177
- configuring, 161–164, 204, 210
- features, 160, 180, 574
- metrics, 166
- migration from RIP, 170–173
- packets, displaying log messages, 161, 202
- versus RIP, 160, 180, 574

infinite metrics, 155

infinite-distance routes, 156

inside global addresses, 263

inside local addresses, 263

interesting packets, 340

interface serial command, 396

interfaces. *See also* ports

- displaying status, 578
- switches, numbering, 579

interior routing protocols, 178, 575

Inverse ARP, 402–403, 473

IP (Internet Protocol), 238

- CIDR, 257–259
- configuring, 280, 464
 - on switches*, 580–582
- IP Version 4, 257
- IP Version 6, 257

- NAT, 257, 269
- Private Addressing, 257, 260
- routing protocols, 568
 - displaying details*, 161, 202, 210
- routing tables, displaying, 161, 202, 210
- IP access lists**
 - extended access lists
 - displaying details of*, 433, 440
 - matching options*, 438, 450
 - standard access lists, 427
 - displaying details of*, 433, 440
 - matching options*, 438, 450
 - planning*, 478
- ip access-group command**, 432, 440
- ip address command**, 14, 578
- IP addresses**
 - address classes, 102–103
 - Boolean AND operation, 109–111
 - calculating number of hosts per subnet, 112–115
 - configuring, 147–148
 - displaying, 16, 578
 - identifying address structure, 112–115
 - NAT, 260, 263, 267
 - configuring*, 269–275
 - dynamic NAT*, 264–265
 - static NAT*, 261–263
 - translating overlapping addresses*, 267–268
 - PAT overloading, 265–266
 - prefix notation, 111
 - secondary addresses, 283–285
 - setting, 14, 578
 - subnet list chart, creating, 130–136
 - subnetting, 104
 - binary conversion*, 107–109
 - deriving subnet broadcast address*, 120, 126
 - identifying subnet broadcast address*, 118–119
 - identifying subnet number in subnet masks*, 116–117
 - identifying valid IP address range*, 119–121
 - identifying valid subnets based on network number*, 130–133
 - selecting correct subnet masks based on given criteria*, 127–129
 - ip classless command**, 239–242
 - ip default-gateway command**, 14, 578
 - ip default-network command**, 240
 - ip mtu command**, 289
 - ip route command**, 240
 - IPX (Internetwork Packet Exchange)**
 - addresses
 - displaying for neighboring routers*, 489
 - secondary addresses*, 481
 - configuring, 464
 - encapsulation, 464
 - accommodating multiple types*, 481
 - network deployment
 - planning*, 474–478
 - verifying configuration*, 481–490
 - ISDN (Integrated Services Digital Network)**
 - BRI, 327
 - DDR parameters, displaying*, 338
 - channels, 327
 - CHAP, 314–315
 - configuring*, 315–317, 535
 - DDR, 336–338
 - dialing*, 344
 - legacy configuration*, 338–339
 - dialer groups, enabling, 337
 - encoding, 335–336
 - framing, 335–336
 - function groups, 331–334
 - home-based, 334
 - incoming call numbers, defining, 337
 - Layer 2 messages, displaying, 338
 - Layer 3 messages, displaying, 338
 - legacy DDR, configuring, 338–339
 - modems, 334
 - Multilink PPP, configuring, 359–362
 - out-of-band signaling, 330
 - PAP, 314–315
 - PRI, 327
 - E1/T1 controller configuration*, 352–354
 - function groups*, 334
 - reference points*, 331–334
 - reference points, 331–334
 - signaling, 339
 - SPIDs, 330
 - defining*, 337
 - status information, displaying, 338

- isdn answer1 command, 337
- isdn caller command, 337
- isdn spid1 command, 336–337
- isdn spid2 command, 337
- isdn switch-type command, 337
- I-series ISDN protocols, 328
- ISL (Inter-Switch Link) trunking, 73, 289–290, 295
 - versus 802.1Q, 74–75
 - VTP pruning, 78–79

K–L

- keepalive command, 396
- LAPF (Link Access Procedure Frame Bearer Services), 382, 604
- Layer 3 addressing, Frame Relay, 388–391, 415
 - fully-meshed networks, configuring, 397–399
 - hybrid networks, configuring, 409–413
 - Layer 2 address mappings, 399–404
 - partially-meshed networks, configuring, 404–409
- LCP (Link Control Protocol), 311
- learning process of switches, 10
- learning state (STP), 45, 63
- leased line WANs, 305
 - data-link protocols, 307–308
 - physical components, 306–307
- legacy DDR, 338–339
 - connection termination, 345
 - sample configurations, 345, 348
 - signaling, 342–344
 - triggering the dial, 340–342
- linecode ami command, 338
- links, 50
- link-state protocols, 178, 575
 - OSPF
 - areas, 195, 197
 - configuring, 201–202
 - dead interval, 194
 - Hello packets, 193
 - loop avoidance, 194
 - multiple area configuration, 204–209
 - neighbors, 192

- scalability, 195–197
 - single-area configuration, 202–204
 - SPF algorithm, 192
 - stub areas, 197
- versus distance vector protocols, 191, 197–198
- listening state (STP), 45, 63
- LMI (Local Management Interface), 376–378, 381–383, 604
- local addressing, 384
- loop avoidance
 - distance vector protocol features, 153, 179
 - hold-down timers, 158–159
 - poison reverse, 157
 - route poisoning, 154
 - split horizon, 155–157
 - triggered updates, 160
- EIGRP, 199–200
- OSPF, 194
- STP, 36, 38, 47
 - convergence, 43–45, 62
 - designated port, 41
 - EtherChannel, 47
 - forwarding state, 38–39, 62
 - PortFast, 48
 - root bridge election, 40–41
 - timers, 43
- looped link detection, PPP, 312
- loops, troubleshooting, 154
- LQM (Link Quality Monitoring), 312–313
- LSAs (link-state advertisements), 192
- LSUs (link-state updates), 192

M

- MAC addresses
 - broadcast addresses, 10
 - dynamic, 582
 - LAN card addressing, 10
 - MAC address table, 11
 - displaying, 16, 578
 - multicast addresses, 10
 - restricted-static entries, 582

- switches
 - learning process*, 12
 - permanent settings*, 578
 - restricted settings*, 578
- mac-address-table permanent command, 578, 583
- mac-address-table restricted command, 583
- mac-address-table restricted static command, 578
- magic numbers, 313
- masks, network masks, 103
- matching packet filtering criteria
 - extended IP access lists, 439
 - standard access lists, 434–436
- MaxAge timer, STP, 43
- maximum transmission unit (MTU), 288
- MD5 (Message Digest 5), 314
- messages, ICMP, 277
 - Destination Unreachable, 277–280, 295
 - Echo, 277–278, 295
 - Echo Request/Reply, 278
 - sending/receiving*, 161, 202, 269
 - Parameter Problem, 277, 295
 - Redirect, 277, 283, 295
 - Source Quench, 277, 295
 - Time Exceeded, 277, 280–283, 295
- metrics
 - administrative distance, 176–177
 - hop count, 152–153
 - IGRP, 166
 - configuring*, 166
 - infinite, 155
- migrating to IGRP, 170–173
- modems, ISDN, 334
- monitoring EtherChannel, 60–61
- MTU (maximum transmission unit), 288
- mtu command, 289
- multiaccess networks, Frame Relay, 376
 - broadcast handling, 392
 - configuring, 395–412
 - DLCI, 383–387
 - Layer 3 addressing, 388–391, 415
 - LMI, 381–383
 - VCs, 377–381
- multicast addresses, 10
- Multilink PPP, 359–362
- multiple area OSPF configuration, 204–209
- multiple switch VLAN configuration, 591–595

N

- named IP access lists, 443–444, 448
- naming VLANs, 80, 588–589
- NAT (Network Address Translation), 257, 260, 263, 267–269. *See also* PAT
 - configuring, 269
 - dynamic NAT, 264–265
 - configuring*, 272–275
 - static NAT, 261–263
 - configuring*, 270–271
 - translating overlapping addresses, 267–268
- NBMA (nonbroadcast multiaccess)
 - networks, 378, 605
- neighbors (OSPF), 192
- Network Address Translation. *See* NAT
- network command, 161–163
- network layer, ISDN specifications, 329, 363
- network numbers
 - aggregating with CIDR, 258–259
 - IPX, planning, 474
- Network Unreachable code (Destination Unreachable ICMP message), 279
- networks
 - Class B network masks, 103
 - Class C network masks, 103
 - contiguous, 236
 - Frame Relay. *See* Frame Relay
 - IPX. *See* IPX
 - private Internets, 259
- next-hop routers, routing table entries, 151
- no address-violation command, 585
- no debug all command, 171
- no keepalive command, 472
- no router rip command, 172
- NT1/NT2 (Network Termination Type 1/ Network Termination Type 2), ISDN
 - function group, 333
- numbered IP access lists, comparing to
 - named IP access lists, 443
- numbering switch ports, 579

O

optional STP features

- EtherChannel, 47
- PortFast, 48

OSI reference model layers, ISDN specifications, 329, 363

OSPF (Open Shortest Path First), 190–191

- areas, 195–197
- configuring, 201–202
 - multiple area configuration, 204–209*
 - single-area configuration, 202–204*
- dead interval, 194
- Hello packets, 193
- loop avoidance, 194
- neighbors, 192
- scalability, 195–197
- SPF algorithm, 192
- stub areas, 197

out-of-band signaling, ISDN, 330

outside global addresses, 263

outside local addresses, 263

P

packet filtering

- extended IP access lists, 437
 - example, 440–442*
- named IP access lists, 443–444, 448
- standard access lists, 427
 - configuring, 433–435*
 - features, 429*
 - matching logic, 429–430*
 - wildcard masks, 430–431*

packets

- default routing, 239–242
- fragmentation, 288
- IGRP log messages, displaying, 161, 202
- interesting, 340
- MTU, 288

packet-switched WANs, 305

PAP (Password Authentication Protocol), 314–315

Parameter Problem ICMP message, 277, 295

partial-mesh Frame Relay networks, 380

- configuring, 404, 406–409

PAT (Port Address Translation), 265–266

- configuring, 275–277

periodic updates, 150

permit statements (access lists), 429

physical layer ISDN specifications, 329, 363

ping command, 146–149, 278–280, 471

planning IPX networks, 474–478

point-to-point leased lines

- components of, 306–307
- data-link protocols, 307–308

poison reverse, 154

port cost, manipulating, 58–60

port roles of RSTP, 50, 52

port secure command, 584–585

port states of RSTP, 50

Port Unreachable code (Destination Unreachable ICMP message), 279

PortFast, 48

ports

- switches
 - address violations, 585*
 - assigning to VLANs, 80, 588–589*
 - full-duplex, 580–582*
 - half-duplex, 580–582*
 - IP configuration, verifying, 581–582*
 - MAC addresses, limiting associations with, 583–585*
 - numbering, 579*
 - security, configuring, 25–27, 583–585, 578*
 - VLAN membership, displaying, 588*

- vtv ports, controlling access with IP access lists, 446

PPP (Point-to-Point Protocol), 310, 317

- configuring, 310–311
- error detection, 312
- LCP, 311
- looped link detection, 312
- LQM, 313
- magic numbers, 313

ppp multilink command, 361

prefix notation, 111

preventing routing loops

with RSTP

- convergence*, 52–55
- physical connectivity*, 49–50
- port roles*, 50–52
- port states*, 50

with STP, 36–38

- convergence*, 43–45, 62
- designated port*, 41
- forwarding state*, 38–39, 62
- hold-down timers*, 158–159
- poison reverse*, 157
- root bridge election*, 40–41
- route poisoning*, 154
- split horizon*, 155–157
- timers*, 43
- triggered updates*, 160

PRI (Primary Rate Interface), 327

- E1/T1 controller configuration, 352–354
- function groups, 334
- reference points, 334

pri-group timeslots command, 338**private addressing**, 257, 260**private Internets**, 259**Protocol Type field**, 309**Protocol Unreachable code (Destination**

Unreachable ICMP message), 279

pruning

- VLANs, 80, 588
- VTP trunks, 78–79

PVCs (permanent virtual circuits), 377, 380

DLCI, 383–387

Q-R**Q-series ISDN protocols**, 328**R ISDN reference point**, 334**Redirect ICMP message**, 277, 283, 295**Redirect messages**, 283**reference points**

- ISDN, 331, 333–334
- ISDN PRI, 334

resellers, required certification, x**restricted-static MAC address entries**, 582**RIP (Routing Information Protocol)**

- administrative distance, 176–177
- configuring, 161–163, 204, 210
 - debug command output*, 168–170
- features, 160, 180, 574
- hop count, 152–153
- migration to IGRP, 170–173
- updates, displaying log messages, 161, 202
- versus IGRP, 160, 180, 574

root bridge (Spanning Tree)

- election process, 40–41
- root port, 39, 62

route aggregation, 236**route poisoning**, 154, 179**route summarization**, 196, 223–228.*See also* VLSM

autosummarization, 233–237

configuring, 230–232

routed protocols, 567**router igrp command**, 161, 202, 209, 269**router rip command**, 161, 202, 209, 269**routers**

configuring

IP, 280, 464

IPX, 464

configuration files

copying to TFTP servers, 587*erasing at reload time*, 587*updating at reload time*, 587

version information, displaying, 587

routes, troubleshooting multiple routes to the same subnet, 173**routing loops, preventing**

with RSTP, 49–50

convergence, 52–55*port roles*, 50–52*port states*, 50

with STP, 36, 38, 47

convergence, 43–45, 62*designated port*, 41*forwarding state*, 38–39, 62*root bridge election*, 40–41*root ports*, 41*timers*, 43

routing protocols, 178–179, 567, 575

- classful, 233
 - autosummarization, 234–237*
- classless, 233
- comparison of, 568
- distance vector, 567
 - autosummarization, 236*
 - comparing, 160*
 - convergence, 154, 179*
 - equal-cost routes, 173, 175–176*
 - hold-down timers, 158–159*
 - IGRP, 164, 166*
 - loop avoidance, 153, 179*
 - poison reverse, 157*
 - route aggregation, 236*
 - route poisoning, 154*
 - routing behavior, 150*
 - split horizon, 155–157*
 - triggered updates, 160*
- link-state, OSPF
 - areas, 195, 197*
 - configuring, 201–202*
 - dead interval, 194*
 - Hello packets, 193*
 - loop avoidance, 194*
 - multiple area configuration, 204–209*
 - neighbors, 192*
 - scalability, 195–197*
 - single-area configuration, 202–204*
 - SPF algorithm, 192*
 - stub areas, 197*
- routing tables, displaying, 161, 202, 210
- routing update timers, 153
- RSTP (Rapid STP), 48**
 - convergence, 52–55
 - edges, 50
 - links, 50
 - physical connectivity, 49–50
 - port roles, 50–52
 - port states, 50

S

- S/T ISDN reference point, 334
- saving switch configuration files to TFTP servers, 578

- scaling
 - IP addresses, PAT, 265–266
 - OSPF, 195–197
- SDLC (Synchronous Data Link Control), 310, 317**
- secondary IP addresses, 283–285
- security
 - access lists
 - extended access lists, 430, 437, 440–442*
 - named IP access lists, 443–444, 448*
 - matching logic, 429–430*
 - standard access lists, 427–429, 433–435*
 - wildcard masks, 430–431*
 - authentication
 - CHAP, 314–315*
 - PAP, 314–315*
 - switch ports, setting, 578
- servers (TFTP), copying switch configuration files from, 578
- service interworking, 393–394
- SF (Super Frame), 336**
- shortcuts, deriving subnet numbers without binary values, 121–127
- show access-lists command, 433
- show cdp neighbor detail command, 481
- show controllers bri command, 338
- show dialer interface bri command, 338, 349
- show frame-relay lmi command, 472, 485
- show frame-relay map command, 469–471, 487
- show frame-relay pvc command, 469, 490
- show interface command, 467
- show interfaces bri command, 338, 348
- show interfaces command, 578, 581
- show ip command, 16, 578, 581
- show ip arp command, 471
- show ip interface command, 433
- show ip interface brief command, 466, 473, 481
- show ip protocol command, 161, 172–173, 202, 210, 469, 473
- show ip route command, 146–148, 166, 171–173, 471
- show isdn active command, 349
- show isdn command, 338
- show isdn status command, 350

- show mac-address-table command, 578, 583–584
- show running-config command, 470, 579
- show spantree command, 595
- show trunk command, 594–595
- show version command, 16, 578, 587
- show vlan command, 590
- show vlan-membership command, 588, 595
- show vtp command, 588, 594
- signal-area OSPF configuration, 202–204
- signaling
 - DDR, 343–344
 - ISDN, 339
- single switch VLAN configuration, 588–590
- Source Quench ICMP message, 277, 295
- Spanning Tree Protocol. *See* STP
- SPF algorithm, 192
- SPIDs (service profile identifiers), 330
 - defining, 337
- split horizon, 154–157, 167, 179
- split horizon with poison reverse, 154, 157, 179
- standard access lists, 427
- standard IP access lists, 427
 - applying to vty ports, 446
 - configuring, 432–435
 - displaying, 433, 440
 - features, 429
 - matching options, 429–430, 438, 450
 - planning, 478
- static default routing, configuring, 239–240
- static Frame Relay maps, 464
- static NAT, 261, 263
 - configuring, 270–271
- STP (Spanning Tree Protocol)
 - blocking state, 39, 62
 - bridge priority, changing, 58–60
 - CBPDUs, 39
 - configuration status, displaying for switches, 595–596
 - configuring, 56–57
 - convergence, 43–45, 62
 - designated port, 41
 - EtherChannel, 47
 - configuring, 60–61
 - features of, 46, 64
 - forwarding state, 39, 62
 - lowest-cost hello, calculating*, 41
 - functions of, 45–46, 64
 - port cost, changing, 58–60
 - port states, 42
 - PortFast, 48
 - root bridge, 39, 62
 - election process*, 40–41
 - root port, 41
 - show commands, 57–58
 - timers, 43
 - VLAN information, displaying, 588
- stub areas (OSPF), 197
- subinterfaces, 390
- subnet chart, creating, 122, 130–136
- subnet masks
 - binary conversion, 114
 - VLSM, configuring, 228–229
- subnet numbers, displaying, 489
- subnets, 104
 - binary conversion, 107–109
 - Boolean AND operation, 110–111
 - calculating number of hosts/subnets, 112–115
 - contiguous, 236
 - deriving subnet broadcast address, 120, 126
 - directly connected, 150
 - equal-cost routes, 173–176
 - finding answers without binary, 121–125
 - identifying subnet broadcast address, 118–119
 - identifying subnet number, 116–117
 - identifying valid IP address range, 119–121
 - identifying valid subnets based on network number, 130–133
 - prefix notation, 111
 - selecting correct subnet masks based on given criteria, 127–129
- summary routes
 - autosummarization, 233–235, 237
 - configuring, 224–228, 230–232
- SVCs (switched virtual circuits), 377, 380, 607

switches

- address violations, 578
- autonegotiation, 580
- basic logic, 14
- Cisco 2950
 - basic operation*, 16–20
 - configuring*, 14–16, 20–25
 - port security*, 25–27
- configuring, 577, 587
 - as VTP clients/servers*, 593
 - duplex*, 580–582
 - IP support*, 58–582
- configuration files
 - copying from TFTP servers*, 578
 - copying to TFTP servers*, 586
 - displaying version information*, 16, 578
 - erasing at reload time*, 587
 - managing*, 586–587
 - saving to TFTP servers*, 578
 - updating at reload time*, 587
- filtering process, 11
- forwarding process, 11
- learning process, 10
- MAC addresses
 - displaying table contents*, 582, 585
 - learning process*, 12
- ports
 - address violations*, 585
 - assigning to VLANs*, 80, 588–589
 - duplex settings, verifyin*, 581–582
 - full-duplex*, 580–582
 - half-duplex*, 580–582
 - IP configuration, verifying*, 581–582
 - MAC addresses, limiting associations with*, 583–585
 - numbering*, 579
 - security, setting*, 578, 583–585
 - VLAN membership, displaying*, 588
- STP
 - configuring*, 56–57
 - show commands*, 57–58
 - status, displaying*, 595–596
- system files, managing, 586–587

- trunking, 72
 - 802.1Q*, 73–75
 - configuring*, 79–88
 - ISL*, 73
 - VTP*, 76–79
- unknown unicast frames, forwarding, 13
- version information, displaying, 587
- VTP configuration information, 594
- synchronization**, 54
- Synchronous Data Link Control**. *See* SDLC
- synchronous serial data-link protocols, comparing**, 308
- synchronous serial leased lines**, 308
- syntax**
 - extended IP access lists, 441
 - named IP access lists, 443
 - standard access lists, 434
- system files (switches)**, 586–587

T

- T1 controllers, ISDN PRI configuration**, 352–354
- TA (Terminal adapter), ISDN function group**, 333
- TCP/IP**
 - FTP, 286–287
 - ICMP, 277
 - Destination Unreachable messages*, 277–280, 295
 - Echo messages*, 277–278, 295
 - Echo Request/Reply messages*, 278
 - Parameter Problem messages*, 277, 295
 - Redirect messages*, 277, 283, 295
 - Source Quench messages*, 277, 295
 - Time Exceeded messages*, 277, 280, 282, 295
 - IP addressing, 112–113, 115
 - address classes*, 102–103
 - CIDR*, 258
 - configuring*, 147–148

- deriving subnet broadcast address*, 126
 - dynamic*, 264–265
 - NAT, 260–275
 - PAT, 265–266
 - private addressing*, 260
 - secondary addresses*, 283–285
 - subnet list chart, creating*, 130–136
 - subnets*, 104, 107–109
- TFTP, 287–288, 295
- TE1 (Terminal Equipment 1), ISDN function group, 333
- TE2 (Terminal Equipment 2), ISDN function group, 332–333
- TFTP (Trivial File Transfer Protocol), configuration file management, 287–288, 295
- Time Exceeded ICMP messages, 277, 280–283, 295
- timers
 - routing update timers, 153
 - STP, 43
- tooggling between classful and classless routing, 243–244
- trace command, 281, 471
- traffic filtering with access lists, 427–429.
 - See also* access lists
- traffic-share command, 161, 209
- transparent mode (VTP), 77–78
 - enabling, 589
- triggered updates, 154, 160, 179
- triggering the dial, 340
- troubleshooting multiple routes to the same subnet, 173
- trunk command, 588, 591
- trunks, 72
 - 802.1Q, 73
 - versus ISL*, 74–75
 - configuring, 79–88, 588, 594
 - ISL, 73, 289–290, 295
 - status, displaying, 80, 588
 - verifying configuration, 595
 - VTP, 76–78
 - pruning*, 79

U-V

- U ISDN reference point, 334
- unknown unicast frames, forwarding process, 13
- unreachable codes (ICMP), 279

V

- valid IP addresses in subnets, identifying, 119, 121
- variance command, 161, 176, 209
- VCs (virtual circuits), 377–381
 - PVCs, DLCI, 383–387
- vlan command, 589
- vlan-membership command, 589
- VLANs
 - collision domains, 71
 - configuring, 587
 - for multiple switches*, 591–595
 - for single switch*, 588, 590
 - defining, 80, 588
 - information, displaying, 80, 588
 - membership, displaying, 588
 - naming, 80, 588–589
 - numbering, 589
 - parameters, verifying, 590
 - pruning, 78–79
 - disabling*, 80, 588
 - Spanning Tree information, displaying, 588
 - switch ports, assigning to, 80, 588–589
 - trunking, 72
 - 802.1Q, 73–75
 - configuring*, 79–88, 588, 594
 - ISL, 73, 289–290, 295
 - status, displaying*, 80, 588
 - verifying configuration*, 595
- VTP
 - advertisements*, 76
 - client mode*, 77–78, 90
 - clients, configuring switches as*, 593
 - configuring*, 594
 - displaying configuration information*, 594
 - mechanics of*, 78, 90
 - modes of operation*, 77
 - parameters, defining*, 80, 588

- parameters, resetting to defaults,*
80, 588
 - pruning,* 78–79
 - server mode,* 77–78, 90
 - servers, configuring switches as,*
593
 - status, displaying,* 80, 588
 - transparent mode,* 77–78, 90, 589
 - VLSMs (variable-length subnet masks),**
configuring, 223, 228–229
 - VTP (VLAN Trunking Protocol), 76**
 - advertisements, 76
 - client mode, 77–78, 90
 - configuration, 594
 - configuration information,
displaying, 594
 - mechanics of, 78, 90
 - modes of operation, 76–78
 - parameters
 - defining,* 80, 588
 - resetting to defaults,* 80, 588
 - pruning, 78–79
 - server mode, 77–78, 90
 - status, displaying, 80, 588
 - transparent mode, 77–78, 90, 589
 - vtp command,** 588–589, 594
 - vtp trunk pruning-disable command,** 588
 - vty ports**
 - access lists, applying, 446
 - controlling access with IP access
lists, 446
- ISDN, 326
 - channels,* 327
 - CHAP, 314–315
 - DDR, 336–338
 - encoding,* 335–336
 - framing,* 335–336
 - function groups,* 331–334
 - home-based,* 334
 - legacy DDR configuration,* 339–
345, 348
 - multilink PPP,* 359–362
 - out-of-band signaling,* 330
 - PAP, 314–315
 - PRI, 352–354
 - protocols,* 328, 363
 - reference points,* 331–334
 - SPIDs, 330
 - leased lines
 - components of,* 306–307
 - data-link protocols,* 307–308
 - PPP, 310, 317
 - error detection,* 312
 - LCP, 311
 - looped link detection,* 312
 - wildcard masks,** 430–431
 - write erase command,** 587

W-Z

WANs

- comparing, 305
- data-link protocols
 - comparing,* 308
 - configuring,* 310–311
 - Protocol Type field,* 309
- error recovery, 309
- Frame Relay, xxii, 376
 - broadcast handling,* 392
 - configuring,* 395–412
 - DLCI, 383–387
 - Layer 3 addressing,* 388–391, 415
 - LMI, 381–383
 - VCs, 377–381