

Index

Symbols & Numerics

? (question mark), CLI help system, 179

10Base2, 53–54, 60

LAN switching, 60–63

repeaters, 55

10Base5, 53–54, 60

LAN switching, 60–63

repeaters, 55

10BaseT

full-duplex, 71

half-duplex, 59

LAN switching, 60–63

10 Gigabit Ethernet, 299–300

10-Mbps Ethernet, 53–56, 60–61

cabling, 57–58

hubs, 59–60

switching, 60–63

802.11 WLANs, 301–302

802.1q trunking, 266–267

A

access links, 97

access lists, 486–487

accessing CLI, 176–177, 214, 221

multiple Telnet connections, 178

on Cisco 2950 switches, 215

passwords, 177

ACK field, TCP connection

establishment, 158

active configuration, 188

adding connected routes to routing tables,
376–379

address classes, 122–124, 319–320

addresses, 51

addressing schemes, 118

AppleTalk addresses

grouping, 118

structure, 119, 139

burned-in addresses, 65

group addresses, 64

IP addresses

Class A networks, 122

Class B networks, 122

Class C networks, 122

grouping, 118

hostnames, displaying, 369

interfaces, displaying, 369

structure, 119, 139

IPX addresses

grouping, 118

structure, 119, 139

MAC addresses, 64

BIAs, 64

broadcast addresses, 64, 237

components, 64

LAN card addressing, 64, 237

multicast addresses, 65, 237

OUI, 64

unicast, 64

network layer, 118–119

amplitude modulation, 443

analog modems

baud, 444

installing, 445–446

modulation, 442–444

PPP, 444

standards, 446–447

analog signals, 436

converting to digital, 438–439

Nyquist's theorem, 440

ANSI (American National Standards Institute), 53, 87
AppleTalk addresses
 cable ranges, 118
 grouping, 118
 structure, 119, 139
application layer
 OSI model, 33
 TCP/IP model, 22–24
APs (access points), 301
arbitration, 50
ARP (Address Resolution Protocol), 117, 127–129, 135
 cache, displaying, 369
AS (autonomous system), 410
asynchronous data links, 95, 577
asynchronous serial leased lines, 95, 588
ATM (Asynchronous Transfer Mode), 101
attenuation, 55
autonegotiation, 244
auxiliary ports, 177

B

back-to-back serial connections, 88–89
balanced hybrid protocols, 421
 EIGRP, 419–420
bandwidth, router configuration, 380
BGP (Border Gateway Protocol), 410–411
BIAs (burned-in addresses), 64
binary values, converting to decimal and hexadecimal values, 324–326, 565, 569
bitwise Boolean AND operation, 327
blocking, 248
Boolean AND operation, 326–328, 333–335
boot field, 199
boot sequence (Cisco IOS), 197–199
boot system command, 199

boot system flash command, 199, 203
boot system tftp command, 199, 203
BOOTP, 130, 132
BPDUs (bridge protocol data units), 248
BRI (Basic Rate Interface), 449, 452
bridge tables, 237–238
bridges
 frame filtering, 238
 MAC address learning process, 239
 transparent, 236
broadcast addresses, 65
 MAC addresses, 64, 237
broadcast domains, 246–247, 253
broadcast firewalls, 246
burned-in addresses, 65

C

cable modems, 460
 two-way communication, 462
 upstream data, 463
cable ranges (AppleTalk), 118
cabling, 287
 10BASE-T, 57–58
 coaxial, 291–293
 Ethernet standards, 298
 Fast Ethernet, 68
 fiber-optic, 293
 connectors, 295–296
 MM, 294–295
 SM, 294
 interference, 288
 shielded, 288
 twisted pair, 288
 UTP, 289–290
 connectors, 290–291
 standards, 290

- WAN standards, 85–86
 - clock rate*, 88
 - link speeds*, 89–90
 - maximum speeds*, 87
- calculating hosts per subnet, 329–332
- call setup, ISDN, 449–450
- Can't Fragment code (Destination Unreachable ICMP message), 385
- carrier sense multiple access collision detect (CSMA/CD), 50, 55
- CatOS, 214
- CATV
 - drop cable, splitting, 461
 - head-end site, 460
 - MCNS, 463
- CDP (Cisco Discovery Protocol), 392–395, 494
- cdp enable command, 393
- cdp run command, 393
- cells (ATM), reassembly, 101
- channels, ISDN, 449
- CIDR (classless interdomain routing), 351–353
- CIR (committed information rate), 99
- Cisco 2950 switches, 213
 - CatOS, 214
 - CLI, 215
 - configuring, 220
 - initial configuration mode, 218–220
 - initialization, 216
 - POST*, 216–217
- Cisco Discovery Protocol. *See* CDP
- Cisco IOS
 - boot sequence, 197–199
 - CLI
 - accessing*, 176–177
 - help system*, 179
 - setup mode*, 190–194
 - configuration files
 - managing*, 188–189
 - updating*, 182
 - example configuration, 183–185
 - IP configuration commands, 368–369
 - privileged EXEC mode, 178
 - user EXEC mode, 178
- Cisco ISL (Inter-Switch Link), 266
- Class B network masks, 320
- Class C network masks, 320
- classes of networks, 122–124, 319–320
- classifying interior routing protocols, 409–410
- classless interdomain routing (CIDR), 351–353
- CLI (command-line interface), 181, 201
 - accessing, 176–177, 214–215, 221
 - commands, recalling, 180
 - configuration mode, 182–183
 - help system, 179
 - passwords, 176–177
 - privileged EXEC mode, returning to, 183
 - setup mode, 190–194
 - user EXEC mode, 181, 201
- clock rate, 88
 - router configuration, 380
- clock sources, 95, 579
- coaxial cabling, 291–293
- codecs, 439
- collision domains, 60, 245–247, 253
- collisions, reducing with LAN switching, 60–63
- commands
 - boot system, 199
 - boot system flash, 199, 203
 - boot system tftp, 199, 203
 - cdp enable, 393
 - cdp run, 393
 - configuration mode end, 183
 - copy, 202
 - copy tftp flash, 197
 - debug ip packet, 369
 - editing in CLI, 180
 - enable secret, 372
 - global commands, 182
 - hostname, 183
 - interface, 182
 - interface ethernet 0, 183
 - ip address, 183, 368
 - ip domain-lookup, 368, 388
 - ip domain-name, 388
 - ip host, 368, 388
 - ip name-server, 368, 388
 - ip netmask-format, 368
 - ip routing, 368
 - key commands, Ctrl+z, 183
 - line aux, 177, 200
 - line console, 177, 200
 - line vty, 177–178, 200
 - login, 178

- no cdp enable, 393
- no cdp run, 393
- no debug all, 181
- no ip domain-lookup, 388
- ping, 130, 383–384, 387, 493
- recalling, 180, 201
- resume, 391
- setup, 190
- show access-lists, 489
- show cdp entry, 393
- show cdp interface, 395
- show cdp neighbor, 393
- show cdp neighbor detail, 394
- show flash, 196
- show hosts, 369
- show interface, 376, 489
- show interfaces, 369
- show ip arp, 492–493
- show ip host, 388
- show ip interface, 369, 377
- show ip interface brief, 369, 376, 379, 489
- show ip protocol, 490
- show ip route, 373, 376–379, 383, 397, 492
- show running-config, 371, 374–375, 380, 491
- subcommands, 182
- telnet, 389
- terminal history size, 179
- terminal ip netmask-format, 369, 374
- trace, 492–493
- comment lines, command output, 183**
- comparing**
 - remote access technologies, 465–466
 - TCP and UDP, 162–163
- computers, 153**
- configuration files (IOS)**
 - copying, 189–190
 - managing, 188–189
 - storing, 188
 - updating, 182
- configuration mode (IOS CLI), 182**
 - exiting, 183
- configuration mode end command, 183**
- configuration register, 198–199, 203**
- configuring**
 - Cisco 2950 switches, 220
 - Cisco IOS, example, 183–185
 - Cisco routers
 - bandwidth*, 380
 - basic administration*, 370–372
 - clock rate*, 380
 - IP address*, 372–375
 - IP configuration commands*, 368–369
 - prefix notation*, 375
 - routing table*, 376–379
 - IP addresses, 368, 371–376, 379
 - host names*, 387–388
 - naming*, 388
 - PPP, 487
 - routers
 - in setup mode*, 190–194
 - IP*, 387
 - IP RIP*, 486–487
- connectionless protocols, 159–160, 164**
- connection-oriented protocols, 159–160, 164**
- connections**
 - TCP, 158–159
 - telnet, suspended, 391
- connectors**
 - fiber cables, 295–296
 - UTP, 290–291
- console ports, 177**
- convergence, 421, 579**
 - STP, 251
- converting**
 - analog signals to digital, 438–440
 - decimal-to-hexadecimal-to-binary values, 565, 569
- copper cabling, 288**
- copy command, 202**
- copy tftp flash command, 197**
- copying**
 - configuration files, 189–190
 - images into Flash memory, 194–197
- CPs (control protocols), 93**
- CRC (cyclical redundancy check), 51**
- creating**
 - subnet chart, 340–342
 - subnet list chart, 347–350
 - VLANs, 264–265
- crosstalk, 288**

CSMA/CD (carrier sense multiple access/
collision detect), 50, 55
 CSU/DSU (channel service unit/data service
unit), 84
 Ctrl+z key sequence, 183
 cut-through switching, 243

D

dark fiber, 294
 data encapsulation, 29–30
 data link layer (OSI model), 33
 addressing, 51
 arbitration, 50
 encapsulated data, identifying, 52
 error detection, 51
 identifying encapsulated data, 52, 66–67
 LAN features, 50–51
 data segmentation, 160–161
 Data Service Unit/Channel Service Unit.
 See DSU/CSU
 data-link layer (OSI model)
 encapsulation, 116
 point-to-point WANs
 HDLC, 91–92
 PPP, 92
 synchronization, 94
 PPP, 444
 data-link protocols, MCNS, 463
 DCE/DTE (data communication equipment/
data termination equipment), 98
 debug ip packet command, 369
 decimal values, converting to hexadecimal
 and binary values, 324–326, 565, 569
 demodulation, 441–444
 deploying networks
 configuration, 486–488
 planning phase, 483–485
 verification, 488–492
 designated bridges, 250
 Destination Unreachable ICMP messages,
 382–387
 development of OSI model, 20
 devices
 A/D converters, 439
 analog modems, 441–442
 installing, 445–446
 modulation, 442–444

 PPP, 444
 standards, 446–447
 cable modems, 460
 hubs, 56
 10BASE-T, 59–60
 shared Ethernet, 56
 L3 switches, 270
 modems
 DSL, 455–457
 ISDN, 448
 repeaters, 55
 routers
 bandwidth, 380
 basic administration, 370–372
 clock rate, 380
 IP address configuration, 372–375
 routing table, 376–379
 telnetting between, suspend function,
 389–391
 DHCP (Dynamic Host Configuration
Protocol), 131–132
 digital modems
 cable modems
 two-way communication, 462
 upstream data, 463
 DSL, 455–456
 standards, 456–457
 ISDN, 448
 installing, 453
 digital signals, 437
 encoding schemes, 438
 Dijkstra's algorithm, 416, 421, 580
 directly connected subnets, 412
 disabling debug options, 181
 discovering neighbor devices, 392–395
 displaying running configuration, 190
 distance vector routing protocols, 135, 140,
 407
 IGRP, 414–416
 RIP, 411–412
 RIPv1, 413
 RIPv2, 414
 DIX (DEC, Intel, and Xerox) Ethernet, 53
 DLCI (data-link connection identifier), 98
 DNS (Domain Name System), 127–129, 154
 UDP interaction, 162
 dotted-decimal notation, 120
 downstream data, 462

DRAM (dynamic random-access memory),
 187, 201
 drop cable, splitting, 461
 DS0 (Digital Signal Level 0), 90, 440
 DS1 (Digital Signal Level 1), 440
 DSAP (destination service access point),
 66–67
 DSL (Digital Subscriber Line), 454
 modems, 455–456
 PPPoA, 458–459
 standards, 456–457
 DSLAM (DSL access multiplexer), 455–456
 DSU/CSU (Data Service Unit/Channel
 Service Unit), 95, 580
 clocking, 88
 DTE (data termination equipment)
 clocking, 88
 DTMF (dual-tone multifrequency), 442
 DUAL (Diffusing Update Algorithm), 419,
 421, 580
 dual-ring topologies, 286
 dynamic random-access memory (DRAM),
 187, 201
 dynamic routing protocols, 407–408
 balanced hybrid, EIGRP, 419–420
 distance vector routing protocols
 IGRP, 414–415
 metric calculation, 415–416
 RIP, 411–412
 RIPv2, 414
 RIPv1, 413
 exterior routing protocols, 408
 BGP, 410–411
 interior routing protocols, classifying,
 409–410
 link-state, 416–417
 integrated IS-IS, 418–419
 OSPF, 417–418

E

E1 lines, 90
 early Ethernet standards, 52
 Echo ICMP message, 382, 387
 Echo Request/Reply messages, 382–384
 editing commands in CLI, 180
 EIA/TIA 232 WAN cabling standard, 86
 EIA/TIA 449 WAN cabling standard, 86

EIA/TIA 530 WAN cabling standard, 86
 EIGRP (Enhanced IGRP), 419–420
 enable secret command, 372
 encapsulation, 29–30, 116
 encoding schemes, 438
 Enhanced IGRP (EIGRP), 419
 enterprise networks, 6
 error detection
 at data-link layer, 51
 PPP, 93
 error recovery, TCP, 155
 Ethernet, 6
 10-Mbps, 56, 60–61
 cabling, 57–58
 hubs, 59–60
 10Base2, 53–54, 60
 repeaters, 55
 10Base5, 53–54, 60
 repeaters, 55
 10BaseT
 full-duplex, 71
 half-duplex, 59
 10 Gigabit Ethernet, 299–300
 arbitration, 50
 autonegotiation, 244
 cabling standards, 298
 collisions, reducing, 60–63
 CSMA/CD, 50
 early standards, 52
 Fast Ethernet, 69
 framing, 65–66
 full-duplex, 242
 Gigabit Ethernet, 69
 group addresses, 64
 IEEE standards, 53
 MAC addresses, 64
 multicast addresses, 65
 topologies, 283–284
 full mesh, 285
 evolution of PSTN, 437
 example configuration, Cisco IOS, 183–185
 extended star topologies, 284
 exterior routing protocols, *BGP*, 408–411,
 421, 581
 external modems, 445

F

- Fast Ethernet, 69
- FCS (frame check sequence), 51
- FDDI (Fiber Distributed Data Interface)
 - ANSI standards, 53
- fiber-optic networking, 293
 - connectors, 295–296
 - MM, 294–295
 - SM, 294
 - SONET, 100
- FIN field, TCP connection establishment, 158
- Flash memory
 - read-only mode, 196
 - routers, 187, 202
 - storing IOS images, 194–197
 - verifying contents of, 196
- Flintstones network example, 7–13
- flow control, TCP, 156–157
- forward acknowledgment, TCP, 155
- forwarding state (STP), 251, 254
- forwarding unknown unicast frames, 240
- four-wire circuits, 95
- FragmentFree processing, 243, 253
- fragment-free switching, 243
- Frame Relay, 96–97
 - access links, 97
 - CIR, 99
 - DTE/DCE, 98
 - VCs, 98
 - versus point-to-point links, 97
- frames, 65–67, 72
 - Ethernet, 66
- frequency modulation, 443
- FTP (File Transfer Protocol), 8–10
- full mesh topologies, 285
- full-duplex, 242
- full-duplex 10BaseT Ethernet, 71
- full-duplex operation (Ethernet), 62

G

- Get Requests (HTTP), 23
- Gigabit Ethernet, 69
- global commands, 182
- goals of routing protocols, 135–136
- group addresses, 64, 237

H

- half-duplex 10BaseT Ethernet, 59
- half-duplex logic, 62
- HDLC (high level data-link control), 91–92
 - synchronization, 94
- head-end site (CATV), 460
- headers, TCP, 150
- help system (CLI), 179
 - IOS commands, 180, 201
- hexadecimal values, converting to decimal
 - and binary values, 565, 569
- history buffer (CLI), recalling commands, 180
- host names, configuring, 387–388
- Host Unreachable code (Destination Unreachable ICMP message), 385
- hostname command, 183
- hosts per subnet, calculating, 329–332
- HTML (Hypertext Markup Language), 23
- HTTP (HyperText Transfer Protocol)
 - headers, 23
- hub-and-spoke topologies, 283
- hubs, 56
 - 10BASE-T, 59–60
 - full-duplex 10BaseT Ethernet, 71
 - half-duplex 10BaseT Ethernet, 59
 - shared Ethernet, 56

I-J

- IBM SNA (Systems Network Architecture), 20
- ICMP (Internet Control Message Protocol), 130–131, 381
 - messages
 - Destination Unreachable*, 382, 385–387
 - Echo*, 382, 387
 - Echo Request/Reply*, 130, 382–384
 - Parameter Problem*, 382
 - Redirect*, 382
 - Source Quench*, 382
 - Time Exceeded*, 382
 - troubleshooting IP addresses, 381, 383

identifying

- encapsulated data at data link layer, 52, 66–67
- IP address structure, 329–332
- subnet broadcast address, 335–336
- valid IP addresses in a subnet, 336–337

IEEE standards

- Ethernet, 53
- group addresses, 64, 237
- LANs, 53

IGRP (Interior Gateway Routing Protocol), 414–415

- features, 416, 419, 424
- metric, 415–416
- versus RIP, 416, 419, 424

image files (IOS), 194

- storing in Flash memory, 194–197

initial configuration mode, Cisco 2950 switches, 218–220**initialization process, Cisco 2950 switches, 216–217****installing**

- ISDN for home-based networks, 453
- modems, 445–446

Integrated IS-IS, 418–419**interface cable standards, WANs, 86****interface command, 182****interface ethernet 0 command, 183****interfaces**

- IP parameters, displaying settings, 369
- routers, numbering, 187
- statistics, displaying, 369

interior routing protocols, 408, 421, 583

- classifying, 409–410
- EIGRP, 419
- IGRP, 414–416
- Integrated IS-IS, 418
- OSPF, 417
- RIPv1, 413
- RIPv2, 414

internal modems, 445**internal switch processing, 243, 252****internetwork layer (TCP/IP model), 26–27****IOS (Internetwork Operating System)****CLI**

- accessing*, 176–177, 214, 221
- configuration mode*, 183
- privileged EXEC mode*, 181–183, 201
- user EXEC mode*, 181, 201
- configuration file, 188
- images, 194

IP (Internet Protocol), 135. See also IP addressing**addresses**

- Class A networks*, 122
- Class B networks*, 122
- Class C networks*, 122
- grouping*, 118
- hostnames, displaying*, 369
- interfaces, displaying*, 369
- Private Addressing*, 354
- structure*, 119, 139

ARP cache, displaying, 369**CIDR, 351, 353****configuration, 387****interface settings, displaying, 369****NAT, 351****Private Addressing, 351****RIP, configuring, 486–487****routing protocols, 407****standard access lists, configuring, 486–487****ip address command, 183, 368****IP addressing, 120****address classes, 122–124, 319–320****Boolean AND operation, 326–328****configuring, 368–379****dotted-decimal notation, 120****grouping concepts, 121****host name configuration, 387–388****identifying address structure, 329–332****naming configuration, 388****NAT, 354****network numbers, 123, 139****prefix notation, 328****subnet list chart, creating, 347–350****subnetting, 124–127, 321***binary conversion, 324–326**Boolean AND operation, 333–335**broadcast address, identifying, 335–336*

- deriving subnet broadcast address, 343*
- hosts per subnet, calculating, 329–332*
- identifying valid IP addresses, 336–337*
- subnet chart, creating, 340–342*
- subnet masks, 344–346*
- troubleshooting with ICMP, 381–383
- IP configuration commands (Cisco IOS Software), 368–369**
- ip domain-lookup command, 368–388**
- ip domain-name command, 388**
- ip host command, 368–388**
- ip name-server command, 368–388**
- ip netmask-format command, 368**
- ip routing command, 368**
- IPv6, 355**
- IPX (Internetwork Packet Exchange)**
 - access lists, configuring
 - SAP filters, 486–487*
 - standard, 486–487*
 - address structure, 118–119, 139
- ISDN (Integrated Services Digital Network), 447–448**
 - BRI, 449
 - call setup, 449–450
 - channels, 449
 - installing, 453
 - out-of-band signaling, 450
 - PRI, 449
 - TA, 448
 - typical uses, 451–453
- ISL (Inter-Switch Link), 266**
- ISO (International Organization for Standardization), development of OSI model, 20**
- ITU (International Telecommunications Union), 86**

K-L

- key sequences, Ctrl+z, 183
- L3 switches, 270
- L3PDU (Layer 3 PDU), 36
- LANs, 6. See also VLANs**
 - broadcast domains, 246
 - cabling, 287
 - coaxial, 291–293*
 - fiber, 293–296*
 - interference, 288*
 - twisted-pair, 288*
 - UTP, 289–291*
 - collision domains, 60, 245
 - Ethernet
 - 10 Gigabit Ethernet, 299–300*
 - 10-Mbps, 53–61*
 - autonegotiation, 244*
 - Fast Ethernet, 69*
 - framing, 65–66*
 - Gigabit Ethernet, 69*
 - group addresses, 64*
 - MAC addresses, 64*
 - switching, 60–63*
 - frames, 67, 72
 - OSI model functionality, 47
 - data link layer, 50–51*
 - physical layer, 47–49*
 - segmenting
 - with bridges, 236*
 - with switches, 240–242, 246*
 - switching, internal processing, 243, 252
- LAPB (Link Access Procedure Balanced), 91, 95, 580**
- LAPD (Link Access Procedure on the D channel), 94, 105**
- Layer 2 switching, 268**
- Layer 3 forwarding, 268–270**
- Layer 4 switching, 271**
- layers of OSI model, 31–34**
 - data link layer
 - addressing, 51*
 - arbitration, 50*
 - error detection, 51*
 - identifying encapsulated data, 52*
 - identifying encapsulated Ethernet data, 66–67*
 - network layer
 - addressing, 118–119*
 - routing, 114–117, 135*
 - transport layer
 - error recovery, 155*
 - features, 149*
 - flow control, 156–157*

- TCP*, 150–154, 158–159
- UDP*, 162
- layers of TCP/IP model
 - application layer, 22–24
 - data encapsulation, 29–30
 - internetwork layer, 26–27
 - network interface layer, 27–28
 - transport layer, 24–25
- LCP (Link Control Protocol), 93
- learning state (STP), 251
- leased lines, 82
 - connectivity, 84–85
- line aux command, 177, 200
- line console command, 177, 200
- line vty command, 177, 178, 200
- link speeds, 89–90
- link state routing protocols, 421
- link-state protocols, 416–417
 - integrated IS-IS, 418–419
 - OSPF, 417–418
- listening state (STP), 251
- logic used by routing protocols, 134–135
- logical topologies, 283
- login command, 178
- loop avoidance, STP, 248–249
 - convergence, 251
 - designated bridges, 250
 - forwarding state, 251, 254
 - root bridges, 250
- lower layers of OSI model, 32
- LQM (Link Quality Monitoring), 93

M

- MAC addresses, 64
 - BIAs, 64
 - broadcast addresses, 64, 237
 - components, 64
 - LAN card addressing, 64, 237
 - learning process, bridges, 239
 - multicast addresses, 65, 237
 - OUI, 64
 - unicast, 64
- managing configuration files, 188–189
- MANs (metropolitan-area networks), 82
- masks
 - network masks
 - Class B networks*, 320
 - Class C networks*, 320
 - subnet masks, display types, setting, 369
- maximum WAN cable speeds, 87
- MCNS (Multimedia Cable Network Systems), 463
- memory, 187
 - Flash, 187
 - read-only mode*, 196
 - routers*, 202
 - storing IOS images*, 194–197
 - verifying contents of*, 196
 - NVRAM, 187, 202
 - RAM, 187, 201
 - ROM, 187, 201
- messages, ICMP, 381
 - Destination Unreachable, 385–387
 - Echo Request/Reply, 130, 382–384
- metallic cabling, 287
 - coaxial, 291–293
 - interference, 288
 - twisted-pair cabling, 288
 - UTP, 289–290
 - connectors*, 290–291
 - standards*, 290
- metrics, IGRP, 415–416
- MM (multimode) fiber, 294–295
- modems
 - analog
 - installing*, 445–446
 - modulation*, 442–444
 - PPP, 444
 - standards*, 446–447
 - analog analog modems, 441–442
 - cable modems, 460
 - two-way communication*, 462
 - upstream data*, 463
 - DSL, 455–456
 - standards*, 456–457
 - ISDN, 448
 - modulation, 442–444
 - MT-RJ connectors, 296
 - MTU (maximum transmission unit), 66, 160–161
- multiaccess networks, Frame Relay, 97–98

- multicast addresses, 65
 - MAC addresses,, 237
- multilayer switching, 272
- multiplexing, 151–152
 - sockets, 152, 154
 - UDP, 161
- multiplexors, T1 mux, 95, 589

N

- naming IP addresses, 388
- NAT (Network Address Translation), 351, 354, 351
- neighboring devices
 - discovery, 392–393, 395
- Network Address Translation, *see* NAT, 351
- Network File System, *See* NFS, 162
- network interface layer (TCP/IP model), 27–28
- network layer (OSI model), 33
 - addressing, 118–119
 - ARP, 127, 129
 - BOOTP, 130, 132
 - DHCP, 131–132
 - DNS, 128–129
 - ICMP echo requests, 130
 - RARP, 130–132
 - routing, 114–116, 135
 - data-link layer interaction, 116–117*
- network numbers, 123, 139
 - aggregating with CIDR, 351, 353
 - Class A networks, 121, 123, 139
 - Class B networks, 121, 123, 139
 - Class C networks, 121, 123, 139
- Network Unreachable code (Destination Unreachable ICMP message), 385–386
- networking, 7
 - end-user perspective, 5–6
 - enterprise, 6
 - Flintstones network example, 7–13
 - Frame Relay VCs, 98
 - private Internets, 353
- networking architectures
 - Ethernet topologies, 283–285
 - OSI model, 15
 - development of, 20*
 - LAN functionality, 47–51*
 - layering, 35–36*

- TCP/IP, 20
 - application layer, 22–24*
 - data encapsulation, 29–30*
 - internetwork layer, 26–27*
 - network interface layer, 27–28*
 - same-layer interaction, 26*
 - transport layer, 24–25*
- Token Ring topologies, 286
- networks masks, 320
- NFS (Network File System), 162
 - UDP interaction, 162
- no cdp enable command, 393
- no cdp run command, 393
- no debug all command, 181
- no ip domain-lookup command, 388
- nonvolatile random-access memory.
 - See* NVRAM
- numbering router interfaces, 187
- NVRAM
 - (nonvolatile RAM), 187, 202
 - configuration files
 - erasing, 190*
 - routers, 187, 202
- Nyquist's theorem, 440

O

- operating systems, CatOS, 214
- ordered data transfer, 160–161
- Organizationally Unique Identifier. *See* OUI
- OSI Reference model, 15, 31–34
 - data link layer
 - addressing, 51*
 - arbitration, 50*
 - error detection, 51*
 - identifying encapsulated data, 52*
 - identifying encapsulated Ethernet data, 66–67*
 - LAN features, 50–51*
 - point-to-point WANs, 91–92, 94*
 - development of, 20
 - LAN functionality, 47
 - layering, 35–36
 - network layer
 - addressing, 118–119*
 - routing, 114–117, 135*
 - PDU's, 36

- physical layer
 - LAN features*, 47–49
 - point-to-point WANs*, 81, 83
- transport layer
 - features*, 149
 - TCP*, 150–152, 154
- OSPF (Open Shortest Path First), 417–418
- OUI (Organizationally Unique Identifier), 64–65
- out-of-band signaling, ISDN, 450
- output (commands), comment lines, 183

P

- packet-switched WANs
 - ATM, 102
 - Frame Relay, 96–97
 - access links*, 97
 - CIR*, 99
 - DTE/DCE*, 98
 - VCs*, 98
- Parameter Problem ICMP message, 382
- partial mesh topologies, 285
- passwords, accessing CLI, 177
- PCM (pulse-code modulation), converting
 - analog signals to digital, 439–440
- PDU (protocol data units), 36
- periodic updates, 412
- phase modulation. *See* modulation
- physical bus topologies, 283
- physical layer (OSI model), 34
 - LAN features*, 47–49
 - point-to-point WANs*, 81–83
 - connectivity*, 84–85
- physical star topologies, 286
- ping command, 130, 383–384, 387, 493
- planning phase of network deployment, 483–485
- point-to-point WANs, 81, 83
 - connectivity, 84–85
 - data-link protocols
 - HDLC*, 91–92
 - PPP*, 92
 - synchronization*, 94
- Port Unreachable code (Destination Unreachable ICMP message), 386
- ports, 154
 - console ports, 177
 - Layer 4 switching, 271
- POST (Power-On Self Test), Cisco 2950 switches, 216–217
- PPP (Point-to-Point Protocol), 92–94, 105, 444
 - configuring, 487
 - LCP, 93
 - synchronization, 94
- PPPoA (PPP over ATM), 458–459
- prefix notation, 328
 - show ip route command, 375
- preparing for exam, 479–494
 - IP addressing
 - creating subnet chart*, 340–342
 - deriving subnet broadcast address*, 343
 - identifying address structure*, 329–330, 332
- presentation layer (OSI model), 33
- preventing routing loops with STP, 249
 - convergence, 251
 - designated bridges, 250
 - forwarding state, 251, 254
 - root bridges, 250
- PRI (Primary Rate Interface), 449
- Private Addressing, 351, 354
- private Internets, 353
- privileged EXEC mode (Cisco IOS), 178, 181, 201
- Protocol Unreachable code (Destination Unreachable ICMP message), 385
- protocols
 - connectionless, 160
 - connection-oriented, 160
 - routed protocols, 407, 422
 - routing protocols, 407, 422
 - comparison of*, 408
 - distance vector routing protocols*, 407
 - goals of*, 140

- PSTN (Public Switched Telephone Network), 435
 - analog signals, converting to digital, 436–440
 - digital signals, 437
 - encoding schemes*, 438
 - DS0/DS1, 440
 - evolution of, 437
 - modem operation, 441–442
 - modulation*, 442–444
 - PPP*, 444
- PTT (public telephone and telegraph) companies, 83
- PVCs (permanent virtual circuits), 98

Q-R

- QAM-256, 463
- QAM-64, 463
- RAM (random-access memory), 187, 201
- RARP (Reverse Address Resolution Protocol), 130–132
- read-only mode (Flash memory), 196
- reassembly, 102
- recalling commands, 180
- Redirect ICMP message, 382
- reducing collisions with LAN switching, 60–63
- reliability of TCP, 155
- removing configuration files from NVRAM, 190
- repeaters, 55
- resume command, 391
- ring topologies, 286
- RIP (Routing Information Protocol), 411–413
 - IP configuration, 486–487
 - versus IGRP, 416, 419, 424
- RIPv2, 414
- RJ-45 connectors, 290
- ROM (read-only memory), 187, 201
- root bridge (Spanning Tree), 250
- root port (Spanning Tree), 251, 254
- routed protocols, 407, 422

- routers
 - auxiliary connections, configuring, 177, 200
 - bandwidth, configuring, 380
 - basic administration, 370–372
 - clock rate, configuring, 380
 - configuration
 - IP*, 387
 - IP RIP*, 486–487
 - configuration files, copying, 189–190
 - configuration register, 199, 203
 - configuring with setup mode, 190–194
 - console connections, configuring, 177, 200
 - interfaces, numbering, 187
 - IP address, configuring, 372–375
 - IP configuration commands, 368–369
 - memory, 187
 - Flash*, 187, 202
 - NVRAM*, 187, 202
 - RAM*, 187, 201
 - ROM*, 187, 201
 - multiple Telnet connections, 178
 - neighboring device discovery, 392–395
 - ports
 - auxiliary ports*, 177
 - console ports*, 177
 - routing table, configuring, 376–379
 - running configuration, viewing, 190
 - Telnet connections
 - configuring*, 177, 200
 - suspend function*, 389–391
- routing, 114. *See also* routing protocols
 - address resolution, 135
 - at network layer, 114–116, 135
 - data-link layer interaction*, 116–117
- routing loops, STP, 248–249
 - convergence, 251
 - designated bridges, 250
 - forwarding state, 251, 254
 - root bridges, 250
- routing protocols, 119, 133, 407, 421–422
 - balanced hybrid protocols,
 - EIGRP, 419–420
 - BGP, 410–411
 - comparison of, 408
 - decision process logic, 134–135

- distance vector, 135, 140, 407
 - IGRP*, 414–416
 - RIP*, 411–412
 - RIPv2*, 414
 - RIPv1*, 413
- dynamic, 407–408
- exterior routing protocols, 408
- goals of, 135–136, 140
- interior routing protocols, classifying, 409–410
- link-state, 416–417
 - integrated IS-IS*, 418–419
 - OSPF*, 417–418
- routing tables, 136–137
 - displaying, 369
- routing updates, 411
- running configuration, 188
 - viewing, 190

S

- same-layer interaction, 24–26
- SAP (Service Advertising Protocol), 67
 - filters, configuring, 486–487
- scenarios, network deployment
 - configuration, 486, 488
 - planning phase, 483, 485
 - verification, 488–490, 492
- SDH (Synchronous Digital Hierarchy), 100
- SDLC (Synchronous Data Link Control), 94, 105
- security, accessing CLI passwords, 177
- seeding routing tables with connected routes, 376–379
- segmentation, 160–161
- segmenting LANs
 - with switches, 240–241, 246
 - full-duplex*, 242
 - with transparent bridges, 236
- Service Advertising Protocol. *See* SAP
- session layer (OSI model), 33
- setup command, 190
- setup mode, router configuration, 190–194
- shared Ethernet, 56
- shielding, 288
- show access-lists command, 489
- show cdp entry command, 393
- show cdp interface command, 395
- show cdp neighbor command, 393
- show cdp neighbor detail command, 394
- show flash command, 196
- show hosts command, 369
- show interface command, 376, 489
- show interfaces command, 369
- show ip arp command, 492–493
- show ip host command, 388
- show ip interface command, 369, 377
- show ip interface brief command, 369, 376, 379, 489
- show ip protocol command, 490
- show ip route command, 373–379, 383, 397, 492
 - prefix notation, 375
- show running-config command, 371, 374–375, 380, 491
- signaling, 450
- single-ring topologies, 286
- sliding windows, 157
- SM (single-mode) fiber, 294
- SNA (Systems Network Architecture), 20
- SNAP (Subnetwork Access Protocol), 67
- SNMP (Simple Network Management Protocol), 154
- sockets
 - multiplexing, 152, 154
 - port numbers, 154
- SONET (Synchronous Optical Network), 100
- Source Quench ICMP messages, 382
- Spanning Tree. *See* STP
- SPF (shortest path first) algorithm, 416
- splitting, 461
- SS7 (Signaling System 7), 450
- ST connectors, 295
- standard IP access lists, configuring, 486–487
- standard IPX access lists, configuring, 486–487
- standards
 - DSL-related, 456–457
 - Ethernet, 52
 - 10BASE2/10BASE5*, 53–55
 - 10BASE-T*, 56–60
 - Ethernet cabling, 298
 - for modems, 446–447

- IEEE standards, LANS, 53
 - UTP, 290
 - WAN cabling, 85–86
 - clock rate*, 88
 - link speeds*, 89–90
 - maximum speeds*, 87
 - star topologies, 283
 - startup configuration, 188
 - status LEDs on Cisco 2950, 216–217
 - store-and-forward switching, 242–243, 252
 - storing IOS images in Flash memory, 194–197
 - STP (Spanning Tree Protocol), 248–249
 - convergence, 251
 - designated bridges, 250
 - forwarding state, 251, 254
 - root bridges, 250
 - straight-through cables, 49, 57
 - strand, 295
 - study tips for exam, 479–494
 - subcommands, 182
 - subnet chart, creating, 340–350
 - subnet masks, 327
 - display types, setting, 369
 - subnetting, 124–127, 321
 - binary conversion, 324–326
 - Boolean AND operation, 333–335
 - broadcast address, identifying, 335–336
 - deriving subnet broadcast address, 343
 - directly connected subnets, 412
 - identifying valid IP addresses, 336–337
 - subnet masks, 344–346
 - suspend function (Telnet), 389–391
 - switches,
 - Cisco 2950, 213
 - CatOS*, 214
 - CLI*, 215
 - configuring*, 220
 - initialization*, 216–217
 - POST*, 216–217
 - store-and-forward processing, 242,
 - VLANs, 263–264
 - creating*, 264–265
 - trunking*, 265–267
 - switching
 - autonegotiation, 244
 - cut-through, 242–243, 253
 - fragment-free, 242–243, 253
 - LANs, 240–241, 246
 - full-duplex*, 242
 - internal processing*, 243, 252
 - Layer 4 switching, 271
 - multilayer switching, 272
 - neighboring device discovery, 392–395
 - store-and-forward, 242, 253
 - VLANs
 - Layer 2 switching*, 268
 - Layer 3 forwarding*, 268–270
 - SYN field, TCP connection
 - establishment, 158
 - synchronization, 94
 - Synchronous Data Link Control. See SDLC
 - synchronous serial interfaces, 85–86
 - synchronous serial leased lines, 94
 - syslog messages, 181
- ## T
- T1 lines, 90
 - T1 mux, 95, 589
 - TA (terminal adapter), 448
 - TCP (Transmission Control Protocol), 150
 - connection establishment/termination, 158–159
 - connection-oriented nature of, 159
 - data segmentation, 160–161
 - error recovery, 155
 - features of, 150
 - flow control, 156–157
 - forward acknowledgment, 155
 - functions of, 161
 - headers, 150
 - multiplexing, 151–152
 - sockets*, 152–154
 - ports, Layer 4 switching, 271
 - versus UDP, 161–163
 - well-known port numbers, 154
 - TCP/IP, 20–21
 - application layer, 22–24
 - ICMP, 381
 - Destination Unreachable messages*, 385–387
 - Echo messages*, 382, 387
 - Echo Request/Reply messages*, 382–384
 - Parameter Problem messages*, 382
 - Redirect messages*, 382
 - Source Quench messages*, 382
 - Time Exceeded message*, 382

- internetwork layer, 26–27
- IP addressing, 120
 - address classes*, 122–124, 319–320
 - CIDR, 351
 - configuring*, 368–379
 - deriving subnet broadcast address*, 343
 - dotted-decimal notation*, 120
 - grouping concepts*, 121
 - host name configuration*, 387–388
 - identifying address structure*, 329–332
 - naming configuration*, 388
 - NAT, 354
 - network numbers*, 123, 139
 - private addressing*, 354
 - subnet list chart, creating*, 342–350
 - subnetting*, 124–127, 321–326
- network interface layer, 27–28
- network layer utilities
 - ARP, 127, 129
 - BOOTP, 130, 132
 - DHCP, 131–132
 - DNS, 128–129
 - ICMP *echo*, 130
 - ping command*, 130
 - RARP, 130–132
- TCP
 - features of*, 150
 - forward acknowledgement*, 155
 - functions of*, 161
 - headers*, 150
- transport layer, 24–25
- UDP
 - data transfer*, 162
 - DNS, 162
 - functions of*, 166
 - NFS, 162
- telcos, 95, 580
 - digital networks, 90
- Telnet
 - router connections
 - configuring*, 177, 200
 - multiple*, 178
 - sessions, resuming, 391
 - suspend function, 389–391
- telnet command, 389
- terminal history size command, 179
- terminal ip netmask-format command, 369, 374
- TFTP (Trivial File Transfer Protocol), 155
- TIA (Telecommunications Industry Association), 86–87
- Time Exceeded ICMP message, 382
- Token Ring
 - IEEE standards, 53
 - ring topologies, 286
- topologies, 283–284
 - full mesh, 285
 - logical, 283
 - physical star, 286
 - ring, 286
- trace command, 492–493
- transparent bridging, 236
- transport layer (OSI model), 24–25, 33
 - connection-oriented/connectionless protocols, 159, 164
 - features, 149
 - TCP, 150–152, 154
 - connection establishment/termination*, 158–159
 - data segmentation*, 160–161
 - error recovery*, 155
 - flow control*, 156–157
 - versus UDP*, 162–163
 - UDP
 - functions of*, 162
 - multiplexing*, 161
- troubleshooting TCP/IP with ICMP, 381, 383
 - destination unreachable messages, 385–386
- trunking VLANs, 265
 - 802.1q, 266–267
 - Cisco ISL, 266
- twisted-pair cabling, 288
 - UTP, 289–290
 - connectors*, 290–291
 - standards*, 290
- two-way communication, cable modems, 462
 - upstream, 463
- two-wire circuits, 95, 582

U

- UAAs (universally administered addresses), 64
- UDP (User Datagram Protocol)
 - data transfer, 162
 - DNS, 162
 - functions of, 162, 166
 - multiplexing, 161
 - NFS, 162
 - ports, Layer 4 switching, 271
 - versus TCP, 161–163
- unicast MAC addresses, 64
- universally administered addresses (UAAs), 64
- unknown unicast frames, forwarding, 240
- unreachable codes (ICMP), 385
- updating configuration files, 182
- upgrading images into Flash memory, 194–197
- upper layers of OSI model, 32
- upstream data, 463
- user EXEC mode (Cisco IOS), 178, 181, 201
- UTP (unshielded twisted-pair), 289–290
 - connectors, 290–291
 - standards, 290

V

- V.35 WAN cabling standard, 86
- VCI (Virtual Channel Identifier), 101
- VCs (virtual circuits), 98
- viewing running configuration, 190
- VLANs, 263–264
 - creating, 264–265
 - Layer 2 switching, 268
 - Layer 3 forwarding, 268–270
 - trunking, 265
 - 802.1q, 266–267
 - Cisco ISL, 266
- VPI (Virtual Path Identifier), 101

W

- WANs
 - asynchronous serial leased lines, 95, 588
 - ATM, 101
 - cell reassembly, 101
 - VPI, 101
 - cabling standards, 85–86
 - clock rate, 88
 - link speeds, 89–90
 - maximum speeds, 87
 - four-wire circuits, 95
 - Frame Relay, VCs, 98
 - ISDN, 447–448
 - call setup, 449–450
 - channels, 449
 - installing, 453
 - out-of-band signaling, 450
 - typical uses, 451–453
 - leased lines, 82
 - packet-switched, Frame Relay, 96–99
 - point-to-point, 81, 83
 - connectivity, 84–85
 - HDLC, 91–92
 - PPP, 92, 94
 - PPP, 94, 105
 - LCP, 93
 - protocols
 - HDLC, 95, 580
 - LAPB, 95, 580
 - LAPD, 94, 105
 - PPP, 95, 580
 - SDLC, 94, 105
 - SONET, 100
 - synchronous serial leased lines, 94
 - two-wire circuits, 95, 582
- well-known port numbers, 154
- windowing, TCP flow control, 157
- wireless communications, 300
 - 802.11 WLANs, 301–302
- wiring. *See* cabling
- WLANs, 300
 - 802.11, 301–302
- WWW (World Wide Web), 154

X-Z

- X.21 WAN cabling standard, 86