

# Index

---

## A

- AAA (authentication, authorization, and accounting), 166
- account management, VPN bridge case study, 361
- accounting, MPLS-based networks, 306–308, 322–323
- ACs (attachment circuits), 40
- additional bandwidth inventories, 231
- address management, dial access, 166
- address translation, VRF-aware feature, 338–339
- addresses
  - IPv6, 288–289
    - basics*, 290–299
    - management*, 299
    - problem providing IPv4 services*, 290
  - network assignment, 334–335
- Any Transport over MPLS. *See* AToM
- anycasting, 288
- APS (automatic protection switching), 34
- ATM (asynchronous transfer mode), 27–28
  - like-to-like transport, 117–118
  - MPLS interworking, 375
- ATM MPLS networks, 366
- ATM over MPLS (ATMoMPLS), 41
- ATMoMPLS (ATM over MPLS), 41
- AToM (Any Transport over MPLS), 111
  - Layer 2 VPNs, 111–112
    - packet forwarding*, 114
    - pseudowires*, 112–113
- attachment circuit values, LDP signaling, 128
- attachment circuits (ACs), 40
- attacks, security scenarios, 189–201
- authentication, authorization, and accounting (AAA), 166

- automatic protection switching (APS), 34
- availability, security considerations, 183

## B

- bandwidths, on-demand service, 371
- best effort grade of services, 250
- best practices, security, 217–218
- BFD factors, network design considerations, 342
- BGP (Border Gateway Protocol), 65, 292
  - IPv6 PE, 292
  - Layer 2 VPN provisioning, 128–131
- Border Gateway Protocol (BGP), 65, 292
  - IPv6 PE, 292
  - Layer 2 VPN provisioning, 128–131
- bridged encapsulation, DSL remote access, 171–172
- British Telecom, 7
- business drivers, service convergence, 9–10
  - enterprise customers, 10–11
  - Layer 3 services, 11–14

## C

- cable, remote access, 172
- campus multicast, 276
- Carrier's Carrier (CsC) networks, Layer 2 VPN security, 212–215
- cases studies, Equant
  - company background, 358–360
  - customer VPN bridge, 360–362
- CBQ (class-based queuing), 67

---

**CE (customer edge), 164**  
remote access, 164–165  
    *cable, 172*  
    *dial access, 166–170*  
    *DSL, 170–172*  
    *routing protocols, 173–174*  
router security considerations, 215–217

**central services, enterprise campus, 18**

**challenges**  
QoS, 250–252  
    *DiffServ, 257*  
    *hybrid model, 258–259*  
    *IntServ, 256–257, 267–268*  
    *MPLS, 259–267*  
    *packet handling, 258*  
    *traffic basics, 252–256*  
SPs, 4–7

**CIR (committed information rate), 35**  
*Cisco ISP Essentials, 217*

**class-based queuing (CBQ), 67**

**classifications, traffic, 252**

**committed information rate (CIR), 35**

**confidentiality, security considerations, 183**

**configuration, management, 306–308, 318–322**

**constrained based shortest path first (CSPF), 252**

**content engines, value-added services, 51**

**content-based services, MPLS Layer 3 services, 373**

**contiguous VC values, BGP signaling, 130**

**control planes, IP and optical network integration**  
bandwidth on-demand service, 371  
basics, 368–370  
G-MPLS and UCP challenges, 371–372

**corporate extranets, Layer 3 VPNs, 148–149**

**corporate intranets, Layer 3 VPNs, 146–148**

**CPE (customer premise equipment), 35**

**CsC (Carrier's Carrier) networks, Layer 2 VPN security, 212–215**

**CSPF (constrained based shortest path first), 252**

**customer edge. *See* CE**

**customer premise equipment (CPE), 35**

## D

**data link connection identifier (DLCI), 35**

**Data-MDT, 275**

**Default-MDT (Default-Multicast Distribution Tunnel), 275**

**Default-Multicast Distribution Tunnel (Default-MDT), 275**

**denial-of-service (DoS)**  
monolithic core, 192  
security threats, 190

**density, network scalability, 353–354**

**deployment**  
MVPNs, IEFT drafts, 285  
network guidelines, 341

**design**  
deployment guidelines, 341  
equipment *versus* network scalability, 343–346  
    *element interaction, 346–347*  
    *Layer 2 VPNs, 352–354*  
    *management, 351–352*  
    *network-wide scale issues, 349–350*  
    *parameters, 347–349*  
management, 342–343  
NAT packet flow, 339–340  
provisioning, 342–343  
troubleshooting, 342–343

- VRF-aware feature, 332–334
    - address translation*, 338–339
    - DHCP deployment*, 335–338
    - IP address assignment*, 334–335
- detection**, 342
- Developing IP Multicast Networks*, 273
- Developing IP-based Services*, 14
- DHCP (Dynamic Host Configuration Protocol)**
  - deployment scenarios, 335–336
  - guidelines for deployment, 338
  - VPN client addresses, 166
  - VRF-aware feature, 334–335
- diagnostics**, 342
- dial access, VPNs remote access**, 166–167
  - dial backup, 168–169
  - individual PSTN access, 167
  - PE-CE dial-out, 169–170
- dial backup, VPN remote access**, 168–169
- dial-out access, VPN remote access**, 169–170
- differentiated services versus integrated services**, 256
- differentiated services model (DiffServ)**, 68
  - MPLS technologies, 91–94, 259–261
  - QoS, 69–70
  - traffic engineering, 262–264
- DiffServ (differentiated services model)**, 68
  - MPLS technologies, 91–94, 259–261
  - QoS, 69–70, 257
  - traffic engineering, 262–264
- DLCI (data link connection identifier)**, 35
- domains, MVPNs deployment**, 285
- DoS (denial-of-service)**
  - monolithic core, 192
  - security threats, 190
- DSL, remote access**, 170–171
  - bridged encapsulation, 171–172
  - routed encapsulation, 171
- Dynamic Host Configuration Protocol (DHCP)**
  - deployment scenarios, 335–336
  - guidelines for deployment, 338
  - VPN client addresses, 166
  - VRF-aware feature, 334–335

## E

- EMS (Ethernet Multipoint Service)**, 37.
  - See also VPLS*
  - forwarding at remote node, 375–376
  - Layer 2 VPNs, 123–124
- encryption, MPLS VPNs**, 373
- enterprise customers, service convergence business drivers**, 10–11
- enterprise organizations**
  - challenges, 7
  - Layer 3 VPNs services, 18–22
  - Layered VPNs, 22–26
  - outsourcing decisions, 14–15
    - central services*, 18
    - network segmentation*, 16–17
    - TCO (total cost of ownership)*, 15–16
  - service convergence, business drivers, 9–14
  - service provider business engineering, 7–8
- EoMPLS (Ethernet over MPLS)**, 41
- EPL (Ethernet Private Line)**, 35
- EPR (Ethernet Private Ring)**, 36
- Equant case study**
  - company background, 358
    - economies of scale*, 359
    - services*, 359–360
  - customer VPN bridge, 360
    - account team success factors*, 361–362
    - company background*, 360
    - conclusions*, 362
    - divestiture issues*, 360–361
- ERS (Ethernet Relay Service)**, 35
- Ethernet**
  - Layer 2 VPNs, 35–37
  - like-to-like transport, 115
- Ethernet Multipoint Service (EMS)**, 37
- Ethernet over MPLS (EoMPLS)**, 41
- Ethernet Private Line (EPL)**, 35
- Ethernet Private Ring (EPR)**, 36
- Ethernet Relay Service (ERS)**, 35
- Ethernet Wire Service (EWS)**, 35
- evolutionary strategies**, 5
- EWS (Ethernet Wire Service)**, 35
- explicit routing**, 230
- extranets**
  - Layer 3 VPNs, 148–149
  - MPLS security, 197–201

**F****failures**

- interface, 317
- notifications
  - BGP signaling*, 129
  - LDP signaling*, 127
- pseudowire, 317
- tunnel LSP, 318

**Farrell, Adrian, 366****fault management, 306–308****Fixed-line-mobile convergence (FMC), 6****FMC (Fixed-line-mobile convergence), 6****Frame Relay, 26–27, 116–117****FRoMPLS (Frame Relay over MPLS), 41****future, MPLS, 366–367**

- increased enterprise deployment, 377
- IP and optical network integration, 367–372
- Layer 2 services, 375–376
- Layer 3 services, 372–374
- provisioning and management, 376–377

**G–H****generalized MPLS. See GMPLS****global VPNs, network segmentation, 16****GMPLS (generalized MPLS), 65**

- IP and optical network integration
  - bandwidth on-demand service*, 371
  - basics*, 368–370
  - challenges*, 371–372

**heterogeneous networks, Layer 3 VPNs, 156–157****hierarchies, 17****hub-and-spoke topology**

- BGP signaling, 131
- LDP signaling, 128

**hybrid models, QoS challenges, 258–259****I****IEFT drafters, MVPNs, 285****IEFT standards**

- Layer 2 VPNs, 136–137
- Layer 3 VPNs, 161
- QoS documents, 268

service management, 328–329

traffic engineering, 246

**IGP (Interior Gateway Protocol), IP network traffic engineering, 227****insider attacks, 190****inside-to-outside packet flow, NAT, 340****integrated services versus differentiated services, 256****integrity, security considerations, 183****Inter-AS (Inter-Autonomous System), 235–236****inter-AS Layer 2 VPNs, 135****inter-AS VPNs, scaling Layer 3 VPNs, 154–155****Inter-Autonomous System (Inter-AS), 235–236****interface failures, 317****Interior Gateway Protocol (IGP), IP network traffic engineering, 227****Internet**

- secure access, 48
- security
  - MPLS*, 197–201
  - threats*, 192

**Internet access, Layer 3 VPNs, 149–151**

- dedicated PE, 152
- dedicated per-VPN, 151
- managed central services, 152–153
- shared PE, 151–152

**Internet Protocol (IP), 28–29****interworking, Layer 2 VPNs, 120–121**

- modes, 121
- transport combinations, 121–122

**Intra-Area TE, 234****intradomain multicast, 276****intranets, Layer 3 VPNs, 146–148****intrusions**

- monolithic core, 192
- security threats, 189

**IntServ, QoS challenges, 256–257, 267**

- mapping traffic flow, 267
- tunnel-based admission control, 268

**IP (Internet Protocol), 28–29****IP addresses, VPN management, 325–327**

**IP networks**

- optical network integration, 367–368
  - bandwidth on-demand service*, 371
  - basics*, 368–370
  - G-MPLS and UCP challenges*, 371–372
- traffic engineering, 224–227
  - IGP (Interior Gateway Protocol)*, 227
  - packet forwarding*, 230–233
  - tunnel signaling*, 228–230

**IP services, shared Internet access, 152–153****IPSec security, 201–208****IPv4, providing services with IPv6, 290****IPv6, 288–289**

- basics, 290–291
  - Inter-AS network capability*, 297–298
  - IPv6 PE*, 292–294
  - IPv6 VPNs*, 294–296
  - MPLS QoS*, 299
  - network core*, 297
  - QoS*, 298
- management, 299
- problem providing IPv4 services, 290

**IPv6 PE, 292**

- BGP extensions, 292
- packet path, 293–294

**IPv6 VPNs, 294**

- IPv4 Layer 3 VPNs, 296
- packet path, 295–296
- route tagging, 294
- virtual routing, 294–295

**L****labels**

- BGP signaling, 130
- Layer 3 VPNs, 80
- LDP signaling, 127

**label-switched paths, Layer 3 services, 372****Layer 2 services, MPLS future**

- ATM-MPLS interworking, 375
- multiple provider network VPNs, 375
- VPLS forwarding at remote node, 375–376

**Layer 2 virtual private networks. See Layer 2 VPNs****Layer 2 VPNs (Layer 2 virtual private networks), 95–99, 106–107**

- AToM, 111–112
  - packet forwarding*, 114
  - pseudowire systems*, 112–113
- benefits, 132–134
- inter-AS, 135
- interworking, 120–121
  - modes*, 121
  - transport combinations*, 121–122
- like-to-like transport, 115
  - ATM service*, 117–118
  - Ethernet service*, 115
  - Frame Relay service*, 116–117
  - link layer service*, 116
  - pseudowire configuration*, 118–119
- provisioning, 124–126
  - BGP*, 128–131
  - LDP*, 126–128
- reasons for building, 22–26
- scalability, 352
  - density*, 353–354
  - grades of service*, 352–353
  - management*, 354
- security, 208–209
  - CE router security*, 215–217
  - CsC networks*, 212–215
  - design options*, 209–211
- services, 34–35
  - Ethernet*, 35–37
  - NGN basics*, 39–42
- supported IETF standards, 136–137
- taxonomy, 108–111
- technologies, 60–62
- VPLS, 123–124

**Layer 3 services, MPLS future**

- content-based services, 373
- dynamic encrypted VPNs, 373
- label-switched paths, 372
- security enhancements, 374
- voice and video integration, 373–374

**Layer 3 VPNs, 140**

- corporate extranets, 148–149
- corporate intranets, 146–148
- enterprise motivations for migration, 11–14

- heterogeneous networks, 156–157
- IETF drafts, 161
- Internet access, 149, 151
  - dedicated PE*, 152
  - dedicated per-VPN*, 151
  - managed central services*, 152–153
  - shared PE*, 151–152
- IPv6 VPNs coexistence, 296
- managed central services, 157–158
  - address management*, 159–161
  - VRF awareness*, 158–159
- meeting enterprise challenges, 32–33
- reasons for building, 22–26
- scaling to network elements, 154
  - hierarchical VPNs*, 155–156
  - inter-AS VPNs*, 154–155
- services, 18–22, 42–44
- technologies, 75–76
  - constrained distribution of routing information*, 142–144
  - label stack role*, 80
  - packet flow through network*, 145–146
  - packet forwarding*, 144
  - peer-to-peer model*, 77–78
  - separation of routing information*, 141–142
  - topologies*, 81–83
  - VRF*, 78–80
- value-added services, 48–53
- LDP, Layer 2 VPN provisioning, 126–128**
- like-to-like relationships, 40**
- like-to-like transport**
  - Layer 2 VPNs, 115
    - ATM service*, 117–118
    - Ethernet service*, 115
    - Frame Relay service*, 116–117
    - link layer service*, 116
    - pseudowire configuration*, 118–119
- link layer services, like-to-like transport, 116**
- links, tunnel protection, 237–239**
- LSR self-test, multipaths, 310–311**

## M

- MAM (maximum allocation model), 263**
- managed central services, Layer 3 VPNs, 157–158**
  - address management, 159–161
  - VRF awareness, 158–159
- managed services versus DIY, 14–15**
  - central services, 18
  - network segmentation, 16–17
  - TCO (total cost of ownership), 15–16
- management**
  - configuration, 318–322
  - IPv6, 299
  - MPLS future, 376–377
  - MVPNs, 283–284
  - network design, 342–343
  - services
    - failures*, 317–318
    - fault management*, 306–308
    - multipaths*, 309–311
    - OAM interworking*, 314–317
    - user concerns*, 304–306
    - VCCV (Virtual Circuit Connection Verification)*, 311–314
    - VRF-aware ping*, 308–309
- martini tunnels, 111**
- Martini, Luca, AToM, 111**
- maximum allocation model (MAM), 263**
- MD (multicast domain), 275**
- MDT (multicast distribution tunnel), 275**
- MEF (Metro Ethernet Forum), 35**
- Metro Ethernet Forum (MEF), 35**
- MIB modules, 327–328**
- modularity, 17**
- monolithic cores, 192**
- Morrow, Monique, *Developing IP-based Services*, 14**
- MPLS**
  - applied technologies, 62–66
  - enterprise markets, 7
  - future, 366–367
    - increased enterprise deployment*, 377
    - IP and optical network integration*, 367–372
    - Layer 2 services*, 375–376
    - Layer 3 services*, 372–374
    - provisioning and management*, 376–377

Layered VPNs, 22–26

QoS

*DiffServ-aware traffic engineering,*  
262–264

*DiffServe,* 259–261

*IPv6,* 299

*traffic engineering,* 262

SPs

*business engineering,* 7–8

*Layer 3 VPNs services,* 18–22

*meeting industry challenges,* 4–7

*outsourcing decisions,* 14–18

*service convergence business drivers,*  
9–14

**MPLS and VPN Architectures (italic), 156**

**MPLS TE**

multicast, 244–246

scalability, 243–244

**MPLS VPNs**

dynamic encryption, 373

IPSec security options, 203–208

remote access, 164–165

*cable,* 172

*dial access,* 166–170

*DSL,* 170–172

*network convergence,*  
174–175

*PE-CE connection,* 173–174

*scalability,* 174–175

**multicast distribution tunnel (MDT), 275**

**multicast domain (MD), 275**

**multicast MPLS TE, 244–246**

**MPLS QoS, 70–71**

**multicast routing, 65**

**multicast services, 52**

**multicast tunnels, 275**

**multicast VPNs. See MVPNs**

**multicast VRF (MVRF), 275**

**MVPNs (multicast VPNs), 273**

basic components, 275–276

challenges, 273–274

IETF drafts, 285

operations, 277–281

security considerations, 283–284

VPN applications, 281–282

**MVRF (multicast VRF), 275**

## N

**NAS (network access server), 166**

**NAT (network address translation), 288**

address translation, 166

IPv6, 288–289

*basics,* 290–299

*management,* 299

*problem providing IPv4 services,* 290

packet flow, 339–340

**NBMA (nonbroadcast multiaccess), MVPN  
deployment, 285**

**network access server (NAS), 166**

**network address translation. See NAT**

**network convergence, remote network access,  
174–175**

**networks**

design

*deployment guidelines,* 341

*equipment versus network scalability,*  
343–354

*NAT packet flow,* 339–340

*VRF-aware feature,* 332–339

segmentation, 16–17

**next-generation networks. See NGNs**

**Next-Generation SDH/SONET services, 35**

**NGNs (next-generation networks), 4**

enterprise markets, 7

Layered VPNs, 22–26

service basics, 39–42

SPs

*business engineering,* 7–8

*industry challenges,* 4–7

*Layer 3 VPNs services,* 18–22

*outsourcing decisions,* 14–18

*service convergence business drivers,*  
9–14

**nodes, tunnel protection, 239–240**

**nonbroadcast multiaccess (NBMA), MVPN  
deployment, 285**

## O

**OAM (operation, administration, and  
maintenance), 304**

interworking, 314

*any-to-any L2VPN,* 314–315

*ATM over MPLS,* 315–316

- Frame Relay over MPLS*, 316–317
    - local switching*, 315
  - solution, 307
- ODAPs (on-demand address pools), AAA**
  - address management, 166
- Olympic service models, MPLS QoS, 265–266**
- on-demand address pools (ODAPs), AAA**
  - address management, 166
- on-demand QoS, MPLS QoS, 266–267**
- operating expense reduction (OPeX), 5**
- operation, administration, and maintenance.**
  - See* OAM
- operations support systems (OSS), 5**
- OPeX (operating expense reduction), 5**
- optical networks, IP network integration, 367–368**
  - bandwidth on-demand service, 371
  - basics, 368–370
  - G-MPLS and UCP challenges, 371–372
- OSS (operations support systems), 5**
- outside-to-inside packet flow, NAT, 340**
- outsourcing *versus* DIY, 14–15**
  - central services, 18
  - network segmentation, 16–17
  - TCO (total cost of ownership), 15–16

## P

- packet forwarding, pseudowires, 114**
- packets**
  - IPv6 PE, 293–294
  - IPv6 VPNs, 295–296
  - Layer 3 VPNs
    - flow through network*, 145–146
    - forwarding through network core*, 144
  - QoS
    - challenges*, 250–268
    - IETF standards documents*, 268
  - traffic engineering, 230–231
    - operation sequence*, 231–232
    - tunnel maintenance*, 232–233
- parameters**
  - network elements, 344–345
  - network scalability, 347–349
- paths**
  - managing multiple, 309–310
    - LSR self-test*, 310–311
    - routers*, 310
  - tunnel protection, 241
- PE (provider edge), 164**
  - Internet access
    - dedicated PE*, 152
    - shared PE*, 151–152
  - NAT packet flow, 339–340
  - remote access, 164–165
    - cable*, 172
    - dial access*, 166–170
    - DSL*, 170–172
    - routing protocols*, 173–174
- peer-to-peer model, Layer 3 VPNs, 77–78**
- performance, management, 306–308, 323–324**
- PIM bidirectional (PIM-BIDIR), 278**
- PIM Dense-mode (PIM-DM), 278**
- PIM modes, 278**
- PIM source specific multicast (PIM-SSM), 278**
- PIM sparse-mode (PIM-SM), 276–278**
- PIM-BIDIR (PIM bidirectional), 278**
- PIM-DM (PIM Dense-mode), 278**
- PIM-SM (PIM sparse-mode), 278**
- PIM-SSM (PIM source specific multicast), 278**
- point-to-cloud models, MPLS QoS, 265**
- policing traffic, 252–253**
- prices, VPN bridge case study, 362**
- priority queuing, 67**
- private addresses, IPv6, 288–289**
  - basics, 290–299
  - management, 299
  - problem providing IPv4 services, 290
- provider edge. *See* PE**
- provisioning**
  - Layer 2 VPNs, 124–126
    - BGP*, 128–131
    - LDP*, 126–128
  - MPLS future, 376–377
  - network design, 342–343
- pseudowires, 65, 111–112**
  - failures, 317
  - Frame Relay over MPLS, 112–113
  - like-to-like transport, 118–119
  - mechanisms, 40
  - packet forwarding, 114



**PSTNs (public switched telephone networks),**  
167  
**public switched telephone networks (PSTNs),**  
167

## Q

**QoE (quality of experience), 272**  
**QoS (Quality of service), 66–69, 250**  
BGP signaling, 129  
challenges, 250–252  
    *DiffServ*, 257  
    *hybrid model*, 258–259  
    *IntServ*, 256–257, 267–268  
    *MPLS*, 259–264  
    *MPLS examples*, 265–267  
    *packet handling*, 258  
    *traffic basics*, 252–256  
DiffServ, 69–70  
IETF standards documents, 268  
IPv6, 298  
LDP signaling, 127  
multicast, 70–71  
traffic engineering, 236  
**quality of experience (QoE), 272**  
**Quality of Service. See QoS**

## R

**random early detection (RED), 67**  
**Real-Time Transport Protocol (RTP), 29**  
**RED (random early detection), 67**  
**remote access, 164–165**  
cable, 172  
dial access, 166–167  
    *dial backup*, 168–169  
    *individual PSTN access*, 167  
    *PE-CE dial-out*, 169–170  
DSL, 170–171  
    *bridged encapsulation*,  
    171–172  
    *routed encapsulation*, 171  
network convergence, 174–175  
PE-CE connection, 173–174  
scalability, 174–175  
VPNs, 45–47  
**return on investment (ROI), 358**  
**reverse path forwarding (RPF), 279**

**ROI (return on investment), 358**  
**route tagging, IPv6 VPNs, 294**  
**routed encapsulation, DSL remote access, 171**  
**routing**  
Layer 3 VPNs  
    *constrained information distribution*,  
    142–144  
    *information separation*,  
    141–142  
    multipath noncompliance, 310  
    remote access, PE-CE connection, 173–174  
**RPF (reverse path forwarding), 279**  
**RTP (Real-Time Transport Protocol), 29**  
**Russian doll model, 263**

## S

**scalability**  
BGP signaling, 128  
equipment *versus* network,  
343–346  
    *element interaction*, 346–347  
    *management*, 351–354  
    *network-wide scale issues*, 349–350  
    *parameters*, 347–349  
Layer 3 VPNs, 154  
    *hierarchical VPNs*, 155–156  
    *inter-AS VPNs*, 154–155  
LDP signaling, 126  
MPLS TE, 243–244  
network design considerations, 342–343  
remote network access, 174–175  
tunnel protection, 242–243  
**schedulers, traffic, 254**  
**security**  
attack scenarios, 189–201  
best practice recommendations, 217–218  
IPSec, 201–208  
Layer 2 VPNs, 208–209  
    *CE router security*, 215–217  
    *CsC networks*, 212–215  
    *design options*, 209–211  
layered, 183  
management, 306–308, 324  
MPLS, 180–188  
MPLS Layer 3 services, 374  
MVPNs, 283–284

NGN (Next-Generation Networks),  
178–180

**segmentation, networks, 16–17**

**self-healing networks, MPLS future, 376–377**

**server VPNs, network segmentation, 16**

**service providers. See SPs**

**services**

- convergence, business drivers,  
9–14
- development technologies, 74–75
- examples, 29–30
- IEFT standards, 328–329
- Layer 2 VPNs, 34–35
  - Ethernet*, 35–37
  - NGN basics*, 39–42
- Layer 3 VPNs, 18–22, 42–44
- management
  - failures*, 317–318
  - fault management*, 306–308
  - multipaths*, 309–311
  - OAM interworking*, 314–317
  - user concerns*, 304–306
  - VCCV (Virtual Circuit Connection Verification)*, 311–314
  - VRF-aware ping*, 308–309
- outsourcing decisions, 14–15
  - central services*, 18
  - network segmentation*, 16–17
  - TCO (total cost of ownership)*, 15–16
- remote access, 45–47
- value-added, 48–53

**shared central services. See managed central services**

**signaling**

- Layer 2 VPNs, 124–126
  - BGP*, 128–131
  - LDP*, 126–128
- tunnels, traffic engineering,  
228–230

**Simple Network Management Protocol (SNMP), 332**

**SNMP (Simple Network Management Protocol), 332**

**spatial gambling, network scalability, 353**

**SPs (service providers), 4, 358**

- business engineering, 7–8
- enterprise markets, 7

- Equant case study
  - company background*,  
358–360
  - customer VPN bridge*,  
360–362
- industry challenges, 4–7
- Layer 3 VPNs services, 18–22
- outsourcing decisions, 14–15
  - central services*, 18
  - network segmentation*, 16–17
  - TCO (total cost of ownership)*, 15–16
- service convergence, business drivers, 9–14
- statistical guarantee, 255**
- Swallow, George, 366**
- switches, membership management, 276**

## T

**TCO (total cost of ownership), outsourcing decisions, 15–16**

**TCP (Transmission Control Protocol), 28**

**TDM (time-division multiplexer), 36, 367**

**TE (traffic engineering), 65, 84–91**

**technologies**

- benefits of MPLS, 71–73
- DiffServ, 91–94
- Layer 2 VPNs, 60–62, 95–99
- Layer 3 VPNs, 75–76
  - label stack role*, 80
  - peer-to-peer model*, 77–78
  - topologies*, 81–83
  - VRF*, 78–80
- MPLS application, 62–66
- QoS (quality of service), 66–69
  - DiffServ*, 69–70
  - multicast*, 70–71
- service development, 74–75
- TE (traffic engineering), 84–91

**temporal gambling, network scalability, 353**

**time to market (TTM), 5**

**time-division multiplexer (TDM), 36, 367**

**topologies, Layer 3 VPNs, 81–83**

**total cost of ownership (TCO), outsourcing decisions, 15–16**

**traffic**

- DiffServ, 262
- queuing, 253–254

- traffic engineering, 224**
  - application, 234
    - delay-sensitive traffic, 236–237*
    - Inter-AS TE, 235–236*
    - Intra-Area TE, 234*
    - QoS, 236*
  - IETF standards, 246
  - IP network operation, 224–227
    - IGP (Interior Gateway Protocol), 227*
    - packet forwarding, 230–233*
    - tunnel signaling, 228–230*
  - MPLS TE
    - multicast, 244–246*
    - scalability, 243–244*
  - MPLS technologies, 84–91
  - tunnel operations, 237
    - link failures, 237–239*
    - node protection, 239–240*
    - path protection, 241*
    - scalability, 242–243*
    - usage scenarios, 242*
- Traffic Engineering with MPLS, 233*
- traffic specification (Tspec), 67**
- traffic-engineered voice models, MPLS QoS, 266**
- transmission, traffic, 254**
- Transmission Control Protocol (TCP), 28**
- troubleshooting network design, 342–343**
- trust, VPN bridge case study, 361**
- Tspec (traffic specification), 67**
- TTM (time to market), 5**
- tunnel mode QoS, 261**
- tunnels**
  - LSP failures, 318
  - protection operations, 237
    - link failures, 237–239*
    - node protection, 239–240*
    - path protection, 241*
    - scalability, 242–243*
    - usage scenarios, 242*
  - TE (traffic engineering), signaling, 228–230

## U

- UCP (Unified Control Plane), 368**
  - IP and optical network integration
    - bandwidth on-demand service, 371*
    - basics, 368–370*
    - challenges, 371–372*
- UDP (User Data Protocol), 28**
- Unified Control Plane. *See* UCP**
- uniform mode QoS, 261**
- User Data Protocol (UDP), 28**
- user VPNs, network segmentation, 16**

## V

- value-added services, Layer 3 VPNs, 48–53**
- VCCV (Virtual Circuit Connection Verification), 311–314**
- VHG (virtual home gateway), 165**
- video, MPLS Layer 3, 373–374**
- videoconferencing, value-added services, 50**
- virtual access interface, dial access, 166**
- Virtual Circuit Connection Verification (VCCV), 311–314**
- virtual home gateway (VHG), 165**
- virtual leased line, MPLS QoS, 266**
- virtual private LAN service. *See* VPLS**
- virtual private networks. *See* VPNs**
- virtual routing, IPv6 VPNs, 294–295**
- voice, MPLS Layer 3, 373–374**
- VPLS (virtual private LAN service), 37. *See also* EMS**
  - forwarding at remote node, 375–376
  - Layer 2 VPNs, 123–124
- VPN bridges, customer case study, 360**
  - account team success factors, 361–362
  - company background, 360
  - conclusions, 362
  - divestiture issues, 360–361
- VPN Routing and Forwarding (VRF), 332**
- VPN-IP PIM, MVPNs deployment, 285**
- VPNs (virtual private networks), 164**
  - dynamic encryption, 373
  - IPv6, 294
    - IPv4 Layer 3 VPNs, 296*
    - packet path, 295–296*

*route tagging*, 294

*virtual routing*, 294–295

Layer 2, 95–99, 106–107

*AToM*, 111–114

*benefits*, 132–134

*inter-AS*, 135

*interworking*, 120–122

*like-to-like transport*,

115–119

*NGN basics*, 39–42

*provisioning*, 124–131

*reasons for building*, 22–26

*scalability*, 352–354

*services*, 34–37

*supported IETF standards*, 136–137

*taxonomy*, 108–111

*technologies*, 60–62

*VPLS*, 123–124

Layer 3, 140

*corporate extranets*, 148–149

*corporate intranets*, 146–148

*heterogeneous networks*, 156–157

*IETF drafts*, 161

*Internet access*, 149–153

MVPNs

*applications*, 281–282

*IETF drafts*, 285

*security considerations*,

283–284

**VRF (VPN Routing and Forwarding ), 332**

## W-Z

**weighted fair queuing (WFQ) 67**

**weighted random early detection (WRED) 67**

**WFQ (weighted fair queuing) 67**

**WRED (weighted random detection) 67**

**zones of trust 181**