

Index

A

- access rate, 22
- acknowledgements
 - forward, 60
 - TCP, 60
- ACLs (access control lists), IP extended
 - matchable fields, 194
- adaptation, traffic shaping, 353
- adaptive shaping, configuring, 354, 380–381
- adjusting Hardware Queue size settings, 258
- advanced integration modules (AIMs), 470
- advertised windows, 419
- AF (assured forwarding), 121
- AIMs (advanced integration modules), 470
- algorithms, 468–471
 - queue service, 93
 - service, 254
- analog phones, calls between, 35
- applications
 - NBAR, 219
 - QoS, requirements, 33
 - TCP, 67
 - UDP, error recovery, 66
- application-specific integrated circuits, 255
- architectural models, comparing, 129
- assigning WFQ sequence numbers, 278
- assured forwarding (AF), 121
- autofill, 51

B

- bandwidth
 - CAC, 102
 - compression, 469
 - cRTP, 471

- data, 63
- link efficiency, 99, 102
- optimizing, 9–10, 15
- VAD, 38
- video, 54, 56
- voice requirements, 35–37
- bandwidth command, 12**
 - configuring LLQ bandwidth reservation, 314–317
- bandwidth interface subcommand, 297, 480**
- bandwidth reservation, CBWFQ configuration, 302–305**
- Bc (committed burst)**
 - calculating, 348–350
 - CB policing default value, 395
 - configuring in CB shaping, 371, 374
- Be (best-effort) service, 129, 395–396**
- BECN (backward explicit congestion notification), 353**
- bits
 - CLP, 203
 - DE, 203
 - marking, 197
 - fields, 203*
 - IP header fields, 197, 200*
 - LAN CoS, 201–203*
- branches (Frame Relay), 341**
- buffers**
 - de-jitter delay, 45
 - one-way video, 56
- bytes, compression ratios, 468**

C

CAC (call admission control), 13, 51, 102

calculating

- Bc, 348–350
- propagation delay, 18
- serialization delay, 16
- SN for WFQ, 277
- Tc, 348–350
- weight for WFQ, 277

call admission control (CAC), 13, 51

CallManager, 35, 102

**CB (class-based) compression,
configuring, 471–475**

CB (class-based) marking, 218, 228

- configuring, 211–214, 222
- NBAR, 195, 219, 223, 222
 - matchable fields*, 197
- show commands, 223, 228

CB policing, 360

- Bc default values, 395
- Be default values, 395–396
- configuring, 384, 388–389
- dual-rate, 360, 392
- dual-rate, three-color, 363–365
- multi-action, 393
- policing by percent, 396
- policing by percentage, 393–395
- single-rate, three-color, 362
- single-rate, two-color, 360–361
- with Be, 363
- without Be, 361

CB shaping, 354

- adaptive shaping, configuring, 380–381
- Bc, configuring, 371, 374
- calculating rate increase per time interval, 354
- comparing with FRTS, 383–384

- configuring, 367–368, 371
- shape peak command, 379–380
- shaping by percent, 381–382

CBWFQ (Class-Based Weighted Fair Queuing), 146

- and Flow-Based WFQ, 297
- bandwidth reservation, 302–305
- class-default class queue, 290
- configuring, 291
- features, 291
- WRED, 433

CDT (congestive discard threshold), 281

**CEF (Cisco Express Forwarding),
enabling, 222**

cell loss priority (CLP), 203

CIR (committed information rate), 11, 96

class class-default command, 301

class-default class queue (CBWFQ), 290

class-default queues, 290

classes of QoS tools, 88

classification, 89, 92, 148, 192, 205, 211, 255

- CB marking, 218
- CB-Marking, 193–197
- design, 205, 211
- through VPN tunnels, 229–236
- WFQ, 274

class-map command, 147, 228

clock rate command, 12

CLP (cell loss priority), 203

codecs

- delay, 43
- MPEG, 53
- video, 55
- voice, 35

commands

- bandwidth, 12
- CB marking, 148, 178, 212–213, 237–238

- class class-default, 301
 - class-map, 147
 - clock rate, 12
 - frame-relay fragment, 502
 - frame-relay traffic-shaping, 501–502
 - interface multilink 9, 495
 - ip nbar pdlm pdlm-name, 223
 - ip nbar protocol discovery, 222
 - ip rtp priority, 489
 - load-interval, 227
 - multilink group 9, 495
 - multilink ppp, 495
 - NBAR, 219
 - policy-map, 147
 - ppp multilink fragment delay, 480
 - ppp multilink fragment-delay, 496
 - ppp multilink interleave, 496
 - priority, 306, 308, 312
 - service-policy, 147
 - service-policy output, 297
 - shape peak, configuring CB shaping, 379–380
 - show controllers, 261
 - show interface, 286
 - show interfaces, 439, 496
 - show ip nbar protocol-discovery, 223
 - show policy-map, 223, 297
 - show policy-map interface, 223, 446
 - show queue, 275
 - show queue serial 0/0, 438
 - show queueing, 503
 - show queuing, 438
 - show running-config, 446
 - subcommands. *See* subcommands.
- committed burst (Bc), 347**
- committed information rate (CIR), 11, 96**
- comparing**
- CB shaping and FRTS, 383–384
 - QoS models, 129
 - queuing tools, 317
- comparing queuing tools, 255**
- components of delay, 40**
- Compressed RTP (cRTP), 38**
- compression, 13, 26**
- classification, 148, 192
 - headers, 468–471
 - link efficiency, 99, 102
 - payload, 468–470
- configuring**
- adaptive traffic shaping, 354
 - CB marking, 211–214, 222
 - CB policing, 384, 388–389
 - Bc default values*, 395
 - Be default values*, 395–396
 - dual-rate*, 392
 - multi-action*, 393
 - policing by percentage*, 393–395
 - CB shaping, 367–368, 371
 - adaptive shaping*, 380–381
 - Bc*, 371, 374
 - shape peak command*, 379–380
 - shaping by percent*, 381–382
 - CBWFQ, 291, 302–305
 - ECN, 450–453
 - FIFO Queuing, 266
 - FRF.12, 508
 - FRTS, 501–502
 - LLQ, 307, 314–317
 - MLP, 496
 - MLP LFI, 508
 - NBAR, 219
 - QoS management tools, 103
 - QoS Pre-classification, 232–236
 - QPM, 159–161
 - RTP header compression, 471–475
 - TCP header compression, 471–475
 - traffic shaping
 - with Be*, 351–352
 - with no Be*, 350–351
 - WFQ, 282
- congestion**
- avoidance, 98–99
 - management, MDRR, 270
 - queuing, 92–94
- congestive discard threshold (CDT), 281**
- CQ (Custom Queuing), 269**
- creating, 69–70**
- creating service classes, 69–70**
- cRTP (Compressed RTP), 38, 471**
- customization, 205, 211**
- CWR (Congestion Window Reduced) flag, 450**

D

data

- bandwidth, 63
- delay, 64
- jitter, 65
- loss, 66
- traffic characteristics of, 58, 67, 78

data terminal equipment (DTE), 11, 96

data-link connection identifiers (DLCIs), 97, 356

DE (discard eligibility), 203

decreasing tail drop, 253

deep packet inspection, 196

deficit feature of MDRR, 272

defining policies for service classes, 70

de-jitter buffer delay, 45

delay, 95, 98

- codec, 43
- compression, 469
- data, 64
- de-jitter buffer delay, 45
- forwarding, 21
- maximum serialization, 479
- network, 22–23
- one-way budget guidelines, 41
- optimizing, 9–10, 15, 27
- packetization, 43
- propagation, 17–19
- QoS tools, 25–27
- queuing, 19–20, 253
- serialization, 16–17
- shaping, 21–22
- video, 56
- voice, 39

deploying QPM, 159–161

designing

- DiffServ, 112, 116, 126, 137
- GOCS class-based, 106
- GOCS flow-based, 103, 106
- IntServ, 126, 129
- Qos for enterprise networks, 108

devices, QPM, 160

differentiated services. See DiffSer, 83

DiffServ, 111

- marking packets, RFC recommended values, 210

QoS models

- classifiers*, 126
- per-hop behaviors*, 116, 126, 137
- specifications*, 112, 116

digital signal processor (DSP), 524

discard eligibility (DE), 203

discarding, logic, 426

DLCI (data-link connection identifier), 97

drop policies, 255

DSCP (Differentiated Services Code Point), 111, 439

DSP (digital signal processor), 524

DTE (data terminal equipment), 11, 96

dual FIFO output queues, 253

Dual FIFO queues, 481

dual token bucket CB policing, 363–365

dual-rate CB policing, 363–365

dual-rate policing, 360, 392

E

ECN (Explicit Congestion Notification), 447–448

- configuring, 450–453
- CWR flag, 450
- ECN field, 448

edge services router (ESR), 203

EF (expedited forwarding), 121

egress blocking, 343

EIGRP (Enhanced Interior Gateway Routing Protocol), 12

enabling

- CEF, 222
- traffic shaping, VCs, 356

encoding, serialization delay, 16–17

Enhanced Interior Gateway Routing Protocol (EIGRP), 12

enterprise networks

- efficient QoS design, 108
- VPN classification, 229–236

error recovery

- TCP, 61
- UDP, 66

ESR (edge services router), 203

excess burst (Be), traffic shaping, 350–352

expedited forwarding (EF), 121

F

- fair-queue interface subcommand, 286**
- features of CBWFQ, 291**
- FECN (forward explicit congestion notification), 353**
- fields**
 - DSCP, 111
 - IP ACL extended matchable, 194
 - marking, 197, 200–203
- FIFO (first in, first out) queuing, 252, 267**
- flow**
 - CAC, 102
 - GOCS flow-based QoS, 103, 106
- Flow-Based WRED (FRED), 423**
- Foreign Exchange Station (FXS), 223**
- Foresight Feedback, 353**
- forward acknowledgements, 60**
- forwarding delay, 21**
- fragmentation**
 - LFI, 475–477
 - FRF.12*, 481, 487, 497
 - MLP*, 487, 497
 - multipoint PPP*, 478
 - link efficiency, 99, 102
 - optimum fragment sizes, 479
- Frame Relay, 203**
 - bandwidth, 11
 - fragments, selecting sizes, 485
 - PVCs, shaping queues, 263
- frame-relay fragment command, 502**
- frame-relay traffic-shaping command, 501–502**
- FRED (Flow-Based WRED), 423**
- FRTS (Frame Relay Traffic Shaping)**
 - and *FRF.12*, 481
 - comparing with CB shaping, 383–384
 - configuring, 501–502
- FT (Finish Time), 276**
- Full Drop, 425**
- functions**
 - autofill, 51
 - CBWFQ, 291, 322
 - WFQ, 288, 321
- FXS (Foreign Exchange Station), 223**

G

- G.729 DSP, 524**
- gigabit switch router (GSR), 203**
- global synchronization, congestion-avoidance, 422**
- GSR 1200 series routers, MDRR, 270–272**

H

- Hardware Queues, 255, 258. *See also* TX Queues.**
- header compression, 100**
- headers**
 - compression, 468–471
 - SNA, 204
 - TCP/UDP, 61
- hidden WFQ queues, 281**
- hierarchical policy maps, 378**
- hold-queue limits, 280**
- hold-queue x out interface subcommand, 266**

I

- identifying traffic requirements, 68–69**
- implementing QoS policies, 68–70**
- input queuing, 92**
- inspecting packets, deep packet inspection, 196**
- integrated services. *See* IntServ.**
- interface multilink 9 command, 495**
- interfaces, 252, 255**
 - MQC, 118
 - queuing, 262–264
 - traffic shaping, 355–356
 - VIPs, 470
- interleaving, LFI, 475–478, 481, 487, 497**
- IntServ (Integrated Services), 83**
 - comparing with DiffServ, 129
 - QoS models, 126, 129
- IP (Internet Protocol)**
 - extended ACL matchable fields, 194
 - precedence, 117
- ip nbar pdlm pdlm-name command, 223**
- ip nbar protocol discovery command, 222**
- ip rtp priority command, 489**

J-L

jitter

- data, 65
- de-jitter buffer delay, 45
- optimizing, 9–10, 27–29
- queuing, 253
- video, 57
- voice, 48

large playout buffers, one-way video, 56

layers of SNA, 204

left-to-right directional flow, 41

LFI (link fragmentation and interleaving), 26, 101, 475–477

- FRF.12, 481, 487, 497
- MLP, 487, 497
- multipoint PPP, 478

link efficiency, 99, 102

link efficiency tools, header compression, 100

links

- header compression, 470–471
- propagation delay, 17–19
- serialization delay, 16–17

LLQ (Low Latency Queuing), 269, 305

load-interval command, 227

locations feature (CallManager), 102

logic, discarding, 426

loss

- congestion, 98–99
- data, 66
- optimizing, 9–10
- packets, TCP/UDP, 418, 421
- video, 57
- voice, 50

M

mark probability denominator (MPD), 426

marking packets

- CB-Marking, 193, 218
 - configuring, 211–214, 222*
 - NBAR, 195–197, 219, 223*
 - show commands, 223, 228*
- IP header fields, 197, 200
- LAN CoS, 201–203
- MPLS Experimental bits, 203

RFC recommended values, 210

through VPN tunnels, 230–236

match not command, 228

match protocol class-map subcommand, 219

match subcommand, 147

maximum serialization delay, 479

maximum thresholds, 425

MDRR (Modified Deficit Round Robin), 270–272

MIR (minimum information rate), 354

minimum thresholds, 425

MLP LFI, configuring, 508

models of QoS

- DiffServ, 112, 116, 126, 137
- GOCS class-based, 106
- GOCS flow-based, 103, 106
- IntServ, 126, 129

modification of queues, 259

Moving Pictures Experts Group (MPEG), 53

MPD (mark probability denominator), 426–427

MPEG (Moving Pictures Expert Group), 53

MPLS Experimental bits, 203

MQC (Modular QoS command-line interface), 118

multi-action policing, configuring, 393

multilink group 9 command, 495

multilink ppp command, 495

N

names

- marking fields, 204, 240
- precedence, 117

NBAR (Network-Based Application Recognition), 195, 219

- class commands, importance of order, 222
- matchable fields, 197

nested policy maps, 378

Network-Based Application Recognition (NBAR), 219

networks

- bandwidth, optimizing, 11
- delay, 22–23, 41
- PSTN, 13

NFS (Network File System), 66
no fair-queue interface subcommand, 266
no priority-group interface subcommand, 261

O

one-way delay budget guidelines, 41
one-way video, 56
operation of policing, 359–360
optimum fragment sizes, 479
optimizing traffic, 9–10
 bandwidth, 10, 15
 delay, 15, 27
 jitter, 27–29
options, 205, 211, 523–524
oversubscription, 504

P

packetization delay, 43
packets
 classification, 89, 92, 148, 192
 congestion avoidance, 98–99
 forwarding delay, 21
 LFI tools, 477
 network delay, 22–23
 policing, 95, 98
 queuing, 252, 255
 queuing delay, 19–20
 reordering, 92–94
 serialization delay, 16–17
 shaping delay, 21–22
 traffic shaping, 95, 98
payload compression, 468–470
payloads
 link efficiency, 99, 102
 video, 54
 voice, 35
PB Tents, 339, 343
PDLMs (packet descriptor language modules), 223
per-hop behaviors, DiffServ, 116, 126, 137
PDLMs (packet descriptor language modules), 223
point-to-point networks, bandwidth, 11
police command, 384

policies, 68–70
 defining for service classes, 70
 drop policies, 255
 implementing, 68
 QoS, 103
 QPM, 159–161
policing, 95, 98
 CB policing
 dual-rate, three color, 363–365
 single-rate, three color, 362
 single-rate, two color, 360–361
 dual-rate policers, 360
 operation, 359–360
 packets, 366–367
policing by percent, 396
policy maps, 378
policy-map command, 147
ppp multilink fragment delay command, 480, 496
ppp multilink interleave command, 496
PQ (Priority Queuing), 268–269
precedence
 IP, 117
 WRED, 430
priority command, 306–308, 312
Priority Queing (PQ), 268
propagation delay, 17–19
protocols
 cRTP, 38
 EIGRP, 12
 RTP, 34
 RTSP, 52
 SNMP, 66
 SSCP, 35
 TCP, 59, 422
 UDP, 59
PSTN (Public Switched Telephone Network), 13
PVCs (permanent virtual circuits), 262–263

Q

QoS Pre-classification, 231–236
QPM (QoS Policy Manager), 159–161
quantum value (QV), 271
queue service algorithm, 93
queuing tools, comparing, 317

queuing, 13, 25, 92–94, 252, 255, 270

- CBWFQ
 - and Flow-Based WFQ, 297*
 - bandwidth reservation, configuring, 302–305*
 - class-default class queue, 290*
 - configuring, 291*
 - features, 291*
- congestion avoidance, 98–99
- delay delay, 19–20
- depth, 424
- Hardware Queues, adjusting size settings, 258
- interfaces, 262–264
- length, 259
- LLQ, configuring bandwidth reservation, 314–317
- MDRR, 270–272
- output, 261
- PQ versus LLQ, 269
- shaping queues, 262
- tail drop, 422
- TCP starvation, 423
- tools, 255
 - CQ, 269*
 - FIFO, 267*
 - LLQ, 305*
 - PQ, 268*
 - WFQ, 273, 288, 322*
- traffic shaping, 356, 359
- TX Queue, 255
- video, recommended queue sizes, 56
- WFQ
 - classification, 274*
 - hidden queues, 281*
 - SN, calculating, 277*
 - weight, calculating, 277*

QV (quantum value), 271**R**

- Random Early Detection (RED), 30**
- random-detect interface subcommand, 438**
- ratios, compression, 468**
- RDT (RealNetworks Data Transport), 52**
- Real-Time Streaming Protocol (RTSP), 52**
- Real-Time Transport Protocol (RTP), 34**
- receiver windows, 419**

RED (Random Early Detection), 30

- congestion-avoidance, 418
- Full Drop, 425
- refilling dual token buckets with CB policing, 362–364, 405–406**
- reordering packets, 92–94**
- RFCs, recommended values for marking traffic, 210**
- routers**
 - ESR, 203
 - forwarding delay, 21
 - GSR, 203
 - network delay, 22–23
 - queuing, 252, 255
 - queuing delay, 19–20
 - shaping delay, 21–22
- RTP (Real-Time Transport Protocol), 34, 227**
- RTP header compression, configuring, 471–475**
- RTSP (Real-Time Streaming Protocol), 52**

S

- scheduling, 25, 92–94, 265**
 - CQ logic, 269
 - FIFO, 252
 - MDRR, 270–272
 - PQ logic, 268
 - WFQ, 275–276
- sequences, WFQ, 278**
- serialization delay, 16–17, 479**
- servers**
 - CallManager, 35
 - COPS, 129
 - QPM, 160
- service algorithms, 254**
- service classes, 69–70, 192**
- service-policy command, 147**
- service-policy output command, 297**
- services**
 - BE, 129
 - LLQ, 307
- shape peak command, configuring CB shaping, 379–380**
- shaping, 95, 98**
 - queues, 262
 - traffic, 27
- shaping delay, 21–22**
- shaping queues on Frame Relay PVCs, 263**

show commands

- CB policing, 384
- CB shaping, 368
- Frame Relay fragmentation, 497
- MLP interleaving, 488
- WRED, 435
- show controllers command, 261**
- show interface command, 286**
- show interfaces command, 439, 496**
- show ip nbar protocol-discovery command, 223**
- show policy-map command, 223, 297**
- show policy-map interface command, 223, 446**
- show queue command, 275**
- show queue serial 0/0 command, 438**
- show queueing command, 438, 503**
- show running-config command, 446**
- simple FIFO queuing, 266**
- Simple Network Management Protocol (SNMP), 66**
- single FIFO queues, 252**
- single-rate CB policing**
 - three color, 362
 - two color, 360–361
- Skinny Station Control Protocol (SSCP), 35**
- slamming the window shut, 420**
- sliding windows, 60**
- slow start threshold (SSTHRESH), 419**
- SN (Sequence Number), calculating for WFQ, 277**
- SNA (System Network Architecture), 204**
- SNMP (Simple Network Management Protocol), 66**
- specifications, DiffServ, 112, 116**
- speed mismatch, 344**
- SSCP (Skinny Station Control Protocol), 35**
- SSTHRESH (slow start threshold), 419**
- subcommands**
 - bandwidth interface, 297, 480
 - fair-queue interface, 286
 - hold-queue x out interface, 266
 - match, 147
 - match protocol class-map, 219
 - no fair-queue, 266
 - no priority-group interface, 261
 - random-detect interface, 438
 - tx-ring-limit 1 interface, 261

subinterfaces, queuing, 262–264

switches, GSR, 203

Systems Network Architecture (SNA), 204

T

tail drops, 13, 98–99, 422

congestion-avoidance, 422

decreasing, 253

WFQ, 273

Tc, calculating, 348–350

TCP (Transmission Control Protocol),

59, 418, 421

acknowledgements, 60

applications, 67

error recovery, 61

starvation, 422

TCP header compression, configuring,

471–475

TCP starvation, 423

TDM (time-division multiplexing), 275

TFTP (Trivial File Transfer Protocol), 66

three-color CB policing

dual-rate, 363–365

single-rate, 362

three-headed policers, 98

thresholds

CDT, 281

logic, discarding, 426

time-division multiplexing (TDM), 275

tools, 262–264

CAC locations feature (CallManager), 102

classification, 89, 92, 148, 192

Congestion Avoidance, queue depth, 99

congestion-avoidance

RED, 418

WRED, 427, 446

LFI, 475–477

link efficiency header compression, 100

marking, 218–219, 223, 228

policing, 95, 98

QoS

bandwidth, 13–15

delay, 25–27

jitter, 28–29

management, 103

- queuing, 255
 - CQ*, 269
 - FIFO*, 267
 - LLQ*, 305
 - PQ*, 268
 - WFQ*, 273, 288, 322
- shaping, 95, 98
- traffic policing, CB policing, 384

ToS (type of service), 204

traffic, 192

- bandwidth, optimizing, 10, 15
- classification, 148
- contracts, 338
- delay, optimizing, 15, 27
- jitter, optimizing, 27–29
- NBAR, 219
- optimizing, 9–10
- policing, 95, 98, 359–360, 367
- QoS requirements, 33
- shaping. *See* traffic shaping
- video, troubleshooting, 52, 58
- voice, troubleshooting, 33, 52

traffic shaping

- Bc, calculating, 348–350
- CB shaping
 - adaptive shaping, configuring, 380–381*
 - comparing with FRTS, 383–384*
 - configuring, 367–368, 371, 374, 379–380*
 - shaping by percent, 381–382*
- queuing, decision logic, 358
- shaping queues, 262–263
- with Be, configuring, 351–352
- with no Be, configuring, 350–351

Transmission Control Protocol (TCP).

See TCP

Transmit (TX) queues, 261

Transmit (TX) rings, 255

Trivial File Transfer Protocol (TFTP), 66

troubleshooting

- congestion, 92–94
- QoS
 - bandwidth, 13–15*
 - data, 58, 67, 78*
 - delay, 25–27*
 - jitter, 28–29*
 - video, 52, 58*
 - voice, 33, 52*

trust boundaries, 206

two color CB policing, single-rate, 360–361

two-headed policers, 98

TX Queue (Transmit Queue), 255, 261

TX Rings(Transmit Rings), 261

tx-ring-limit 1 interface subcommand, 261

type of service (ToS), 204

U-V

UDP (User Datagram Protocol), 59, 66

VAD (Voice Activity Detection), 38, 223

values

- compression, 468
- DSCP-based WRED, 431
- precedence, 117
- QV, 271
- WFQ, 278

VCs (virtual circuits), 11, 262–264

Versatile Interface Processors (VIPs), 470

video

- bandwidth, 54–56
- codecs, 55
- conferences, 53
- delay, 56
- jitter, 57
- loss, 57
- payloads, 54
- recommended queue sizes, 56
- traffic characteristics of, 52, 58

VIPs (Versatile Interface Processors), 470

VoFR (Voice over Frame Relay), voice

options, 34

voice

- delay, 39
- jitter, 48
- loss, 50
- traffic characteristics of, 33, 52

Voice Activity Detection (VAD), 38

Voice over Frame Relay (VoFR), 34

Voice over IP (VoIP), 34

W

weight, calculating for WFQ, 277

WFQ (Weighted Fair Queing), 273, 288, 322

classification, 274

configuring for RSVP flows, 282

hidden queues, 281

SN, calculating, 277

weight, calculating, 277

windows, sliding, 60

WRED (Weighted Random Early Detection)

CBWFQ, 289

congestion-avoidance, 427, 446

ECN, 447

configuring, 450–453

CWR flag, 450

ECN field, 448

MPD, 427

profiles, 427

with CBWFQ, 432