

Index

When looking up methods for PyQt widgets, also consider looking under their base classes, such as `QFrame`, `QWidget`, and `QObject`. Functions and methods are listed in their own right, and in most cases under their module or class. Where a method or function name is close enough to a concept, the concept is not listed. For example, there is no entry for “splitting strings”, but there is an entry for the `split()` methods.

Symbols

- `!=` (not equal operator), 47, 81, 82
- `"` (double quote), 21
- `%` (modulus/remainder operator, string formatting operator), 24, 26, 53, 84, 98
- `%=` (modulus augmented assignment operator), 84
- `&` (bitwise and operator, accelerator indicator), 38, 47, 143
- `'` (single quote), 21
- `()` (tuple creation operator, function and method call operator, expression operator), 30, 51, 54, 55, 81
- `*` (multiplication operator, replication operator, positional argument list indicator, `from ... import` operator), 19, 25, 84, 91
- `**` (power/exponentiation operator, keyword argument list indicator), 40
- `*=` (multiplication augmented assignment operator), 84, 91
- `+` (addition operator, concatenation operator), 25, 33, 84, 90, 500
- `+=` (addition augmented assignment operator, append operator), 84, 90, 234
- `-` (subtraction operator, negation operator), 84
- `--` (subtraction augmented assignment operator), 84
- `.` (dot operator), 78
- `/` (division operator), 84, 91
- `/=` (division augmented assignment operator), 84, 91
- `//` (“true” division operator), 84, 86, 91
- `//=` (“true” division augmented assignment operator), 84, 91
- `:` (suite follows indicator, slice index separator), 46
- `:/` (resource path, root of), 173
- `<` (less than operator), 47, 81, 82
- `<<` (`QDataStream` and `QTextStream` write operator, int and long shift left operator), 242, 245, 250, 254, 359, 435, 525, 533
- `<=` (less than or equal to operator), 38, 47, 81, 82
- `<>` (not equal operator—deprecated), 47
- `=` (name binding operator, object reference creation and assignment operator), 81, 82, 83
- `==` (equal operator), 13, 47, 81, 82
- `>` (greater than operator), 47, 81, 82
- `>=` (greater than or equal to operator), 38, 47, 81, 82
- `>>` (`QDataStream` and `QTextStream` read operator, int and long shift right operator), 245, 360, 435, 528, 532, 541

@ (decorator operator), 85
 [] (indexing operator, slicing operator), 22, 54, 93
 \ (escape character), 21, 51, 220
 \n (newline character), 51
 ^ (bitwise xor operator), 47
 _ (underscore character), 76, 80
 __ (double underscore), 77, 80, 82, 88
 `` (repr() operator), 83
 {} (braces), 46
 | (bitwise or operator), 38, 47
 ~ (bitwise not operator), 47
 € (euro symbol), 21

A

about() (QMessageBox), 200
 aboutToShow() signal (QMenu), 178, 187, 285, 292
 abs(), 40, 84, 403
 __abs__() (abs()), 84
 absolute positions and sizes, 119
 abstract base class, 102
 accelerator; *see* keyboard accelerator
 “accept” button, 141, 188
 accept()
 QDialog, 151, 154, 425
 QEvent, 314, 333, 391
 accepted() signal (QDialogButtonBox), 145, 150
 access, private and public, 76, 88
 accessor methods, 79–80
 action; *see* QAction
 action group; *see* QActionGroup
 activateWindow() (QWidget), 160, 289
 activeWindow() (QWorkspace), 296
 add() (set), 37, 38, 372, 556
 __add__() (+), 84, 90
 addAction() (QWidget), 172, 178, 180, 307, 330, 365, 392, 393
 addActions() (QWidget), 178
 addBindValue() (QSqlQuery), 448, 450
 addButton() (QDialogButtonBox), 150
 addDatabase() (QSqlDatabase), 446, 459
 addDays() (QDate), 491
 addDockWidget() (QMainWindow), 169, 186
 addEllipse()
 QGraphicsScene, 354
 QPainterPath, 374, 376
 addItem()
 QComboBox, 276
 QGraphicsScene, 354, 356, 362, 364, 371
 QListWidget, 418
 addItem() (QComboBox), 440
 addLayout()
 QBoxLayout, 146
 QGridLayout, 146, 151
 addLine() (QGraphicsScene), 354
 addMapping() (QDataWidgetMapper), 453, 456
 addMenu() (QMenu and QMenuBar), 177, 178
 addPath() (QGraphicsScene), 354
 addPixmap() (QGraphicsScene), 354
 addPolygon()
 QGraphicsScene, 354
 QPainterPath, 376
 addRect() (QGraphicsScene), 354, 355
 addSeparator(), 178, 180, 307
 QMenu, 178, 180
 QToolBar, 178, 180
 addSpacing() (QBoxLayout), 146
 addStretch() (QBoxLayout), 146
 addText() (QGraphicsScene), 354
 addToolBar() (QMainWindow), 179, 186
 addWidget()
 QLayout, 146, 151, 273
 QToolBar, 180
 addYears() (QDate), 490
 adjusted() (QRect/QRectF), 355, 367
 aggregation, 93
 Alert application, 112–116
 alignment, 168, 338, 429
 aliveness, of PyQt objects, 287–288, 289
 all(), 38

and operator, 47
anonymous functions; *see* lambda statement
antialiasing, 337, 342, 361, 369
any(), 38
append()
 list, 33
 QTextEdit, 120
application modal dialogs, 140
application termination, 115, 185
applicationDirPath() (QCoreApplication), 173
applicationName() (QCoreApplication), 194
applications
 lrelease, 207, 513, 518
 Make PyQt (makepyqt.pyw), 174, 206, 207, 216, 519
 mkpyqt.py, 174, 206, 207, 216, 519
 pylupdate4, 207, 513, 517, 518
 pyrcc4, 173, 174, 207
 pyuic4, 206, 207, 216, 221, 515
 Qt Assistant, 510
 Qt Linguist, 513
arg() (QString), 402, 418, 419, 423, 427, 428, 455, 513, 515
arguments; *see* parameters
argv variable (sys), 114
array module, 29
as keyword, 104
ASCII, 20, 22, 250, 501, 513, 555
 see also codecs, QString, and Unicode encodings
aspect ratio, 329, 400
assert statement, 69, 498, 500, 501, 502, 503, 504
AssertionError exception, 69
Asset Manager application, 457–469
assignment operators, 15, 83
associative array; *see* dict, defaultdict, and OrderedDict
atEnd() (QDataStream and QTextStream), 245, 252, 253, 254
attribute() (QDomElement), 261
AttributeError exception, 89, 101
attributes, 75, 78, 103, 106, 125

augmented assignment operators, 15, 16, 84, 90, 91
automatic disconnection, 130
automatic garbage collection; *see* garbage collection
automatic reparenting, 119
automatic signal–slot connections, 217
automatically deleting windows, 156, 284, 286

B

backslash escapes, 21, 22, 51
base class, 75, 76, 102
basename() (os.path), 189
beforeInsert() (QSqlTableModel), 470
beginInsertRows() (QAbstractItemModel), 432, 433
beginRemoveRows() (QAbstractItemModel), 433
bibliography; *see* books
binary chop algorithm, 93, 95, 238
binary data, 20
binary files, 240–248
binding names, 14–16
 see also assignment operators
bindValue() (QSqlQuery), 448, 450, 468
bisect module, 93, 238
bisect_left() (bisect), 95, 239, 498
bitwise operators, 47
BLOBs (Binary Large Objects), 449
block of code; *see* suite of code
block structure, 46
blockSignals() (QObject), 135
.bmp (image file), 193
books
 Core PYTHON Programming, 27
 Dive into Python, 327
 Mastering Regular Expressions, 220
 Python and XML, 256
 Python Cookbook, 27
 Python in a Nutshell, 27

books (*cont.*)

XML Processing in Python, 256

`bool()`, 83

bool type, 16–17, 46

Boolean context, 83

Booleans, 45, 46

bounding rectangle, 338, 367, 373,
377

`boundingRect()`

`QGraphicsItem`, 365, 366, 367, 373,
377

`QPainterPath`, 377

`boundValue()` (`QSqlQuery`), 450

braces, no need for, 46

break statement, 49, 50, 53

buddies, 143, 206, 215, 217

see also `QLabel.setBuddy()`

built-ins

`!=` operator, 47, 81, 82

`%` operator, 24, 26, 53, 84

`&` operator, 38, 47

`*` operator, 19, 25, 84, 91

`**` operator, 40

`*=` operator, 84, 91

`+` operator, 25, 33, 84, 90

`+=` operator, 84, 90

`-` operator, 38, 84

`-=` operator, 84

`.` operator, 78

`/` operator, 84, 91

`/=` operator, 84, 91

`//` operator, 84, 86, 91

`//=` operator, 84, 91

`<` operator, 47, 81, 82

`<=` operator, 38, 47, 81, 82

`=` operator, 81, 82, 83

`==` operator, 13, 47, 81, 82

`>` operator, 47, 81, 82

`>=` operator, 38, 47, 81, 82

`@` operator, 85

`[]` operator, 22, 54

`^` operator, 47

`|` operator, 38, 47

`~` operator, 47

`abs()`, 40, 84, 403

`all()`, 38

built-ins (*cont.*)

and operator, 47

`any()`, 38

as keyword, 104

assert statement, 69, 498, 500,
501, 502, 503, 504

`bool()`, 83

bool type, 16–17, 46

break statement, 49, 50, 53

`callable()`, 102

`chr()`, 21, 39

class statement, 69, 75, 76, 77, 85,
86, 103, 115

`cmp()`, 82, 89

complex type, 17–20

continue statement, 53

def statement, 55, 62–63, 77

del statement, 32, 355, 359, 361,
372, 556

dict type, 35–36, 51, 93

`dir()`, 39, 40

`divmod()`, 40

`enumerate()`, 87, 419, 498

`eval()`, 39, 81, 83, 89, 120, 247

except statement, 66–67

exceptions; *see* exceptions

False constant, 45

finally statement, 66, 70–71, 78,
541, 542, 543, 548, 550, 551, 553,
554, 556

`float()`, 40, 84, 91

float type, 17–20, 241

for loop, 50–51, 54, 59

frozenset type, 37, 552

`hasattr()`, 39, 102, 218, 336

`help()`, 37, 39

`hex()`, 40

`id()`, 13, 39, 231, 237, 418

if statement, 46–49

import statement, 18, 19

in operator, 25, 33, 36, 38, 45, 96

`int()`, 40, 84, 91, 256

int type, 16–17, 241

is statement, 13, 47, 57

built-ins (*cont.*)

- `isinstance()`, 39, 94, 102, 135, 289, 296, 359, 372, 375, 393, 395, 440, 496, 499, 502, 503
- `iter()`, 97, 237
- lambda statement, 61–62, 134, 453
- `len()`, 20, 25, 33, 36, 38, 96, 237, 503
- list type, 31–35, 93
- `long()`, 40
- long type, 16–17, 231, 241
- `max()`, 38
- `min()`, 38
- None constant, 13, 57
- not operator, 47
- object type, 76, 77, 78
- `oct()`, 40
- `open()`, 39, 70
- or operator, 47
- `ord()`, 21, 39, 50
- pass statement, 47
- `pow()`, 40
- print statement, 10, 26
- `property()`, 80
- `range()`, 39, 50–51, 54
- `repr()`, 81, 83, 89, 90, 98
- return statement, 58, 97, 554
- `round()`, 40, 91, 333
- set type, 37, 93
- `sorted()`, 52, 53, 63, 432, 434, 551
- special methods; *see* special methods
- `staticmethod()`, 85, 239, 288
- str type; *see* str type
- `sum()`, 38
- `super()`, 100, 153, 217
- True constant, 45
- try statement, 66, 70, 78, 541, 542, 543, 548, 550, 551, 553, 554, 556
- tuple type, 29–31, 30, 50, 87
- `type()`, 18, 39, 102
- `unichr()`, 21, 39, 236, 554
- unicode type; *see* unicode type
- while loop, 49–50

built-ins (*cont.*)

- with statement, 549
- `xrange()`, 51, 54
- yield statement, 58, 97, 237
- `button()`
 - `QDialogButtonBox`, 150, 158
 - `QMouseEvent`, 333
- buttons; *see* `QAbstractButton`, `QDialogButtonBox`, and `QPushButton`
- byte array; *see* `QByteArray`
- bytecode, 11, 111
- `bytesAvailable()` (`QIODevice`), 528, 531, 540

C

Calculate application, 116–121

- `__call__()`, 81
- `callable()`, 102
- callable, 63, 97, 102, 115, 128, 131
- callbacks; *see* object references to, under functions
- calling context, 64
- `canPaste()` (`QTextEdit`), 385
- case statement; *see* if statement
- `center()` (`QRect/QRectF`), 392, 393
- centering, 168, 338
- central widget, 168
- character escapes, 21, 22
- character formatting, 397
- `characters()` (`QXmlContentHandler`), 263
- checkable actions, 176, 177
- `chr()`, 21, 39
- class statement, 69, 75, 76, 77, 85, 86, 103, 115
- `clear()`, 98
 - dict, 36
 - `QListWidget`, 418
 - `QTableWidget`, 418
 - `QTextDocument`, 383
 - `QTreeWidget`, 420
 - set, 38
- `clearMessage()` (`QStatusBar`), 170, 232

- clearSelection() (QGraphicsScene), 356, 361, 362, 364
- click; *see* mousePressEvent() and mouseReleaseEvent()
- clicked() signal (QPushButton), 219
- client/server applications, 522
- clipboard; *see* QClipboard
- clipboard() (QApplication), 297, 311
- close button, 118, 121
- close()
 - file, 70, 555
 - QIODevice, 243, 259, 525, 528
 - QWidget, 175, 285, 289, 330
- closeAllWindows() (QMainWindow), 289, 293
- closeEvent() (QWidget), 175, 185, 187, 282, 285, 289, 293, 309, 551
- closeSubPath() (QPainterPath), 376
- closing dialogs, 118, 121
- closures; *see* partial function application
- cmp(), 82, 89
- __cmp__() (cmp()), 81, 82, 89, 416, 432
- code suite, 46
- codecs; *see* encodings
- codecs module, 255–256
 - open(), 255, 260, 501, 555
 - readline(), 255
- collections, 29–37, 92–98
- collections module, 29
 - defaultdict type, 529, 532, 545
- collidesWithPath() (QGraphicsItem), 366
- collidingItems()
 - QGraphicsItem, 366
 - QGraphicsScene, 354, 375
- collision detection, 349, 374, 375
- color palette; *see* QPalette
- column() (QModelIndex), 428, 431, 439, 461, 462, 486, 496, 503
- columnCount() (QAbstractItemModel), 427, 428, 433, 503
- combining comparison expressions, 47
- combobox; *see* QComboBox
- command-line arguments, 113, 114
- commercial licensing, 3
- commit() (QSqlDatabase), 449, 465, 468, 469
- communication mechanisms; *see* events and signals and slots
- compare() (QString), 435
- comparisons, 13, 38, 47, 57, 63, 82
 - cmp(), 89
 - __cmp__(), 89, 416, 432
 - creating operators for, 82
 - disallowing, 83
 - expressions, 47
 - operators, 47
 - see also* == operator, != operator, id(), and is statement
- compile() (re), 220
- complex type, 17–20
- composite widgets, 168, 280, 325–326
- composition, 93
- conditional expression, 49, 390
- connect() (QObject), 124, 130, 133, 145, 146, 151, 158, 453
- connecting to databases, 446
- connections; *see* signals and slots
- Connections application, 132–135
- connectSlotsByName() (QMetaObject), 217
- connectToHost() (QAbstractSocket), 525
- constructors; *see* initializers, __init__(), and __new__()
- containers; *see* collections, and dict type, list type, and tuple type
- contains()
 - QGraphicsItem, 366
 - QRect/QRectF, 357
 - QString, 234
 - QStringList, 189
 - __contains__() (in), 93, 96
- context managers, 549, 554
- context menus, 168, 180–181, 307, 365, 390
- contextMenuEvent()
 - QGraphicsItem, 365

- contextMenuEvent() (*cont.*)
 - QWidget, 307, 309, 390
 - continue statement, 53
 - control structures; *see* if, for, while, and try statements
 - controls; *see* QWidget
 - convenience widgets; *see* QListWidget, QTableWidgetItem, and QTreeWidgetItem
 - conventional entry point, 62
 - conversions
 - bool() conversion, 83
 - float() conversion, 40, 84, 91
 - generator to list, 58
 - int() conversion, 40, 84, 91
 - int to float, 14, 20
 - int to long, 17
 - long() conversion, 40
 - str() conversion, 81, 83, 90, 98
 - str to unicode, 20
 - unicode() conversion, 81, 83
 - unicode to QString, 28
 - coordinates, 309, 328–331, 339, 342, 350, 357, 374
 - copy constructor, unnecessary, 83
 - copy(), 98
 - copy module, 83, 88, 89
 - dict, 36
 - set, 38, 548, 551
 - copy module
 - copy(), 83, 88, 89
 - deepcopy(), 34, 83
 - copy_reg module, 247
 - copying, 34, 51, 88, 89, 98
 - cos() (math), 371, 375
 - count()
 - list, 33
 - str/unicode, 25
 - cPickle module, 235, 246–248
 - see also* pickle module
 - createActions() helper, 174–175
 - createEditor() (QAbstractItemDelegate), 436, 440, 461, 486, 487, 488, 491
 - createIndex() (QAbstractItemModel), 433, 504
 - critical() (QMessageBox), 188
 - cStringIO module, 23
 - see also* StringIO module
 - Currency Converter application, 121–127
 - current mouse position, 318
 - currentCharFormat() (QTextEdit), 393, 395
 - currentColumn() (QTableWidget), 422
 - currentDate() (QDate), 46, 236, 401, 490
 - currentDateTime() (QDateTime), 454
 - currentFrame() (QTextCursor), 404
 - currentIndex()
 - QAbstractItemView, 427, 463, 465, 466, 468, 469
 - QDataWidgetMapper, 454, 455
 - currentIndexChanged() signal (QComboBox), 124, 275
 - currentItem() (QTableWidget), 422
 - currentRowChanged() signal (QListWidget), 275
 - currentText() (QComboBox), 441
 - currying; *see* partial function application
 - cursor, text; *see* insertion point
 - cursorRect() (QTextEdit), 392, 393
 - custom data containers, 235
 - custom delegates, 436–442
 - custom models, 423–435
 - customized message boxes, 188
 - cut() (QTextEdit), 385
 - cycles, avoiding in signal–slot connections, 135
- ## D
- dangling else trap, not possible, 48
 - data containers, 235
 - data dictionary; *see* dict type
 - data()
 - QAbstractItemModel, 414, 427, 428, 429, 430, 433, 438, 441, 462, 481, 487, 488, 489, 491, 496, 503
 - QAction, 172, 393, 395
 - QMimeData, 315, 316

- data() (*cont.*)
 - QTableWidgetItem, 422
- data stream; *see* QDataStream
- data structures; *see* dict type, list type, and tuple type
- database forms; *see* QDataWidgetMapper and QSqlTableModel
- database() (QSqlDatabase), 465, 468, 469
- database queries; *see* QSqlQuery and SQL statements
- databases
 - connecting to, 446
 - data types, 447
 - drill-down, 467
 - drivers, 445
 - foreign keys, 455–457
 - in-memory, 446
 - master-detail forms, 458, 464, 469
 - prepared queries, 447
 - SELECT statements, 449–451
 - stored procedures, 448
 - transactions, 465–466, 468
 - see also* SQL statements
- dataChanged() signal (QAbstractItemModel), 431, 432, 478
- date formats, 250, 258
- date() (QDateTimeEdit), 487
- dates; *see* QDate and QDateTime
- dateTime() (QDateTime), 455
- DB2 database, 445
- Decimal class (decimal), 17–20
- decorations, window, 112
- decorators, 85–86, 218, 219
- deepcopy() (copy), 34, 83
- deeply nested loops, 69
- def statement, 55, 62–63, 77
- default arguments, 56
- defaultdict type (collections), 529, 532, 545
 - base class*, dict
- del statement, 32, 355, 359, 361, 372, 556
 - __del__() (del statement), 78
- delegates; *see* custom delegates and QItemDelegate
- deleteLater() (QObject), 287, 531, 539, 544
- deleting; *see* del statement, deleteLater(), garbage-collection, and remove()
- deleting windows, automatically, 156, 284, 286
- __delitem__() (del statement), 93, 95
- destroyed() signal (QObject), 286, 288
- destructors, 78
- device coordinates; *see* viewport coordinates
- device() (QDataStream), 525, 533
- dial; *see* QDial
- dialog buttons; *see* QDialogButtonBox and QPushButton
- dialogs, 145
 - closing, 118, 121
 - hiding, 118, 121, 160
 - modal, 140, 142, 511
 - modeless, 140, 155
 - showing, 160
 - see also* QDialog
- dict type, 35–36, 51–53, 93
 - clear(), 36, 98
 - __contains__() (in), 96
 - copy(), 36, 98
 - get(), 36, 95, 420, 532, 541, 551
 - has_key(), 96
 - items(), 36, 52, 97
 - __iter__(), 97
 - iterating, by keys, 50
 - iteritems(), 53, 97, 98
 - iterkeys(), 53, 97
 - itervalues(), 53, 97
 - keys(), 36, 51, 52
 - pop(), 36, 96
 - popitem(), 96
 - remove(), 95, 532, 543
 - __repr__(), 98
 - setdefault(), 36, 95, 532
 - values(), 36, 52, 96

- dict type (*cont.*)
 - see also* defaultdict type and OrderedDict example class
 - difference() (set), 38
 - dir(), 39, 40
 - dirname() (os.path), 173, 477, 496, 512
 - dirty flag, 168, 187, 192, 232, 356, 361, 362, 364, 365, 422, 425, 431
 - disabling widgets and actions, 219, 274, 385
 - discard() (set), 38
 - disconnect() (QObject), 130
 - division (/ and //), 17, 84, 86, 91
 - divmod(), 40
 - dock window; *see* QDockWidget
 - dock windows, 169–170
 - docstrings, 57, 77, 105
 - doctest module, 105–107
 - document() (QTextEdit), 286, 287, 383, 384, 385, 396
 - documentation, 27, 111
 - documentElement() (QDomDocument), 260
 - DOM parser, 259–262
 - done() (QDialog), 154, 457, 464
 - double-click; *see* mouseDoubleClickEvent()
 - double-quoted strings, 21
 - drag and drop, 312–317
 - drag icon, 316
 - dragEnterEvent() (QWidget), 309, 314, 316
 - dragMoveEvent() (QWidget), 309, 314, 315, 316
 - drawArc() (QPainter), 344
 - drawChord() (QPainter), 344
 - drawContents() (QTextDocument), 438, 489
 - drawConvexPolygon() (QPainter), 344
 - drawEllipse() (QPainter), 344, 374, 377, 481
 - drawImage() (QPainter), 344, 363, 400
 - drawLine() (QPainter), 338, 344
 - drawPath() (QPainter), 344, 377
 - drawPicture() (QPainter), 363
 - drawPie() (QPainter), 344
 - drawPixmap() (QPainter), 344, 363, 408
 - drawPoint() (QPainter), 344
 - drawPolygon() (QPainter), 338, 343, 344, 345
 - drawPolyline() (QPainter), 344, 345
 - drawRect() (QPainter), 337, 344, 368, 410
 - drawRoundRect() (QPainter), 344
 - drawText() (QPainter), 306, 338, 344, 408, 410, 481
 - drill-down, 467
 - driver()
 - QSqlDatabase, 449
 - QSqlQuery, 450
 - drivers, for databases, 445
 - dropEvent() (QWidget), 309, 315, 316
 - DSU (decorate, sort, undecorate), 551
 - duck typing, 101, 222, 497
 - dump() (pickle/cPickle), 248
 - duplicated data, avoiding, 413
 - dynamic attributes, 78
 - dynamic function definitions, 62–63
 - dynamic menus; *see* menus and QMenu
 - dynamic typing, 12, 13–15, 101
- ## E
- edit() (QAbstractItemView), 426, 465, 468
 - editing, in-place, 414, 458
 - editing, initiating, 417, 426, 440, 465, 468
 - editItem() (QTableWidget), 422
 - editor, IDLE, 10, 105, 382
 - editors; *see* IDEs
 - elif statement; *see* if statement
 - else statement; *see* if statement
 - emit() (QObject), 130, 131, 219, 333, 340, 391, 431, 440, 556
 - enabling widgets and actions, 219, 274, 385
 - encodings, 20, 250, 258, 501

- encodings (*cont.*)
 - ASCII, 20, 236, 250, 501, 555
 - Latin1, 20
 - UTF-8, 236, 250, 258, 501, 555
 - see also* codecs module, QString, and Unicode
- endElement() (QXmlContentHandler), 263
- endInsertRows() (QAbstractItemModel), 432, 433
- endRemoveRows() (QAbstractItemModel), 432, 433
- endsWith() (str/unicode), 25, 31, 555
- endsWith() (QString), 240
- ensureCursorVisible() (QTextEdit), 392, 393
- Enter keypress, 120, 145, 188, 391, 421, 422, 440, 511
- entities; *see* HTML
- entry point, no fixed, 62
- enumerate(), 87, 419, 498
- __eq__() (==), 81
- Eric4, IDE, 2, 10, 105, 382
- error handling, for files, 244
- errorString() (QIODevice), 241, 243, 250, 252, 258, 259, 528
- Esc keypress, 121, 161, 188, 421, 422
- escape()
 - Qt namespace, 258, 397, 401
 - re, 220
- escaped characters, 21, 22, 401
 - newlines, 51
- euro symbol (€), 21
- eval(), 39, 81, 83, 89, 120, 247
- event handlers; *see* events
- event loop, 115–116, 184, 221, 537, 539
- event() (QObject), 304, 309, 310, 384
- events, 115, 303–310
 - see also* closeEvent(), keyPressEvent(), keyReleaseEvent(), paintEvent(), resizeEvent(), timerEvent(), and wheelEvent()
- examples
 - Alert application, 112–116
 - Asset Manager application, 457–469
- examples (*cont.*)
 - Calculate application, 116–121
 - Connections application, 132–135
 - Currency Converter application, 121–127
 - FractionSlider class, 331–338
 - frange(), 55–57
 - Image Changer application, 165–200
 - Length class, 86–91
 - Multipedes application, 368–377
 - My Movies application, 227–265
 - OrderedDict class, 92–98
 - Page Designer application, 351–368
 - partial(), 64–65, 133
 - RichTextLineEdit class, 389–398
 - RomanSpinBox class, 326–328
 - Signals and Slots application, 128–131
 - simplified(), 61
 - simplify(), 59, 61
 - YPipe class, 339–345
- except statement, 66–67
 - see also* finally statement and try statement
- exceptions, 52, 66–71
 - AssertionError, 69
 - AttributeError, 89, 101
 - Exception, 68, 69
 - handling, 66–71
 - hierarchy, 67
 - IOError, 243, 244
 - KeyError, 94
 - NotImplementedError, 83, 102
 - OSError, 243, 244
 - RuntimeError, 288
 - StopIteration, 52, 58, 59
 - TypeError, 56
 - ValueError, 68, 114
 - vs. testing for errors, 68
- exec_()
 - QCoreApplication, 115, 184
 - QDialog, 142, 154, 511
 - QDrag, 316

- exec_() (*cont.*)
 - QMenu, 307, 365, 392, 393
 - QSqlQuery, 447, 448, 449, 450, 464, 468, 469
- exists() (QFile), 294
- exiting applications; *see* terminating applications
- expandItem() (QTreeWidgetItem), 421
- exporting files, 229
- extend() (list), 33
- extension; *see* file extensions
- extension dialogs, 276–280

- F**

- F2 keypress, 417, 422, 440
- False constant, 45
- fatalError() (QXmlErrorHandler), 263
- field-level validation, 140
- fieldIndex() (QSqlTableModel), 456
- file; *see* file type, open(), and QFile
- file dialog; *see* QFileDialog
- file error handling, 244
- file extensions
 - .bmp, .jpg, .jpeg, and .png (image files), 193
 - .pro (C++/Qt project file), 518
 - .py and .pyw (Python file), 11, 111, 207
 - .pyc and .pyo (Python bytecode file), 11, 207
 - .qm (Qt message file), 516, 518
 - .qrc (PyQt resource file), 173, 207, 517
 - .ts (translation source file), 517, 518, 519
 - .ui (user interface file), 206, 207, 515
- file formats, 241
- file handle, generator, 70
- file type
 - close(), 70, 555
 - __file__ variable, 173
- fileName() (QFileInfo), 189
- files, 70, 229
- fill() (QPixmap), 392
- fillPath() (QPainter), 344
- fillRect() (QPainter), 344, 438, 481, 489
- finally statement, 66, 70–71, 78, 541, 542, 543, 548, 550, 551, 553, 554, 556
 - see also* except statement and try statement
- financial calculations, 18
- find() (str/unicode), 24, 25, 68
- findText() (QComboBox), 142, 441, 457
- first() (QSqlQuery), 450
- firstChild() (QDomNode), 260
- fixed size, of widget, 277
- flags() (QAbstractItemModel), 427, 430, 433
- flags, window, 115
- float(), 40, 84, 91
- float type, 17–20, 241
 - %f format specifier, 26
- __float__() (float()), 84, 91
- floating-point division; *see* “true” division
- __floordiv__() (//), 84
- focus; *see* keyboard focus
- font; *see* QFont
- font()
 - QGraphicsTextItem, 359
 - QWidget, 336, 342
- for loop, 50–51, 54, 59
 - break statement, 53
 - continue statement, 53
 - else statement, 50, 53, 254
 - vs. list comprehensions, 96–97
- foreign keys, 455–457
- form design; *see* user interface design
- form-level validation, 140, 158, 491
- format specifiers, for %, 26
- formats, of images, 193
- formatting, of characters, 397
- forms, previewing, 215
- FractionSlider example class, 331–338
- frame; *see* QFrame
- frange() example, 55–57

from `__future__` import `division`, 86
 from `__future__` import
 with `statement`, 549
 from ... import `statement`; *see* import
 statement
 fromImage() (QPixmap), 199
 frozenset type, 37, 552
 function definitions, nested, 261
 functions; *see under the functions'*
 names, and built-ins
 as closures, 64
 dynamic definitions, 62–63
 nested, 65, 261
 object references to, 63, 64
 signatures, 56
 wrapping; *see* partial function
 application
 functools module
 partial(), 64–65, 133, 365

G

garbage collection, 15, 78, 168, 169,
 170
`__ge__` (>=), 81
 generating lists, 54
 generators, 54–55, 58–59, 70, 92, 97
 geometry() (QWidget), 357
 get() (dict), 36, 95, 420, 532, 541,
 551
 getcwd() (os), 173
 getDouble() (QInputDialog), 199
 getExistingDirectory() (QFile-
 Dialog), 547
 getInteger() (QInputDialog), 199
 getItem() (QInputDialog), 199
`__getitem__` ([]), 93, 94
 getOpenFileName() (QFileDialog), 193,
 194, 233, 234, 287, 295, 356
 getSaveFileName() (QFileDialog), 196
 getText() (QInputDialog), 199
 global functions; *see under the func-*
 tions' names, and built-ins
 global scope, 55
 globalPos() (QEvent), 307, 309
 gradient fills; *see* QLinearGradient

graphics items; *see* QGraphicsItem
 graphics scenes; *see* QGraphicsScene
 graphic transformations; *see* trans-
 formations
 graphics item coordinates, 350
 graphics, rotating, 349
 graphics, scaling, 349, 370, 374
 grid layout; *see* QGridLayout
 group() (re), 554
`__gt__` (>), 81

H

handling errors, reading and writ-
 ing files, 244
 has_key() (dict), 96
 hasattr(), 39, 102, 218, 336
 hasChildren() (QAbstractItemModel),
 433
 hasFeature() (QSqlDriver), 449
 hasFocus() (QWidget), 330, 426
 hasFormat() (QMimeData), 314, 316
 hash, Perl; *see* dict type
 hasHtml() (QClipboard), 312
 hasMouseTracking() (QWidget), 308
 hasSelection() (QTextCursor), 385
 headerData() (QAbstractItemModel),
 427, 430, 433, 503
 height() (QWidget), 330
 help(), 37, 39
 hex(), 40
 hide() (QWidget), 280, 330
 hiding dialogs, 118, 121, 160
 hiding widgets, 277, 280
 high-level communication mecha-
 nisms; *see* signals and slots
 homePath() (QDir), 545
 horizontal layout; *see* QHBoxLayout
 horizontal lines; *see* QFrame
 horizontalHeader() (QTableView), 463,
 464
 hotspot, icon, 316
 HTML (Hyper-Text Markup Lan-
 guage), 114, 117, 168, 188, 311,
 349, 381, 396, 397, 401, 488, 511,
 552

html() (QMimeData), 312

I

`__iadd__()` (+=), 84, 90

icon; *see* QIcon

icon, for dragging, 316

icon, hotspot, 316

id(), 13, 39, 231, 237, 418

idealWidth() (QTextDocument), 390,
439, 489

identifiers, 36

identity

 comparison of, 13, 57

 operators, 47

see also id(), and is statement

IDEs (integrated development environments)

 Eric4, 2, 10, 382

 IDLE, 9, 10, 60, 105, 382

if statement, 46–49

 conditional expression, 49

`__ifloordiv__()` (//=), 84

ignore() (QEvent), 186, 314

image; *see* QImage

image formats, 193

Image Changer application,
165–200

images, 168, 193, 195, 196

images, printing, 363

immutable objects, 15, 16, 20, 23, 29,
34, 35, 37, 57

`__imod__()` (%=), 84

import statement, 18, 19

 from `__future__`, 86, 549

 paths, 60

importing files, 229

`__imul__()` (*=), 84, 91

in-memory databases, 446

in operator, 25, 33, 36, 38, 45, 96

in-place editing, 414, 458

incomingConnection() (QTcpServer),
530, 539

indentation, 46

index()

 list, 33

index() (*cont.*)

 QAbstractItemModel, 433, 465, 468,
504

 QModelIndex, 427

 str/unicode, 24, 25, 68

indexing, 22, 30, 32

indexOf() (QString), 306, 387, 388

infinite recursion, risk of, 100

information() (QMessageBox), 188

inheritance, 76, 99–103, 103

`__init__.py` module, 104

`__init__()`, 77, 78, 437

initial processing, 184

initializers, 77

inputMask property (QLineEdit), 157

insert() (list), 33, 500

insertBlock() (QTextCursor), 404

insertImage() (QTextCursor), 404

insertion point, 386, 392, 393, 404

insertPlainText() (QTextEdit), 297

insertRecord() (QSqlTableModel), 464

insertRow() (QAbstractItemModel),
433, 465, 468

insertRows() (QAbstractItemModel),
426, 427, 432, 433

insertTable() (QTextCursor), 404

insertText() (QTextCursor), 384, 404

insort() (bisect), 499, 532, 543

insort_left() (bisect), 95, 238

insort_right() (bisect), 499

installEventFilter() (QObject), 304

installTranslator() (QCoreApplication),
516

instances

 callable, 97, 102

 copying, 88, 89

see also objects

int(), 40, 84, 91, 256

int type, 16–17, 241

 %i and %d format specifiers, 26

 promotion to float, 14, 20

 promotion to long, 17

see also long type

`__int__()` (int()), 84, 91

integer literals, 17

- integrated development environments; *see* IDEs
 - interactive, use of Python, 60
 - Interbase database, 445
 - interdependent actions; *see also* QAction, 176
 - interdependent values; *see* form-level validation
 - interfaces, 102
 - internalPointer() (QModelIndex), 504
 - interpreter, Python, 60
 - intersection() (set), 38
 - introspection, 102, 105
 - invertPixels() (QImage), 197
 - IOError exception, 243, 244
 - is statement, 13, 47, 57
 - isActive() (QSqlQuery), 449, 450
 - isAlive() helper, 287–288, 289
 - isalpha() (str/unicode), 25
 - isChecked() (QAction), 172, 176
 - isdigit() (str/unicode), 25, 238, 554
 - isEmpty()
 - QString, 233
 - QTextDocument, 385
 - isEnabled() (QAction), 172
 - isFile() (QFileInfo), 294
 - isinstance(), 39, 94, 102, 135, 289, 296, 359, 372, 375, 393, 395, 440, 496, 499, 502, 503
 - isModified() (QTextDocument), 287, 385
 - isNull()
 - QDate, 45
 - QDateTime, 45
 - QDomNode, 260
 - QImage, 400
 - QPixmap, 496
 - QString, 45
 - QStringList, 45
 - QTime, 45
 - ISO date format, 250, 258
 - isObscured() (QGraphicsItem), 366
 - isOpen() (QDataStream), 525
 - isRunning() (QThread), 547, 551
 - isSelected() (QGraphicsItem), 366
 - issubset() (set), 38
 - issuperset() (set), 38
 - __isub__() (==), 84
 - isValid()
 - QModelIndex, 427, 428, 504
 - QSqlQuery, 450
 - item() (QTableWidget), 422
 - itemChange() (QGraphicsItem), 362, 366
 - itemChanged() signal (QTableWidget), 417
 - items(), 97
 - dict, 36, 97
 - QGraphicsScene, 354, 372
 - iter(), 97, 237
 - __iter__() (iter()), 93, 97, 237
 - iterable, 50
 - iteration; *see* for loop, while loop, and generators
 - iterator protocol, 52
 - iterators, 52, 54, 87, 92, 97
 - iteritems() (dict), 97, 98
 - iterkeys() (dict), 97
 - itervalues() (dict), 97
 - __itruediv__() (/=), 84, 91
- ## J
- join()
 - os.path module, 496, 512, 555
 - str/unicode, 23, 25, 61, 193, 477
 - .jpg and .jpeg (image file), 193
- ## K
- key() (QKeyEvent), 307, 334, 365, 384, 391, 483
 - key sequences, 171–172, 175, 176
 - see also* QKeySequence
 - keyboard accelerator, 143, 144, 189, 299
 - keyboard focus, 206, 218, 304, 351, 364, 478
 - keyboard shortcut, 144, 394
 - keyboard users, support for, 149, 218, 390, 417, 482, 511

- KeyError exception, 94
- keypresses, 483
 - Enter, 120, 145, 188, 391, 421, 422, 440, 511
 - Esc, 121, 161, 188, 421, 422
 - F2, 417, 422, 440
 - Shift, 365
 - Tab, 206, 218, 310, 421, 422, 511
- keyPressEvent()
 - QGraphicsItem, 365
 - QWidget, 307, 309, 334, 391, 483
- keyReleaseEvent() (QWidget), 307
- keys() (dict), 36
- keyword arguments, 55, 59–61
- keywords, table of, 16

- L**
- label; *see* QLabel
- lambda statement, 61–62, 134, 453
- last() (QSqlQuery), 450
- lastError()
 - QSqlDatabase, 446, 450, 459, 465
 - QSqlQuery, 449
- lastIndexOf() (QString), 234
- Latin1 encoding, 20
- layout managers, 118–120, 123, 144–146, 145, 150, 209–210, 212, 213–215, 270–271, 332
- layout() (QWidget), 277
- layout policies, 270–271
 - `__le__` (<=), 81
- left() (QString), 234, 306
- len(), 20, 25, 33, 36, 38, 96, 237, 503
 - `__len__` (len()), 93, 96, 237, 503
- Length example class (length), 86–91
- length() (QString), 388
- level of detail, 374
- licensing, 3
- lifetime, of PyQt objects, 287
- line editor; *see* QLineEdit
- line width; *see* pen width
- lineEdit() (QAbstractSpinBox), 327
- list comprehensions, 53–54, 96–97
- list type, 31–35, 33, 38, 93
 - list type (*cont.*)
 - + concatenation operator, 33
 - append(), 33, 53
 - count(), 25, 33
 - extend(), 33
 - generating, 54
 - index(), 24, 33
 - indexing, 32
 - insert(), 33, 500
 - iterating, 50
 - pop(), 33, 355, 361
 - remove(), 32, 33
 - reverse(), 33
 - slicing, 32
 - sort(), 33, 53, 63, 95, 239
 - title(), 24
 - list widget; *see* QListWidget
 - listen() (QTcpServer), 529
 - literals
 - integer, 17
 - string, 20
 - live dialogs, 159–162
 - loading files, 184, 229, 240–248, 249–256, 256–265
 - local scope, 55
 - local variables, 87
 - locale; *see* QLocale and QString.arg()
 - localeAwareCompare() (QString), 416, 434
 - lock() (QMutex), 553, 554
 - lockForRead() (QReadWriteLock), 541, 542, 543, 548, 550, 551, 556
 - lockForWrite() (QReadWriteLock), 542, 543, 556
 - logical coordinates; *see* window coordinates
 - logical operators, 47
 - long(), 40
 - long type, 16–17, 231, 241
 - `%i` and `%d` format specifiers, 26
 - see also* int type
 - loops; *see* for statement and while statement
 - deeply nested, 69

low-level communication mechanisms; *see* events
 lower() (str/unicode), 25, 238
 lrelease application, 207, 513, 518
 __lt__ () (<), 81, 82, 432

M

Mac OS X detection, 218
 magic number, 241
 mailing lists, 5
 main(), conventional entry point, 62
 main window; *see* QMainWindow
 __main__ module attribute value, 106
 Make PyQt application
 (makepyqt.pyw), 174, 206, 207, 216, 519
 mangling names, 77, 88, 89
 mapFromGlobal() (QWidget), 357
 mapToGlobal() (QWidget), 309, 392, 393
 mapToScene() (QGraphicsView), 357
 master-detail forms, 458, 464, 469
 math module, 40, 117, 371, 375
 matrix()
 QGraphicsItem, 359, 377
 QGraphicsView, 370
 max(), 38
 maximum size, of layouts and widgets, 271
 maximumHeight() (QWidget), 390
 MDI (Multiple Document Interface), 290–300
 membership operators, 47
 menu separators, 178, 180
 menuBar() (QMainWindow), 186
 menus, 168, 177–178
 see also QMenu and QMenuBar
 mergeCurrentCharFormat() (QText-Edit), 395
 message box; *see* QMessageBox
 meta-characters
 regular expression, 220
 XML, 257, 258
 methods, 81

methods (*cont.*)
 static, 78
 virtual, 75, 99
 mid() (QString), 252
 MIME (Multipurpose Internet Mail Extensions) format, 310, 313
 mimeTypeData()
 QClipboard, 312
 QDropEvent, 314
 min(), 38
 minimizing windows, 297
 minimum size, of layouts and widgets, 270, 271, 335
 minimumHeight() (QWidget), 390
 minimumSizeHint() (QWidget), 271, 335, 340, 341, 479
 mirrored() (QImage), 198
 mkpyqt.py application, 174, 206, 207, 216, 519
 __mod__ () (%), 84
 modality, 140, 142, 511
 model() (QModelIndex), 438, 441, 462, 489
 modeless dialogs, 140, 155, 159, 286
 models; *see* custom models and QAbstractItemModel
 modifiers() (QInputEvent), 307, 365, 391
 modules, 104
 modulus (%), 53
 mouse position, 318
 mouse tracking; *see* hasMouseTracking() and setMouseTracking()
 mouseDoubleClickEvent()
 QGraphicsItem, 362
 QWidget, 308, 309, 417, 422, 440
 mouseMoveEvent() (QWidget), 309, 317
 mousePressEvent() (QWidget), 309, 333, 482
 mouseReleaseEvent() (QWidget), 308, 309
 move() (QWidget), 183, 330, 341
 moveBy() (QGraphicsItem), 366
 __mul__ () (*), 84, 91
 multifile applications, 104
 Multipedes application, 368–377

multiple document interface; *see*
MDI

multiple inheritance, 76, 103, 216,
217, 373

multiway branching; *see* if state-
ment

mutable objects, 16, 23, 28, 29, 31, 32,
34, 35, 37, 51, 57

mutually exclusive actions, 176
see also QAction

My Movies application, 227–265

MySQL database, 445

N

name mangling, 77, 88, 89

__name__ module attribute, 106

names, of variables, 76, 80, 88

namespaces, 19

__ne__() (!=), 81

__neg__() (-), 84

negative lookahead, in regular ex-
pressions, 387

nested functions, 65, 261, 554

network protocols, 521

new-style vs. old-style classes, 76

__new__(), 77, 78, 81

newlines, escaping, 51

newlines, universal, 256

newPage() (QPrinter), 410

next()
 iterator method, 52, 59, 97
 QSqlQuery, 449, 450, 451, 468, 469

nextSibling() (QDomNode), 260

nodeType() (QDomNode), 261

None constant, 13, 45, 57

__nonzero__() (bool()), 81, 83

not operator, 47

notify() (QCoreApplication), 305

NotImplementedError exception, 83,
102

number() (QString), 338

numRowsAffected() (QSqlQuery), 449,
450

O

object names; *see* QObject.setObjectName()
Name()

object references, 12, 55, 57, 58, 63,
64

object type, 76, 77, 78

objects
 callable, 97, 102
 comparing, 13
 copying, 88, 89
 function references, 63, 64
 immutable, 15, 16, 20, 23, 29, 34,
 35, 37, 57
 mutable, 16, 23, 28, 29, 31, 32, 34,
 35, 37, 51, 57
 ownership of, 119, 168, 170, 172,
 180, 355, 357, 359, 372, 376
 references, 12, 15, 55, 57, 58, 63,
 64

oct(), 40

ODBC database, 445, 448

okToContinue() helper, 187

old-style vs. new-style classes, 76

open()
 built-in, 39, 70
 codecs, 255, 260, 501, 555
 gzip, 248
 QIODevice, 241, 243, 250, 252, 258,
 259
 QSqlDatabase, 446, 459

Open Source licensing, 3

or operator, 47

Oracle database, 445, 448

ord(), 21, 39, 50

OrderedDict example class, 92–98

orientation, 430

os module
 walk(), 555

os.path module
 basename(), 189
 dirname(), 173, 477, 496, 512
 join(), 496, 512, 555

OSError exception, 243, 244

overloading, 75

ownership, of objects, 119, 168, 170,
172, 180, 355, 357, 359, 372, 376

P

- page size, printer, 400
- Page Designer application, 351–368
- pageRect() (QPrinter), 408
- paint devices; *see* QImage, QPainter, QPicture, QPixmap, QPrinter, QSvgGenerator, and QWidget
- paint()
 - QAbstractItemDelegate, 436, 438, 461, 486, 489
 - QGraphicsItem, 366, 368, 374, 377
- paintEvent() (QWidget), 306, 309, 336, 342, 480
- palette; *see* QPalette
- palette()
 - QApplication, 438, 489
 - QWidget, 337
- parameters, 55, 56
 - default, 56
 - keyword, 55, 59–61
 - passing by value, 57
 - positional, 55
- parent() (QObject), 433, 504
- parent, of widget, 118, 119, 172, 340, 372
- parenting, automatic, 119
- parse() (QXmlReader), 262
- parsing XML, 259–262, 262–265
- partial() example, 64–65
- partial() (functools), 64–65, 133, 365
- partial function application, 63–65, 133, 365
- pass-by-value, 57
- pass statement, 47
- pasteboard; *see* QClipboard
- patents, disadvantages of, for software, 222
- path() (QFileInfo), 233, 356
- path variable (sys), 60, 104
- PDF (Portable Document Format), 398, 401
- pen width, 144
- physical coordinates; *see* viewport coordinates
- pickle() (copy_reg), 247
- pickle module, 235, 246–248
 - see also* cPickle module
- pixmap; *see* QPixmap
- pixmap()
 - QClipboard, 311
 - QGraphicsPixmapItem, 359
- platform module
 - python_version(), 200
 - system(), 200, 217, 336, 390
- .png (image file), 193
- pointers; *see* object references
- policies for
 - file error handling, 244
 - size and layout, 270–271, 335
 - strings, 28, 228
- polymorphism, 99–103
- pop(), 96
 - dict, 36, 96
 - list, 33, 355, 361
 - set, 372
- popitem() (dict), 96
- populating list widgets, 418
- populating table widgets, 418
- populating trees, 420, 502
- portable document format; *see* PDF
- pos()
 - QCursor, 318, 357
 - QGraphicsItem, 359, 366
 - QMouseEvent, 309
- positional arguments, 55
- post-mortem validation, 140, 150, 151
- PostgreSQL database, 445
- PostScript, 401
- pow(), 40
- preferred size, of layouts and widgets, 271, 335
- prepare() (QSqlQuery), 448, 450, 468
- prepared queries, 447
- prepend() (QStringList), 189
- preserving aspect ratio, 329
- preventative validation, 140, 157, 159, 162, 327
- previewing forms, 215
- previous() (QSqlQuery), 449, 450

print statement, 10, 26
 trailing comma, 49
 print_() (QTextDocument), 403, 407
 printer; *see* QPrinter
 printImage() helper, 363
 printing, 170, 363, 398–410
 printing images, 363
 private names, 76, 80, 88
 .pro (C++/Qt project file), 518
 processEvents() (QCoreApplication),
 294, 537
 processing, at start-up, 184
 propagating hide and show calls,
 280
 properties, 80, 211, 322
 properties, of QObjects, 157, 211
 property()
 built-in, 80
 QObject, 322, 324
 .py and .pyw (Python file), 11, 111,
 207
 .pyc and .pyo (Python bytecode file),
 11, 207
 pylupdate4 application, 207, 513,
 517, 518
 PyQt4 modules; *see the individual*
 modules, QtCore, QtGui, etc.
 pyqtProperty() (QtCore), 322
 @pyqtSignature decorator (QtCore),
 218, 219
 PYQT_VERSION_STR variable, 200
 pyrcc4 application, 173, 174, 207
 python_version() (platform), 200
 pyuic4 application, 206, 207, 216,
 221, 515

Q

QAbstractButton (QtGui)
 base class, QWidget
 setCheckable(), 276, 278
 setText(), 370
 toggled() signal, 277, 280
 QAbstractItemDelegate (QtGui)
 base class, QObject

QAbstractItemDelegate (QtGui) (*cont.*)
 createEditor(), 436, 440, 461,
 486, 487, 488, 491
 paint(), 436, 438, 461, 486, 489
 setEditorData(), 436, 441, 462,
 486, 487, 488
 setModelData(), 436, 441, 462,
 486, 487, 488
 sizeHint(), 436, 439, 489
 QAbstractItemModel (QtCore), 425,
 433, 434, 445, 500
 base class, QObject
 beginInsertRows(), 432, 433
 beginRemoveRows(), 433
 columnCount(), 427, 428, 433, 503
 createIndex(), 433, 504
 data(), 414, 427, 428, 429, 430,
 433, 438, 441, 462, 481, 487, 488,
 489, 491, 496, 503
 dataChanged() signal, 431, 432,
 478
 endInsertRows(), 432, 433
 endRemoveRows(), 432, 433
 flags(), 427, 430, 433
 hasChildren(), 433
 headerData(), 427, 430, 433, 503
 index(), 433, 465, 468, 504
 insertRow(), 433, 465, 468
 insertRows(), 426, 427, 432, 433
 removeRow(), 434, 466, 469
 removeRows(), 427, 432, 434, 469
 reset(), 432, 434, 501, 502
 rowCount(), 426, 427, 428, 434,
 454, 455, 479, 481, 503
 setData(), 414, 427, 431, 434, 441,
 462, 465, 487, 488
 setHeaderData(), 434, 460, 462
 QAbstractItemView (QtGui)
 base class, QAbstractScrollArea
 currentIndex(), 427, 463, 465,
 466, 468, 469
 edit(), 426, 465, 468
 selectionModel(), 463
 setAlternatingRowColors(), 231,
 477
 setCurrentIndex(), 426, 465, 468

- QAbstractItemView (QtGui) (cont.)**
 setDragEnabled(), 312, 313, 315
 setEditTriggers(), 231
 setItemDelegate(), 437, 460, 463, 490
 setModel(), 425, 437, 460, 463, 477, 490
 setSelectionBehavior(), 231, 460, 463, 495
 setSelectionMode(), 231, 460, 463
 startDrag(), 316
- QAbstractScrollArea (QtGui)**
base class, QFrame
 viewport(), 392, 393
- QAbstractSlider (QtGui)**
base class, QWidget
 setRange(), 369
 setValue(), 128, 369
- QAbstractSocket (QtNetwork), 521**
base class, QIODevice
 connectToHost(), 525
 state(), 540
 waitForDisconnected(), 544
- QAbstractSpinBox (QtGui)**
base class, QWidget
 lineEdit(), 327
 setAlignment(), 340, 487
 validate(), 327, 328
- QAbstractTableModel (QtCore), 425, 427**
base class, QAbstractItemModel
- QAction (QtGui), 171–172, 175, 194, 385**
base class, QObject
 data(), 172, 393, 395
 editor, visual, 206
 isChecked(), 172, 176
 isEnabled(), 172
 setCheckable(), 393
 setChecked(), 172, 177, 393
 setData(), 172, 189, 392, 393
 setEnabled(), 172
 setSeparator(), 172
 setShortcut(), 171, 172
 setStatusTip(), 172
 setText(), 172
- QAction (QtGui) (cont.)**
 setToolTip(), 172
 setWhatsThis(), 172
 toggled() signal, 172, 176, 177
 triggered() signal, 172, 176
- QActionGroup (QtGui), 176**
- QApplication (QtGui), 113, 115, 304**
base class, QCoreApplication
 clipboard(), 297, 311
 palette(), 438, 489
 setQuitOnLastWindowClosed(), 121
- QBoxLayout (QtGui), 146, 326**
base class, QLayout
 addLayout(), 146
 addSpacing(), 146
 addStretch(), 146
 setStretchFactor(), 146
- QBrush (QtGui), 374, 377**
- QByteArray (QtCore), 313, 316, 358, 359, 525, 526, 533**
- QCalendarWidget (QtGui), 575**
- QCheckBox (QtGui), 575**
- QClipboard (QtGui), 297, 310–312**
base class, QObject
 hasHtml(), 312
 mimeTypeData(), 312
 pixmap(), 311
 setImage(), 311
 setMimeData(), 311
 setPixmap(), 311
 setText(), 297, 311
 text(), 297, 311
- QCloseEvent (QtGui), 186**
- QColor (QtGui), 337, 345, 371, 392, 393, 438, 481, 489**
- QComboBox (QtGui), 440, 576**
base class, QWidget
 addItem(), 276
 addItem(), 440
 currentIndexChanged() signal, 124, 275
 currentText(), 441
 findText(), 142, 441, 457
 setCurrentIndex(), 441, 457
 setEditable(), 440
 setModel(), 456

- QComboBox (QtGui) (*cont.*)
 - setModelColumn(), 456
- QContextMenuEvent (QtGui), 307
 - base class*, QInputEvent
- QCoreApplication (QtCore), 538
 - base class*, QObject
 - applicationDirPath(), 173
 - applicationName(), 194
 - exec_(), 115, 184
 - installTranslator(), 516
 - notify(), 305
 - processEvents(), 294, 537
 - quit(), 115
 - translate(), 513, 515
- QCursor (QtGui), 318
 - pos(), 318, 357
- QDataStream (QtCore), 240–246, 242,
245, 315, 316, 358, 359, 435, 525,
528, 531, 533, 540
 - atEnd(), 245
 - device(), 525, 533
 - isOpen(), 525
 - readBool(), 245
 - readDouble(), 241, 245
 - readIntn(), 243, 245, 360, 435
 - readUIntn(), 245, 528, 540
 - setVersion(), 241, 243, 245, 525,
528, 531, 533, 540
 - write(), 526, 533
 - writeBool(), 245
 - writeDouble(), 241, 245
 - writeIntn(), 241, 242, 245, 359,
435
 - writeUIntn(), 245, 525, 533
- QDataWidgetMapper (QtGui), 453, 456
 - base class*, QObject
 - addMapping(), 453, 456
 - currentIndex(), 454, 455
 - setCurrentIndex(), 454, 455
 - setItemDelegate(), 456
 - setModel(), 453, 456
 - setSubmitPolicy(), 453, 456
 - submit(), 454
 - toFirst(), 453, 456
- QDate (QtCore), 19, 45, 253, 513
 - addDays(), 491
- QDate (QtCore) (*cont.*)
 - addYears(), 490
 - currentDate(), 46, 236, 401, 490
 - isNull(), 45
 - toPyDate(), 532, 541
 - toString(), 258, 401
- QDateEdit (QtGui), 487, 576
 - base class*, QDateTimeEdit
- QDateTime (QtCore), 45, 454, 513
 - currentDateTime(), 454
 - dateTime(), 455
 - isNull(), 45
 - setDateTime(), 454
 - toString(), 455
- QDateTimeEdit (QtGui), 452, 576
 - base class*, QAbstractSpinBox
 - date(), 487
 - setCalendarPopup(), 487
 - setDate(), 487
 - setDateRange(), 452, 487
 - setDisplayFormat(), 452, 487
- QDesktopServices (QtGui), 510
- QDial (QtGui), 128
- QDialog (QtGui), 118, 154, 217
 - base class*, QWidget
 - accept(), 151, 154, 425
 - done(), 154, 457, 464
 - exec_(), 142, 154, 511
 - reject(), 215
 - setSizeGripEnabled(), 154
- QDialogButtonBox (QtGui), 145, 150,
576
 - base class*, QWidget
 - accepted(), 145, 150
 - addButton(), 150
 - button(), 150, 158
 - default button, 145, 188
 - rejected(), 145, 150
- QDir (QtCore)
 - homePath(), 545
 - toNativeSeparators(), 547, 551
- QDockWidget (QtGui), 169
 - base class*, QWidget
 - setAllowedAreas(), 169, 170
 - setFeatures(), 170
- QDomDocument (QtXml), 257, 259–262
 - base class*, QDomNode

- QDomDocument (QtXml) (*cont.*)
 - documentElement(), 260
 - setContent(), 259
 - toString(), 257, 260
- QDomElement (QtXml)
 - base class*, QDomNode
 - attribute(), 261
 - tagName(), 260
- QDomNode (QtXml)
 - firstChild(), 260
 - isNull(), 260
 - nextSibling(), 260
 - nodeType(), 261
 - toElement(), 260
 - toText(), 261
- QDoubleSpinBox (QtGui), 123, 578
 - base class*, QAbstractSpinBox
- QDrag (QtGui), 316
 - base class*, QObject
 - exec_(), 316
 - setHotSpot(), 316
 - setMimeData(), 316
 - setPixmap(), 316
 - start(), 316
- QDropEvent (QtGui)
 - base class*, QEvent
 - mimeData() (QDropEvent), 314
 - setDropAction(), 314, 315, 316
- QEvent (QtCore)
 - accept(), 314, 333, 391
 - globalPos(), 307, 309
 - ignore(), 314
 - type(), 384
- QFile (QtCore), 241, 243, 250, 252, 258, 259, 262
 - base class*, QFileDevice
 - exists(), 294
- QFileDialog (QtGui)
 - getExistingDirectory(), 547
 - getOpenFileName(), 193, 194, 233, 234, 287, 295, 356
 - getSaveFileName(), 196
- QFileInfo (QtCore), 189
 - fileName(), 189
 - isFile(), 294
 - path(), 233, 356
- QFont (QtGui), 335, 336, 408, 478
 - setPointSize(), 335, 336
- QFontComboBox (QtGui), 576
 - base class*, QComboBox
- QFontMetrics/QFontMetricsF (QtGui), 335, 336, 340, 341, 342, 390, 408, 439
- QFrame (QtGui), 277
 - base class*, QWidget
 - setFrameStyle(), 170, 278
- QGraphicsItem (QtGui), 349, 364, 365, 366, 367, 373, 376
 - boundingRect(), 365, 366, 367, 373, 377
 - collidesWithPath(), 366
 - collidingItems(), 366
 - contains(), 366
 - contextMenuEvent(), 365
 - isObscured(), 366
 - isSelected(), 366
 - itemChange(), 362, 366
 - keyPressEvent(), 365
 - matrix(), 359, 377
 - mouseDoubleClickEvent(), 362
 - moveBy(), 366
 - paint(), 366, 368, 374, 377
 - pos(), 359, 366
 - resetMatrix(), 366
 - rotate(), 360, 366, 371, 375, 377
 - scale(), 366
 - scene(), 366, 375
 - sceneBoundingRect(), 366, 379
 - setCursor(), 366
 - setEnabled(), 366
 - setFlag(), 366
 - setFlags(), 351, 356, 362, 364
 - setFocus(), 364, 366
 - setFont(), 362
 - setMatrix(), 362, 364, 367, 377
 - setPos(), 356, 362, 364, 367, 373, 375
 - setSelected(), 356, 362, 364, 367
 - setZValue(), 367
 - shape(), 365, 367, 374, 377
 - shear(), 367
 - translate(), 367

- QGraphicsItem (QtGui) (*cont.*)
 - update(), 365, 367
 - zValue(), 367
- QGraphicsLineItem (QtGui), 349
 - base class*, QGraphicsItem
- QGraphicsPixmapItem (QtGui), 349, 356
 - base class*, QGraphicsItem
 - pixmap(), 359
- QGraphicsRectItem (QtGui), 355
 - base class*, QAbstractGraphicsShapeItem
- QGraphicsScene (QtGui), 349, 354, 369
 - base class*, QObject
 - addEllipse(), 354
 - addItem(), 354, 356, 362, 364, 371
 - addLine(), 354
 - addPath(), 354
 - addPixmap(), 354
 - addPolygon(), 354
 - addRect(), 354, 355
 - addText(), 354
 - clearSelection(), 356, 361, 362, 364
 - collidingItems(), 354, 375
 - items(), 354, 372
 - removeItem(), 354, 355, 359, 361, 372
 - render(), 354, 361
 - selectedItems(), 358, 360, 361
 - setBackgroundBrush(), 354
 - setSceneRect(), 354, 369
 - update(), 354
 - views(), 354, 362
- QGraphicsSceneContextMenuEvent (QtGui), 365
 - base class*, QEvent
 - screenPos(), 365
- QGraphicsSimpleTextItem (QtGui), 349
 - base class*, QAbstractGraphicsShapeItem
- QGraphicsTextItem (QtGui), 349, 362
 - base class*, QGraphicsItem
 - font(), 359
 - toPlainText(), 359
- QGraphicsView (QtGui), 349, 351–352, 369, 577
 - base class*, QAbstractScrollArea
 - mapToScene(), 357
 - matrix(), 370
 - render(), 361
 - scale(), 352
 - setDragMode(), 352
 - setMatrix(), 370
 - setRenderHint(), 352, 369
 - setScene(), 354, 369
- QGridLayout (QtGui), 123, 144, 146, 150, 270, 273
 - base class*, QLayout
 - addLayout(), 146, 151
 - setColumnStretch(), 146
 - setRowStretch(), 146
- QGroupBox (QtGui), 577
- QHBoxLayout (QtGui), 144, 146, 270
 - base class*, QBoxLayout
- QIcon (QtGui), 173, 313, 392
- QImage (QtGui), 168, 195, 197, 198, 199, 329, 400
 - base class*, QPaintDevice
 - invertPixels(), 197
 - isNull(), 400
 - mirrored(), 198
 - rgbSwapped(), 197
 - save(), 196
 - scaled(), 199
 - size(), 363, 400
- QImageReader, 193
- QImageWriter, 196
- QInputDialog (QtGui), 199
- QInputEvent (QtGui)
 - base class*, QEvent
 - modifiers(), 307, 365, 391
- QIODevice (QtCore), 526
 - base class*, QObject
 - bytesAvailable(), 528, 531, 540
 - close(), 243, 259, 525, 528
 - errorString(), 241, 243, 250, 252, 258, 259, 528
 - open(), 241, 243, 250, 252, 258, 259
 - readAll(), 254

- QIODevice (QtCore) (*cont.*)
 waitForReadyRead(), 540
- QItemDelegate (QtGui), 436, 437,
 485–489
 base class, QAbstractItemDelegate
- QKeyEvent (QtGui), 307
 base class, QInputEvent
 key(), 307, 334, 365, 384, 391,
 483
- QKeySequence (QtGui), 171, 175, 285,
 292, 393
- QLabel (QtGui), 114, 168, 340, 577
 base class, QFrame
 setAlignment(), 168, 340
 setBuddy(), 143, 425
 setPixmap(), 199
- QLayout (QtGui), 146
 base class, QLayoutItem
 addWidget(), 146, 151, 273
 setSizeConstraint(), 277, 279
- QLCDNumber (QtGui), 577
- QLinearGradient (QtGui), 343
- QLineEdit (QtGui), 117, 310, 314, 440,
 461, 577
 base class, QWidget
 inputMask property, 157
 returnPressed() signal, 440
 setAlignment(), 461
 setInputMask(), 461
 setText(), 441, 462
 setValidator(), 461
 text(), 441
 textEdited() signal, 161, 217,
 218
- QListView (QtGui), 415, 578
 base class, QAbstractItemView
- QListWidget (QtGui), 275, 312, 315,
 414, 418, 578
 base class, QListView
 addItem(), 418
 clear(), 418
 currentRowChanged() signal, 275
 populating, 418
 setCurrentItem(), 418
- QListWidgetItem (QtGui), 316, 418
 setIcon(), 316
- QListWidgetItem (QtGui) (*cont.*)
 takeItem(), 316
- QLocale (QtCore), 513, 516
 .qm (Qt message file), 516, 518
- QMainWindow (QtGui), 168, 186, 284,
 290
 base class, QWidget
 addDockWidget(), 169, 186
 addToolBar(), 179, 186
 closeAllWindows(), 289, 293
 menuBar(), 177, 186
 restoreState(), 183, 186
 saveState(), 183, 186
 setCentralWidget(), 168, 186, 285
 statusBar(), 170, 186
- QMatrix and QTransform (QtGui), 356
 reset(), 370, 377
 scale(), 370
- QMdiArea (QtGui), 290
- QMenu (QtGui), 307, 365, 392, 393
 base class, QWidget
 aboutToShow() signal, 178, 187,
 285, 292
 addMenu(), 178
 addSeparator(), 178, 180, 307
 exec_(), 307, 365, 392, 393
- QMenuBar (QtGui), 177, 178
- QMessageBox (QtGui), 153, 187, 188,
 200, 361, 423, 455
- QMetaObject (QtCore), 217
 connectSlotsByName(), 217
- QMimeData (QtCore), 311, 313, 316
 base class, QObject
 data(), 315, 316
 hasFormat(), 314, 316
 html(), 312
 setData(), 316
 setHtml(), 311
- QModelIndex (QtCore), 414, 432, 504
 column(), 428, 431, 439, 461, 462,
 486, 496, 503
 index(), 427
 internalPointer(), 504
 isValid(), 427, 428, 504
 model(), 438, 441, 462, 489
 row(), 427, 491

- QModelIndex (QtCore) (*cont.*)
 - sibling(), 491
- QMouseEvent (QtGui), 309
 - base class*, QInputEvent
 - button(), 333
 - pos(), 309
- QMutex (QtCore), 541, 552, 553, 554
- QMutexLocker (QtCore), 554
- QObject (QtCore), 119, 127, 304, 322, 370
 - blockSignals(), 135
 - connect(), 124, 130, 133, 145, 146, 151, 158, 453
 - deleteLater(), 287, 531, 539, 544
 - destroyed() signal, 286, 288
 - disconnect(), 130
 - emit(), 130, 131, 219, 333, 340, 391, 431, 440, 556
 - event(), 304, 309, 310, 384
 - installEventFilter(), 304
 - parent(), 433, 504
 - properties, 157, 211
 - property(), 322, 324
 - sender(), 135, 289, 393, 395, 440
 - setObjectName(), 169, 183, 324
 - setProperty(), 322, 324
 - startTimer(), 370
 - timerEvent(), 372
 - tr(), 513, 514, 515
 - trUtf8(), 513
- QPainter (QtGui), 306, 328, 337, 342, 343, 344, 361, 363, 400, 407–410, 408, 480
 - drawArc(), 344
 - drawChord(), 344
 - drawConvexPolygon(), 344
 - drawEllipse(), 344, 374, 377, 481
 - drawImage(), 344, 363, 400
 - drawLine(), 338, 344
 - drawPath(), 344, 377
 - drawPicture(), 363
 - drawPie(), 344
 - drawPixmap(), 344, 363, 408
 - drawPoint(), 344
 - drawPolygon(), 338, 343, 344, 345
 - drawPolyline(), 344, 345
- QPainter (QtGui) (*cont.*)
 - drawRect(), 337, 344, 368, 410
 - drawRoundRect(), 344
 - drawText(), 306, 338, 344, 408, 410, 481
 - fillPath(), 344
 - fillRect(), 344, 438, 481, 489
 - restore(), 343, 346, 410, 438, 482, 489
 - rotate(), 343
 - save(), 343, 346, 438, 481, 489
 - scale(), 343
 - setBrush(), 337, 344, 345, 374, 377, 481
 - setFont(), 344, 408, 482
 - setMatrix(), 343
 - setPen(), 337, 338, 343, 344, 345, 374, 377, 409, 410, 481
 - setRenderHint(), 306, 337, 342, 343, 363
 - setViewport(), 329, 342, 343, 363
 - setWindow(), 329, 342, 343, 363
 - shear(), 343
 - translate(), 343, 438, 489
 - viewport(), 363, 400
- QPainterPath (QtGui), 374, 376
 - addEllipse(), 374, 376
 - addPolygon(), 376
 - boundingRect(), 377
 - closeSubPath(), 376
- QPaintEvent (QtGui), 480
 - base class*, QEvent
 - rect(), 480
- QPalette (QtGui), 337, 481
- QPen (QtGui), 368
 - setColor(), 368
 - setWidth(), 368
- QPicture (QtGui), 329
 - base class*, QPaintDevice
- QPixmap (QtGui), 199, 329, 392, 404, 408, 496
 - base class*, QPaintDevice
 - fill(), 392
 - fromImage(), 199
 - isNull(), 496

- QPoint/QPointF (QtCore), 309, 338, 343, 371
- QPolygon/QPolygonF (QtGui), 343, 345, 376
- QPrintDialog (QtGui), 361, 363, 400, 403, 404, 408
- QPrinter (QtGui), 170, 329, 353, 361, 363, 398, 400, 401
 - base class*, QPainterDevice
 - newPage(), 410
 - pageRect(), 408
 - setPageSize(), 353, 398, 400
- QProcess (QtCore), 537
- QProgressBar (QtGui), 578
- QPushButton (QtGui), 276, 278, 369, 578
 - base class*, QAbstractButton
 - clicked() signal, 219
 - default button, 145, 188
 - see also* QDialogButtonBox
- QRadioButton (QtGui), 577
- .qrc (PyQt resource file), 173, 207, 517
- QReadWriteLock (QtCore), 540, 541, 545, 552
 - lockForRead(), 541, 542, 543, 548, 550, 551, 556
 - lockForWrite(), 542, 543, 556
 - unlock(), 541, 542, 543, 548, 550, 551, 556
- QRect/QRectF (QtCore), 355, 357, 364, 376, 410
 - adjusted(), 355, 367
 - center(), 392, 393
 - contains(), 357
 - setBottom(), 365
 - setRight(), 365
 - size(), 400
- QRegExp (QtCore), 327, 386, 387, 461
- QRegExpValidator (QtGui), 157, 327, 461
- QScintilla add-on, 381, 382
- QScrollArea (QtGui), 476, 477, 479
- QSettings (QtCore), 182–183, 228, 282, 293, 514
 - base class*, QObject
- QSettings (QtCore) (*cont.*)
 - IniFormat constant, 228
 - value(), 183
- QSignalMapper (QtCore), 292, 297–300
- QSize (QtCore), 183, 335, 341, 390, 400, 439, 489
 - scale(), 363, 400
- QSlider (QtGui), 369, 578
 - base class*, QAbstractSlider
- QSpacerItem (QtGui), 212
 - base class*, QLayoutItem
- QSpinBox (QtGui), 180, 326, 340, 440, 578
 - base class*, QAbstractSpinBox
 - setRange(), 180, 340, 440
 - setSingleStep(), 440
 - setSuffix(), 180, 340
 - setValue(), 128, 180, 340, 441
 - textFromValue(), 327, 328
 - value(), 441
 - valueChanged(), 124, 128, 199
 - valueFromText(), 327, 328
- QSplitter (QtGui), 280–283, 477
 - base class*, QFrame
 - restoreState(), 282
 - saveState(), 282
 - setStretchFactor(), 283
- QSqlDatabase (QtSql), 446
 - addDatabase(), 446, 459
 - commit(), 449, 465, 468, 469
 - database(), 465, 468, 469
 - driver(), 449
 - lastError(), 446, 450, 459, 465
 - open(), 446, 459
 - rollback(), 449, 465, 469
 - setDatabaseName(), 446, 459
 - transaction(), 449, 465, 468, 469
- QSqlDriver (QtSql), 449
 - base class*, QObject
 - hasFeature(), 449
- QSqlQuery (QtSql), 445, 446–451, 450, 464, 468, 469
 - addBindValue(), 448, 450
 - bindValue(), 448, 450, 468
 - boundValue(), 450
 - driver(), 450

- QSqlQuery (QtSql) (*cont.*)
 - exec_(), 447, 448, 449, 450, 464, 468, 469
 - first(), 450
 - isActive(), 449, 450
 - isValid(), 450
 - last(), 450
 - lastError(), 449
 - next(), 449, 450, 451, 468, 469
 - numRowsAffected(), 449, 450
 - prepare(), 448, 450, 468
 - previous(), 449, 450
 - record(), 450
 - seek(), 449, 451
 - setForwardOnly(), 451
 - size(), 450
 - value(), 449, 450, 451
- QSqlQueryModel (QtSql)
 - base class*, QAbstractTableModel
 - record(), 464, 465, 466, 469
 - setQuery(), 464
- QSqlRecord (QtSql)
 - value(), 464, 465, 466, 469
- QSqlRelation (QtSql), 456, 460, 462
- QSqlRelationalDelegate (QtSql), 456, 460, 461
- QSqlRelationalTableModel (QtSql), 445, 456, 462
 - base class*, QSqlTableModel
 - relationModel(), 456
 - setRelation(), 456, 460, 462
- QSqlTableModel (QtSql), 445, 453
 - base class*, QSqlQueryModel
 - beforeInsert(), 470
 - fieldIndex(), 456
 - insertRecord(), 464
 - select(), 453, 456, 460, 462, 464, 469
 - setFilter(), 464, 469
 - setSort(), 453, 456, 460, 462
 - setTable(), 453, 456, 460, 462
 - submitAll(), 455, 466, 469
- QSqlSocket (QtNetwork), 521
- QStackedWidget (QtGui), 274–276
 - base class*, QFrame
 - setCurrentIndex(), 275
- QStatusBar (QtGui)
 - QStatusBar (QtGui) (*cont.*)
 - base class*, QWidget
 - clearMessage(), 170, 232
 - setSizeGripEnabled(), 170
 - showMessage(), 170, 233
- QString (QtCore), 19, 23, 28, 233, 234, 256, 313, 402
 - arg(), 402, 418, 419, 423, 427, 428, 455, 513, 515
 - compare(), 435
 - contains(), 234
 - endsWith(), 240
 - indexOf(), 306, 387, 388
 - isEmpty(), 233
 - isNull(), 45
 - lastIndexOf(), 234
 - left(), 234, 306
 - length(), 388
 - localeAwareCompare(), 416, 434
 - mid(), 252
 - number(), 338
 - simplified(), 61, 422
 - split(), 253
 - startsWith(), 252
 - toInt(), 251, 422
 - toUpper(), 327
 - trimmed(), 252, 422
 - see also* str type and unicode type
- QStringList (QtCore), 45, 189
 - contains(), 189
 - isNull(), 45
 - prepend(), 189
 - takeLast(), 189
- QStyleOptionGraphicsItem (QtGui), 374
- QStyleOptionViewItem (QtGui), 438, 439, 461
- QSvgGenerator (QtGui), 329, 363
 - base class*, QPainterDevice
- QSvgRenderer (QtSvg), 363
- QSyntaxHighlighter (QtGui), 386–389
- Qt namespace, 258
 - escape(), 258, 397, 401
 - WindowStaysOnTopHint, 529
- Qt Assistant application, 510

- Qt Designer* application, 205–216, 272, 274, 275, 276, 277, 280, 324, 326, 333
- Qt.ItemDataRole (QtGui), 231
- Qt Linguist* application, 513
- Qt.WidgetAttribute (QtGui)
 - WA_DeleteOnClose, 156, 158, 284, 286
 - WA_GroupLeader, 511
- QTableView (QtGui), 415, 425, 437, 458, 460, 463, 477, 490, 579
 - base class*, QAbstractItemView
 - horizontalHeader(), 463, 464
 - resizeColumnsToContents(), 232, 419, 460, 463, 490
 - setColumnHidden(), 460, 463
 - setSortingEnabled(), 418, 419
- QTableWidget (QtGui), 230–232, 310, 313, 414, 418, 579
 - base class*, QTableView
 - clear(), 418
 - currentColumn(), 422
 - currentItem(), 422
 - editItem(), 422
 - item(), 422
 - itemChanged() signal, 417
 - populating, 418
 - scrollToItem(), 232
 - setColumnCount(), 231, 418
 - setCurrentItem(), 232, 419
 - setHorizontalHeaderLabels(), 231, 418
 - setItem(), 231, 419
 - setRowCount(), 231, 418
- QTableWidgetItem (QtGui), 231–232, 418, 419
 - data(), 422
 - setData(), 419
 - setSelected(), 232, 419
 - setTextAlignment(), 231, 419
 - text(), 422
- QTabWidget (QtGui), 272–274, 579
 - base class*, QWidget
- QtCore module (PyQt4), 19
 - pyqtProperty(), 322
 - @pyqtSignature(), 218, 219
- QtCore module (PyQt4) (*cont.*)
 - PYQT_VERSION_STR variable, 200
 - QT_VERSION_STR variable, 200
 - SIGNAL(), 131
 - SLOT(), 131
 - see also under class names*
- QTcpServer (QtNetwork), 529, 530, 539
 - incomingConnection(), 530, 539
 - listen(), 529
- QTcpSocket (QtNetwork), 522, 524, 531, 540
 - base class*, QAbstractSocket
- QTextBlock (QtGui), 396
- QTextBlockFormat (QtGui), 404
- QTextBrowser (QtGui), 117, 381, 511, 579
 - base class*, QTextEdit
- QTextCharFormat (QtGui), 386, 387, 404
- QTextCursor (QtGui), 297, 384, 403–407
 - currentFrame(), 404
 - hasSelection(), 385
 - insertBlock(), 404
 - insertImage(), 404
 - insertTable(), 404
 - insertText(), 384, 404
 - removeSelectedText(), 297
 - selectedText(), 297
 - setPosition(), 406
- QTextDocument (QtGui), 381, 383, 396, 398, 401–407, 403, 438, 439, 489
 - base class*, QObject
 - clear(), 383
 - drawContents(), 438, 489
 - idealWidth(), 390, 439, 489
 - isEmpty(), 385
 - isModified(), 287, 385
 - print_(), 403, 407
 - setDefaultFont(), 438, 439, 489
 - setHtml(), 403, 438, 439, 489
 - setModified(), 286, 383, 384
 - toHtml(), 407
- QTextEdit (QtGui), 285, 310, 381, 383, 390, 392, 579

- QTextEdit (QtGui) (*cont.*)
 - base class*, QAbstractScrollArea
 - append(), 120
 - canPaste(), 385
 - currentCharFormat(), 393, 395
 - cursorRect(), 392, 393
 - cut(), 385
 - document(), 286, 287, 383, 384, 385, 396
 - ensureCursorVisible(), 392, 393
 - insertPlainText(), 297
 - mergeCurrentCharFormat(), 395
 - setHtml(), 488
 - setLineWrapMode(), 390
 - setPlainText(), 384
 - setTabChangesFocus(), 390
 - setTextColor(), 393
 - textCursor(), 297, 384, 385
 - toHtml(), 395
 - toPlainText(), 384, 395
- QTextOption (QtGui), 409
- QTextStream (QtCore), 250–255, 254, 258, 384
 - atEnd(), 252, 253, 254
 - readAll(), 384
 - readLine(), 252, 253, 254
 - setCodec(), 250, 252, 254, 258, 384
- QTextTableFormat (QtGui), 404
- QtGui module (PyQt4), 19
 - see also under class names*
- QThread (QtCore), 538, 540
 - isRunning(), 547, 551
 - run(), 538, 540, 548, 553
 - start(), 539, 547, 553
 - wait(), 547, 548, 551
- QTime (QtCore), 45
 - isNull(), 45
 - see also* time module
- QTimeEdit (QtGui), 576
 - base class*, QDateTimeEdit
- QTimer (QtCore), 373, 376
 - base class*, QObject
 - singleShot(), 115, 306
 - start(), 373, 376
 - timeout() signal, 373, 376
- QtNetwork module (PyQt4), 521, 523
 - see also under class names*
- QToolBar (QtGui), 179–180, 180
 - base class*, QWidget
 - addSeparator(), 178, 180
- QToolTip (QtGui), 171, 200, 514
- QTransform (QtGui), 356
- QTranslator (QtCore), 516
- QTreeView (QtGui), 415, 495, 579
 - base class*, QAbstractItemView
 - populating, 502
 - setItemsExpandable(), 420
 - setUniformRowHeights(), 495
- QTreeWidgetItem (QtGui), 414, 579
 - base class*, QTreeView
 - clear(), 420
 - expandItem(), 421
 - populating, 420
 - setColumnCount(), 420
 - setCurrentItem(), 421
 - setHeaderLabels(), 420
- QTreeWidgetItem (QtGui), 420, 421
- QtSql module (PyQt4), 445, 446
 - see also under class names*
- QtSvg module (PyQt4), 363
 - see also under class names*
- QT_VERSION_STR variable, 200
- QtXml module (PyQt4), 235
 - see also under class names*
- QUdpSocket (QtNetwork), 522
 - base class*, QAbstractSocket
- queries, database; *see* QSqlQuery and SQL statements
- question() (QMessageBox), 187, 188, 361, 423, 455
- quit() (QCoreApplication), 115
- quitting applications; *see* terminating applications
- quoted strings; *see* string literals
- QVariant (QtCore), 183, 185, 231, 323, 392, 414, 427, 428, 429, 430, 441, 448, 451, 488, 496
 - toBool(), 324
 - toDate(), 487, 491
 - toDateTime(), 449
 - toDouble(), 481

- QVariant (QtCore) (*cont.*)
 toInt(), 395, 431, 449
 toLongLong(), 422
 toString(), 427, 431, 441, 449, 488
- QVBoxLayout (QtGui), 146, 270
base class, QVBoxLayout
- QWidget (QtGui), 118, 119, 127, 168, 273, 305, 306, 309, 322–324, 324, 325–326, 328, 329, 330, 331, 370, 421
base classes, QObject and QPaintDevice
 activateWindow(), 160, 289
 addAction(), 172, 178, 180, 307, 330, 365, 392, 393
 addActions(), 178
 close(), 175, 285, 289, 330
 closeEvent(), 175, 185, 187, 282, 285, 289, 293, 309, 551
 contextMenuEvent(), 307, 309, 390
 dragEnterEvent(), 309, 314, 316
 dragMoveEvent(), 309, 314, 315, 316
 dropEvent(), 309, 315, 316
 font(), 336, 342
 geometry(), 357
 hasFocus(), 330, 426
 hasMouseTracking(), 308
 height(), 330
 hide(), 279, 330
 keyPressEvent(), 307, 309, 334, 391, 483
 keyReleaseEvent(), 307
 layout(), 277
 mapFromGlobal(), 357
 mapToGlobal(), 309, 392, 393
 maximumHeight(), 390
 minimumHeight(), 390
 minimumSizeHint(), 271, 335, 340, 341, 479
 mouseDoubleClickEvent(), 308, 309, 417, 422, 440
 mouseMoveEvent(), 309, 317
 mousePressEvent(), 309, 333
 mouseReleaseEvent(), 308, 309
- QWidget (QtGui) (*cont.*)
 move(), 183, 330, 341
 paintEvent(), 306, 309, 336, 342, 480
 palette(), 337
 raise_(), 160, 289, 330
 rect(), 306, 330
 resize(), 183
 resizeEvent(), 306, 309, 341
 restoreGeometry(), 183, 186, 330
 saveGeometry(), 183, 186, 330
 setAcceptDrops(), 312, 313, 314, 315, 316, 330
 setAttribute(), 156, 284, 330, 511
 setContextMenuPolicy(), 168, 330, 365
 setCursor(), 330
 setEnabled(), 219, 330
 setFocus(), 120, 310, 330, 422
 setFocusPolicy(), 180, 217, 331, 369, 478
 setFont(), 330
 setLayout(), 273, 279, 330
 setMaximumHeight(), 390
 setMinimumHeight(), 390
 setMinimumSize(), 168, 340
 setMinimumWidth(), 340
 setMouseTracking(), 308, 334
 setSizePolicy(), 330, 331, 340
 setStatusTip(), 171, 180
 setStyleSheet(), 323, 330
 setTabOrder(), 206
 setToolTip(), 171, 180, 390
 setVisible(), 277, 280
 setWindowFlags(), 529
 setWindowIcon(), 186, 330
 setWindowModified(), 192
 setWindowTitle(), 146, 151, 186, 330, 370
 show(), 115, 155, 280, 286, 330, 511
 showMinimized(), 297
 showNormal(), 297
 sizeHint(), 335, 390, 479
 update(), 306, 330, 332, 479, 482

- QWidget (QtGui) (*cont.*)
 - updateGeometry(), 330, 332, 479
 - wheelEvent(), 352
 - width(), 330
 - QWorkspace (QtGui), 290, 297
 - base class*, QWidget
 - activeWindow(), 296
 - setActiveWindow(), 292, 295
 - windowList(), 295
 - QXmlContentHandler (QtXml)
 - characters(), 263
 - endElement(), 263
 - startElement(), 263
 - QXmlDefaultHandler (QtXml), 263
 - base class*, QXmlContentHandler
 - QXmlErrorHandler (QtXml)
 - fatalError(), 263
 - QXmlInputSource (QtXml), 262
 - QXmlReader (QtXml)
 - parse(), 262
 - setContentHandler(), 262
 - setErrorHandler(), 262
 - QXmlSimpleReader (QtXml), 262–265
 - base class*, QXmlReader
 - gzip module, 248
- R**
- __radd__() (+), 84
 - radians() (math), 371, 375
 - raise_() (QWidget), 160, 289, 330
 - raising windows, 160
 - randint() (random), 19, 357, 371, 375
 - range(), 39, 50–51, 54
 - see also* xrange()
 - “raw” strings, 157, 220
 - re module, 219, 220, 554, 556
 - read-only models, 427
 - read-only widgets, 421
 - readAll()
 - QIODevice, 254
 - QTextStream, 384
 - readBool() (QDataStream), 245
 - readDouble() (QDataStream), 241, 245
 - readIntn() (QDataStream), 243, 245, 360, 435
 - readline() (codecs), 255
 - readLine() (QTextStream), 252, 253, 254
 - readUIntr() (QDataStream), 245, 528, 540
 - rebinding names; *see* binding names
 - recently used files, 187–190
 - record-level validation, 140, 491
 - record()
 - QSqlQuery, 450
 - QSqlQueryModel, 464, 465, 466, 469
 - rect()
 - QPaintEvent, 480
 - QWidget, 306, 330
 - recursion, risk of infinite, 100
 - reentrant methods, 542
 - references; *see* object references
 - regression testing, 105
 - regular expressions, 157, 220, 327, 386, 387, 461, 552
 - “reject” button, 141, 188
 - reject() (QDialog), 215
 - rejected() signal (QDialogButtonBox), 145, 150
 - relationModel() (QSqlRelationalTableModel), 456
 - remainder (%), 53
 - remove()
 - dict, 95, 532, 543
 - list, 32, 33
 - set, 38
 - removeItem() (QGraphicsScene), 354, 355, 359, 361, 372
 - removeRow() (QAbstractItemModel), 434, 466, 469
 - removeRows() (QAbstractItemModel), 427, 432, 434, 469
 - removeSelectedText() (QTextCursor), 297
 - render()
 - QGraphicsScene, 354, 361
 - QGraphicsView, 361
 - QSvgRenderer, 363
 - replace() (str/unicode), 25, 238

- repr(), 81, 83, 89, 90, 98
 - __repr__() (repr()), 81, 83, 90, 98
 - reset()
 - QAbstractItemModel, 432, 434, 501, 502
 - QMatrix, 370, 377
 - resize() (QWidget), 183
 - resizeColumnsToContents() (QTableView), 232, 419, 460, 463, 490
 - resizeEvent() (QWidget), 306, 309, 341
 - resource path, root of (:/), 173
 - resource files, 173–174, 206, 401, 517
 - restore() (QPainter), 343, 346, 410, 438, 482, 489
 - restoreGeometry() (QWidget), 183, 186, 330
 - restoreState()
 - QMainWindow, 183, 186
 - QSplitter, 282
 - restoring windows, 297
 - Return keypress; *see* Enter keypress
 - return statement, 58, 97, 554
 - returnPressed() signal (QLineEdit), 440
 - reverse() (list), 33
 - rfind() (str/unicode), 25
 - __rfloordiv__() (//), 84
 - rgbSwapped() (QImage), 197
 - rich text; *see* HTML
 - RichTextLineEdit example class, 389–398
 - rindex() (str/unicode), 25
 - __rmod__() (%), 84
 - __rmul__() (*), 84, 91
 - rollback() (QSqlDatabase), 449, 465, 469
 - RomanSpinBox example class, 326–328
 - rotate()
 - QGraphicsItem, 360, 366, 371, 375, 377
 - QPainter, 343
 - rotating, graphics, 349
 - round(), 40, 91, 333
 - row() (QModelIndex), 427, 491
 - rowCount() (QAbstractItemModel), 426, 427, 428, 434, 454, 455, 479, 481, 503
 - __rsub__() (-), 84
 - __rtruediv__() (/), 84
 - rubber band, 352
 - run() (QThread), 538, 540, 548, 553
 - RuntimeError exception, 288
- ## S
- save()
 - QImage, 196
 - QPainter, 343, 346, 438, 481, 489
 - saveGeometry() (QWidget), 183, 186, 330
 - saveState()
 - QMainWindow, 183, 186
 - QSplitter, 282
 - saving files, 229, 240–248, 249–256, 256–265
 - SAX parser, 262–265
 - scale()
 - QGraphicsItem, 366
 - QGraphicsView, 352
 - QMatrix, 370
 - QPainter, 343
 - QSize, 363, 400
 - scaled() (QImage), 199
 - scaling, graphics, 349, 370, 374, 400
 - scaling, widgets, 329, 331
 - scene coordinates; *see* window coordinates
 - scene() (QGraphicsItem), 366, 375
 - sceneBoundingRect() (QGraphicsItem), 366, 379
 - scenes, graphic; *see* QGraphicsScene
 - Scintilla; *see* QScintilla add-on
 - scope, 55
 - screen coordinates, 309, 357
 - screenPos() (QGraphicsSceneContextMenuEvent), 365
 - scrollbars and scrolling, 393, 476, 479
 - scrollToItem() (QTableWidget), 232

- SDI (Single Document Interface), 283–290
- search() (re), 219
- seek() (QSqlQuery), 449, 451
- select() (QSqlTableModel), 453, 456, 460, 462, 464, 469
- SELECT statements, 449–451
- selected text, 392
- selectedItems() (QGraphicsScene), 358, 360, 361
- selectedText() (QTextCursor), 297
- selecting graphics items, 352
- selectionModel() (QAbstractItemView), 463
- self, 77, 78
- sender() (QObject), 135, 289, 393, 395, 440
- separators, menu, 178, 180
- sequences, 22
- set type, 37, 38, 93, 551
 - add(), 37, 38, 372, 556
 - clear(), 38
 - copy(), 38, 548, 551
 - discard(), 38
 - pop(), 372
 - remove(), 38
- setAcceptDrops() (QWidget), 312, 313, 314, 315, 316, 330
- setActiveWindow() (QWorkspace), 292, 295
- setAlignment()
 - QAbstractSpinBox, 340, 487
 - QLabel, 168, 340
 - QLineEdit, 461
- setAllowedAreas() (QDockWidget), 169, 170
- setAlternatingRowColors() (QAbstractItemView) (QAbstractItemView), 231, 477
- setAttribute() (QWidget), 156, 284, 330, 511
- setBackgroundBrush() (QGraphicsScene), 354
- setBottom() (QRect/QRectF), 365
- setBrush() (QPainter), 337, 344, 345, 374, 377, 481
- setBuddy() (QLabel), 143, 425
- setCalendarPopup() (QDateTimeEdit), 487
- setCentralWidget() (QMainWindow), 168, 186, 285
- setCheckable()
 - QAbstractButton, 276, 278
 - QAction, 393
- setChecked() (QAction), 172, 177, 393
- setCodec() (QTextStream), 250, 252, 254, 258, 384
- setColor() (QPen), 368
- setColumnCount()
 - QTableWidget, 231, 418
 - QTreeWidget, 420
- setColumnHidden() (QTableView), 460, 463
- setColumnStretch() (QGridLayout), 146
- setContent() (QDomDocument), 259
- setContentHandler() (QXmlReader), 262
- setContextMenuPolicy() (QWidget), 168, 330, 365
- setCurrentIndex()
 - QAbstractItemView, 426, 465, 468
 - QComboBox, 441, 457
 - QDataWidgetMapper, 454, 455
 - QStackedWidget, 275
- setCurrentItem()
 - QListWidget, 418
 - QTableWidget, 232, 419
 - QTreeWidget, 421
- setCursor()
 - QGraphicsItem, 366
 - QWidget, 330
- setData(), 189, 231
 - QAbstractItemModel, 414, 427, 431, 434, 441, 462, 465, 487, 488
 - QAction, 172, 189, 392, 393
 - QMimeData, 316
 - QTableWidgetItem, 231
 - QTableWidgetItem, 419
- setDatabaseName() (QSqlDatabase), 446, 459
- setDate() (QDateTimeEdit), 487

- setDateRange() (QDateTimeEdit), 452, 487
- setDateTime() (QDateTime), 454
- setDefault() (dict), 36, 95, 532
see also defaultdict type
- setDefaultFont() (QTextDocument), 438, 439, 489
- setDisplayFormat() (QDateTimeEdit), 452, 487
- setDragEnabled() (QAbstractItemView), 312, 313, 315, 316
- setDragMode() (QGraphicsView), 352
- setDropAction() (QDropEvent), 314, 315, 316
- setEditable() (QComboBox), 440
- setEditorData() (QAbstractItemDelegate), 436, 441, 462, 486, 487, 488
- setEditTriggers() (QAbstractItemView), 231
- setEnabled()
 - QAction, 172
 - QGraphicsItem, 366
 - QWidget, 219, 330
- setErrorHandler() (QXmlReader), 262
- setFeatures() (QDockWidget), 170
- setFilter() (QSqlTableModel), 464, 469
- setFlag() (QGraphicsItem), 366
- setFlags() (QGraphicsItem), 351, 356, 362, 364
- setFocus()
 - QGraphicsItem, 364, 366
 - QWidget, 120, 310, 330, 422
- setFocusPolicy() (QWidget), 180, 217, 331, 369, 478
- setFont()
 - QGraphicsItem, 362
 - QPainter, 344, 408, 482
 - QWidget, 330
- setForwardOnly() (QSqlQuery), 451
- setFrameStyle() (QFrame), 170, 278
- setHeaderData() (QAbstractItemModel), 434, 460, 462
- setHeaderLabels() (QTreeWidget), 420
- setHorizontalHeaderLabels() (QTableWidget), 231, 418
- setHotSpot() (QDrag), 316
- setHtml()
 - QMimeData, 311
 - QTextDocument, 403, 438, 439, 489
 - QTextEdit, 488
- setIcon() (QListWidgetItem), 316
- setImage() (QClipboard), 311
- setInputMask() (QLineEdit), 461
- setItem() (QTableWidget), 231, 419
- __setitem__() ([]), 93, 95
- setItemDelegate()
 - QAbstractItemView, 437, 460, 463, 490
 - QDataWidgetMapper, 456
- setItemsExpandable() (QTreeView), 420
- setLayout() (QWidget), 273, 279, 330
- setLineWrapMode() (QTextEdit), 390
- setMatrix()
 - QGraphicsItem, 362, 364, 367, 377
 - QGraphicsView, 370
 - QPainter, 343
- setMaximumHeight() (QWidget), 390
- setMimeData()
 - QClipboard, 311
 - QDrag, 316
- setMinimumHeight() (QWidget), 390
- setMinimumSize() (QWidget), 168, 340
- setMinimumWidth() (QWidget), 340
- setModel()
 - QAbstractItemView, 425, 437, 460, 463, 477, 490
 - QComboBox, 456
 - QDataWidgetMapper, 453, 456
- setModelColumn() (QComboBox), 456
- setModelData() (QAbstractItemDelegate), 436, 441, 462, 486, 487, 488
- setModified() (QTextDocument), 286, 383, 384
- setMouseTracking() (QWidget), 308, 334
- setObjectName() (QObject), 169, 183, 324

- setSizePolicy() (QWidget), 330, 331, 340
- setSizeGripEnabled()
 - QDialog, 154
 - QStatusBar, 170
- setSizePolicy() (QWidget), 330, 331, 340
- setSort() (QSqlTableModel), 453, 456, 460, 462
- setSortingEnabled() (QTableView), 418, 419
- setStatusTip()
 - QAction, 172
 - QWidget, 171, 180
- setStretchFactor()
 - QBoxLayout, 146
 - QSplitter, 283
- setStyleSheet() (QWidget), 323, 330
- setSubmitPolicy() (QDataWidgetMapper), 453, 456
- setSuffix() (QSpinBox), 180, 340
- setTabChangesFocus() (QTextEdit), 390
- setTable() (QSqlTableModel), 453, 456, 460, 462
- setTabOrder() (QWidget), 206
- setText()
 - QAbstractButton, 370
 - QAction, 172
 - QClipboard, 297, 311
 - QLineEdit, 441, 462
- setTextAlignment()
 - QTableWidgetItem, 231, 419
 - QTreeWidgetItem, 421
- setTextColor() (QTextEdit), 393
- setToolTip()
 - QAction, 172
 - QWidget, 171, 180, 390
- setUniformRowHeights() (QTreeView), 495
- setupUi() (generated by pyuic4), 217, 218
- setValidator() (QLineEdit), 461
- setValue()
 - QAbstractSlider, 128, 369
 - QSpinBox, 128, 180, 340, 441
- setVersion() (QDataStream), 241, 243, 245, 525, 528, 531, 533, 540
- setPageSize() (QPrinter), 353, 398, 400
- setPen() (QPainter), 337, 338, 343, 344, 345, 374, 377, 409, 410, 481
- setPixmap()
 - QClipboard, 311
 - QDrag, 316
 - QLabel, 199
- setPlainText() (QTextEdit), 384
- setPointSize() (QFont), 335, 336
- setPos() (QGraphicsItem), 356, 362, 364, 367, 373, 375
- setPosition() (QTextCursor), 406
- setProperty() (QObject), 322, 324
- setQuery() (QSqlQueryModel), 464
- setQuitOnLastWindowClosed() (QApplication), 121
- setRange()
 - QAbstractSlider, 369
 - QSpinBox, 180, 340, 440
- setRelation() (QSqlRelationalTableModel), 456, 460, 462
- setRenderHint()
 - QGraphicsView, 352, 369
 - QPainter, 306, 337, 342, 343, 361, 363
- setRight() (QRect/QRectF), 365
- setRowCount() (QTableWidget), 231, 418
- setRowStretch() (QGridLayout), 146
- setScene() (QGraphicsView), 354, 369
- setSceneRect() (QGraphicsScene), 354, 369
- setSelected()
 - QGraphicsItem, 356, 362, 364, 367
 - QTableWidgetItem, 232, 419
- setSelectionBehavior() (QAbstractItemView), 231, 460, 463, 495
- setSelectionMode() (QAbstractItemView), 231, 460, 463
- setSeparator() (QAction), 172
- setShortcut() (QAction), 171, 172
- setSingleStep() (QSpinBox), 440
- setSizeConstraint (QLayout), 277, 279

- setViewport() (QPainter), 329, 342, 343, 363
- setVisible() (QWidget), 277, 280
- setWhatsThis() (QAction), 172
- setWidth() (QPen), 368
- setWindow() (QPainter), 329, 342, 343, 363
- setWindowFlags() (QWidget), 529
- setWindowIcon() (QWidget), 186, 330
- setWindowModified() (QWidget), 192
- setWindowTitle() (QWidget), 146, 151, 186, 330, 370
- setZValue() (QGraphicsItem), 367
- shallow copying, 34, 51, 98
- shape() (QGraphicsItem), 365, 367, 374, 377
- shear()
 - QGraphicsItem, 367
 - QPainter, 343
- Shift keypress, 365
- short-circuit logic, 47
- short-circuit signals, 130–131
 - see also* signals and slots
- shortcut; *see* keyboard shortcut and QKeySequence
- show() (QWidget), 115, 155, 280, 286, 330, 511
- showing dialogs, 160
- showing images, 168
- showing widgets, 277, 280
- showMessage() (QStatusBar), 170, 233
- showMinimized() (QWidget), 297
- showNormal() (QWidget), 297
- sibling() (QModelIndex), 491
- SIGNAL() (QtCore), 131
- signals and slots, 115, 120, 124, 127–136, 206, 215, 217, 292, 307, 333, 385, 440, 482, 539, 544
 - see also* short-circuit signals
- Signals and Slots application, 128–131
- signature of, function, method, signal or slot, 56, 129
- simplified() (QString), 61, 422
- sin() (math), 371, 375
- single click; *see* mousePressEvent() and mouseReleaseEvent()
- single document interface; *see* SDI
- single-quoted strings, 21
- singleShot() (QTimer), 115, 306
- sip module, 288
- size; *see* QSize
- size grip, 170
- size hint, 271
- size()
 - QImage, 363, 400
 - QRect/QRectF, 400
 - QSqlQuery, 450
- size of layout or widget
 - fixed, 277
 - maximum, 271
 - minimum, 270, 271, 335
 - preferred, 271
- size policies, 270–271, 335
- sizeHint()
 - QAbstractItemDelegate, 436, 439, 489
 - QWidget, 335, 390, 479
- sleep() (time), 114, 115
- slicing, 22, 30, 32
- slot; *see* signals and slots
- SLOT() (QtCore), 131
- __slots__ class attribute, 103, 115
- software patents, disadvantages of, 222
- sort() (list), 33, 53, 63, 95, 239
- sorted(), 52, 53, 63, 432, 434, 551
- sorting, 52, 418, 425, 432–435
- spacer; *see* QSpacerItem
- spacers, in layouts, 212, 214
- special methods, 81
 - __abs__() (abs()), 84
 - __add__() (+), 84, 90
 - __call__(), 81
 - __cmp__() (cmp()), 81, 82, 89, 416, 432
 - __contains__() (in), 93
 - __del__() (del statement), 78
 - __delitem__() (del statement), 93, 95
 - __eq__() (==), 81
 - __float__() (float()), 84, 91
 - __floordiv__() (//), 84

- special methods (*cont.*)
 - `__ge__` () (>=), 81
 - `__getitem__` () ([]), 93, 94
 - `__gt__` () (>), 81
 - `__iadd__` () (+=), 84, 90
 - `__ifloordiv__` () (/=/), 84
 - `__imod__` () (%=), 84
 - `__imul__` () (*=), 84, 91
 - `__init__` (), 77, 78, 437
 - `__int__` () (int()), 84, 91
 - `__isub__` () (-=), 84
 - `__iter__` () (iter()), 93, 97
 - `__itruediv__` () (/=), 84, 91
 - `__le__` () (<=), 81
 - `__len__` () (len()), 93, 96
 - `__lt__` () (<), 81, 82, 432
 - `__mod__` () (%), 84
 - `__mul__` () (*), 84, 91
 - `__ne__` () (!=), 81
 - `__neg__` () (-), 84
 - `__new__` (), 77, 78, 81
 - `__nonzero__` () (bool()), 81, 83
 - `__radd__` () (+), 84
 - `__repr__` () (repr()), 81, 83, 90
 - `__rfloordiv__` () (/=/), 84
 - `__rmod__` () (%), 84
 - `__rmul__` () (*), 84, 91
 - `__rsub__` () (-), 84
 - `__rtruediv__` () (/), 84
 - `__setitem__` () ([]), 93, 95
 - `__str__` () (str()), 81, 83, 90, 98, 100
 - `__sub__` () (-), 84
 - `__truediv__` () (/), 84, 91
 - `__unicode__` () (unicode()), 81, 83
- spinbox; *see* `QDoubleSpinBox` and `QSpinBox`
- `split()`
 - `QString`, 253
 - str/unicode, 25, 114, 238, 501
- splitter; *see* `QSplitter`
- SQL queries; *see* `QSqlQuery` and SQL statements
- SQL Server database, 445
- SQL statements, 445, 446, 447, 448, 449, 449–451, 458, 464, 468, 469
- SQLite database, 445, 446, 447
- stacked widgets; *see* `QStackedWidget`
- standard key sequence; *see* keyboard shortcut and `QKeySequence`
- `start()`
 - `QDrag`, 316
 - `QThread`, 539, 547, 553
 - `QTimer`, 373, 376
- start-up processing, 184
- `startDrag()` (`QAbstractItemView`), 316
- `startElement()` (`QXmlContentHandler`), 263
- `startswith()` (str/unicode), 25, 238, 255
- `startsWith()` (`QString`), 252
- `startTimer()` (`QObject`), 370
- state, changes; *see* signals and slots
- `state()` (`QAbstractSocket`), 540
- state, preserving using generators, 58, 97
- statement separators, 51
- static data, 85–86
- static methods, 78, 85–86
- static typing, 12
- `staticmethod()`, 85, 239, 288
- status bar; *see* `QStatusBar`
- `statusBar()` (`QMainWindow`), 170, 186
- `StopIteration` exception, 52, 58, 59
- stored procedures, in databases, 448
- str type, 20–28, 25
 - % formatting, 24, 98
 - %s format specifier, 26
 - * replication operator, 25
 - + concatenation operator, 25
 - `count()`, 25
 - `endswith()`, 25, 31, 555
 - `find()`, 24, 25, 68
 - `index()`, 24, 25, 68
 - indexing, 22
 - `isalpha()`, 25
 - `isdigit()`, 25, 238, 554
 - iterating, 50
 - `join()`, 23, 25, 61, 193, 477
 - literals, 21

- str type (*cont.*)
 - lower(), 25, 238
 - promotion to unicode, 20
 - replace(), 25, 238
 - rfind(), 25
 - rindex(), 25
 - slicing, 22
 - split(), 25, 114, 238, 501
 - startswith(), 25, 238, 255
 - strip(), 25, 59, 255
 - title(), 24
 - upper(), 25
 - see also* QString and unicode type
 - `__str__()` (str()), 81, 83, 90, 98, 100
 - stream reading and writing, 242, 245, 250, 252, 258
 - streams; *see* QDataStream and QTextStream
 - stretch factors, 144, 212, 271, 283
 - string literals, 20
 - string module, 26
 - Template class, 26
 - StringIO module, 23
 - see also* cStringIO module
 - strings; *see* QString, str type, and unicode type
 - strip() (str/unicode), 25, 59, 255
 - style sheets, 322–324
 - sub() (re), 220, 556
 - `__sub__()` (-), 84
 - subcontrols, in widgets, 324
 - submit() (QDataWidgetMapper), 454
 - submitAll() (QSqlTableModel), 455, 466, 469
 - suite of code, 46, 47
 - sum(), 38
 - super(), 100, 153, 217
 - support for keyboard users; *see* keyboard users, support for
 - supportedImageFormats()
 - QImageReader, 193
 - QImageWriter, 196
 - SVG (Scalable Vector Graphics) format, 363
 - switch statement; *see* if statement
 - Sybase database, 445
 - sys module, 60, 63, 114
 - argv variable, 114
 - path variable, 60, 104
 - version_info tuple, 63
 - system() (platform), 200, 217, 336, 390
- ## T
- Tab keypress, 206, 218, 310, 386, 390, 421, 422, 511
 - tab order, 206, 215, 217, 310
 - tab widget; *see* QTabWidget
 - table widget; *see* QTableWidgetItem
 - tagName() (QDomElement), 260
 - takeItem() (QListWidgetItem), 316
 - takeLast() (QStringList), 189
 - taskbar entries, 142
 - TCP (Transmission Control Protocol), 522
 - Template class (string), 26
 - terminating applications, 115, 121, 185
 - terminology, 13, 75
 - ternary operator; *see* conditional expression
 - testing for errors vs. exception handling, 68
 - testing, user interface, 221–222
 - testmod() (doctest), 106
 - text cursor; *see* insertion point
 - text editor; *see* QTextEdit
 - text files, 249–256
 - text()
 - QClipboard, 297, 311
 - QLineEdit, 441
 - QTableWidgetItem, 422
 - text stream; *see* QTextStream
 - text stream reading and writing, 250, 252, 258
 - textCursor() (QTextEdit), 297, 384, 385
 - textEdited() signal (QLineEdit), 161, 217, 218
 - textFromValue() (QSpinBox), 327, 328
 - this* pointer; *see* self

- thread safety, 541–542
- time module
 - sleep(), 114, 115
 - see also* QTimer
- timeout() signal (QTimer), 373, 376
- timer; *see* QTimer
- timerEvent() (QObject), 372
- times; *see* QDateTime, QTime, and time module
- title bar, 115
- title() (str/unicode), 24
- toBool() (QVariant), 324
- toDate() (QVariant), 487, 491
- toDateTime() (QVariant), 449
- toDouble() (QVariant), 481
- toElement() (QDomNode), 260
- toFirst() (QDataWidgetMapper), 453, 456
- toggle actions, 176
 - see also* QAction
- toggle button, 276, 278
 - see also* QPushButton
- toggled() signal
 - QAbstractButton, 277, 280
 - QAction, 172, 176, 177
- toHtml()
 - QTextDocument, 407
 - QTextEdit, 395
- toInt()
 - QString, 251, 422
 - QVariant, 395, 431, 449
- toLongLong() (QVariant), 422
- toNativeSeparators() (QDir), 547, 551
- toolbar; *see* QToolBar
- toolbar buttons, 169
- tools; *see* applications
- tooltip; *see* QToolTip
- top-level windows, 115, 118, 221
- toPlainText()
 - QGraphicsTextItem, 359
 - QTextEdit, 384, 395
- toPyDate() (QDate), 532, 541
- toString()
 - QDate, 258, 401
 - QDateTime, 455
 - toString() (*cont.*)
 - QDomDocument, 257, 260
 - QVariant, 427, 431, 441, 449, 488
- toText() (QDomNode), 261
- toUpper() (QString), 327
- tr() (QObject), 513, 514, 515
- transaction() (QSqlDatabase), 449, 465, 468, 469
- transactions, database, 465–466, 468
- transformations, graphics, 349, 350, 356, 360, 370, 374, 376, 438
- translate()
 - QCoreApplication, 513, 515
 - QGraphicsItem, 367
 - QPainter, 343, 438, 489
- triggered() signal (QAction), 172, 176
- trimmed() (QString), 252, 422
- triple quoted strings, 21, 57
- True constant, 45
- “true” division, 17, 84, 86
- __truediv__() (/), 84, 91
- truncating division, 17, 84, 86, 91
- trUtf8() (QObject), 513
- try statement, 66, 78, 541, 542, 543, 548, 550, 551, 553, 554, 556
 - else statement, 70, 295
 - see also* except statement and finally statement
- .ts (translation source file), 517, 518, 519
- tuple type, 29–31, 30, 50, 87
- Twisted networking framework, 522
- type conversions; *see* conversions
- type(), 18, 39, 102
 - see also* isinstance()
- type() (QEvent), 384
- type promotion; *see* conversions
- type testing, 94
- TypeError exception, 56
- typing; *see* duck typing, dynamic typing, and static typing

U

UDP (User Datagram Protocol), 522

.ui (user interface file), 206, 207, 515

ultimate base class; *see* object type

underscores, leading, 77, 80, 82

unichr(), 21, 39, 236, 554

Unicode, 20, 117, 236, 250, 258, 447, 478, 512, 552, 555

- characters, 22
- encodings, 20, 21, 250, 258, 501
- see also* ASCII, codecs, and QString

unicode type, 20–28, 25, 256, 401

- % formatting, 24
- %s format specifier, 26
- * replication operator, 25
- + concatenation operator, 25
- count(), 25
- endswith(), 25, 31, 555
- find(), 24, 25, 68
- index(), 24, 25, 68
- indexing, 22
- isalpha(), 25
- isdigit(), 25, 238, 554
- iterating, 50
- join(), 23, 25, 61, 193, 477
- literals, 20, 21
- lower(), 25, 238
- promotion to QString, 28
- replace(), 25, 238
- rfind(), 25
- rindex(), 25
- slicing, 22
- split(), 25, 114, 238, 501
- startswith(), 25, 238, 255
- strip(), 25, 59, 255
- title(), 24
- upper(), 25
- see also* str type and QString

__unicode__() (unicode()), 81, 83

union() (set), 38

unit testing, 105–107

universal newlines, 256

unlock()

unlock() (*cont.*)

- QMutex, 553, 554
- QReadWriteLock, 541, 542, 543, 548, 550, 551, 556

unpacking tuples, 87

unsaved changes, 168, 187, 192, 232, 293, 356, 361, 362, 364, 365, 425, 453

update()

- QGraphicsItem, 365, 367
- QGraphicsScene, 354
- QWidget, 306, 330, 332, 479, 482

updateGeometry() (QWidget), 330, 332, 479

upper() (str/unicode), 25

urlopen() (urllib2), 126

urlretrieve() (urllib), 521

user actions; *see* QAction

user interface design, 205–216

user preferences; *see* QSettings

UTF-8 encoding, 236, 250, 258, 501, 555

V

validate() (QAbstractSpinBox), 327, 328

validation, 140, 151, 157, 327, 328, 491

value comparison, 13, 57

value()

- QSettings, 183
- QSpinBox, 441
- QSqlQuery, 449, 450, 451
- QSqlRecord, 464, 465, 466, 469

valueChanged()

- QDial, 128
- QSpinBox, 124, 128, 199

ValueError exception, 68, 114

valueFromText() (QSpinBox), 327, 328

values() (dict), 36, 96

variable names, 15, 76, 80, 88

version_info tuple (sys), 63

version string, application, 167

__version__, application variable, 167

vertical layout; *see* QVBoxLayout
vertical lines; *see* QFrame
view widgets; *see* QGraphicsView, QListView, QTableView, and QTreeView
viewport coordinates, 328–331, 339, 342, 350, 400
viewport()
 QAbstractScrollArea, 392, 393
 QPainter, 363, 400
views() (QGraphicsScene), 354, 362
virtual methods, 75, 99
visual design tool; *see* Qt Designer

W

wait() (QThread), 547, 548, 551
waitForDisconnected() (QAbstractSocket), 544
waitForReadyRead() (QIODevice), 540
walk() (os), 555
warning() (QMessageBox), 153, 188, 293
Web browser, launching, 510
wheelEvent() (QWidget), 352
while loop, 49–50
 break statement, 53
 continue statement, 53
 else statement, 49–50, 254
widget attributes; *see* Qt.WidgetAttribute
widget coordinates, 309
widget-level validation, 140, 144
widget stack; *see* QStackedWidget
widgets; *see* QWidget
width() (QWidget), 330
window coordinates, 328–331, 339, 342, 350, 354, 357
window decorations, 112
window flags, 115
window menu, MDI, 292–293, 297–300
window menu, SDI, 285, 288–289
window modal dialogs, 140, 511
window system detection, 218, 336, 389, 390

windowList() (QWorkspace), 295
windows, 115, 118, 160
 see also widgets, QWidget, QDialog, and QMainWindow
Windows detection, 389, 390
windows, previewing, 215
WindowStaysOnTopHint (Qt namespace), 529
with statement, 549
wrapping functions; *see* partial function application
write() (QDataStream), 526, 533
writeBool() (QDataStream), 245
writeDouble() (QDataStream), 241, 245
writeIntn() (QDataStream), 241, 242, 245, 359, 435
writeUIntn() (QDataStream), 245, 525, 533
writing files; *see* saving files

X

X Window System detection, 336
XML files, 256–265
XML meta-characters, 257, 258
XML parser, DOM, 259–262
XML parser, SAX, 262–265
xrange(), 51, 54
 see also range()

Y

yield statement, 58, 97, 237
YPipe example class, 339–345

Z

z value, 349
zoom; *see* scaling, graphics
zValue() (QGraphicsItem), 367