

Index

10-BASE 2 Ethernet, 19
10-BASE 5 Ethernet, 19
10/100-BASE T Ethernet, 19
100-BASE FX Ethernet, 19
100-BASE T Ethernet, 19
1000-BASE T Ethernet, 19
1000-BASE ZX Ethernet, 19

A

abbreviating

IPv6 addresses, 377

access attacks

mitigating, **189-190**

access control lists, see ACLs, 288

Access layer

Cisco three-layer hierarchical network model, 29

access layer (three-layer hierarchical model, 29

acknowledgment number (TCP), 33

ACL

configuring

with SDM, 302-303, 305

ACLs

(access control lists), 288

exam prep questions, 308-312

answers to, 313-314

ACLS

extended IP type

configuring, 296-300

established keyword, 300

ACLs

extended IP type

filtering criteria, 292

IP ranges, 291

ACLS

extended IP type

log keyword, 300

log-input keyword, 300

ACLs

ACLs

- extended IP type
 - SSH access filters, 298-299
 - Telnet access filters, 298-299
- named type, 292

ACLs

- named type
 - configuring, 301-302

ACLs

- numbered
 - treating as name type, 301
- roters
 - dial-on-demand routing (DDR), 288
- routers
 - logic, 289-290
 - Network Address Translation (NAT), 288
 - packet filtering functions, 288-290
 - Quality of Service (QoS) traffic, 288
 - update filtering functions, 288

ACLs

- standard IP type
 - configuring, 293-295

ACLs

- standard IP type
 - filtering criteria, 291
 - IP ranges, 291

ACLs

- standard IP type
 - wildcard masks, 293-295

ACLs

- troubleshooting commands
 - Show ACLs, 306-307
 - show IP ACLs, 306-307
 - show ip interface, 306-307

- verification commands
 - Show ACLs, 306-307
 - show IP ACLs, 306-307
 - show ip interface, 306-307
- Virtual Teletype (VTY) lines
 - Telnet access, 298-299

active routes, 320**Ad Hoc mode, 173****address learning (switches)**

- MAC addresses, 123

administrative distance (AD)

- routers, 372

administrative distances

- dynamic routers, 203-204
- EIGRP routing source, 204
- OSPF routing source, 204
- RIP routing source, 204
- static routers, 203-204

AH

- hashing, 354

AH (authentication header), 353**ANDing, 65****Anomaly Guard and Protector, 192****anycast IPv6 addresses, 378****application layer, 31-32****Application layer**

- TCP/IP network model, 44-45

Application layer (OSI), 31

- DHCP, 32
- DNS, 32
- FTP, 31
- HTTP, 31
- NTP, 32
- POP3, 32
- SMTP, 31
- SNMP, 32
- Telnet, 32
- TFTP, 32

APs

- BSS, 174
- ESS, 174
- rogue APs, 176

ARP

- (Address Resolution Protocol), 41
- Network layer (OSI), 41

ASA, 192**ASIC chips (Application-Specific Integrated Circuit), 126****authentication**

- PPP
 - Challenge Handshake Authentication Protocol (CHAP), 141, 339
 - configuring, 142-143, 340-341
 - Password Authentication Protocol (PAP), 141, 339
- WLANs, 176

automatic security configuration

- enabling on SDM, 234

Autonomous mode, 173**AUX port**

- Cisco devices
 - external connections, 84

availability, 187**B****backing up**

- IOS, 108-109
 - image configurations, 109-110

Backoff Algorithm time calculations

- Ethernet collisions, 18

backup designated routers

- use of (OSPF), 323-325

Backward Explicit Congestion Notification (BECN)

- Frame Relay (WANs), 344-345
- frame-relay (WANs), 146-147

Bellman-Ford algorithm (RIP), 209**binary numbering**

- IP addresses, 52
 - decimal conversions, 52-54
 - high-order bits, 53
 - low-order bits, 53
 - values represented, 52
- versus hexadecimal numbering, 54-55

Blocked port (STP), 260**Blocking port state (STP), 261****branch office**

- routers, configuring, 396-397
 - requirements, 395-396
- switches, configuring, 392-394
 - requirements, 390-391

Bridge Protocol Data Units (BPDUs)

- STP packet communications, 257

bridges, 18

- collision isolation, 122
- frames per second, 127
- function of, 122
- number of ports, 127
- source-route, 123
- source-route translational, 123
- transparent, 123
- versus switches, 126-127

broadcast domains

- VLANs
 - segmenting with switches at Layer 2, 264

broadcast frames

- forwarding by switches, 124

Broadcast IDs

- subnetting, 65-67

broadcast storms

- switch looping problem, 131-132, 254-255

BSS(Basic Service Set), 174**bus topology, 17**

C

CD-ROM

- installing, 473
- system requirements, 472
- test modes
 - certification mode, 471
 - custom mode, 472
 - study mode, 471

CDP

- routers
 - remote management, 113-114

cell-switched connections (WANs), 21

cell-switched WANs, 21

certification mode (CD-ROM), 471

certification status

- benefits of, 3-4
- official package contents, 3-4

certification status (exam)

- tracking, 3-4

Challenge Handshake Authentication Protocol (CHAP)

- PPP, 141, 339
 - configuration process, 142-143, 340-341

chart (subnetting)

- creating, 70-72

China Next Generation Internet, 382

CIDR (Classless Inter-Domain Routing), 59

circuit switched WANs, 138, 336

- encapsulation types, 138-139, 336-337

circuit-switched connections (WANs), 20

circuit-switched WANs, 20

Cisco

- HDLC (High-level Data-Link Control) version, 139, 337-338

Cisco Anomaly Guard, 192

Cisco ASA, 192

Cisco CCNA Prep Center website, 4

Cisco CSA, 192

Cisco DDoS Guard, 192

Cisco devices

- command line modes
 - Interface configuration, 92
 - Line configuration, 92
 - privileged exec, 91
 - Router configuration, 92
 - user exec, 91
- command shortcuts
 - error messages, 92-93
- configuration register, 89
- context-sensitive help, 93-94
- Ethernet ports
 - duplex settings, 95
 - speed settings, 95
- exam prep questions, 100-102
 - answers to, 102-103
- external connections, 82
 - AUX port, 84
 - console port, 82-84
 - Ethernet port, 84-85
 - serial port, 85-86
- IOS startup process, 87-89
- management IP addresses
 - setting, 94
- memory types
 - Flash, 87
 - NVRAM (non-volatile RA), 87
 - RAM, 87
 - ROM, 87
- password recovery process, 89-91
- passwords
 - logon requirements, 97
- routers
 - information retrieval, 99
 - interfaces, enabling, 96
 - securing, 96, 98-99
 - serial ports, configuring, 95

- Setup mode, 89
- switches
 - hostnames, setting, 94
 - securing, 96, 98-99
- Cisco routers**
 - SSHaccess
 - configuring, 98-99
- Cisco SDNsolutions, 191-193**
- Cisco SWAN(Structured Wireless-Aware Network), 177**
- Cisco three-layer hierarchical network model, 28**
 - Access layer, 29
 - benefits, 30
 - Core layer, 29
 - Distribution layer, 29
- class A IP addresses, 57**
- class B IP addresses, 57**
- class C IP addresses, 57**
- class D IP addresses, 57**
- class E IP addresses, 57**
- classful networks, 61**
- classless routing protocols, 212**
- CLI**
 - switch configuration, 244-246
- collision domains, 18**
- collisions, 17**
 - CSMA/CD, 18
 - Ethernet, 17
 - Backoff Algorithm time calculations, 18
 - CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 17
 - domains, 18
 - effect of, 18
 - elimination of, 18
 - Full Duplex connections, 18
 - isolating on bridges, 122
 - isolating with switches, 122
 - jam signals, 18

command line modes

- Cisco devices
 - Interface configuration, 92
 - Line configuration, 92
 - privileged exec, 91
 - Router configuration, 92
 - user exec, 91

command shortcuts

- Cisco devices
 - error messages, 92-93

commands

- context-sensitive help, 93-94
- enable secret, 97
- show flash
 - router information retrieval, 99
- show interface
 - router information retrieval, 99
- show ip protocols, 318, 320
- show running-config
 - router information retrieval, 99
- show startup-config
 - router information retrieval, 99
- show version
 - router information retrieval, 99

committed information rates (CIRs)

- Frame Relay (WANs), 344
- frame-relay (WANs), 146

compression identifiers

- router images, 107

confidentiality, 187

configuration register

- Cisco devices, 89

configuring

- ACLs
 - with SDM, 302-303, 305
- authentication for PPP, 142-143, 340-341
- Cisco devices
 - command line modes, access levels, 91-92
 - command shortcuts, 92-93

- configuration register, 89
- IOS startup process, 87-89
- memory locations, 87
- password recovery process, 89-91
- Setup mode, 89
- Cisco routers
 - SSH access, 98-99
- duplex communication, 130
- extended IP ACLs, 296-300
- Frame Relay (WANs), 348
- frame-relay (WANs), 149-152, 348-350
 - LMI, 150, 348
 - troubleshooting guidelines, 152-153, 350-351
 - verification of, 152-153, 350-351
- FrameRelay
 - multipoint subinterfaces, 349
 - point-to-point subinterfaces, 349
- IPv6
 - stateless autoconfiguration, 378
 - verifying configuration, 379
- named ACLs, 301-302
- OSPF, 326-327
- RIP, 210-212
- routers
 - for branch office, 395-397
- routers with SDM Express
 - IP addressing, 228-229
- routers with SDMExpress
 - DHCP Server, 230
 - firewall, 233
 - NAT, 232
 - WAN interfaces, 230, 232
- standard IP ACLs, 293-295
- STP
 - Portfast, 263
- switches
 - for branch office, 390-394

- switches with CLI, 244
 - default gateway, configuring, 246
 - management IP, configuring, 245
 - security, 244-245
- WLANs, 179-180

configuring routers with SDM

- hostname, 228
- user credentials, 228

connecting

- Cisco devices
 - command line modes, access levels, 91-92
 - command shortcuts, 92-93
 - configuration register, 89
 - IOS startup process, 87-89
 - memory locations, 87
 - password recovery process, 89-91
 - Setup mode, 89

connection-oriented communication, 33

connectionless communication, 33

connectivity

- testing with SDM, 241

console port

- Cisco devices
 - external connections, 82-84
 - local management connections, 83
- rollover cable pinouts, 83
- terminal session settings, 84

content networks, 22

context-sensitive help

- Cisco devices, 93-94

contiguous subnets, 365

Core layer

- Cisco three-layer hierarchical network model, 29

core layer (three-layer hierarchical model), 29

CRC (Cyclic Redundancy Check)

- use in Store and Forwarding switching, 128

CSA (Cisco Secure Agent), 192
CSMA/CD, 17-18
CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 17
custom mode (CD-ROM), 472
Cut-Through mode (switches), 128

D

data link layer, 41-42
Data Link layer (OSI)
 flat addressing, 41
 frame types, 41
 MAC addresses, 42
data-link connection identifiers (DLCIs), 145, 343
DDoS attacks
 mitigating, 190-191
DDoS Guard, 192
debug ppp authentication command (PPP), 144, 342
decapsulation, 44
decimal numbering
 IP addresses
 conversion from hexadecimal system, 56
 conversion to binary system, 54
 conversion to binary system, 52-54
 hexadecimal conversions, 56
 versus hexadecimal numbering, 54-55
dedicated leased lines (WANs)
 expense of, 20
default gateway
 switch configuration, 246
default masks
 IP addresses
 subnetting, 60-61

default route
 configuring with SDM, 240
default routes
 routers
 creating, 201-202
 example of, 202
 uses, 201
default subnet masks
 IP addresses, 57-58
Designated port (STP), 258
designated routers
 network types (OSPF), 323
 use of (OSPF), 323
destination ports, 37
devices (Cisco)
 external connections, 82
 AUX port, 84
 console port, 82-84
 Ethernet port, 84-85
 serial port, 85-86
DH(Diffie-Helman) algorithm, 355
DHCP
 (Dynamic Host Configuration Protocol), 32
 Application layer (OSI), 32
DHCP server
 configuring with SDMExpress, 230
dial-on-demand routing (DDR), 288
Diffusing Update Algorithm (DUAL)
 EIGRP, 316
Dijkstra, Edgar, 320
distance vector routing protocols, 205
 routing loops
 control and prevention of, 205-208
 maximum hop counter, 206
Distribution layer
 Cisco three-layer hierarchical network model, 29

distribution layer

distribution layer (three-layer hierarchical model), 29

DNS

Application layer (OSI), 32

DSSS, 171

Dual Stack, 383

dynamic IPv6 configuration, 379

Dynamic Key Exchange, 178

dynamic keying, 178

Dynamic NAT, 159-160

dynamic routes

routers

administrative distances, 203-204

EIGRP (Enhanced Interior Gateway Routing Protocol), 202, 209

OSPF (Open Shortest Path First), 202

RIP (Routing Information Protocol), 202

Dynamic Trunking Protocol (DTP), 273

Dynamic VLAN membership, 269

E

edge ports, 263

EIGRP

(Enhanced Interior Gateway Routing Protocol), 202

combination of link state and distance vector routing, 209

configuring, 318

Diffusing Update Algorithm (DUAL), 316

Feasible Successor Route, 316

main features of, 317

routers

administrative distances, 204

routing metrics, 204-205

Successor Route, 316

tables

neighbor, 317

routing, 317

topology, 317

verifying configuration, 318, 320

enable secret command, 97

password encryption, 97

encapsulation, 43-44

encapsulation types (WANs)

Frame Relay

selecting, 348

frame-relay

selecting, 150

High-level Data-Link Control (HDLC), 138-139, 336-338

PPP

authentication configuration, 142-143, 340-341

Challenge Handshake Authentication Protocol (CHAP), 141, 339

link control protocol (LCP), 140-141, 338-339

network control protocol (NCP), 140-141, 338-339

Password Authentication Protocol (PAP), 141, 339

troubleshooting configuration, 144, 342

verification of configuration, 144, 342

PPP frame, 138-140, 336-338

Serial Line IP frame, 138-139, 336-337

encrypting

passwords

enable secret command, 97

encryption

WLANs, 177

Enhanced Interior Gateway Routing Protocol, see EIGRP, 202

ESP, 354

ESP(encapsulating security payload), 353

ESS(Basic Service Set), 174

established keyword

extended IP ACLs, 300

Etherent

speeds, 18

Ethernet, 17

10-BASE 2 (Thinnet), 122

10-BASE 5 (Thicknet), 122

bridges

collision isolation, 122

function of, 122

versus switches, 126-127

cabling

10-BASE 2, 19

10-BASE 5, 19

10/100-BASE T, 19

100-BASE FX, 19

100-BASE T, 19

1000-BASE T, 19

1000-BASE ZX, 19

collisions, 17-18

Backoff Algorithm time calculations, 18

CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 17

domains, 18

effect of, 18

elimination of, 18

Full Duplex connections, 18

jam signals, 18

development of, 17

exam prep questions, 23-25

answers to, 25-26

IEEE 802.3 specification, 17

segments, 17

specifications, 19

switches

address learning, 123

collision isolation, 122

Cut-Through mode, 128

duplex connection configuration, 130-131

exam prep questions, 133-134

exam prep questions, answers to, 135-136

Fragment-Free mode, 129

frame filters, 125

frame forwarding, 123-125

Full-Duplex connections, 129-130

function of, 122

Half-duplex connections, 129

looping problems, 131-132, 254-255

Spanning Tree Protocol (STP), 132, 254-255

Store and Forward mode, 128

versus bridges, 126-127

Ethernet port

Cisco devices

external connections, 84-85

straight-through cables, 84-85

Ethernet ports

duplex settings

configuring (Cisco devices), 95

speed settings

configuring (Cisco devices), 95

EUI-64

static IPv6 configuration, 379

EUI-64 MAC address format, 378

exam

allowable materials during test, 3

certification status

tracking, 3-4

classroom training resources, 4

closed book format, 3

pass/fail notification, 3

practice exam #1, 404-405, 407-408,
410-411, 414-426

answers, 428-429, 431-440

hint and pointers, 403

practice exam #2, 441, 443-445,
447-448, 451, 453, 455, 457-458

answers, 460-462, 465, 467-470

preparation materials, 4-5

publication resources, 4

retests

scheduling, 3

waiting periods, 3

scheduling, 2

signing up

Prometric Test Centers, 2-3

VUE Test Centers, 2-3

single-exam option

cost of, 2

two-exam option

cost of, 2

ExamCram2.com

additional exam resources, 1

exams

prep questions

ACLs, 308-312

ACLs, answers to, 313-314

Cisco devices, 100-102

Cisco devices, answers to,
102-103

IP addresses, 73-76, 384-386

IP addresses, answers to, 78-79,
387

networking fundamentals, 23-25

networking fundamentals, answers
to, 25-26

OSI model, 46-48

OSI model, answers to, 48-49

routers, 116-118, 330-331,
384-386

routers, answers to, 118-119, 221,
333, 387

subnetting, 73-76

subnetting, answers to, 78-79

switches, 133-134

switches, answers to, 135-136

VLANs, 280-281, 283

VLANs, answers to, 285-286

WANs, 165, 357-359

exams (practice)

MeasureUp, 472

shortcuts, creating, 473

extended IP ACLs

configuring, 296-300

established keyword, 300

filtering criteria, 292

IP ranges, 291

log keyword, 300

log-input keyword, 300

SSH access

filtering, 298-299

Telnet access

filtering, 298-299

extended NAT entry, 160-162

external connections

Cisco devices, 82

AUX port, 84

console port, 82-84

Ethernet port, 84-85

serial port, 85-86

F

Fast Ethernet

VLANs

trunking, 269

features of IPv6, 380

features sets

routers, 106

FHSS(Frequency Hopping Spread Spectrum), 170

fields

of IPv6 header, 381-382

firewalls

- configuring with SDMExpress, 233

Flash memory

- Cisco devices, 87

flat addressing

- Data Link layer (OSI), 41

flat topologies, 40**Forward Explicit Congestion Notification (FECN)**

- Frame Relay (WANs), 344-345

- frame-relay (WANs), 146-147

Forwarding port state (STP), 261**Fragment-Free mode (switches), 129****frame duplication**

- switch looping problem, 131-132, 254-255

frame filters (switches)

- MAC addresses, 125

frame forwarding (switches)

- MAC addresses, 123-125

Frame Relay

- configuring, 348

- data transmission rates

- Backward Explicit Congestion Notification (BECN), 344-345

- Forward Explicit Congestion Notification (FECN), 344-345

- encapsulation types

- selecting, 348

- inverse-arp, 345

- non-broadcast multi-access (NBMA)

- medium, 346

- permanent virtual circuits

- (PVCs), 343

- committed information rates (CIRs), 344

- DLCIs (data-link connection identifiers), 343

- LMI (local management interface), 343-344

- split horizon problem, 346-347

- use of subinterfaces, 347

frame tagging

- VLANs

- trunking, 270

frame types

- Data Link layer (OSI), 41

frame-relay

- configuring, 149-152, 348-350

- data transmission rates

- Backward Explicit Congestion Notification (BECN), 146-147

- Forward Explicit Congestion Notification (FECN), 146-147

- encapsulation types

- selecting, 150

- inverse-arp, 147

- LMI

- configuring, 150, 348

- non-broadcast multi-access (NBMA)

- medium, 148

- permanent virtual circuits

- (PVCs), 145

- committed information rates (CIRs), 146

- DLCIs (data-link connection identifiers), 145, 343

- LMI (local management interface), 145-146

- split horizon problem, 148

- use of subinterfaces, 149

- subinterfaces

- configuring, 150, 348

- troubleshooting configuration, 152-153, 350-351

- verification of correct configuration, 152-153, 350-351

frame-relay map command, 150, 348-349**FrameRelay**

- multipoint subinterfaces

- configuring, 349

- point-to-point subinterfaces

- configuring, 349

frames

- CRC (Cyclic Redundancy Check)

- use in Store and Forwarding switching, 128

- runts

- Fragment-Free switching, 129

FTP

- (File Transfer Protocol), 31

- Application layer (OSI), 31

full mesh topology, 17**Full-Duplex connections**

- switches, 129-130

- microsegmentation, 130

full-mesh topology, 17

G–H

Gigabit Ethernet

- VLANs

- trunking, 269

global addresses (NAT), 155**hackers, 176****Half-Duplex connections**

- switches, 129

hashing, 354**HDLC**

- (High-Level Data-Link Control), 138-139, 336-337

- Cisco version, 139, 337-338

- ISO version, 139, 337-338

header fields (IPv6), 381-382**headers**

- UDP, 38-39

headers (TCP), 38**help**

- context-sensitive commands

- Cisco devices, 93-94

- technical support, 474

hexadecimal IPv6 address notation, 376

- slash notation, 377

hexadecimal numbering

- IP addresses

- conversion from decimal system, 56

- decimal conversions, 56

- versus binary values, 54

- versus decimal values, 54-55

- versus binary values, 55

hierarchical routing, 321-323**High-level Data-Link Control, see HDLC, 138-139, 336-337****high-order bits**

- binary numbering system, 53

hold-down timers (distance vector routing protocol), 208**hop counts**

- monitoring (distance vector routing protocol), 206-207

host devices, 16**host fields**

- IP addresses, 59

hostname

- assigning to routers, 228

hostnames

- Cisco switches

- setting, 94

hosts

- broadcast frames

- forwarding by switches, 124

- IP addresses

- number of, 64-65

- multicast frames

- forwarding by switches, 125

- subnetting

- number of, 64-65

- requirements, determining, 69

- unicast frames

- forwarding by switches, 123

HTTP

- Application layer (OSI), 31

hubs

- versus switch usage, 123, 125-126

I**IANA**

- port number ranges
 - Transport layer (OSI), 36-37

ICANN(Internet Corporation for Assigned Network Numbers), 375**ICMP**

- (Internet Connection Management Protocol), 41
- Network layer (OSI), 41
- ping command, 114-115
- routers
 - remote management, 114-115
 - traceroute command, 114-115

IDS, 177**IEEE 802.11 a standard, 170****IEEE 802.11 standard, 169****IEEE 802.11 Wireless Fidelity (WiFi) standard, 21****IEEE 802.11 Wireless Fidelity Standard, 21****IEEE 802.11b standard, 171****IEEE 802.11g standard, 172****IEEE 802.11i**

- WPA2, 179

IEEE 802.11n standard, 172**IEEE 802.1Q protocol**

- frame tagging encapsulation, 272
- VLANs
 - trunking protocol, 272

IEEE 802.3 (Ethernet), 17**IKE(Internet Key Exchange), 355****images (IOS)**

- backup configurations, 109-110
- restore configurations, 109-110
- transferring to/from servers (TFTP), 108-109

Increment

- subnetting
 - requirements, determining, 70
 - spacing between, 61-63

Infrastructure mode, 173**inside addresses (NAT), 154-155****inside global addresses (NAT), 155****inside local addresses (NAT), 155****installing**

- WLANs, 179-180

installing CD-ROM, 473

- system requirements, 472

integrity, 187**Inter-Switch Link protocol, see ISL protocol, 271****Inter-VLAN Routing, 277**

- Layer 3 Switching, 279
- Router-on-a-Stick, 277-278

Interesting octet, 62**Interface configuration mode**

- Cisco devices, 92

interfaces

- routers
 - administratively down, 96
 - configuring (Cisco devices), 96
 - shutdown states, 96

Intermediate System-Intermediate System (IS-IS) protocol, 208**internal attacks, 176****Internet layer**

- TCP/IP network model, 44-45

inverse masks, see wildcard masks, 294**inverse-arp**

- Frame Relay (WANs), 345
- frame-relay (WANs), 147

IOS

- backing up, 108-109

images

- backup configurations, 109-110
- restore configurations, 109-110
- transferring to/from servers (TFTP), 108-109

- restoring, 109

routers

- naming conventions, 106-108
- See Cisco IOS Software, 108

IOS startup process

- Cisco devices, 87-89

IP

- Network layer (OSI), 41

IP ACLs, see ACLs, 288**IP addresses**

ACLs

- configuring for extended type, 296-300
- configuring for named type, 301-302
- configuring for standard type, 293
- established keyword, 300
- extended type, 291-292
- log keyword, 300
- log-input keyword, 300
- named type, 292
- packet filtering functions, 288-290
- SSH access filters, 298-299
- standard type, 291
- Telnet access filters, 298-299
- wildcard masks, 293-295

binary numbering, 52

- decimal conversions, 52-54
- high-order bits, 53
- low-order bits, 53
- values represented, 52

Cisco devices

- management VLAN, 94

classes, 57

classful networks, 61

decimal numbering

- hexadecimal conversions, 56

default subnet masks, 57-58

EIGRP

- configuring, 318

exam prep questions, 73-76, 384-386

- answers to, 78-79, 387

hexadecimal numbering

- decimal conversions, 56
- versus binary values, 54-55
- versus decimal values, 54-55

host fields, 59

host requirements

- determining, 69

Increment requirements

- determining, 70

network fields, 58

- CIDR (Classless Inter-Domain Routing), 59

non-default subnet masks, 59

RIP protocol

- configuring, 210-212

routers

- administrative distance (AD), 372
- Longest Match rule, 373-374
- metric comparisons, 373
- NAT, advantages, 156-157
- NAT, disadvantages, 157
- NAT, dynamic, 159-160
- NAT, global addresses, 154-155
- NAT, load distribution, 156
- NAT, local addresses, 154-155
- NAT, Port Address Translation (PAT), 160-162
- NAT, static, 157, 159
- NAT, uses, 155-156
- next-hop addresses, 372

subnet fields, 59-60

subnet masks

- route summarization, 364-365, 368-370
- route summarization, guidelines for, 366-367
- VLSM, advantages, 362
- VLSM, development of, 362
- VLSM, function of, 362
- VLSM, need for, 362
- VLSM, optimized addressing scheme, 363-364

- subnet requirements
 - determining, 69-70
 - subnets
 - Subnet Zero Rule, 68-69
 - subnetting
 - Broadcast IDs, 65-67
 - chart, creating, 70-72
 - class determination, 60-61
 - default mask, 60-61
 - Increment, 61-63
 - number of hosts, 64-65
 - number of hosts, calculating, 64
 - number of subnets, 67-69
 - IP addressing**
 - configuring on routers with SDMExpress, 228-229
 - ip default-network command**
 - default routes for routers, 202
 - ip ospf cost command (OSFP), 328**
 - ip ospf priority command (OSFP), 328**
 - IPaddressing**
 - subnetting
 - logical AND operation, 65
 - IPS, 177**
 - IPS (Intrusion Prevention System), 192**
 - IPSec**
 - IKE, 355
 - VPNs
 - Tunnel mode, 353
 - IPSec VPNs, 352-353**
 - ESP, 354
 - security algorithms, 356
 - shared keys, 355
 - IPv4**
 - address exhaustion, 374
 - IPv6, 375**
 - address allocation, 375
 - address notation, 376
 - slash notation, 377
 - China Next Generation Internet, 382
 - EUI-64 format, 378
 - features, 380
 - header fields, 381-382
 - migrating to, 382-383
 - Dual Stack, 383
 - PMTU Discovery, 381
 - RA messages, 381
 - RS messages, 381
 - stateless autoconfiguration, 378
 - verifying configuration, 379
 - IPX**
 - Network layer (OSI), 41
 - ISL protocol**
 - (Inter-Switch Link), 271
 - Cisco device requirements, 271
 - frame size, 271
 - frame tagging encapsulation, 272
 - VLANs
 - trunking protocol, 271
 - ISM(Industrial, Scientific, Medical) bands, 168**
 - ISO**
 - HDLC (High-level Data-Link Control) version, 139, 337-338
-
- J-L**
- jam signals, 18**
 - Ethernet collisions, 18
 - Backoff Algorithm time calculations, 18
 - LANS**
 - (local area networks), 17
 - LANs**
 - collisions, 17
 - Ethernet, 17-18
 - 10-BASE 2, 19
 - 10-BASE 5, 19
 - 10/100-BASE T, 19
 - 100-BASE FX, 19
 - 100-BASE T, 19

- 1000-BASE T, 19
- 1000-BASE ZX, 19
- collisions, 17-18
- development of, 17
- IEEE 802.3 specification, 17
- segments, 17
- specifications, 19
- exam prep questions, 23-25
 - answers to, 25-26

Layer 2

- See data link layer, 41

Layer 3

- See network layer, 39

Layer 3 Switching

- Inter-VLAN Routing, 279

Layer 4

- See transport layer, 33

Layer 5

- See session layer, 32

Layer 6

- See presentation layer, 32

Layer 7

- See application layer, 31

LCP (link control protocol)

- PPP sub-layer, 141

Learning port state (STP), 261**leased line WANs, 138, 336**

- encapsulation types, 138-139, 336-337

leased lines, 20**leased lines (WANs)**

- expense of, 20

Lightweight mode, 173**Line configuration mode**

- Cisco devices, 92

link control protocol (LCP)

- PPP sub-layer, 140, 338-339

link state routing protocols, 208**link-state protocols**

OSPF

- characteristics of, 320-321
- configuring, 326-327

Listening port state (STP), 261**LMI (local management interface)**

Frame Relay (WANs)

- states, 343
- types, 344

frame-relay (WANs)

- states, 145
- types, 146

load distribution (NAT), 156**local area networks, see LANs, 17****log keyword**

- extended IP ACLs, 300

log-input keyword

- extended IP ACLs, 300

logging in to SDM Express, 225-227**logging in to SDMExpress, 225****logical AND operation, 65****logos**

- certification status
 - allowable usage of, 3-4

Longest Match rule

- routers, 373-374

loop-free paths

- root bridges (STP), 255-256

loops

- distance vector routing protocols
 - control and prevention of, 205-208
- hold-down timers (distance vector routing protocol), 208
- hop counts
 - maintaining (distance vector routing protocol), 206-207
- poison reverses (distance vector routing protocol), 207

- route poisoning (distance vector routing protocol), 207
- split-horizon rule (distance vector routing protocol), 207
- switch problems
 - broadcast storms, 131-132, 254-255
 - frame duplication, 131-132, 254-255
 - MAC table instability, 131-132, 254-255
- switches
 - preventing (STP), 132, 254-255

low-order bits

- binary numbering system, 53

LWAPP(Lightweight Access Point Protocol), 173

M**MAC addresses, 42**

- Data Link layer (OSI), 42
- EUI-64 format, 378
- OUI (Organizationally Unique Identifier), 42
- switches
 - address learning functions, 123
 - frame filtering functions, 125
 - frame forwarding functions, 123-125
- table instability
 - switch looping problem, 131-132, 254-255

management IP

- switch configuration, 245

MANs, 21**MANs (metropolitan area networks), 21****mapping TCP/IP model layers to OSI model layers, 45****MARS (Security Monitoring, Analysis, and Response System), 193****maximum hop counts**

- monitoring (distance vector routing protocol), 206-207

MeasureUp practice tests, 472

- shortcuts, creating, 473

memory types

- Cisco devices
 - Flash, 87
 - NVRAM (non-volatile RA), 87
 - RAM, 87
 - ROM, 87

mesh topology, 17**metrics**

- routers
 - comparing, 373

metrics (routers)

- EIGRP, 204-205
- OSPF, 204-205
- RIP, 204-205

metropolitan area networks (MANs), 21**microsegmentation, 130**

- Full-Duplex connections (switches), 130

migrating

- to IPv6, 382-383
 - Dual Stack, 383

MIMI(Multiple Input Multiple Output), 172**mitigating security threats, 187**

- access attacks, 189-190
- DDoS attacks, 190-191
- reconnaissance attacks, 188-189

MITM attacks, 189-190**multicast frames**

- forwarding by switches, 125

multicast IPv6 addresses, 377**multiplexing**

- VLANs
 - trunking, 270

multipoint subinterface

multipoint subinterface

- Frame Relay (WANs)
 - resolving split horizon problems, 347
- frame-relay (WANs)
 - resolving split horizon problems, 149

multipoint subinterfaces

- configuring, 349

N

NAC (Network AccessControl), 193

named ACLs, 292

- configuring, 301-302
- numbered, 301

naming

- routers
 - IOS conventions, 106-108

NAT

- (Network Address Translation), 153
- advantages, 156-157
- configuring with SDMExpress, 232
- disadvantages, 157
- Dynamic, 159-160
- global addresses, 155
- inside addresses, 154-155
- inside global addresses, 155
- inside local addresses, 155
- load distribution, 156
- outside addresses, 154
- outside global addresses, 155
- outside local addresses, 155
- Overlapping Address Space problem
 - resolving, 156
- Port Address Translation (PAT), 160-162
- Static, 157, 159
- translations
 - troubleshooting, 162-163
 - verification of, 162-163

typical setup, 154

uses, 155-156

- Well-Meaning Admin Error problem
 - resolving, 156

neighbor table (EIGRP), 317

Network Address Translation, see NAT, 153

network control protocol (NCP)

- PPP sub-layer, 140-141, 338-339

network devices, 16

network fields

- IP addresses, 58
 - (CIDR (Classless Inter-Domain Routing), 59

Network Interface layer

- TCP/IP network model, 44-45

network interface layer (TCP/IPmodel), 45

network layer, 39-40

- protocols, 41

Network layer (OSI), 41

- hierarchical organization of, 40
- packets, 40
- path determination for routers, 39
- protocols
 - ARP, 41
 - ICMP, 41
 - IP, 40-41
 - IPX, 41

networks, 16

- Cisco three-layer hierarchical model, 28
 - Access layer, 29
 - benefits, 30
 - Core layer, 29
 - Distribution layer, 29
- content, 22
- MANs (metropolitan area networks), 21
- OSI model, 30
 - Application layer, 31-32
 - Data Link layer, 41-42

- layer sequence, 30-31
- Network layer, 39-41
- Physical layer, 42-43
- Presentation layer, 32
- sending data between hosts, 43-44
- Session layer, 32
- Transport layer, 33-39
 - versus TCP/IP model, 45
- SANs (storage area networks), 22
- TCP/IP model
 - Application layer, 44-45
 - Internet layer, 44-45
 - Network Interface layer, 44-45
 - Transport layer, 44-45
 - versus OSI model, 45
- topologies
 - bus, 17
 - full mesh, 17
 - partial mesh, 17
 - point-to-point, 16
 - ring, 16
 - star, 16
- next-hop address**
 - routers, 372
- no auto-summary command (RIP), 211**
- non-broadcast multi-access (NBMA) medium**
 - Frame Relay (WANs), 346
 - frame-relay (WANs), 148
- non-default subnet masks**
 - IP addresses, 59
- NTP**
 - (Network Time Protocol), 32
 - Application layer (OSI), 32
- numbered ACLs**
 - treating as named type, 301
- NVRAM (non-volatile RAM) memory**
 - Cisco devices, 87

O

- OFDM (Orthogonal Frequency Division Multiplexing), 170**
- Open Shortest Path First, see OSPF, 202**
- Open System Interconnect model, see OSI model, 30**
- OSI model, 30**
 - (Open System Interconnect), 30
 - Application layer, 31-32
 - DHCP, 32
 - DNS, 32
 - FTP, 31
 - HTTP, 31
 - NTP, 32
 - POP3, 32
 - SMTP, 31
 - SNMP, 32
 - Telnet, 32
 - TFTP, 32
 - data link layer, 41-42
 - Data Link layer
 - flat addressing, 41
 - frame types, 41
 - MAC addresses, 42
 - exam prep questions, 46-48
 - answers to, 48-49
 - layer sequence, 30-31
 - network layer, 39-41
 - Network layer
 - ARP, 41
 - hierarchical organization of, 40
 - ICMP, 41
 - IP, 40-41
 - IPX, 41
 - packets, 40
 - path determination, 39
 - network layer
 - protocols, 41
 - Physical layer, 42-43

OSI model

- physical layer
 - encapsulation, 43-44
- Physical layer
 - sending data between hosts, 43-44
- presentation layer, 32
- Session layer, 32
- transport layer, 33
- Transport layer
 - connection-oriented, 33
 - connectionless, 33
 - port numbers, 36-38
 - reliable communication with TCP, 33-35
- transport layer
 - TCP, 34-38
- Transport layer
 - TCP Sliding Window, 35-36
- transport layer
 - UDP, 38-39
- Transport layer
 - unreliable communication with UDP, 38-39
- versus TCP/IP network model, 45

OSPF

- (Open Shortest Path First), 202
- backup designated routers
 - use of, 323-325
- characteristics of, 320-321
- configuring, 326-327
- designated routers
 - use of, 323
- hierarchical routing, 321-323
- implementing, 328
- ip ospf cost command, 328
- ip ospf priority command, 328
- route summarization, 322
- routers
 - administrative distances, 204
 - routing metrics, 204-205

- show ip ospf interface command, 328-329
- show ip ospf neighbor command, 328-329
- troubleshooting, 328-329
- verifying configuration of, 328-329

OUI (Organizationally Unique Identifier)

- MAC addresses, 42

OUI(Organizationally Unique Identifier), 42**outside addresses (NAT), 154****outside global addresses (NAT), 155****outside local addresses (NAT), 155****Overlapping Address Space problem**

- resolving (NAT), 156

P
packet filters

- ACLs, 288-290

packet switched WANs, 138, 336

- encapsulation types, 138-139, 336-337

packet-switched connections (WANs), 20-21**packet-switched WANs, 20-21****packets, 40**

- Network layer (OSI), 40
- routing, 200

PAR (Positive acknowledgment and retransmission), 34**partial mesh topology, 17****passive routes, 320****Password Authentication Protocol (PAP)**

- PPP, 141, 339
- configuration process, 142-143, 340-341

passwords

- encrypting (enable secret command), 97
- logging in to SDMExpress, 226-227

- recovery process
 - Cisco devices, 89-91
 - requiring for device logons, 97
 - routers
 - remote access, enabling, 111
- path determination, 39**
 - longest match rule, 373-374
- path determination for routers**
 - Network layer (OSI), 39
- permanent virtual circuits (PVCs)**
 - Frame Relay (WANs), 343
 - committed information rates (CIRs), 344
 - data-link connection identifiers (DLCIs), 343
 - LMI (local management interface), 344
 - frame-relay (WANs), 145
 - committed information rates (CIRs), 146
 - data-link connection identifiers (DLCIs), 145
 - LMI (local management interface), 145-146, 343
- physical layer, 42**
 - encapsulation, 43-44
- Physical layer (OSI), 42-43**
 - sending data between hosts, 43-44
- ping command (ICMP), 114-115**
- PMTU(Path MTU) Discovery, 381**
- Point-to-Point Protocol, see PPP, 140, 338**
- point-to-point subinterface**
 - Frame Relay (WANs)
 - resolving split horizon problems, 347
 - frame-relay (WANs)
 - resolving split horizon problems, 149
- point-to-point subinterfaces**
 - configuring, 349
- point-to-point topology, 16**
- poison reverses (distance vector routing protocol), 207**
- POP3**
 - (Post Office Protocol 3), 32
 - Application layer (OSI), 32
- Port Address Translation (PAT), 160-162**
- port numbers**
 - Transport layer (OSI), 36-37
 - destination ports, 37
 - multiplex connections, 37
 - segments, 38
 - source ports, 37
- port numbers (TCP/UDP), 36-37**
- port-based VLAN membership, 268**
- Portfast**
 - configuring, 263
- ports**
 - states, 261
 - Blocking (STP), 261
 - Forwarding (STP), 261
 - Learning (STP), 261
 - Listening (STP), 261
 - timers (STP), 261-262
 - STP types
 - Blocked, 260
 - Designated, 258
 - Root, 257-258
 - selection criteria, 259-260
 - switches for VLANs
 - Auto mode, 273
 - Desirable mode, 273
 - NoNegotiate mode, 273
 - Off mode, 273
 - On mode, 273
 - VLANs
 - dynamic assignment, 269
 - static assignment, 268

PPP

- (Point-to-Point Protocol), 140, 338
- authentication
 - Challenge Handshake Authentication Protocol (CHAP), 141, 339
 - configuring, 142-143, 340-341
 - Password Authentication Protocol (PAP), 141, 339
- debug ppp authentication command, 144, 342
- show interfaces command, 144, 342
- sub-layers
 - link control protocol (LCP), 140-141, 338-339
 - network control protocol (NCP), 140-141, 338-339
- troubleshooting configuration, 144, 342
- verifying configuration, 144, 342

PPP frame

- encapsulation type (WANs), 138-140, 336-338

practice exam #1, 404-405, 407-408, 410-411, 414-426

- answers, 428-429, 431-440
- hint and pointers, 403

practice exam #2, 441, 443-445, 447-448, 451, 453, 455, 457-458

- answers, 460-462, 465, 467-470

practice exams

- MeasureUp, 472
- shortcuts, creating, 473

prep questions

- ACLs, 308-312
 - answers to, 313-314
- Cisco devices, 100-102
 - answers to, 102-103
- IP addresses, 73-76, 384-386
 - answers to, 78-79, 387

- networking fundamentals, 23-25
 - answers to, 25-26
- OSI model, 46-48
 - answers to, 48-49
- routers, 116-118, 330-331, 384-386
 - answers to, 118-119, 221, 333, 387
- subnetting, 73-76
 - answers to, 78-79
- switches, 133-134
 - answers to, 135-136
- VLANs, 280-281, 283
 - answers to, 285-286
- WANs, 357-358
 - answers to, 165, 359

preparing

- exams
 - material resources, 4-5

presentation layer, 32

Presentation layer (OSI), 32

privileged exec access

- Cisco devices, 91

Prometric Test Centers

- exam sign up process, 2-3

protocols

- Network layer (OSI)
 - ARP, 41
 - ICMP, 41
 - IP, 40-41
 - IPX, 41
- routers
 - administrative distance (AD), 372
- VLANs
 - trunking, 270-272

pruning

- VLAN Trunking Protocol (VTP), 276

Q–R

Quality of Service (QoS) traffic

routers, 288

RA (Router Advertisement) messages, 381

RAM memory

Cisco devices, 87

Rapid Spanning Tree Protocol, *see* RSTP, 262-263

RCC 1661

PPP (Point-to-Point Protocol), 140, 338

reconnaissance attacks

mitigating, 188-189

reconnecting to router after SDMconfiguration, 235-236, 240

reliability

UDP, 39

reliable transmission, 33

remote management

routers, 110

CDP protocol, 113-114

ICMP protocol, 114-115

SSH, 112-113

telnet protocol, 110-111

requirements

for branch office router configuration, 395-396

for branch office switch configuration, 390-391

restoring

IOS, 109

image configurations, 109-110

resuming

telnet sessions, 111

retests

exams

waiting periods, 3

ring topology, 16

RIP

(Routing Information Protocol), 202

Bellman-Ford algorithm, 209

configuring, 210-212

no auto-summary command, 211

routers

administrative distances, 204

routing metrics, 204-205

troubleshooting, 212-215

updates, 209

verifying configuration of, 212-215

version 2 command, 211

versions, 209

rogue APs, 176

rollover cable pinouts

console port, 83

terminal session settings, 84

ROM (read only memory)

Cisco devices, 87

root bridges

loop-free paths

STP, 255-256

Root port (STP), 257-258

route poisoning (distance vector routing protocol), 207

route summarization, 364-365

guidelines for, 366-367

OSPF, 322

summary address determination, 368-370

Router configuration mode

Cisco devices, 92

Router-on-a-Stick

Inter-VLAN Routing scheme, 277-278

routers

ACLs

dial-on-demand routing (DDR), 288

Network Address Translation (NAT), 288

- packet filtering functions, 288-290
- Quality of Service (QoS) traffic, 288
- update filtering functions, 288
- administrative distance (AD), 372
- branch office configuration, 396-397
 - requirements, 395-396
- Cisco devices
 - interfaces, enabling, 96
 - serial ports, configuring, 95
- classless routing protocols, 212
- compression identifiers, 107
- default route
 - configuring with SDM, 240
- default routes
 - creating, 201-202
 - example of, 202
 - uses, 201
- distance vector protocols, 205
 - loops, controlling, 205-208
 - maximum hop counter, 206
- dynamic routes, 202
 - administrative distances, 203-204
 - EIGRP (Enhanced Interior Gateway Routing Protocol), 202
 - OSPF (Open Shortest Path First), 202
 - RIP (Routing Information Protocol), 202
- EIGRP
 - configuring, 318
 - Diffusing Update Algorithm (DUAL), 316
 - Feasible Successor Route, 316
 - main features of, 317
 - metrics, 204-205
 - Successor Route, 316
 - tables, 317
- exam prep questions, 116-118, 330-331, 384-386
 - answers to, 118-119, 221, 333, 387
- feature sets, 106
- information retrieval
 - show flash command, 99
 - show interface command, 99
 - show running-config command, 99
 - show startup-config command, 99
 - show version command, 99
- Inter-VLAN Routing, 277
 - Layer 3 Switching, 279
 - Router-on-a-Stick, 277-278
- interfaces
 - administratively down, 96
 - shutdown states, 96
- IOS naming conventions, 106-108
- link state protocols, 208
- Longest Match rule, 373-374
- metrics
 - comparing, 373
- name example
 - feature set component, 106
 - platform component, 106
 - run location component, 106
 - version number component, 106
- neighboring connected devices
 - viewing (show cdp neighbors command), 113-114
 - viewing (show cdp neighbors detail command), 114
 - viewing (show cdp neighbors entry command), 114
- next-hop address, 372
- OSPF
 - backup designated routers, 323-325
 - characteristics of, 320-321
 - configuring, 326-327
 - designated routers, 323
 - hierarchical routing, 321-323
 - implementing, 328
 - ip ospf cost command, 328
 - ip ospf priority command, 328

- metrics, 204-205
- show ip ospf interface command, 328-329
- show ip ospf neighbor command, 328-329
- troubleshooting, 328-329
- verifying configuration of, 328-329
- path determination
 - Network layer (OSI), 39
- remote access
 - passwords, enabling (telnet), 111
- remote management, 110
 - CDP protocol, 113-114
 - ICMP protocol, 114-115
 - SSH, 112-113
 - telnet protocol, 110-111
- RIP
 - Bellman-Ford algorithm, 209
 - configuring, 210-212
 - metrics, 204-205
 - troubleshooting, 212-215
 - updates, 209
 - verifying configuration of, 212-215
 - versions, 209
- route summarization, 364-365
 - guidelines for, 366-367
- securing, 96, 98-99
- show flash command
 - IOS flash memory files, 107-108
- SSH access
 - configuring, 98-99
- static routes
 - administrative distances, 203-204
 - example of, 200-201
 - syntax, 200
 - uses, 200
- telnet sessions
 - resuming, 111
 - suspending, 111

routing

- packets
 - process of, 200
- Routing Information Protocol, see RIP, 202**
- routing table**
 - active routes, 320
 - passive routes, 320
- routing table (EIGRP), 317**
- RS (Router Solicitation) messages, 381**
- RSTP**
 - (Rapid Spanning Tree Protocol), 262-263
 - versus STP, 262-263
- RTF(Rapid Transition to Forwarding), 263**
- runts**
 - frames
 - Fragment-Free switching, 129

S

SANs (storage area networks), 22

scheduling

- exams, 2

SDM

- ACLs
 - configuring, 302-303, 305
- automatic security configuration, 234
- connectivity, testing, 241
- routers, configuring
 - default route, 240

SDM Express

- hostname
 - configuring, 228
- logging in, 225
- reconnecting after router configuration, 235-236, 240
- user credentials
 - configuring, 228

SDMExpress, 224

- logging in, 225-227
- routers, configuring
 - DHCPserver, 230
 - firewall, 233
 - IP addressing, 228-229
 - NAT, 232
 - WAN interfaces, 230, 232

SDN (self-defending network) solutions, 191-193**security**

- best practices, 193
- Cisco SDNsolutions, 191-193
- goals of, 187
- need for, 186
- routers, 96, 98-99
- switch configuration, 244-245
- switches, 96, 98-99
- threats to, mitigating, 187
 - access attacks, 189-190
 - DDoS attacks, 190-191
 - reconnaissance attacks, 188-189
- WLANs, 175-177
 - WEP, 177-178
 - WPA, 179
 - WPA2, 179

segments, 17-18, 38**segments (Ethernet), 17****sequence numbers (TCP), 33****serial port**

- Cisco devices
 - external connections, 85-86

serial ports

- routers
 - configuring (Cisco devices), 95

session layer, 32**Session layer (OSI), 32****Setup mode**

- Cisco devices, 89

shared keys, 355**shortcuts (MeasureUp practice tests), creating, 473****Show ACLs command, 306-307****show cdp neighbors command (CDP), 113-114****show cdp neighbors detail command (CDP), 114****show cdp neighbors entry command (CDP), 114****show flash command**

- router information retrieval, 99
- routers
 - IOS flash memory files, 107-108

show interface command

- router information retrieval, 99

show interfaces command (PPP), 144, 342**show IP ACLs command, 306-307****show ip interface command, 306-307****show ip nat statistics command, 162-163****show ip nat translations command, 162-163****show ip ospf interface command (OSFP), 328-329****show ip ospf neighbor command (OSFP), 328-329****show ip protocols command, 318, 320****show running-config command**

- router information retrieval, 99

show sessions command (telnet), 111**show startup-config command**

- router information retrieval, 99

show version command

- router information retrieval, 99

single-exam option

- cost of, 2

slash notation (IPv6), 377**sliding windows (TCP), 35****SLIP frame (Serial Line IP)**

- encapsulation type (WANs), 138-139, 336-337

SMTp

(Simple Mail Transfer Protocol), 31
Application layer (OSI), 31

SNMP

(Simple Network Management Protocol), 32
Application layer (OSI), 32

source ports, 37**source-route bridges, 123****source-route translational bridges, 123****Spanning Tree Protocol, see STP, 132, 254-255****split horizon rule**

Frame Relay (WANs)
 problem resolution, 346-347
 problem resolution via subinter-
 faces, 347
frame-relay (WANs)
 problem resolution, 148
 problem resolution via subinter-
 faces, 149

split-horizon rule (distance vector routing protocol), 207**SSH, 112-113**

extended IP ACLs
 access filters, 298-299

SSH access

configuring on Cisco routers, 98-99

SSID(Service Set Identifier), 174**SSL VPNs, 356****standard IP ACLs**

configuring, 293-295
filtering criteria, 291
IP ranges, 291
wildcard masks, 293-295

standards

WLANs, 169
 IEEE802.11a, 170
 IEEE802.11b, 171
 IEEE802.11g, 172
 IEEE802.11n, 172

star topology, 16**stateless autoconfiguration (IPv6), 378****states (STP ports), 261**

Blocking, 261
Forwarding, 261
Learning, 261
Listening, 261
timers, 261-262

static IPv6 configuration, 379**Static NAT, 157, 159****static routes**

routers
 administrative distances, 203-204
 example of, 200-201
 syntax, 200
 uses, 200

Static VLAN membership, 268**storage area networks (SANs), 22****Store and Forward mode (switches), 128
STP**

(Spanning Tree Protocol), 132, 254-255

Bridge Protocol Data Units (BPDUs)
 packet communication mechanism, 257

port states

Blocked, 261
Blocking, 261
Forwarding, 261
Learning, 261
Listening, 261
timers, 261-262

port types

Blocked, 260
Designated, 258
Root, 257-258
selection criteria, 259-260

Portfast

configuring, 263

- root bridges
 - loop-free paths, 255-256
- switches
 - loop prevention, 132, 254-255
- versus RSTP, 262-263

straight-through cables

- Ethernet port connections, 84-85

study mode (CD-ROM), 471

study resources, 475, 477

subinterfaces

- Frame Relay (WANs)
 - resolving split horizon problems, 347
- frame-relay (WANs)
 - configuring, 150, 348
 - resolving split horizon problems, 149

subnet fields

- IP addresses, 59-60

subnet masks

- default (IP addresses), 57-58
- non-default (IP addresses), 59
- route summarization, 364-365, 368-370
 - guidelines for, 366-367
- supernetting, 368
- VLSM
 - advantages, 362
 - development of, 362
 - function of, 362
 - need for, 362
 - optimized addressing scheme, 363-364

Subnet Zero Rule, 68-69

subnets

- IP addresses
 - number of, 67-69
- subnetting
 - requirements, determining, 69-70

subnetting

- Broadcast IDs, 65-67
- chart
 - creating, 70-72
- default masks, 60-61
- exam prep questions, 73-76
 - answers to, 78-79
- hosts
 - number of, 64-65
- Increment
 - spacing between IP addresses, 61-63
- IP addresses
 - host requirements, 69
 - Increment requirements, 70
 - subnet requirements, 69-70
- IP class determination, 60-61
- logical AND operation, 65
- Subnet Zero Rule, 68-69
- subnets
 - number of, 67-69

summary addresses

- creating, 368-370

supernetting

- subnet masks, 368

suspending

- telnet sessions, 111

switches, 18

- address learning
 - MAC addresses, 123
- ASIC chips (Application-Specific Integrated Circuit), 126
- basic operation of, 122
- branch office configuration, 392-394
 - requirements, 390-391
- Cisco devices
 - hostnames, setting, 94
- CLI, 244
 - security, configuring, 244-245

- collision isolation, 122
- Cut-Through mode, 128
- duplex connections
 - configuring, 130-131
- exam prep questions, 133-134
 - answers to, 135-136
- Fragment-Free mode, 129
- frame filters
 - MAC addresses, 125
- frame forwarding
 - MAC addresses, 123-125
- frames per second, 127
- Full-Duplex connections, 129-130
- function of, 122
- Half-Duplex connections, 129
- looping problems
 - broadcast storms, 131-132, 254-255
 - frame duplication, 131-132, 254-255
 - MAC table instability, 131-132, 254-255
- number of ports, 127
- port states (STP), 261
 - Blocking, 261
 - Forwarding, 261
 - Learning, 261
 - Listening, 261
 - timers, 261-262
- RSTP
 - versus STP, 262-263
- securing, 96, 98-99
- Spanning Tree Protocol (STP)
 - loop prevention, 132, 254-255
- Store and Forward mode, 128
- STP
 - Blocked port type, 260
 - Designated port type, 258
 - Root port type, 258
 - versus RSTP, 262-263
- versus bridges, 126-127

- versus hubs usage, 123, 125-126
- VLAN Trunking Protocol (VTP)
 - Client mode, 275
 - Server mode, 275
 - Transparent mode, 275
- VLANs
 - configuring for trunking, 272-274
 - port modes, 273
 - segmenting broadcast domains at Layer 2, 264
 - trunking, 270

system requirements, CD-ROM installations, 472

T

tables (EIGRP)

- neighbor, 317
- routing, 317
- topology, 317

TCP, 33

- headers, 38
- port numbers, 36-37
- sliding windows, 35
- three-way handshake, 34-35

TCP ports

- filtering, 297

TCP/IP network model

- Application layer, 44-45
- Internet layer, 44-45
- Network Interface layer, 44-45
- Transport layer, 44-45
- versus OSI model, 45

TCP/IP model, 44

- layers, mapping to OSI model layers, 45

technical support, 474

Telnet

- Application layer (OSI), 32
- extended IP ACLs
 - access filters, 298-299

telnet

- passwords
 - enabling for access, 111
- routers
 - remote management, 110-111
- sessions
 - resuming, 111
 - suspending, 111

terminal sessions

- console port settings, 84

test modes (CD-ROM)

- certification mode, 471
- custom mode, 472
- study mode, 471

testing connectivity with SDM, 241**tests (practice)**

- MeasureUp, 472
- shortcuts, creating, 473

TFTP

- (Trivial File Transfer Protocol), 32, 108
- Application layer (OSI), 32
- IOS images
 - backup configurations, 109-110
 - restore configurations, 109-110
 - transferring to/from servers, 108-109
- troubleshooting tips, 109

Thicknet (10-Base 5 Ethernet), 122**Thinnet (10-Base 2 Ethernet), 122****threats**

- to WLAN security, 175-176

threats to DDoS attacks

- mitigating, 190-191

threats to security

- access attacks
 - mitigating, 189-190
- mitigating, 187
- reconnaissance attack
 - mitigating, 188-189

three-layer hierarchical model, 28

- access layer, 29
- advantages of, 30
- distribution layer, 29

three-layer hierarchical network model (Cisco), 28

- Access layer, 29
- benefits, 30
- Core layer, 29
- Distribution layer, 29

three-way handshake, 34-35**timers**

- port states (STP), 261-262

TKIP(Temporal Key Integrity Protocol), 179**topologies, 16-17**

- flat, 40

topologies (networks)

- bus, 17
- full mesh, 17
- partial mesh, 17
- point-to-point, 16
- ring, 16
- star, 16

topology table (EIGRP), 317**traceroute command (ICMP), 114-115****transitioning**

- to IPv6, 382-383
 - Dual Stack, 383

translations

- troubleshooting (NAT), 162-163
- verifying (NAT), 162-163

transparent bridges, 123**transport layer, 33**

- TCP
 - headers, 38
 - port numbers, 36-37
 - sliding windows, 35
 - three-way handshake, 34-35

Transport layer

TCP/IP network model, 44-45

transport layer

UDP, 38-39

Transport layer (OSI)

connection-oriented, 33

connectionless, 33

port numbers

destination ports, 37

IANA ranges, 36-37

multiplex connections, 37

segments, 38

source ports, 37

unreliable communication with
UDP, 38-39

reliable communication with TCP,
33-35

TCP Sliding Window, 35-36

**trivial file transfer protocol, see TFTP,
108****troubleshooting**

ACLs

command options, 306-307

frame-relay (WANs) configuration,
152-153, 350-351

OSPF protocol, 328-329

PPP configuration, 144, 342

RIP configuration, 212-215

trunking (VLANs), 269

Dynamic Trunking Protocol
(DTP), 273

Fast Ethernet, 269

frame tagging, 270

Gigabit Ethernet, 269

multiplexing, 270

protocol selection, 270

IEEE 802.1Q, 272

ISL, 271

switches, 270

configuring, 272-274

port modes, 273

**VLAN Trunking Protocol
(VTP), 274**

communication configuration,
275-276

pruning, 276

switches, Client mode, 275

switches, Server mode, 275

switches, Transparent mode, 275

troubleshooting, 276

verification of, 276

Tunnel mode (IPSec VPNs), 353**twisted-pair cabling, 18****two-exam option**

cost of, 2

U

UDP, 33, 38-39

headers, 38-39

port numbers, 36-37

Transport layer (OSI)

unreliability of connections, 38-39

UDP ports

filtering, 297

unicast frames

forwarding by switches, 123

unicast IPv6 addresses, 377**UNII(Unlicensed National Information
Infrastructure) bands, 168****unlicensed radio bands, 168-169****unreliable communication with UDP**

Transport layer (OSI), 38-39

user credentials

assigning with SDMExpress, 228

user exec access

Cisco devices, 91

V

Variable Length Subnet Masking, see VLSM, 362

verifying

ACLs

command options, 306-307

EIGRP configuration, 318, 320

IPv6 configuration, 379

OSPF protocol configuration, 328-329

PPP configuration, 144, 342

RIP configuration, 212-215

version 2 command (RIP), 211

Virtual LANs, see VLANs, 264

Virtual Teletype (VTY) lines

extended ACLs

Telnet access, 298-299

viruses, 190

VLAN Membership Policy Server (VMPS), 269

VLAN Trunking Protocol (VTP), 274

communication configuration, 275-276

pruning, 276

switches

Client mode, 275

Server mode, 275

Transparent mode, 275

troubleshooting, 276

verification of, 276

VLANs

(Virtual LANs), 264

benefits of, 265

broadcast domains, 264

segmenting with switches at Layer 2, 264

exam prep questions, 280-281, 283

answers to, 285-286

implementation process

creation step, 266-268

naming step, 266-268

switch port assignment step, 266-268

Inter-VLAN Routing, 277

Layer 3 Switching, 279

Router-on-a-Stick, 277-278

IP subsets, 264

membership

dynamic, 269

port-based, 268

multi-switch configuration, 266

ports

dynamic assignment, 269

static assignment, 268

sample configuration of, 264

trunking, 269

Dynamic Trunking Protocol (DTP), 273

Fast Ethernet, 269

frame tagging, 270

Gigabit Ethernet, 269

multiplexing, 270

protocol selection, 270-272

switches, 270

switches, configuring, 272-274

switches, port modes, 273

VLAN Trunking Protocol (VTP), 274-276

VLSM

(Variable Length Subnet Masking), 362

advantages, 362

development of, 362

function of, 362

need for, 362

optimized addressing scheme, 363-364

VPNs, 352

- IPSec, 352-353
 - security algorithms, 356
 - shared keys, 355
- IPsec
 - Tunnel mode, 353
- SSL, 356

VTY lines, 97**VUE Test Centers**

- exam sign up process, 2-3

W

waiting periods

- exam retakes, 3

WANinterfaces

- configuring with SDMExpress, 230, 232

WANs, 19

- (wide area networks), 19, 138, 336
- cell-switched, 21
- cell-switched connections, 21
- circuit switched, 138, 336
 - encapsulation types, 138-139, 336-337
- circuit-switched, 20
- circuit-switched connections, 20
- dedicated leased line connections
 - expense of, 20
- encapsulation types
 - High-level Data-Link Control (HDLC), 138-139, 336-338
 - PPP frame, 138-140, 336-338
 - Serial Line IP frame, 138-139, 336-337
- exam prep questions, 23-25, 357-358
 - answers to, 25-26, 165, 359
- Frame Relay
 - Backward Explicit Congestion Notification (BECN), 344-345
 - configuration of, 348

- encapsulation types, selecting, 348
 - Forward Explicit Congestion Notification (FECN), 344-345
 - inverse-arp, 345
 - non-broadcast multi-access (NBMA) medium, 346
 - permanent virtual circuits (PVCs), 343-344
 - split horizon problem, 346-347
 - split horizon problem, resolving with subinterfaces, 347
- frame-relay
- Backward Explicit Congestion Notification (BECN), 146-147
 - configuration of, 149-152, 348-350
 - encapsulation types, selecting, 150
 - Forward Explicit Congestion Notification (FECN), 146-147
 - inverse-arp, 147
 - LMI configuration, 150, 348
 - non-broadcast multi-access (NBMA) medium, 148
 - permanent virtual circuits (PVCs), 145-146, 343
 - split horizon problem, 148
 - split horizon problem, resolving with subinterfaces, 149
 - subinterfaces, configuring, 150, 348
 - troubleshooting configuration, 152-153, 350-351
 - verifying configuration, 152-153, 350-351
- leased line, 138, 336
- encapsulation types, 138-139, 336-337
- leased lines, 20
- packet switched, 138, 336
- encapsulation types, 138-139, 336-337
- packet-switched, 20-21
- packet-switched connections, 20-21
- wireless networks, 21

war driving

war driving, 176

websites

- Cisco CCNA Prep Center, 4
- ExamCram2.com
 - additional exam resources, 1
- Prometric Test Centers, 2-3
- VUE Test Centers, 2-3

Well-Meaning Admin Error problem

- resolving (NAT), 156

WEP (Wired Equivalent Privacy), 177

- Cisco's alternative to, 178

Wi-Fi, 169-170

wide area networks, see WANs, 19, 138, 336

wildcard masks

- standard IP ACLs, 293-295

wireless networks, 21

- advantages/disadvantages, 21
- IEEE 802.11 Fidelity standard, 21

WLANs

- APs
 - BSS, 174
 - ESS, 174
- configuring, 179-180

- IEEE 802.11, 169
- IEEE 802.11a, 170
- IEEE 802.11b, 171
- IEEE 802.11g, 172
- IEEE 802.11n, 172
- operational modes, 173
- security, 175
 - WEP, 177-178
 - WPA, 179
 - WPA2, 179
- security methods, 176-177
- standards, 168-169
 - IEEE 802.11a, 170
 - IEEE 802.11b, 171
 - IEEE 802.11g, 172
 - IEEE 802.11n, 172
- unlicensed radio bands, 168-169

WPA (Wi-Fi Protected Access), 179

WPA2, 179

X-Y-Z

Zero Subnets Rule, 68-69