

# Index

## NUMBERS

---

- 3-layer hierarchical models. *See* hierarchical models**
- 3DES (Triple Data Encryption Standard algorithm),  
IPsec encryption, 818**
- 10-Gigabit Ethernet (10GbE), 93**
- 10BASE-FL Ethernet networks, 89**
- 10BASE-T Ethernet networks, 89**
- 10BASE2 Ethernet networks, 88**
- 10BASE5 Ethernet networks, 89**
- 100BASE-FX, 90**
- 100BASE-T4, 90**
- 100BASE-TX, 90**
- 802.11 (wireless networks), 560-561**
  - 802.11a, 63-64, 567
  - 802.11b, 63-64, 567
  - 802.11g, 63-64, 567-568
  - 802.11i (WPA2), wireless network security, 584
  - 802.11n, 568
  - channel surfing, 565
  - data transmission, 562-563
  - IEEE, 561
  - ITU-R, 561
  - overlapping signals, 564-565
  - RF bands, 563-564
  - Wi-Fi Alliance, 561
- 802.1q trunks, VLAN, 508-510**
- 802.1x (wireless authentication), 585-586**
- 802.3. *See* Ethernet**
- 802.3u. *See* Fast Ethernet**
- 1000BASE-T, 91**
- 1000BASE-X, 92**

## A

---

- AAA (Authentication, Authorization, Accounting),  
network security, 122, 125**
- ABR (Area Border Routers), 397**
- access attacks**
  - man-in-the-middle attacks, 116
  - network security, 837

## access attacks

- password attacks, 115
- port redirection, 116
- trust exploitation, 116

**Access layer (hierarchical models), 34****access lists**

- extended access lists, 869-872
- functions of, 869
- interfaces, applying to, 870
- “permit all” statements, 872
- standard access lists, 869, 872
- TCP port numbers, 871
- UDP port numbers, 872
- verifying, 872
- vtv ports, applying to, 870

**access ports, 503****access rates (local), Frame Relay, 877****access-group command, 618****access-list command, 610, 614****ACK packets, 28****ACL (Access Control Lists), 604**

- deny statements, 604-606
- Dial-on-Demand routing, 608
- extended ACL
  - blocking subnets, 626-630
  - configuring, 620-626
  - restricting HTTP/HTTPS access, 631-632
- IOS formatting, 606
- named ACL, configuring, 632-633
- NAT, 609
- network security, 123-125
- packet filtering, 607
- permit statements, 604-606
- QoS, 608
- route filtering, 609
- standard ACL
  - configuring, 610-613
  - isolating networks, 616-619
  - placement of, 614-615
  - restricting VTY access, 619
  - verifying, 613-614
- verifying
  - show ip access-lists command, 636
  - show ip interface command, 635
  - show running-config command, 634

**ACTIVE states (PVC), 769****ad hoc wireless networks, 587****adjacency tables. *See* neighbor tables****administration routing distances (default), 857-858****administrative distances (IOS), 324****advanced distance vector routing protocols. *See* balanced hybrid routing protocols****Advanced NAT wizard (NAT Configuration window), 663-669****advertised distances, neighbor routers, 419****AES (Advanced Encryption Standard algorithm), IPsec encryption, 818****AH (Authentication Headers), IPsec, 822****ambiguous command syntax errors, IOS, 845****answers (practice exams), 901-909****AP (Access Points), wireless networks**

- BSS, 588
- ESS, 588
- troubleshooting, 593

**Application layer**

- OSI model, 16-17
  - functions of, 829
  - protocols list, 830
- TCP/IP model, 26-27

**area command, OSPF, 409****areas (link-state routing protocols), 395-398****ARP (Address Resolution Protocol), 33**

- Inverse ARP, 765
- Proxy ARP, 137
- RARP, 137

**asynchronous serial interfaces, 188****ATM (Asynchronous Transfer Mode), WAN, 726-727****attenuation, 57****authentication**

- 802.1x (wireless authentication), 585-586
- IPsec, VPN, 820
- PPP, 729, 875-876
  - callbacks, 731
  - CHAP, 730-731, 734-736
  - compression, 732
  - configuring, 734-736
  - MPPC, 733
  - MPPP, 733

- PAP, 730
- Predictor algorithm, 732
- Stacker algorithm, 732
- wireless networks, 868

**autonomous systems, 339**

**auxiliary ports, 210**

- password configuration, 537-538
- User EXEC access, securing, 248

---

## B

**backbone areas (OSPF), 397**

**BackboneFast**

- configuring, 478
- STP, 852
- verifying activation, 479

**backups, TFTP servers, 267-269**

**balanced hybrid routing protocols, 416**

**bandwidth, 56, 833**

- EIGRP configuration, 423
- OSPF, cost values based on bandwidth chart, 863

**bandwidth command, router configuration, 254**

**banner motd (message of the day command), 242**

**banners**

- login banners, creating, 242
- SDM, changing in, 297

**baseband, WAN, 722**

**Basic NAT wizard (NAT Configuration window), 659-663**

**BDR (Backup Designated Routers), OSPF elections, 401-403**

**BECN (Backwards Explicit Congestion Notifications), 761, 877**

**BGP (Border Gateway Protocols), 340**

**binary, 137**

- binary-to-decimal conversion, 138-139
- decimal-to-binary conversion, 141, 150, 840

**blocking**

- ports, 447, 451
- subnets, extended ACL, 626-630

**Bluetooth technology, 64**

**Boolean AND, 146-147**

**boot processes, IOS, 843**

**boot system command, 241**

**bootstrap process, 213**

**BPDU (Bridge Protocol Data Units)**

- blocked ports, 451
- designated ports, 450
- inferior BPDU, 478
- root ports, 448-449
- RSTP topology changes via, 485
- spanning-tree portfast bpduguard command, 479

**BPDU Guard, 477**

- configuring, 478
- verifying activation, 479

**BRI (Basic Rate Interfaces), 187-188, 836**

**bridges, 97**

- blocked ports, 451
- Bridge ID, 447-449
- designated ports, 450
- diameters, 454
- frame-forwarding, 444
- MAC filtering, 98
- primary tasks of, 95
- root bridges
  - changing switch priorities in STP, 458
  - root ports, 448-449
  - STP, 447-449

**broadband, WAN, 722**

**broadcast addresses, 83**

**broadcast domains, 832**

**broadcast IP, 144, 149**

**broadcast multiaccess topologies (OSPF), 400-403**

**broadcast storms, 446**

**BSS (Basic Service Sets), WAP, 588**

**bus topologies, 52-53**

---

## C

**cable**

- coaxial cable, 57-58
- cross-over cable, 60
- fiber-optic cable, 62
- rolled cable, 61
- straight-through cable, 59
- twisted-pair cable, 58-61, 833

**call setups.** *See* **three-way handshakes**

**callbacks, PPP authentication, 731**

**CAM (Content Addressable Memory) tables, 442**

**catalyst switches, securing, 195**

physical access to, 536

terminal access to, 537-539

**CD-ROM**

installing, 912

test modes, 911

**CDP (Cisco Discovery Protocol), 270**

disabling, 273

Layer 2 security, 546

no cdp enable command, 273

no cdp run command, 273

show cdp neighbors command, 271

**certification mode (CD-ROM), 911**

**channel surfing (wireless networks), 565**

**channel-group command, EtherChannel assignments, 480**

**CHAP (Challenge Handshake Authentication Protocol), PPP authentication, 730-731, 734-736, 875**

**CIDR (Classless Interdomain Routing), 147, 338, 840**

**CIR (Committed Information Rates), 760-762, 877**

**circuit-switched networks (WAN), 721, 874**

**classful network boundaries, RIP, 369**

**classful routing, 333-334, 859**

**classless routing, 333-339, 859**

**clear ip nat translations \* command, troubleshooting NAT, 676, 707**

**client mode (VTP), 512**

**clientless SSL VPN (Secure Socket Layer Virtual Private Networks), 813**

**clock rate command, router configuration, 254**

**coaxial cable, 57-58**

**collision domains, 95, 832**

**commands**

context-sensitive help, 844

displaying, 844

EIGRP

troubleshooting commands list, 866

verification commands list, 866

interface configuration commands list, 847

**IOS**

abbreviations, 224

common syntax errors, 226-227

global configuration, 845

listing, 223

shortcut keys, 225

**OSPF**

troubleshooting commands list, 865

verification commands list, 865

**RIP**

troubleshooting commands list, 862

verification commands list, 862

switch configuration commands list, 847

**compression**

MPPC, PPP authentication, 733

PPP, 732, 736, 875-876

**config-register command, 240**

**configure command, 221.** *See also* **Global Configuration**

**configuring**

access lists, extended access lists, 871

**ACL**

extended ACL, 620-626

named ACL, 632-633

standard ACL, 610-613

BackboneFast, STP, 478

BPDU Guard, STP, 478

default routers, SDM, 329-330

dynamic NAT, 695-698

EIGRP, 422, 866

bandwidth, 423

ip default-network command, 424

stub routing, 424

unequal-path load balancing, 423-424

via SDM, 425

Frame Relay, 879

multipoint interfaces, 773-779

point-to-point interfaces, 780-785

single neighbors, 767-772

interface commands list, 847

IOS, global configuration commands list, 845

IPv6 autoconfiguration, 164

- NAT, 659
  - NAT Overload/PAT, 873
  - Static NAT, 873
- NAT overload, 699-704
  - advanced configuration, 663-669
  - basic configuration, 659-663
  - editing configurations, 670-672
  - verifying configurations, 672-675
- OSPF, 407-408, 864
  - loopback interfaces, 404
  - via SDM, 410-411
  - wildcard masks, 405-407
- PortFast, STP, 478
- PPP
  - authentication, 734-736
  - compression, 736
- RIP, 368-370, 374, 862
- RIPv2, 373
- routers, 255
  - assigning duplexes, 253
  - assigning IP addresses, 252
  - assigning speed to, 253
  - backing up IOS files via TFTP servers, 268
  - backing up via TFTP servers, 267-269
  - bandwidth command, 254
  - clock rate command, 254
  - enabling interfaces, 253
  - LAN-specific commands, 253
  - no keepalives command, 253
  - no shutdown command, 253
  - returning to default configurations, 255
  - saving configurations, 254
  - verifying configurations, 257-258
  - WAN-specific commands, 254
- SDM
  - banners, 297
  - domain names, 297
  - global configurations, 296-297, 301-306
  - host names, 297
  - router interface configuration, 306-308
  - secret passwords, 297
  - static NAT, 689-695
  - static routers, SDM, 329-330
  - STP, 852
  - subinterfaces, Frame Relay, 773
  - switches
    - assigning IP addresses via DHCP, 456-457
    - assigning management IP addresses to, 455
    - backing up IOS files via TFTP servers, 268
    - backing up via TFTP servers, 267-269
    - configuration commands list, 847
    - defining default gateways, 455
    - multiple switch interfaces, 457
    - returning to default configurations, 255
  - trunks, 855
  - UplinkFast, STP, 478
  - VLAN, 505, 854
    - 802.1q trunks, 509
    - DTP dynamic trunks, 510
    - ISL trunks, 509
  - VTP, 514-515, 856
  - WAN, PPP, 875-876
- Connection-Oriented Communication sessions, 28**
- console access, securing to USER EXEC, 246-247**
- console ports, 209**
- context-sensitive help, commands, 844**
- copy command, 254, 270, 847-848**
- copy running-config flash command, 269**
- copy tftp flash command, 269**
- Core layer (hierarchical models), 35-36**
- counts to infinity, mitigating, 363**
- CPE (Customer Premise Equipment), 189**
- CRC (Cyclic Redundancy Checks), 444**
- cross-over cable, 60**
- crosstalk, 57, 833**
- crypto key generate rsa command, 246**
- CSMA/CD (Carrier Sense Multiple Access Collision Detection), 88, 445**
- CSU/DSU (Channel Service Units/Data Service Units), 189-190, 724**
- Ctrl+Shift+6 keyboard shortcut, suspending Telnet sessions, 274-275**
- custom mode (CD-ROM), 911**
- cut-through method (frame-forwarding), 444**

## D

**data integrity, IPsec, 820**

**Data Link layer (OSI model), 21-23, 94**

bridges, 97

MAC filtering, 98

primary tasks of, 95

Ethernet

addressing, 81-84

framing, 85-87

FDDI protocols, 80-81

functions of, 829

switches, 95, 98-99

Token Ring protocols, 78-79

**Data Link WAN encapsulations**

ATM, 726

Frame Relays, 726

HDLC, 726

LAPB, 726

PPP, 726

PPPoA, 727

PPPoE, 727

SLIP, 725

**data packets, Network layer (OSI model) routing, 168**

**data transmission, wireless networks, 562-563**

**DCE (Data Communications Equipment), 23, 188, 836**

**DDoS (Distributed Denial of Service) attacks, 119**

**DE (Discard Eligible), 877**

**dead/invalid timers, 367**

**debug command, 266-267, 377**

**debug frame-relay lmi command, troubleshooting Frame Relays, 788**

**debug ip eigrp command, 427**

**debug ip nat command, troubleshooting NAT, 706**

**debug ip ospf command, 415**

**debug ppp authentication command, 740, 876**

**debug spanning-tree command, 461**

**decimals**

binary-to-decimal conversion, 138-139

decimal-to-binary conversion, 141-142, 150, 840

decimal-to-hexadecimal conversion, 142-143

**default administrative routing distances, 857-858**

**default gateways (routing), 320-321**

**default routes, 328, 858**

configuring via SDM, 329-330

verifying, 330-331

**default-information originate command, OSPF, 410**

**delays (forward), 454**

**DELETED states (PVC), 770**

**demarcation points, 189**

**deny statements, ACL, 604-606**

**DES (Data Encryption Standard algorithm), IPsec encryption, 817**

**description command, assigning descriptions to router interfaces, 253**

**designated ports**

RSTP, 486

STP, 450

**Desktop layer (hierarchical models). *See* Access layer (hierarchical models)**

**Destination Unreachable error messages (ICMP), 265, 837**

**device monitoring, SDM, 309**

**DH (Diffie-Hellman) key exchange algorithm, VPN encryption, 818**

**DHCP (Dynamic Host Configuration Protocol), 850**

IOS, 278

ip dhcp excluded-address ip-address command, 277

ip dhcp pool poolname command, 276

show ip dhcp binding command, 277

IP addresses

assigning to switches, 456-457

IPv6 autoconfiguration, 164

router amnesia, 278

SDM, configuring, 304, 306

**dial-on-demand connections (WAN), 721**

**Dial-on-Demand routing, 608**

**Dijkstra Shortest Path First (SPF) algorithms, 394**

**discovery protocol, 849**

**displaying commands, 844**

**distance vector routing protocols, 340. *See also* routing loops**

hold-down timers, 861

maximum hop counts, 860

operations of, 358-359

RIP, 861-862  
 routing poisoning with poison reverse, 861  
 split horizon, 861  
 updates, 861

**distribution frames, 62**

**Distribution layer (hierarchical models), 35**

**DLCI (Data Link Connection Identifiers), 759-760, 877**  
 inverse ARP, 765, 878  
 static mappings, 878

**DNS (Domain Name Servers)**  
 SDM, configuring, 302  
 TCP/UDP support, 30

**DoD (Department of Defense) models. *See* TCP/IP model**

**domains**  
 collision domains, segmenting/creating, 95  
 names  
   changing in SDM, 297  
   configuring resolution, 244-245

**DoS (Denial of Service) attacks**  
 DDoS attacks, 119  
 network security, 838  
 wireless networks, 581

**DR (Designated Routers), OSPF elections, 401-403**

**DRAM (Dynamic Random Access Memory), 191.**  
*See also* RAM

**DS1 (Digital Signal level 1) services, 188**

**DTE (Data Terminal Equipment), 23, 189-190, 836**

**DTP (Dynamic Trunk Protocol), VLAN, 510**

**DUAL algorithms (EIGRP), 419-421**

**duplexes**  
 interfaces, 851  
 logic, 99  
 router assignments, 253

**dynamic DTP trunks, VLAN, 510**

**dynamic NAT (Network Address Translation), 655, 686, 695-698, 873**

**dynamic routing protocols, 331, 858**  
 distance vector routing protocols, 340  
   hold-down timers, 861  
   maximum hop counts, 860  
   RIP, 861-862  
   RIPv2, 861

EIGRP (Enhanced Interior Gateway Routing Protocol)  
 route poisoning with poison reverse, 861  
 split horizon, 861  
 updates, 861

EG, 859  
 hybrid routing protocols, 341, 860  
   balanced hybrid routing protocols, 416  
   EIGRP, 417-427, 865-866

IG, 859  
 interior/exterior gateway routing protocols, 339  
 link state routing protocols, 340-341, 860  
   areas, 395  
   LSA, 394  
   LSU, 395  
   neighbor tables, 394  
   OSPF, 396-415, 862-865  
   SPF, 394  
 redistribution, 860  
 routed protocols versus, 331  
 routing metrics, 859  
 routing updates, 859

## E

**Edit NAT Configuration window (SDM), 670-672**

**EG (Exterior Gateway) routing protocols, 859**

**EIA/TIA (Electronic Industries Association/Telecommunications Industry Association), 190**

**EIGRP (Enhanced Interior Gateway Routing Protocol)**  
 characteristics of, 417-418, 865-866  
 configuring, 422, 866  
   bandwidth, 423  
   ip default-network command, 424  
   stub routing, 424  
   unequal-path load balancing, 423-424  
   via SDM, 425  
 DUAL algorithms, 419-421  
 feasible successor routes, 419  
 SIA timers, 421  
 stub routing, 421, 424  
 successor routes, 419-421  
 troubleshooting, 427, 866  
 verifying, 425-427, 866

eigrp stub command, EIGRP stub routing configuration

**eigrp stub command, EIGRP stub routing configuration, 424**

**EMI (Electromagnetic Interference), 57**

**enable password command, 243, 251, 846**

**enable secret command, 243, 251, 539, 846**

**encapsulation, 24**

Frame Relay, 767, 770-771

PPP, 875

**encapsulation frame-relay command, 768**

**encryption**

IPsec, 124-125, 816-820

SSH, 124-125

SSL, 124-126

VPN, 816-820, 880

wireless networks, 867

WEP, 582-583

WPA, 584

WPA2, 584

**erase startup-config command, 255**

**ESP (Encapsulating Security Payload), IPsec, 822**

**ESS (Extended Service Sets), WAP, 588**

**EtherChannel, 479-481, 852**

**Ethernet, 87**

10BASE-FL, 89

10BASE-T, 89

10BASE2, 88

10BASE5, 89

10GbE, 93

802.3, 89, 834

802.3ab, 834

802.3u, 91, 834

802.3z, 92-93, 834

addressing, 81-84

Fast Ethernet, 90

framing, 85-87, 835

Gigabit Ethernet

1000BASE-T, 91

1000BASE-X, 92

GBIC, 187

ports, 187

LRE, 93

Metro Ethernet, WAN, 723

switch interfaces. *See* ports

**exams (practice)**

answers, 901-909

MeasureUp, 912-913

questions, 881-899

**EXEC, 211**

IOS terminal access methodologies, 843

ping command, 265

Privileged EXEC, 220. *See also* configure command

access, security, 846

debug command, 266-267

passwords, assigning, 243

ping command, 266

Telnet, virtual terminal access, 275

terminal monitor command, 275-276

Telnet, virtual terminal access, 274-276

User EXEC

access security, 845

auxiliary access, securing, 248

console access, securing, 246-247

overview, 219

SSH access security, 248-251

Telnet, 248-251, 275

**exec-timeout command, 247, 539**

**extended access lists, 869-872**

**extended ACL (Access Lists), 620**

blocking subnets, 626-630

configuring, 620-626

restricting HTTP/HTTPS access by, 631-632

**exterior/interior gateway routing protocols, 339**

## F

**Fast Ethernet, 90**

**FCS (Frame Check Sequence) fields, 508**

**FDI (Fiber Distributed Data Interface) protocol, 80-81**

**feasible distances (local routers), 419**

**feasible successor routes, 419**

**feature sets (IOS), 192**

**FEEN (Forward Explicit Congestion Notifications), 762, 877**

**FEXT (Far-End Crosstalk), 57**

**fiber-optic cable, 62, 833**



**filtering**

- MAC addresses, 443
- packets, 607
- routes, 609

**firewalls, 125-126, 814****flapping, 396****Flash, 191**

- copy running-config flash command, 269
- copy tftp flash command, 269
- distance vector routing protocol updates, 861
- show flash command, 262

**flash updates (routers), 367****floating static routes, 327, 858****FLSM (Fixed Length Subnet Masks), 334****formatting ACL, IOS, 606****forward delays, 454****fragment-free method (frame-forwarding), 444****fragmentation, MLPPP, 733****Frame Relay, 754. See also NBMA networks**

- address mapping, 765-766
- BECN, 761, 877
- CIR, 760-762, 877
- configuring, 879
  - multipoint interfaces, 773-779
  - point-to-point interfaces, 780-785
  - single neighbors, 767-772
- DE, 877
- DLCI, 759-760, 877-878
- encapsulation, 767, 770-771
- FECN, 762, 877
- LMI, 759, 877
- Local Access Rates, 760, 877
- PVC, 769-770
- show frame-relay map command, 772, 777
- show frame-relay pvc command, 769, 777
- subinterfaces
  - configuring, 773
  - multipoint subinterfaces, 764
  - overview, 764
  - point-to-point subinterfaces, 765
- troubleshooting, 786-789, 879
- verifying operation of, 785-786

## virtual circuits, 755

- CIR, 877
- full mesh topologies, 757, 877
- hub and spoke topologies, 756, 876
- multipoint subinterfaces, 877
- partial mesh topologies, 757, 877
- point-to-point subinterfaces, 877
- PVC, 758, 877-878
- SVC, 758-759, 877-878
- WAN, 726

**frame-forwarding, 442-444, 850****full duplex connections (switches), 445****full mesh topologies (virtual circuits), 757, 877****full-duplex modes, 99****G****gain, 65****gateways**

- routers
  - default gateways, 320-321
  - interior/exterior gateway routing protocols, 339
- switches, defining default gateways, 455

**GBIC (Gigabit Interface Converters), 187****Gigabit Ethernet**

- 10-Gigabit Ethernet (10GbE), 93
- 1000BASE-T, 91
- 1000BASE-X, 92
- GBIC, 187
- overview, 91
- ports, 187

**Global Configuration, 221**

- banner motd (message of the day command), 242
- boot sequences, changing, 240-241
- boot system command, 241
- config-register command, 240
- crypto key generate rsa command, 246
- domain name resolution, configuring, 244-245
- enable password command, 243
- enable secret command, 243
- host names, changing, 242
- hostname command, 242

- interface configuration, 222
- IOS commands list, 845
- ip dhcp excluded-address ip-address command, 277
- ip domain-name command, 245
- ip host command, 244
- ip name-server command, 245
- line configuration, 222-223
- login banners, creating, 242
- no cdp enable command, 273
- no cdp run command, 273
- Privileged EXEC mode, assigning passwords to, 243
- SDM, 296
  - banners, 297
  - DHCP, 304-306
  - DNS, 302
  - domain names, 297
  - host names, 297
  - router access, 301
  - secret passwords, 297
- service password-encryption command, 244
- service timestamp command, 267
- SSH, 245-246

**global IP addresses, 162, 842, 873**

**global/local (NAT), 657, 687**

---

## H

- hacking wireless networks, 581**
- half-duplex connections, switches, 445**
- half-duplex modes, 99**
- hashing**
  - algorithms, 821
  - passwords, 731
- HDLC (High-Level Data Link Control), 726-727, 874**
- help**
  - context-sensitive help, commands, 844
  - technical support, 913
- hexadecimals, 142-143**
- hierarchical models, 33-34**
  - Access layer, 34
  - Core layer, 35-36
  - Distribution layer, 35
  - overview, 33-34

- hold-down timers, 366, 861**
- hop counts, distance vector routing protocols, 860**
- host names, changing, 242, 297**
- hostname command, 242**
- HSSI (High-Speed Serial Interfaces), 188**
- HTTP (Hypertext Transfer Protocol), 210, 631-632**
- HTTPS (Secure Hypertext Transfer Protocol), 631-632**
- hub and spoke topologies**
  - EIGRP, stub routing, 421
  - virtual circuits, 756, 876
- hubs, 65**
- hybrid routing protocols, 341, 860**
  - balanced hybrid routing protocols, 416
  - EIGRP
    - characteristics of, 417-418, 865-866
    - configuring, 422-425, 866
    - DUAL algorithms, 419-421
    - feasible successor routes, 419
    - SIA timers, 421
    - stub routing, 421, 424
    - successor routes, 419-421
    - troubleshooting, 427, 866
    - verifying, 425-427, 866

---

## I

- IANA (Internet Assigned Numbers Authority), IP addresses**
  - assigning, 137, 148
  - private addresses, class ranges of, 840
- ICMP (Internet Control Messaging Protocol), 136, 165**
  - Destination Unreachable error messages, 265, 837
  - overview, 32-33
  - PING command, 265, 837
  - traceroute command, 266, 837
- IDF (Intermediate Distribution Frames), 62**
- IDS (Intrusion Detection Systems), 125-126**
- IEEE (Institute of Electrical and Electronic Engineers), 561, 834**
- IEEE 802.3. *See* Ethernet**
- IEEE 802.3ab. *See* Gigabit Ethernet**
- IEEE 802.3u. *See* Fast Ethernet**

- IEEE 802.3z. *See* Gigabit Ethernet**
- IFS (Integrated File Systems), 270**
- IGP (Interior Gateway Protocols), 339, 859**
- IGRP. *See* EIGRP**
- image files, naming (IOS), 193**
- INACTIVE states (PVC), 770**
- incomplete command syntax errors, IOS, 845**
- inferior BPDU, 478**
- information queries (reconnaissance attacks), 118**
- infrared technology, 64**
- inside global addresses (NAT), 657, 873**
- inside local addresses (NAT), 657, 688, 873**
- inside/outside (NAT), 657, 687**
- installing**
  - CD-ROM, 912
  - SDM, 295
- interface configuration (Global Configuration), 222, 847**
- interface range command, 457, 480**
- interface status values (show command), 848**
- interior/exterior gateway routing protocols, 339**
- Internet, isolating internal networks from, 618-619**
- Internet layer (TCP/IP model), 31-33**
- internetworks, 10**
  - LAN, 11
  - layered architecture. *See* OSI model
  - MAN, 12
  - SAN, 14
  - VAN, 14
  - WAN, 12-13
- interVLAN routing, 517, 856**
  - routers “on a stick,” 517-519
  - security, 857
  - SVI, 519-520
- invalid input syntax errors, IOS, 845**
- invalid/dead timers, 367**
- Inverse ARP, 765, 878**
- inverse masks. *See* wildcard masks**
- IOS (Internetworking Operating System), 191-193**
  - ACL, formatting, 606
  - administrative distances, 324
  - boot processes, 843
  - commands
    - abbreviations, 224
    - common syntax errors, 226-227
    - context-sensitive help, 844
    - displaying, 844
    - listing, 223
    - shortcut keys, 225
  - configuration files, creating static entries, 244-245
  - DHCP, 276-278
  - EXEC access methodologies, 843
  - feature sets, 192
  - file naming conventions, 836
  - Global Configuration. *See also* configure command
    - commands list, 845
    - interface configuration, 222
    - line configuration, 222-223
  - image files, naming, 193
  - loading, router/switch start-up, 213-216
  - navigation modes, 844
  - Privileged EXEC, 220
  - routers, backing up via TFTP servers, 268
  - security
    - enable password command, 846
    - enable secret command, 846
    - network security, 123-125
    - privileged EXEC access, 846
    - service password-encryption command, 846
    - SSH, 846
    - user EXEC access, 845
  - show flash command, 262
  - show version command, 262-263
  - syntax errors, 845
  - terminal editing keystrokes, 844
  - trains, 192
  - User EXEC, 219
- IP (Internet Protocol) addresses, 31, 137**
  - binary
    - binary-to-decimal conversion, 138-139
    - decimal-to-binary conversion, 141, 150
  - Boolean AND, 146-147
  - broadcast IP, 144, 149

## IP (Internet Protocol) addresses

hexadecimals, 142-143

## IPv4

- address classes, 143-145
- class ranges of, 839
- classes of, 839
- default subnet masks, 839
- IPv6 integration, 164, 842
- private (RFC 1918) addressing, 148
- subnet masks, 146-150, 156
- subnetting IP, 149-159

## IPv6

- address format, 160-161
- autoconfiguration, 164
- communications, 160
- format summary, 841
- global addresses, 162, 842
- ICMPv6, 165
- IPv4 integration, 164, 842
- link-local addresses, 161
- multicast addresses, 163, 842
- site-local addresses, 162, 842
- unique addresses, 162, 842

management addresses, assigning to switches, 455

NAT, 148, 653, 873

network ID, 144

## routers

- assigning to, 252
- verifying assignment in, 277

SDM, assigning to, 306

subnet ID, 144

subnets, 841

switches, assigning to via DHCP, 456-457

**ip address dhcp command, 457**

**ip command, configuring named ACL, 632**

**ip default-gateway command, 456**

**ip default-network command, EIGRP configuration, 424**

**ip dhcp excluded-address ip-address command, 277**

**ip dhcp pool poolname command, 276**

**ip domain-name command, 245**

**ip host command, 244**

**ip name-server command, 245**

**ip nat inside command**

- NAT overload configuration, 661
- troubleshooting NAT, 705

**ip nat outside command, NAT overload configuration, 661**

**ip ospf cost command, OSPF, 410**

**ip ospf priority command, OSPF, 410**

**ip summary-address eigrp command, EIGRP configuration, 424**

**IPS (Intrusion Prevention Systems), 125-126, 586**

**IPsec (Internet Protocol Security)**

- AH, 822
- ESP, 822
- network security, 124-125
- VPN, 815
  - authentication, 820
  - data integrity, 820
  - DH (Diffie-Hellman) key exchange algorithm, 818
  - encryption, 816-817
  - SSL, 819-820

**IPv4 (Internet Protocol version 4) addresses, 838.**

**See also CIDR**

- address classes, 143-145
- class ranges of, 839
- classes of, 839
- default subnet masks, 839
- IPv6 integration, 164, 842
- private (RFC 1918) addressing, 148
- subnet masks, 146-150, 156
- subnetting IP, 149-151
  - calculating hosts, 152-153
  - calculating increments, 155-157
  - calculating networks, 153-154
  - determining range of valid IP, 158-159
  - zero subnet rule, 155

**IPv6 (Internet Protocol version 6) addresses**

- address format, 160-161
- autoconfiguration, 164
- communications, 160
- format summary, 841
- global addresses, 162, 842
- ICMPv6, 165
- IPv4 integration, 164, 842

link-local addresses, 161, 842  
 multicast addresses, 163, 842  
 site-local addresses, 162, 842  
 unique addresses, 162, 842

**ISDN (Integrated Services Digital Networks), BRI, 187-188**

**ISL (Inter-Switch Link) protocol, trunks, 508-510**

**ISO HDLC (PPP), 729**

**isolating networks via standard ACL, 616-619**

**ITU-R (International Telecommunication Union-Radiocommunication Sector), 561**

## J - K - L

**keyboard shortcuts, suspending Telnet sessions, 274-275**

**keystrokes, IOS terminal editing, 844**

**LAN (Local Area Networks), 11, 186-187**

router configuration, 253

VLAN, 502

access ports, 503

configuring, 505, 854

interVLAN routing, 517-520, 856-857

Layer 2 security, 543-545

management VLAN, 504

membership methods, 503

single-switch scenarios, 504

subinterfaces, 517-518

troubleshooting, 522-523

trunks, 506-510, 855

verifying, 506

VMPS, 504

voice VLAN, 520-521, 855

VTP, 511-517, 546

WLAN

hacking, 581

Spread Spectrum Wireless LAN, 833

**LAPB (X.25 Link Access Procedure, Balanced), WAN Data Link encapsulations, 726**

**Layer 1, 23-24. See also Physical layer**

**Layer 2 security, 21-23. See also Data Link layer (OSI model)**

CDP, 546

port security, 540

static MAC addresses, 541

verifying, 542-543

VLAN, 543-545

VTP, 546

**Layer 3 switches, 20, 165, 168. See also Network layer (OSI model)**

interVLAN routing, 856-857

purpose of, 842

**Layer 4, 19. See also Session layer (OSI model); Transport layer (OSI model)**

**Layer 5, 18. See also Session layer (OSI model)**

**Layer 6, 17. See also Presentation layer (OSI model)**

**Layer 7, 16-17. See also Application layer layered architectures. See OSI model**

**LCP (Link Control Protocol), PPP authentication, 729**

callbacks, 731

CHAP, 730-731, 734-736

compression, 732

MPPC, 733

MPPP, 733

PAP, 730

Predictor algorithm, 732

Stacker algorithm, 732

**leased-line networks (WAN), 721, 874**

**Line Configuration, 222-223**

enable password command, 251

enable secret command, 251

exec-timeout command, 247

logging synchronous command, 247

service password-encryption command, 251

User EXEC, securing

auxiliary access, 248

console access, 246-247

SSH access, 248-251

Telnet access, 248-251

**link state routing protocols, 340-341, 860**

areas, 395

LSA, 394

LSU, 395

neighbor tables, 394

## OSPF, 396

- area command, 409
- areas, 396-398
- BDR elections, 401-403
- broadcast multiaccess, 400-403
- characteristics of, 396-403, 862-863
- configuring, 404-411, 864
- cost values based on bandwidth chart, 863
- default-information originate command, 410
- DR elections, 401-403
- initializing, 404
- ip ospf cost command, 410
- ip ospf priority command, 410
- loopback interfaces, 404
- metrics, 399
- NBMA, 400
- point-to-point, 400
- router ID, 399-400
- troubleshooting, 415, 865
- verifying, 412-414, 865
- wildcard masks, 405-407

## SPF, 394

**link-local IPv6 addresses, 161, 842****LLC (Logical Link Controls), 22-23****LMI (Local Management Interfaces), 759, 877****load balancing (unequal-path), EIGRP, 423-424****Local Access Rates, 760, 877****local IP addresses, NAT, 873****local routers, feasible distances, 419****local/global (NAT), 657, 687****log command, configuring standard ACL, 612****logging synchronous command, 247****login banners, 242****longest match rule, 343****loopback interfaces, 400, 404****loops (routing), 360-362**

- counts to infinity, 363
- invalid/dead timers, 367
- route poisoning, 365-366
- split horizons, 363-364, 763
- triggered updates, 367

**lower layers (OSI model), 18****LRE (Long Reach Ethernet), 93****LSA (Link-State Advertisements), 394****LSU (Link-State Updates), 395****M****MAC (Media Access Control) addresses, 22, 834.*****See also* Ethernet, addressing**

- CAM tables, 442
- filtering, 98, 443
- limitations of, 759
- ports, limiting in, 540
- router assignments, 166
- static MAC addresses, switch port security, 541

**man-in-the-middle attacks, network security, 116****management IP addresses, assigning to switches, 455****management VLAN (Virtual Local Area Networks), 504****MAN (Metropolitan Area Networks), 12****mapping NAT port numbers, 668-669****max age timers, 453****MD5 (Message Digest 5) hashing algorithm, 821****MDF (Main Distribution Frames), 62****MeasureUp practice tests, 912-913****memberships, VLAN, 503****memory**

- components of, 191
- types of, 836

**mesh topologies, 55****Metro Ethernet, WAN, 723****microsegmentation, 100****mitigating network attacks**

- AAA, 122, 125
- ACL, 123-125
- encryption, 124-126
- IOS security, 123-125

**MLPPP (Multilink Point-to-Point Protocol), PPP authentication, 733****modules, routers, 194-195****MPPC (Microsoft Point-to-Point Compression), 733, 875****multicast addresses, 83, 163, 842****multilayer switches, 168****multimode (MM) fiber-optic cable, 62****multipoint subinterfaces, 764, 877**

**N**

- 
- named ACL (access lists), configuring, 632-633**
  - naming conventions, IOS files, 836**
  - NAT (Network Address Translation), 148, 609, 872**
    - configuring via SDM, 659
    - debug ip nat command, 706
    - development of, 652
    - dynamic NAT, 655, 686, 695-698, 873
    - inside global addresses, 657, 873
    - inside local addresses, 657, 688, 873
    - inside/outside, 657, 687
    - ip nat inside command, 705
    - local/global, 657, 687
    - outside global addresses, 658, 688, 873
    - outside local addresses, 658, 688, 873
    - private IP addresses, 653
    - show ip nat statistics command, 704
    - show ip nat translations command, 704-705
    - static NAT, 654-655, 686
      - configuring, 689-695, 873
      - show ip nat translations command, 692
      - show running-config command, 692
    - telnet command, 706
    - troubleshooting, 705-707
      - clear ip nat translations \* command, 676, 707
      - show running-config command, 675, 704
    - verifying operation of, 704
  - NAT Configuration window (SDM)**
    - Advanced NAT wizard, 663-669
    - Basic NAT wizard, 659-663
  - NAT overload, 656, 686, 699-704, 873**
    - configuring via SDM
      - advanced configuration, 663-669
      - basic configuration, 659-663
      - editing configurations, 670-672
      - verifying configurations, 672-675
    - port numbers, mapping, 668-669
    - show ip nat statistics command, 673
    - show ip nat transition command, 675
  - native VLAN (Virtual Local Area Networks), 508**
  - navigation modes (IOS), 844**
  - NBMA (Non-Broadcast Multi-Access) topologies (OSPF), 400. *See also* Frame Relay**
  - NCP (Network Control Protocol), PPP, 733**
  - neighbor discovery, CDP, 270-273**
  - neighbor routers, advertised distances, 419**
  - neighbor tables, 394**
  - network command, DHCP IOS, 276**
  - network ID, 144**
  - Network Interface layers (TCP/IP model), 33**
  - Network layer (OSI model), 20**
    - ARP, 137
    - functions of, 136, 829
    - ICMP, 136
    - IP addresses, 137, 142. *See also* IPv4; IPv6
      - binary-to-decimal conversion, 138-139
      - Boolean AND, 146-147
      - broadcast IP, 144, 149
      - decimal-to-binary conversion, 141, 150
      - decimal-to-hexadecimal conversion, 142-143
      - hexadecimals, 142-143
      - management addresses, assigning to switches, 455
      - NAT, 148, 653, 873
      - network ID, 144
      - private (RFC 1918) addressing, 148
      - router assignments, 252, 277
      - subnet ID, 144
      - subnets, 149-159, 841
      - switch assignments via DHCP, 456-457
    - Layer 3 switches, 165, 168
    - Proxy ARP, 137
    - RARP, 137
    - routers, 165-168
    - traceroutes, 136
  - networks**
    - domains, 832
    - HTTP/HTTPS access, restricting by extended ACL, 631-632
    - interfaces, 65
    - security, 114
      - access attacks, 115-116, 837
      - DoS attacks, 119-121, 838
      - mitigating attacks, 122-126, 838
      - reconnaissance attacks, 117-118, 838

standard ACL, isolating via, 616-619

subnets

bus topologies, 52-53

changing RSTP via BPDU, 485

calculating in, 841

mesh topologies, 55

ring topologies, 53-54

star topologies, 54

wireless networks, 587-588

wireless networks, 560

802.11a, 567

802.11b, 567

802.11g, 567-568

802.11n, 568

channel surfing, 565

data transmission, 562-563

IEEE, 561

ITU-R, 561

overlapping signals, 564-565

RF bands, 563-564

Wi-Fi Alliance, 561

**NEXT (Near-End Crosstalk), 57**

**nibbles, 143**

**no access-list command, 618**

**no cdp enable command, 273, 546**

**no cdp run command, 273, 546**

**no command, 240**

**no debug all command, 267**

**no exec command, catalyst switch security, 539**

**no ip directed-broadcast command, 121-122**

**no keepalives command, 253**

**no shutdown command, 253, 270, 540**

**nonedge ports, RSTP, 486**

**NTP (Network Time Protocol), network security, 124-125**

**NVRAM (Nonvolatile Random Access Memory), 191**

## O

**one-way redistribution (routing protocols), 860**

**OSI model, 14**

Application layer, 16-17, 829-830

compared to TCP/IP models, 26

Data Link layer, 21-23, 829

information, controlling, 830

layered communications, 24

list of layers, 25

lower layers, 18

Network layer, 20, 829

Physical layer, 23-24, 829

Presentation layer, 17, 829

related TCP/IP layers, 831

Session layer, 18, 829

Transport layer, 19, 829

upper layers, 15

**OSPF (Open Shortest Path First), 862**

area command, 409

backbone areas, 397

BDR elections, 401-403

configuring, 407-408, 864

loopback interfaces, 404

via SDM, 410-411

wildcard masks, 405-407

cost values based on bandwidth chart, 863

debug ip ospf command, 415

default-information originate command, 410

DR elections, 401-403

initializing, 404

ip ospf cost command, 410

ip ospf priority command, 410

metrics of, 399

router ID, 399-400

stub areas, 398

topologies, 400-403

troubleshooting, 415, 865

verifying, 412-414, 865

wildcard masks, 405-407

**outside global addresses (NAT), 658, 688, 873**

**outside local addresses (NAT), 658, 688, 873**

**outside/inside (NAT), 657, 687**

**overlapping signals (wireless networks), 564-565**

## P

**packet filtering, 607**

**packet sniffers, 117**

**packet-switched networks (WAN), 722, 874**



**PAP (Password Authentication Protocol), PPP authentication, 730, 875**

**PAR (Positive Acknowledgment and Retransmission), 27, 831**

**partial mesh topologies (virtual circuits), 757, 877**

**passive RIP interfaces, 371-372**

**passive-interface command, 867**

**passwords**

aux ports, 537-538

enable password command, 243, 251

enable secret command, 251

hashing, 731

network security, 115

Privileged EXEC mode, assigning to, 243

recovery (router/switch start-ups), 216-217

secret passwords, changing in SDM, 297

service password-encryption command, 244, 251

switch security, 537-538

VTP, 546

**PAT (Port Address Translation). See NAT Overload**

**PDU (Protocol Data Units), 24**

**permanent virtual circuits, 722**

**“permit all” statements, access lists, 872**

**permit statements, ACL, 604-606**

**Physical layer**

hubs, 65

network interfaces, 65

OSI model, 23-24, 829

repeaters, 64

WAN, 724-725

**physical security, switches, 536**

**ping command, 265, 460, 837**

**ping sweeps, 117**

**pinouts, 59**

**PoE (Power over Ethernet), 196**

**point-to-point subinterfaces, 765, 877**

**point-to-point topologies (OSPF), 400**

**poison reverse, 365, 861**

**PortFast, 476-477**

configuring, 478

verifying activation, 479

**PortFast, STP, 852**

**ports, 455**

access ports, 503

auxiliary ports, 210, 537-538

blocked ports, 447, 451

console ports, 209

designated ports, 450, 486

Gigabit Ethernet ports, 187

Layer 2 security, 540

static MAC addresses, 541

verifying, 542-543

MAC addresses, limiting in, 540

NAT port numbers, mapping, 668-669

nonedge ports, RSTP, 486

redirecting

network security, 116

static NAT configuration, 694

roles, RSTP, 482-483

root ports, 448-449

scans, 118

states

RSTP, 482-483

transitioning, 453-454

synchronization, RSTP, 486-488

TCP port number access lists, 871

UDP port number access lists, 872

**POST (Power-On Self-Tests), router/switch startup processes, 212**

**PPP (Point-to-Point Protocol), 727**

authentication, 732-736

compression, 736, 875

configuring, 734-736

ISO HDLC, 729

LCP, 729-736

NCP, 733

troubleshooting, 738-740

verifying operation of, 737-738

WAN, 726, 874-876

**PPPoA (PPP over ATM), WAN, 727**

**PPPoE (PPP over Ethernet), WAN, 727**

**practice exams**

answers, 901-909

MeasureUp, 912-913

questions, 881-899

Predictor algorithm, PPP authentication

**Predictor algorithm, PPP authentication, 732**  
**predictor compression algorithms, PPP compression, 875**  
**Presentation layer (OSI model), 17, 829**  
**private (RFC 1918) addressing, 148**  
**private IP addresses, NAT, 653**  
**Privileged EXEC, 220. *See also* configure command; User EXEC**  
 access, security, 846  
 debug command, 266-267  
 passwords, assigning, 243  
 ping command, 266  
 Telnet, virtual terminal access, 275  
 terminal monitor command, 275-276  
**Proxy ARP (Address Resolution Protocol), 33, 137**  
**pruning, VTP, 514**  
**PVC (Permanent Virtual Circuits), 758, 769-770, 877-878**

## Q - R

**QoS (Quality of Service), 608**  
**queries (information), reconnaissance attacks, 118**  
**questions (practice exams), 881-899**  
**RAM (Random Access Memory), 191**  
**RARP (Reverse Address Resolution Protocol), 33, 137**  
**rebooting via reload command, 269**  
**reconnaissance attacks**  
 information queries, 118  
 network security, 838  
 packet sniffers, 117  
 ping sweeps, 117  
 port scans, 118  
**redirecting ports, static NAT configuration, 694**  
**redistributing routing protocols, 343-344, 860**  
**reload command, 269**  
**remote-access VPN (Virtual Private Networks), 811-813, 880**  
**repeaters, 64**  
**resequence command, configuring named ACL, 634**  
**revisioning, VTP, 514**  
**RF bands, wireless networks, 563-564**  
**RFC 1918 (private) addressing, 148**

**ring topologies, 53-54**  
**RIP (Routing Information Protocol), 379-380**  
 characteristics of, 367  
 configuring, 368-370, 374, 862  
 passive interfaces, 371-372  
 RIPv2 versus, 381, 861  
 troubleshooting, 377-378, 862  
 verifying, 375-376, 862  
**RIPv2 (Routing Information Protocol version 2)**  
 characteristics of, 372  
 configuring, 373  
 RIP versus, 381, 861  
 update authentication, 374  
**rolled cable, 61**  
**ROM (Read-Only Memory), 191**  
**ROMmon, router/switch start-up, 213**  
**root bridges**  
 Bridge ID, 447-449  
 root ports, 448-449  
 STP, 447-449  
 switch priorities changing in STP, 458  
**root ports, STP, 448-449**  
**route filtering, 609**  
**route poisoning**  
 distance vector routing protocols, 861  
 mitigating, 365-366  
**route summarization, VLSM, 338-339**  
**route update packets, Network layer (OSI) routing, 168**  
**router ID (OSPF), 399-400**  
**routers, 194-195**  
 ABR, 397  
 access lists, 869  
 address mapping, Inverse ARP, 765  
 administrative distances, 324  
 amnesia via DHCP, 278  
 boot sequences, changing, 240-241  
 classful routing protocols, 333-334  
 classless routing protocols, 333-339  
 configuration  
 backing up via TFTP servers, 267-269  
 verifying, 257-258  
 default gateways, 320-321

- default routes, 328, 858
    - configuring via SDM, 329-330
    - verifying, 330-331
  - Dial-on-Demand routing, 608
  - dynamic routing protocols, 858
    - distance vector routing protocols, 340, 358-359, 860-861. *See also* routing loops
    - EG, 859
    - hybrid routing protocols, 341, 860
    - IG, 859
    - interior/exterior gateway routing protocols, 339
    - link state routing protocols, 340-341, 394-415, 860
    - redistribution, 860
    - routed protocols versus, 331
    - routing metrics, 859
    - routing updates, 859
  - ICMP, Destination Unreachable error messages, 837
  - interface configuration
    - assigning duplexes, 253
    - assigning IP addresses, 252
    - assigning speed to, 253
    - bandwidth command, 254
    - clock rate command, 254
    - enabling, 253
    - LAN-specific commands, 253
    - no keepalives command, 253
    - no shutdown command, 253
    - returning to default configurations, 255
    - saving, 254
    - WAN-specific commands, 254
  - interface status/statistics, viewing
    - show controller command, 261
    - show interfaces command, 259-260
    - show ip interface brief command, 261
  - interVLAN routing, 856-857
  - IOS files, backing up via TFTP servers, 268
  - IP addresses, verifying assignment of, 277
  - Layer 3 functions, 842
  - Local Access Rates, 760
  - local routers, feasible distances, 419
  - metrics of, 332-333, 859
  - multipoint subinterfaces, 877
  - neighbor routers, advertised distances, 419
  - Network layer (OSI model), 165-168
  - passive-interface command, 867
  - point-to-point subinterfaces, 877
  - redistributing, 343-344
  - RIP, 379-380
    - characteristics of, 367
    - configuring, 368-370, 374, 862
    - passive interfaces, 371-372
    - RIPv2 versus, 381, 861
    - troubleshooting, 377-378, 862
    - verifying, 375-376, 862
  - RIPv2
    - characteristics of, 372
    - configuring, 373
    - RIP versus, 381, 861
    - update authentication, 374
  - routing sources, 323-324, 857-858
  - SDM, 294
    - access configuration, 301, 306-308
    - device monitoring, 309
    - global configurations, 296-297, 301-306
    - installing, 295
  - show processes command, 267
  - smurf attacks, 121
  - start-up procedures
    - bootstrap, 213
    - configuration loading, 215
    - IOS loading, 213-216
    - password recovery, 216-217
    - POST, 212
    - practice challenge, 218
    - ROMmon, 213
    - setup mode, 216
  - static routes, 325
    - configuring, 326, 329-330
    - floating static routes, 327, 858
    - verifying, 330-331
  - VPN, 814
  - WAN, 874-876
- routers “on a stick,” interVLAN routing, 517-519**
- routing by rumor, 358**

**routing loops, 360-362. See also distance vector routing protocols**

- counts to infinity, 363
- invalid/dead timers, 367
- route poisoning, 365-366
- split horizons, 363-364
- triggered updates, 367

**routing tables, 341-343****RSTP (Rapid Spanning Tree Protocol), 481, 486, 490**

- convergence, 854
- designated ports, 486
- edge types, 485
- link types, 485, 853
- nonedge ports, 486
- port roles, 482-483, 853
- port states, 482-483, 853
- port synchronization, 486-488
- STP comparisons to, 481
- topology changes via BPDU, 485

**S****SAN (Storage Area Networks), 14****SDM (Security Device Manager), 294**

- default routes, configuring, 329-330
- device monitoring, 309
- Edit NAT Configuration window, 670-672
- EIGRP configuration, 425
- global configurations, 296
  - banners, 297
  - DHCP, 304, 306
  - DNS, 302
  - domain names, 297
  - host names, 297
  - router access, 301
  - secret passwords, 297
- installing, 295
- NAT Configuration window
  - Advanced NAT wizard, 663-669
  - Basic NAT wizard, 659-663
- NAT overload configuration
  - advanced configuration, 663-669
  - basic configuration, 659-663
  - editing configurations, 670-672
  - verifying configurations, 672-675

OSPF configuration, 410-411

RIP, configuring, 374

router interface configuration

- enabling interfaces, 307

- IP address assignments, 306

- saving configuration, 308

- verifying configurations, 308

static routes, configuring, 329-330

**secret passwords, changing in SDM, 297****security (networks), 114**

access attacks, 837

- man-in-the-middle attacks, 116

- password attacks, 115

- port redirection, 116

- trust exploitation, 116

DoS attacks, 838

- DDoS attacks, 119

- smurf attacks, 121

- TCP SYN attacks, 120-121

interVLAN routing, 857

IOS, 845-846

mitigating attacks, 838

- AAA, 122, 125

- ACL, 123-125

- encryption, 124-125

- firewalls, 125-126

- IDS, 125-126

- IPS, 125-126

- IPsec, 124-125

- NTP, 124-125

- SNMP, 123, 125

- SSH, 123-125

- SSL, 124, 126

- syslog, 124-125

reconnaissance attacks, 838

- information queries, 118

- packet sniffers, 117

- ping sweeps, 117

- port scans, 118

VPN, encryption, 880

wireless networks

- authentication, 868

- encryption standards, 867

- Segment Header format (TCP), 831**
- server mode (VTP), 511**
- service password-encryption command, 244, 251, 539, 846**
- service timestamp command, 267**
- Session layer (OSI model), 18, 829**
- setup mode (router/switch start-ups), 216**
- SHA-1 (Secure Hash Algorithm), 821**
- shortcuts**
  - keyboard, suspending Telnet sessions, 274-275
  - MeasureUp practice tests, creating, 913
- show cdp neighbors command, 271**
- show commands, 256**
  - access lists, verifying, 872
  - EIGRP verification, 425-427
  - general commands list, 848
  - IFS, 270
  - interface status values, 848
  - list of, 264
  - OSPF verification, 412-414
  - router configurations, verifying, 257-258
- show compress command, verifying PPP compression, 738**
- show controller command, viewing router interface status/statistics, 261**
- show controllers serial command, 273**
- show dhcp lease command, 278, 457**
- show flash command, 262**
- show frame-relay lmi command, 768, 785**
- show frame-relay map command, 772, 777, 786**
- show frame-relay pvc command, 769, 777, 785**
- show interface command, 259-261, 876**
- show interface <interface> command, verifying PPP operation, 737-738**
- show interface trunk command, 510, 522-523, 545**
- show interfaces interface-id command, 461**
- show ip access-lists command, verifying ACL, 613-614, 636**
- show ip dhcp binding command, 277**
- show ip interface brief command, viewing router interface status/statistics, 261**
- show ip interface command, verifying ACL, 635**
- show ip nat statistics command, 673, 704**
- show ip nat transition command, verifying NAT overload configurations, 675**
- show ip nat translations command, 692, 704-705**
- show port-security address command, 542**
- show port-security interface command, 542**
- show processes command, 267**
- show running-config command, 257-258, 270, 278, 692**
  - troubleshooting NAT, 675
  - verifying
    - ACL, 634
    - NAT configuration, 704
    - standard ACL, 613-614
- show sessions command, Telnet sessions, 274**
- show startup-config command, 257**
- show version command, 193, 262-263**
- show vlan command, 506, 510, 522**
- show vtp password command, 523**
- show vtp status command, 515, 523**
- SIA (Stuck in Active) timers, 421**
- single-mode (SM) fiber-optic cable, 62**
- site-local IPv6 addresses, 162, 842**
- site-to-site VPN (Virtual Private Networks), 810, 879**
- SLIP (Serial Line Internet Protocol), WAN Data Link encapsulations, 725**
- smurf attacks, 121**
- SNAP (Subnetwork Access Protocol), 87**
- SNMP (Simple Network Management Protocol), network security, 123-125**
- sources (routing tables), 323-324**
- spanning-tree portfast bpduguard command, 479**
- speed, router assignments, 253**
- SPF (Shortest Path First) algorithms, 394**
- split horizons, 763**
  - distance vector routing protocols, 861
  - mitigating, 363-364
- Spread Spectrum Wireless LAN (Local Area Networks), 833**
- SSH (Secure Shell)**
  - catalyst switch security, 538
  - enabling, 245-246
  - EXEC sessions, 211
  - IOS security, 846

## SSH (Secure Shell)

network security, 123-125

User EXEC access, securing, 248-251

**SSL (Secure Socket Layer)**

network security, 124-126

## VPN

clientless SSL VPN, 813

encryption, 819-820

thin-client SSL VPN, 813

**Stacker algorithm, PPP authentication, 732****stacker compression algorithms, PPP compression, 875****standard ACL (access lists), 869, 872**

configuring, 610-613

isolating networks, 616

from specific hosts, 617-618

internal networks from Internet, 618-619

placement of, 614-615

verifying, 613-614

VTY, restricting access, 619

**star topologies, 54****startup processes. *See* boot processes****static MAC addresses, switch port security, 541****static maps, 766, 878****static NAT (Network Address Translation), 654-655, 686**

configuring, 689-695, 873

show ip nat translations command, 692

show running-config command, 692

**static routes, 325**

configuring, 326, 329-330

floating static routes, 327, 858

verifying, 330-331

**STATIC states (PVC), 770****store-and-forward method (frame-forwarding), 444****STP (Spanning Tree Protocol)**

BackboneFast, 478-479, 852

blocked ports, 451

BPDU Guard, 477-479

configuring, 852

designated ports, 450

EtherChannel, 479-481, 852

PortFast, 476-479, 852

## ports

cost values, 851

designated ports, 486

nonedge ports, 486

roles, 482-483, 853

root ports, 448-449

states, 453-454, 482-483, 851-853

synchronization, 486-488

root bridges, 446-449

## RSTP, 490

comparisons to STP, 481

convergence, 854

designated ports, 486

edge types, 485

link types, 485, 853

nonedge ports, 486

port roles, 482-483, 853

port states, 482-483, 853

port synchronization, 486-488

topology changes via BPDU, 485

switches, 458

topology changes, 852

troubleshooting, 461

UplinkFast, 477-479, 852

verifying, 459

**STP cable, 58-59. *See also* twisted-pair cable****straight-through cable, 59, 833****stub areas (OSPF), 398****stub networks, 325****stub routing, 421, 424****study mode (CD-ROM), 911****subinterfaces**

configuring, 773

Frame Relays, 764-765

VLAN, 517-518

**subnet ID, 144****subnets**

blocking, extended ACL, 626-630

decimal to binary conversions, 840

hosts, calculating, 841

IP addresses, 841

masks, 150, 156

CIDR notation, 147

FLSM, 334

- IPv4, 146-149
- IPv4 addresses, 839
- VLSM, 335-339
- networks, calculating, 841
- subnetting IP (Internet Protocol), 149-151**
  - calculating
    - hosts, 152-153
    - increments, 155-157
    - networks, 153-154
  - range of valid IP, determining, 158-159
  - zero subnet rule, 155
- successor routes (EIGRP), 419-421**
- summarization (route), VLSM, 338-339**
- SVC (Switched Virtual Circuits), 758-759, 877-878**
- SVI (Switched Virtual Interfaces), interVLAN routing, 519-520**
- switches, 98-99, 195-196**
  - basic connectivity, troubleshooting, 460-461
  - boot sequence, changing, 240-241
  - catalyst switches
    - securing physical access to, 536
    - securing terminal access to, 537-539
  - configuration
    - backing up via TFTP servers, 267-269
    - commands list, 847
    - returning to default configurations, 255
  - default gateways, defining, 455
  - diameters, 454
  - filtering, 443
  - frame-forwarding, 442-444, 850
  - full duplex connections, 445
  - functions of, 850
  - half-duplex connections, 445
  - interface range command, 457
  - IOS files, backing up via TFTP servers, 268
  - IP addresses, assigning
    - management IP addresses, 455
    - via DHCP, 456-457
  - ip default-gateway command, 456
  - Layer 2 security
    - CDP, 546
    - port security, 540-541
    - verifying, 542-543
  - VLAN, 543-545
  - VTP, 546
  - Layer 3 switches, 842
    - functions of, 165, 168
    - interVLAN routing, 856-857
  - microsegmentation, 100
  - multilayer switches, 168
  - multiple switch interfaces, configuring, 457
  - physical security, 536
  - ports, 455
    - access ports, 503
    - blocked ports, 451
    - changing costs of, 458
    - designated ports, 450
    - limiting MAC addresses in, 540
  - primary tasks, 95
  - redundant design, 446
  - show dhcp lease command, 457
  - show interfaces interface-id command, 461
  - start-up procedures
    - bootstrap, 213
    - configuration loading, 215
    - IOS loading, 213-216
    - password recovery, 216-217
    - POST, 212
    - practice challenge, 218
    - ROMmon, 213
    - setup mode, 216
  - STP, 446
    - changing port costs in, 458
    - changing priority in, 458
    - root bridges, 447-449
  - trunks, 855
  - VLAN, single-switch scenarios, 504
- switchport access vlan command, configuring VLAN, 506**
- switchport mode trunk command, VLAN trunking, 522**
- switchport port security mac-address sticky command, 541**
- switchport port-security command, 540**
- switchport port-security maximum command, 541**
- switchport port-security violation shutdown command, 541**

**SYN packets, 28**  
**SYN-ACK packet, 28**  
**synchronization, RSTP, 486-488**  
**synchronous serial interfaces, 188**  
**syntax errors, IOS, 845**  
**syslog, network security, 124-125**  
**system requirements, CD-ROM installations, 912**

## T

**T1 controller cards, 188**  
**TCN (Topology Change Notifications), 486**  
**TCP (Transfer Control Protocol), 27-29**  
   applications that utilize, 832  
   PAR, 831  
   port number access lists, 871  
   Segment Header format, 831  
**TCP SYN attacks, 120-121**  
**TCP/IP layers, related OSI layers, 831**  
**TCP/IP model**  
   Application layers, 26-27  
   compared to OSI model, 26  
   Internet layers, 31-33  
   Network Interface layers, 33  
   overview, 26  
   Transport layers, 27-30  
**technical support, 913**  
**Telnet, 210, 849**  
   catalyst switch security, 538  
   multiple session example, 275  
   resuming sessions, 275  
   showing sessions, 274  
   suspending sessions, 274-275  
   terminal monitor command, 275-276  
   User EXEC access, securing, 248-251  
   virtual terminal access, 274-276  
**telnet command, troubleshooting NAT, 706**  
**terminal, 208**  
   auxiliary ports, 210  
   console ports, 209  
   editing, IOS editing keystrokes, 844  
   HTTP, 210  
   SSH, 211  
   virtual terminal access, Telnet, 274-276

**terminal monitor command, 275-276**  
**test modes (CD-ROM), 911**  
**tests (practice)**  
   answers, 901-909  
   MeasureUp, 912-913  
   questions, 881-899  
**TFTP servers**  
   routers, backing up  
     configurations, 267-269  
     IOS files, 268  
   switches, backing up  
     configurations, 267-269  
     IOS files, 268  
**thin-client SSL VPN (Secure Socket Layer Virtual Private Networks), 813**  
**three-way handshakes, 28**  
**throughput, 12**  
**timers (max age), 453**  
**timestamps**  
   debug messages, 267  
   service timestamp command, 267  
**Token Ring protocols, 78-79**  
**topologies**  
   bus topologies, 52-53  
   mesh topologies, 55  
   ring topologies, 53-54  
   RSTP, changing via BPDU, 485  
   star topologies, 54  
   wireless networks, 587-588  
**traceroute command, 136, 266, 837**  
   RIP, 377  
   switches, troubleshooting basic connectivity, 460  
**traffic policing (QoS), 608**  
**trains (IOS), 192**  
**transmitting data over wireless networks, 562-563**  
**transparent mode (VTP), 512-513**  
**Transport layer (OSI model), 19, 27-30, 829**  
**triggered updates (routing), 367**  
**troubleshooting**  
   debug command, 266-267  
   EIGRP, 427, 866  
   Frame Relays, 786-789, 879  
   NAT, 675-676, 705-707



- OSPF, 415, 865
- ping command, 265
- PPP, 738-740, 876
- RIP, 377-378, 862
- show processes command, 267
- STP, 461
- switches, basic connectivity, 460-461
- traceroute command, 266
- VLAN, 522-523
- wireless networks, 592-593

**trunks, 855**

- configuring, 855
- VLAN, 506
  - 802.1q trunks, 508-510
  - DTP dynamic trunks, 510
  - ISL trunks, 508-510
- VTP, 855

**trust exploitation, network security, 116****twisted-pair cable, 58-61****two-way redistribution (routing protocols), 860****U****UDP (User Datagram Protocol), 29-30**

- applications that utilize, 832
- headers, 832
- port number access lists, 872

**undebug all command, 267****unequal-path load balancing, EIGRP, 423-424****unicast addresses, 82****unique IPv6 addresses, 162, 842****unshielded twisted-pair cable versus fiber-optic cable, 833****updates**

- broadcast multiaccess topologies (OSPF), 401-403
- dynamic routing protocols, 861
- LSU, 395
- RIPv2, 374
- routers, 859

**UplinkFast, 477**

- configuring, 478
- STP, 852
- verifying activation, 479

**upper layer (OSI model), 15****User EXEC. See also Privileged EXEC**

- access security, 845
- auxiliary access, securing, 248
- console access, securing, 246-247
- overview, 219
- SSH access, securing, 248-251
- Telnet
  - securing access, 248-251
  - virtual terminal access, 275

**UTP cable, 58-59. See also twisted-pair cable****V****VAN (Virtual Area Networks), 14****variance command, unequal-path load balancing in EIGRP, 424****verifying**

- access lists, 872

**ACL**

- show ip access-lists command, 636
- show ip interface command, 635
- show running-config command, 634
- standard ACL, 613-614

- EIGRP, 425-427, 866

- Frame Relay operation, 785-786

- NAT, 672-675, 704

- OSPF, 412-414, 865

- port security, switch ports, 542-543

- PPP, 876

- show compress command, 738

- show interface <interface> command, 737-738

- RIP, 375-376, 862

- router configurations, 257-258

- SDM router interface configurations, 308

- STP, 459

- VLAN, 506, 510

- VTP, 515

**virtual circuits, 755, 876**

- CIR, 877

- full mesh topologies, 757, 877

- hub and spoke topologies, 756, 876

- multipoint subinterfaces, 877

## virtual circuits

- partial mesh topologies, 757, 877
- permanent virtual circuits, 722
- point-to-point subinterfaces, 877
- PVC, 758, 877-878
- SVC, 758-759, 877-878

**virtual terminal access, Telnet, 274-276****VLAN (Virtual Local Area Networks), 502**

- access ports, 503
- configuring, 505, 854
- interVLAN routing, 856
  - “routers on a stick,” 517-519
  - security, 857
  - SVI, 519-520
- Layer 2 security, 543-545
- management VLAN, 504
- membership methods, 503
- show interfaces trunk command, 522-523
- show vlans command, 522
- show vtp password command, 523
- show vtp status command, 523
- single-switch scenarios, 504
- subinterfaces, 517-518
- switchport mode trunk command, 522
- troubleshooting, 522-523
- trunks, 506-507
  - 802.1q trunks, 508-510
    - configuring, 855
    - DTP dynamic trunks, 510
    - ISL trunks, 508-510
    - VTP, 855
- verifying, 506
- VMPS, 504
- voice VLAN, 520-521, 855
- VTP, 516-517
  - client mode, 512
  - configuring, 514-515
  - pruning, 514
  - revisioning, 514
  - server mode, 511
  - transparent mode, 512-513
  - verifying, 515
- workgroups, 34

**VLSM (Variable-Length Subnet Masks), 335-339****VMPS (VLAN Membership Policy Servers), 504****voice VLAN (Virtual Local Area Networks), 520-521, 855****VPN (Virtual Private Networks)**

- components of, 814-815
- connectivity, 808-810
- encryption, 880
- IPsec, 815
  - AH, 822
    - authentication, 820
    - data integrity, 820
    - encryption, 816-820
    - ESP, 822
- remote-access VPN, 811-813, 880
- site-to-site VPN, 810, 879
- SSL VPN, 813
- WAN, 723

**VTP (VLAN Trunking Protocol), 516-517, 855**

- client mode, 512
- configuring, 514-515
- Layer 2 security, 546
- pruning, 514
- revisioning, 514
- server mode, 511
- show vtp status command, 515
- transparent mode, 512-513
- verifying, 515
- vtp mode command, 515

**vtp mode command, 515****vtp password command, 546****VTY (Virtual Teletype)**

- access, restricting via standard ACL, 619
- ports, access lists, 870

**W****WAN (Wide Area Networks), 12-13, 835-836**

- baseband connections, 722
- broadband connections, 722
- circuit-switched networks, 721, 874
- Data Link encapsulations
  - ATM, 726
  - Frame Relays, 726

- HDLC, 726
- LAPB, 726
- PPP, 726
- PPPoA, 727
- PPPoE, 727
- SLIP, 725
- dial-on-demand connections, 721
- interfaces
  - asynchronous serial interfaces, 188
  - BRI, 187-188
  - DCE, 188
  - DTE, 189-190
  - HSSI, 188
  - synchronous serial interfaces, 188
  - T1 controller cards, 188
- leased line connections, 721
- leased-line networks, 723, 874
- packet-switched networks, 722, 874
- Physical layer, 724-725
- routers, 167
  - configuring, 254
  - connecting to, 874
  - HDLC, 874
  - PPP, 874-876
- VPN, 723
- WAP (Wireless Access Points)**
  - BSS, 588
  - ESS, 588
  - troubleshooting, 593
- war driving, 580**
- WEP (Wired Equivalent Privacy), wireless networks, 582-583**
- Wi-Fi, IEEE 802 characteristics, 63-64, 834**
- Wi-Fi Alliance, 561**
- wildcard masks, OSPF, 405-407**
- windowing, 28**
- wireless networks, 560-561**
  - 802.11a, 567
  - 802.11b, 567
  - 802.11g, 567-568
  - 802.11n, 568
  - 802.1x (wireless authentication), 585-586
  - ad hoc networks, 587
  - channel surfing, 565
  - characteristics of, 867
  - data rates, 590-591
  - data transmission, 562-563
  - encryption, 582-584
  - IEEE, 561
  - implementing, 587, 592, 869
  - IPS, 586
  - ITU-R, 561
  - overlapping signals, 564-565
  - RF bands, 563-564
  - security
    - authentication, 868
    - encryption standards, 867
  - threats to
    - direct hacking, 581
    - employee ignorance, 581-582
    - war driving, 580
  - topologies, 587-588
  - troubleshooting, 592-593
- WAP**
  - BSS, 588
  - ESS, 588
  - troubleshooting, 593
- Wi-Fi Alliance, 561
- WLAN (wireless local area networks). See wireless networks**
- workgroup layers (hierarchical models). See Distribution layer (hierarchical models)**
- workgroups**
  - hubs, 65
  - VLAN, 34
- WPA (Wi-Fi Protected Access), wireless networks, 584**
- WPA2 (Wi-Fi Protected Access version 2), wireless networks, 584**

## X - Y - Z

**X.25 link access procedure, balanced. See LAPB (X.25 Link Access Procedure, Balanced)**

**zero subnet rule, 155**