

Index

NUMBERS

- 3-layer hierarchical models, 33**
- 10-Gigabit Ethernet (10GbE), 99**
- 10BASE-FL Ethernet networks, 95**
- 10BASE-T Ethernet networks, 95**
- 10BASE2 Ethernet networks, 94**
- 10BASE5 Ethernet networks, 94**
- 100BASE-FX, 96**
- 100BASE-T4, 96**
- 100BASE-TX, 96**
- 802.11 (wireless networks), 476-477**
 - 802.11a, 65, 483
 - 802.11b, 65, 483
 - 802.11g, 65, 483-484
 - 802.11i (WPA2), wireless network security, 498
 - 802.11n, 484
 - channel surfing, 481
 - data transmission, 478-479
 - IEEE, 477
 - ITU-R, 477
 - overlapping signals, 480-481
 - RF bands, 479-480
 - Wi-Fi Alliance, 477
- 802.1x (wireless authentication), 499-500**
- 802.3. *See* Ethernet; IEEE 802.3**
- 802.3u. *See* Fast Ethernet**
- 1000BASE-T, 97**
- 1000BASE-X, 98**

A

AAA (Authentication, Authorization, Accounting), network security, 130, 133

access attacks, 559

- man-in-the-middle attacks, 124
- password attacks, 123
- port redirection, 124
- trust exploitation, 124

Access layer (hierarchical models), 34

ACK packet, 28

ACL (Access Control Lists), network security, 130, 133

ad hoc wireless networks, 501

administrative distances (IOS), 324

Advanced NAT wizard (NAT Configuration window), 401-407

ambiguous command syntax errors, 566

answers (practice exams), 602-609

AP (Access Points), wireless networks, 501, 507

Application layer

- OSI model, 15-16, 550
- protocols list, 551-552
- TCP/IP model, 26-27

ARP (Address Resolution Protocol), 33, 144-145

asynchronous serial interfaces, 190

ATM (Asynchronous Transfer Mode), WAN, 524-525

attenuation, 58

authentication

- 802.1x (wireless authentication), 499-500
- PPP, 527
 - callbacks, 529-530
 - CHAP, 528-529, 533-534
 - compression, 530
 - configuring, 532-534
 - MPPC, 531
 - MPPP, 531
 - PAP, 528

Predictor algorithm, 530

Stacker algorithm, 530

wireless networks, 578

autonomous systems, 340

auxiliary ports, 212

- password configuration, 459-460
- User EXEC access, securing, 250

B

backups, TFTP servers

- routers
 - configurations, 269-271
 - IOS files, 270
- switches
 - configurations, 269-271
 - IOS files, 270

bandwidth, 58, 554

bandwidth command, 256

banner motd (message of the day command), 244

banners

- login, creating, 244
- SDM, changing in, 299-301

baseband, WAN, 520

Basic NAT wizard (NAT Configuration window), 397-400

BGP (Border Gateway Protocols), 340

binary, 145

- binary-to-decimal conversion, 146-147
- converting to decimals, 561
- decimal-to-binary conversion, 148-149, 157-158

blocked ports, 431, 435

Bluetooth technology, 66

Boolean AND, 154-155

boot processes, IOS, 564

boot system command, 243

bootstrap process, 215

BPDU (Bridge Protocol Data Units)

- blocked ports, 435
- designated ports, 434
- root ports, 432-433

BRI (Basic Rate Interface), 189-190, 557**bridges, 101-103, 571**

- blocked ports, 435
- Bridge ID, 431-433
- designated ports, 434
- diameters, 438
- frame-forwarding, 428
- MAC filtering, 104
- primary tasks of, 102
- root bridges, 431-433

broadband, WAN, 520**broadcast addresses, 89****broadcast IP, 152, 157****broadcast storms, 430****BSS (Basic Service Sets), WAP, 501****bus topologies, 54****C****cable**

- coaxial cable, 59-60
- cross-over cable, 62
- fiber-optic cable, 63-64, 554
- rolled cable, 63
- straight-through cable, 61-62
- twisted-pair cable, 60-63, 554

call setups. *See* three-way handshakes**callbacks, PPP authentication, 529-530****CAM (Content Addressable Memory) tables, 426****catalyst switches, 458-461, 572****CD-ROM**

- installing, 612-613
- test modes, 611

CDP (Cisco Discovery Protocol), 272

- disabling, 275
- Layer 2 security, 464
- no cdp enable command, 275
- no cdp run command, 275
- show cdp neighbors command, 273

certification mode (CD-ROM), 611**channel surfing (wireless networks), 481****CHAP (Challenge Handshake Authentication Protocol), PPP, 528-529, 533-534, 581-582****CIDR (Classless Interdomain Routing), 155, 339, 561****circuit-switched networks, 519, 580****Cisco 3-layer hierarchical models.** *See* hierarchical models**classful network boundaries, RIP, 369****Classful Routing, 333-334, 575****Classless Routing, 333-340, 575****clear ip nat translations * command, troubleshooting NAT, 414****clock rate command, router configuration, 256****coaxial cable, 59-60****collision domains, segmenting/creating, 100****compression, PPP authentication, 530-531, 534-535****config-register command, 242****configure command, 222.** *See also* Global Configuration**configuring**

- default routers, SDM, 329-330
- NAT overload via SDM
 - advanced configuration, 401-407
 - basic configuration, 397-400
 - editing configurations, 407-410
 - verifying configurations, 410-413
- NAT via SDM, 397
- PPP
 - authentication, 532-534
 - compression, 534-535

RIP, 368-370, 373, 577

RIPv2, 372

routers

assigning duplexes, 255

assigning IP addresses, 254

assigning speed to, 255

backing up IOS files via TFTP servers, 270

backing up via TFTP servers, 269-271

bandwidth command, 256

clock rate command, 256

enabling interfaces, 255

LAN-specific commands, 255

no keepalives command, 255

no shutdown command, 255

returning to default configurations, 257

saving configurations, 256

verifying configurations, 259-260

WAN-specific commands, 256

SDM

banners, 299-301

domain names, 299-301

global configurations, 298-307

hostnames, 299-301

router interface configuration, 308-310

secret passwords, 299-301

static routers, SDM, 329-330

switches

assigning IP addresses via DHCP, 440-441

assigning management IP addresses to, 439

backing up IOS files via TFTP servers, 270

backing up via TFTP servers, 269-271

defining default gateways, 439

multiple switch interfaces, 441

returning to default configurations, 257

Connection-Oriented Communication sessions, 28

console access, securing to USER EXEC, 248-249

console ports, 210-211

context-sensitive help, 565

copy command, 256, 272, 568

copy running-config flash command, 271

copy tftp flash command, 271

Core layer (hierarchical models), 35-36

counts to infinity, mitigating, 363

CPE (Customer Premise Equipment), 191

CRC (Cyclic Redundancy Checks), 428

cross-over cable, 62, 554

crosstalk, 59, 554

crypto key generate rsa command, 247-248

CSMA/CD (Carrier Sense Multiple Access Collision Detection), 94, 429

CSU/DSU (Channel Service Units/Data Service Units), 191-192, 522

Ctrl+Shift+6 keyboard shortcut, suspending Telnet sessions, 276-277

custom mode (CD-ROM), 611

cut-through method (frame forwarding), 428

D

Data Link layer, 100

bridges, 101-104

Ethernet

addressing, 87-90

framing, 91-92

FDDI protocols, 86-87

switches, 102-105

OSI model, 21-23, 550

Token Ring protocols, 84-85

Data Link WAN encapsulations, 523-525

data packets, Network layer (OSI model) routing, 170

data transmission, wireless networks, 478-479

- DCE (Data Communications Equipment), 23, 190, 557**
- DDoS (Distributed Denial of Service) attacks, 127**
- dead/invalid timers, 367**
- debug command, 268-269, 375**
- debug ppp authentication command, 538, 582**
- debug spanning-tree command, 444**
- decimals**
 - binary-to-decimal conversion, 146-147
 - decimal-to-binary conversion, 148-150, 157-158, 561
 - decimal-to-hexadecimal conversion, 150-151
- default gateways (routing), 320-321**
- default routes, 328, 573**
 - configuring via SDM, 329-330
 - verifying, 330-331
- delays (forward), 438**
- demarcation points, 191**
- description command, assigning descriptions to router interfaces, 255**
- designated ports, STP, 434**
- desktop layer (hierarchical models). *See* Access layer (hierarchical models)**
- Destination Unreachable messages, ICMP, 267**
- device monitoring, SDM, 310**
- DHCP (Dynamic Host Configuration Protocol), 571**
 - IOS
 - ip dhcp excluded-address ip-address command, 279
 - ip dhcp pool poolname command, 278
 - show ip dhcp binding command, 280
 - IP addresses, assigning to switches, 440-441
 - router amnesia, 280
 - SDM, configuring, 305-307
- dial-on-demand connections (WAN), 519**
- discovery protocol, 570**
- distance vector routing loops, preventing, 576**
- distance vector routing protocols, 340-341, 358-359**
- distribution frames, 64**
- Distribution layer (hierarchical models), 35**
- DNS (Domain Name Servers)**
 - SDM, configuring, 304
 - TCP/UDP support, 30
- DoD (Department of Defense) model. *See* TCP/IP model**
- domains**
 - collision domains, segmenting/creating, 100
 - names
 - configuring resolution, 246-247
 - changing in SDM, 299-301
- DoS (Denial of Service) attacks, 559**
 - DDoS attacks, 127
 - wireless networks, 495
- DRAM (Dynamic Random Access Memory), 193. *See also* RAM**
- DS1 (Digital Signal level 1) services, 190**
- DTE (Data Terminal Equipment), 23, 191-192, 557**
- duplexes**
 - interfaces, 572
 - logic, 105-106
 - router assignments, 255
- dynamic NAT (Network Address Translation), 393, 580**
- dynamic routing protocols, 331, 574**
 - distance vector routing protocols, 340-341
 - hybrid protocols, 341
 - interior/exterior gateway routing protocols, 340
 - link-state routing protocols, 341
 - routed protocols versus, 331

E

Edit NAT Configuration window (SDM), 407-410

EGP (Exterior Gateway Protocol), 574

EIA/TIA (Electronic Industries Association/Telecommunications Industry Association), 192

EMI (Electromagnetic Interference), 59

enable password command, 245, 253, 567

enable secret command, 245, 253, 461, 567

encapsulation, 24

encryption

IPsec, 132-133

SSH, 132-133

SSL, 132-133

wireless networks, 496-498, 578

erase startup-config command, 257

ESS (Extended Service Sets), wireless AP, 501

Ethernet, 87, 93

10-Gigabit Ethernet (10GbE), 99

10BASE-FL, 95

10BASE-T, 95

10BASE2, 94

10BASE5, 94

802.3 characteristics, 95

802.3u standards, 97

802.3z standards, 99

addressing, 87-90

Fast Ethernet, 96

framing, 91-92

Gigabit Ethernet

1000BASE-T, 97

1000BASE-X, 98

GBIC, 189

ports, 189

LRE, 100

Metro Ethernet, WAN, 521

switch interfaces. *See* ports

exams (practice)

answers, 602-609

MeasureUp, 612-613

EXEC

IOS access, gaining, 564

ping command, 267

Privileged EXEC, 221-222

debug command, 268-269

passwords, assigning to, 245

ping command, 268

securing, 567

Telnet, virtual terminal access, 277

terminal monitor command, 277-278

sessions. *See* terminal options

Telnet, virtual terminal access, 276-278

User EXEC, 220

auxiliary access, securing, 250

console access, securing, 248-249

securing, 566

securing access to Telnet, 250-253

SSH access, securing, 250-253

virtual terminal access, 277

exec-timeout command, 249, 461

exterior/interior gateway routing protocols, 340

F

Fast Ethernet, 96

FDDI (Fiber Distributed Data Interface) protocol, 86-87

feature sets (IOS), 194

FEXT (Far-End Crosstalk), 59

fiber-optic cable, 63-64, 554

files, IOS naming conventions, 558

filtering MAC addresses, 427

firewalls, 132-133

Flash, 193

copy running-config flash command, 271

copy tftp flash command, 271

show flash command, 264

flash updates (routing), 366
floating static routes, 327, 573
FLSM (Fixed Length Subnet Masks), 334
forward delays, 438
fragment-free method (frame forwarding), 428
fragmentation, MLPPP, 531
frame-forwarding, 426-428, 571
Frame Relays, WAN, 524
full-duplex connections, switches, 429
full-duplex modes, 105

G

gain, 67
gateways
 routing
 default gateways, 320-321
 interior/exterior gateway routing protocols, 340
 switches, defining default gateways, 439
GBIC (Gigabit Interface Converters), 189
Gigabit Ethernet
 10-Gigabit Ethernet (10GbE), 99
 1000BASE-T, 97
 1000BASE-X, 98
 GBIC, 189
 ports, 189

Global Configuration, 222-223

banner motd (message of the day command), 244
 boot sequences, changing, 242-243
 boot system command, 243
 commands list, 566
 config-register command, 242
 crypto key generate rsa command, 247-248
 domain name resolution, configuring, 246-247
 enable password command, 245
 enable secret command, 245

host names, changing, 244
 hostname command, 244
 interface configuration, 223
 ip dhcp excluded-address ip-address command, 279
 ip domain-name command, 247
 ip host command, 246
 ip name-server command, 247
 line configuration, 224
 login banners, creating, 244
 no cdp enable command, 275
 no cdp run command, 275
 Privileged EXEC mode, assigning passwords to, 245
 service password-encryption command, 246
 service timestamp command, 269
 SSH, enabling, 247-248
 SDM, 298
 banners, 299-301
 DHCP, 305-307
 DNS, 304
 domain names, 299-301
 hostnames, 299-301
 router access, 303
 secret passwords, 299-301

global IPv6 addresses, 563

global/local (NAT), 395

H

hacking wireless networks, 495
half-duplex connections, switches, 429
half-duplex modes, 105
hashing passwords, 529
HDLC (High-level Data Link Control), 524-525, 581
help, technical support, 614
hexadecimals, 150-151
hierarchical models, 33

hold-down timers, 366

hostname command, 244

hostnames, changing, 244, 299-301

hosts, calculating in subnets, 562

HSSI (High-Speed Serial Interface), 190

HTTP (Hypertext Transfer Protocol), 212

hubs, 67

hybrid routing protocols, 341

I

IANA (Internet Assigned Numbers Authority), 145, 156, 561

ICMP (Internet Control Messaging Protocol), 32-33, 144

Destination Unreachable messages, 267

ping command, 267

traceroute command, 268

IDF (Intermediate Distribution Frames), 64

IDS (Intrusion Detection Systems), 133

IEEE (Institute of Electrical and Electronic Engineers), 477

IEEE 802.3. *See* Ethernet

IEEE 802.3ab. *See* Gigabit Ethernet

IEEE 802.3u. *See* Fast Ethernet

IEEE 802.3z. *See* Gigabit Ethernet

IFS (Integrated File System), 272

IGP (Interior Gateway Protocol), 340, 574

image files, naming (IOS), 195

incomplete command syntax errors, 566

information queries (reconnaissance attacks), 126

infrared technology, 65

inside global addresses (NAT), 395

inside local addresses (NAT), 395

inside/outside (NAT), 395

installing

CD-ROM, 612-613

SDM, 297

interface configuration (Global Configuration), 223, 568

interface range command, 441

interface status values (show commands), 569

interfaces. *See* networks, interfaces

interior/exterior gateway routing protocols, 340

Internet layer (TCP/IP model), 31-33

internetworks, 10

LAN, 11

layered architecture. *See* OSI (Open Systems Interconnection) model

MAN, 12

SAN, 13

VAN, 14

WAN, 12-13

invalid input syntax errors, 566

invalid/dead timers, 367

IOS (Internetworking Operating System), 193-195

administrative distances, 324

boot process, 564

commands

abbreviations, 226

common syntax errors, 227-229

listing, 224-225

shortcut keys, 226-227

configuration files, creatin static entries, 246-247

context-sensitive help, 565

DHCP

ip dhcp excluded-address ip-address command, 279

ip dhcp pool poolname command, 278

show ip dhcp binding command, 280

editing keystrokes, 565

EXEC access, 564

feature sets, 194

file naming conventions, 558

- Global Configuration. *See also* configure command
 - interface configuration, 223
 - line configuration, 224
 - image files, naming, 195
 - loading, router/switches start-up, 215-218
 - navigation modes, 565
 - network security, 131-133
 - Privileged EXEC, 221-222, 567
 - routers, backing up via TFTP servers, 270
 - show flash command, 264
 - show version command, 264-265
 - SSH, 567
 - syntax errors, 566
 - trains, 194
 - Use EXEC, 220, 566
- IP (Internet Protocol) addresses, 31, 145**
- binary
 - binary-to-decimal conversion, 146-147
 - decimal-to-binary conversion, 148-149, 157-158
 - Boolean AND, 154-155
 - broadcast IP, 152, 157
 - hexadecimals, 150-151
 - IPv4
 - address classes, 151-153
 - private (RFC 1918) addressing, 156
 - subnet masks, 154-157, 163
 - subnetting IP, 156-167
 - management addresses, assigning to switches, 439
 - NAT, 156, 391, 580
 - network ID, 152
 - routers
 - assigning to, 254
 - verifying assignment in, 280
 - SDM, assigning to, 308
 - subnet ID, 152
 - subnets, 562
 - switches, assigning to via DHCP, 440-441
- ip address dhcp command, 440**
- ip default-gateway command, 440**
- ip dhcp excluded-address ip-address command, 279, 571**
- ip dhcp pool poolname command, 278, 571**
- ip domain-name command, 247**
- ip host command, 246**
- ip name-server command, 247**
- ip nat inside command, NAT overload configuration, 399**
- ip nat outside command, NAT overload configuration, 399**
- IPS (Intrusion Prevention Systems), 132-133, 500**
- IPsec (Internet Protocol Security), network security, 132-133**
- IPv4 (Internet Protocol version 4), 560-561. *See also* CIDR**
- address classes, 151-153
 - IPv6 integration, 563
 - private (RFC 1918) addressing, 156
 - subnet masks, 154-157, 163
 - subnetting IP, 156-158
 - calculating hosts, 159-160
 - calculating increments, 162-165
 - calculating networks, 161-162
 - determining range of valid IP, 165-167
 - zero subnet rule, 162
- IPv6 addresses, 562-563**
- ISDN (Integrated Services Digital Network), BRI, 189-190**
- ISO HDLC (High-level Data Link Control), 527, 581**
- ITU-R (International Telecommunication Union-Radiocommunication Sector), 477**

J - K - L

keyboard shortcuts, suspending Telnet sessions, 276-277

keystrokes, IOS editing, 565

LAN (Local Area Networks), 11

interfaces, 188-189

router configuration, 255

WLAN

hacking, 495

Spread Spectrum Wireless LAN, 555

LAPB (X.25 Link Access Procedure, Balanced), WAN Data Link encapsulations, 524

Layer 1, 23. *See also* Physical layer

Layer 2 security, 21-23, 462-464. *See also* Data Link layer

Layer 3, 20. *See also* Network Layer (OSI model)

Layer 3 switches, 167, 170, 563-564

Layer 4, 18-19. *See also* Transport layer

Layer 5, 18. *See also* Session layer

Layer 6, 17. *See also* Presentation layer

Layer 7, 15-16. *See also* Application layer

layered architectures. *See* OSI model

LCP (Link Control Protocol)

HDLC, 581

PPP authentication, 527

callbacks, 529-530

CHAP, 528-529, 533-534

compression, 530

MPPC, 531

MPPP, 531

PAP, 528

Predictor algorithm, 530

Stacker algorithm, 530

leased line connections, WAN, 519, 580

Line Configuration, 224

enable password command, 253

enable secret command, 253

exec-timeout command, 249

logging synchronous command, 249

service password-encryption command, 253

User EXEC, securing

auxiliary access, 250

console access, 248-249

SSH access, 250-253

Telnet access, 250-253

link-local IPv6 addresses, 563

link-state routing protocol, 341

LLC (Logical Link Controls), 22-23

local/global (NAT), 395

logging synchronous command, 249

login banners, creating, 244

longest match rule, 343

loops (routing), 360-362

counts to infinity, 363

invalid/dead timers, 367

route poisoning, 364-366

split horizons, 363-364

triggered updates, 366

lower layers (OSI model), 18

LRE (Long Reach Ethernet), 100

M

MAC (Media Access Control) addresses, 21-22.

See also Ethernet, addressing

CAM tables, 426

definition of, 556

filtering, 427

ports, limiting in, 462

router assignments, 168

static MAC addresses, switch port security, 463

MAC (Media Access Control) filtering, bridges, 104

man-in-the-middle attacks, network security, 124

management IP addresses, assigning to switches, 439

MAN (Metropolitan Area Networks), 12

mapping NAT port numbers, 407

max age timers, 437

maximum hop counts, 576

MDF (Main Distribution Frames), 64

MeasureUp practice tests, 612-613

memory

- components, of, 193
- types of, 557

mesh topologies, 57

Metro Ethernet, WAN, 521

microsegmentation, 106

mitigating network attacks, 130-133, 559

MLPPP (Multilink Point-to-Point Protocol), PPP authentication, 531

modules (routers), 196-197

MPPC (Microsoft Point-to-Point Compression), PPP authentication, 531

multicast addresses, 89

multicast IPv6 addresses, 563

multilayer switches, 170

multimode (MM) fiber-optic cable, 64

N

NAT (Network Address Translation), 156, 579

- development of, 390
- dynamic NAT, 393, 580
- inside global addresses, 395
- inside local addresses, 395
- inside/outside, 395
- IP addresses, 580

- local/global, 395
- NAT overload, 394, 580
 - configuring via SDM, 397-410
 - mapping port numbers, 407
 - show ip nat statistics command, 411
 - show ip nat transition command, 413
 - verifying configurations via SDM, 410-413
- outside global addresses, 396
- outside local addresses, 396
- private IP addresses, 391
- SDM, configuring via, 397
- static NAT, 392, 580
- troubleshooting, 413-414

NAT Configuration window (SDM)

- Advanced NAT wizard, 401-407
- Basic NAT wizard, 397-400

NAT overload, 394, 580

- port numbers, mapping, 407
- SDM, configuring via
 - advanced configuration, 401-407
 - basic configuration, 397-400
 - editing configurations, 407-410
 - verifying configurations, 410-413
 - show ip nat statistics command, 411
 - show ip nat transition command, 413

navigation modes (IOS), 565

NCP (Network Control Protocol), 532, 581

neighbor discovery, CDP, 272-275

network command, DHCP IOS, 279

Network Interface layer (TCP/IP model), 33

Network layer (OSI model), 20, 550

- ARP, 144
- functions of, 144
- ICMP, 144
- IP addresses, 145, 150
 - binary-to-decimal conversion, 146-147
 - Boolean AND, 154-155

- broadcast IP, 152, 157
- decimal-to-binary conversion, 148-149, 157-158
- decimal-to-hexadecimal conversion, 150-151
- IPv4 address classes, 151-153
- IPv4 subnet masks, 154-157, 163
- NAT, 156
- network ID, 152
- private (RFC 1918) addressing, 156
- subnet ID, 152
- subnetting IP, 156-167
- Layer 3 switches, 167, 170
- Proxy ARP, 145
- RARP, 145
- routers, 167-170
- traceroutes, 144

networks

- domains, determining data transport reliability, 554
- ID, 152
- interfaces, 67
- security, 122
 - access attacks, 123-124, 559
 - DoS attacks, 127-129, 559
 - mitigating attacks, 130-133, 559
 - reconnaissance attacks, 125-126, 559
- subnets, calculating in, 562
- topologies
 - bus topologies, 54
 - mesh topologies, 57
 - ring topologies, 55-56
 - star topologies, 56-57
 - wireless networks, 501-503
- wireless networks, 476
 - 802.11a, 483
 - 802.11b, 483
 - 802.11g, 483-484
 - 802.11n, 484
 - channel surfing, 481

- data transmission, 478-479
- IEEE, 477
- ITU-R, 477
- overlapping signals, 480-481
- RF bands, 479-480
- topologies, 501-503
- Wi-Fi Alliance, 477

NEXT (Near-End Crosstalk), 59**nibbles, 151****no cdp enable command, 275, 465****no cdp run command, 275, 465****no command, 242****no debug all command, 269****no exec command, catalyst switch security, 461****no ip directed-broadcast command, 129-130****no keepalives command, 255****no shutdown command, 255, 271, 462****NTP (Network Time Protocol), network security, 132-133****NVRAM (Nonvolatile Random Access Memory), 193****O****OSI (Open Systems Interconnection) model, 14-15, 550-551**

- Application layer, 15-16
- compared to TCP/IP models, 26
- Data Link layer, 21, 23
- layered communications, 23-24
- list of layers, 24-25
- lower layers, 18
- Network layer, 20
- Physical layer, 23
- Presentation layer, 17
- Session layer, 18, 550
- Transport layer, 18-19
- upper layers, 15

outside global addresses (NAT), 396

outside local addresses (NAT), 396
outside/inside (NAT), 395
overlapping signals (wireless networks),
480-481

P

packet sniffers, 125
packet-switched networks, 520, 581
PAP (Password Authentication Protocol), 528,
581
PAR (Positive Acknowledgement and
Retransmission), 27
passive RIP interfaces, 371
password recovery (router/switch start-ups), 218
passwords
 attacks, network security, 123
 aux ports, 459-460
 enable password command, 245, 253
 enable secret command, 253
 hashing, 529
 Privileged EXEC mode, assigning to, 245
 recovery (router/switch start-ups), 218
 secret passwords, changing in SDM,
 299-301
 service password-encryption command,
 246, 253
 switch security, 459-460
PAT (Port Address Translation). *See* NAT over-
load
PDU (Protocol Data Units), 24
permanent virtual circuits, 520
Physical layer
 hubs, 67
 network interfaces, 67
 OSI Model, 23, 551
 repeaters, 66
 WAN, 522-523
physical security, switches, 458

ping command, 267, 558
 sweeps, 125
 switches, troubleshooting basic connectivi-
 ty, 443
pinouts, 61
PoE (Power over Ethernet), 198
poison reverse, 365
ports, 439
 auxiliary ports, 212
 password configuration, 459-460
 User EXEC access, securing, 250
 blocked ports, 431, 435
 console ports, 210-211
 designated ports, 434
 Gigabit Ethernet ports, 189
 Layer 2 security, 462-464
 MAC addresses, limiting in, 462
 NAT port numbers, mapping, 407
 redirection, network security, 124
 root ports, 432-433
 scans, 126
 security, 572
 states, transitioning, 437-438
POST (Power-On Self-Tests), 214
PPP (Point-to-Point Protocol), 525
 CHAP, 581-582
 configuring
 authentication, 532-534
 compression, 534-535
 ISO HDLC, 527
 LCP, 527-534
 NCP, 532
 PAP, 581
 troubleshooting, 537-538
 verifying, 535-536
 WAN, 581
 Data Link encapsulations, 524
 troubleshooting authentication in, 582

PPPoA (PPP over ATM), WAN, 525

PPPoE (PPP over Ethernet), WAN, 525

practice exams

answers, 602-609

MeasureUp, 612-613

questions, 585, 594, 598

Predictor algorithm, PPP authentication, 530

Presentation layer (OSI model), 17, 550

private addresses

IANA, 561

IP, NAT, 391

RFC 1918, 156

Privileged EXEC, 221-222. *See also* configure command; User EXEC

debug command, 268-269

passwords, assigning to, 245

ping command, 268

securing, 567

Telnet, virtual terminal access, 277

terminal monitor command, 277-278

Proxy ARP (Address Resolution Protocol), 33, 145

Q - R

queries (information), reconnaissance attacks, 126

question mark (?), context-sensitive help, 565

RAM (Random Access Memory), 193

RARP (Reverse Address Resolution Protocol), 33, 145

rebooting via reload command, 271

reconnaissance attacks, 559

information queries, 126

packet sniffers, 125

ping sweeps, 125

port scans, 126

redistribution (routing protocols), 343-344, 575

reload command, 271

repeaters, 66

RF bands, wireless networks, 479-480

RFC 1918 (private) addressing, 156

ring topologies, 55-56

RIP (Routing Information Protocol), 377

characteristics of, 367

configuring, 368-370, 373, 577

passive interfaces, 371

RIPv2 comparisons, 379, 576

troubleshooting, 375-376, 577

verifying, 374, 577

RIPv2 (Routing Information Protocol version 2)

characteristics of, 371

configuring, 372

RIP comparisons, 379, 576

rolled cable, 63

ROM (Read-Only Memory), 193

ROMmon, router/switches start-up, 215

root bridges, 431-433

root ports, STP, 432-433

routers, 196-197

amnesia via DHCP, 280

boot sequences, changing, 242-243

configuration

backing up via TFTP servers, 269-271

verifying, 259-260

interface configuration

assigning duplexes, 255

assigning IP addresses, 254

assigning speed to, 255

bandwidth command, 256

clock rate command, 256

LAN-specific commands, 255

no keepalives command, 255

no shutdown command, 255

returning to default configurations, 257

- saving, 256
- WAN-specific commands, 256
- interface status/statistics, viewing
 - show controller command, 263
 - show interfaces command, 261-262
 - show ip interface brief command, 263
- IOS files, backing up via TFTP servers, 270
- IP addresses, verifying assignment of, 280
- Layer 3 functions, 563-564
- Network layer (OSI model), 167-170
- SDM, 296
 - access configuration, 303, 308-310
 - device monitoring, 310
 - global configurations, 298-307
 - installing, 297
- show processes command, 269
- smurf attacks, 129
- start-up procedures
 - bootstrap, 215
 - configuration loading, 217
 - IOS loading, 215-218
 - password recovery, 218
 - POST, 214
 - practice challenge, 219-220
 - ROMmon, 215
 - setup mode, 217
- routing**
 - administrative distances, 324
 - Classful Routing, 575
 - classful routing protocols, 333-340, 575
 - default gateways, 320-321
 - default routes, 328-331, 573
 - dynamic routing protocols, 331, 574
 - metrics of, 332-333, 574
 - poisoning, mitigating, 364-366
 - redistributing, 343-344
 - RIP, 377
 - characteristics of, 367
 - configuring, 368-370
 - configuring via SDM, 373
 - passive interfaces, 371
 - RIPv2 comparisons, 379
 - troubleshooting, 375-376
 - verifying, 374
 - RIPv2
 - characteristics of, 371
 - configuring, 372
 - RIP comparisons, 379
 - routing sources, 323-324
 - sources, 572-573
 - static routes, 325, 573
 - configuring, 326, 329-330
 - floating static routes, 327
 - verifying, 330-331
 - summarization, VLSM, 338-340
 - update packets, Network layer (OSI model) routing, 170
- routing by rumor, 358**
- routing loops, 360-362**
 - counts to infinity, 363
 - invalid/dead timers, 367
 - route poisoning, 364-366
 - split horizons, 363-364
 - triggered updates, 366
- routing protocols, 573**
 - classes of, 575
 - distance vector routing loops, preventing, 576
 - distance vector routing protocols, 358-359
 - dynamic routing protocols
 - hybrid protocols, 341
 - interior/exterior gateway routing protocols, 340
 - link-state routing protocols, 341
 - routed protocols versus, 331
 - interior/exterior gateway protocols, 574
 - maximum hop counts, 576
 - redistribution, 575
- routing tables, 342-343**

S

SAN (Storage Area Networks), 13

SDM (Security Device Manager), 296

- default routes, configuring, 329-330
- device monitoring, 310
- Edit NAT Configuration window, 407-410
- global configurations, 298
 - banners, 299-301
 - DHCP, 305-307
 - DNS, 304
 - domain names, 299-301
 - hostnames, 299-301
 - router access, 303
 - secret passwords, 299-301
- installing, 297
- NAT Configuration window
 - Advanced NAT wizard, 401-407
 - Basic NAT wizard, 397-400
- NAT overload configuration
 - advanced configuration, 401-407
 - basic configuration, 397-400
 - editing configurations, 407-410
 - verifying configurations, 410-413
- RIP, configuring, 373
- router interface configuration
 - enabling interfaces, 309
 - IP address assignments, 308
 - saving configuration, 310
 - verifying configurations, 310
- static routes, configuring, 329-330
- secret passwords, changing in SDM, 299-301**
- security (networks), 122**
 - access attacks
 - man-in-the-middle attacks, 124
 - password attacks, 123
 - port redirection, 124
 - trust exploitation, 124

DoS attacks

- DDoS attacks, 127
 - smurf attacks, 129
 - TCP SYN attacks, 128-129
- ### mitigating attacks
- AAA, 130, 133
 - ACL, 130, 133
 - encryption, 132-133
 - firewalls, 132-133
 - IDS, 133
 - IPS, 132-133
 - IPsec, 132-133
 - NTP, 132-133
 - SNMP, 131, 133
 - SSH, 131-133
 - SSL, 132-133
 - syslog, 131-133
- ### reconnaissance attacks
- information queries, 126
 - packet sniffers, 125
 - ping sweeps, 125
 - port scans, 126
- service password-encryption command, 246, 253, 461, 567**
 - service timestamp command, 269**
 - Session layer (OSI model), 18, 550**
 - setup mode (router/switch start-ups), 217**
 - shortcuts (keyboard), suspending Telnet sessions, 276-277**
 - shortcuts (MeasureUp practice tests), creating, 613**
 - show cdp neighbors command, 273**
 - show commands, 258**
 - general commands list, 569
 - IFS, 272
 - interface status values, 569
 - list of, 266
 - router configurations, verifying, 259-260

- show compress command, verifying PPP compression, 536**
- show controller command, viewing router interface status/statistics, 263**
- show controllers serial command, 275**
- show dhcp bindings command, 571**
- show dhcp lease command, 280, 441**
- show flash command, 264**
- show interface <interface> command, verifying PPP operation, 535-536**
- show interfaces command, viewing router interface status/statistics, 261-263**
- show interfaces interface-id command, 444**
- show ip dhcp binding command, 280**
- show ip interface brief command, viewing router interface status/statistics, 263**
- show ip nat statistics command verifying NAT overload configurations, 411**
- show ip nat transition command verifying NAT overload configurations, 413**
- show port-security address command, 464**
- show port-security interface command, 463**
- show processes command, 269**
- show running-config command, 259-260, 271, 280, 413**
- show sessions command, Telnet sessions, 276**
- show spanning-tree command, 442**
- show startup-config command, 259**
- show version command, 195, 264-265**
- single-mode (SM) fiber-optic cable, 64**
- site-local IPv6 addresses, 563**
- SLIP (Serial Line Internet Protocol), WAN Data Link encapsulations, 523**
- smurf attacks, 129**
- SNAP (Subnetwork Access Protocol), 93**
- SNMP (Simple Network Management Protocol), network security, 131-133**
- sources (routing tables), 323-324**
- speed, router assignments, 255**
- split horizons, mitigating, 363-364**
- Spread Spectrum Wireless LAN, 555**
- SSH (Secure Shell), 567**
 - catalyst switch security, 460
 - enabling, 247-248
 - EXEC sessions, 213
 - network security, 131-133
 - User EXEC access, securing, 250-253
- SSL (Secure Socket Layer), network security, 132-133**
- Stacker algorithm, PPP authentication, 530**
- star topologies, 56-57**
- startup processes. See boot processes**
- static MAC addresses, switch port security, 463**
- static NAT (Network Address Translation), 392, 580**
- static routes, 325, 573**
 - configuring, 326, 329-330
 - floating static routes, 327
 - verifying, 330-331
- store-and-forward method (frame forwarding), 428**
- STP (Spanning Tree Protocol)**
 - blocked ports, 435
 - designated ports, 434
 - port states, transitioning, 437-438
 - root bridges, 430-433
 - root ports, 432-433
 - show spanning-tree command, 442
 - troubleshooting, 444
 - verifying, 442
- STP cable, 60-61. See also twisted-pair cable**
- straight-through cable, 61-62, 554**
- stub networks, 325**
- study mode (CD-ROM), 611**
- subnet ID, 152**

subnet masks, 163

- CIDR notation, 155
- FLSM, 334
- IPv4, 154-155, 157
- VLSM, 335-340

subnets, 562**subnetting IP (Internet Protocol), 156-158**

- calculating
 - hosts, 159-160
 - increments, 162-165
 - networks, 161-162
- range of valid IP, determining, 165-167
- zero subnet rule, 162

switches, 104-105, 197-198

- basic connectivity, troubleshooting, 442-444
- blocked ports, 435
- boot sequence, changing, 242-243
- catalyst switches, 572
 - securing physical access to, 458
 - securing terminal access to, 459-461
- configuration
 - backing up via TFTP servers, 269-271
 - commands, 568
 - returning to default configurations, 257
- default gateways, defining, 439
- designated ports, 434
- diameters, 438
- filtering, 427
- frame forwarding, 426-428, 571
- full-duplex connections, 429
- half-duplex connections, 429
- interface range command, 441
- IOS files, backing up via TFTP servers, 270
- IP addresses, assigning via DHCP, 440-441
- ip default-gateway command, 440
- Layer 2 security, 462-465

- Layer 3 switches, 167, 170
- management IP addresses, assigning, 439
- microsegmentation, 106
- multilayer switches, 170
- multiple switch interfaces, configuring, 441
- physical security, 458
- ports, 439, 462
- primary tasks, 102
- redundant design, 430
- show dhcp lease command, 441
- show interfaces interface-id command, 444
- start-up procedures
 - bootstrap, 215
 - configuration loading, 217
 - IOS loading, 215-218
 - password recovery, 218
 - POST, 214
 - practice challenge, 219-220
 - ROMmon, 215
 - setup mode, 217
- STP, 430-433

switchport port security mac-address sticky command, 463**switchport port-security command, 462****switchport port-security mac-address command, 572****switchport port-security maximum command, 463****switchport port-security violation shutdown command, 463****SYN packet, 28****SYN-ACK packet, 28****synchronous serial interfaces, 190****syntax errors, 566****syslog, network security, 131-133****system requirements, CD-ROM installations, 612**

T

T1 controller cards, 190

TCP (Transmission Control Protocol), 27-29

- applications that utilize, 553
- processes of, 552-553
- segment header formats, 553
- SYN attacks, 128-129

TCP/IP (Transmission Control Protocol/Internet Protocol) layer, 552

TCP/IP (Transmission Control Protocol/Internet Protocol) model

- Application layer, 26-27
- compared to OSI models, 26
- Internet layer, 31-33
- Network Interface layer, 33
- Transport layer, 27-30

technical support, 614

Telnet, 212, 570

- catalyst switch security, 460
- multiple session example, 277
- resuming sessions, 277
- showing sessions, 276
- suspending sessions, 276-277
- terminal monitor command, 277-278
- User EXEC access, securing, 250-253
- virtual terminal access, 276-278

terminal monitor command, 277-278

terminal options

- auxiliary ports, 212
- console ports, 210-211
- HTTP, 212
- SSH, 213

test modes (CD-ROM), 611

tests (practice)

- answers, 602-609
- MeasureUp, 612-613

TFTP servers

- routers
 - configuration backups, 269-271
 - IOS file backups, 270
- switches
 - configuration backups, 269-271
 - IOS file backups, 270

three-way handshakes, 28

throughput, definition of, 12

timers (max age), 437

timestamps, 269

Token Ring protocols, 84-85

topologies

- bus topologies, 54
- mesh topologies, 57
- ring topologies, 55-56
- star topologies, 56-57
- wireless networks, 501-503

traceroute command, 268

- RIP, 375
- switches, troubleshooting basic connectivity, 443

traceroutes, 144, 558

trains (IOS), 194

transmitting data, wireless networks, 478-479

Transport layer

- OSI model, 18-19, 550
- TCP/IP model, 27-30

triggered updates (routing), 366

troubleshooting

- debug command, 268-269
- NAT, 413-414
- ping command, 267
- PPP, 537-538
- RIP, 375-376, 577
- show processes command, 269
- STP, 444
- switches, basic connectivity, 442-444

- traceroute command, 268
- WAN, PPP authentication, 582
- wireless networks, 506-507

trust exploitation, network security, 124

twisted-pair cable, 60-63

U

UDP (User Datagram Protocol), 29-30

- applications that utilize, 553
- headers, 553

undebg all command, 269

unicast addresses, definition of, 88

unique IPv6 addresses, 563

unshielded twister pair cables versus fiber-optic cable, 554

upper layers (OSI model), 15

User EXEC, 220. *See also* Privileged EXEC

- auxiliary access, securing, 250
- console access, securing, 248-249
- securing, 566
- SSH access, securing, 250-253
- Telnet
 - securing access to, 250-253
 - virtual terminal access, 277

UTP cable. *See also* twisted-pair cable

V

VAN (Virtual Area Networks), 14

verifying

- NAT overload configurations via SDM, 410-413
- port security, switch ports, 463-464
- PPP operation
 - show compress command, 536
 - show interface <interface> command, 535-536
- RIP, 374, 577
- router configurations, 259-260

- SDM router interface configurations, 310
- STP, 442

virtual circuits (permanent), 520

virtual terminal access, Telnet, 276-278

VLAN workgroups, 34

VLSM (Variable-Length Subnet Masks), 335-340

VPN (Virtual Private Networks), WAN, 521

W

WAN (Wide Area Networks), 12-13

- baseband connections, 520
- broadband connections, 520
- circuit-switched networks, 519
- circuit-switched WAN, 580
- Data Link encapsulations, 523-525
- dial-on-demand connections, 519
- HDLC, 581
- interfaces
 - asynchronous serial interfaces, 190
 - BRI, 189-190
 - DCE, 190
 - definition of, 557
 - DTE, 191-192
 - HSSI, 190
 - synchronous serial interfaces, 190
 - T1 controller cards, 190
- leased line connections, 519
- leased line WAN, 580
- Metro Ethernet connections, 521
- packet-switched networks, 520
- packet-switched WAN, 581
- Physical layer, 522-523
- PPP, 581-582
- routers, 169, 256
- VPN, 521

war driving, 494

WEP (Wired Equivalent Privacy), wireless networks, 496-497

Wi-Fi Alliance, 477

windowing, 28

wireless networks, 476, 577

802.11a, 483

802.11b, 483

802.11g, 483-484

802.11n, 484

802.1x (wireless authentication), 499-500

ad hoc networks, 501

AP

BSS, 501

ESS, 501

troubleshooting, 507

authentication, 578

channel surfing, 481

data rates, 503-505

data transmission, 478-479

encryption, 578

WEP, 496-497

WPA, 498

WPA2, 498

hacking, 495

IEEE, 477

implementing, 501, 506, 579

IPS, 500

ITU-R, 477

overlapping signals, 480-481

RF bands, 479-480

threats to

direct hacking, 495

employee ignorance, 495-496

war driving, 494

topologies, 501-503

troubleshooting, 506-507

Wi-Fi Alliance, 477

workgroup hubs, definition of, 67

workgroup layer (hierarchical models). See

Distribution layer (hierarchical models)

workgroups, VLAN, 34

WPA (Wi-Fi Protected Access), wireless networks, 498

WPA2 (Wi-Fi Protected Access version 2), wireless networks, 498

X - Y - Z

X.25 link access procedure, balanced. See LAPB
(X.25 Link Access Procedure, Balanced)

zero subnet rule, 162