

## Numerics

---

- 1-out-of-N sampling, 115**
- 64-bit high-capacity counters, 240**

## A

---

- AAA, accounting, 405. See also RADIUS**
- accounting. See also accounting management;**
  - accounting MIBs**
    - AAA, 405
    - application monitoring and profiling scenario, 26–30
    - billing scenarios, 43–45, 47–49
      - connection-based, 55*
      - content-based, 55*
      - destination-sensitive, 50–51*
      - QoS billing, 53–54*
      - source-sensitive, 52–53*
      - VoIP billing, 55–57*
      - volume-based, 49–50*
    - capacity planning scenario, 31
      - link capacity planning, 31–32*
      - network-wide capacity planning, 32–34*
    - NetFlow, customer applications, 320–321
    - network monitoring scenario, 22–24
    - peering agreements, 37–43
  - RADIUS**
    - Acct-Session-Id field, 423–424*
    - VSAs, 419–422*
  - security analysis, 57–61
  - time stamps, 602
  - traffic engineering scenario, 34–37
  - types of, 405
  - user monitoring and profiling scenario, 24–25
  - versus billing, 599
  - voice services, 573
    - standards and technologies, 573–576*
    - with CDRs, 575*
- accounting management, 181–182**
  - defining, 11–13
  - TMN/FCAPS model, 176
  - versus performance management, 17–20
- accounting MIBs, 239, 247**
  - CISCO-FRAME-RELAY-MIB, 247–249
  - for IPv6, 251–252
  - for multicast
    - IF-MIB, 253*
    - RMON-MIB, 253*
  - for telephony, 257–258
    - CISCO-CALL-HISTORY-MIB, 261–262*
    - CISCO-VOICE-COMMON-DIAL-CONTROL-MIB, 261*
    - CISCO-VOICE-DIAL-CONTROL-MIB, 260–261*
    - Dial Control Management MIB, 259*
    - SIP MIB, 262–265*
  - for VLANs, 253–255
  - MPLS LSR MIB, 249–250
  - MPLS Traffic Engineering MIB, 250
  - traffic management and control
    - CISCO-CAR-MIB, 255*
    - CISCO-CLASS-BASED-QOS-MIB, 256–257*
- Acct-Delay-Time AVP, 414**
- Acct-Session-Id field, RADIUS accounting, 423**
  - versus VSAs, 424
- accuracy of measured metrics (Cisco IP SLA), 455**
- active monitoring, 120–128**
- active voice performance measurement, 565**
- aggregation, 87**
- aggregators, 344**
- aging mechanism for NetFlow flows**
  - on Catalyst switches, 328–329
  - on Cisco IOS routers, 327–328
- APM (Application Performance Measurement) MIB, 289–291**
- application monitoring, 534–536**
- application traffic classification**
  - Citrix ICA traffic, 437
  - NBAR classification, 435–436
  - subport classification, 436–437
- application metrics, linking, 456**
- application-wide SMI data types, 195**
- applying performance management and accounting techniques, 74–80**
- Arbor's Peakflow SP anomaly-detection system, 585**

**ART (Application Response Time) MIB, 289–291**  
**ASN.1 (Abstract Syntax Notation 1), 228**  
**ATM operation (Cisco IP SLA), 475–476**  
**attacks**  
 DoS, 580  
 postmortem, performing, 594–596  
 source of, tracing, 591–592  
**attributes of RADIUS, 409–414**  
 VSAs, 418–422  
**authentication, RADIUS, 408**  
**authNoPriv SNMP example configuration, 233–235**  
**authorization, RADIUS, 408**  
**authPriv SNMP example configuration, 235**  
**average triggers (Cisco IP SLA), 497**  
**AVPs (attribute/value pairs), 409, 411–414**  
 Acct-Delay-Time, 414

## B

**backup options for SCTP, 341**  
**bandwidth, capacity planning. *See* capacity planning**  
**baselining, 68–70, 583**  
**basic NBAR configuration example, 445–446**  
**Bell, Alexander Graham, 559**  
**BER (Basic Encoding Rule), 228**  
**best-effort traffic class, 119**  
**BGP AS Path, classifying, 91–93**  
**BGP next-hop key-field, 362–363**  
**BGP passive peer feature (NetFlow), collecting core traffic matrix, 554–555**  
**BGP Policy Accounting, collecting core traffic matrix, 555**  
**billing**  
 destination-sensitive, 606  
 enterprise departmental charge back, 608  
 flat rate, 609  
 for peer-to-peer traffic, 557  
 network blueprint, 600  
 service-based, 607–608  
 time- and distance-based, 606  
 time-based, 602  
*dial-in*, 603  
*pWLANs*, 602  
 versus accounting, 599

volume-based, 603  
*peering agreements*, 604–606  
*residential broadband access*, 603–604  
*transit agreements*, 604–606  
**billing agreements, 604, 606**  
**black holes, 593**  
**blocking security attacks, 59–60**  
**BML (Business Management Layer), 178**  
**business traffic class, 119**  
**B-RAS (broadband remote access server), 404**

## C

**cable access, volume-based billing, 603**  
**cache (NetFlow), 325**  
 flow record expiry, 327  
 parameters, 325  
**calculating**  
 core traffic matrix, 556  
 ICPIF, 563  
**call legs, 416–418**  
**call stateful proxy servers, 263**  
**capacity planning**  
 core traffic matrix  
*collecting*, 551–555  
*generating*, 548–550  
 for enterprises, 544–545  
 for ISPs, 544–545  
 link capacity planning, 541–543  
 network blueprint, 543  
 tools, 546  
**CAR (CDR Analysis and Reporting), 569**  
**CAR (committed access rate), 255, 593**  
**Cariden MATE capacity planning tool, 546**  
**case studies. *See* scenarios**  
**Catalyst switches, NetFlow**  
 example configuration, 348–349  
 NetFlow version 7, 330–331  
**CCM (Cisco CallManager)**  
 CDRs, voice service accounting, 575  
 Serviceability, utilities, 568–569  
 voice performance, measuring, 565, 568  
**CDRs (call detail records), 404, 565**  
 fields, 566  
 voice service accounting, 575  
**child population, 106**

**Cisco Catalyst switches**

- RMON groups, configuring, 279–280
- Statistics and History group, configuring, 282

**Cisco CNS NetFlow Collection Engine, 344–345****Cisco IOS Netflow. See NetFlow****Cisco IOS Software**

- Cisco IP SLA support, 501–502
- DSMON MIB support, 286
- IP Accounting
  - Layer 3, supported IOS versions, 299*
  - MAC address support, 309*
- NBAR support, 438–439
- NetFlow. *See* NetFlow
- RMON support, 277–278
- SMON MIB support, 288
- SNMP support, 229

**Cisco IP SLA, 127**

- ATM operation, 475–476
- CLI operations, 480–482
- CPU utilization, effect on accuracy, 504–506
- deploying, 507
- DHCP operation, 471
- distribution of statistics feature, 492–494
- DLSw+ operation, 479
- DNS operation, 471–472
- Enhanced Object Tracking, 499–501
- error statistics, 464
- features, 451
- Frame Relay operation, 473–475
- FTP operation, 470
- history collection feature, 494–495
- HTTP operation, 472
- ICMP operations, 464
  - ICMP Echo operation, 465*
  - ICMP Path Echo operation, 465–466*
  - ICMP Path Jitter operation, 467*
- IP SLA Responder, 459–462
  - time-stamping, 461*
- measured metrics, 453
  - accuracy of, 455*
  - DHCP response time, 456*
  - DNS response time, 456*
  - HTTP response time, 456*
  - jitter, 454*
  - network delay, 454*
- metrics
  - frequency parameter, 457*

- interpacket interval parameter, 458*
- lifetime parameter, 459*
- measuring, 457*
- number of packets parameter, 458*
- packet size parameter, 458*
- start time parameter, 459*
- timeout parameter, 458*

**MPLS VPN awareness, 459**

- network connectivity monitoring, 530–531, 534
- non-IP SLA responder-based operations, 463
- operational statistics, 464
- operations, 453

- configuring with CISCO-RTTMON-MIB, 482–483*

- multiple operations, scheduling, 490–491*

- random operations, scheduling, 491*

- scheduling, 488–489*

- summary table, 511–513*

- verifying router support for, 483–486*

- performance impact on devices, 503–504

- placement of, 508, 511

- responder-based operations, 463

- RTP-based VoIP operation, 477–479

- security considerations, 506–507

- supported devices and IOS versions, 501–502

- TCP Connect operation, 470

- threshold monitoring, 495–499

- threshold violation triggers, 497–498

- UDP operations

- UDP Echo operation, 468*

- UDP Jitter operation, 468–469*

- VoIP UDP Jitter operation, 469–470*

- VoIP Call Setup Monitoring operation, 477

- VoIP Gatekeeper Registration Delay

- Monitoring operation, 476*

- VoIP operations, example, 486–488

**Cisco Network Planning Solution, 547****Cisco routers**

- NetFlow version 8, 332–333

- non-TOS aggregation schemes, 334–335*

- TOS aggregation schemes, 334–336*

- RMON support, 279

**CISCO-CALL-HISTORY-MIB, 261–262****CISCO-CAR-MIB, 255****CISCO-CLASS-BASED-QOS-MIB, 256–257****CISCO-DATA-COLLECTION-MIB, 244–246****CISCO-ENVMON-MIB, 244**

- CISCO-HEALTH-MONITOR-MIB, 244**
- CISCO-IF-EXTENSION-MIB, 241**
- CISCO-MEMORY-POOL-MIB, 244**
- CISCO-NETFLOW-MIB MIB**
  - NetFlow SNMP operations, 346
- ciscoPingCompleted trap, 242**
- CISCO-PING-MIB, 241**
  - read-only objects, 242
  - read-write objects, 241
- CISCO-PROCESS-MIB, 242**
  - objects, 242–244
- CISCO-RTTMON-MIB, configuring Cisco IP SLA operations, 482–483**
- CISCO-VOICE-COMMON-DIAL-CONTROL-MIB, 261**
- CISCO-VOICE-DIAL-CONTROL-MIB, 260–261**
- CiscoWorks Unified Operations Manager, measuring voice performance, 572**
- Citrix ICA traffic classification (NBAR), 437**
- classification phase of six-stage security operations model, 587–590**
- classifying application traffic**
  - NBAR, 435–436
  - subport classification, 436–437
- clear counters command, 309**
- clear ip accounting command, 300–302, 305–307**
- CLI operations**
  - Cisco IP SLA, 480–482
  - Flexible NetFlow, 377–379
- CMIP (Common Management Information Protocol), 218–219**
- CMISE (Common Management Information Service Element), 218**
- CMRs (call management records), 565**
  - fields, 567–568
- collecting**
  - core traffic matrix
    - pull model*, 555
    - push model*, 551–555
  - NetFlow records, 585
- collection monitoring**
  - IP Accounting ACL, 306–308
  - IP Accounting (Layer 3), 302–303
  - IP Accounting MAC Address, 311–312
  - IP Accounting Precedence, 315–317
- collection servers**
  - placement, 154–56
  - real-time requirements, 156–157
- columnar objects, 228**
- command accounting, 406**
- commands**
  - Cisco IP SLA, enabling, 481–482
  - clear counters, 309
  - clear ip accounting, 300–302, 305–307
    - for IP Accounting (Layer 3), 299–300
    - for IP Accounting ACL, 304–305
    - for IP Accounting MAC Address, 309
    - for IP Accounting Precedence, 314
    - for NBAR configuration, 443
    - for NetFlow configuration, 345–346
    - for RADIUS, 415–416
    - for VoIP accounting with RADIUS, 425–428
  - ip nbar custom, 443
  - show commands, NBAR-related, 443–445
  - show ip accounting, 300, 305
  - show ip accounting access violations, 307
  - show ip accounting output-packets, 307
  - show ip cache flow, 325, 589
  - show ip cache verbose flow, 326
  - show ip nbar, 444
  - show ip sla application, 483–486
  - show rmon stats, 284
  - show snmp, 231
  - show snmp group, 233
  - show snmp view, 234
- community string indexing, 254**
- comparing**
  - active and passive monitoring, 103
  - data collection MIBs, 517–521
  - features of IP Accounting, 317
  - MIB functional areas, 238–239
  - Netflow information elements on different export protocol versions, 338–339
  - network monitoring applications, 292–293
  - original NetFlow and Flexible NetFlow, 375–377
  - RADIUS accounting, Acct-Session-Id field versus VSAs, 424
  - RADIUS and Diameter characteristics, 429–430
  - RADIUS and TACACS+, 406–407
- configuration management, 181**

**configuring**

- Cisco Catalyst switches
  - RMON groups*, 279–280
  - Statistics and History group*, 282
- Cisco IP SLA operations, CISCO-RTTMON-MIB, 482–483
- IP Accounting (Layer 3), 302
- IP Accounting ACL, 305–306
- IP Accounting MAC Address, 311
- IP Accounting Precedence, 315
- MPLS-Aware NetFlow, 360–362
- multicast egress accounting, example configuration, 363
- multicast ingress accounting, example configuration, 363–365
- NBAR
  - basic NBAR configuration example*, 445–446
  - related commands*, 443
- NetFlow
  - commands*, 345–346
  - on Catalyst switch, example configuration*, 348–349
  - version 5, example configuration*, 347
  - version 8, example configuration*, 350
  - version 9, example configuration*, 350–351
- NetFlow Input Filters, example configuration, 359–360
- NetFlow Top Talkers, example configuration, 368–370
- Sampled NetFlow, example configuration, 354–356
- SNMPv2c, 230
- SNMPv3, 231–233
  - with user authentication*, 235
  - without user authentication*, 233–235

**connection accounting, 405****connection-oriented flows, 325****connectivity, performance monitoring MIBs, 530–531, 534****consecutive triggers (Cisco IP SLA), 497****continuous thresholds, 71****core traffic matrix**

- classifying, 98–99
- collecting
  - with pull model*, 555
  - with push model*, 551–555

- estimating, 556
- generating, 548
  - external versus internal core traffic matrix*, 549–550
  - granularity, defining*, 548

**counters, 64-bit high-capacity counters, 240****CPU utilization of Cisco IP SLA, effect on accuracy, 504–506****creating**

- conceptual rows, 281
- MIB objects, 265–268

**custom NBAR application example, 446–447****D****data collection. See also data collection protocols**

- categories of data, 94
- event-based model, 145–146
- export protocols
  - FTP*, 150–151
  - NetFlow*, 149–150
  - SNMP*, 148–149
- MIBs, comparing, 517–521
- NBAR summary, 449
- push versus pull model, 144–145
- required data, 93

**data collection protocols**

- CMIP, 218–219
- CMISE, 218
- Diameter, 216–217
- IPDR, 218
- IPFIX, 208
  - charter objectives*, 211
  - export protocol*, 209–210
  - RFCs*, 211
- metering methods, 102
  - active monitoring*, 103, 120–128
  - passive monitoring*, 104–120
- NetFlow, 201
  - export protocol*, 204
  - FlowSets*, 204–205
  - NetFlow version 9 export protocol*, 202
  - template management*, 205–206
  - template mechanism*, 203

network design considerations, 151–152  
 PSAMP  
     *protocol specifications, 212–213*  
     *RFCs, 213–214*  
 RADIUS, 214–215  
     *RFCs, 215*  
 TACACS+, 216  
**Data FlowSets, 204**  
**data groups, 246**  
**data integrity, ensuring, 168–169**  
**data models, 190**  
**DATA-COLLECTION-MIB, 529**  
**de facto standards, 174**  
**defining granularity of core traffic matrix, 548**  
**delay metric, 454**  
**deleting conceptual rows, 281**  
**deploying**  
     Cisco IP SLA, 507  
     NetFlow, 385–386  
**destination-sensitive billing, 606**  
**deterministic sampling, 108–114**  
**deviation from normal, 73**  
**device-level architecture (NetFlow), 342**  
**devices**  
     availability, testing, 121  
     NBAR-supported, 438–439  
     network elements, performance monitoring,  
         63–64  
     performance monitoring, 526  
         *MIBs, 527–530*  
     RMON-supported, 277–278  
     servers, performance monitoring, 64–65  
**DHCP operation (Cisco IP SLA), 471**  
**DHCP response time, 456**  
**Dial Control Management MIB, 259**  
**dial-in services, time-based billing, 603**  
**Diameter, 216, 407, 428**  
     base protocol structure, 428  
     intermediary agents, 428  
     RFCs, 217  
**discrete thresholds, 71**  
**displaying**  
     NetFlow cache entries, 325  
     SNMPv2c statistics, 231  
**distribution of statistics feature (Cisco IP SLA),  
 492–494**  
**DLSw+ operation (Cisco IP SLA), 479**

**DNBAR (Distributed NBAR), 435**  
**DNS operation (Cisco IP SLA), 471–472**  
**DNS response time, 456**  
**DoS attacks, 169, 580**  
**DSCP data, classifying, 89–91**  
**DSMON MIB, 284**  
     MIB object groups, 286  
     principles, 286  
     supported devices and IOS versions, 286

---

## E

**EML (Element Management Layer), 178**  
**enabling NetFlow, 385–386**  
**Enhanced Object Tracking feature (Cisco IP  
 SLA), 499–501**  
**enterprise departmental charge back, 608**  
**enterprise networks**  
     capacity planning, 544–545  
     monitoring, 525  
     optimized routing, 536–538  
**error statistics, Cisco IP SLA, 464**  
**estimating core traffic matrix, 556**  
**eTOM (enhanced Telecom Operations Map)  
 model, 185**  
**eTOM model, 185, 188**  
     FAB, 188  
     OPS, 186  
**event-based data collection model, 145–146**  
**EVENT-MIB, 268**  
**example configurations**  
     authNoPriv SNMP, 233–235  
     authPriv SNMP, 235  
     multicast egress accounting, 363  
     multicast ingress accounting, 363–365  
     NetFlow  
         *on Catalyst switch, 348–349*  
         *version 5 on router, 347*  
         *version 8, 350*  
         *version 9, 350–351*  
     NetFlow Input Filters, 359–360  
     NetFlow Top Talkers, 368–370  
     Sampled NetFlow, 354–356  
     SNMPv2, 230

**examples**

- of basic NBAR configuration, 445–446
- of EXPRESSION-MIB, 266–268
- of Flexible NetFlow applications, 379–385
- of NBAR custom application, 446–447
- of NetFlow version 9 export protocol, 206–208
- of VoIP operations, 486–488

**EXEC accounting, 406****export protocols (NetFlow), 204, 340**

- FTP, 150–151
- NetFlow, 149–150
- SCTP, 341
- SNMP, 148–149

**EXPRESSION-MIB, 265–268****external core matrix, 40**

- generating, 549–550

**F****FAB (Fulfillment, Assurance, and Billing) model, 186–188****failover mode (SCTP), 342****fault management, 70, 74, 180**

- thresholds, 71–72

**FCAPS (Fault, Configuration, Accounting, Performance, and Security) model, 174, 179–180**

- accounting management, 181–182
- configuration management, 181
- fault management, 180
- performance management, 182–183
- security management, 183

**features**

- of Cisco IP SLA, 451
- of NBAR application classification, 436
- of NetFlow, 351–353
  - Layer 2 and Security Monitoring Exports feature, 365–366*
  - Top Talkers, 366–368*

**fields**

- of CDRs, 566
- of CMRs, 567–568

**filtering, 105–106, 118–120****flat rate billing, 47, 609****Flexible NetFlow, 324, 370–371**

- CLI operations, 377–379

core traffic matrix, collecting, 552–553

example applications of, 379–385

Flow Caches, 374–375

Flow Monitors, 371

key-fields, 372–374

packet sections feature, 374

versus original NetFlow, 375–377

**Flow Caches in Flexible NetFlow, 374–375****flow keys, 323****flow mask, 324****Flow Monitors, 371****flow sampling, 109****flow values, 323****flow-based Sampled NetFlow, 356–357****flows, 322**

aging mechanism

*on Catalyst switches, 328–329*

*on Cisco IOS routers, 327–328*

connection-oriented, 325

key-fields, 323–324

*BGP next-hop, 362–363*

**FlowSets, 204–205****formal languages, 190****Frame Relay, CISCO-FRAME-RELAY-MIB, 247–249****Frame Relay operation (Cisco IP SLA), 473–475****frequency parameter of metric measurement, 457****FTP operation (Cisco IP SLA), 470****full-mesh design, 508****full collection, 104–105****fundamentals of NetFlow, 322****G****general-purpose MIBs, 237**

for accounting and performance, 239

**generating core traffic matrix, 548**

external versus internal core traffic matrix, 549–550

granularity, defining, 548

**GetBulk operations (SNMP), 197****GetNext operations (SNMP), snmpwalk utility, 236****Gnutella, limiting peer-to-peer traffic, 447****granularity of core traffic matrix, defining, 548****gravity model, estimating core traffic matrix, 556**

**groups**  
 configuring on Cisco Catalyst switches, 279–280  
 in DSMON MIB, 286  
 in SMON MIB, 288–289  
 NAM-supported, 279  
 RMON 1, 275  
 RMON 2, 276

## H

**HC-RMON, 276**  
**Headquarters OER configuration, 538**  
**HIDSs, 591**  
**history collection feature (Cisco IP SLA), 494–495**  
**honeypots, 590**  
**hot-potato routing, 141, 549**  
**HTTP, subport classification, 436–437**  
**HTTP operation (Cisco IP SLA), 472**  
**HTTP requests, payload inspection, 447–448**  
**HTTP response time, 456**  
**hysteresis function (Cisco IP SLA), 495**

## I

**IANA (Internet Assigned Numbers Authority)**  
 assigned protocol numbers, 94  
 well-known ports, 95  
**ICMP operations (Cisco IP SLA), 464**  
 ICMP Echo operation, 465  
 ICMP Path Echo operation, 465–466  
 ICMP Path Jitter operation, 467  
**ICPIF (Impairment/Calculated Planning Impairment Factor)**  
 calculating, 564  
 voice performance, measuring, 563  
**Idd (Delay Impairment Factor), 563**  
**identification phase of six-stage security operations model, 584–586**  
**IDSs, 590**  
**Ie (Equipment Impairment Factor), 563**  
**IETF RFCs**  
 Diameter, 217  
 IPFIX-related, 211  
 obtaining, 269  
 PSAMP-related, 213–214  
 RADIUS, 215  
 RFC 2924, *Accounting Attributes and Record Formats*, 189  
 RFC 2975, *Introduction to Accounting Management*, 189–190  
 SMI-related, 199  
 SNMP-related, 200–201  
**IETF PSAMP working group, 338**  
**IF-MIB, 253**  
**ifTable, 236**  
**ILMI (Interim Local Management Interface), 234**  
**immediate Cache Flows, 375**  
**immediate triggers (Cisco IP SLA), 497**  
**impact**  
 of Cisco IP SLA CPU utilization on accuracy, 504–506  
 of Cisco IP SLA on device performance, 503–504  
**include parameter (show ip cache flow command), 589**  
**in-depth flow inspection, 587**  
**Inform operation (SNMP), 197**  
**information elements (NetFlow), comparing on different export protocol versions, 338–339**  
**information modeling, 176, 190–191**  
**Input Filters (NetFlow), 358**  
 example configuration, 359–360  
**inspecting HTTP requests payload, 447–448**  
**interfaces supported on NetFlow, 339**  
**internal core matrix, 40**  
**Internet management model, 191**  
**interpacket interval parameter of metric measurement, 458**  
**intranet as security threat, 582**  
**intrusion attacks, 580**  
**IP Accounting, 297**  
 features, comparing, 317  
 IP Accounting (Layer 3), 298  
*collection monitoring, 302–303*  
*configuring, 302*  
*principles, 298*  
*related IOS commands, 299–300*  
*SNMP operations, 300*  
*supported devices, 299*  
*supported IOS versions, 299*  
 IP Accounting ACL, 303



- collection monitoring, 306–308*
  - commands, 304–305*
  - configuring, 305–306*
  - principles, 304*
  - SNMP operations, 305*
  - supported devices, 304*
  - supported IOS versions, 304*
- IP Accounting MAC Address, 308
  - collection monitoring, 311–312*
  - commands, 309*
  - configuring, 311*
  - MIBs, 310–311*
  - principles, 308*
  - supported devices, 309*
  - supported IOS versions, 309*
- IP Accounting Precedence, 312
  - collection monitoring, 315–317*
  - commands, 314*
  - configuring, 315*
  - MIBs, 314–315*
  - principles, 313*
  - supported IOS versions, 313*
- NBAR PD MIB features, 440–441
- IP Accounting (Layer 3), 298**
  - collection monitoring, 302–303*
  - configuring, 302*
  - principles, 298*
  - related IOS commands, 299*
  - SNMP operations, 300*
  - supported devices, 299*
  - supported IOS versions, 299*
- IP Accounting ACL, 303**
  - collection monitoring, 306–308*
  - commands, 304–305*
  - configuring, 305–306*
  - principles, 304*
  - SNMP operations, 305*
  - supported devices, 304*
  - supported IOS versions, 304*
- IP Accounting MAC Address, 308**
  - collection monitoring, 311–312*
  - commands, 309*
  - configuring, 311*
  - MIBs, 310–311*
  - principles, 308*
  - supported devices, 309*
  - supported IOS versions, 309*
- IP Accounting Precedence, 312**
  - collection monitoring, 315–317*
  - commands, 314*
  - configuring, 315*
  - MIBs, 314–315*
  - principles, 313*
  - supported IOS versions, 313*
- ip nbar custom command, 443**
- IP SLA. *See* Cisco IP SLA**
- IP SLA Responder, 451, 459–462**
- IP spoofing attacks, 591**
- IP telephony**
  - metering sources, 561*
  - network blueprint, 560–561*
  - voice performance, measuring, 561*
    - active measurement, 565*
    - ICPIF, 563*
    - MOS, 562*
    - passive measurement, 564*
    - standards and technology, 561*
    - with CCM, 565, 568*
    - with CiscoWorks Unified Operations Manager, 572*
    - with NAM, 571*
- IPDR (Internet Protocol Data Record), 604**
- IPDR (Internet Protocol Detail Record), 217, 404**
- IPDR.org website, 218**
- IPDV (IP Packet Delay Variation), 454**
- IPFIX (IP Flow Information eXport), 208–209, 321**
  - charter objectives, 211*
  - export protocol, 209–210*
  - RFCs, 211*
- IPM (CiscoWorks Internet Performance Monitor), 531**
- IPPM (IETF IP Performance Metric ), 221**
  - RFCs, 222*
- IPv4 multicast routing MIB, 253**
- IPv6 MIBs, 251–252**
- ISPs, capacity planning, 544–545**
- ITU-T recommendations**
  - M.3010, 178, 184*
  - M.3400, FCAPS, 179–180*
    - accounting management, 181–182*
    - configuration management, 181*
    - fault management, 180*

*performance management, 182–183*  
*security management, 183*

- ITU-T specification Y.1541, Network Performance Objectives for IP-Based Services, 221**
- ITU-T standards, measuring voice performance, 561**

## J-K

### **jitter, 454**

ICMP Path Jitter operation, 467  
 UDP Jitter operation, 468–469

### **key-fields, 89, 323–324**

BGP next-hop, 362–363  
 in Flexible NetFlow, 372–374

## L

### **Lakhina, Anukool, 549**

### **Layer 2 and Security Monitoring Exports feature (NetFlow), 365–366**

### **lifetime parameter of metric measurement, 459**

### **limiting peer-to-peer traffic with NBAR, 447**

### **link capacity planning, 541, 543**

### **linking metrics to applications, 456**

### **links, performance monitoring, 526**

MIBs, 527–530

### **LLA (logical layered architecture), 178**

### **load balancing, 122**

### **low-priority processing, 465**

## M

### **M.3010 recommendation, 178, 184**

### **M.3400 recommendation, FCAPS, 179–180**

accounting management, 181–182  
 configuration management, 181  
 fault management, 180  
 performance management, 182–183  
 security management, 183

### **managed devices, 192**

### **measuring**

#### **metrics, 457**

*frequency parameter, 457*  
*interpacket interval parameter, 458*  
*lifetime parameter, 459*  
*number of packets parameter, 458*  
*operations parameters, 457*  
*packet size parameter, 458*  
*start time parameter, 459*  
*timeout parameter, 458*

#### **standards and technology, 561**

*with CCM, 565–568*  
*with CiscoWorks Unified Operations Manager, 572*  
*with NAM, 571*

#### **voice performance, 561, 564**

*active measurement, 565*  
*CCM, 565–568*  
*CiscoWorks Unified Operations Manager, 572*  
*ICPIF, 563*  
*MOS, 562*  
*NAM, 571*

### **memory consumption of Cisco IP SLA on devices, 503–504**

### **metering devices**

positioning, 130–144  
 sources in IP telephony, 561

### **metrics**

linking to applications, 456  
 measuring, 453, 457  
*accuracy, 455*  
*DHCP response time, 456*  
*DNS response time, 456*  
*HTTP response time, 456*  
*jitter, 454*  
*network delay, 454*

### **MIB table, example data retrieval, 235–237**

### **MIB-II objects, 240**

### **MIBs, 193–194, 228. *See also* groups**

APM MIB, 289  
*suggested default response times, 291*  
*supported IOS versions and devices, 291*  
 CISCO-CLASS-BASED-QOS-MIB, traffic classification, 543  
 CISCO-DATA-COLLECTION-MIB, 244–246  
 CISCO-ENVMON-MIB, 244  
 CISCO-HEALTH-MONITOR-MIB, 244

- CISCO-IF-EXTENSION-MIB, 241
- CISCO-NETFLOW-MIB, NetFlow SNMP operations, 346
- CISCO-PING-MIB, 241
  - read-only objects*, 242
  - read-write objects*, 241
- CISCO-PROCESS-MIB, 242
  - objects*, 243–244
- data collection, accounting and performance features, 515–516
- DATA-COLLECTION-MIB, 529
- DSMON MIB, 284
  - MIB object groups*, 286
  - principles*, 286
  - supported devices and IOS versions*, 286
- EVENT-MIB, 268
- EXPRESSION-MIB, examples, 266–268
- for data collection, comparing, 517–521
- for device and link performance monitoring, 527–530
- for IP Accounting (Layer 3), 300
- for IP Accounting ACL, 305
- for IP Accounting MAC Address, 310–311
- for IP Accounting Precedence, 314–315
- for network connectivity monitoring, 530–531, 534
- functional areas, comparing, 238–239
- general-purpose, 237–239
- Interface-MIB, objects, 240
- MEMORY-POOL-MIB, 244
- NBAR PD MIB, 439
  - IP accounting features*, 440–441
- objects
  - creating*, 265
  - NBAR PD thresholds*, 442–443
- obtaining, 269–271
- SMI, 194, 196
- SMON MIB, 287
  - groups*, 288–289
  - supported devices and IOS versions*, 288
- technology-specific accounting and performance MIBs, 247
  - CISCO-CAR-MIB*, 255
  - CISCO-CLASS-BASED-QOS-MIB*, 256–257
  - CISCO-FRAME-RELAY-MIB*, 247–249
  - for IPv6*, 251–252
  - for multicast*, 253
  - for telephony*, 257–265
  - for VLANs*, 253–255
  - MPLS LSR MIB*, 249–250
  - MPLS Traffic Engineering MIB*, 250
- transport technology-specific, 237
- mini-RMON, 274**
  - configuring on Cisco Catalyst switches, 282–284
- MOS (Mean Opinion Score), 221**
  - voice performance, measuring, 562
- MPLS LSR MIB, 249–250**
- MPLS Traffic Engineering MIB, 250**
- MPLS-Aware NetFlow, 360–361**
  - configuring, 360–362
  - core traffic matrix, collecting, 553–554
- MPLS-Aware NetFlow Top Label Aggregation, 553**
- MRTG (Multi-Router Traffic Grapher), 86**
- MTBF (mean time between failure), 62**
- MTTR (mean time to repair), 62**
- multicast**
  - egress accounting, example configuration, 363
  - ingress accounting, example configuration, 363–365
  - MIBs, 253
- Multiple Operation Scheduling feature (Cisco IP SLA), 490–491**

## N

- NAM (Network Analysis Module), 319**
  - attacks, classifying, 589–590
  - modules, 278
  - network connectivity monitoring, 532
  - supported MIB groups, 279
  - voice performance, measuring, 571
- naming conventions for call legs, 417**
- NAS (Network Access Server), 403**
- NBAR (Network-Based Application Recognition), 433**
  - application classification, 435–436
  - attacks, classifying, 589
  - Citrix ICA traffic classification, 437
  - configuration commands, 443

- configuring, basic NBAR configuration
  - example, 445–446
- custom application example, 446–447
- inspecting HTTP request payload, 447–448
- PD MIB, 439
  - IP accounting features*, 440–441
- PDLMs, 437
- peer-to-peer traffic, limiting, 447
- Protocol Discovery feature, 434
  - thresholds*, 442–443
- Protocol Discovery statistics group, 440
- QoS features, 433
- show commands, 443–445
- subport classification, 436–437
- supported devices, 438–439
- supported protocols, 440
- Top-N statistics, 441–442
- unsupported capabilities, 438
- NEL (Network Element Layer), 178**
- NetFlow, 201–202**
  - application monitoring, 534–536
  - attacks, classifying, 587–589
  - cache, 325
    - entries, displaying*, 325
    - entry sizes*, 326
    - flow record expiry*, 327
    - parameters*, 325
  - Cisco CNS NetFlow Collection Engine, 344–345
  - configuration commands, 345–346
  - core traffic matrix, collecting, 551
  - customer applications, 320–321
  - deploying, 385–386
  - device-level architecture, 342
  - example Catalyst switch configuration, 348–349
  - export protocols, 204, 340
    - SCTP*, 341
  - Flexible NetFlow, 370–371
    - CLI operations*, 377–379
    - Flow Caches*, 374–375
    - Flow Monitors*, 371
    - key-fields*, 372–374
    - packet sections feature*, 374
  - flow aging mechanisms
    - on Catalyst switches*, 328–329
    - on Cisco IOS routers*, 327–328
  - flow mask, 324
  - flows
    - BGP next-hop key-field*, 362–363
    - connection-oriented*, 325
    - key fields*, 323
    - key-fields*, 323
  - FlowSets, 204–205
  - fundamentals, 322
  - information elements, comparing on different
    - export protocol versions, 338–339
  - Input Filters, 358
    - example configuration*, 359–360
  - IPv6 environment monitoring, 322
  - Layer 2 and Security Monitoring Exports
    - feature, 365–366
  - MPLS-Aware, configuring, 360–362
  - NetFlow version 9 export protocol, 202
  - Options Template FlowSet, 204
  - records, collecting, 585
  - router-based aggregation feature, 323
  - Sampled NetFlow, 353–354
    - example configuration*, 354–356
    - flow-based*, 356–357
  - SNMP operations, 346
  - supported devices and Cisco IOS versions, 387
  - supported interface types, 339
  - template management, 205–206
  - template mechanism, 203, 336
  - Top Talkers feature, 366
    - example configuration*, 368–370
    - match statement options*, 367–368
  - version 1, 330
  - version 5, 330
    - example router configuration*, 347
  - version 7, 330–331
  - version 8, 332–333
    - example configuration*, 350
    - non-TOS aggregation schemes*, 334–335
    - TOS aggregation schemes*, 334–336
  - version 9, 336
    - example configuration*, 350–351
    - export protocol example*, 206–208
    - supported features*, 351–353
  - version 10, 337–338
  - versus Flexible NetFlow, 375–377
- NetFlow Collector, 344–345**
- NetFlow Multicast, 363**

- multicast egress accounting, example configuration, 363
- multicast ingress accounting, example configuration, 363–365

**net-snmp tools, 229****network accounting, 405****network availability, testing, 122–124****network blueprint**

- for capacity planning, 543
- for IP telephony, 560–561
- security, 580

**network connectivity, performance monitoring****MIBs, 530–531, 534****network delay, 454**

- versus processing delay, 460

**network monitoring applications**

- comparing, 292–293

**network performance monitoring, 65–66****NFC (NetFlow Collection Engine), 319**

- filters, 158

**NGOSS (Next-Generation Operations Support Systems), 185****NIDSs, 591****NML (Network Management Layer), 178****non-IP SLA responder-based operations, 463****normal Cache Flows, 374****NTP (Network Time Protocol), 405, 455****O****objects**

- for CISCO-FRAME-RELAY-MIB, 247–249
- for CISCO-PING-MIB, 241–242
- for CISCO-PROCESS-MIB, 242–244
- for IPv6 MIBs, 251–252
- for MPLS LSR MIB, 249–250
- for MPLS Traffic Engineering MIB, 250 MIB-II, 240

**obtaining**

- IETF RFCs, 269
- MIBs, 269–271

**OER (Optimized Edge Routing), 536–538****OIDs (object identifiers), 193, 228****operational statistics (Cisco IP SLA), 464****operations (Cisco IP SLA)**

- ATM operation, 475–476
- CLI operations, 480–482
- DHCP operation, 471
- DLSw+ operation, 479
- DNS operation, 471–472
- Frame Relay operation, 473–475
- FTP operation, 470
- HTTP operation, 472
- ICMP operations, 464
  - ICMP Echo operation, 465*
  - ICMP Path Echo operation, 465–466*
  - ICMP Path Jitter operation, 467*
- multiple, scheduling, 490–491
- placement of, 508, 511
- random, scheduling, 491
- router support for, verifying, 483–486
- RTP-based VoIP operation, 477, 479
- scheduling, 488
  - Recurring function, 489*
- summary table, 511, 513
- TCP Connect operation, 470
- UDP operations
  - UDP Echo operation, 468*
  - UDP Jitter operation, 468–469*
  - VoIP UDP Jitter operation, 469–470*
- VoIP Call Setup Monitoring operation, 477
- VoIP Gatekeeper Registration Delay
  - Monitoring operation, 476

**operations parameters of Cisco IP SLA metric measurement, 457**

- frequency, 457
- interpacket interval, 458
- lifetime, 459
- number of packets parameter, 458
- packet size, 458
- start time, 459
- timeout, 458

**optimized routing on enterprise networks, 536–538****Options Template FlowSet, 204–205****OSR (Operations Support and Readiness), 186****out-of-band-management, 177****OWD analysis, 129**

## P

**packet accounting, 87**

**packet sampling, 109**

probabilistic, 116–117

random, 114–115

stratified, 117

**packet sections feature (Flexible NetFlow), 374**

**packet size parameter of metric measurement, 458**

**packet-based flow sampling, configuring, 357**

**packets**

flows, 322

RADIUS, 408

**Papagiannaki, Konstantina, 549**

**parameters**

for ip nbar custom commands, 443

for NetFlow cache, 325

**parent population, 106**

**partial-mesh design, 508**

**partial collection, 105**

**passive monitoring, 19, 104**

filtering, 105–106, 118–120

full collection, 104–105

OWD analysis, 128–129

partial collection, 105

sampling methods, 107

*deterministic sampling, 109–114*

*probabilistic packet sampling, 116–117*

*random sampling, 114–115*

*stratified sampling, 117*

**passive voice performance measurement, 564**

**PD MIB, 439**

IP accounting features, 440–441

**PDL (Packet Description Language), 434**

**PDLM (Packet Description Language Modules), 434, 437**

**PDP (Policy Decision Point), 403**

**peer-to-peer traffic**

billing for, 557

limiting, 447

**peering agreements, 37–38**

transit agreements, 38–43

**PEP (Policy Enforcement Point), 403**

**per-call billing, 574**

**performance features of data collection MIBs, 515–516**

**performance management, 182–183**

combining with accounting management, 20–21

defining, 13–17

SLA parameters, 219–221

MIBs, 239

*CISCO-DATA-COLLECTION-MIB, 244–246*

*CISCO-ENVMON-MIB, 244*

*CISCO-HEALTH-MONITOR-MIB, 244*

*CISCO-MEMORY-POOL-MIB, 244*

*CISCO-PROCESS-MIB, 242–244*

versus performance monitoring, 14

**performance monitoring. *See also* Cisco IP SLA**

device and link performance, 526

*MIBs, 527–530*

network connectivity MIBs, 530–531, 534

**periodic fix-interval sampling, 110**

**permanent Cache Flows, 375**

**PFC (Policy Feature Card), 330**

**ping tests, 126–127, 464**

**placing Cisco IP SLA operations, 508, 511**

**polling period, 246**

**positioning metering devices, 130–131**

edge versus core collection, 132–136

embedded versus external device collection, 136–138

flow lookup direction, 140–141

ingress versus egress collection, 138–140

technology-dependent special constraints, 141–144

priority traffic class, 119

**postmortem performing on network attacks, 594–596**

**preparation phase of six-stage security operations model, 583–584**

**principles**

of DSMON MIB, 286

of RMON, 277

**probabilistic sampling, 116–117**

**processing data records**

data aggregation, 160–164

data record correlation, 164

filtering, 157–159

flow de-duplication, 165

formatting, 165–166

sampling, 159

threshold monitoring, 159–160

**processing delay versus network delay, 460**  
**Protocol Discovery feature (NBAR), 434**  
     thresholds, 442–443  
**Protocol Discovery statistics group (NBAR), 440**  
**protocols supporting NBAR, 440**  
**proxy servers, 263**  
**PSAMP (Packet Sampling) working group, 212**  
     protocol specifications, 212–213  
     RFCs, 213–214  
**publish and subscribe bus, 152**  
**pull model**  
     core traffic matrix, collecting with BGP Policy Accounting, 555  
     core traffic matrix, generating, 550  
**push model, 204**  
     core traffic matrix, collecting  
         with *BGP passive peer feature*, 554–555  
         with *Flexible NetFlow*, 552–553  
         with *MPLS-Aware NetFlow*, 553–554  
         with *NetFlow*, 551  
     core traffic matrix, generating, 550  
**pWLANs, time-based billing, 602**

## Q

**QoS**  
     CAR, 593  
     NBAR features, 433  
**QRT (Quality Report Tool), 568**

## R

**RADIUS, 214–215, 406–407**  
     accounting  
         *Acct-Session-Id field*, 423–424  
         VSAs, 419–422  
     attributes, 409–414  
     authentication, 408  
     authorization, 408  
     AVPs, 414  
     commands, 415–416  
     Diameter, 407, 428  
         *base protocol structure*, 428  
         *intermediary agents*, 428  
     packets, 408

    RFC 2866 versus RFC 2865, 407  
     RFCs, 215  
     voice extensions, 416  
         *call legs*, 416–418  
         VSAs, 418–419  
     VoIP accounting commands, 425–428  
**random sampling, 108, 114–115**  
**Random Scheduling feature (Cisco IP SLA), 491**  
**RAS (Reliability, Availability, and Survivability), 180**  
**reaction stage of six-stage security operations model, 593–594**  
**reconnaissance attacks, 580**  
**Recurring function, scheduling Cisco IP SLA operations, 489**  
**recursive accounting, 38**  
**redirect servers, 263**  
**redundant mode (SCTP), 342**  
**registered ports, 95**  
**registrars, 263**  
**Remote Office OER configuration, 538**  
**responder-based operations (Cisco IP SLA), 463**  
**retrieving**  
     MIB table data, example, 235, 237  
     SNMPv2c data, 231  
**RFC 1213, MIB-II, 240**  
**RFC 2863, Interface-MIB, 240**  
**RFC 2865, 409**  
**RFC 2866, 409**  
**RFC 2924, Accounting Attributes and Record Formats, 189**  
**RFC 2975, Introduction to Accounting Management, 189–190**  
**RFC 3812, MPLS Traffic Engineering MIB, 250**  
**RFC 3813, MPLS LSR MIB, 249**  
**RFCs**  
     Diameter, 217  
     IPFIX-related, 211  
     obtaining, 269  
     PSAMP-related, 213–214  
     RADIUS, 215  
     SMI-related, 199  
     SNMP-related, 200–201  
**RM&O (Resource Management & Operations), 188**

**RMON, 273**

- groups, configuring on Cisco Catalyst switches, 279–280
- MIBs, DSMON MIB, 284–286
- NAM modules, 278
- principles, 277
- rows, 280, 282
- supported devices, 277–278
- supported IOS versions, 277–278

**RMON 1 groups, 275****RMON 2, 274**

- groups, 276

**RMON-MIB, 253****rogue access points, detecting, 61****round-trip times, measuring, 454****router-based aggregation, 324****router-based aggregation feature (NetFlow), 323****routing optimization, 536–538****row (RMON), 280–282****RRDtool (Round Robin Database), 86****RSPAN (Remote SPAN), 278–279****RTMP (Real-Time Messaging Protocol), 568****RTP-based VoIP operation (Cisco IP SLA), 477–479****RTR (Response Time Reporter), 451****S****SAA (Service Assurance Agent), 451****SAMIS (Subscriber Account Management Interface Specification), 604****Sampled NetFlow, 353–354**

- example configuration, 354–356
- flow-based, 356–357

**sampling methods, 107**

- deterministic, 109–114
- probabilistic, 116–117
- random, 114–115
- stratified, 117

**scalar objects, 228****scenarios**

- capacity planning
  - for enterprises, 544–545
  - for ISPs, 544–545
  - link capacity planning, 541–543
- for voice networks, 559–560
- security-related, 579

**scheduling**

- Cisco IP SLA operations, 488
  - Recurring function*, 489
- multiple Cisco IP SLA operations, 490–491
- random Cisco IP SLA operations, 491

**SCTP (Stream Control Transport Protocol), 340**

- as NetFlow export protocol, 340–341

**security. *See also* security management**

- attack postmortem, performing, 594–596
- intrusion attacks, 580
- network blueprint, 580
- reconnaissance attacks, 580
- scenarios, 579
- source authentication, 167–168
- threats from intranet, 582

**security management, 183, 582**

- six-stage security operations model, 582
  - classification stage*, 587–590
  - identification stage*, 584–586
  - preparation stage*, 583–584
  - reaction stage*, 593–594
  - tracing back source of attack*, 591–592

**security models and levels (SNMP), 199****selecting, 175–176****service availability, testing, 124–126****service monitoring, 66–67, 536–538****Serviceability, 568****service-based billing, 607–608****show commands, NBAR-related, 443–445****show ip accounting access violations command, 307****show ip accounting command, 300, 305****show ip accounting output-packets command, 307****show ip cache flow command, 325, 589****show ip cache verbose flow command, 326****show ip nbar command, 444****show ip sla application command, 483–486****show rmon stats command, 284****show snmp command, 231****show snmp group command, 233****show snmp view command, 234****simple SMI types, 195****simply constructed SMI data types, 196**



- sinkholes, 590**
- SIP MIB, 262–265**
- six-stage security operations model, 582**
  - classification stage, 587–590
  - identification stage, 584–586
  - preparation stage, 583–584
  - reaction stage, 593–594
  - tracing back source of attack, 591–592
- size-based flow sampling, 112–114**
- SLAs, 219**
  - generic, 68
  - monitoring, 99
  - network connectivity monitoring, 530–531, 534
  - parameters, 219–221
- SM&O (Service Management & Operations), 188**
- SMI (Structure of Management Information), 194–196, 227**
  - related RFCs, 199
- SML (Service Management Layer), 178**
- SMON MIB, 287**
  - groups, 288–289
  - supported devices and IOS versions, 288
- SNMP, 148–149**
  - ifTable, 236
  - managed devices, 192
  - message-level security, 198
  - MIBs, 193–194
    - for data collection, 517–521*
    - for device and link performance monitoring, 527–530*
    - for IP Accounting (Layer 3), 300*
    - for IP Accounting ACL, 305*
    - for IP Accounting MAC Address, 310–311*
    - for IP Accounting Precedence, 314–315*
    - for network connectivity monitoring, 530–531, 534*
    - NBAR PD MIB, 439–441*
    - SMI, 194–196*
  - related RFCs, 200–201
  - security models and levels, 199
  - traps, ciscoPingCompleted trap, 242
  - versions, 196
- SNMP operations (NetFlow), 346**
- snmpget utility, arguments, 235**
- SNMPv1, 196**
- SNMPv2, 197**
  - configuring, 230
  - data retrieval, 231
  - statistics, displaying, 231
- SNMPv3, 198**
  - configuring, 231–233
  - with user authentication, example
    - configuration, 235
  - without user authentication, example
    - configuration, 233–235
- snmpwalk utility, 236**
- source of attack, tracing, 591–592**
- SPAN (Switched Port Analyzer), 278–279**
- spectrum of test, 457**
- spoofed source addresses, tracing, 591**
- SRLG (Shared Risk Link Group), 546**
- standards, 175–176**
  - accounting and performance management, 176
  - de facto, 174
  - for voice service accounting, 573–576
  - selection process, 175–176
  - voice performance, measuring, 561
- start time parameter of metric measurement, 459**
- stateful inspection, 95**
- stateful proxy servers, 263**
- stateless proxy servers, 263**
- Statistics and History group (RMON 1)**
  - switch configuration, 282
- statistics distribution collection (Cisco IP SLA), 492–494**
- statistics for SNMPv2c, displaying, 231**
- Stewart, John, 582**
- stratified sampling, 117**
- Stratum 0, 405**
- streams, 340**
- support classification, 436–437**
- summary of NBAR data collection criteria, 449**
- summary table of Cisco IP SLA operations, 511–513**
- supported features on NetFlow version 9, 351–353**
- suspending conceptual rows, 281**
- switched network environments, SMON MIB, 287**
  - groups, 288–289
  - supported devices and IOS versions, 288
- syntax for net-snmp tools, 229**

system accounting, 406  
 system clock synchronization, 455

## T

TACACS+, 216, 406–407

Taft, Nina, 549

TCP connect, 456

TCP Connect operation (Cisco IP SLA), 470

technology-specific accounting and performance MIBs, 247

CISCO-FRAME-RELAY-MIB, 247, 249

for IPv6, 251–252

for multicast

*IF-MIB*, 253

*RMON-MIB*, 253

for telephony, 257–258

*CISCO-CALL-HISTORY-MIB*, 261–262

*CISCO-VOICE-COMMON-DIAL-CONTROL-MIB*, 261

*CISCO-VOICE-DIAL-CONTROL-MIB*, 260–261

*Dial Control Management MIB*, 259

*SIP MIB*, 262–265

for traffic management and control

*CISCO-CAR-MIB*, 255

*CISCO-CLASS-BASED-QOS-MIB*, 256–257

for VLANs, 253–255

*community string indexing*, 254

MPLS LSR MIB, 249–250

MPLS Traffic Engineering MIB, 250

Telecommuter OER configuration, 538

telephony, MIBs, 257–258

*CISCO-CALL-HISTORY-MIB*, 261–262

*CISCO-VOICE-COMMON-DIAL-CONTROL-MIB*, 261

*CISCO-VOICE-DIAL-CONTROL-MIB*, 260–261

*Dial Control Management MIB*, 259

*SIP MIB*, 262–265

Template FlowSets, 204

templates (NetFlow), 203–206, 336

test packets, 452

testing

device availability, 121

network availability, 122–124

service availability, 124–126

threats from intranet, 582

thresholds

for NBAR Protocol Discovery, 442–443

monitoring (Cisco IP SLA), 495–499

violation triggers (Cisco IP SLA), 497–498

time- and distance-based billing, 606

time stamps, 602

time-based billing, 602

dial-in, 603

pWLANs, 602

time-based flow sampling, configuring, 356–357

timeout parameter of metric measurement, 458

time-stamping, 461

TMF (TeleManagement Forum), eTOM model, 185

FAB, 188

OPS, 186

TMN (Telecommunications Management Network), 176

TMN framework, 184

TMN/FCAPS model, 176

TOM (Telecom Operations Map), 185

tools for capacity planning, 546

Top Talkers feature (NetFlow), 366

example configuration, 368–370

match statement options, 367–368

top-down accounting and performance

management, TM-FCAPS model, 176

Top-N statistics, 441–442

Top-N traffic volume, identifying, 587

TOS aggregation schemes, 335–336

ToS bits, relationship to Precedence and DSCP bits, 95

traceroute, 127

tracing source of attacks, 591–592

traffic classification, CISCO-CLASS-BASED-QOS-MIB, 543

traffic engineering, 548

traffic management and control MIBs

*CISCO-CAR-MIB*, 255

*CISCO-CLASS-BASED-QOS-MIB*, 256–257

transit agreements, 38–39, 604–606

transport technology-specific MIBs, 237

**traps (SNMP), 197**  
CiscoPingCompleted trap, 242

## U

**UAC (User Agent Client), 262**  
**UAS (User Agent Server), 262**  
**UDP as NetFlow export protocol, 340**  
**UDP operations (Cisco IP SLA)**  
UDP Echo operation, 468  
UDP Jitter operation, 468–469  
VoIP UDP Jitter operation, 469–470  
**UML (Unified Modeling Language), 190**  
**unicast communication, 152**  
**unsupported NBAR capabilities, 438**  
**users, defining, 100–102**  
**utilities for capacity planning, 546**

## V

**VACM (View-based Access Control Model), 198**  
**verifying router-supported IP SLA operations, 483–486**  
**versions**  
of SNMP, 196  
of Cisco IOS Software supporting NBAR, 438–439  
**VLAN-related MIBs, 253–255**  
community string indexing, 254  
**VoD (video on demand), 608**  
**voice extensions for RADIUS, 416**  
call legs, 416–418  
VSAs, 418  
*accounting, 419–422*  
**voice gateways, 416**  
**voice networks**  
metering sources, 561  
performance, measuring, 561  
*active measurement, 565*  
*CCM, 565, 568*  
*CiscoWorks Unified Operations Manager, 572*  
*ICPIF, 563*  
*MOS, 562*  
*NAM, 571*

*passive measurement, 564*  
*standards and technology, 561*  
scenarios, 559–560

**voice quality, MOS, 221**

**voice service accounting**  
standards and technology, 573–576  
with CDRs, 575

**VoIP**

accounting with RADIUS, commands, 425–428  
per-call billing, 574  
RTP-based VoIP operation (Cisco IP SLA), 477–479

**VoIP Call Setup Monitoring operation (Cisco IP SLA), 477**

**VoIP Gatekeeper Registration Delay Monitoring operation (Cisco IP SLA), 476**

**VoIP operations (Cisco IP SLA), example, 486–488**

**VoIP UDP Jitter operation, 469–470**

**volume-based billing, 603**

peering agreements, 604–606  
residential broadband access, 603–604  
transit agreements, 604–606

**VRF table, 459**

**VSAs, 418–419**

accounting, 419–422  
RADIUS accounting versus Acct-Session-Id field, 424

## W-X-Y-Z

**W3C, 175**

**well-known ports, 95**

**x of y triggers (Cisco IP SLA), 497**