

Index

Symbols

- (* , G), 614
- (S , G), 612–614

Numerics

- 6-to-4 tunnels, migration to IPv6, 693–694
- 802.3 MAC address format, 599

A

- ABRs (area border routers), 165–166, 227
 - summarization, configuring, 242–244
- access layer (hierarchical network model), 11
- ACK packets, suppressing, 107
- active IGMP version, displaying, 607
- Active Process Enhancement feature (EIGRP), 120
- active routes (EIGRP), 73
- active state (BGP), troubleshooting, 540
- AD (advertised distance), 71, 83–84
- address bindings, 433–434
- address format, IPv6, 657–658
- address space (IPv6), 651–652
 - need for increase in, 652–653
- adjacencies (OSPF), 166
 - displaying, 203–205
 - in broadcast networks, 190–191
 - in NBMA networks, 192
 - in point-to-point networks, 189–190
- adjacency database, 163
- adjusting
 - EIGRP hello interval, 75
 - EIGRP link utilization, 103
 - administrative distance, 42–43, 383–384
 - best path selection, influencing, 420–422
 - modifying, 423–424
 - redistribution, example of, 425–430
 - advanced distance vector protocols, 484
 - EIGRP. *See* EIGRP
 - advantages of multicast, 596
 - AfriNIC (African Network Information Centre), 471
 - ALGs (application-layer gateways), 694
 - allocating IP addresses in multiple routing protocol environments, 374–377
 - ANSI (American National Standards Institute), 319
 - anycast addresses (IPv6), 663–664
 - anycast IPv6 addresses, 658
 - APNIC (Asia Pacific Network Information Centre), 471
 - application layer, Cisco SONA, 9
 - architectural frameworks for integrated networks, Cisco SONA, 7–9
 - area addresses, 326
 - area authentication command, 268
 - area virtual-link command, 263
 - areas, 164, 248–249
 - NSSAs, configuring, 257–259
 - standard areas
 - default routes, injecting, 260
 - routing table, interpreting, 255
 - stub areas
 - configuring, 250–252
 - routing table, interpreting, 255–256
 - totally stubby areas
 - configuring, 252–254
 - routing table, interpreting, 256–257
 - verifying configuration, 260
 - virtual links, configuring, 261–266

ARIN (American Registry for Internet Numbers), 471

AS (autonomous systems), 470–471
BGP, interdomain routing, 471
IBGP route propagation, 488–489

AS numbers, prepending, 501–502

ASBRs (autonomous system border routers), 227
summarization, configuring, 243–245

AS-path attribute (BGP), 501–502

asymmetric routing, 332

attribute inheritance (DHCP), 434

attributes (BGP), 498
AS-path, 501–502
community, 507
local preference, 506
configuring, 545–549
MED, 507–508
changing with route maps, 549–553
IETF conformity, configuring, 510
next-hop, 502, 505
changing, 521–522
optional, 499
origin, 505
role in best path selection, 509–511
type codes, 501
weight, 508–509
weight attribute, 500
configuring, 553
well-known, 499

authentication
BGP neighbor authentication, configuring, 524–525
EIGRP MD5 authentication
configuring, 109–114
troubleshooting, 115–116
verifying configuration, 114

EIGRP neighbor authentication, configuring, 107–108

OSPF MD5 authentication
configuring, 272–275
troubleshooting, 276–278
verifying, 276

simple password authentication
configuring on OSPF, 267–270
troubleshooting, 270–272
verifying configuration, 270

auto-cost reference-bandwidth command, 240

automatic bindings, 433–434

autonomous systems, 74, 380
boundary routers, 380

autosummarization, 36–37

autosummarization across the network boundary, 33

avoiding routing feedback with route maps, 419–420

B

backbone areas, 248

backbone routers, 165, 227
configuration exercises, 786–787

bandwidth command, 103

bandwidth metric (EIGRP), calculating, 81

basic BGP example configuration, 529–530

BDRs (Backup Designated Routers), 166–167, 338
election process, 190–191

best path selection
administrative distance, 42–43
BGP
path manipulation, 541–543
with multihomed connections, 543–545

- during redistribution, 383
- for BGP, 509–511
- influencing with administrative distance, 420–422
- OSPF, 236
- best-effort delivery, UDP, 596**
- BGP**
 - advertised networks, defining, 522–524
 - AS, 470–471
 - attributes, 498
 - AS-path*, 501–502
 - community*, 507
 - local preference*, 506
 - MED*, 507–508
 - next-hop*, 502, 505
 - optional*, 499
 - origin*, 505
 - type codes*, 501
 - weight*, 500, 508–509
 - well-known*, 499
 - basic configuration example, 529–530
 - best path selection with multihomed connections, 543, 545
 - characteristics, 484–485
 - CIDR support, 473
 - comparing with other scalable routing protocols, 474
 - configuration exercises, 555–565
 - configuration mode, entering, 514
 - configuring, 512
 - EBGP, example configuration, 532–533
 - EBGP multihop, 519–521
 - full-mesh, example, 490–491
 - IBGP, example configuration, 532–533
 - implementing in enterprise networks, 554
 - in enterprise networks, 475–476
 - interdomain routing, 471
 - keepalive messages, 497–498
 - local preference, configuring, 545–548
 - MED attribute, changing with route maps, 549–553
 - multihoming, 476–477
 - with default routes and partial table from all providers*, 478–479
 - with default routes from all providers*, 477–478
 - with full routes from all providers*, 480
 - multiprotocol extensions, 470

- neighbor authentication, configuring, 524–525
- neighbor relationships, 485–486
 - disabling*, 516
 - external neighbors*, 486
 - internal neighbors*, 487
- neighbor states, 498
 - troubleshooting*, 539–541
- notification messages, 497
- open messages, 496
- partial-mesh, example, 490–491
- path manipulation, 541–543
 - configuration exercises*, 574–575, 577–585
- path vector characteristics, 481–483
- peer groups
 - configuring*, 512–514
 - example configuration*, 530–532
- related RFCs, 472
- route selection process, 509–511
 - maximum-paths command*, 511
- sessions
 - configuring*, 514–516
 - resetting*, 526–529
- source IP address, configuring, 516–518
- speakers, 486
- synchronization, 492–494, 572
 - configuring*, 526
- TCP as transport layer in full-mesh BGP, 491
- transport layer, 484–485
- troubleshooting, 534
 - show ip bgp command*, 534–538
- update messages, 497
 - path attribute*, 499
- versus standard distance vector protocols, 484–485
- weight attribute, configuring, 553
- when to use, 483–484
- bgp always-compare-med command, 508**
- BGP tables, 495–496**
- BGP4+, 470**
- bindings, DHCP, 433–434**
- black holes, 493**
- boundary routers, 380**
- branch architecture (Cisco Enterprise Architecture), 10**
- broadcast mode (OSPF), configuring, 195**

- broadcast networks, 189**
 - IS-IS, implementing, 337–338
 - DIS selection, 338–339*
 - OSPF adjacency behavior, 190–191
- broadcast storms, 658**

C

- cabling for Configuration Exercise equipment, 785–786**
- calculating**
 - cost on high-bandwidth interfaces, 240
 - EIGRP metric, 80–83
 - metrics, OSPF, 167–169
 - best path, 236*
 - cost, 240*
 - external router cost, 237*
- CAM (content-addressable memory) table, 609**
- campus architecture (Cisco Enterprise Architecture), 10**
- CDP (Cisco Discovery Protocol), ODR, 29–31**
- CGMP, 608–609**
- changing**
 - BGP local preference attribute, 545–547
 - IS-IS interface level, 350
 - IS-IS metric, 350
 - routing protocols, 373–374, 378–379
- characteristics**
 - of BGP, 484–485
 - of RIPv1, 39
 - of RIPv2, 39
 - of routing protocols, 46
- CIDR (classless interdomain routing), BGP support, 473**
- CIDR report website, 485**
- Cisco AON (Application-Oriented Networking), 7**
- Cisco Catalyst switches**
 - multicast switching, 608
 - CGMP, 608–609*
 - IGMP snooping, 609*
- Cisco Enterprise Composite Network Model, 13**
- Cisco Enterprise Architecture, 9, 11**
- Cisco Hierarchical Network model, 11, 13**
- Cisco IIN, 6**
 - features of, 6
 - phases of expansion, 7
- Cisco IOS Software**
 - Active Process Enhancement feature, 120
 - equal-cost path support, 28
- Cisco SONA, 7–9**
- Cisco Unified Communications, 7**
- classful routing protocols, 32–33**
 - ip classless command, 34–35
- classless routing protocols, 32, 36–37**
- clear counters tunnel command, 692**
- clear ip bgp command, 527**
- clear ip bgp peer-group command, 514**
- clear ipv6 ospf command, 680**
- CLNP (Connectionless Network Protocol), 311**
- CLNS (Connectionless Network Service), 311**
 - NSAP addresses, 324
- clns router isis command, 348**
- “coloned hex format”, 657–658**
- commands**
 - area authentication, 268
 - area virtual-link, 263
 - auto-cost reference-bandwidth, 240
 - bandwidth, 103
 - bgp always-compare-med, 508
 - clear counters tunnel, 692
 - clear ip bgp, 527
 - clear ip bgp peer-group, 514
 - clear ipv6 ospf, 680
 - clns router isis, 348
 - debug, verifying EIGRP operation, 133, 140–144
 - debug eigrp packets, 140–142
 - debug ip bgp, 538
 - debug ip ospf adj, 204–205
 - debug ip ospf packet, 178
 - default-information originate, 246–248
 - distance, 429
 - distance eigrp, 423
 - eigrp stub, 128
 - frame-relay map clns, 337
 - ip address secondary, 377
 - ip classless, 34–35
 - ip default-network, 95–96
 - ip multicast-routing, 620
 - ip ospf network, 194–195
 - ip pim send-rp-discovery scope, 621

- ip-helper address, 442–444
 - ipv6 unicast-routing, 677
 - is-is circuit-type, 350
 - isis metric, 350
 - is-type, 349
 - maximum-paths, 511
 - max-lsa, 239
 - neighbor, 523
 - neighbor peer-group, 513
 - neighbor remote-as, 515
 - neighbor update-source, 518
 - network, 28, 181, 522–524
 - passive-interface, 399–400
 - router bgp, 514
 - router isis, 347
 - router odr, 30
 - router-id, 187
 - service password-encryption, 268
 - show, verifying EIGRP operation, 132–140
 - show clns, 355
 - show clns interface, 359
 - show clns neighbors, 358
 - show clns protocol, troubleshooting IS-IS, 358
 - show clns route, 356
 - show igmp statistics, 630
 - show ip bgp, 534–538
 - show ip bgp neighbors, 529
 - show ip bgp rib-failure, 536
 - show ip bgp summary, 536–538
 - show ip bgp, 534
 - show ip eigrp interfaces, 138
 - show ip eigrp neighbors, 76
 - show ip eigrp topology, 139–140
 - show ip eigrp traffic, 140
 - show ip igmp group, 604
 - show ip igmp interface, 628
 - show ip mroute, 622–623
 - show ip ospf, 188–189, 265
 - show ip ospf database, 234–235, 266
 - show ip ospf events, 185–186
 - show ip ospf interface, 183–184
 - show ip ospf neighbor, 184–185
 - show ip ospf virtual-links, 264
 - show ip pim neighbor, 624
 - show ip pim rp, 625
 - show ip protocols, 137–138, 354
 - show ip route, 26, 237
 - show ip route eigrp, 135–136
 - show ip route isis, 355
 - show ip route ospf, 183
 - show ip rpf, 626
 - show ipv6 interface, 681–683
 - show ipv6 ospf, 683–684
 - show ipv6 ospf database, 686–687
 - show ipv6 ospf interface, 683
 - show ipv6 ospf neighbor, 684, 686
 - show ipv6 route, 681
 - show isis database, 356
 - show isis route, 355
 - show isis topology, 356–357
 - show multicast router igmp, 630
 - summary-address, 353
 - timers throttle spf, 176
 - update-source loopback, 517
 - variance, 101–103
- community attribute (BGP), 507**
- comparing**
- BGP with other scalable routing protocols, 474
 - multicast and unicast, 594–595
 - network and neighbor command, 523
 - OSPF modes of operation, 203
 - OSPFv3 and OSPFv2, 672–675
 - routing protocols, 45–46
- configuration excises**
- backbone routers, configuring, 786–787
 - BBR1, configuring, 787–788, 790
 - BBR2, configuring, 791–793
 - BGP, 555–565
 - BGP path manipulation, 574–585
 - configuring and examining OSPF in single area, 206–219
 - configuring and tuning EIGRP, 145–155
 - configuring OSPF for multiple areas and Frame Relay nonbroadcast, 279–305
 - equipment wiring, 785–786
 - Frame-Switch, configuring, 794–797
 - full-mesh IBGP, 565–573
 - IPv6, configuring, 696–710
 - migration to classless routing protocol, 47–49, 51–62
 - redistribution, 449–465
 - required equipment, 781–783
 - setup diagram, 784–785
 - TFTP server setup, 783

configuring

- backbone routers for configuration
 - exercises, 786–787
- BGP, 512
 - EBGP multihop*, 519, 521
 - local preference*, 545–548
 - neighbor authentication*, 524–525
 - peer groups*, 512–514
 - sessions*, 514–516
 - source IP address*, 516–518
 - synchronization*, 526
 - verifying configuration*, 534–538
 - weight attribute*, 553
- DHCP, 431, 433
 - attribute inheritance*, 434
 - clients*, 447
 - verifying operation*, 447
- DHCP relay agents, 442–446
- DHCP servers, 434–439
 - example configuration*, 439–440
 - import options example*, 441–442
- distribute lists, 409–411
- dynamic routing, 28–29
- EIGRP, 92–93
 - default networks*, 95–96
 - example configuration*, 93–94
 - load balancing*, 100–103
 - manual summarization*, 98–100
 - MD5 authentication*, 109–114
 - neighbor authentication*, 107–108
 - on WANs*, 106–107
 - summarization*, 97
 - with wildcard masks, example configuration*, 94–95
- Integrated IS-IS, 346–348
- IPv6, 677
 - configuration exercises*, 696–710
 - stateless autoconfiguration*, 666–668
- IS-IS
 - route summarization*, 352–353
 - verifying configuration*, 354–355
- multicast group membership, 621
- ODR, 30–31
- OSPF, 179–180
 - default routes*, 245–248
 - interface priority*, 192
 - loopback interface router ID*, 186
 - LSDB overload protection*, 238–239
 - MD5 authentication*, 272–275

- multiarea*, 181
 - NSSAs*, 257–259
 - over Frame Relay*, 193
 - router ID*, 187
 - simple password authentication*, 267–270
 - single-area*, 181
 - stub areas*, 250–252
 - summarization on ABRs*, 242–244
 - summarization on ASBRs*, 243–245
 - totally stubby areas*, 252–254
 - verifying configuration*, 182–186
 - virtual links*, 261–266
- OSPF mode for NBMA networks
 - broadcast mode*, 195
 - nonbroadcast mode*, 196–198
 - point-to-multipoint mode*, 198–200
 - point-to-multipoint nonbroadcast mode*, 200
 - OSPFv3, 677–679
 - verifying configuration*, 680–688
 - PIM-SM, 620–621
 - redistribution, 388–390
 - default-metric command*, 399
 - example*, 401–404
 - into EIGRP*, 394–396
 - into IS-IS*, 397–398
 - into OSPF*, 392–394
 - into RIP*, 390–391
 - passive-interface command*, 399–400
 - verifying operation*, 430
 - RIP, 40–41
 - route maps, 416–418
 - static default routes, 26
 - static routes, 25
- controlling**
- redistribution with distribute lists, 412–413
 - routing updates, 405
 - with default routes*, 407
 - with distribute lists*, 408–411
 - with route maps*, 413–418
 - with static routes*, 406–407
- converged networks, 5–6**
- architectural frameworks, Cisco SONA, 7, 9
- convergence, 24**
- EIGRP
 - graceful shutdown*, 131–132
 - query scoping*, 121–124
 - forcing, 57

Core layer (hierarchical network model), 11
cost, 71
 changing, 350
 on high-bandwidth interfaces, calculating, 240
 OSPF, calculating, 168–169
external routes, 237
criteria for populating IP routing table, 44–45
CSNPs, 341
current successors. See successors

D

data architecture (Cisco Enterprise Architecture), 10
debug commands, verifying EIGRP operation, 133, 140–144
debug eigrp packets command, 140–142
debug ip bgp updates command, 538
debug ip eigrp command, 142–144
debug ip ospf adj commad, 204–205
debug ip ospf adj command, 205
debug ip ospf events command, 185–186
debug ip ospf packet command, 178
default networks (EIGRP), configuring, 95–96
default routes
 OSPF
configuring, 245–248
generating, 260
 routing updates, controlling, 407
default-information originate command, 246–248
default-metric command, 399
defining
 BGP advertised networks, 522–524
 BGP source address, 516–518
dense mode (PIM), 612
design principles for Integrated IS-IS, 315–316
designing OSPF networks, 228
Destination address field (IPv6), 655
DHCP (Dynamic Host Configuration Protocol)
 address bindings, 433–434
 attribute inheritance, 434
 clients, configuring, 447
 configuring, 431–433
 IPv6, stateless autoconfiguration, 666–668
 verifying configuration, 447
DHCP relay agents
 configuring, 442–446
 helper addresses, configuring, 442, 444
DHCP servers
 configuring, 434–439
 example configuration, 439–440
 import options example, 441–442
differences between OSPF and IS-IS, 321–323
Dijkstra, Edsger, 167
Dijkstra’s algorithm, 162
disabling
 autosummarization, 37
 BGP neighbors, 516
disadvantages of multicast, 596–597
discontiguous subnets, route summarization, 34
displaying
 active IGMP version, 607
 EIGRP neighbor table, 76
 IP multicast routing table, 622–623
 IS-IS topology database, 356–357
 OSPF LSDB information, 235–236
 OSPF adjacencies, 203–205
 PIM interface information, 623–625
distance command, 429
distance eigrp command, 423
distance vector routing protocols, 31, 474
 compared to BGP, 484–485
 RIP, configuring, 40–41
 routing by rumor, 163
distribute lists
 configuring, 409–411
 IP route filtering, 411–412
 redistribution, controlling, 412–413
 routing updates, controlling, 408
Distribution layer (hierarchical network model), 11
distribution trees, 611
 multicast notation, 614–615
DNS-ALG (DNS-application layer gateway), 694
DR (Designated Router), 166–167
DROTHERs, 167
DRs (Designated Routers), 338
 election process, 190–192
DSP (domain-specific part), 325

DUAL (Diffusing Update Algorithm), 67, 70, 86–91
dual stack, migrating from IPv4 to IPv6, 689–690
dynamic inbound soft resets, performing on BGP sessions, 528–529
dynamic routing, 24–26
 configuring, 28
 RIP, configuring, 29

E

EBGP (External Border Gateway Protocol)
 example configuration, 532–533
 next hop, 502
EBGP multihop, 519, 521
EGPs (Exterior Gateway Protocols), 469
EIGRP
 Active Process Enhancement feature, 120
 AD, 71, 83–84
 configuring, 92–95
 default networks, configuring, 95–96
 DUAL, 67, 70, 86–91
 external routes, 80
 FD, 71, 83–84
 features of, 67–69
 FS, 72, 84–85
requirements, 85–86
 in enterprise networks
graceful shutdown, 131–132
queries, 119
query range, limiting, 124–130
query scoping, 121–124
scalability, 117
SIA connections, preventing, 120
SIA state, 119–120
 initial route discovery process, 78–79
 internal routes, 80
 IPv6 support, 672
 link utilization, 103–104
 load balancing, configuring, 100–103
 MD5 authentication
configuring, 109–114
troubleshooting, 115–116
verifying configuration, 114
 metric, calculating, 80–83
 neighbor authentication
configuring, 107–108

neighbor discovery, 70
 neighbor table, 71–72, 75
 on WANs, example, 104–107
 packets, 74
hello, 74–75
 protocol-dependent modules, 70
 reliability, 77
RTP, 77–78
 route selection process, 80
 route summarization, 69
 routing table, 71
 successors, 71, 84–85
 summarization
configuring, 97
in enterprise networks, 117
manual summarization, configuring, 98–100
 summary routes, 80
 topology table, 71–73
 verifying operation, 132–135
with debug commands, 133, 140–144
with show commands, 132–140

eigrp stub command, 128

election process for DRs/BDRs, 190–191

enabling

BGP synchronization, 493

Integrated IS-IS on interfaces, 348

entering BGP configuration mode, 514

Enterprise Campus functional area, 14

Enterprise Composite Network Model, 13

functional areas, 13–15

routing protocols, 16–17

Enterprise Edge functional area, 15

enterprise networks

BGP, implementing, 554

Cisco Enterprise Architecture, 9–11

EIGRP

graceful shutdown, 131–132

queries, 119

query range, limiting, 124–130

query scoping, 121–124

scalability, 117

SIA connections, preventing, 120

SIA state, 119–120

summarization, 117

running BGP in, 475–476

equal-cost paths, support for on Cisco IOS Software, 28

ESHs (End System Hellos), 317
ES-IS (End System-to-Intermediate System), 316–317
established state (BGP), troubleshooting, 541
Ethernet interface IDs for IPv6, 660–661
examples
 of BGP, 529–532
 EBGP, 532–533
 full-mesh, 490–491
 IBGP, 532–533
 partial-mesh, 490–491
 of DHCP server configuration, 439–440
 server import options, 441–442
 of EIGRP configuration, 93–94
 with wildcard mask, 94–95
 of IS-IS routing, 331–333
 of redistribution using administrative distance, 425–430
exchange process, OSPF neighbor states, 173–175
exchange state, 174
exercises. See configuration exercises
expansion phases of Cisco IINs, 7
exstart state, 174
Extension headers field (IPv6), 655–656
external BGP neighbors, 486
external LSAs, 233
external networks, 138
external routes
 cost, calculating, 237
 EIGRP, 80
 summarization, 241

F

FD (feasible distance), 71, 83–84
feasibility conditions for EIGRP load balancing, 102
feasible routes, 101
features
 of Cisco IIN, 6
 of EIGRP, 67–69
 of IPv6, 650–653
fields
 of BGP open messages, 497
 of IPv6 header, 653–655
floating static routes, 43–44
flooding LSAs in multiaccess networks, 176

Flow label field (IPv6), 654
forcing
 convergence, 57
 EIGRP summarization, 99
frame-relay map clsns broadcast command, 337
FS (feasible successors), 72, 84–86
full-mesh BGP
 example of, 490–491
 TCP as transport layer, 491
full-mesh iBGP, 489
 configuration exercises, 565–573
full-mesh topologies, 193
functional areas of Enterprise Composite Network Model, 13–15

G

“G” bit, 660
generating
 default routes in OSPF domains, 245–248
 OSPF default routes, 260
global unicast addresses, 661
globally scoped IP addresses addresses, 598
going active on a route, 119
goodbye messages, 132
graceful shutdown, EIGRP, 131–132
group membership (IGMP), 604
 configuring, 621
 joining a group, 606
 leaving a group, 605
group-specific queries (IGMPv2), 603

H

H (handle), 76
hard resets, performing on BGP sessions, 527
header fields (IPv6), 653–655
 extension headers, 655–656
header fields of OSPF packets, 170–171
hello interval adjusting, 75
hello packets
 EIGRP, 74–75
 hello interval, adjusting, 75
 hold time, 75
 OSPF, 171–175

helper addresses, 442, 444
hexadecimal IPv6 address representation, 657–658
hierarchical network model, 11–13
hierarchical routing, OSPF, 226
history of IS-IS, 319–320
HODSP (high-order domain-specific part), 325
hold time, 75–76
Hop limit field (IPv6), 654
hub-and-spoke topologies, ODR, 29
 configuring, 30–31
Huitema, Christian, 320
hybrid routing protocols, 31
 EIGRP. *See* EIGRP

IANA (Internet Assigned Numbers Authority), 471, 597

IBGP

 example configuration, 532–533
 full mesh, 489
 configuration exercises, 565–573
 in nontransit AS, 489
 in transit AS, 488
 next hop, 502

idle state (BGP), troubleshooting, 540

IDRPs (Interdomain Routing Protocols), 470

IGMP, 602

 active version, displaying, 607
 multicast groups
 verifying, 627–628

IGMP snooping, 609

 verifying, 629–630

IGMPv1, 603

IGMPv2, 603–604

 group membership, 604
 groups, leaving, 605

IGMPv3 groups, joining, 606

ignore state (OSPF), 239

IGPs (Interior Gateway Protocols), 469

IHs (IS-IS Hellos), 317

IINs (Intelligent Information Networks), 5

 features of, 6
 phases of expansion, 7

implementing

 BGP in enterprise networks, 554

 IS-IS

in broadcast networks, 337–339

in NBMA networks, 337–340

import options example (DHCP servers), 441–442

influencing best path selection with administrative distance, 420–422

inherited DHCP parameters, 434

init state, 173

initial route discovery process (EIGRP), 78–79

injecting default routes into standard areas, 260

Integrated IS-IS, 314–315

 advantages of, 322

 configuring, 346–348

 design principles, 315–316

 enabling on interfaces, 348

 NSAP address structure, 324–326

interactive services layer (Cisco SONA), 8

inter-area routing, 329–330

interdomain routing with BGP, 471

interface identifiers (IPv6), 659

 Ethernet, 660–661

interface level (IS-IS), changing, 350

interfaces (OSPF), configuring priority, 192

internal BGP neighbors, 487

internal routers, 227

internal routes (EIGRP), 80

interpreting OSPF routing tables

 in standard areas, 255

 in stub areas, 255–256

 in totally stubby areas, 256–257

 LSDB, 234–236

intra-area routing, 318, 329–330

ip address secondary command, 377

IP addresses

 allocating in multiple routing protocol environments, 374–376

secondary addresses, configuring, 377

 for multicast, 597–598

Layer 2, 598–600

ip classless command, 34–35

ip default-network command, 95–96

ip helper-address command, 442–444

IP multicast routing table, displaying, 622–623**ip multicast-routing command, 620****ip ospf network command, 194–195****ip pim send-rp-discovery scope command, 621****IP route filtering with distribution lists, 411–412****IPv4, migrating to IPv6, 688–689**

dual stack, 689–690

tunneling, 690–694

IPv6

address representation, 657–658

address space, 651–652

need for increase in, 652–653

anycast addresses, 658, 663–664

available routing protocols, 669–670

*EIGRP, 672**IS-IS, 671**MP-BGP4, 672**OSPFv3, 671**RIPng, 670*

configuration exercises, 696–710

configuring, 677

extension headers, 655–656

features, 650–651

interface identifiers, 659

Ethernet, 660–661

migrating from IPv4, 688–689

*6-to-4 tunneling, 693–694**dual stacking, 689–690**manually configured tunnels, 691–692**tunneling, 690–694*

mobility, 668–669

MTU discovery, 656

multicast addresses, 658, 664–666

packet header, 653, 655

stateless autoconfiguration, 666, 668

static routing, 670

supported data-link layers, 659

supported routing protocols, OSPFv3, 675–688

translation mechanisms, 694–695

unicast addresses, 658

*global unicast addresses, 661***ipv6 unicast-routing command, 677****ISHS (Intermediate System Hellos), 317****IS-IS (Intermediate System-Intermediate System), 312–313. See also Integrated IS-IS**

area boundaries, 314

asymmetric routing, 332

comparing with OSPF, 319

differences with OSPF, 321–323

history of, 319–320

implementing in broadcast networks, 337–338

DIS selection, 338–339

implementing in NBMA networks, 337

*L1 and L2 IIHs, 340**L1 and L2 LSPs, 339*

inter-area routing, 329–330

interface level, changing, 350

intra-area routing, 329–330

IPv6 support, 671

L1 routers, 313

L1/L2 routers, 313

L2 routers, 313

LAN adjacencies, 343

LSDB synchronization, 341–342

LSPs, 335–336

flooding, 340–341

metric

*changing, 350**narrow, 316*

NSAP addresses, 324

*area addresses, 326**NET addresses, 328–329**system ID, 327–328*

optimizing, 349–352

PDUs, 334

route leaking, 333

route summarization, configuring, 352–353

router types, 329

routing examples, 331–333

routing levels, 312–313

similarities to OSPF, 320

topology database, displaying, 356–357

troubleshooting, show clns commands, 355

tuning, 350–352

verifying configuration, 354–355

WAN adjacencies, 343–344

wide metrics, 316

isis circuit-type command, 350**isis metric command, 350****ISO (International Organization for Standardization), 311**

ISPs, 471

- BGP, multihoming, 476–477
 - with default routes and partial table from all providers, 478–479
 - with default routes from all providers, 477–478
 - with full routes from all providers, 480

ISs (intermediate systems), 312

is-type command, 349

K-L

keepalive messages (BGP), 497–498

key chains, 109

L0 routing, 313, 318

L1 routing, 318, 329

L1/L2 routing, 313, 329

L2 routing, 313, 319, 329

L3 routing, 319

LACNIC (Latin American and Caribbean IP Address Regional Registry), 471

LAN adjacencies, 343

Layer 2 multicast addresses, 598–600

Layer 2 switches, 608

- multicast switching
 - CGMP, 608–609
 - IGMP snooping, 609

Layer 3 protocols, IGMP, 608

Leave Group message (IGMPv2), 604

limiting EIGRP query range, 124–130

link utilization, EIGRP, 103–104

link-state routing protocols, 31, 162, 474

- IS-IS, 312–313
 - comparing with OSPF, 319
 - differences with OSPF, 321–323
 - history of, 319–320
 - LAN adjacencies, 343
 - LSDB synchronization, 341–342
 - LSP flooding, 340–341
 - LSPs, 335–336
 - PDU, 334
 - routing examples, 331–333
 - routing levels, 312–313
 - similarities to OSPF, 320
 - WAN adjacencies, 343–344

LSAs, 161

OSPFv3

- comparing with OSPFv2, 672–675
- configuring, 677–679
- LSAs, 675–676
- verifying configuration, 680–688
- shopping mall map analogy, 162

link-state sequence numbers field, 177–179

load balancing, EIGRP, 100–103

loading state, 175

local network control block, 597

local preference (BGP), configuring, 545–548

local preference attribute (BGP), 506

local scope IP multicast addresses, 597

loopback interfaces, configuring router ID on OSPF, 186

LSAs, 161, 228–229

- flooding process, 176
- for OSPFv3, 675–676
- link-state sequence number field, 177–179
- Type 1, 230–231
- Type 2, 231
- Type 3, 231–232
- Type 4, 232–233
- Type 5, 233

LSDB (link-state database), 161, 227, 234

- information, displaying, 235–236
- synchronization on IS-IS, 341–342

LSPs, IS-IS, 335–336

- flooding, 340–341

LSRefreshTime, 177

LSUs (link-state updates), 168

M

MAC addresses, 598

managing routing protocol migration, 373–374, 378–379

manual binding, 433–434

manual summarization

- EIGRP, configuring, 98–100
- RIP, configuring, 40–41

manually configured tunnels, migration to IPv6, 691–692

many-to-many multicast applications, 595

maximum-paths command, 511

max-lsa command, 239

MBone (Multicast Backbone), 598

MD5 authentication

- configuring on BGP, 524–525
- configuring on EIGRP, 109–114
 - troubleshooting, 115–116*
 - verifying configuration, 114*
- configuring on OSPF, 272–275
- troubleshooting, 276–278
- verifying, 276

MED attribute (BGP), 507–508

- changing with route maps, 549–553
- IETF conformity, configuring, 510

messages, BGP

- keepalive messages, 497–498
- notification messages, 497–499
- open messages, 496
- update messages, 497

metrics, 27

- EIGRP, 71
 - calculating, 80–83*
- IS-IS, changing, 350
- narrow, 316
- OSPF, calculating, 167–169
- seed metrics, 384–386
- wide, 316

migrating

- from existing routing protocol, 373–374, 378–379
- from IPv4 to IPv6, 688–689
 - dual stack, 689–690*
 - tunneling, 690–694*
- to classless routing protocol, configuration exercise, 47–62

mobility of IPv6, 668–669**modifying**

- administrative distance, 423–424
- BGP next-hop attribute, 521–522

modules

- within Enterprise Campus functional area, 14
- within Service Provider Edge functional area, 16

MP-BGP4, IPv6 support, 672**MTU discovery (IPv6), 656****multiarea OSPF, configuring, 181****multicast**

- advantages of, 596
- disadvantages of, 596–597
- IGMP, 602
- IGMPv1, 603

IGMPv2, 603–604

- group membership, 604*
- groups, leaving, 605*

IGMPv3, joining groups, 606

IP addresses, 597–598

- Layer 2, 598, 600*

IP multicast routing table, displaying, 622–623

versus unicast, 594–595

multicast addresses (IPv6), 664–666**multicast distribution tree notation, 614–615****multicast groups, 593**

- verifying, 627–628

multicast IPv6 addresses, 658**multicast OSPF addresses, 177****multicast routing protocols, PIM, 610**

- dense mode, 612, 615–617
- displaying configured interface information, 623–625
- distribution trees, 611
- group membership, configuring, 621
- multicast distribution tree notation, 614–615
- RP information, troubleshooting, 625–626
- RPF, 611
- shared distribution trees, 614
- shared trees, 611
- source distribution trees, 612–613
- source trees, 611
- sparse-dense mode, 619–620
- sparse mode, 611, 617–621

multicast sessions, 600–602**multicast switching, 608**

- CGMP, 608–609
- IGMP snooping, 609

multihoming options for BGP, 476–477

- best path selection, 543–545
- multihoming with default routes and partial table from all providers, 478–479
- multihoming with default routes with all providers, 477–478
- multihoming with full routes from all providers, 480

multiple routing protocol environments

- IP address allocation, 374–376
 - secondary addresses, configuring, 377*

- redistribution, 379–381
 - administrative distance*, 383–384
 - best route selection*, 383
 - configuring*, 388–400
 - example of*, 401–404
 - performing*, 387
 - seed metrics*, 384–386

multipoint subinterfaces, 202

N

narrow metrics, 316

NBMA networks, 189

- IS-IS, implementing, 337
 - L1 and L2 IIHs*, 340
 - L1 and L2 LSPs*, 339

OSPF

- adjacency behavior*, 192
- broadcast mode, configuring*, 195
- modes of operation*, 194
- multipoint subinterfaces*, 202
- nonbroadcast mode, configuring*, 196–198
- point-to-point subinterfaces*, 201–202
- subinterfaces*, 200–201

- OSPF point-to-multipoint mode, configuring, 198–200

- OSPF point-to-multipoint nonbroadcast mode, configuring, 200

neighbor adjacencies (OSPF), establishing, 171–175

neighbor authentication

- BGP, configuring, 524–525
- EIGRP, configuring, 107–108

neighbor command, 523

neighbor discovery, EIGRP, 70

neighbor peer-group command, 513

neighbor relationships, BGP, 485–486

- BGP table, 495–496
- disabling, 516
- EBGP multihop, 519–521
- external neighbors, 486
- internal neighbors, 487

neighbor remote-as command, 515

neighbor states (BGP), 498

- idle, 540–541
- troubleshooting, 539

neighbor table (EIGRP), 71–72, 75

- displaying, 76

neighbor update-source command, 518

NET (network entity title), 324

NET addresses, 328–329

network command, 28, 181, 522–524

network LSAs, 231

networked infrastructure layer (Cisco SONA), 8

Next header field (IPv6), 654

next-hop attribute (BGP), 502, 505

- changing, 521–522

nonbroadcast mode (OSPF), 194

- configuring, 196–198

non-real-time applications, 595

nontransit AS, IBGP route propagation, 489

notification messages (BGP), 497

NSAPs (network service access points), 324

- area addresses, 326
- Integrated IS-IS NSAP address structure, 324–326
- NET addresses, 328–329
- system ID, 327–328

NSSAs (not-so-stubby areas), 249

- configuring, 257–259

O

ODR (on-demand routing), 29

- configuring, 30–31

one to many multicast applications, 595

one-way redistribution, 387

open messages (BGP), 496

optimizing IS-IS, 349–350, 352

optional attributes (BGP), 499

optional nontransitive BGP attributes, MED, 507–508

optional transitive BGP attributes, community, 507

origin attribute (BGP), 505

OSI model

- and ISO, 311
- L0 routing, 318
- L1 routing, 318
- L2 routing, 319
- L3 routing, 319
- PDU, 333

OSI (Open System Interconnection), 311**OSPF (Open Shortest Path First)**

- ABRs, 165–166, 227
- adjacencies, 166
 - displaying, 203–205*
- adjacency database, 163
- advantages of, 323
- areas, 164, 248–249
 - verifying configuration, 260*
- ASBRs, 227
- authentication
 - MD5 authentication, configuring, 272–275*
 - MD5 authentication, troubleshooting, 276–278*
 - MD5 authentication, verifying, 276*
 - simple password authentication, configuring, 267–270*
 - simple password authentication, troubleshooting, 270–272*
 - simple password authentication, verifying configuration, 270*
- backbone routers, 227
- BDRs, 166–167
- best path calculation, 236
- broadcast mode, configuring, 195
- broadcast networks, 189
 - adjacency behavior, 190–191*
- comparing with IS-IS, 319
- configuring, 179–180
- cost, calculating, 240
- default routes
 - configuring, 245–248*
 - generating, 260*
- design guidelines, 228
- differences with IS-IS, 321–323
- DRs, 166–167
- external route cost, calculating, 237
- hierarchical routing, 226
- in single area, configuring, 181
- interface priority, configuring, 192
- internal routers, 227
- link-state sequence numbers, 177–179
- loopback interfaces, configuring router ID, 186
- LSAs, 228–229
 - flooding, 176*
 - Type 1, 230–231*
 - Type 2, 231*
 - Type 3, 231–232*
 - Type 4, 232–233*
 - Type 5, 233*
- LSDB, 227, 234
 - information, displaying, 235–236*
 - overload protection, configuring, 238–239*
- metrics, calculating, 167–169
- modes of operation, comparing, 203
- multiarea, configuring, 181
- multicast addresses, 177
- NBMA networks, 189
 - adjacency behavior, 192*
 - modes of operation, 194*
- nonbroadcast mode, configuring, 196–198
- NSSAs, configuring, 257–259
- over Frame Relay
 - configuring, 193*
 - multipoint subinterfaces, 202*
 - point-to-point subinterfaces, 201–202*
 - subinterfaces, 200–201*
- packets, 169
 - header fields, 170–171*
 - hello, 171–175*
- point-to-multipoint mode, configuring, 198–200
- point-to-multipoint nonbroadcast mode, configuring, 200
- point-to-point networks, 189
 - adjacency behavior, 189–190*
- router designators, 236
- router IDs, 186
 - verifying, 188–189*
- similarities to IS-IS, 320
- standard areas, interpreting routing table, 255
- stub areas
 - configuring, 250–252*
 - routing table, interpreting, 255–256*
- summarization, 240–242
 - on ABRs, configuring, 242–244*
 - on ASBRs, configuring, 243–245*
- totally stubby areas
 - configuring, 252–254*
 - routing table, interpreting, 256–257*
- verifying configuration, 182
 - with debug ip ospf events command, 185–186*

- with *show ip ospf interface* command, 183–184
- with *show ip ospf neighbor* command, 184–185
- with *show ip route ospf* command, 183
- virtual links
 - configuring, 261–263
 - verifying configuration, 264–266

OSPFv3

- configuring, 677–679
 - verifying configuration, 680–688
- IPv6 support, 671
- LSAs, 675–676
- versus OSPFv2, 672–675

overload protection on OSPF LSDB, configuring, 238–239

P

packets

- ACKs, suppressing, 107
- EIGRP, 74
 - hello*, 74–75
 - reliable transport*, 77–78
- LSAs. *See* LSAs
- OSPF, 169
 - header fields*, 170–171
 - hello*, 171–175

parameters

- for area authentication command, 268
- for area nssa command, 258
- for area stub command, 251
- for area stub no-summary command, 253
- for area virtual-link command, 262
- for default-information originate command, 246
- for eigrp stub command, 128
- for eigrp stub command, 128
- for ip ospf message-digest-key command, 273
- for max-lsa command, 239
- for network command, 180
- for router ospf command, 179

partial-mesh topologies, 193

- BGP, example of, 490–491

passive routes (EIGRP), 73

passive-interface command, 399–400

path attribute of BGP update messages, 499

path manipulation (BGP) using route maps, 541–543

path vector characteristics (BGP), 481–483

Payload length field (IPv6), 654

PDUs (protocol data units), 167 333

- IS-IS, 334

peer groups (BGP)

- configuring, 512–514
- example configuration, 530–532
- resetting member connections, 514

phases of Cisco IIN expansion, 7

PIM (Protocol-Independent Multicast), 610

- dense mode, 612, 615–617
- displaying configured interface information, 623–625
- distribution trees, 611
- multicast distribution tree notation, 614–615
- RP information, troubleshooting, 625–626
- RPF, 611
- shared distribution trees, 614
- shared trees, 611
- source distribution trees, 612–613
- source trees, 611
- sparse mode, 611, 617–621
- sparse-dense mode, 612, 619–621
- configuring, 620–621

planning routing protocol migration, 378–379

point-to-multipoint mode (OSPF), 194

- configuring, 198–200

point-to-multipoint nonbroadcast mode (OSPF), configuring, 200

point-to-point networks, 189

- OSPF adjacency behavior, 189–190

point-to-point subinterfaces, 201–202

populating IP routing table, criteria for, 44–45

preemptive behavior, 338

prepending AS numbers, 501–502

preventing EIGRP SIA connections, 120

primary addresses, assigning, 377

protocol-dependent modules (EIGRP), 70

prune messages (PIM-DM), 615

pseudo-nodes, 339

PSNPs, 341

“pull” model, 612, 618

“push” model, 612

Q**queries (EIGRP)**

- in enterprise networks, 119
- range of, limiting, 124–125
 - with stub router, 126–130*
 - with summarization, 125–126*

query scoping, 121–124**query-interval response time (IGMPv2), 604****R****real-time applications, 595****recomputation (EIGRP), 73****redistribution, 379–381**

- administrative distance, 383–384
- best route selection, 383
- configuration exercises, 449–465
- configuring, 388–390
 - passive-interface command, 399–400*
- controlling with distribute lists, 412–413
- default-metric command, configuring, 399
- example of, 401, 403–404
- into EIGRP, configuring, 394–396
- into IS-IS, configuring, 397–398
- into OSPF, configuring, 392–394
- into RIP, configuring, 390–391
- performing, 387
- seed metrics, 384–386
- using administrative distance, example of, 425–430
- verifying configuration, 430
- with route maps, 419

regular areas, 164**reliable packet transport (EIGRP), 77**

- RTP, 77–78

remaining lifetime (IS-IS LSPs), 336**report suppression, 603****required Configuration Exercise equipment, 781–783****requirements**

- for converged networks, 6
- for EIGRP FS, 85–86

resetting

- BGP peer group member connections, 514
- BGP sessions, 526–529

restricting

- routing update traffic, 405
 - with default routes, 407*

with distribute lists, 408–411

with route maps, 413–418

with static routes, 406–407

RFC 1112, Host Extensions for IP Multicasting, 603**RFC 3266, Support for IPv6 in Session Description Protocol (SDP), 601****RFCs, BGP-related, 472****RIP (Routing Information Protocol)**

- configuring, 29, 40
- manual summarization, configuring, 40–41

RIPE NCC (Reséaux IP Européens Network Coordination Centre), 471**RIPng, IPv6 support, 670****RIPv1, characteristics, 39****RIPv2, characteristics, 39****RIRs (Regional Internet Registries), 471****route designators (OSPF), 236****route leaking, 333****route maps**

- BGP route manipulation, 541–543
- changing BGP local preference attribute, 547–549
- configuring, 416–418
- redistribution, 419
- routing feedback, avoiding, 419–420
- routing updates, controlling, 413–415
- setting BGP MED attribute, 549–553

route propagation, IBGP, 488–489**route redistribution, 227****route refreshing bgp sessions, 528–529****route selection process**

- EIGRP, 80
- for BGP, 509–511
 - maximum-paths command, 511*
 - with multihomed connections, 543–545*

route summarization

- autosummarization, 36
 - disabling, 37*
- in discontinuous subnets, 34
- IS-IS, configuring, 352–353

router bgp command, 514**router IDs, 186**

- selecting, 187
- verifying, 188–189

router isis command, 347**Router LSAs, 230–231****router odr command, 30**

router-id command, 187
routing by rumor, 163
routing domains, 380
routing feedback, avoiding with route maps, 419–420
routing levels (IS-IS), 312–313
routing protocols
 administrative distance, 42–43
 changing, 373–374, 378–379
 classful, 32–33
 classless, 32, 36
autosummarization, 36–37
 comparing, 45–46
 IPv6 supported, 669–670
EIGRP, 672
IS-IS, 671
MP-BGP4, 672
OSPFv3, 671
RIPng, 670
 metric, 27
 multiple protocol environments, redistribution, 379–404
 selecting for Enterprise Composite Network Model, 16–17

routing tables
 controlling, 405
with default routes, 407
with distribute lists, 408–411
with route maps, 413–418
with static routes, 406–407
 criteria for populating, 44–45
 EIGRP, 71–72

RPF (Reverse Path Forwarding), 611
RPs (rendezvous point), 611
 troubleshooting, 625–626

RTO (retransmit timeout), 76
RTP (Reliable Transport Protocol), 70, 77–78
RTSP (Real Time Streaming Protocol), 601

S

“SAFE” blueprint, 13–17
scalability of EIGRP, 117
SDP (Session Description Protocol), 600
seed metrics, 384–386
selecting
 BGP advertised networks, 522–524

OSPF mode for NBMA networks, 194–195
 OSPF router ID, 187

service password-encryption command, 268
service providers, 471
Session Directory, 600
sessions, BGP
 configuring, 514–516
 resetting, 526–529

shared distribution trees (PIM), 614
shared trees, 611
show cns commands, 355
show cns interface command, 359
show cns neighbors command, 358
show cns protocol command, troubleshooting IS-IS, 358
show cns route command, 356
show commands, verifying EIGRP operation, 132–140
show igmp statistics command, 630
show ip bgp command, 534–538
show ip bgp neighbors command, 529
show ip bgp rib-failure command, 536
show ip bgp summary command, 536–538
show ip eigrp interfaces command, 138
show ip eigrp neighbors command, 76
show ip eigrp topology command, 139–140
show ip eigrp traffic command, 140
show ip igmp group command, 604
show ip igmp interface command, 628
show ip mroute command, 623
show ip mroute command, 622
show ip ospf command, 188–189
show ip ospf database command, 234–235, 265–266
show ip ospf interface command, 183–184
show ip ospf neighbor command, 184–185
show ip ospf virtual-links command, 264
show ip pim neighbor command, 624
show ip pim rp command, 625
show ip protocols command, 137–138, 354
show ip route command, 26, 237
show ip route eigrp command, 135–136
show ip route isis command, 355
show ip route ospf command, 183
show ip rpf command, 626
show ipv6 interface command, 681–683
show ipv6 ospf command, 683–684
show ipv6 ospf database command, 686–687
show ipv6 ospf interface command, 683

- show ipv6 ospf neighbor command, 684–686**
- show ipv6 route command, 681**
- show isis database command, 356**
- show isis route command, 355**
- show isis topology command, 356–357**
- show multicast router igmp command, 630**
- SIA (stuck-in-active) connections, 119–120**
 - in enterprise networks, 119–120
- SIIT (Stateless IP/ICMP Translation), 694**
- similarities between OSPF and IS-IS, 320**
- simple password authentication**
 - configuring on OSPF, 267–270
 - troubleshooting, 270–272
 - verifying configuration, 270
- simulcasts, 595**
- SIN (ships-in-the-night) routing, 382**
- single-area OSPF, configuring, 181**
- sliding window (TCP), 485**
- SNPA (subnetwork point of attachment), 328**
- soft resets, performing on BGP sessions, 528–529**
- SONA (Service-Oriented Network Architecture), 5**
- source address (BGP), configuring, 516, 518**
- source address field (IPv6), 654**
- source distribution trees (PIM), 612–613**
- source trees, 611**
- sparse mode (PIM), 611**
- speakers (BGP), 486**
 - synchronization rule, 492–494
- split horizon, 79**
- SRTT (Smooth Round Trip Timer), 76**
- standard areas, 248**
 - default routes, injecting, 260
 - routing table, interpreting, 255
- star topologies, 193**
- stateless autoconfiguration (IPv6), 666–668**
- static routes, 23–24**
 - configuring, 25
 - floating static routes, 43–44
 - in IPv6, 670
 - routing updates, controlling, 406–407
 - static default routes, configuring, 26
- stub areas, 172, 248**
 - configuring, 250–252
 - routing table, interpreting, 255–256
- stub networks, 231**
- stub routers (EIGRP), limiting query range, 126–130**

- subinterfaces, 200–201**
 - multipoint, 202
 - point-to-point, 201–202
- successors, 71**
- summarization**
 - EIGRP
 - configuring, 97–100*
 - in enterprise networks, 117*
 - query range, limiting, 125–126*
 - in discontinuous subnets, 34
 - OSPF, 240–242
 - on ABRs, configuring, 242–244*
 - on ASBRs, configuring, 243–245*
- summary LSAs, 231–233**
- summary routes (EIGRP), 80**
- summary-address command, 353**
- suppressing EIGRP ACK packets, 107**
- switches supporting CGMP and IGMP snooping, 608**
- symmetric routing, 333**
- synchronization (BGP), configuring, 526**
- synchronization rule (BGP), 492–494, 572**
- system ID, 327–328**

T

- TCP (Transport Control Protocol)**
 - as BGP transport layer, 484–485
 - as transport layer in full-mesh BGP, 491
 - sliding window, 485
- teleworker architecture (Cisco Enterprise Architecture), 11**
- TFTP servers, setting up for Configuration Exercises, 783**
- third-party next hop, 503**
- timers throttle spf command, 176**
- TLV fields (IS-IS LSPs), 334–336**
- topology table (EIGRP), 71–73**
- totally stubby areas, 249**
 - configuring, 252–254
 - routing table, interpreting, 256–257
- Traffic class field (IPv6), 654**
- transit areas, 164**
- transit AS, IBGP route propagation, 488**
- translation mechanisms for IPv6, 694–695**
- transport layer of BGP, 484–485**

troubleshooting

- BGP, 534
 - neighbor states*, 539–541
 - show ip bgp command*, 534–538
- EIGRP, MD5 authentication, 115–116
- IS-IS, show clns commands, 355
- OSPF
 - MD5 authentication*, 276–278
 - simple password authentication*, 270–272
- PIM RP information, 625–626

tuning IS-IS, 350–352**tunneling, IPv4 migration to IPv6, 690–694**

- 6-to-4 tunnels, 693–694
- manually configured tunnels, 691–692

two-way adjacency state, 167**two-way redistribution, 387****Type 1 LSAs, 229–231****Type 10 LSAs, 230****Type 11 LSAs, 230****Type 2 LSAs, 229–231****Type 3 LSAs, 231–232****Type 4 LSAs, 229, 232–233****Type 5 LSAs, 229, 233****Type 6 LSAs, 229****Type 7 LSAs, 230****Type 8 LSAs, 230****type codes for BGP attributes, 501****Types 3 LSAs, 229****Types 9 LSAs, 230****U****UDP (User Datagram Protocol), 596****unicast versus multicast, 594–595****unicast IPv6 addresses, 658**

- global unicast addresses, 661

unicast routing protocols, 610**unidirectional links, 119****update messages (BGP), 497**

- path attribute, 499

update-source loopback command, 517**uptime, 76****V****variance command, 101–103****verifying**

- BGP configuration, 534–538
- DHCP configuration, 447
- EIGRP MD5 configuration, 114
- EIGRP operation, 132–135
 - with debug commands*, 133, 140–144
 - with show commands*, 132–140
- IGMP snooping, 629–630
- IS-IS configuration, 354–355
- multicast groups, 627–628
- OSPF configuration, 182
 - areas*, 260
 - MD5 authentication*, 276
 - router ID*, 188–189
 - simple password authentication*, 270
 - virtual links*, 264–266
 - with debug ip ospf events command*, 185–186
 - with show ip ospf interface command*, 183–184
 - with show ip ospf neighbor command*, 184–185
 - with show ip route ospf command*, 183
- OSPFv3 configuration, 680–688
- redistribution operation, 430

Version field (IPv6), 654**virtual links**

- configuring, 261–263
- verifying configuration, 264–266

VLSM (variable-length subnet masking), 242**W-X-Y-Z****WANs**

- adjacencies, 343–344
- Cisco Enterprise Architecture, 11
- EIGRP link utilization, 103–104
- point-to-point links, EIGRP configuration, 106–107

websites, CIDR report, 485**weight attribute (BGP), 500, 508–509**

- configuring, 553

well-known attributes (BGP), 499**well-known discretionary attributes (BGP),**

- local preference, 506**

818 well-known mandatory attributes (BGP)

well-known mandatory attributes (BGP)

AS-path, 501–502

next-hop, 502, 505

origin, 505

when to use BGP, 483–484

wide metrics, 316

**wiring, Configuration Exercise equipment,
785–786**