



## Numerics

---

### 911 services

- basic components of, 232–233
- mobile environment call processing, 234
- nonmobile environment call processing, 233

## A

---

- address management, 288
- address resolution, 289
- address signaling, 15, 48
- addressing, SIP, 322–323
- ad-hoc multipoint conferences, 306
- adjusting, voice quality, 129–132
- admission control, 289
- ADPCM (adaptive differential pulse code modulation), 71–72
- advanced call routing, 192
- a-law, 69
- ALI (automatic location identification), 232
- aliasing, 66
- allocating bandwidth, traffic engineering, 246–260
- AMIS-a (Audio Messaging Interchange Specification analog), 437
- analog interfaces, 27–28
  - call signaling, 18
  - local-loop signaling, 46
    - address signaling*, 48
    - information signaling*, 50
    - supervisory signaling*, 46–47
  - trunks, 50–52. *See also* trunks
- analog-to-digital encoding, 64–66
  - quantization, 68–69
  - sampling, 66
  - voice compression standards, 70–72
    - G.729 variants*, 73
- ANI (automatic number identification), 157, 232
- answer-address command, 159
- ATIS (Alliance for Telecommunications Industry Solutions), 373

attenuation, 129

auto discovery qos command, 388

auto qos command, 390

### AutoQoS

- configuring
  - on Catalyst switches*, 390–391
  - on Cisco IOS Software*, 386–388
- features, 384–386
- verifying configuration, 386

auxiliary VLANs, 34

availability, five nines, 197

## B

---

B2BUAs (back-to-back user agents), 203

background noise, 374

### bandwidth

- on VPNs, calculating, 270
- oversubscription, 391
- requirements, calculating, 236–242
- traffic engineering, 246–260

BBSM (Cisco Building Broadband Service Manager), 425

bearer channels, 194

best-effort traffic, 26

break segment, 16

BRI interfaces, 30

building scalable dial plans, 218

business case for VoIP, 191–193

busy hour traffic, calculating, 250

## C

---

CAC (Call Admission Control), 23, 202

- Cisco SAA CAC, configuring, 406–408
- implementing, 391–408
- MGCP CAC, 404–405
- MGCP RSVP CAC, configuring, 405
- SIP CAC, 399–401
  - call treatment, configuring*, 402
  - resource availability checking, configuring*, 403

**calculating**

- bandwidth requirements, 236–242
- busy hour traffic, 250
- busy hour trunk requirements, 251–258
- decibel levels, 128
- digital voice bit rate, 69
- traffic flow, 249
- VPN bandwidth requirements, 270

**call agents, MGCP, 334****call control, 281–289**

- call administration, 286, 289
- call setup, 285–286
- components of, 22–23
- endpoints, 282
- H.323, 289
  - call establishment*, 296
  - call flows*, 298, 301–305
  - Cisco-supported components*, 309
  - functional components*, 292
  - gatekeepers*, 295
  - gatekeepers, configuring*, 311–314
  - gateways, configuring*, 311–314
  - IP-to-IP gateways*, 294
  - multipoint conferences*, 296, 305–306
  - proxy servers*, 308–309
  - RAS messages*, 297–298
  - survivability strategies*, 307–308
  - troubleshooting*, 314–316

**MGCP**

- call agents*, 334
- call establishment*, 335
- call flows*, 337–338
- Cisco Unified CallManager, configuring*, 349–351
- Cisco-supported components*, 340
- configuring*, 341–342
- control commands*, 336
- endpoints*, 332–333
- gateways*, 334
- standards*, 331
- survivability strategies*, 339
- troubleshooting*, 352–353

**models, 282**

- centralized*, 25–26, 208–209
- comparing*, 354–357
- distributed*, 23, 208
- selecting*, 358–361

signaling between endpoints, 283

**SIP, 316–317**

- addressing*, 322–323
- applications*, 320
- call setup using proxy server*, 325
- call setup using redirect server*, 327
- Cisco-supported components*, 317–318, 328
- components*, 319
- dial peers, configuring*, 329–330
- direct call setup*, 324–325
- messages*, 321–322
- status codes*, 322
- survivability strategies*, 328
- troubleshooting*, 330
- UAs, configuring*, 329

**call density matrix, 255****call establishment, MGCP, 335****call flows, MGCP, 337–338****call legs, 143****call maintenance, 23****call processing in enterprise environments, 36****call setup process, 13, 145**

SIP, 325–327

**call signaling, 12**

- address signaling, 15
- information signaling, 16–17
- over analog and digital connections, 17
- supervisory signaling, 13–15

**call spike command, 395–396****call teardown, 23****call threshold command, 395****call treatment (SIP CAC)**

- configuring, 402–404
- triggers, disabling, 397

**call treatment command, 402****calling privileges, 219****call-progress indicators, 50****CAMA (centralized automated message**

**accounting), 233**

**campus LAN environments, 34–36****capacity planning, 256–257****CAS (channel associated signaling), 17, 74**

T1 CAS, 75–77

TE1 CAS, 77

**case studies, distributed network architectures, 209–210**

- Catalyst switches, configuring AutoQoS, 390–391**
- CBWFQ (Class-Based Weighted Fair Queuing), 382**
- CCS (common channel signaling), 17, 79**
  - DPNSS, 84
  - ISDN, 80–81
  - QSIG, 82–83
  - SIGTRAN, 84
  - SS7, 85
  - T-CCS, configuring, 121–123
- CDRs (call detail records), 287**
- CELP (code excited linear prediction), 71–73**
- centralized call control model, 25–26, 208–209**
- centralized network architectures, 201–203**
- centralized voice enterprise networks, 36**
- Centrex, 427**
- CER (Cisco Emergency Responder), 233**
- characteristics of default dial peer, 155–156**
- Cisco AS5400 Series Universal Gateway, VoiceXML, 435**
- Cisco ATA 186 Analog Telephone Adaptor, 317**
- Cisco BTS 10200 Softswitch, 318**
- Cisco fax relay, 87**
- Cisco IOS Software, configuring AutoQoS, 386–388**
- Cisco IP phones, 317**
- Cisco PIX and ASA Security Appliances, 318**
- Cisco SAA CAC, configuring, 406–408**
- Cisco SIP Proxy Server, 318**
- Cisco Unified CallManager, 36, 283, 422–424**
- Cisco Unity, 437**
- Cisco voice CODEC bandwidth calculator, 244–245**
- class-based policing, 382**
- CO (central office)**
  - switches, 5, 8–10
  - trunks, 51
- CODEC (coder-decoder), 27, 194–196**
  - complexity, 74
  - payload bandwidth requirements, 237
- coding, 375**
- collaborative computing, 433–434**
- commands**
  - answer address, 159
  - auto discovery qos, 388
  - auto qos, 390
  - call spike, 395–396
  - call threshold, 395
  - call treatment, 402
  - connection tie-line, 180
  - destination-pattern, 150
  - dial peer, 158
  - echo-cancel coverage, 132
  - forward-digits, 163
  - hunt group-related, 162
  - huntstop, 163
  - incoming called-number, 158
  - ip rsvp, 405
  - isdn-reject-value, 398
  - no-exp, 169
  - non-linear, 133
  - preference, 162–164
  - prefix, 170
  - rtr responder, 400, 406
  - session target, 150
  - show auto discovery qos, output, 389–390
  - show dialplan number, 161
- comparing**
  - call control models, 354–357
  - network architectures, 208–209
  - voice quality metrics, 380
- components of VoIP**
  - bearer channel control, 194
  - CODECs, 194
  - database services, 194
  - signaling, 193
- compression, 70–73**
- concurrent multiservice servers, 406**
- configuring**
  - AutoQoS
    - on Catalyst switches, 390–391*
    - on Cisco IOS Software, 386–388*
  - CAC
    - Cisco SAA CAC, 406–408*
    - MGCP RSVP CAC, 405*
  - call treatment, 402–404
  - cRTP, 200

dial peers  
*destination-pattern options*, 153–155  
*digit manipulation*, 168–174  
*POTS*, 147–149  
*VoIP*, 149–153

H.323

*gatekeepers*, 311–314  
*gateways*, 311–314

hunt groups, 161–163, 166

MGCP, 341–342

*Cisco Unified CallManager*, 349–351

PSTN Fallback, 400–401

resource availability checking, 401–402

SAA, Responder feature, 399

SIP

*dial peers*, 329–330

*UAs*, 329

voice ports, 109

*digital*, 117–118

*E&M ports*, 113–114

*echo cancellation*, 132–133

*FXO ports*, 112–113

*FXS ports*, 109–112

*ISDN*, 119

*special connection support*, 174–181

*T1 controllers*, 118–119

*T-CCS*, 121–123

*timers*, 115–117

*voice-quality tuning*, 129–132

**connection tie-line command, 180**

**connector blocks, 11**

**contact centers, 435–436**

**control commands, MGCP, 336**

**control complex (PBXs), 11**

**converged networks**

designing, preliminary steps, 3

VoIP, implementing, 197–198

**cRTP (Compressed Real-Time Transport Protocol), 383**

configuring, 200

**CS-ACELP (Conjugate Structure Algebraic CELP), 73**

**CTE (Cisco Content Transformation Engine), 426**

**CTI (computer telephony integration) applications, 431–432**

**current detectors, 9**

**customer support, 193**

## D

**database services, 194**

**decentralized multipoint conferences, 306**

**decibel levels, calculating, 128**

**default dial peer, characteristics of, 155–156**

**delay**

effect on voice quality, 375

G.114 recommendations, 377

**delay-start signaling, 60**

**designing converged networks, preliminary steps, 3**

**destination pattern matching, digit collection and analysis, 166–167**

**destination-pattern command, 150**

**destination-pattern options on dial peers, configuring, 153–155**

**DGKs (directory gatekeepers), 205**

**dial peer 0, 155**

**dial peer command, 158**

**dial peers, 145**

configuring, 329–330

destination pattern matching, digit collection and analysis, 166–167

destination-pattern options, configuring, 153–155

digit manipulation, 168

*practice scenario*, 173–174

*translation rules*, 169–172

hunt groups, configuring, 161, 163, 166

inbound, matching process, 157–160

outbound, matching process, 161

POTS, configuring, 147–149

VoIP, 146

*configuring*, 149–153

**dial plans, 218–220, 223**

number normalization, 229

scalable, attributes of, 227

technology prefixes, 231

**dial register, 9**

**dial-tone generator, 9**

**digit collection and analysis, 166–167**

**digit manipulation, 168, 173–174, 219**

translation rules, 169–172

**digit stripping, 166**  
**digital interfaces**  
     BRI, 30  
     call signaling, 18  
     E1, 30  
     T1, 29  
**digital voice bit rate, calculating, 69**  
**digital voice ports, configuring, 117–118**  
**direct call setup, SIP, 324–325**  
**disabling**  
     call treatment triggers, 397  
     digit stripping, 166  
**distributed call control model, 23, 208**  
**distributed network architectures, 203, 206**  
     case study, 209–210  
     H.323, 206  
     SIP, 206–208  
         *H.323, 205*  
**distributed voice enterprise networks, 39**  
**DNIS (dialed number identification service), 157**  
**DPNSS (Digital Private Network Signaling System), 84**  
**DS0 (Digital Service Level Zero), 332**  
**DTMF (dual-tone multifrequency), 15, 48**  
**dynamic access control process, 266**

## E

**E&M ports, configuring, 113–114**  
**E&M signaling, 28, 54–55**  
     delay-start, 60  
     four-wire Type I, 55  
     immediate-start, 60  
     wink-start, 58  
**E.164 standard, 218**  
**E1 CAS, 77**  
**E1 interfaces, 30**  
**echo, 61–62, 126, 373**  
**echo cancellation, 63**  
     configuring, 132–133  
**echo suppression, 63, 133**  
**echo-cancel coverage command, 132**  
**edge devices, 4**

**electrical characteristics of interfaces, impact on voice quality**  
     echo, 126  
     signal strength, 128–129  
**ELIN (emergency location identification number), 232**  
**emergency services, 911**  
     basic components of, 232–233  
     mobile environment call processing, 234  
     nonmobile environment call processing, 233  
**enabling**  
     modem transmission  
         *modem pass-through, 91*  
         *modem relay, 92–93*  
     VoIP fax, 87  
         *Cisco fax relay, 87*  
         *fax pass-through, 90–91*  
         *T.37 fax store and forward, 89–90*  
         *T.38 fax relay, 88*  
**encoding, 64**  
**encryption, 193**  
**endpoint addressing, 219**  
**endpoints, 282**  
     MGCP, 332–333  
     signaling between, 283  
**end-to-end calls, 144**  
**enterprise central gateways, interconnection requirements, 213–214**  
**enterprise networks, 36, 39**  
**ERL (emergency response location), 232**  
**Erlang B traffic model, 253**  
**Erlangs, 251**  
**expedite queuing, 385**  
**Extended Superframe format, 29, 75**

## F

**fax, enabling, 87**  
     Cisco fax relay, 87  
     fax pass-through, 90–91  
     T.37 fax store and forward, 89–90  
     T.38 fax relay, 88  
**fax pass-through, 90–91**  
**FDM (frequency-division multiplexing), 18**  
**features of AutoQoS, 384–386**  
**fidelity, 373**

- firewalls, 265–266
- five nines of availability, 197
- fixed delay, 375
- forward-digits command, 163
- FRF.12 (Frame Relay Forum 12), 383
- FX (foreign exchange) trunks, 51
- FXO (foreign exchange office) interfaces, 28
  - interfaces, 52
  - ports, configuring, 112–113
- FXO-to-FXS connections, 28
- FXS (foreign exchange station)
  - interface, 27–28, 52
  - ports, configuring, 109–112

## G

---

- G.114 recommendations for acceptable delay, 377
- G.729 compression, 73
- gatekeeper zone CAC, 408
- gatekeeper-routed call signaling, 302
- gatekeepers (H.323), 295
- gateways
  - MGCP, 334
    - fallback*, 339
  - selecting, 212
  - SIP, 319
- gathering voice traffic statistics, 247
- GKRCS (gatekeeper-routed call signaling), 203
- glare, 54
- GoS (grade of service), 248
- ground-start signaling, 18, 54

## H

---

- H.323, 195, 289
  - call establishment, 296
  - call flows, 298
    - with gatekeeper*, 301–302
    - with multiple gatekeepers*, 303–305
  - Cisco-supported components, 309
  - distributed network architectures, 203, 206
  - functional components, 292

- gatekeepers, 295
  - configuring*, 311–314
- gateways, configuring, 311–314
- IP-to-IP gateways, 294
- multipoint conferences, 296, 305–306
- proxy servers, 308–309
- RAS messages, 297–298
- survivability strategies, 307–308
- troubleshooting, 314–316
- hierarchical numbering plans, 223–224
- holler down circuits. *See* hoot and holler networks
- hoot and holler networks, 421
- hospitality networks, 425
- HSRP (Hot Standby Router Protocol), 307
- hunt groups, 143
  - commands, 162
  - configuring, 161–163, 166
- huntstop command, 163
- hybrid multipoint conferences, 306
- hybrid telephone systems, 12
- hysteresis, 395

## I

---

- identifying peak usage times, 249
- immediate-start signaling, 60
- implementing CAC, 391–408
- in-band signaling, 76
- inbound call legs, 144
- inbound dial peers, matching process, 157–160
- incoming called-number command, 158
- information signaling, 16–17, 50
- input gain, 129
- interconnecting VoIP protocols, 211
- interconnection requirements for gateways, 213–214
- interdigit timeout, 154
- interfaces
  - electrical characteristics, impact on voice quality
    - echo*, 126
    - signal strength*, 128–129
  - low-speed, 386

resource availability checking, configuring,  
401–402

**internal/public numbering plan integration,**  
224–226

**interoffice trunks, 51**

**interoperability of signaling formats, 86**

**IP Centrex, 427**

**IP phones, 31–32**

**ip rsvp bandwidth command, 405**

**IPCC (Cisco IP Contact Center), 436**

**IP-to-IP gateways, 294**

**ISDN (Integrated Services Digital Network),**  
80–81

configuring, 119

**isdn-reject-value command, 398**

## J-K-L

**jitter, 374**

**junkyard circuits. *See* hoot and holler networks**

**key telephone systems, 12**

**Layer 2 overhead requirements, 239**

**LDCELP (Low-Delay CELP), 73**

**link efficiency mechanisms, 412**

**listener echo, 127**

**LLQ (low latency queuing), 382**

**local calls, 104**

**local loop, 45–46**

**local loops, 4**

**local-loop signaling, 46**

address signaling, 48

information signaling, 50

supervisory signaling, 46–47

**location server (SIP), 320**

**locations CAC, 408**

**long-distance calling, toll bypass, 424**

**long-distance toll bypass, 192**

**loop start, 18**

**loop-start signaling, 53**

**low-speed interfaces, 386**

## M

**make segment, 16**

**matching process**

on inbound dial peers, 157–160

on outbound dial peers, 161

**measuring voice quality, metrics, 378–380**

**Megaco protocol, 195, 283**

**messages, SIP, 321–322**

**MGCP (Media Gateway Control Protocol), 195,**  
283

call agents, 334

call establishment, 335

call flows, 337–338

Cisco Unified CallManager, configuring,  
349–351

Cisco-supported components, 340

configuring, 341–342

control commands, 336

endpoints, 332–333

gateways, 334

*fallback, 339*

standards, 331

survivability strategies, 339

troubleshooting, 352–353

**MGCP CAC, 404–405**

**MGCP RSVP CAC, configuring, 405**

**MGCP switchover, 339**

**migration, 3**

**MLP (Multilink PPP), 383**

**mobile environment 911 call processing, 234**

**modem pass-through, enabling, 91**

**modem relay, enabling, 92–93**

**modem transmission**

**monitoring**

H.323, 314–316

MGCP, 352–353

voice ports, 123–125

**MOS (Mean Opinion Score), 378**

**MSAG (master street address guide), 232**

**mu-law, 69**

**multiplexing, 18–19**

**multipoint conferences, 296, 305–306**

**multitenant applications, 428–429**



## N

**native VLANs, 34**  
**network architectures, practice scenarios, 215–216**  
**non-linear command, 133**  
**nonmobile environment 911 call processing, 233**  
**number normalization, 229–231**  
**numbering plans, 218–220, 223**  
     hierarchical, 223–224  
     internal/public integration, 224–226  
**num-exp command, 169**  
**Nyquist Theorem, 66**

## O

**objectives of QoS, 381**  
     improving voice quality, 382–383  
     recognizing common design faults, 383–384  
**off hook supervisory signaling, 14**  
**off-net calls, 105**  
**on hook supervisory signaling, 14**  
**on-net calls, 104**  
**outbound call legs, 144**  
**outbound dial peers, matching process, 161**  
**output for show auto discovery qos command, 389–390**  
**overlapping number processing, 220**  
**oversampling, 66**  
**oversubscription, 391**

## P

**packet drops, 374**  
**packet size, effect on bandwidth, 237, 239**  
**packet telephony networks**  
     analog interfaces, 27–28  
     benefits of, 19–21  
     best-effort traffic, 26  
     call control  
         *centralized, 25–26*  
         *components of, 22–23*  
         *distributed, 23*  
     campus LAN environment, 34–36

    components of, 21  
     digital interfaces  
         *BRI, 30*  
         *E1, 30*  
         *T1, 29*  
     enterprise networks, 36, 39  
     IP phones, 31–32  
     real-time traffic, 26  
     service provider networks, 39  
**packet voice gateways, 318**  
**PBXs (private branch exchanges), 10–12**  
     switches, 5  
**PBX-to-PBX calls, 106**  
**PCM (pulse code modulation), 66, 71**  
**peak usage times, identifying, 249**  
**PESQ (Perceptual Evaluation of Speech Quality), 378**  
**PLAR (private line automatic ringdown)**  
     calls, 106  
     connections, configuring on voice ports, 175–176  
**PLAR-OPX connections, configuring on voice ports, 177–178**  
**postdial delay, 227**  
**POTS (plain old telephone service), 8**  
     dial peers, 146  
         *configuring, 147–149*  
         *hunt groups, configuring, 161–163, 166*  
         *inbound, matching process, 157–160*  
         *outbound, matching process, 161*  
**practice scenarios**  
     bandwidth, calculating, 258–260  
     network architectures, 215–216  
     Span Engineering dial plan worksheet, 228–229  
     Span Engineering numbering plans, 235–236  
     Span Engineering voice bandwidth requirements, 243  
     Span Engineering VoIP network security components, 270–271  
**preference command, 162–164**  
**prefix command, 170**  
**prepaid calling cards, 429–430**  
**private numbering plans, 219**  
**private trunk lines, 51**  
**propagation, 375**

proxy servers  
 H.323, 308–309  
 SIP, 320  
**PSQM (Perceptual Speech Quality Management)**, 378  
**PSTN Fallback**, configuring, 400–401  
**Public International Telecommunications Numbering Plans (E.164)**, 218  
 public/internal numbering plan integration, 224–226  
 pulse dialing, 15

## Q

**QoS (quality of service)**, objectives of, 381  
 improving voice quality, 382–383  
 recognizing common design faults, 383–384  
**QSIG**, 82–83  
 quantization, 64, 68–69

## R

**RAS messages**, 297–298  
**RBS (robbed-bit signaling)**, 76  
 real-time traffic, 26  
 redirect server (SIP), 320  
 registrar server (SIP), 320  
 regular expressions characters for translation rules, 171–172  
 remote site gateways, interconnection requirements, 213–214  
 resource availability checking, configuring, 401–402  
**Responder feature (SAA)**, configuring, 399  
 ring generator, 9  
 ring wire, 46  
 ringing patterns, 15  
 rotary groups. *See* hunt groups  
**RSVP (Resource Reservation Protocol)**, 383  
**RTCP (RTP Control Protocol)**, 196–198  
**RTP (Real-Time Transport Protocol)**, 195, 198  
**RTP header compression**, 200  
 rtr responder command, 400, 406  
**RTSP (Real Time Streaming Protocol)**, 283

## S

**SAA (Service Assurance Agent)**, configuring  
 Responder feature, 399  
 sampling, 64–66  
**SAP (Session Announcement Protocol)**, 283, 316  
 scalable dial plans, attributes, 227  
**SDP (Session Description Protocol)**, 207  
 security threats to VoIP networks, 263–264  
 security policies for VoIP networks, 261–262  
 selecting  
 call control models, 358–361  
 gateways, 212  
 selective routers, 233  
 serialization delay, packetization, 375  
 service provider networks, 39  
 session target command, 150  
 shout down circuits. *See* hoot and holler networks  
 show auto discovery qos command, output, 389–390  
 show dialplan number command, 161  
 sidetone, 374  
**signaling**, 281–289  
 call administration, 286, 289  
 call setup, 285–286  
 CAS, 74  
   *E1 CAS*, 77  
   *T1 CAS*, 75–77  
 CCS, 79  
   *DPNSS*, 84  
   *ISDN*, 80–81  
   *QSIG*, 82–83  
   *SIGTRAN*, 84  
   *SS7*, 85  
 endpoints, 282  
 format interoperability, 86  
**SIGTRAN**, 84  
**SIP (Session Initiation Protocol)**, 195, 207, 283, 316–317  
 addressing, 322–323  
 applications, 320  
 call setup using proxy server, 325  
 call setup using redirect server, 327  
 Cisco-supported components, 317–318, 328  
 components, 319  
 dial peers, configuring, 329–330  
 direct call setup, 324–325

- distributed network architectures, 205–208
  - messages, 321–322
  - status codes, 322
  - survivability strategies, 328
  - troubleshooting, 330
  - UAs, configuring, 329
  - SIP CAC, 399, 401**
    - call treatment, configuring, 402
    - resource availability checking, configuring, 402
  - SMTP (Simple Mail Transfer Protocol), 195**
  - source algorithms, 70**
  - special connection support, configuring on voice ports, 174–175**
    - PLAR, configuring on voice ports, 175–176
    - PLAR-OPX, configuring on voice ports, 177–178
    - tie-lines, configuring on voice ports, 180–181
    - trunks, configuring on voice ports, 178–179
  - SRST (Survivable Remote Site Telephony), 25, 203**
  - SS7 (Signaling System 7), 85**
  - standards bodies of call control models, 355**
  - stateful packet inspection, 265–266**
  - status codes, SIP, 322**
  - Super Frame format, 29, 75**
  - supervisory signaling, 13,–15, 46–47**
  - survivability strategies**
    - MGCP, 339
    - SIP, 328
  - switches, 8–10. See also Catalyst switches**
    - functions of, 9
    - PBXs, 10–2
    - trunks, 50, 52
      - E&M delay-start signaling, 60*
      - E&M immediate-start signaling, 60*
      - E&M signaling, 54–55*
      - E&M wink-start signaling, 58*
      - ground-start signaling, 54*
      - loop-start signaling, 53*
      - signaling standards, 52*
  - T1 framing standards, 75**
  - T1 CAS, 75–77**
  - T1 controllers, configuring, 118–119**
  - T1 interfaces, 29**
  - talker echo, 127**
  - T-CCS, configuring, 121–123**
  - TDM (time-division multiplexing), 18**
  - TDM hairpinning, 395**
  - technology prefixes, 231**
  - telephony networks**
    - call signaling, 12
      - address signaling, 15*
      - information signaling, 16–17*
      - over analog and digital connections, 17*
      - supervisory signaling, 13, 15*
    - CO switches, 8–10
    - components of
      - CO switch, 5*
      - edge devices, 4*
      - local loops, 4*
      - trunks, 6*
    - multiplexing, 18–19
    - packet-switched
      - benefits of, 19–21*
      - best-effort traffic, 26*
      - call control, 22–26*
      - components of, 21*
      - real-time traffic, 26*
    - PBXs, 10–2
  - terminal interface (PBXs), 10**
  - termination blocks, 11**
  - testing translation rules, 169**
  - threats to VoIP networks, 263–264**
  - tie-lines, 51, 180**
    - configuring on voice ports, 180–181
  - timers, configuring, 115–117**
  - tip wire, 46**
  - to/from traffic matrix, 255**
  - toll bypass, 424**
  - tone combinations, information signaling, 16**
  - traffic engineering, 246–260**
    - GoS, 248
  - traffic flow, calculating, 249**
  - traffic shaping, 382**
  - translation rules, 169–174**
    - regular expressions, 171–172
    - testing, 169
- 
- T.37 fax store and forward, 89–90**
  - T.38 fax relay, 88**

**TRIP (Telephony Routing over IP), 316****troubleshooting**

- H.323, 314–316
- MGCP, 352–353
- SIP, 330
- voice ports, 123–125

**trunk groups, 253****trunks, 6, 50, 52**

- busy hour requirements, calculating, 251–258
- capacity planning, 256–257
- connections, configuring on voice ports, 178–179
- signaling standards, 52
  - E&M delay-start signaling, 60*
  - E&M immediate-start signaling, 60*
  - E&M signaling, 54–55*
  - E&M wink-start signaling, 58*
  - ground-start signaling, 54*
  - loop-start signaling, 53*
- tie-lines, 180

**tuning voice ports, 129–132****Type I E&M signaling, 55****Type II E&M signaling, 57****Type III E&M signaling, 57****Type IV E&M signaling, 58**

## U-V

**UAs (user agents), 319**

- configuring, 329

**unified messaging, 192, 437****VAD (voice activity detection), 374**

- effect on bandwidth, 241–242

**variable delay, 375****verifying**

- AutoQoS configuration, 386
- voice port configuration, 124–125

**VIA (Cisco Voice Infrastructure and Applications), 430****voice applications, types of, 103–106, 109****voice dial peers. *See* dial peers****voice encoding schemes, analog-to-digital conversion, 64–66**

- quantization, 68–69
- sampling, 66
- voice compression standards, 70–73

**voice ports**

- applications, types of, 103
- configuring, 109
- digital, configuring, 117–118
- E&M ports, configuring, 113–114
- echo cancellation, configuring, 132–133
- FXO ports, configuring, 112–113
- FXS ports, configuring, 109–112
- ISDN, configuring, 119
- monitoring, 123–125
- special purpose connection support
  - configuring, 174–175*
  - PLAR, configuring, 175–176*
  - PLAR-OPX, configuring, 177–178*
  - tie-lines, configuring, 180–181*
  - trunks, configuring, 178–179*
- T1 controllers, configuring, 118–119
- T-CCS, configuring, 121–123
- timers, configuring, 115–117
- troubleshooting, 123–125
- tuning, 129–132

**voice protocol ports, 266****voice quality**

- factors affecting, 373
  - delay, 375*
  - jitter, 374*
- metrics, 378–380

**voice sample size**

- effect on bandwidth, 237–239

**voice traffic statistics, gathering, 247****voice VLANs, 34****voice-enabled web applications, 435****VoiceXML applications, 435****VoIP**

- 911 services, 232–233
  - mobile environment call processing, 234*
  - nonmobile environment call processing, 233*
- bandwidth requirements, calculating, 236–242
- business drivers, 191–193
- centralized network architectures, 201–202
  - characteristics of, 202–203*

- dial peers, 146
  - configuring, 149–153*
  - hunt groups, configuring, 161–163, 166*
- distributed network architectures, case study, 209–210
- functional components
  - bearer channel control, 194*
  - CODECs, 194*
  - database services, 194*
  - signaling, 193*
- H.323 distributed network architectures, 203, 206
- implementing in converged networks, 197–198
- network security policies, 261–262
- over VPNs, 267–268
- protocols, interconnecting, 211
- secure LAN design, 264
- SIP distributed network architectures, 205–208
- threats to, 263–264

**VoIP fax**

- Cisco fax relay, enabling, 87
- enabling, 87
- fax pass-through, enabling, 90–91
- T.37 fax store and forward, enabling, 89–90
- T.38 fax relay, enabling, 88

**VPN (virtual private network) bandwidth, calculating, 270**

**VRRP (Virtual Router Redundancy Protocol), 307**

## W-X-Y-Z

---

- waveform algorithms, 70
- WFQ (weighted fair queuing), 382
- wink-start signaling, 58
- WRED (weighted random early detection), 382