

Index

Numerics

- 1/2 pel motion estimation, 80–81
- 1/4 pel motion estimation, 80–81
- 4:2:0 format, 49
- 4:2:0 interstitial/co-sited format, 52
- 4:2:0 interstitial format, 52
- 4:4:4 format, 49
- 16-16 intra predication model (H.264), 347
- 30 FPS (frames per second), 236

A

- AC coefficients, 58
- acceptable lip sync skew tolerance, 224
- accessing focus in distributed conferencing architecture, 39
- ad hoc audio conferencing, 160–162
- ad hoc video conferencing, 4, 162
 - de-escalation, 169–171
 - escalation, 169–171
 - media control support, 172–173
 - media stream grouping, 169
 - multiple stream support, 168
 - SDP bandwidth information, 167–168
 - video SDP extensions, 163
 - H.261 codec attributes*, 164
 - H.263 attributes*, 164–166
 - H.264 attributes*, 166–167
- adaptive encoding
 - content-adaptive arithmetic coders, 72
 - content-adaptive VLC, 71
- adaptive frame/field coding, 101
- adaptive jitter buffer, 33
- address- and port-dependent filtering (NAT), 281
- administrative interface, 22

- advanced conferencing features, 42
 - lecture mode conferences, 41
 - panel mode conferences, 42
 - point-to-point-to-multipoint call escalation, 41
- AES (Advanced Encryption Standard), 299
- Alerting messages (H.225), 190
- ALGs (Application Layer Gateways), 274, 285
 - symmetric pinhole, 275
- analysis filters, 94–96
- annex C (H.263), 338
- annex L (H.263), 338–339
- annex N (H.263), 339
- annex P (H.263), 339
- annex Q (H.263), 340
- annex U (H.263), 340
- annex W (H.263), 341
- annex X (H.263), 342
- Apache web servers, 268
- APP packets, 120
- arithmetic coding, 66–68
- ARP cache poisoning, mitigating, 265
- artifacts, 238
- aspect ratio, 48
- asymmetric encryption, 300
 - certificates, 302–304
 - digital signatures, 301–302
 - public key encryption, 301
- AtoV, calculating, 253
- ATSC (Advanced Television Systems Committee), Report IS-191, 224
- audio conferencing, ad hoc, 160–162
- audio devices
 - packets, 233
 - presentation time, 225
- audio frames, 233

audio mixers, 31, 123–124
encoder, 36–37
jitter buffer, 33
network module, 32
RFC 2833 DTMF detection and generation module, 32
speaker selection module, 34
VAD module, 34
audio receiver path (receiver-side), sources of delay, 241–242
audio starvation, 242
audio streams, RTP sample stamps, 246–247
audio transmission path (sender-side), sources of delay, 233–234
authentication, single-sided, 315
authorization versus authentication, 258
availability, 258
AVC (Advanced Video Coding), 133, 342
AVT (Audio/Video Transport), development of RTP, 105

B

B2BUA (Back-2-Back UA), 146
backward motion vector, 83
basis functions, 57
B-frames, 46, 82–83
direct mode, 84
support for H.263 codecs, 334
support for H.264 codecs, 346
support for MPEG-4, Part 2 codecs, 356
temporal scalability, 85–86
bidirectional pinhole, 275
binary arithmetic coders, 68
bit rate as video codec performance criteria, 45
bitstream order, 84
block artifacting, 54

buffer-level managment, 247–250
Krl, calculating, 248
buttons
Conference, 4
RmLstC, 5

C

CA (certificate authority), 303
calculating
AtoV, 253
PSNR, 46
VTB, 253
Call Proceeding messages (H.225), 190
CAM table flooding, mitigating, 264
cameras, FECC, 17–18
canonical RTP/RTCP model, 244–245
capture devices, 225
CAs (certificate authorities), certificate enrollment process, 306–307
CDP (CRL Distribution Point), 307
centralized conferencing architecture, 37–38
centralized multipoint conferencing model, 157
certificate-based key distribution, 309
certificates, 302–304
endpoint authentication, 307
enrollment, 306–307
installing, 305–306
nonrepudiation, 309
reenrollment, 309
revoking, 307–309
CHC (Conversational High Compression) profile, 342
chroma channels, 49
chroma decimation, 49
chroma keying, 50
CIF (Common Interchange Format), 164

- CIF (Common Intermediate Format), 48**
- ciphertext, 299**
- Cisco IOS routers, configuring gatekeepers, 217**
- Cisco SCCP (Signaling Connection Control Part), 10**
- classes of SIP responses, 152–153**
- CLC ACK (Close Logical Channel Acknowledgment) message (H.245), 201**
- cleartext, 299**
- clipping, 61**
- Close Logical Channel message (H.245), 200**
- CNAME (Canonical Name), 113**
- CNG (comfort noise generation), 34**
- nonce (client nonces), 323**
- codecs**
 - encoders, transform processing, 55–59, 62–72
 - H.261, attributes, 164
 - H.263, 330
 - annex C*, 338
 - annex L*, 338–339
 - annex N*, 339
 - annex O scalability options*, 335–336
 - annex P*, 339
 - annex Q*, 340
 - annex U*, 340
 - annex W*, 341
 - annex X*, 342
 - attributes*, 164–166
 - B-frame support*, 334
 - coefficient prediction*, 332
 - data independence*, 337
 - DCT characteristics*, 332
 - entropy coding*, 333–334
 - key frame detection*, 132–133
 - MV characteristics*, 331
 - PB-frame support*, 334–335
 - quantization characteristics*, 333
 - RTP payload formats*, 126
 - slice support*, 336
 - source video formats*, 330
 - H.263 v1 mode-A, RTP payload formats, 127–128
 - H.263-1996, RTP payload formats, 127
 - H.263-1998, RTP payload formats, 130–132
 - H.263-2000, RTP payload formats, 130–132
 - H.263v1 mode C, RTP payload formats, 130
 - H.263v1 mode-B, RTP payload formats, 129–130
 - H.264, 342
 - attributes*, 166–167
 - B-frames*, 346
 - deblocking filter*, 352
 - entropy coding*, 351
 - error resilience*, 352–353
 - integer transform*, 349–350
 - intra predication mode*, 346–349
 - key frame detection*, 140
 - MV characteristics*, 345
 - MVs*, 345
 - packet structure*, 133–135
 - profiles*, 343–344
 - quantization characteristics*, 350–351
 - RTP payload formats*, 133–140
 - source video formats*, 344
 - hybrid, 72, 74
 - B-frames*, 82–86
 - encoder*, 76
 - error resiliency*, 88–91
 - motion estimation*, 77–82
 - P-frames*, 74
 - predicted loop*, 76–77
 - predictor loop parameters*, 86–88
 - lossy, 59
 - MPEG-4, Part 2, 353**
 - B-frame support*, 356
 - DCT coefficient prediction*, 355
 - entropy coding*, 356
 - MV characteristics*, 354–355
 - profiles*, 353–354
 - quantization methods*, 356
 - scalability*, 357
 - source video formats*, 354
 - scalable layered, 91–93**
 - SNR scalability*, 93
 - spatial scalability*, 93–95
 - temporal scalability*, 95–98
 - specifications**
 - frame rates*, 47–48
 - layout*, 47–48
 - levels*, 47
 - profiles*, 47
 - transcoding, 12**

video codecs, 100
HD-capable, 102
macroblocks, 101–102
video stream hierarchy, 100
 video coding process
post-processing, 54–55
preprocessing, 54
coefficient prediction of H.263, 332
coefficients, 57
color formats, 49, 52
colorspace conversion, 49
comfort noise, 34
common reference lip sync, 232
common reference timebase, 226
composition mode conferences, 13
conference control, 22
conference control layer, 25–26
conference scheduler, 25
conference URI, 39, 157
conferencing architectures
 centralized model, 37–38
 distributed model, 38
focus, accessing, 39
 full-mesh model, 41
conferencing systems
 components
conference control layer, 25–26
control plane, 26
media plane, 27
user interface, 23–24
Meet Me button, 24
VUI, 24
 receiver-side processing, 241
audio receiver path, sources of delay,
 241–242
 sender-side processing, 232
audio transmission path, sources of delay,
 233–234
video capture delay, sources of, 238,
 241
confidentiality, 257
 attacks, mitigating, 258
configuring
 gatekeepers
with Cisco IOS routers, 217
with CUCM, 215
 scheduled conferences, 6
 video conferencing security, 269–270
Connect messages (H.225), 190

connection hijacking attacks, mitigating, 262
connections, RTP, 106
constant quantization, 61
content-adaptive arithmetic coders, 72
content-adaptive processing, 71
content-adaptive VLC, 71
control plane, 22, 26
controlled meetings, 41
conventions for motion estimation, 81
CP (continuous presence) conferences, 13, 28
 floor control policy, 14
creating scheduled conferences, 7–8
crystal clocks, RTP time stamp accuracy, 246
CSRC (contributing source identifier)
 field, 110
CUCM (Cisco Unified CallManager),
 configuring gatekeepers, 215

D

data dependency isolation, error resiliency, 90
data independence on H.263, 337
data integrity, 299
data prioritization, error resiliency, 90–91
data resiliency for H.261, 329–330
DC coefficient, 58
DCT (discrete cosine transform), 56
 H.263 characteristics, 332
DCT coefficient prediction for MPEG-4, Part 2 codecs, 355
DCT scanning, 69–70
DDoS attacks, 259
deblocking filter for H.264, 352
declining lip sync as goal, 254
decode delay in receiver video path, 244
decoders on hybrid codecs, 72, 74
decoding order, 84
deep-packet rewrites, 285
de-escalation, 169–171
de-interlacing, 238
delay
 as video codec performance criteria, 46
 in audio receiver path, sources of, 241–242
 in audio transmission path, sources of, 233–234
 in video transmission path, sources of, 238, 241
delay accumulation, 226

delayed offer, 158
depletion of network bandwidth attacks,
 mitigating, 259
depletion of server resource attacks,
 mitigating, 260–261
desktop endpoint attacks, mitigating, 266
desktop endpoints, 16
detecting stream loss, 141–142
devices
 H.323, 208
gatekeepers, 209–213
gateways, 208
MCUs, 209
terminals, 208
 playout devices, 244
 transcoders in video conferencing
 network, 229
DHCP exhaustion, mitigating, 265
DHCP snooping, 266
dialogs (SIP), 148
dial-out meetings, 4
dial-out operations, 9
Diffie-Hellman key distribution, 310
digital signatures, 301–302
direct endpoint signaling (H.323), 211
direct mode, 84
direct signaling mode (H.323), 272
disabling unneeded services, 268
display order, 84
distributed conferencing architecture, 38
 focus, accessing, 39
distributed multipoint conferencing models,
 157
DoS attacks, mitigating
 connection hijacking, 262
 depletion of network bandwidth, 259
 depletion of server resources, 260–261
 malware, 262
 mitigating, 259
 replay attacks, 261
 RTP hijacking, 262
DTMF relay support indicators (H.245),
 193–194
DTMF support on SIP endpoints
 KPML, 159
 RFC 2833, 159
dual view video presentations, 43
Dynamic ARP, 265

E

E.164 Dialed Digits, 187
early offer, 158
ECS (Empty Capability Set) messages, 207
ejecting conference participants, 9
e-mail ID (H.323), 187
encoder module, 36–37
encoders, 55
 audio transmission path delay sources, 233
 on hybrid codecs, 76
transform processing, 55–57
adaptive encoding, 71–72
binary arithmetic coders, 68
coefficients, 58–59
DCT scanning, 69–70
entropy coding, 62–68
quantization, 59, 62
encoding delay, 241
encryption
 asymmetric encryption, 300
certificates, 302–304
digital signatures, 301–302
public key encryption, 301
 H.235, 313
H.235.1, 314–316
H.235.2, 316–319
H.235.3, 319
H.235.6, 319–320
 media encryption
MIKEY, 313
security-descriptions, 312
 SCCP, 324
 secure hashes, 299
 SIP encryption, 321
SIP-Digest, 321–324
 symmetric encryption, 299
key distribution, 309–310
endpoint aliasing (H.323), 187
endpoint infrastructure attacks,
 mitigating, 266
endpoint-dependent filtering (NAT), 281
endpoint-dependent mappings (NAT), 278
endpoint-independent filtering (NAT),
 279–281
endpoint-independent mappings (NAT), 278
endpoints, 146. *See also UAs (user agents)*
 authentication, 307
 desktop, 16

FECC, 17–18
 high-end systems, 16
 key distribution
certificate-based, 309
Diffie-Hellman, 310
 nonrepudiation, 309
 signaling security methods, 311–312
 SIP, DTMF support, 159
 supported annexes, 357
 supported bit rates, 357
 supported codecs, 357
 telepresence systems, 16
end-to-end path, 225
enrollment process (CAs), 306–307
entropy coding, 62–63
 arithmetic coding, 66–68
 for MPEG-4, Part 2 codecs, 356
 run-length coding, 63
 variable-length coding, 63–66
entropy coding for H.261, 329
entropy coding for H.263, 333–334
entropy coding for H.264, 351
entry IVR, 174
ephemeral ports, 272
error correction, 89
error resiliency, 88
 for H.264, 352–353
 using data dependency isolation, 90
 using data prioritization, 90–91
 using error correction, 89
 using redundant slices, 90
 using reversible VLCs, 89
 using start codes, 89
escalation, 169–171
evaluating codec video performance criteria
 bit rate, 45
 delay, 46
event subscriptions (SIP), 154–155

F

Fast Connect feature (H.323), 204–206
Fast Connect method (H.323v4), 273
FDCT (forward DCT), 56
features
 of reservationless conferences, 8–9
 of scheduled conferences, 8–9
FECC (far-end camera control), 17–18

filtering characteristics of NAT, 279
 address- and port-dependent filtering, 281
 endpoint-dependent filtering, 281
 endpoint-independent filtering, 279–281
firewalls
 NAT, 276–277
ALGs, 285
complications for VoIP protocols,
 284–285
filtering characteristics, 279–281
mapping characteristics, 278–279
symmetric NAT, 282–283
 PAT, 276–277
firmware attacks, mitigating, 266
fixed-point IDCT, 341
floater ports, 25
floor control, 42
 round-robin mode, 16
floor control policy, 14
Flow Control command (H.245), 202
FMO (flexible MB ordering), 100
focus, 26
 accesing, 39
form factors, 47–48
forward motion vector, 83
frame rates, 47–48
frames, switching, 99
frequency domain, 59
FU (fragmentation unit) packets, 138–140
full-mesh conferencing architecture, 41
FVU (fast video update), 172

G

gatekeepers (H.323), 209
 configuring
with Cisco IOS routers, 217
with CUCM, 215
 optional features, 211
 RAS signaling, 212–213
 required features, 209–210
 signaling options, 211–212
gateways (H.323), 208
GKRS (Gatekeeper-Routed Call Signaling mode), 273
GOBs (group of blocks), 172
gratuitous ARP replies, 265

H

- H.224, FECC applications, 17–18**
- H.225, 188**
 - connection establishment with gatekeepers, 217
 - messages, 188–189
 - Alerting*, 190
 - Call Proceeding*, 190
 - Connect*, 190
 - Notify*, 191
 - Release Complete*, 191
 - Setup*, 189–190
 - Setup ACK*, 190
- H.232v4, H.235, 313**
 - H.235.1, 314–316
 - H.235.2, 316–319
 - H.235.3, 319
 - H.235.6, 319–320
- H.235, 313**
 - H.235.1, 314–316
 - H.235.2, 316–319
 - H.235.3, 319
 - H.235.6, 319–320
- H.235.1, 314–316**
- H.235.2, 316–319**
- H.235.3, 319**
- H.235.6, 319–320**
- H.245, 191–192**
 - DTMF relay support indicators, 193–194
 - messages
 - CLC ACK*, 201
 - Close Logical Channel*, 200
 - Flow Control Command*, 202
 - Master Slave Determination*, 194
 - Miscellaneous command message*, 202–204
 - Miscellaneous Indication*, 202
 - OLC ACK Determination*, 200
 - Open Logical Channel*, 195, 198
 - Request Channel Close*, 201
 - Simultaneous Capability Set Set*, 193
 - Terminal Capability Set*, 192–193
 - User Input Indications Set*, 193
 - tunneling, 273
- H.261 codecs, 327**
 - attributes, 164
 - data resiliency, 329–330
 - entropy coding, 329

- MV characteristics, 328
- quantization characteristics, 328
- H.263 codecs, 330**
 - annex C, 338
 - annex L, 338–339
 - annex N, 339
 - annex O, scalability options, 335–336
 - annex P, 339
 - annex Q, 340
 - annex U, 340
 - annex W, 341
 - annex X, 342
 - attributes, 164–166
 - B-frame support, 334
 - coefficient prediction, 332
 - data independence, 337
 - DCT characteristics, 332
 - entropy coding, 333–334
 - key frame detection, 132–133
 - MV characteristics, 331
 - PB -frame support, 334–335
 - quantization characteristics, 333
 - RTP payload formats, 126
 - slice support, 336
 - source video formats, 330
- H.263 v1 mode-A codecs, RTP payload formats, 127–128**
- H.263 v1 mode-B codecs, RTP payload formats, 129–130**
- H.263 v1 mode-C codecs, RTP payload formats, 130**
- H.263-1996 codecs, RTP payload formats, 127**
- H.263-1998 codecs, RTP payload formats, 130–132**
- H.263-2000 codecs, RTP payload formats, 130–132**
- H.264 codecs, 342**
 - attributes, 166–167
 - B-frames, 346
 - deblocking filter, 352
 - entropy coding, 351
 - error resilience, 352–353
 - integer transform, 349–350
 - intra predication mode, 346, 348–349
 - key frame detection, 140
 - MV characteristics, 345
 - MVs, 345
 - packet structure, 133, 135
 - profile value and level, 198–200

- profiles, 343–344
- quantization characteristics, 350–351
- RTP payload formats, 133
 - FU packets*, 138–140
 - MTAP*, 136
 - SNALU*, 135
 - STAP*, 136
- source video formats, 344
- H.264-SVC**, 353
- H.323**, 185, 208, 270
 - call flow, 270
 - direct signaling mode, 272
 - endpoint aliasing, 187
 - Fast Connect feature, 204–206
 - FECC applications, 17–18
 - gatekeepers, 209
 - configuring with Cisco IOS routers*, 217
 - configuring with CUCM*, 215
 - mid-call bandwidth requests*, 214–215
 - optional features*, 211
 - RAS messages*, 213–214
 - RAS signaling*, 212–213
 - required features*, 209–210
 - signaling options*, 211–212
 - gateways, 208
 - GKRS mode, 273
 - H.225, 188
 - Alerting messages*, 190
 - Call Proceeding messages*, 190
 - Connect messages*, 190
 - connection establishment*, 217
 - message format*, 188–189
 - Notify messages*, 191
 - Release Complete messages*, 191
 - Setup ACK messages*, 190
 - Setup messages*, 189–190
- H.245, 191–192
 - CLC ACK messages*, 201
 - Close Logical Channel messages*, 200
 - Flow Control Command messages*, 202
 - Master-Slave Determination messages*, 194
 - Miscellaneous command messages*, 202–204
 - Miscellaneous Indication messages*, 202
- OLC ACK messages*, 200
- Open Logical Channel messages*, 195–198
- Request Channel Close messages*, 201
- Simultaneous Capability Set messages*, 193
- Terminal Capability Set messages*, 192–193
- User Input Indications messages*, 193
- logical channels, 195
- MCUs, 209
- messages, ECS, 207
- port usage, 273–275
- Slow Start mode, 204
- stack components, 186
- terminals, 208
- H.323 ID**, 187
- H.323v4, call flow**, 273
- hashes**, 300
 - message signing, 301
- HD (high definition) video**, 48–49
- HD-capable video codecs**, 102
- header extensions (RTP), 112
- headers of SIP requests, 151
- high-end conferencing endpoints, 16
- high-resolution video input, 237
- HMAC (hashed message authentication code)**, 300
- hold and resume during scheduled conferencing**, 178–179
- “Hollywood Squares” conferences, 13
- HSM (hardware security module)**, 306
- HTTP-Digest**, 268
- hybrid codecs**
 - B-frames, 82–83
 - direct mode*, 84
 - temporal scalability*, 85–86
 - decoder, 72–74
 - encoder, 76
 - error resiliency, 88
 - using data dependency isolation*, 90
 - using data prioritization*, 90–91
 - using error correction*, 89
 - using redundant slices*, 90
 - using reversible VLCs*, 89
 - using start codes*, 89

motion estimation, 77–80
1/2 pel motion estimation, 80–81
1/4 pel motion estimation, 80–81
conventions for, 81
overlapped blocked motion compensation, 81–82
P-frames, 74
predictor loop, 76–77
parameters, 86–88

I

ICE (Interactive Connectivity Establishment), 296–299
IDCT (inverse DCT), 56
I-frames, 55
image passthrough, 12, 41
in-conference controls, 8
dial-out operations, 9
muting and ejecting participants, 9
of scheduled conferencing, 177
sidebar conferences, 9
talk-over mode, 9
whiteboard collaboration, 9
in-dialog event subscriptions (SIP), 154
informational responses (SIP), 152
informative recommendations, 77
insecure services, disabling, 268
installing certificates, 305–306
integer transform (H.264), 349–350
integrity, 258
interlaced video signals, 48
interlacing, 236
intra predication mode for H.264 codecs, 346–349
intraframes (I-frames), 55
IPB patterns, 85
IPsec, 311
ITU (International Telecommunication Union), 10
IVR (Interactive Voice Response), 24

J

jitter buffer, 33
audio starvation, 242
joining
reservationless conferences, 8
scheduled conferences, 8

K

key distribution, 309
certificate-based, 309
Diffie-Hellman, 310
key frame detection
in H.263, 132–133
in H.264, 140
kiosk-quality lip sync, 232
KPML (Key Press Markup Language), 159

L

Layer 2 attacks, mitigating, 264
layered codecs, 91, 93
SNR scalability, 93
spatial scalability, 93–95
temporal scalability, 95–98
layout, 13
floor control policy, 14
LCN (logical channel number), 195
lecture mode conferences, 15, 41
levels, 47
lip sync, 223
as goal, declining, 254
Common Reference lip sync, 232
kiosk-quality, 232
Poor Man's lip sync, 230
offset slider of doom, 231
skew
acceptable tolerance, 224
delay accumulation, 226
measuring, 225–226
network delay, sources of, 228–229
lossy decoding, 54
low-resolution video input, 237

M

macroblocks, 101–102, 172
malleable playout devices, 244
malware, 262
mapping characteristics of NAT, 278–279
matrix quantization, 61
MC (multipoint controller), 10
MCTF (motion-compensated temporal filtering), 353
MCUs (multipoint control units), 9, 26, 209
 MC, 10
 service prefixes, 219–220
 transrating, 12
measuring
 resolution, 236
 skew, 225
media control support for ad hoc video conferencing, 172–173
media encryption
 MIKEY, 313
 security-descriptions, 312
media multiplexing, 294
media plane, 22, 27
 audio mixer, 31
 encoder, 36–37
 jitter buffer, 33
 network module, 32
 RFC 2833 DTMF detection and generation module, 32
 speaker selection module, 34
 VAD module, 34
 player/recorder, 27
 video mixer/compositor, 27
 video transcoder, 30
 video transrater, 28–30
media stream grouping for ad hoc video conferencing, 169
media synchronization using RTCP, 252–254
media-level parameters (SDP), 156
Meet Me button, 24
Meet Me conferences, 5
meeting ID, 7
message signing, 301
messages
 H.225, 188–189
 Alerting, 190
 Call Proceeding, 190
 Connect, 190

Notify, 191
Release Complete, 191
Setup, 189–190
Setup ACK, 190
H.323
 ECS, 207
 RAS messages, 213–214
SIP, 149
 notify, 155
 requests, 149–151
 responses, 152–153
 SUBSCRIBE, 155
microflow policing, 259
Microsoft DirectX
 render filters, 253
 source filters, 252
Microsoft IIS web servers, 268
mid-call bandwidth requests (H.323), 214–215
MIKEY (Multimedia Internet KEYing), 313
Miscellaneous command messages (H.245), 202–204
Miscellaneous Indication messages (H.245), 202
mitigating security threats
 confidentiality attacks, 258
 desktop endpoint attacks, 266
 DoS attacks, 259
 connection hijacking, 262
 depletion of network bandwidth, 259
 depletion of server resources, 260–261
 malware, 262
 replay attacks, 261
 RTP hijacking, 262
 endpoint infrastructure attacks, 266
 firmware attacks, 266
 MitM attacks, 263
 network infrastructure attacks, 263
 ARP cache poisoning, 265
 CAM table flooding, 264
 DHCP exhaustion, 265
 Layer 2 attacks, 264
 reconnaissance attacks, 264
 rogue DHCP servers, 266
 rogue configuration files, 267
 server attacks, 267
 port-based attacks, 267
 unneeded or insecure services, 268
 web server vulnerabilities, 268
 theft of service, 262

- MitM (Man in the Middle) attacks,**
 - mitigating,** 263
- MobileUIM,** 187
- motion compensation,** 73
- motion estimation,** 77–80
 - 1/2 pel motion estimation, 80–81
 - 1/4 pel motion estimation, 80–81
 - conventions, 81
 - overlapped block motion compensation, 81–82
- MPs (multipoint processors),** 10
- MPEG2 program stream,** 227
- MPEG-4, Part 2 codec,** 353
 - B-frame support, 356
 - DCT coefficient prediction, 355
 - entropy coding, 356
 - MV characteristics, 354–355
 - profiles, 353–354
 - quantization methods, 356
 - scalability, 357
 - source video formats, 354
- MSD (Master-Slave Determination) messages (H.245),** 194
- MSE (mean squared error),** 46
- MTAP (multi-time aggregation packet),** 136–138
- MTPs (media termination points),** 120–121
- multipass coding,** 46
- multiple stream support for ad hoc video conferencing,** 168
- multipoint conferencing models (SIP),** 157
- muting and ejecting participants feature,** 9
- muting during scheduled conferencing,** 179
- MV (motion vector) characteristics**
 - of H.261 codecs, 328
 - of H.263 codecs, 331
 - of H.264 codecs, 345
 - of MPEG-4, Part 2 codecs, 354–355
- address- and port-dependent filtering,** 281
- endpoint-dependent filtering,** 281
- endpoint-independent filtering,** 279–281
- mapping characteristics,** 278–279
- symmetric NAT,** 282–283
- NAT/FW (NAT/firewall traversal),** 270
 - ICE,** 298–299
 - solution requirements,** 285–286
 - H.460 solution,** 289
 - H.460.17 solution,** 290–291
 - H.460.18 solution,** 291–93
 - H.460.19 solution,** 293–294
 - IP-IP gateway inside firewall solution,** 288–289
 - ISDN gateway solutions,** 287
 - UPnP solutions,** 288
 - VPN solutions,** 287
 - STUN,** 296
 - TURN,** 297–298
- network (IP/UDP) module,** 32
- network delay, sources of,** 228–229
- network infrastructure attacks, mitigating**
 - ARP cache poisoning, 265
 - CAM table flooding, 264
 - DHCP exhaustion, 265
 - Layer 2 attacks, 264
 - mitigating, 263
 - reconnaissance attacks, 264
 - rogue DHCP servers, 266
- nonce count,** 322
- nonmalleable playout devices,** 244
- nonrepudiation,** 309
- Notify messages (H.225),** 191
- NOTIFY messages (SIP),** 155
- NTP (Network Time Protocol),** 250
- NTSC (National Television Systems Committee),** 235

N

- N-1 summation,** 31
- N-array arithmetic coder,** 68
- NAT (Network Address Translation),** 276–277
 - ALGs, 285
 - bindings, 277
 - complications for VoIP protocols, 284–285
 - filtering characteristics, 279

O

- OCSP (Online Certificate Status Protocol),** 308
- octets in RTP header,** 108
- offline coding,** 46
- offset slider of doom,** 231

OLC (Open Logical Channel) messages, 195
 fields, 197
 for audio streams, 195
 for H.264 streams, 198
 for video, 195

OLC ACK (Open Logical Channel Acknowledgment) messages, 200

open meetings, 41

open-ended meetings, 6

optional H.263 codec parameters, 165

optional H.323 gatekeeper features, 211

outdial feature of scheduled conferencing, 179

out-of-dialog event subscriptions (SIP), 154

overbooking, 7, 25

overlapped block motion compensation, 81–82

P

P-frames, 73–74

packetization delay in receiver video path, 243

packets
 audio device packets, 233
 H.264, 133–135
 RTCP, 113–114
 APP, 120
 BYE, 119
 RRs, 116–117
 SDES, 117–118
 SRs, 114–116

PAL (Phase-Alternating Line), 235

panel mode conferences, 42

PAT (Port Address Translation), 276–277

payload header field (RTP), 110–111

payload type field (RTP), 108

PB-frame support for H.263, 334–335

performance of video codecs, evaluating, 46
 bit rate, 45
 delay, 46

picture number order, 84

pixels, 48
 1/2 pel motion estimation, 80–81
 1/4 pel motion estimation, 80–81
 blocks, 54

PKI (public key infrastructure), 301
 CA certificate installation, 305–306
 CA enrollment, 306–307

certificate revocation, 307, 309
 endpoint authentication, 307
 nonrepudiation, 309
 reenrollment, 309

layout delay in receiver video path, 244

layout devices, 244

PLC (packet loss concealment), 242

PlusType header, 132

point-to-point-to-multipoint call
 escalation, 41

Poor Man's lip sync, 230
 offset slider of doom, 231

port numbers, RTP, 111

port security, 265
 H.323, 270
 call flow, 270
 port usage, 273–275
 H.323v4, call flow, 273
 SCCP, port usage, 275
 SIP, port usage, 275

port-based attacks, mitigating, 267

post-processing of video signals, 54–55

predefined service prefixes, 219–220

predicted frame, 73

predicted frames (P-frames), 73–74

predicted loop, 76–77

predictor loop, parameters, 86–88

preprocessing of video signals, 52, 54

presentation devices, 225

presentation modes, 28

presentation time, 225

presentation windows, text overlay, 18

preset port numbers, 276

profile value (H.264), 198–200

profiles, 47
 for H.264 codecs, 343–344
 for MPEG-4, Part 2 codecs, 353–354

progressive scan, 48

provisional responses (SIP), 152

proxy server, 146

PSNR (peak signal-to-noise ratio), 45
 calculating, 46

public mapped address, 276

pyramid coding, 93

Q

QCIF (Quarter CIF), 164
QoS (quality of service) conferencing support, 180–82
quadrate view video presentations, 43
quantization, 59, 62
 H.261 characteristics, 328
 H.263 characteristics, 333
 H.264 characteristics, 350–351
 MPEG-4, Part 2 codecs, methods of, 356
 step size, 60
quantization levels, 60

R

RAS messages (H.323), 213–214
RAS signaling (H.323), 212–213
receiver-side processing, 241
reconnaissance attacks, mitigating, 264
reconstructed images, 74
record routing (SIP), 153
redirect servers, 147
redundant slices, error resiliency, 90
reenrollment, 309
reference frames, 73
reflexive transport addresses, 276
registrars, 147
Release Complete messages (H.225), 191
render filters, 253
replay attacks, mitigating, 261
Request Channel Close message (H.245), 201
requests, SIP, 149
 components of, 150–151
required H.323 gatekeeper features, 209–210
reservationless conferences, 5
 in-conference controls, 8
dial-out operations, 9
muting and ejecting participants, 9
sidebar conferences, 9
talk-over mode, 9
whiteboard collaboration, 9
 joining, 8
reservations, 6
resolution, 48
 4:2:0 format, 49
 4:2:0 interstitial/co-sited format, 52
 4:2:0 interstitial format, 52

4:4:4 format, 49
 measuring, 236
resource reservation, 7
response codes (SIP), 153
 classes of, 152–153
reverse pinhole, 275
reversible VLCs, error resiliency, 89
RFC 2833, DTMF detection and generation module, 32
RGB color format, 49
RmLstC button, 5
rogue configuration, mitigating, 267
rogue DHCP servers, mitigating, 266
roll call (scheduled conferencing), 177
round-robin mode, 16
RRs (receiver reports), 116–117
RSVP (Resource Reservation Protocol), conferencing support, 180, 182
RTCP (Real-Time Transport Control Protocol), 27, 113
 media synchronization, 252–254
 packets, 113
APP, 120
BYE, 119
format, 114
forming, 251–252
RRs, 116–117
RTCP BYE, 119
SDES, 117–118
SRs, 114–116
 time base correlation, 250–252
RTP (Real-time Transport Protocol), 27, 105
 buffer-level management, 247–250
 conference system devices
RTP mixers, 123–124
translators, 120–122
video switcher, 124–126
 connections, 106
 destination ports, 106
 development, 105
 header extensions, 112
 header fields, 108
CSRC field, 110
payload, 111
payload header, 110
payload type field, 108
sequence number field, 109
SSRC field, 110
time stamp field, 109–110

hijacking attacks, mitigating, 262
 packetization, 36–37, 241
as audio transmission path delay source, 234
as source of video path delay, 241
 payload formats, H.263 codecs, 126, 132–133
H.263-1996 codecs, 127
H.263-1998 codecs, 130–132
H.263-2000 codecs, 130–132
H.263v1 mode-A codecs, 127–128
H.263v1 mode-B codecs, 129–130
H.263v1 mode-C codecs, 130
H.264 codecs, 133–140
 port numbers, 111
 SSRC collisions, 111
 stream loss, detecting, 141–142
 time stamps, 246–247
RTP mixers, 123
 audio mixers, 123–124
 video MCU, 124
RTPCP (RTP Control Protocol), 105
run-length coding, 63

S

scalability options
 on H.263 codecs, 335–336
 on MPEG-4, Part 2 codecs, 357
scalable layered codecs, 91–93
 SNR scalability, 93
 spatial scalability, 93–95
 temporal scalability, 95–98
SCCP (Skinny Client Control Protocol)
 encryption, 324
 port usage, 275
scheduled conferences, 6, 160, 173, 177
 configuring, 6
 creating, 7–8
 entry IVR, 174
 hold and resume, 178–179
 in-conference features, 8–9, 177
 joining, 8
 muting, 179
 outdial, 179
 roll call, 177
 unmuting, 179

SD (standard definition) video, 48–49
SDES (source description), 117–118
SDP (Session Description Protocol), 155
 bandwidth information, 167–168
 media-level parameters, 156
 session-level parameters, 155
 video extensions, 163
H.261 codec attributes, 164
H.263 codec attributes, 164–166
H.264 codec attributes, 166–167
SECAM (sequential couleur a memoire), 235
secure hashes, 299
security, 257. *See also port security*
 configuring, 269–270
 encryption
asymmetric encryption, 300–304
SCCP encryption, 324
secure hashes, 299
SIP encryption, 321–324
symmetric encryption, 299
 threats, mitigating
confidentiality attacks, 258
desktop endpoint attacks, 266
DoS attacks, 259–262
endpoint infrastructure attacks, 266
firmware attacks, 266
MitM attacks, 263
network infrastructure attacks, 263–266
rogue configuration files, 267
server attacks, 267–268
theft of service, 262
security-descriptions, 312
sender-side processing, 232
 audio receiver path delay, sources of, 241–242
 audio transmission path delay, sources of, 233–234
 video capture delay, sources of, 238
encoding delay, 241
sequence number field (RTP), 109
server attacks, mitigating, 267
 port-based attacks, 267
 web server vulnerabilities, 268
service prefixes, 219–220
session-level parameters (SDP), 155
Setup ACK messages (H.225), 190
Setup messages (H.225), 189–190
sidebar conferences, 9

- SI-frames, 99**
- signaling protocols**
 - H.323, 185, 208
 - ECS message*, 207
 - endpoint aliasing*, 187
 - Fast Connect feature*, 204–206
 - gatekeepers*, 209–215
 - gateways*, 208
 - H.225 call signaling*, 188–191
 - H.225 control protocol*, 193
 - H.245 control protocol*, 191–204
 - MCUs*, 209
 - RAS messages*, 213–214
 - stack components*, 186
 - terminals*, 208
 - SIP, 145
 - conferencing elements*, 157–159
 - dialogs*, 148
 - messages*, 149
 - multipoint conferencing models*, 157
 - proxy server*, 146
 - record routing*, 153–155
 - redirect server*, 147
 - registrars*, 147
 - requests*, 149–151
 - resource reservation support*, 180–182
 - responses*, 152–153
 - scheduled conferencing*, 173–174, 177–179
 - transactions*, 148
 - UAs*, 146
 - signal-to-noise ratio as video codec performance criteria**, 45
 - Simultaneous Capability Set messages (H.245), 193**
 - single view video presentations**, 43
 - single-sided authentication**, 315
 - SIP (Session Initiation Protocol), 145**
 - conferencing elements
 - conference URI*, 157
 - delayed offer*, 158
 - DTMF support*, 159
 - early offer*, 158
 - dialogs, 148
 - encryption, 321
 - SIP-Digest*, 321–324
 - event subscriptions, 154–155
 - messages**, 149
 - NOTIFY*, 155
 - requests*, 149–151
 - responses*, 152–153
 - multipoint conferencing models**, 157
 - port usage**, 275
 - proxy server**, 146
 - record routing**, 153
 - redirect server**, 147
 - registrars**, 147
 - resource reservation support**, 180–182
 - scheduled conferencing**, 173, 177
 - entry IVR*, 174
 - hold and resume*, 178–179
 - in-conference features*, 177
 - muting*, 179
 - outdial*, 179
 - roll call*, 177
 - unmuting*, 179
 - SDP, 155**
 - media-level parameters*, 156
 - session-level parameters*, 155
 - transactions**, 148
 - UAs**, 146
 - SIP-Digest, 321–324**
 - skew, 223**
 - acceptable tolerance, 224
 - delay accumulation, 226
 - measuring, 225–226
 - network delay, sources of, 228–229
 - slices, 241**
 - H.263 support of, 336
 - Slow Start mode (H.323), 204**
 - SNR scalability (H.263)**, 93, 336
 - source filters**, 252
 - source video formats for MPEG-4, Part 2 codecs**, 354
 - spatial domain**, 59
 - spatial scalability (H.263)**, 93–95, 336
 - speaker selection algorithm**, 35–36
 - speaker selection module**, 34
 - SP-frames, 99**
 - SRs (sender reports)**, 114–116
 - SRTP (Secure RTP)**, 312
 - SSRC (synchronization source identifier field)**, 110
 - SSRC collisions**, 111
 - STAP (single-time aggregation packet)**, 136

start codes, error resiliency, 89
stateful proxy servers, 146
stateless proxy servers, 146
static payload types (RTP), 108
stream loss, detecting, 141–142
stream switching mode, 12
STUN (Simple Traversal Underneath NATs), 296
Stunnel, 311
sub-band filtering, 93–95
switching frames, 99
symmetric encryption, 299
 key distribution, 309
 certificate-based, 309
 Difflie-Hellman, 310
symmetric NAT, 282–283
symmetric pinhole, 275
SYN attacks, 260–261
synchronization delay in receiver video path, 244
synthesis, 94–96
synthesis filters, 96

T

talk-over mode feature, 9
TCP intercept, 261
TCS (Terminal Capability Set) messages, 192
 DTMF relay support indicators, 193–194
telepresence systems, 16
temporal order, 84
temporal scalability, 85–86, 95–98, 335
terminals (H.323), 208
text overlay in presentation windows, 18
theft of service attacks, mitigating, 262
time base correlation using RTCP, 250–252
time stamp field (RTP), 109–110
timebases, calculating VTB, 253
TLS, 311–312
transactions (SIP), 148
transcoders, 12, 22, 122
 in video conferencing networks, reasons for, 229
transform processing, 55, 57, 59
 adaptive encoding
 content-adaptive arithmetic coders, 72
 content-adaptive VLC, 71
 binary arithmetic coders, 68

coefficients, 58
DCT scanning, 69–70
entropy coding, 62–63
 arithmetic coding, 66–68
 run-length coding, 63
 variable-length coding, 63–66
quantization, 59, 62
translators, 120
 MTPs, 120–121
 transcoders, 122
 transraters, 122
transmission order, 84
transport address (H.323), 187
transraters, 12, 122, 229
TURN (Traversal Using Relay NAT), 296–298

U

UACs (user agent clients), 146
UAs (user agents), 146
UDP ALG firewall, 274
unmuting during scheduled conferencing, 179
unneeded services, disabling, 268
URI (Uniform Resource Identifier), 39
URL ID (H.323), 187
user interface, 21–24

V

VAD module, 34
variable-length coding, 63–66
VAS (voice-activated switched) mode, 11–12, 28
vertical resolution, 236
video capture, sender-side delay sources, 238–241
video codecs, 100
 H.261, 327
 data resiliency, 329–330
 entropy coding, 329
 MV characteristics, 328
 quantization characteristics, 328
 H.263, 330
 annex C, 338
 annex L, 338–339
 annex N, 339
 annex O scalability options, 335–336

annex P, 339
annex Q, 340
annex U, 340
annex W, 341
annex X, 342
B-frame support, 334
coefficient prediction, 332
data independence, 337
DCT characteristics, 332
entropy coding, 333–334
MV characteristics, 331
PB-frame support, 334–335
quantization characteristics, 333
slice support, 336
source video formats, 330
H.264, 342
B-frames, 346
deblocking filter, 352
entropy coding, 351
error resilience, 352–353
integer transform, 349–350
intra predication mode, 346–349
MV characteristics, 345
MVs, 345
profiles, 343–344
quantization characteristics, 350–351
source video formats, 344
HD-capable, 102
macroblocks, 101–102
MPEG-4, Part 2, 353
B-frame support, 356
DCT coefficient prediction, 355
entropy coding, 356
MV characteristics, 354–355
profiles, 353–354
quantization methods, 356
scalability, 357
source video formats, 354
performance criteria, 46
bit rate, 45
delay, 46
specifications
form factors, 47–48
frame rates, 47–48
layout, 48
levels, 47
profiles, 47
video stream hierarchy, 100

video coding process
transform processing, 55–59, 62–72
post-processing, 54–55
preprocessing, 52–54
video composition schemes, 11
video conferencing, ad hoc, 162
de-escalation, 169–171
escalation, 169–171
media control support, 172–173
media stream grouping, 169
multiple stream support, 168
SDP bandwidth information, 167–168
video SDP extensions, 164–167
video displays, presentation time, 225
video endpoints, 237
video formats for H.264 codecs, 344
video MCU, 124
video mixer/compositor, 27
video source formats, 235
color formats, 49, 52
HD, 48–49
SD, 48–49
video streams, RTP time stamps, 246–247
video switches, 28
video switchers, 124, 126
video transcoders, 30
video transrating, 28–30
video-specific H.245 messages
Flow Control command, 202
Miscellaneous command, 202–204
Miscellaneous Indication, 202
VLC code table, 64
VTB (video device timebase), calculating, 253
VUI (voice and telephony user interface), 24

W-X-Y-Z

wall clock time, 250
wavelet filtering, 93
web server vulnerabilities, mitigating, 268
whiteboard collaboration feature, 9
whole-packet processing as audio
transmission path delay source, 234
worms, 262
YCbCr color format, 49
zero-run-length coders, 63