

Symbols

- ! (exclamation point) character, 124
- # (pound sign) character, 124

Numerics

- 10GBASE-xyz, naming conventions, 69
- 10GE, 68
 - distance limitations, 70–71
- 10-Mbps Ethernet, 62
- 802.1D, compatibility with RSTP, 250
- 802.1Q, 176
 - misconfiguring, 178
- 802.11 operational standards, 830–831
- 802.11a standard, 834–835
 - calculating bandwidth, 838
 - channel reuse, 836–838
- 802.11b standard, calculating bandwidth, 838
- 802.11b/g standard, channel reuse, 836
- 802.11g standard, 832–834
 - calculating bandwidth, 838

A

- AAA
 - accounting, configuring, 660–665
 - authentication, configuring, 658–661
 - authorization, configuring, 659–663
 - on Cisco IOS-based Catalyst switches, configuring, 658, 665–666
- aaa new-model command, 106
- absorption, 824
- access layer, 25
- access networks, 44
- access
 - to vty lines, securing, 654
 - unauthorized, 95
- access-layer switches, 64
- accounting, 660
 - configuring, 663–665
- ACLs (access control lists), 5

- applying, 679–680
- configuring on Cisco Catalyst switches, 653
- PACLs, applying, 683–684
- RACLs, applying, 680–681
- VACLs, applying, 681–683

active keyword, 537

active scanning, 857

ad hoc mode, 815, 819

adding switches, 206

Address Resolution Protocol. *See* ARP

addresses

- globally scoped, 506
- GLOP, 506–507
- IP multicast, 502
- limited-scope, 506
- MAC address notification, 337–338
- reserved link local, 505–506
- source-specific multicast, 506
- virtual MAC, VRRP, 596

adjacencies, 428

adjacency tables, 413–414

ADSL (asymmetric digital subscriber line), 71

ADU (Aironet Desktop Utility), 860

AES (Advanced Encryption Standard), 859

AES-CCMP (Advanced Encryption Standard-Counter Mode with Cipher Block Chaining Message Authentication Code Protocol), 852

agents, DHCP relay, 399

aggregate policers, 468

aggressive mode UDL, 356–358

- case study, 360–364
- configuration exercises, 374
- versus Loop Guard, 292

answers to review questions

- chapter 1, 881–883
- chapter 10, 892–893
- chapter 11, 893–894
- chapter 12, 894–895
- chapter 13, 895
- chapter 14, 896
- chapter 15, 897
- chapter 16, 897
- chapter 17, 898
- chapter 18, 899–900
- chapter 2, 884–885
- chapter 3, 885–886

- chapter 4, 886–888
- chapter 5, 888–889
- chapter 6, 889
- chapter 7, 890–891
- chapter 8, 891
- chapter 9, 892

antenna diversity, 829

antennas, 827

- highly directional, characteristics of, 829
- omnidirectional, characteristics of, 828
- RP-TNC connectors, 829
- selecting, 828
- semidirectional, characteristics of, 829

AP-manager interfaces, 861–862

application layer (Cisco SONA), 19

applications

- Cisco AVVID, 21
- statistics, checking, 311

applying ACLs, 679–680

- PACLs, 683–684
- RACLs, 680–681
- VACLs, 681–683

APs

- active scanning, 857
- autonomous, 816
- Cisco Aireospace, roaming, 848
 - Layer 2 roaming, 849*
 - Layer 3 roaming, 850–851*
- Cisco Aireospace AP, 841
- Cisco Aironet 1500 Series Lightweight Outdoor Mesh AP, 818
- Cisco wireless client AP association, 856–857
- Lightweight, 816–817
 - comparing with autonomous, 844–845*
 - managing, 845–846*
- LWAPP, 852
 - AP association, 854–855*
 - combining with autonomous APs, 855–856*
 - Layer 2, 853*
 - Layer 3, 853*
- microcell architecture, 823
- passive scanning, 856
- wireless repeaters, 820

ARP (Address Resolution Protocol), 13

- throttling, 416–418

ASICs (application-specific integrated circuits), 6, 295

- memory limitations, 7

assured forwarding, 451–452

asymmetrical routing, 674

attenuation, 760, 824

authentication, 658

- 802.1X, 675–677
- configuring, 661
- VTP, 192

authorization, 659–660

- configuring, 661–663

auto-negotiation issues, 67

autonomous APs, 816

- combining with LWAPP, 855–856
- comparing with lightweight APs, 844–845

Auto-RP, 517

availability of VoIP, 4

AVPs (attribute-value pairs), 659

AVVID (Architecture for Voice, Video and Integrated Data). See Cisco AVVID

AWP (Adaptive Wireless Path) protocol, 818

B

baby giants, 177, 346

BackboneFast, 280

- configuration exe, 301, 304–306
- configuring, 284
- in RSTP, 247
- link failures, 281

backup ports, 245

backup root bridges, 231

bandwidth provisioning in IP telephony installations, 629–630

best practices for IP Telephony deployment in Enterprise Composite Network Model, 633–634

bidir-PIM, 516

binary image mode (Cisco IOS Software Modularity), 572

black holes, preventing with Loop Guard, 289–291

blocking state, 226

boot system flash command, 121

bootstrap router (BSR), 518

both keyword, traffic monitoring with SPAN, 768

BPDU (bridge protocol data units), 223

- filtering, 286
- format, 246–247
- frame formats, 224
- TCN, 233
- timers, 224

BPDU Guard, 278, 284

bridge IDs, 222

bridge virtual interface (BVI), 393

bridging

- backup/primary root, 231
- loops, 218
 - building loop-free networks, 220*
 - Loop Guard, 290*
 - preventing, 219–220*
 - troubleshooting, 297*
- signaling topology changes, 233–235
- study tips, 260–261

broadcast domains, 9

broadcast suppression, 344–345

broadcasting packets, 502

BSA (basic service area), 819

BSR (bootstrap router), 518

BSSs (Basic Service Sets), 819

building

- Layer 3 networks, 22–23
- loop-free networks, 220

Building Access submodule (Enterprise

Composite Network Model), 31, 34, 633

building blocks of wireless bridges, 821–822

Building Distribution submodule, 31, 34

burst size, 467

BUS mode (SFM), 726

BVI (bridge virtual interface), 393

C

cabling standards, EIA/TIA 568A and 568B, 841

calculating

- bandwidth for 802.11 networks, 838
- WLAN transmit power, 826–827

CAM (content addressable memory), 418

Campus Backbone layer, 82

Campus Backbone submodule, 31, 34

Campus Infrastructure module, 73

campus networks, 27, 153

- and data centers, 3
- Cisco Enterprise Campus Architecture, 3–4, 23
- VLANs, 152

Canonical Format Indicator (CFI), 176

capturing traffic with VSPAN on Cisco

CatOS-based switches, 772

case studies

- aggressive mode UDLD, 360–364
- designing a Cisco multilayer switched network, 85–86
- VLAN hopping attacks, preventing, 698–700

CatOS 8.x, 95

CCX (Cisco Compatible Extensions), 860–861

CDP (Cisco Discovery Protocol), 331, 334

- restricting use of, 655–656

CEF (Cisco Express Forwarding), 5, 411

- components, 413–415

CEF-based MLS, 411–415

- ARP throttling, 416–418
- centralized/distributed switching, 415–416
- commands, 434
- configuration, 424–426
 - viewing Layer 3 Engine adjacency table, 428–431*
 - viewing Layer 3 Engine CEF table, 426*
- distributed switching, 416
- load sharing, 424
- sample operation, 422–423
- study tips, 432–434
- switching table architectures
 - CAM, 418*
 - TCAM, 419–421*
- troubleshooting
 - configuration exercise, 435–438*
 - debugging CEF on Layer 3 Engine, 430*
 - methodology, 431–432*
- verifying, 425

centralized switching, 415–416

CFI (Canonical Format Indicator), 176

channel reuse

- for 802.11a, 836–838
- for 802.11b/g, 836

channeling EtherChannel, 318

chassis options

- for Cisco Catalyst 4500 switches, 730
- for Cisco Catalyst 6500 switches, 722

chromatic dispersion, 760**Cisco ACAT (Aironet Configuration Administration Tool), 859****Cisco ACAU (Aironet Client Administration Utility), 860****Cisco Airespace APs, 841**

roaming, 848

*Layer 2, 849**Layer 3, 850–851*

REAPs, 848

Cisco Aironet 1000 Series Lightweight AP, 817**Cisco Aironet 1500 Series Lightweight Outdoor Mesh AP, 818****Cisco Aironet 802.11a/b/g CardBus Wireless LAN Client Adapter, 816****Cisco Aironet 802.11a/b/g PCI Wireless LAN Client Adapter, 816****Cisco Aironet Power Injector products, 840****Cisco Auto RF feature, 847****Cisco AutoQoS, 483–484****Cisco AVVID (Architecture for Voice, Video and Integrated Data), 15, 20–21, 53****Cisco Catalyst 2950 switches, 51**

WRR, 473

Cisco Catalyst 2960 switches, 51, 737–738

manageability features, 52

Cisco Catalyst 2970 switches, SRR, 473–474**Cisco Catalyst 3550 switches, 50**

security, 50–51

updating software versions, 124

Cisco Catalyst 3560 switches, 50, 86, 736

available models, 736

features, 736

security, 50–51

Cisco Catalyst 3750 switches, 50, 733

Cisco StackWise technology, 735

features, 734

security, 50–51

SRR, 473–474

Cisco Catalyst 4500 switches, 47–48

chassis options, 730

fixed configuration models, 730–731

high availability, 560

redundancy, 558

security, 49

SSO, 562–566

Supervisor Engines, 731–733

Cisco Catalyst 4948-10GE switch, 48**Cisco Catalyst 6500 switches, 45, 95, 558, 721**

chassis options, 722

Cisco IOS Software Modularity, 571–572

CPU monitoring, troubleshooting, 775

EEM, 790–791

ERSPAN performance monitoring,

configuring, 784

features, 45–46

FWSM, 684–685

high availability, 560

hybrid-mode, 96

line cards, 724

line modules, 727

NAM, 791–792

*configuring, 793–797**troubleshooting, 799**verifying configuration, 797–798*

performance monitoring using VACLs with

capture option, 785–787

recommended deployment scenarios, 729

redundant Supervisor Engine Uplink

modules, 572

redundant power supplies, 573–575

security, 47

service modules, 723, 728–729

Supervisor Engines, 723

*Supervisor Engine II, 725–727**Supervisor Engine 32, 724–725**Supervisor Engine 720, 727*

supported data paths, 724

supported interfaces, 723

WRR, configuring, 472

Cisco Catalyst QoS trust concept, 457**Cisco Catalyst switches, 560–563. *See also* Cisco Catalyst 29xx switches; Cisco Catalyst 35xx switches; Cisco Catalyst 4500 switches; Cisco Catalyst 6500 switches**

ACLs, 679

*configuring, 653**PACLs, applying, 683–684**RACLs, applying, 680–681**VACLs, applying, 681–683*

BackboneFast, 283

bridge IDs, 222

CatOS 8.x, 95

Cisco NAC, 678–679

- configuring
 - as VTP servers, 193*
 - multilayer switching, 411*
 - EtherChannel, 318
 - management parameters, configuring, 98
 - clock and NTP settings, 101–103*
 - DNS, 108*
 - management IP address, 99–100*
 - system logging, 109*
 - system names, 98*
 - telnet and SSHs, 104–106*
 - multilayer, 389
 - overview, 44
 - passwords, configuring, 653
 - policing, 468
 - pVLANs, 168
 - QoS
 - enabling, 484*
 - fundamentals, 453–479*
 - marking, 463–464*
 - redundant Supervisor Engines, 557–561, 564
 - running Cisco IOS, configuring voice VLANs, 628–629
 - software images, 114
 - naming, 118–119*
 - "top of rack", 65
 - troubleshooting, 126
 - configuration commands, 128*
 - connecting to switches via console ports, 130*
 - debug commands, impact and use, 128*
 - IP connectivity, 131–132*
 - show and debug commands, 127*
 - updating software versions, 120–121, 124
 - VLAN requirements, 156
 - VLAN support, 157
 - VMPS support, 155
 - wavelengths, 758
- Cisco CatOS**
- compared to Cisco IOS (Native Mode), 96–97
 - converting to Cisco IOS (Native Mode), 125
 - feature parity with Cisco IOS (Native Mode), 96–97
 - MDGs, 336–337
 - VLANs, configuring, 161
- Cisco CatOS-based Catalyst switches, 100**
- configuration changes, 113
 - DNS lookup, 108
 - ERSPAN, supported switches, 784
 - local SPAN, configuring, 771
 - passwords, 104
 - RSPAN performance monitoring, configuring, 780–782
 - Syslog destination, 109
 - time adjustments, 103
 - traffic, capturing, 772
- Cisco Data Center Network Architecture, 4**
- Cisco Enterprise Branch Architecture, 24**
- Cisco Enterprise Campus Architecture, 23**
- Cisco Enterprise Data Center, 24, 41–42**
- access networks, 44
 - data center interconnect, 44
 - SANs, 43
 - server fabrics, 42
- Cisco Enterprise Teleworker Architecture, 24**
- Cisco Enterprise WAN Architecture, 24**
- Cisco Express Forwarding. See CEF**
- Cisco Firewall Services Module, 46**
- Cisco IFS (IOS File System), 114**
- determining IFS size and contents, 116
 - formatting and copying images, 114
- Cisco IIN (Intelligent Information Network), 19–20, 54**
- Cisco IOS software**
- Catalyst switches, configuration exercise, 134–141
 - debug command, 127
 - file system, 114
 - determining size and contents, 116*
 - image naming, 118–119*
 - global configuration mode, 157, 159
 - hybrid mode, naming conventions, 118
 - ISSU, 572
 - native mode, feature parity with Cisco CatOS, 96–97
 - show command, 127
 - SLB, 602
 - switches
 - DNS lookup, 108*
 - NTP settings, 103*

- Syslog destination, 109*
 - time adjustments, 103*
 - VLAN database configuration mode, 157
- Cisco IOS Software Modularity, 571–572**
- Cisco IOS-based Catalyst switches**
 - AAA, configuring, 665–666
 - ERSPAN, supported sessions, 784
 - local SPAN, configuring, 771
 - port security, configuring, 670
 - RSPAN performance monitoring, configuring, 778–780
 - traffic monitoring, 769
 - VSPAN, configuring, 773
- Cisco IP Telephony, components of, 623**
- Cisco LRE (Long-Reach Ethernet), 71**
- Cisco metro solutions, 743–745**
- Cisco NAC (Network Admission Control), 678–679**
- Cisco REAP (Remote Edge Access Point), 856**
- Cisco SONA (Service-Oriented Network Architecture), 17–18, 54, 632**
- Cisco StackWise technology, 735**
- Cisco Unified Wireless Network, 843–845**
- Cisco WCS (Wireless Control System), 846**
- Cisco WGB (Work Group Bridge), 820**
- Cisco wireless clients**
 - AP association, 856–857
 - open authentication, 857
 - pre-shared key authentication, 858
- Cisco Wireless Location Appliance, WLAN management, 847**
- Cisco WiSM, WLAN management, 846**
- Cisco WLANs**
 - APs
 - combining with autonomous APs, 855–856*
 - LWAPP, 852–855*
 - Auto RF feature, 847
 - group mode feature, 847
 - mobility group feature, 848
 - split MAC architecture, 851
- Cisco WLCM (Wireless LAN Controller Module), WLAN management, 846**
- CiscoWorks WLSE (Wireless LAN Solution Engine), 844, 847**
- CiscoWorks WLSE Express, WLAN management, 847**
- classification, 464**
- clear VLAN command, 161**
- CLI (command-line interface), 95**
- client adapters (WLANs), 816**
- clients, 815**
- commands**
 - bridging, 261
 - CEF-based MLS, 434
 - clear, 539
 - clear vlan, 161
 - copy running-config startup-config, 121
 - debug ip cef, 431
 - encryption-type, 104
 - line vty, 104
 - multicast traffic deployment, 542
 - QoS-related, 486
 - redundancy, 609
 - show catalyst 6000 traffic-meter, 310
 - show interface, 101, 131
 - show ip mroute, 536–537
 - show ip route, 131
 - show logging, 308
 - show process cpu, 309
 - show running-config interface, 163
 - show system, 310
 - shutdown interface-level, 310
 - snmp-server user, 112
 - spanning-tree portfast, 305
 - srr-queue bandwidth shape, 474
 - srr-queue bandwidth share, 474
 - STP-related, 301
 - switchport, 205
 - switchport host, 160
 - vtp domain domain-name, 204
 - vtp mode, 204
 - vtp password, 204
 - vtp v2-mode, 193
- community VLANs, 167**
- Compact mode (SFM), 726**
- comparing**
 - IEEE 802.11 standards, 835–836
 - PIM versions, 519–520
 - shared/source trees, 512–513
 - WLANs and Ethernet, 812–813
 - compression issues, 814*
 - environmental issues, 813–814*
 - mobility, 814*

privacy issues, 813
regulatory issues, 814–815

components

of CEF, 413–415
 of Cisco AVVID, 21
 of Internet Connectivity module, 37
 of IP telephony, 623–624
 of Remote Access module, 38
 of VPN module, 38
 of WLANs, 816–817

compression, comparing WLANs and Ethernet, 814

configuring, 593

AAA, 658
 accounting, 660–665
 authentication, 658–661
 authorization, 659–663
 on Cisco IOS-based Catalyst switches, 665–666
 aggressive mode UDLD, 363
 baby giant and jumbo frame support, 349
 BackboneFast, 284
 configuration exercise, 301, 304–306
 BPDU filtering, 286
 broadcast and multicast suppression, 345
 burst size, 467
 CEF-based MLS, 424–426
 Cisco Catalyst switches, 653. *See also* Cisco Catalyst switches
 DAI, 693–695
 debounce timer feature, 343
 DNS lookup, 108
 EEM, 791
 ERSPAN, performance monitoring, 783–784
 EtherChannel, 324–326
 GLBP, 601
 HSRP, 585–592
 IEEE 802.1Q trunking, 182–183
 IEEE 802.1X, 676–677
 IGMP snooping, 534
 inter-VLAN routing, verifying configuration, 396
 IPSG, 690–691
 ISL trunking, 181
 LACP, 321
 loop-free networks, 220
 MAC address notification, 338

MDGs, 337
 MST, 256, 258–259
 multilayer switching, 411
 NAM, verifying configuration, 797–798
 performance monitoring on RSPAN, 776–782
 policers, 468
 policy maps, 463
 PortFast, 277, 305–306
 protocol filtering, 340
 PVST+
 port cost, 240
 root bridges, 239–240
 Root Guard, 288
 configuration exercise, 305
 SNMP, 111–112
 SPAN
 destination ports, 770
 for CPU monitoring, 773–775
 source ports, 768
 SRM, 569
 SSO, 564
 STP, 264
 verifying configuration, 241–243
 switches for SSH, 106
 syslog destination, 109
 system logging, 657
 system warning banners, 654
 UDLD, 358–359
 UplinkFast, 279
 configuration exercise, 304
 virtual servers, SLB, 606
 VLANs, 158–161
 private VLANs, 168–171, 208–209
 verifying configuration, 162–163
 voice VLANs on Catalyst switches running Cisco IOS, 628–629
 VSPAN on Cisco IOS-based Catalyst switches, 773
 VTP, 192–193
 verifying configuration, 195
 WLANs
 available interfaces, 861–864
 controllers, 865–869
 controllers, connecting to, 864–865
 WRR on Catalyst 6500 switches, 472

connectivity, troubleshooting with L2 traceroute, 787–789

control packets, prioritizing, 299

controllers

- available interfaces, 861
- configuring, 865–869
- connecting to, 864–865
- verifying configuration, 869
 - with show 802.11 commands, 869*
 - with show advanced 802.11 commands, 869–870*
 - with show ap commands, 870*
 - with show client commands, 871–872*
 - with show radius commands, 872*
 - with show rogue ap commands, 872*
 - with show rogue client commands, 872–873*
 - with show stats commands, 870–871*

converting Cisco CatOS to Cisco IOS (Native Mode), 125

copy command, 112

copy running-config startup-config command, 121

copy tftp flash command, 120

copying images on Cisco IFS, 114

core layer, 25

cost of wireless bridging, 822

count keyword, 537

coverage holes, 813

CPU monitoring

- on Catalyst 6500 switches, troubleshooting, 775
- SPAN, configuring, 773–775

CQ (custom queuing), 476

creating

- loop-free spanning trees, 228–231
- VLANs, 161
 - VLAN database configuration mode, 159*

critical performance-management tasks, 766–767

crypto key generate command, 106

CSMA/CD (carrier sense multiple access/collision detect), 811

CST (Common Spanning Tree), 252

current-generation NICs, 64

custom queuing (CQ), 476

CWDM (coarse wavelength division multiplexing)

- GBIC modules, 760
- metro Ethernet, 758–760
- OADM modules, 760

D

DAI (Dynamic ARP Inspection), 692
configuring, 693–695

Data Center access submodule (Enterprise Composite Network Model), 633

data center interconnect, 44

data centers, 3–4

- and campus networks, 3
- Cisco Enterprise Data Center Architecture, 24, 41–42
 - access networks, 44*
 - data center interconnect, 44*
 - SANs, 43*
 - server fabrics, 42*

data path support (Catalyst 6500), 724

data link technologies, 67

- 10-Gigabit Ethernet, 68
- 10-Mbps Ethernet, 62
- Fast Ethernet, 63
- GBICs, 71
- Gigabit Ethernet, 64
 - distance limitations, 66*
- LRE, 71

data-planes, 413

daylight savings time, Energy Policy Act of 2005, 103

dB (decibel), 826

dB_i (isotropic decibel), 826

dB_m (decibels per milliwatt), 826

dBW (decibels per watt), 826

dCEF256 (distributed CEF 256) mode, 726

debounce timer feature, 342

- configuring, 343
- enabling, 342

debug all command, 129

debug ip cef command, 431

decibel to milliwatt conversion table, 826

default gateway router redundancy, 575

- GLBP, 598
- HSRP, 579–593
- IRDP, 577
- proxy ARP, 576
- VRRP, 594–597

deleting VLANs, 159**deploying IP Telephony in Enterprise Composite Network Model, best practices, 633–634****designing**

- IP telephony installations, 625
 - high availability, 632*
 - network bandwidth provisioning, 629–630*
 - network management, 631*
 - power considerations, 630–631*
 - QoS, 626–627*
 - security, 632–633*
 - voice VLANs, 627–629*
- loop-free networks, 220
- multilayer switched networks
 - case study, 85–86*
 - Cisco Catalyst switches and data link technologies, 73*
 - data link technologies, 61*
 - large campus networks, 77, 79–80*
 - medium-sized campus networks, 76–77*
 - selecting Layer 2 or Layer 3 switches, 74*
 - Server Farm module, 80, 82–83*
 - small campus networks, 75*

destination ports, configuring SPAN, 770**devices, PDUs, 12****DF (designated forwarder) election, 516****DFC (Distributed Forwarding Cards), 415****DHCP relay agents, enabling, 399****DHCP snooping, 687, 689****DHCP-based management IP configuration, 340–341****DiffServ (differentiated services), 441, 448–450****differences between Ethernet and WLANs, 812**

- compression issues, 814
- environmental issues, 813–814
- mobility, 814
- privacy issues, 813
- regulatory issues, 814–815

diffraction, 824**disabled state, 226****disabling**

- Integrated HTTP daemon, 656
- multicast traffic monitoring on source ports, 768
- Telnet access, 140
- unused services, 654–655

disaster recovery on multilayer switched networks, 5**discard adjacency, 428****distance limitations**

- for Ethernet wire, 64
- for typical 10GE deployments, 70–71

Distributed Forwarding Cards (DFC), 415**distributed switching, 416****distribution layer, 25****distribution-layer switches, 64****DNS, configuring on switches, 108****drop adjacency, 428****DSCPs (differentiated services code points), 456****DTP (Dynamic Trunking Protocol), 178****duplex mismatch, 294****DVS (directed VLAN service), 750****DWDM (dense wavelength division multiplexing)**

- metro Ethernet, 754
- OADM, 758
- optical multiplexers, 758
- wavelengths, 756

dynamic interfaces, 861–863**dynamic NAT, 686****dynamic VLANs, 155–156****E****EAPoL (Extensible Authentication Protocol over LAN), 675****EDFAs (erbium doped fiber amplifiers), 758****EEM (Embedded Event Manager), 790–791****egress queuing, SRR, 474–475****egress SPAN, 768****EIA/TIA 568A and 568B cabling standards, 841****EIGRP (Enhanced Interior Gateway Routing Protocol), 79****electing a root bridge, 228****enabling**

- debounce timer feature, 342
- DHCP relay agents, 399

- passwords, 104
 - VMPS, 155
 - encapsulation dot1Q 1 native command, 395**
 - encryption-type command, 104**
 - end-span devices, 840**
 - Energy Policy Act of 2005, 103**
 - Enterprise Campus Architecture, 3–4**
 - infrastructure, 31
 - meeting the needs of Enterprise networks, 33
 - modules, 33–34
 - Enterprise Composite Network Model, 15, 25–26**
 - Campus Infrastructure module, 73
 - Enterprise Campus, 30
 - submodules, 31–33
 - Enterprise Edge, 27, 35
 - E-Commerce module, 36*
 - Internet Connectivity module, 37*
 - modules, 35
 - Remote Access module, 38*
 - sample implementation, 39*
 - VPN module, 38*
 - WAN module, 38*
 - IP Telephony deployment, best practices, 633–634
 - overview, 27
 - sample implementation, 29
 - Service Provider Edge, 27, 39
 - ISP module, 39*
 - PSTN module, 40*
 - sample implementation, 41*
 - Enterprise Edge submodule, 5, 34, 84, 633**
 - enterprise MANs, metro Ethernet, 746**
 - enterprise network architectures**
 - Cisco AVVID framework, 20
 - Cisco IIN, 19–20
 - Cisco SONA, 17–18
 - regulatory standards, 6
 - storage networks, 80
 - enterprise WLANs, top-ten issues, 842**
 - environmental issues, comparing WLANs and Ethernet, 813–814**
 - erase startup-config command, 113**
 - erbium doped fiber amplifiers (EDFAs), 758**
 - error-disable feature, 349–353**
 - ERSPAN (Enhanced Remote SPAN), 782–784**
 - ESA (extended service area), 820**
 - ESCON (Enterprise Systems Connection), 745**
 - ESS (Extended Service Set), 819**
 - EtherChannel, 318**
 - configuration examples, 323–326
 - configuration exercises, 366–370
 - guidelines, 322
 - LACP modes, 321–322
 - link redundancy, 556
 - load balancing, 329–331
 - PAgP modes, 320
 - Ethernet, 63**
 - baby giants, 346
 - comparing with WLANs, 812–813
 - compression issues, 814*
 - environmental issues, 813–814*
 - mobility, 814*
 - privacy issues, 813*
 - regulatory issues, 814–815*
 - Gigabit Ethernet, deployment strategies, 65
 - jumbo frames, 347, 349
 - metro Ethernet, 72, 746
 - CDWM, 758, 760*
 - connectivity and transport, 747–750*
 - DWDM, 755*
 - optical distance challenges, 760–761*
 - SONET, 751–753*
 - WDM, 754*
 - trunking modes, 181
 - wire standards and maximum distances, 64
 - EtherType (TPID), 176**
 - ETSI (European Telecommunications Standards Institute), 815, 830**
 - exam study tips, 635–637**
 - exclamation point (!) character, 124**
 - expedited forwarding, 452**
-
- F**
- Fast Ethernet, 63**
 - FCC (Federal Communications Commission), 830**
 - FCIP (Fibre Channel over IP), 5, 80**
 - features**
 - of Catalyst 3560 switches, 736
 - of Catalyst 3750 switches, 734
 - of port security, 666–671
 - MAC filtering, 671–673*

sticky feature, 671
unicast flood-blocking feature, 674

FFI (Full Flow Information), 412
FIB (forwarding information base), 413–414
Fibre Channel over IP (FCIP), 5
FIBs (forwarding information bases), 413–414
FIFO queuing, 470
file systems, 114
firewalls, 5, 684
fixed configuration models for Catalyst 4500, 730–731
flow control, IEEE 802.3, 354–355
formatting images on the Cisco IFS, 114
forwarding loops, 289–291
forwarding state, 226
Frame Relay, ATM, and PPP module, 40
frames
 baby giants, 177, 346
 BPDU, 224
 corrupt, 295
 IEEE 802.1 Q, 176
 ISL, 174
 jumbo, 347–349
Fresnel zone, 839
Full Flow Information (FFI), 412
functional areas (Enterprise Composite Network Model), 29
FWSM (Firewall Services Module), 684–685

G

gain, 827
GBICs (Gigabit Interface Converters), 71
Gigabit Ethernet, 64
 deployment strategies, 65
 Fast Ethernet and Gigabit Ethernet
 auto-negotiation, 67
GLBP (Gateway Load Balancing Protocol)
 configuring, 601
 support, 598
global configuration mode, 159
globally scoped addresses, 506
GLOP addresses, 506–507
group mode feature (Cisco WLANs), 847

groups
 multicast, 504
 SNMP, configuring, 112

H

hardware, 526–527
 loops, troubleshooting, 310
hardware-switching, 6
hello time timer, 226
hierarchy in IP addresses, 385–386
high availability, 553–554, 560
 for IP telephony installations, 632
highly directional antennas, 827–829
HSRP (Hot Standby Routing Protocol), 5, 10, 593
 configuring, 614–616
 virtual MAC address, 582
hybrid mode Cisco IOS, naming conventions, 118

I

IBSS (Independent Basic Service Set), 819
IEEE (Institute of Electrical and Electronic Engineers), 830
IEEE 802.1d. standard, 222
IEEE 802.1q standard, 173
 implementing, 175–178
 trunks, 238
 Q-in-Q tunneling, 179
IEEE 802.1w standard, 243
IEEE 802.1x, 675–677
IEEE 802.3 flow control feature, 354–355
IEEE 802.11 standards, 830–831
 802.11a, 834–835
 802.11g, 832, 834
 comparing, 835–836
IGMP snooping, configuring, 534
IIN (Intelligent Information Network), 19–20
images
 loading on Catalyst switches, 120
 naming, 118–119
implementing
 ISL, 174
 pVLANs, 167
 SSO, 557, 562–563

individual policers, 468
InfiniBand, 42, 65
infrastructure of Enterprise Campus networks, 31
infrastructure mode, 815
ingress SPAN, 768
inline power, 840
installed image mode (Cisco IOS Software Modularity), 572
Integrated HTTP daemon, disabling, 656
interactive services layer (Cisco SONA), 19
interfaces
 Catalyst 2960 switch support, 737
 Catalyst 6500 switch support, 723
interference, 814
 multipath, 825
Inter-Switch Link (ISL), 173
inter-VLAN routing, 385–389
 configuration exercise, 405
 router on a stick, 393–395
 study tips, 400–401
 verifying, 396
IntServ model, 441, 448
IP addresses
 hierarchies, 385–386
 multicast, 502
 subnets, troubleshooting, 299
IP helper-address command, 399
IP telephony
 components of, 623–624
 network design recommendations, 625
 high availability, 632
 network bandwidth provisioning, 629–630
 network management, 631
 power considerations, 630–631
 QoS, 626–627
 security, 632–633
 voice VLANs, 627–629
IPSG (IP Source Guard), 689–691
IR (infrared), 811
ISL (Inter-Switch Link), 173–174
ISM (Industrial, Scientific, and Medical) bands, 808
isolated VLANs, 167–168
ISPs (Internet service providers), 8
ISSU (In-Service Software Upgrade), 571–572
ITU grid, 757

J-K

jitter, 445, 502
jumbo frames, 347, 349

keywords

active, 537
 count, 537
 summary, 536

L

L2 traceroute, 787–789

LACP (Link Aggregation Control Protocol)

configuring, 321
 modes, 321–322

LANs (local-area networks), 809

latency, 444

Layer 2, 527–528

Cisco CatOS, 96
 legacy switches, 9
 loops, troubleshooting, 306–312
 multilayer switching, 15
 protocols
 CDP, 331, 334
 UDLD, 355
 redundancy, SSO protocol support, 562
 switching, 9, 12

Layer 2 LWAPP, 853

Layer 3

entries, populating, 412
 marking, 463
 multilayer switching, 15
 networks, building, 22–23
 protocol filtering, 339–340
 switching, 10, 13, 21
 ARP, 14
 packet rewriting, 13
 routing protocol support, 389
 viewing
 Layer 3 Engine adjacency table, 428
 Layer 3 Engine CEF table, 426

Layer 3 LWAPP, 853

Layer 4
 performance, 11
 QoS marking, 9
 terminology, 10

Layer 7 switching, 811

layers
 of Cisco SONA, 18
 of Network Design Hierarchical Model, 25
 of Server Farm module, 82

leaky token bucket algorithm, 466

learning state, 226

Lightweight APs, 816–817
 comparing with autonomous APs, 844–845
 managing, 845–846

limited-scope addresses, 506

limiting trunk connections, 657

line cards (Catalyst 6500), 724, 727

line vty command, 104

listening state, 226

LLDP (Link Layer Discovery Protocol), 331

load balancing
 EtherChannel, 329–331
 HSRP, 583
 SLB, 602

load sharing, CEF-based MLS, 424

logging syslog servers, 109

Loop Guard
 Root Guard, 291
 versus aggressive mode UDLD, 292

loop-free networks, building, 220

loops
 bridging, 218
building loop-free networks, 220
preventing, 219–220
 Layer 2, troubleshooting, 306–312

loss, 827

LWAPP (Lightweight Access Point Protocol), 817, 852
 AP association, 854–855
 combining with autonomous APs, 855–856
 Layer 2, 853
 Layer 3, 853

M

MAC address notification, 337–338

MAC addresses, 222

MAC filtering, 671–673

manageability features of Catalyst 2960 switches, 52

management interfaces, 861–862

managing
 Catalyst switch configurations, 112
 WLANs
Cisco WCS, 846
Cisco Wireless Location Appliance, 847
Cisco WiSM, 846
Cisco WLCM, 846
CiscoWorks WLSE, 847
CiscoWorks WLSE Express, 847
lightweight APs, 845–846

man-in-the-middle attacks, mitigating with DAI inspection, 692

MANs (metropolitan-area networks), 809

mapping multicast IP to MAC, 507

MDGs (Multiple Default Gateways), 336–337

membership in multicast groups, 504

memory, ASICs, 7

mesh networks, wireless, 818

Metro Ethernet, 72, 746
 CDWM, 758, 760
 connectivity and transport, 747
DVS, 750
TLS, 748–749
 DWDM, 755
 optical distance challenges, 760–761
 SONET, 751–753
 WDM, 754

metro solutions, 743–745

MFIB (multicast forwarding information base), 527

MFSC (Multilayer Feature Switch Card) model, 125

MIC (Message Integrity Check), 859

microcell architecture, 819, 823

microflow policing, 468

microwave networks, 823

midspan devices, 840

misconfiguring 802.1q, 178

MLS (multilayer switching), 5, 7, 411

- CEF-based MLS, 413–415
 - ARP throttling, 416–418*
 - centralized/distributed switching, 415–416*
 - configuration, 424–426*
 - distributed switching, 416*
 - load sharing, 424*
 - sample operation, 422–423*
 - study tips, 432–434*
 - switching table architectures, 418–421*
 - troubleshooting, 430–432, 435–438*
 - verifying, 425*
 - viewing Layer 3 Engine adjacency table, 428–429, 431*
 - viewing Layer 3 Engine CEF table, 426*
- traditional MLS, 412

MMLS (multicast multilayer switching), 526**mobility, comparing WLANs and Ethernet, 814****mobility group feature (Cisco WLANs), 848****mode rpr-plus command, 613****modifying STP, identifying changes in topologies, 269–270****modules**

- Cisco Firewall Services, 46
- Enterprise Campus, 33–34
- Network Management, 32

monitoring performance with SPAN and VSPAN, 767–768**moving configurations between devices, 112****MSFC (Multilayer Switch Feature Card), 95****MSFC 2A (Multilayer Switch Feature Card 2A), 725****MST(Multiple Spanning Tree), 251–253**

- 802.1Q, 252
- configuring, 256–259
- IST instances, 254
- instances, 256
- PVST+, 252
- regions, 253

multicast PIM, bidir-PIM, 516**multicast forwarding information base (MFIB), 527****multicast IP addresses, 502****Multicast Quick-Start Configuration Guide, 531****multicast suppression, 345****multicast traffic, 501–503**

- deploying, study tips, 540–541
- forwarding trees, 510–513
- hardware switching, 525
 - CEF-based MMLS, 526*
 - MFIB, 527*
 - MMLS, 526*
- IP addresses, 504–507
- IP protocols, 513, 530–531
 - configuring, 531–535*
 - IGMP, 520, 522–525*
 - monitoring, 535–539*
 - PIM, 513–520*
- Layer 2 protocols, 527–528
 - CGMP, 529–530*
 - IGMP snooping, 528–529*
- MAC addresses, 507–508
- monitoring, disabling on source ports, 768
- reverse path forwarding, 508–510

Multilayer Feature Switch Card (MFSC) model, 95, 125**multilayer switched networks, 8**

- Cisco AVVID
 - applications, 21*
 - supported components, 21*
- Cisco metro solutions, 744
- data link technologies, 61
 - 10-Gigabit Ethernet, 68*
 - 10-Mbps Ethernet, 62*
 - Fast Ethernet, 63*
 - Fast Ethernet and Gigabit Ethernet auto-negotiation, 67*
 - GBICs, 71*
 - Gigabit Ethernet, 64–66*
 - LRE, 71*
- default gateway router redundancy, 575
 - GLBP, 598*
 - HSRP, 579–593*
 - IRDP, 577*
 - proxy ARP, 576*
 - static default gateway configuration, 578*
 - VRRP, 594–597*
- designing
 - case study, 85–86*
 - large campus networks, 77–80*
 - medium-sized campus, 76–77*
 - selecting, 74*

- Server Farm module, 80–83*
- small campus networks, 75*
- disaster recovery, 5
- Enterprise Composite Network Model, 15, 25, 38
- Enterprise Edge, 84
- EtherChannel, 323
- hardware switching, 525–526
 - MFIB, 527*
 - MMLS, 526*
- high availability, 553–555
- IP address hierarchies, 385–386
- Layer 2
 - design properties, 12*
 - switching, 9*
- Layer 2 protocols, 527–528
 - CGMP, 529–530*
- Layer 3, 13, 21
 - ARP, 14*
 - packet rewriting, 13*
 - switching, 10*
- Layer 4
 - performance, 11*
 - terminology, 10*
- Layer 7 switching, 11
- multicast traffic, 501–503, 540–541
 - forwarding, 510–513*
 - IP addresses, 504–507*
 - IP protocols, 513–531*
 - MAC addresses, 507–508*
 - monitoring, 535–539*
- OSI reference model, 8
- QoS, 440–441, 480
 - assured forwarding, 451–452*
 - Building Access submodule, 482*
 - Building Distribution submodule, 482*
 - Campus Backbone, 483*
 - Catalyst fundamentals, 453–464*
 - congestion avoidance, 476–479*
 - congestion management, 469–472, 475–476*
 - DiffServ model, 448–450*
 - expedited forwarding, 452*
 - IntServ model, 448*
 - jitter, 445*
 - latency, 444*
 - need for, 442–443*

- packet loss, 446*
- service models, 447*
- traffic conditioning, 465–466, 468*
- routed ports, 390
- security, 5
- study tips, 53
- trunking, 173

multipath interference, 814, 825

Multiple Default Gateways. See MDGs, 336

Multiple Spanning Tree. See MST, 251

N

NAM (Network Analysis Module), 791–792

- autostart collection, configuring, 797

- configuring, 793

- data sources, 794

- configuring, 793–797*

- troubleshooting, 799

- verifying configuration, 797–798

naming conventions

- for 10GBASE-xyz, 69

- for Cisco IOS images, 118

NAS (Network Area Storage), 5

NAT (Network Address Translation), 7, 686

Native IOS, 96

NBAR, 461

network access security, 675–676

- IEEE 802.1X, configuring, 676–677

network bandwidth provisioning in IP telephony installations, 629–630

Network Design Hierarchical Model, 25

network infrastructure layer (Cisco SONA), 18

network management for IP telephony installations, 631

Network Management module, 32

NMP (Network Management Processor), 724

no switchport command, 324

no switchport interface command, 390

nonlinearities, 761

non-root bridges, 839

NSF (Non-Stop Forwarding), 557, 564–566

NTP (Network Time Protocol), 10

null adjacencies, 428

O

- OADMs (optical add/drop multiplexers), 758–760**
- OFDM (Orthogonal Frequency-Division Multiplexing), 807**
- omnidirectional antennas, 827–828**
- open authentication, 857**
- operating systems. *See also* Cisco IOS software**
 - Cisco CatOS, compared to Cisco IOS (Native Mode), 96
 - Hybrid OS, 96
- optical add/drop multiplexers (OADMs), 758**
- order-dependent ACL merge, 680**
- order-independent ACL merge, 680**
- OSI reference model, 8**
- OSPF (Open Shortest Path First), 79**

P

- packet rewriting, 13**
- packets**
 - broadcasting, 502
 - loss, 446
 - prioritizing, 299
- PACLs, applying, 683–684**
- PAgP modes, 320**
- PANs (personal-area networks), 808**
- parameters for GLBP configuration, 601**
- passive scanning, 856**
- passwords, 104**
 - Catalyst Cisco IOS-based switches, 104
 - configuring on Cisco Catalyst switches, 653
- PAT (Port Address Translation), 686**
- PDUs (protocol data units), 11**
- Per VLAN Spanning Tree Plus. *See* PVST+, 235**
- performance, monitoring**
- performance management, critical issues, 765–767**
- performance monitoring**
 - on Catalyst 6500 switches using VACLs with capture option, 785, 787
 - with NAM, 791–792
 - autostart collection, 797*
 - configuring, 793*
 - data sources, 794*
 - data sources, configuring, 793–797*
 - verifying configuration, 797–798*
 - with ERSPAN, configuring, 783–784
 - with RSPAN, 776–778
 - configuring, 778–782*
 - with SPAN and VSPAN, 767–768
- permanent MAC filters, 673**
- PFC 3B (Policy Feature Card 3B), 725**
- physical security of network devices, 654**
- pico cells, 835**
- PIM (Protocol-Independent Multicast)**
 - bidir-PIM, 516
 - show commands, 539
- plain old telephone service (POTS), 71**
- PoE (Power-over-Ethernet), 840**
- policy maps, configuring, 463**
- populating Layer 3 entries, 412**
- port cost, configuring, 240**
- port roles, RSTP, 245**
- port security**
 - configuring on Cisco IOS-based Catalyst switches, 670
 - features provided by, 666–671
 - MAC filtering, 671–673*
 - sticky feature, 671*
 - unicast flood-blocking, 674*
 - violation detection, 668–670
- PortFast, 276**
 - configuration errors, 296
 - configuring, 277, 305–306
 - verifying, 305–306
- PortFast-enabled interfaces, receiving BPDUs, 286**
- ports**
 - backup, 245
 - checking status, 299
 - EtherChannel, 322
 - root port, selecting, 232
 - Root Guard, 286–288
 - routed, 390
 - Spanning-tree port states, 227
 - SSO, 563
 - uplink ports, 573
- POTS (plain old telephone service), 71**
- power considerations for IP telephony installations, 630–631**

Power Injector Media Converter, 841
power injectors, 841
power supplies, redundancy, 573–575
preparing for exam, study tips, 635–637
pre-shared key authentication, 858
preventing
 bridging loops, 219–220
 VLAN hopping attacks, case study, 698–700
primary root bridges, 231
priorities (STP), verifying, 264–267
prioritizing control packets, 299
priority queuing, 475
privacy, comparing WLANs and Ethernet, 813
pruning, 189
punt adjacency, 428
pVLANs (private VLANs), 695–696
 configuring, 168–171, 208–209
 port structure, 166
 troubleshooting, 165–169
PVST+ (Per VLAN Spanning Tree Plus), 235–236
 configuring
 port cost, 240
 root bridges, 239–240
 MAC address allocation and reduction, 237
 MST, 252

Q

QoS (Quality of Service), 440–441, 697
 Catalyst switches, 453–454
 classification, 455–462
 congestion avoidance, 476–479
 congestion management, 469–472, 475–476
 marking, 463–464
 traffic conditioning, 465–468
 Cisco AutoQoS, 483–484
 commands, 486
 deploying in IP telephony installations, 626–627
 enabling on Catalyst switches running Cisco IOS, 484
 jitter, 445
 latency, 444
 Layer 2 switching, 9
 marking in Layer 4, 9

 multilayer switched networks, 480
 Building Access submodule, 482
 Building Distribution submodule, 482
 Campus Backbone, 483
 need for, 442–443
 packet loss, 446
 service models, 447
 assured forwarding, 451–452
 DiffServ model, 448
 IP precedence bit mappings, 450
 packet classification, 449
 expedited forwarding, 452
 IntServ model, 448
 study tips, 485
queuing, SRR, 474–475

R

RACLs, applying, 680–681
RADIUS, AVPs, 659
random early detection (RED), 478
ranges (VLANs), 156
rapid transition to forwarding, 247–248
RDMA (Remote Direct Memory Access), 42, 65
recommended Catalyst 6500 deployment scenarios, 729
RED (random early detection), 478
redundancy, 554
 Catalyst 6500 switch SRM, 566
 configuring, 569
 displaying status, 570
 commands, 609
 default, 577–598
 disconnecting, 310
 Layer 2, SSO protocol support, 562
 multilayer switched networks, 25
 redundant power supplies, 573–575
 study tips, 608–611
redundant Supervisor Engines, 48, 557, 559
 route processor redundancy, 560
 RPR+, 561, 564
 Uplink modules, 572
redundant switched networks, 554
reflection, 824
refraction, 824

regulatory agencies for wireless networks, 830**regulatory issues**

- comparing WLANs and Ethernet, 814–815
- requirements as enterprise architecture drivers, 6

relay agents (DHCP), enabling, 399**reserved link local addresses, 505–506****resiliency (STP), 284****restricting CDP usage, 655–656****restrictions**

- for RSPAN performance monitoring, 776–778
- for SPAN traffic monitoring, 769–770
- for VSPAN traffic monitoring, 770

RF signals

- absorption, 824
- attenuation, 824
- coverage holes, 813
- diffraction, 824
- gain, 827
- interference, 814
- loss, 827
- multipath interference, 825
- reflection, 824
- refraction, 824
- scattering, 824
- units of measurement, 826

roaming, Cisco Airespace, 848–849

- Layer 2, 849
- Layer 3, 850–851

root bridges, 231, 838

- characteristics of, 839
- configuring, 239–240
- election process, 228
- planning selection, 229–230
- selection process, 232

Root Guard, 286–287

- configuration exercise, 305
- configuring, 288
- Loop Guard, 291

root mode (wireless bridges), 822**root ports, selecting, 232–233****routing**

- BSR, 518
- inter-VLAN routing, 385–388
 - bridge virtual interface, 393*
 - IP broadcast forwarding, 398–399*
 - multilayer Catalyst switches, 388–389*
- router on a stick, 393–395*
- switch virtual interface, 391–393*
- UDP broadcast forwarding, 399*
- verifying configuration, 396*

routing protocols, support for Cisco Catalyst Layer 3 switches, 389**RPs, automatic distribution of, 516–518****RPR+, configuring, 611– 613****RP-TNC (reverse-polarity TNC) connectors, 829****RSPAN (Remote SPAN), performance monitoring, 776–782****RSTP (Rapid Spanning Tree Protocol), 243**

- 802.1D compatibility, 250
- BackboneFast in, 247
- BPDU format, 246–247
- port roles, 245
- rapid transition to forwarding, 247–248
- topology change mechanism, 249–250

S**S/D (Source and destination IP address), 412****SANs (storage area networks), 43, 80****scattering, 824****secondary VLANs, types of, 167****Secure-HTTP (S-HTTP), 10****security**

- ACLs, applying, 679–680
- Catalyst 3550 switches, 50–51
- Catalyst 3560 switches, 50–51
- Catalyst 3750 switches, 50–51
- Catalyst 4500 switches, 49
- Catalyst 6500 switches, 47
- CDP, restricting usage, 655–656
- DAI, 692
 - configuring, 693–695*
- DHCP snooping, 687, 689
- Enterprise Campus modules, 34
- firewalls, 684
- for IP telephony installations, 632–633
- for WLANs, 858–859
- Integrated HTTP daemon, disabling, 656
- IPSG, 689–691
- Layer 3 networks, 23

- multilayer switched networks, 5
- NAT, 686
- PACLs, applying, 683–684
- port security, features provided by, 666–671, 673–674
- private VLANs, 695–696
- QoS, 444, 697
- RACLs, applying, 680–681
- SNMP-related issues, 110, 657
- STP, 697–698
- system logging, configuring, 657
- system warning banners, configuring, 654
- trunking connections, limiting, 657
- unused services, disabling, 654–655
- VACLs, applying, 681–683
- vtv line access, 654
- vulnerabilities, SSH, 107–108
- selecting**
 - antennas, 828
 - root ports, 232
- semidirectional antennas, 827**
 - characteristics of, 829
- server fabrics, 42**
- Server Farm module**
 - SANs, 80
 - access layer, 82–84
 - distribution layer, 82
 - switches, 81
- Server Farm submodule, 34**
- service modules for Catalyst 6500 switches, 723, 728–729**
- service provided-managed VLAN services, 179**
- service providers, metro Ethernet, 746**
- service-port interfaces, 861–863**
- set boot system flash command, 121**
- SFM (Switch Fabric Module) module, 726**
- shaped round robin (SRR), 473–474**
- shared round robin (SRR), 474–475**
- shared trees, 511–513**
- show 802.11 commands, 869**
- show adjacency command, 429**
- show adjacency detail command, 429**
- show advanced 802.11 command, 869–870**
- show ap command, 870**
- show catalyst6000 traffic-meter command, 310**
- show client command, 871–872**
- show command, 127**
- show current command, 258**
- show interface command, 101, 131**
- show interfaces command, 163**
- show IP cef command, 426**
- show ip cef detail command, 426**
- show ip mroute command, 536–537**
- show ip route command, 131**
- show looging command, 308**
- show mac address-table interface command, 163**
- show pending command, 258**
- show process cpu command, 309**
- show processes cpu command, 299**
- show radius command, 872**
- show rogue ap command, 872**
- show rogue client command, 872–873**
- show running-config command, 163**
- show running-config interface command, 163**
- show Spanning-Tree command, 242**
- show stats command, 870–871**
- show system command, 310**
- show vlan command, 162**
- show VTP domain command, 195–196**
- show vtp status command, 195–196**
- S-HTTP (Secure-HTTP), 10**
- shutdown interface-level command, 310**
- Single Router Mode (SRM), 566, 569**
- SLB (Server Load Balancing), 602**
 - configuring virtual servers, 606–607
 - configuring the server farm with real servers, 604
 - modes of operation, 603
- slow throughput, troubleshooting, 165**
- SNAP (Subnetwork Access Protocol), 331**
- SNMP (Simple Network Management Protocol), 110–111**
 - configuring, 111–112
 - security issues, 657
- snmp-server user command, 112**
- software, updating versions, 120–121, 124**
- software-switching, 6**
- SONET, metro Ethernet, 751–753**
- source ports**
 - multicast traffic monitoring, disabling, 768
 - SPAN, configuring, 768
- source trees, 510–513**
- source-specific multicast addresses, 506**

SPAN (switch port analyzer)

- CPU monitoring on Catalyst switches, 773–775
- destination ports, configuring, 770
- performance, monitoring, 767–768
- source ports, configuring, 768
- traffic monitoring
 - on Cisco IOS-based Catalyst switches, 769
 - restrictions, 769–770
- Spanning-Tree portfast command, 305**
- split MAC architecture, 851**
- SPT (shortest path tree), 510**
- SRM (Single Router Mode), redundancy on Catalyst 6500 switches, 566–571**
- SRR (shaped round robin), 473–475**
- srr-queue bandwidth shape command, 474**
- srr-queue bandwidth share command, 474**
- SSH (Secure Shell), 5**
 - accessing switches during an upgrade, 121
 - configuring switches for, 106
 - software support, 105
 - study tips, 132
 - vulnerabilities, 107–108
- SSO (Stateful Switchover), 48, 557, 562–563**
 - configuring, 564
 - NSF, 564–566
 - verifying, 564
- SSTP (Shared STP), 238**
- StackWise technology on Catalyst 3750 switches, 735**
- standards for wireless networks, 830**
- stateful inspection, 685**
- Stateful Switchover (SSO), 48, 557, 562–563**
 - configuring, 564
 - NSF, 564–566
 - verifying, 564
- static default gateway configuration, 578**
- static MAC filtering, 673**
- static NAT, 686**
- static VLANs, 154**
- statistics on applications, checking, 311**
- steady state STP, 357**
- sticky feature of Cisco Catalyst switch port security, 671**

STP (Spanning Tree Protocol), 5, 217, 222

- BackboneFast, 280
 - configuring, 284
 - link failures, 281
- BPDUs, 223
 - frame format, 224
 - timers, 224
- bridge IDs, 222
- commands, 301
- configuring, 264
 - verifying configuration, 241–243
- enhancements, 276
- events debug, 298
- IEEE 802.1Q trunks, 238
- Multiple Spanning Tree, 251, 253
 - 802.1q, 252
 - configuring, 256, 258–259
 - IST instances, 254
 - instances, 256
 - PVST+, 252
 - regions, 253
- operation overview, 227
 - planning root bridge selection, 229–230
 - root bridge election, 228
 - selection of root and designated ports, 230–231
- overview, 217
- path cost, 222
- port path cost, 240
- port states, 224–227
- PortFast, 276
 - configuring, 277
- resiliency, 284
 - BPDU filtering, 286
 - BPDU Guard, 284
 - Root Guard, 286–288
- RTSP, 243
 - BPDU format, 246–247
 - port roles, 245
 - rapid transition to forwarding, 247–248
 - topology change mechanism, 249–250
- sample election process scenario, 232–233
- security mechanisms, 697–698
- study tips, 300
- topologies, identifying changes in, 233–235, 269–270

- troubleshooting, 293
 - duplex mismatch*, 294
 - frame corruption*, 295
 - inappropriate STP diameter parameter tuning*, 296
 - methodology*, 297–299
 - PortFast configuration errors*, 296
 - resource error*, 295
 - unidirectional link failures*, 294
- UplinkFast, 278, 300
 - configuring*, 279
- STS-1 (synchronous transport signal-level 1), 752**
- study tips for exam, 635–637**
- subnets**
 - routing packets between, 10
 - troubleshooting, 299
- Subnetwork Access Protocol (SNAP), 331**
- summary keyword, 536**
- Supervisor Engines**
 - redundancy, 557, 559
 - route processor redundancy*, 560–561
 - RPF+*, 561, 564
 - Supervisor Engine 32 (Catalyst 6500), 723–725
 - Supervisor Engine 720 (Catalyst 6500), 86, 727
 - Supervisor Engine II (Catalyst 6500), 725–727
 - Supervisor Engine V-10GE (Catalyst 4500), 48, 731–733
- support for VLANs on Catalyst switches, 157**
- suppression broadcast, 344–345**
- SVI (switch virtual interface), 391**
- switch virtual interface (SVI), 391**
- switching, 560**
 - access layer, 64
 - Cisco Catalyst 3550, 50
 - security*, 50–51
 - Cisco Catalyst 3560, 50, 86
 - security*, 50–51
 - Cisco Catalyst 3750, 50
 - security*, 50–51
 - Cisco Catalyst 4500
 - security*, 49
 - Cisco Catalyst 6500, 95
 - features of*, 45–46
 - hybrid-mode*, 96
 - security*, 47
 - Cisco Catalyst switches
 - configuring*, 98–100
 - DNS*, 108
 - managing configurations*, 112
 - system switches*, 109
 - telnet and SSH*, 104–106
 - troubleshooting*, 126
 - Cisco CatOS, 100
 - MDGs*, 336–337
 - passwords*, 104
 - Cisco IOS Software, NTP settings, 103
 - configuring for SSH, 106
 - distributed, 416
 - distribution layer, 64
 - hardware-switching, 6
 - high availability, 553–555
 - Layer 2, 9, 12
 - Layer 3, 10, 21
 - ARP*, 14
 - packet rewriting*, 13
 - Layer 4
 - performance*, 11
 - terminology*, 10
 - Layer 7, 11
 - legacy Layer 2 switches, 9
 - multilayer, 15
 - physical security, 654
 - port security, features provided by, 666–671, 673–674
 - role of (study tips), 87–88
 - Server Farm module, 81
 - SNMP, 110–112
 - software-switching, 6
 - SSO, 562–566
 - STP topology, securing, 657–658
 - terminology, 8
 - trunking connections, limiting, 657
 - unauthorized access, 95
 - VLANs, troubleshooting, 197
 - VTP-transparent switches, 188
- switching table architectures, 418–421**
- switchport command, 205, 324**
- switchport host command, 160**
- synchronous data, 744**
- synchronous transport signal-level 1 (STS-1), 752**
- syslog servers, logging, 109**

system logging, configuring, 657
 system names, adding meaning to, 98
 system warning banners, configuring, 654

T

TACACS+, AVPs, 659

tail drop, 477

TC (Topology Change) bit set, 233

TCAM (ternary content addressable memory), 7

Telnet

accessing switches during an upgrade, 121
 disabling access, 140
 establishing IP connectivity, 131–132

throttling (ARP), 416–418

TKIP (Temporal Key Integrity Protocol), 859

TLS (transparent LAN service), 748–749

"top of rack" Catalyst switches, 65

topologies

metro Ethernet, 73
 multiple Ethernet technologies, 62
 RTSP, change mechanism, 249–250
 STP, identifying changes in, 269–270

top-ten enterprise WLAN issues, 842

traffic

load balancing, EtherChannel, 329–331
 multicast, 501–503
 CEF-based MMLS, 526
 CGMP, 529–530
 configuring IP, 531–535
 deploying (study tips), 540–541
 forwarding trees, 510–513
 hardware switching, 525
 IGMP snooping, 528–529
 IP addresses, 504–507
 IP protocols, 513–525, 530–531
 Layer 2 protocols, 527–528
 MAC addresses, 507–508
 MFIB, 527
 MMLS, 526
 monitoring IP, 535–539
 reverse path forwarding, 508–510

traffic monitoring

on Cisco IOS-based Catalyst switches, 769
 with SPAN, restrictions, 769–770
 with VSPAN, restrictions, 770

transmit power (WLANs), calculating, 826–827

trees

shared, 511–513
 source, 510–513

troubleshooting

backup/primary root bridges, 231
 building loop-free netwo, 220
 Catalyst switches, 126
 configuration commands, 128
 IP connectivity, 131–132
 show and debug commands, 127
 CEF-based MLS, 430
 configuration, 435–438
 methodology, 431–432
 CPU monitoring on Catalyst 6500 switches, 775
 forwarding loops and black holes, Loop Guard,
 289–291
 IP subnets, 299
 Layer 2 loops, 306–312
 NAM, 799
 preventing bridging loops, 219–220
 STP, 293
 duplex mismatch, 294
 frame corruption, 295
 inappropriate STP diameter parameter
 tuning, 296
 methodology, 297–299
 PortFast configuration errors, 296
 unidirectional link failures, 294
 trunking, 185
 using L2 traceroute, 787–789
 VLANs, 164
 communication issues, 165
 private VLANs, 165–169
 slow throughput, 165
 trunking issues on switches, 197
 VTP, 196

Truncated mode (SFM), 726

trunking

connections, limiting, 657
 DTP, 178
 troubleshooting, 185
 VLANs, 172
 configuring, 181–183
 IEEE 802.1q, 175–178
 ISL, 174
 modes and methods, 181

multilayer switched networks, 173
protocols, 174
verifying configurations, 183–185
 VTP, 185–193
trusting DSCP, 456
tunneling, IEEE 802.1Q-in-Q tunneling, 179

U

UDLD (Unidirectional Link Detection), 275, 355–358
 case study, 362
 configuring, 358–359
UDP (User Datagram Protocol)
 broadcast forwarding, 399
 multicast traffic, 503
unauthorized access, 95
unicast flood-blocking feature, 674
unicast suppression, 345
unidirectional links
 failures, 294
 Loop Guard, 290
UNII (Unlicensed National Information Infrastructure) band, 808
unused services, disabling, 654–655
updating software versions on Catalyst switches, 120–124
uplink port support, 573
UplinkFast, 278,–300
 configuration exercise, 304
 configuring, 279
UPS systems for IP telephony installations, 631
UTP (unshielded twisted-pair), 63

V

VACLs
 applying, 681–683
 with capture option, performance monitoring on Catalyst 6500 switches, 785–787
verifying
 CEF-based MLS, 425
 controller configuration, 869
 show 802.11 commands, 869

show advanced 802.11 commands, 869–870
 show ap commands, 870
 show client commands, 871–872
 show radius commands, 872
 show rogue ap commands, 872
 show rogue client commands, 872–873
 show stats commands, 870–871
 NAM configuration, 797–798
 PortFast, 305–306
 SSO, 564
 STP bridges, 264–267
 STP configuration, 241–243
 VLAN, 207–208
 VTP configuration, 195, 207–208
virtual interfaces, 861–862
virtual LANs. See VLAN
Virtual LANs. See also VLANs, 9, 149
virtual MAC addresses, VRRP, 596
virtualization, 4
VLAN database configuration mode, deleting VLANs, 159
VLAN hopping attacks, preventing, case study, 698–700
VLAN IDs, 176
VLANs (virtual LANs), 5, 9, 149–151
 Cisco metro solutions, 750
 commands, 401
 configuring, 158–161
 private VLANs, 168–171, 208–209
 verifying configuration, 162–163
 deleting, 159
 dynamic, 155
 implementing in campus networks, 152
 end-to-end and local VLANs, 153
 inter-VLAN routing, 385–388
 IP broadcast forwarding, 398–399
 multilayer Catalyst switches, 388–390
 router on a stick, 393–395
 study tips, 400–401
 switch virtual interface, 391–393
 UDP broadcast forwarding, 399
 verifying configuration, 396
 load balancing, 251
 PVST+, 236
 ranges, 156
 ranges and mappings, 178

- service provider-managed VLAN services, 179
 - static, 154
 - study tips, 197, 199–200
 - support for on Catalyst switches, 157
 - troubleshooting, 164, 197
 - communication issues*, 165
 - private VLANs*, 165–169
 - slow throughput*, 165
 - trunking, 172
 - configuration*, 181–183
 - IEEE 802.1 Q*, 175–178
 - ISL*, 174
 - modes and methods*, 181
 - multilayer switched networks*, 173
 - protocols*, 174
 - troubleshooting*, 185
 - verifying configurations*, 183–185
 - VMPSs (VLAN management policy servers), 154–155**
 - voice VLANs**
 - configuring on Catalyst switches running Cisco IOS, 628–629
 - deploying in IP telephony installations, 627–629
 - VoIP (Voice over IP), deploying in converged networks, reasons for, 622–623**
 - VPNs (Virtual Private Networks), 4**
 - VRRP (Virtual Router Redundancy Protocol), 10, 596**
 - VSPAN**
 - on Cisco CatOS-based switches, capturing traffic, 772
 - on Cisco IOS-based Catalyst switches
 - configuring*, 773
 - performance monitoring, 767–768
 - traffic monitoring, restrictions, 770
 - VTP (VLAN Trunking Protocol), 185–186**
 - advertisements, 188
 - authentication, 192
 - configuring, 192–193
 - modes of operation, 187
 - pruning, 189
 - troubleshooting, 196
 - verifying, 207–208
 - versions, 190–191
 - vtp domain domain-name command, 204**
 - vtp mode command, 204**
 - vtp password command, 204**
 - vtp v2-mode command, 193**
 - VTP-transparent switches, 188**
 - vtv lines, securing access to, 654**
 - vulnerabilities of SSH, 107–108**
-
- ## W
-
- WANs (wide-area networks), 809**
 - wavelengths (electromagnetic spectrum), 756**
 - WDM (Wave Division Multiplexing), metro Ethernet, 754–755**
 - WEP (Wired Equivalent Privacy), 813**
 - Wi-Fi Alliance, 830**
 - wireless bridges**
 - building blocks, 821–822
 - cost of, 822
 - non-root bridges, 839
 - root bridges 838
 - root mode, 822
 - wireless clients, AP association, 856–857**
 - Wireless LAN Controllers, 817**
 - wireless networks, 818**
 - ISM bands, 808
 - microwave, 823
 - regulatory agencies and standards, 830
 - UNII band, 808
 - wireless repeaters, 820**
 - WLANA (Wireless LAN Association), 830**
 - WLANS, 818**
 - ad hoc mode, 815, 819
 - antennas, 827–828
 - highly directional*, 829
 - omnidirectional*, 828
 - selecting*, 828
 - semidirectional*, 829
 - APs
 - autonomous*, 816
 - Lightweight*, 816
 - lightweight*, 817
 - microcell architecture*, 823
 - wireless repeaters*, 820
 - BSSs, 819
 - Cisco WCS, 846
 - Cisco Wireless Location Appliance, 847
 - Cisco WiSM, 846

- Cisco WLCM, 846
- CiscoWorks WLSE, 847
- CiscoWorks WLSE Express, 847
- clients, 815–816
- comparing with Ethernet, 812–813
 - compression issues, 814*
 - environmental issues, 813–814*
 - mobility, 814*
 - privacy issues, 813*
 - regulatory issues, 814–815*
- controllers
 - configuring, 865–869*
 - connecting to, 864–865*
 - verifying configuration, 869–873*
- ESS, 819
- infrastructure mode, 815
- interfaces, configuring, 861, 863–864
- lightweight APs, managing, 845–846
- RF gain, 827
- security, 858–859
- topology building blocks, 819–820
- transmit power, calculating, 826–827
- Wireless LAN Controllers, 817

WRED (weighted random early detection), 478

write erase command, 113

WRR (weighted round robin), 471

X-Y-Z

- Yagi antennas, 829
- ynamic, 156