

Index

Numerics

- “10/100” ports, 87
- “10/100/1000” ports, 90
- 10 Mbps Ethernet, 85–86
- 10GbE, 90–91
 - PMD types, 91
 - switch compatibility listing, website, 91
- 10-Gigabit Ethernet Alliance, 90
- 20/80 rule, 19, 118
- 80/20 rule, 18, 118
- 802.11 standard
 - 802.11a, 463–464
 - 802.11b, 460
 - channels, 461
 - data rates, 462
 - 802.11g, 463
 - ASDs, 481
 - authentication methods, 476–477
 - backward compatibility, 463
 - BSS, 440
 - frame type compliance, 460
 - regulatory agencies, 459–460
 - security
 - EAP-based, 477–479
 - WPA, 479–480
 - WPA2, 480
 - service sets, ESS, 440
- 802.1Q. *See* IEEE 802.1Q
- 802.1x, configuring, 392

A

- absorption, 448–449
- access layer, 21
- accessing trunks with switch spoofing, 420–422
- aCEF (Accelerated CEF), 299

- ACLs (access control lists), 64. *See also* VACLs
- active scanning, 484–485
- active STP features, verifying on switch ports, 254
- adding text descriptions to switch ports, 96
- ad-hoc wireless networks, 439
- adjacency table, 299
 - contents, displaying, 300
 - discard adjacencies, 302
 - drop adjacency, 301
 - null adjacencies, 301
 - punt adjacencies, 302
- adjacent hosts, 297
- advertisements, VTP, 139–141
 - requests, 143–144
 - subset advertisements, 142
 - summary advertisements, 142
- AES (Advanced Encryption Standard), 480
- aggressive mode (UDLD), 252
- alternate port on RSTP topology, 264
- AM (amplitude modulation), 446
- anchor points, 518
- ANSI (American National Standards Institute) X3T11 FibreChannel.
See FibreChannel
- answers to scenarios
 - scenario 1, 544
 - scenario 2, 544–545
 - scenario 3, 545
 - scenario 4, 545–546
 - scenario 5, 547
 - scenario 6, 547–548
 - scenario 7, 548–549
 - scenario 8, 550
 - scenario 9, 551
- antenna gain, 456

antennas, 457
diversity, 458
highly directional, 458–459
omnidirectional, 457–458
semi-directional, 458

application-specific integrated circuits (ASICs), 10

applying VACLs to VLAN interfaces, 414

APs (access points), 440–442. *See also*
lightweight APs
ASDs, 481
associations, 482–486
autonomous
 management processes, 504
 real-time processes, 504
 SSIDs, 502–503
 traffic patterns through, 502
cells, 442–443
 coverage, expanding, 444–445
 microcells, 445
 sizing, 488–489
channels, layout considerations, 489–492
current running mode, displaying, 528
lightweight
 inter-controller roaming, 514–518
 intra-controller roaming, 512–513
 roaming, 511
overall gain, calculating, 456–457
RF communication, EIRP, 456
roaming, 444, 482–484
 associations, 486
 implications of, 486–487
 scanning process, 484–485
security, implementing, 475–480
signal strength, 452–453
 dB values, 453–454
 increase in, 455–456
 loss of, 454–455

ARP inspection, configuring, 399–401

ARP spoofing, 400

ARP throttling, 301

ASDs (application-specific devices), 481

ASICs (application-specific integrated circuits), 10

assessing
current traffic patterns, 47
interface data rates, 46–47

assigning
descriptions to switch ports, 96
management addresses to VLANs, 40
switch ports to VLANs, 116

associating secondary VLANs to primary VLAN SVI, 419–420

associations, 440, 482–486

attributes of core devices, 22

authentication
in 802.11 networks, 476–477
MD5, 321
port-based
 configuring, 392–394
 example, 394

automatically configuring STP timers, 231–232

autonegotiation, 87
10/100/1000 ports, 9
autonomous APs, 501
management processes, 504
real-time processes, 504
SSIDs, 502–503
traffic patterns through, 502

Auto-QoS, 375–378

autosensing on Catalyst switches, 92

AVF (active virtual forwarder), 330–333

AVG (active virtual gateway), 330–331

avoiding collisions in WLANs, 436–437
DCF, 437–438

B

- baby giant frames, 123**
- BackboneFast, 236**
 - enabling, 236–237
- backup port on RSTP topology, 264**
- backward compatibility of 802.11 standards, 463**
- bands, 446**
 - ISM, 461
- best effort QoS, 367–368**
- best practices for securing Catalyst switches, 401–404**
- Blocking state (STP), 197**
- bootstrap process for LAPs, 508**
- BPDU filtering, 254**
- BPDU Guard, 248–249**
- BPDUs (bridge protocol data units)**
 - Configuration BPDUs, 189–190
 - convergence, 267
 - in RSTP topology, 265
 - MST, 274
 - protecting against sudden loss, 250
 - Root Guard, 247–248
 - RSTP, 265
 - TCN BPDUs, 200
- Bridge IDs, 191**
- bridging, transparent**
 - redundancy, 187–188
 - versus Ethernet switches, 185–186
- bridging loops, 187**
 - broadcast storms, 188
 - preventing, 189
- broadcast domains, 14**
 - flat networks, 113
- broadcast storms, 188**
- BSS (Basic Service Set), 440**
- BSSI (Basic Service Set Identifier) field, 460**
- building access switches, 21**
- building block model**
 - core block, 36–38
 - enterprise edge block, 40–41
 - network management block, 40
 - server farm block, 39–40
 - service provider edge block, 41
- bundled ports (EtherChannel), 165**
 - distributed EtherChannel traffic, 165–167
 - troubleshooting, 172–175

C

- cabling**
 - Category 5 crossover cables, 93
 - connecting to switch console port, 92
 - Ethernet
 - distance limitations, 86
 - Fast Ethernet specifications, 87
- calculating**
 - EIRP, 456
 - Fresnel zone radius, 451–452
 - overall gain, 456–457
 - Root Path Cost, 193
- CAM (Content Addressable Memory), 64**
- CAM tables, 69–70**
 - duplicate entries, handling, 70
 - entries, viewing, 74
 - stale entries, 69
 - static entries, configuring, 69
 - troubleshooting, 75
- campus networks, 13**
 - building block model
 - core block, 36–38
 - enterprise edge block, 40–41
 - network management block, 40
 - server farm block, 39–40
 - service provider edge block, 41
 - dual-core with Layer 2 distribution switches, 41–42
 - LAN segmentation model, 15–17
 - modular design, 31
 - core block, 35–38
 - switch block, 32–35
 - network traffic models, 18–19
 - predictable network model, 19–20
 - shared network model, 13–14
- campus-wide VLANs, deploying, 118–119**
- canonical format, 123**
- carrier signals, 446**
- Catalyst switches**
 - autosensing, 92
 - Fast Ethernet ports, 92
 - NSF, configuring, 343
 - port security, 389–391
 - PortFast feature, 205
 - ports, configuring, 94
 - power supply redundancy, configuring, 343–345
 - redundancy modes, 339
 - configuring, 340–341

- securing, best practices, 401–404
- supervisor synchronization,
 - configuring, 342
- UDLD, default message interval times, 253
- Category 5 crossover cables, 93**
- CCX (Cisco Compatible Extensions), 481**
- CDP (Cisco Discovery Protocol), 43**
 - discovering network topology, 44–46
- CEF (Cisco Express Forwarding), 66, 295.**
 - See also fallback bridging*
 - adjacency table, 299, 301
 - configuring, 303
 - entry information, displaying, 298
 - FIB, 296, 299
 - glean state, ARP throttling, 301
 - packet rewrites, 302–303
 - process switching, 68
 - verifying operation, 307–308
- cells, 442–443**
 - coverage, expanding, 444–445
 - microcells, 445
 - sizing for WLAN design, 488–489
- CFI (Canonical Format Indicator), 123**
- channel reuse, 490**
- channel-protocol command, 170**
- channels, 447**
 - 802.11b, 461
 - layout considerations, 489–492
 - spectral masks, 461
- Cisco ILP (Inline Power), 357**
- Cisco IP Phones**
 - inline power, 359–360
 - PoE, 357
 - configuring, 360*
 - powered device detection, 358–360*
 - verifying power status, 360–361*
 - trunking modes, 363
- Cisco Unified Wireless Network, 503**
 - traffic patterns within, 509–511
- class selector bits, 371–372**
- classification, 372–373**
- clearing port cache, 390**
- client mode (VTP), 140**
 - configuring, 146
- collapsed core block, 36–37**
- collision domain, 13**
- collisions**
 - avoiding in WLANs, 436–437
 - DCF, 437–438*
 - preventing, 15
- commands**
 - channel-protocol, 170
 - debug spanning-tree switch state, 198
 - errdisable detect cause, 98
 - interface range, 95
 - lACP port-priority, 172
 - name, 116
 - no shutdown, 294
 - show adjacency summary, 300
 - show cdp neighbors, 44
 - show cdp neighbors detail, 45
 - show dot1x all, 394
 - show etherchannel load-balance, 175
 - show etherchannel port, 173
 - show etherchannel port-channel, 168
 - show etherchannel summary, 173
 - show glbp, 336
 - show interface, 99
 - show interface status, 305
 - show interface switchport, 364
 - show interface trunk, 129–130
 - show interfaces switchport, 129
 - show ip cef, 297
 - show ip interface, 306
 - show ip interface brief, 307
 - show lacp sys-id, 175
 - show mac address-table, 74
 - show port-security interface,
 - 391–392
 - show power, 345
 - show spanning-tree interface,
 - 198, 229, 365
 - show spanning-tree vlan,
 - 232, 271
 - show vlan, 116, 305
 - show vlan id, 128
 - show vtp counters, 148
 - show vtp, 153
 - show vtp status, 144, 148
 - shutdown, 99, 305
 - spanning-tree guard loop, 251
 - spanning-tree guard root, 248
 - spanning-tree portfast, 270
 - speed, 97
 - switchport, 116, 124, 292–293
 - switchport host, 404
 - switchport priority extend trust, 379
 - udld, 252
 - vtp mode transparent, 115
- community VLANs, 415**

comparing

- Ethernet switches and transparent bridges, 185–186
- STP switch ports, roles versus states, 264
- wired and wireless LANs, 435–436
- wireless service sets, 439

conceding HSRP router election, 321–322**Configuration BPDUs, 189–190****configuring**

- ARP inspection, 399–401
- BackboneFast, 236–237
- Catalyst switches
 - NSF*, 343
 - port security*, 389–391
 - power supply redundancy*, 343–345
 - redundancy mode*, 340–341
 - supervisor synchronization*, 342
- CEF, 303
- DHCP snooping, 395–397
- dual core blocks, 38
- EtherChannel, 170
 - LACP*, 171
 - load balancing*, 167–168
 - PAgP*, 170
- Ethernet switch ports, 88
- fallback bridging, 304
- interVLAN routing, 292
 - Layer 2 ports*, 292
 - Layer 3 ports*, 293–294
 - SVI ports*, 294
- IP Source Guard, 397–399
- LACP EtherChannel, 171–172
- LAPs, 524–528
 - power supply*, 525
 - switch port*, 525–526
- modular network designs, 31
- MST, 277–279
- PAgP negotiation, 170–171
- PoE, 360
- port-based authentication, 392
 - 802.1x method lists*, 393–394
- PortFast, 233–234
- PVLANS, 416–417
 - mapping promiscuous mode ports*, 418–419
- QoS
 - trust*, 374–375
 - with Auto-QoS*, 375–378

RPVST+, 271–272

RSTP, 270

static CAM table entries, 69

static VLANs, 115–116

STP

network diameter value, 200*Root Bridge*, 223–226*timers*, 230–231*UDLD*, 253

switch ports, 94–95

duplex mode, 97*speed*, 96

UDLD message interval, 252

VACLs, 413–414

VLAN trunks, 124–126

example configuration, 126–127

voice VLANs, 362–363

VRRP, 328

VTP, 144

client mode, 146*example configuration*, 148*management domains*, 145*pruning*, 151–152*server mode*, 145*transparent mode*, 146*version*, 146

WLC, 519–524

congestion

80/20 rule, 18

relieving, 13

connecting

switch block devices, 92–93

to console ports, 92

connectivity

core blocks, 36–38

logical, 113

of switch ports, troubleshooting, 100–101

connectors for GbE, 93–94**consistency checks, VTP version 2, 147****console ports**

connecting switch block devices, 92

connecting to, 92

Control frames, 460**controllers, foreign agents, 518****convergence**

controlling on STP

with BackboneFast, 236*with PortFast*, 233*with UplinkFast*, 234–235

- of RSTP topology, 265
 - port types*, 266
 - synchronization*, 267–268
- STP, tuning, 229–232
- STP timers, 199
- TCN BPDUs, 200
- core block, 31, 35–38**
 - collapsed core, 36–37
 - dual core, 37–38
 - scaling, 38–39
- core layer, 22**
- CoS (class of service), 369**
- criteria for process switching, 68**
- crossover cables, Category 5, 93**
- CSMA/CA (carrier sense multiple access collision avoidance), 436–437**
- CSMA/CD (carrier sense multiple access collision detect), 85**
- CST (Common Spanning Tree), 206**
- current traffic patterns, assessing, 47**
- customizing STP, 226–227**
 - Port ID, 228–229
 - Root Path Cost, 227–228
 - timers, 230–231

D

- DAI (dynamic ARP inspection), 400**
 - status information, displaying, 401
- Data frames, 460**
- data rates for 802.11b standard, 462**
- dB (decibel), 453**
- dCEF (Distributed CEF), 299**
- DCF (Distributed Coordination Function), 437–438**
- debug spanning-tree switch state command, 198**
- decision processes for MLS packet forwarding, 66–68**
- default UDLD message interval times, 253**
- defining**
 - MST regions, 277–278
 - VACL matching conditions, 413–414
- delay, 367**
- deleting VLANs from switch ports, 116**
- demand-based switching, 65**
- deploying VLANs, 117**
 - end-to-end, 118–119
 - local, 118

descriptions, adding to switch ports, 96

designated ports

- election procedure, 195–196
- on RSTP topology, 264
- selection of, 196–197

designing

- campus networks
 - enterprise edge block*, 40–41
 - network management block*, 40
 - predictable network model*, 19–20
 - server farm block*, 39–40
 - service provider edge block*, 41
- enterprise networks, evaluating existing network, 42–47
- hierarchical networks
 - access layer*, 21
 - core layer*, 22
 - devices*, 22
 - distribution layer*, 21
- WLANs, 487
 - AP cells, sizing*, 488–489
 - channel layout*, 489–492

detecting

- duplex mode mismatches on links, 100–101
- switch port error conditions, 97–99

devices

- distribution layers, 21
- in hierarchical network design, 22
- Layer 2 switching, 10
- Layer 3 routing, 11
- Layer 3 switching, 11
- Layer 4 switching, 12
- MLS, 12

DHCP snooping, configuring, 395–397

diffraction, 449–450

DiffServ QoS model, 368–369

- Layer 2 classification, 369
- Layer 3 classification, 370–371
 - class selector bits*, 371–372
 - drop precedence*, 372
- packet classification, 372–373
- trust boundaries, 373

DIFS (DCF interframe space), 437

direct topology changes, 201–202

Disabled state (STP), 197

disabling

- DTP, 126
- STP with BPDU filtering, 254

discard adjacencies, 302

discovering network topology, 43–47**displaying**

- active EtherChannel parameters on ports, 175
- adjacency table contents, 300
- AP current running mode, 528
- CAM table entries, 74
- CEF entry information, 298
- DAI status information, 401
- detailed GLBP configuration information, 337–338
- port configuration, 175
- port status, 391
- PortFast status, 234
- STP information, 237
- switch ports
 - in root-inconsistent state, 248*
 - speed, 99*
- trunking status, 126
- UpLinkFast status, 235
- VRRP status information, 328
- VTP management domain parameters, 148
- VTP status, 148–149

distributing EtherChannel traffic, 165–167**distribution layer, 21**

- collapsed core block, 36

diversity, 458**“don’t care” bits, 72****double tagging. See ISL****drop adjacencies, 301****drop precedence, 372****DSCP (Differentiated Service Code Point), Layer 3 QoS classification, 370–371****DSSS (Direct Sequence Spread Spectrum), 462****DTP (Dynamic Trunking Protocol), 123–124**
disabling, 126**dual-core campus networks, 37–38**

- with Layer 2 distribution switches, 41–42

dual-homing, 39**duplex autonegotiation, 88****duplex mode**

- link mismatches, detecting, 100–101
- switch port configuration, 97

duplicate CAM table entries, handling, 70**dynamic auto trunking mode, 125****dynamic data rate scaling, 462****dynamic desirable trunking mode, 125****dynamic VLANs, 117****E****EAP-based security, 477–479**

- EAP-FAST, 479
- EAP-TLS, 478
- LEAP, 478
- PEAP, 479

EAP-FAST (EAP Flexible Authentication via Secure Tunneling), 479**EAPOL (Extensible Authentication Protocol over LANs)**

- configuring, 392
- port-based authentication, configuring, 392–394

EAP-TLS (EAP-Transport Layer Security), 478**edge ports, RSTP, 266**

- configuring, 270

EIRP (Effective Isotropic Radiated Power), 456**election process**

- of Designated Ports, 195–196
- of Root Bridge, 191–192
- of Root Ports, 192–194

enabling

- BPDU guard as default, 249
- GLBP, 334–337
- loop guard as default, 251
- MST, 277–279
- PortFast, 270
- root guard, 248
- UDLD, 252
- VTP pruning, 151–152

encryption, AES, 480**end-to-end VLANs, deploying, 118–119****enterprise composite network model**

- core block, 35–36
 - collapsed core block, 36–37*
 - dual core block, 37–38*
- enterprise edge block, 40–41
- network management block, 40
- server farm block, 39–40
- service provider edge block, 41
- switch block, 32–33
 - distribution layer, 33*
 - sizing, 33–35*

enterprise edge block, 31, 40–41

enterprise networks
 designing, 42–47
 end-to-end VLANs, deploying, 118

errdisable detect cause command, 98

errdisable state, 249

ESS (Extended Service Set), 440

EtherChannel, 164
 active parameters, displaying, 175
 bundled ports, 165
 configuring, 170
 hashing algorithm, 165
 LACP, 169
 configuring, 171–172
 load balancing
 configuring, 167–168
 verifying effectiveness of, 168
 negotiation protocols
 LACP, 169–170
 PAgP, 169–171
 PAgP, 169
 configuring, 170
 redundancy, 165
 routers, forwarding frames based on IP
 address, 168
 traffic distribution, 165–167
 troubleshooting, 172–175
 XOR operation, 165

Ethernet
 10-Gigabit Ethernet, 90–91
 10-Mbps Ethernet, 85–86
 cabling, distance limitations, 86
 CSMA/CD, 85
 Fast Ethernet, 86
 autonegotiation, 88
 backward compatibility, 87
 cabling specifications, 87
 FEC, 89
 FibreChannel, 89
 full-duplex, 87–89
 full-duplex operation, 86
 GbE, 89–90
 available SPF modules, 93–94
 port cables, 93–94
 half-duplex operation, 85
 switch block connections, 92–93
 Gigabit Ethernet port cables, 93–94

examples
 of port-based authentication, 394
 of TCAM tables, 72–73
 of VTP configuration, 148

expanding AP cell coverage, 444–445

exploits, VLAN hopping, 422
 thwarting, 423–424

extended-range VLANs, 115

F

fallback bridging, 68, 303
 configuring, 304
 verifying, 308
 verifying configuration, 308

Fast Ethernet, 86
 autonegotiation, 88
 backward compatibility, 87
 cabling specifications, 87
 Catalyst switch ports, 92
 FEC, 89
 FibreChannel, 89
 full-duplex, 87–89
 link speed, autonegotiation, 88
 links, duplex mismatches, 88
 switch ports, configuring, 88

FDDI (Fiber Distributed Data Interface), 10

FEC (Fast EtherChannel), 89, 164

FIB (Forwarding Information Base), 66, 296–298
 adjacency table, 299

Fiber Distributed Data Interface (FDDI), 10

FibreChannel, 89

fields of Configuration BPDUs, 190

flat networks, 113

flooding, VTP pruning, 149–152

FM (frequency modulation), 446

foreign agents, 518

Forward Delay, 197

Forward Delay timer (STP), 199, 230

forwarding
 frames
 decision processes, 63–65
 Layer 2 switching, 10
 Layer 3 switching, 11
 oversize, 123
 packets
 Layer 3 routing, 11
 Layer 4 switching, 12

Forwarding state (STP), 197

frame identification. See tagging

frames
 802.11 compliance, 460
 baby giants, 123

BPDUs
Configuration BPDUs, 189–190
TCN BPDUs, 200
 forwarding through Layer 2 switches,
 63–65
 Layer 2 switching, 10
 Layer 3 switching, 11
 multicast, 14
 tagging
IEEE 802.1Q, 122
internal tagging, 122
 unknown unicast, 149, 186

frequencies

bands, 446
ISM, 461
 channels, 447
spectral masks, 461
 modulation
DSSS, 462
OFDM, 463

Fresnel zones, 450–452**full-duplex Ethernet, 435****full-duplex Fast Ethernet, 87–89****full-duplex operation, 86****functionality, switching, 9–12****functions of WLCs, 506–507****G****gateway redundancy, 317**

GLBP, 330–337
 HSRP, 318–326
 verifying, 338
 VRRP, 327–329

GbE (Gigabit Ethernet)

available SPF modules, 93–94
 port cables, 93–94

GBIC (Gigabit Interface Converter) modules, 93

Gigabit Ethernet media, 93–94

GEC (Gigabit EtherChannel), 90, 164**Get Nearest Server (GNS), 14****Gigabit Ethernet, 89–90****GLBP (Gateway Load Balancing Protocol), 330**

AVF, 331–333
 AVG, 330–331
 displaying detailed configuration
 information, 337–338

enabling, 334–337
 load balancing, 333
 verifying operation, 336

glean state, ARP throttling, 301**GNS (Get Nearest Server), 14****grouping resources into building blocks, 39****H****half-duplex operation, 85**

in RSTP topology, 266
 in WLANs, 436

hardening Catalyst switches, best practices, 401–404**hardware-based bridging, 10****hashing algorithm (EtherChannel), 165****Hello Time interval (RSTP), 265****Hello timer (STP), 199, 230****hierarchical network design, 20**

access layer, 21
 core layer, 22
 devices, 22
 distribution layer, 21
 migrating to, 47–50

highly directional antennas, 458–459**host mode (switch ports), 416****HSRP (Hot Standby Routing Protocol), 318**

gateway addressing, 322–323
 hello time, decreasing, 319
 load balancing, 324–326
 MD5 authentication, 321
 plain-text authentication, 320
 router election, 318–320
conceding, 321–322

I**IBSS (Independent Basic Service Set), 439****identifying**

switch ports, 96
 VLAN frames
IEEE 802.1Q, 122
on trunk links. See tagging

IEEE 802.11 standard

802.11a, 463–464
 802.11b, 460
channels, 461
data rates, 462
 802.11g, 463

- ASDs, 481
- authentication methods, 476–477
- backward compatibility, 463
- BSS, 440
- frame type compliance, 460
- regulatory agencies, 459–460
- security
 - EAP-based*, 477–479
 - WPA*, 479–480
 - WPA2*, 480
- service sets, ESS, 440
- IEEE 802.1d. See STP (Spanning Tree Protocol)**
- IEEE 802.1Q, 122, 272, 369**
 - CST, 206
 - native VLAN, 122
 - TCI field, 123
 - VID, 123
- IEEE 802.1w. See RSTP (Rapid STP)**
- IEEE 802.1x, configuring, 392**
- IEEE 802.3 standard. See Ethernet implementing**
 - MST, 274
 - security in WLANs, 475–476
 - EAP-based*, 477–479
 - WPA*, 479–480
 - WPA2*, 480
- independence, 265**
- indirect failures on STP, 230**
- indirect topology changes, 202–204**
- initial LAP configuration, 526–528**
- initial WLC configuration, 521**
- inline power for Cisco IP Phones, 359–360.**
 - See also PoE (Power over Ethernet)*
- insignificant topology changes, 204–205**
- inter-controller roaming, 514–518**
- interface data rates, assessing, 46–47**
- interface range command, 95**
- interface range macro, 95**
- interfaces**
 - MAC addresses, clearing, 390
 - SVIs, 294
- internal tagging, 122**
- interoperability of STP and RSTP, 265**
- interVLAN routing, 291**
 - configuring, 292
 - interfaces, 292
 - Layer 2 ports, configuring, 292
 - Layer 3 ports, configuring, 293–294

- multilayer switches, interface types, 292
 - SVI ports, configuring, 294
 - verifying, 304–307
- intra-controller roaming, 512–513**
- IntServ QoS model, 368**
- IP addressing, VLANs, 117**
- IP Source Guard, configuring, 397–399**
- IP Telephony**
 - Cisco IP Phones
 - inline power*, 359
 - PoE*, 357–361
 - trunking modes*, 363
 - QoS, 366
 - trust, configuring*, 374–375
 - verifying*, 379
 - voice VLANs, 361–362
 - configuring*, 362–363
 - verifying operation*, 364–366
- ISL (Inter-Switch Link), 121–122, 369**
- ISM (Industrial, Scientific, and Medical) band, 461**
- isolated VLANs, 415**
- IST (Internal Spanning Tree), 275**

J-K-L

- jitter, 367

- keywords for CAM table commands, 69

- LACP (Link Aggregation Control Protocol), 169–170**

- negotiation, configuring, 171–172

- lacp port-priority command, 172**

- LAN PHY, 91**

- LAN segmentation model, 15–17**

- LAN switching, duplicate entries in CAM table, handling, 70**

- LANs**

- campus networks

- predictable network model*, 19–20

- shared network model*, 13–14

- Cisco Unified Wireless Network, 503

- Ethernet, 85–86

- 10-Gigabit Ethernet*, 90–91

- cabling, distance limitations*, 86

- CSMA/CD*, 85

- Fast Ethernet*, 86–87, 89

- full-duplex operation*, 86
 - Gigabit Ethernet*, 89–90
 - half-duplex operation*, 85
 - Token Ring, susceptibility to collisions, 13
 - LAPs (lightweight access points), 505**
 - bootstrap process, 508
 - configuring, 524–528
 - linking to WLCs, 505–506
 - power supply, configuring, 525
 - switch port, configuring, 525–526
 - latency, 367**
 - Layer 2 distribution switches on dual-core campus networks, 41–42**
 - Layer 2 ports, interVLAN routing configuration, 292**
 - Layer 2 QoS classification, 369**
 - Layer 2 switching, 10, 61**
 - CAM table, 69–70
 - entries, viewing*, 74
 - stale entries*, 69
 - static entries, configuring*, 69
 - troubleshooting*, 74–75
 - frame processing, 63–65
 - TCAM tables, 70
 - example*, 72–73
 - LOUs*, 74
 - port operation*, 73
 - structure*, 70–71
 - troubleshooting*, 75
 - VMR combinations*, 71
 - transparent bridging, 61–63
 - Layer 3 Engine, 296**
 - CEF
 - adjacency table*, 299
 - configuring*, 303
 - packet rewrites*, 302–303
 - FIB, 296–297
 - adjacency table*, 299
 - Layer 3 ports, interVLAN routing configuration, 293–294**
 - Layer 3 QoS classification, 370–372**
 - class selector bits, 371–372
 - drop precedence, 372
 - Layer 3 routing, 11**
 - Layer 3 switching, 11**
 - MLS, 13
 - Layer 4 switching, 12**
 - layers, 9–12**
 - distribution, 21
 - LEAP (Lightweight EAP), 478**
 - Learning state (STP), 197**
 - lightweight APs**
 - inter-controller roaming, 514–518
 - intra-controller roaming, 512–513
 - roaming, 511
 - limitations**
 - of extended-range VLANs, 115
 - of flat networks, 113
 - line-of-sight links, 441**
 - Fresnel zones, 451
 - link speed, autonegotiation, 88**
 - linking LAPs and WLCs, 505–506**
 - links**
 - duplex mismatches, 88
 - detecting*, 100–101
 - EtherChannel, 164
 - redundancy*, 165
 - Listening state (STP), 197**
 - listing switch ports in root-inconsistent state, 248**
 - load balancing**
 - EtherChannel configuration, 167
 - GLBP, 333
 - HSRP, 324–326
 - local VLANs, deploying, 118**
 - logical addressing, 11**
 - logical connectivity, 113**
 - loop avoidance, STP, 250**
 - BPDU Guard, 248–249
 - loop guard, 251
 - Root Guard, 247–248
 - troubleshooting, 254
 - UDLD, 251–253
 - loop guard, 250–251**
 - enabling as default, 251
 - ports, loop-inconsistent state, 250
 - loop-inconsistent state, 250**
 - loss, 367**
 - LOUs (Logical Operation Units), 74**
- ## M
- MAC addresses, sticky, 389**
 - macros**
 - interface range macro, 95
 - spanning-tree vlan command, 226

- management addresses, assigning to VLANs, 40**
- management blocks, 31**
- management domains, 139**
 - advertisement process, 140–141
 - advertisement requests, 143–144*
 - subset advertisements, 142*
 - summary advertisements, 142*
 - configuring, 145
 - parameters, displaying, 148
 - viewing status, 148–149
- management frames, 460**
- manually configuring STP timers, 230–231**
- mapping**
 - promiscuous mode ports
 - PVLAN configuration, 418–419*
 - to primary/secondary VLAN, 418*
 - VLANs to multiple STP instances, 274–275
 - IST, 275*
 - MSTIs, 275–277*
- matching conditions for VACLs, defining, 413–414**
- MaxAge timer (STP), 199, 230**
- MD5 authentication, 321**
- membership methods of VLANs, port-based, 114**
- message interval on UDLD, configuring, 252**
- messages, TC (topology change), 269**
- method lists (802.1x), configuring port-based authentication, 393–394**
- MIC (Message Integrity Check), 479–480**
- microcells, 445**
- migrating to hierarchical network design, 47–50**
- mismatched duplex/speed on ports, monitoring, 100–101**
- mitigating spoofing attacks**
 - with ARP inspection, 399–401
 - with DHCP snooping, 395–397
 - with IP Source Guard snooping, 397–399
- MLS (multilayer switching), 12**
 - CAM table, 69–70
 - duplicate entries, handling, 70*
 - entries, viewing, 74*
 - stale entries, 69*
 - static entries, configuring, 69*
 - troubleshooting, 74–75*
 - CEF, 66, 295
 - adjacency table, 299–301*
 - configuring, 303*
 - FIB, 296, 299*
 - glean state, 301*
 - packet rewrites, 302–303*
 - verifying operation, 307–308*
 - interVLAN routing
 - configuring, 292–294*
 - interfaces, 292*
 - verifying, 304–307*
 - packet forwarding, exceptions for, 68
 - packet processing, 66–68
 - route-caching, 65
 - TCAM table, 70
 - example, 72–73*
 - LOUs, 74*
 - port operations, 73*
 - structure, 70–71*
 - troubleshooting, 75*
 - VMR combinations, 71*
 - topology-based, 65
- mobility groups, 518**
- models of campus networks, 13**
- modifying STP timers, 230–231**
- modular network design, 31**
 - core block, 35–36
 - collapsed core, 36–37*
 - dual core, 37–38*
 - migrating to, 48–50*
 - switch block, 32–33
 - distribution layer, 33*
 - sizing, 33–35*
- modulation, 446**
 - DSSS, 462
 - ODFM, 463
- monitoring port speed/duplex mismatches, 100–101**
- MST (Multiple Spanning Tree), 273–274**
 - configuring, 277–279
 - IST instances, 275
 - MST instances, 276
 - regions, 274
- MSTIs (Multiple Spanning Tree instances), 275–277**
- MSTP (Multiple Spanning Tree Protocol), 272**
- MT-RJ connectors, 92**
- multicast frames, 14**
- multicast traffic, 14**

- multilayer switching (MLS), 12**
 - CEF, 295
 - interface types, 292
 - interVLAN routing
 - configuring, 292*
 - Layer 2 ports, configuring, 292*
 - Layer 3 ports, configuring, 293–294*
 - SVI ports, configuring, 294*
 - router redundancy, 317
 - GLBP, 330–337*
 - HSRP, 318–326*
 - VRRP, 327–329*
- multipath interference, 458**

N

- name command, 116**
- native VLAN, 122**
- negotiation protocols**
 - LACP, 169–170
 - configuring, 171–172*
 - PAgP, 169
 - configuring, 170–171*
- NetFlow switching, 295**
- network diameter value, configuring, 200**
- network management block, 40**
- network topology, discovering, 43–47**
- network traffic models, 18–19**
- no shutdown command, 294**
- normal mode (UDLD), 252**
- NSF (non-stop forwarding), configuring on**
 - Catalyst switches, 343
- null adjacencies, 301**

O

- ODFM (Orthogonal Frequency Division Multiplexing), 463**
- omnidirectional antennas, 457–458**
- “one-armed router,” 291**
- open authentication, 477**
- overall gain, calculating, 456–457**
- oversize frames, forwarding, 123**

P

- packet filtering, configuring VACLs, 413–414**
- packet forwarding, 317**
- packet rewrites, 302–303**

- packets**
 - CEF punt, 298
 - classification, 372–373
 - Layer 3 routing, 11
 - Layer 4 switching, 12
 - processing through multilayer switches, 66–68
- PAgP (Port Aggregation Protocol), 169**
 - configuring, 170–171
 - silent submode, 171
- parameters of VTP management domains, displaying, 148**
- passive scanning, 484–485**
- Path Cost, 193**
- path loss, 454**
- PDU (protocol data unit), 9**
- PEAP (Protected EAP), 479**
- physical connectivity, 113**
- PKC (proactive key caching), 480**
- plain-text HSRP authentication, 320**
- PMD (Physical Media Dependent) interfaces, 91**
- PoE (Power over Ethernet), 357**
 - configuring, 360
 - power status, verifying, 360–361
 - powered device detection, 358–360
- point-to-point links, RSTP configuration, 270**
- point-to-point ports (RSTP), 266**
- port cables, GbE, 93–94**
- port cache, clearing, 390**
- port compatibility errors (EtherChannel), troubleshooting, 175**
- Port ID, tuning, 228–229**
- port operations on TCAM tables, 73**
- port priority value, 169**
- port security, 389–391**
- port speed, configuring, 96**
- port states**
 - of RSTP, 264
 - of STP, 197–198
- port-based authentication**
 - 802.1x method lists, configuring, 393–394
 - configuring, 392, 394
 - example, 394
- port-based VLAN membership, 114**
 - static VLAN configuration, 115–116
- PortFast, 205, 233**
 - configuring, 233–234
 - enabling, 270
 - status, displaying, 234

ports

- active EtherChannel parameters, displaying, 175
- BPDU filtering, enabling, 254
- duplex mode, configuring, 97
- Fast Ethernet on Catalyst switches, 92
- in errdisable state, viewing, 391
- roles
 - assigned in Root guard*, 247
 - RSTP*, 266
 - versus states*, 264
- selecting as ranges, 95
- speed/duplex mismatches, monitoring, 100–101
- status, displaying, 391
- UDLD, enabling, 252
- verifying active STP protection features, 254

power supply

- for LAPs, configuring, 525
- redundancy, configuring on Catalyst switches, 343–345

powered device detection (PoE), 358–360**predictable network model, 19–20****preparing for exam, scenarios**

- advanced STP, 539
- EtherChannel, 537–538
- implementing a wireless LAN, 542–543
- QoS in a switched network, 541
- router redundancy with HSRP and GLBP, 540–541
- securing access and managing traffic in a switched network, 541–542
- traditional STP, 538
- trunking and DTP, 535–536
- VLANs, trunking, and VTP, 536–537

preventing

- bridging loops, 189
- collisions, 15
- routing loops with RSTP
 - BPDU*s, 265
 - configuring*, 270
 - convergence*, 267
 - port behavior*, 263–264
 - port states*, 264
- routing loops with STP, 230–232
 - BackboneFast*, 236–237
 - PortFast*, 233
 - Root Bridge, configuring*, 223–226

Root Bridge, placement, 219–222

tuning, 227

UplinkFast, 234–235

primary VLANs, 415**process switching, 68****promiscuous mode ports, 416**

- mapping to primary/secondary VLANs, 418

proposal messages (RSTP), switch**synchronization, 267–268****protect mode (switch ports), 390****protecting against sudden BPDU loss, 250****protocol data units (PDUs), 9****pruning (VTP), 149–152****PSK authentication, 477****punt adjacencies, 302****PVID (Port VLAN ID), 114****PVLANs (private VLANs), 414–415**

- associating secondary VLANs to primary, 419–420

configuring, 416–419

PVST (Per-VLAN STP), 206**PVST+ (Per-VLAN Spanning Tree Plus), 207, 272****Q****QoS, 366**

Auto-QoS, 375–378

best effort, 367–368

DiffServ, 368–369

Layer 2 classification, 369

Layer 3 classification, 370–372

implementing on voice networks, 372–373

IntServ, 368

packet classification, 372–373

trust, configuring, 374–375

trust boundaries, 373

verifying, 378–381

R**radius of Fresnel zones, calculating, 451–452****ranges of ports, selecting, 95****REAP (Cisco Remote Edge Access Point), 509****reception of RF signals, factors affecting**

absorption, 448–449

diffraction, 449–450

Fresnel zones, 450–452

- reflection, 447–448
- refraction, 448
- scattering, 449
- recovering from switch port error conditions, 99**
- redirect timer (AVFs), 332**
- redundancy, 313**
 - gateway addresses, 317
 - HSRP, 318
 - of Catalyst switches
 - non-stop forwarding, 343*
 - power supplies, 343–345*
 - supervisor synchronization, 342*
 - of EtherChannel, 165
 - of gateway addresses
 - GLBP, 330–337*
 - HSRP, 318–326*
 - VRRP, 327–329*
 - of gateways, verifying configuration, 338
 - within switch chassis, 339
 - redundant switch supervisors, 339–340*
- redundancy modes of Catalyst switches, 339**
 - configuring, 340–341
- redundant bridging, 187–188**
- redundant link convergence (STP)**
 - BackboneFast, 236
 - PortFast, 233
 - UplinkFast, 234–235
- redundant switch supervisors, 339–340**
- reflection, 447–448**
- refraction, 448**
- regions (MST), 274**
 - defining, 277–278
 - IST instances, 275
 - MSTIs, 275
- relieving network congestion, 13**
- removing descriptions from switch ports, 96**
- request advertisements (VTP), 143–144**
- resources, grouping into building blocks, 39**
- restrict mode (switch ports), 390**
- revision number (VTP), setting to zero, 144**
- RF (radio frequency) communication, 445–446**
 - modulation schemes, 447
- RF communication**
 - antennas, 457
 - highly directional, 458–459*
 - omnidirectional, 457–458*
 - semi-directional, 458*
 - EIRP, 456
 - multipath interference, 458
 - overall gain, calculating, 456–457
 - signal reception, factors affecting
 - absorption, 448–449*
 - diffraction, 449–450*
 - Fresnel zones, 450–452*
 - reflection, 447–448*
 - refraction, 448*
 - scattering, 449*
 - signal strength, 452–453
 - dB values, 453–454*
 - increase in, 455–456*
 - loss of, 454–455*
- roaming, 444, 482–484**
 - associations, 486
 - implications of, 486–487
 - on lightweight APs, 511
 - inter-controller roaming, 514–518*
 - intra-controller roaming, 512–513*
 - scanning process, 484–485
- roles of RSTP switch ports, 264–266**
- rollover cables, 92**
- Root Bridge**
 - configuring, 223–226
 - election procedure, 191–192
 - network diameter value, configuring, 200
 - placement of, 219–222
 - Root Bridge ID value, 191
- Root Guard, 247–248**
- Root Path Cost (STP), 192**
 - calculating, 193
 - tie conditions, 195
 - tuning, 227–228
- root port**
 - election procedure, 192–194
 - on RSTP topologies, 264–266
- root-inconsistent STP state, 248**
- route cache switching, 295**
- route-caching, 65**
- router election (HSRP), 318–320**
 - conceding, 321–322
- “router on a stick,” 291**
- routers**
 - AVFs, 330–332
 - redundancy, HSRP, 318
- routing, 236. See also interVLAN routing**
 - Layer 3, 11

routing loops, 234

- preventing with RSTP
 - BPDU*s, 265
 - configuring, 270
 - convergence, 267
 - port behavior, 263–264
 - port states, 264
- preventing with STP, 232
 - Root Bridge* configuration, 223–226
 - Root Bridge* placement, 219–222

RPR (Route Processor Redundancy), 339–340**RPVST+ (Rapid PVST+), 263, 270–272****RSTP (Rapid STP)**

- BPDU*s, 265
- configuring, 270
- convergence, 265–267
 - synchronization*, 267–268
- edge ports, configuring, 270
- interoperability with STP, 265
- port behavior, 263–264
- port states, 264
- port types, 266
- switch ports
 - point-to-point links*, configuring, 270
 - role assignments*, 264
 - roles versus states*, 264
- topology changes, 269

S**SAP (Service Advertising Protocol), 14****SC connectors, 92****scaling**

- core block, 38–39
- Layer 2 switching, 10
- VLANs, 118

scanning process, 484–485**scattering, 449****scenarios**

- advanced STP, 539
 - answers*, 547
- EtherChannel, 537–538
 - answers*, 545
- implementing a wireless LAN, 542–543
 - answers*, 551
- QoS in a switched network, 541
- router redundancy with HSRP and GLBP, 540–541
 - answers*, 547–548

- securing access and managing traffic in a switched network
 - answers*, 549–550
- telephony in a switched network
 - answers*, 548–549
- traditional STP, 538
 - answers*, 545–546
- trunking and DTP, 535–536
 - answers*, 544
- VLANs, trunking, and VTP, 536–537
 - answers*, 544–545

secondary VLANs, 415

- associating to a primary VLAN, 419–420

security in WLANs, 475–476

- EAP-based, 477–479
- WPA, 479–480
- WPA2, 480

segmentation, 11**selecting**

- Designated Ports, 195–197
- ranges of ports, 95
- Root Ports (STP), 192–194
- switch ports for configuration, 94–96

semi-directional antennas, 458**server farm block, 31, 39–40****server mode (VTP), 139**

- configuring, 145

Service Advertisement Protocol (SAP), 14**service provider edge block, 31, 41****service sets, 438**

- BSS, 440
- comparing, 439
- ESS, 440
- IBSS, 439

setting VTP revision number to zero, 144**SFP (small form factor pluggable)****modules, 93****shared network model, 13–14, 436****show adjacency summary command, 300****show cdp neighbors command, 44****show cdp neighbors detail command, 45****show dot1x all command, 394****show etherchannel load-balance command, 175****show etherchannel port command, 173****show etherchannel port-channel command, 168****show etherchannel summary command, 173****show glbp command, 336**

- show interface command, 99
- show interface status command, 305
- show interface switchport command, 364
- show interface trunk command, 129–130
- show interfaces switchport command, 129
- show ip cef command, 297
- show ip interface brief command, 307
- show ip interface command, 306
- show lacp sys-id command, 175
- show mac address-table command, 74
- show port-security interface command, 391–392
- show power command, 345
- show spanning-tree interface command, 198, 229, 365
- show spanning-tree vlan command, 232, 271
- show vlan command, 116, 305
- show vlan id command, 128
- show vtp commands, 153
- show vtp counters command, 148
- show vtp status command, 144, 148
- shutdown command, 99, 305
- shutdown mode (switch ports), 390
- signal gain, 455–456
- signal loss, 454–455
- signal strength (RF), 452–453
 - dB values, 453–454
 - increase in, 455–456
 - loss of, 454–455
- silent submode (PAGP), 171
- single-host support, configuring, 234
- single-tagging, 122
- site surveys, 443
- sizing switch blocks, 33–35
- spanning-tree guard loop command, 251
- spanning-tree guard root command, 248
- spanning-tree portfast command, 270
- Spanning-Tree Protocol, 33
- spanning-tree vlan command, 226
- spectral masks, 461
- speed command, 97
- split-MAC architecture, 505
- spoofing attacks, mitigating
 - with ARP inspection, 399–401
 - with DHCP snooping, 395–397
 - with IP Source Guard, 397–399
- Spurgeon, Charles, 86
- SSIDs (service set identifiers), 438
- SSO (Stateful Switchover), 340
- stale entries (CAM tables), 69
- static CAM table entries, configuring, 69
- static VLANs
 - configuring, 115–116
 - port-based membership, 114
- static WEP keys, 477
- sticky MAC addresses, 389
- store-and-forward switching, 61
- STP (Spanning Tree Protocol)
 - active protection features, verifying on switch ports, 254
 - Blocking state, 197
 - BPDU Guard, 248–249
 - BPDUs
 - Configuration BPDUs, 189–190
 - protecting against sudden loss of, 250
 - TCN BPDUs, 200
 - bridging loops, 187–189
 - CST, 206
 - customizing, 226–227
 - Designated Ports
 - election procedure, 195–196
 - selecting, 196–197
 - Disabled state, 197
 - disabling with BPDU filtering, 254
 - displaying information, 237
 - Forwarding state, 197
 - IEEE 802.1Q, 272
 - interoperability with RSTP, 265
 - Learning state, 197
 - Listening state, 197
 - loop guard feature, 250–251
 - MST
 - IST instances, 275
 - MST instances, 276
 - network diameter value, configuring, 200
 - Path Cost, 193
 - Port ID, tuning, 228–229
 - port numbers, 228
 - PVST, 206
 - PVST+, 207
 - redundant link convergence, 232
 - BackboneFast, 236–237
 - PortFast, 233
 - UplinkFast, 234–235
 - Root Bridge
 - configuring, 223–226
 - election procedure, 191–192
 - placement, 219–222

- Root Guard, 247–248
- Root Path Cost, 192
 - tuning*, 227–228
- Root Ports, election procedure, 192–194
- running multiple instances of, 273
- switch ports, roles versus states, 264
- timers, 199
 - automatic configuration*, 231–232
 - manual configuration*, 230–231
 - modifying*, 230–231
- topology changes
 - direct topology changes*, 201–202
 - indirect topology changes*, 202–204
 - insignificant topology changes*, 204–205
- troubleshooting, 237, 254
- UDLD, 251–253
- unknown unicast frames, 186
- subset advertisements, 142**
- summary advertisements, 142**
- superior BPDUs, 248**
- supervisor modules, redundant switch supervisors, 339–340**
- supervisor synchronization, 342**
- supplicants, 439**
- SVI (switched virtual interface), 292**
- SVI ports, interVLAN routing configuration, 294**
- SVIs (switched virtual interfaces), 419–420**
- switch block connections**
 - console port, 92
 - Ethernet port cables, 92–93
 - Gigabit Ethernet port cables, 93–94
- switch blocks, 31–33**
 - distribution layer, 33
 - sizing, 33–35
- switch chassis, redundant switch supervisors, 339–340**
- switch ports**
 - aggregation, EtherChannel, 164
 - assigning to VLANs, 116
 - BPDUs filtering, enabling, 254
 - configuring, 94
 - connectivity, troubleshooting, 100–101
 - duplex mode, configuring, 97
 - errdisable state, 249
 - error conditions, recovering from, 97–99
 - for LAPs, configuring, 525–526
 - identifying, 96
 - loop-inconsistent state, 250
 - PortFast, configuring, 233–234
 - role assignments
 - Root guard*, 247
 - RSTP*, 264–266
 - selecting for configuration, 94–96
 - speed
 - configuring*, 96
 - displaying*, 99
 - text descriptions, adding, 96
 - trunks
 - configuring*, 124–126
 - example configuration*, 126–127
 - UDLD, enabling, 252
 - verifying active STP protection features, 254
 - VLAN tagging
 - IEEE 802.1Q*, 122
 - ISL*, 121–122
 - VLANs
 - and multiple subnets*, 119
 - troubleshooting*, 128–130
 - trunk links*, 119
- switch spoofing, 420–422**
- switches, 38**
 - VLANs, deleting, 116
 - VTP
 - configuring*, 144–147
 - example configuration*, 148
- switching**
 - Auto-QoS, 375–378
 - CAM table, 69–70
 - troubleshooting*, 74–75
 - console ports, connecting to, 92
 - Fast Ethernet ports, 92
 - frame processing, 63–65
 - functionality, 9–12
 - Layer 2, 10
 - Layer 3, 11
 - Layer 4, 12
 - MLS, 65
 - packet processing*, 66–68
 - MLS (multilayer switching), 12
 - port IDs, 228
 - port security, 389–391
 - redundant bridging, 187–188
 - single host support, configuring, 234
 - store-and-forward, 61
 - TCAM table, troubleshooting, 75

- TCAM tables, 70
 - example*, 72–73
 - port operations*, 73
 - structure*, 70–71
 - VMR combinations*, 71
- transparent bridging, 61–63
- trunks, 119–120
 - configuring*, 124–126
 - DTP*, 123–124
 - traffic identification methods*, 120
 - VLAN frame identification*, 121–123
 - VTP*, 139–142
- switchport command**, 116, 124, 292–293
- switchport host command**, 404
- switchport priority extend trust command**, 379
- synchronization of RSTP switches**, 267–268
- synchronization problem (VTP)**, 141
- syntax for CAM table commands**, 69
- system priority value**, 169

T

- tagging**, 121
 - IEEE 802.1Q, 122
 - ISL, 121–122
- TC (topology change) messages**, 269
- TCAM (Ternary Content Addressable Memory)**, 64, 413
- TCAM tables**, 70
 - example of*, 72–73
 - LOUs, 74
 - port operations*, 73
 - structure of*, 70–71
 - VMR combinations*, 71
- TCI (Tag Control Information) field**, 123
- TCN BPDUs**, 200
- text descriptions, adding to switch ports**, 96
- throttling adjacencies**, 301
- thwarting VLAN hopping**, 423–424
- tie conditions of Root Path Cost**, 195
- timers, STP**, 199
 - automatic configuration, 231–232
 - manual configuration, 230–231
 - modifying, 230–231
- TKIP (Temporal Key Integrity Protocol)**, 479–480
- Token Ring**
 - collisions, susceptibility to, 13
 - support on VTP version 2, 147
- topologies**
 - direct changes, 201–202
 - flat network, 113
 - indirect changes, 202–204
 - insignificant changes, 204–205
 - RSTP, detecting, 269
- topology-based MLS**, 65
- ToS (type of service)**, 370
- traffic**
 - 20/80 rule, 118
 - core blocks, 36–38
 - flooding, VTP pruning, 151–152
 - multicast, 14
 - within Cisco Unified Wireless Networks, 509–511
- transparent bridges**, 61–63
 - redundancy, 187–188
 - versus Ethernet switches, 185–186
- transparent mode (VTP)**, 140
 - configuring, 146
 - version-dependent, 147
- troubleshooting**
 - CAM table operation, 74–75
 - EtherChannel, 172–175
 - STP, 237, 254
 - switch ports
 - connectivity*, 100–101
 - error conditions*, 97–99
 - TCAM table operation, 75
 - trunks, 128–130
 - VLANs, 128–130
 - VTP, 152–153
- trunk links**, 119
 - VLAN tagging
 - IEEE 802.1Q, 122
 - ISL, 121–122
- trunks**, 119–120
 - accessing with switch spoofing, 420–422
 - between switches in different VTP domains, 124
 - configuring, 124–126
 - DTP, 123–126
 - example configuration, 126–127
 - IEEE 802.1Q, CST, 206
 - status, displaying, 126
 - troubleshooting, 128–130

VLAN hopping, 422–424
 VTP, 139

- advertisements, 139–144*
- client mode, 140, 146*
- configuring, 144*
- example configuration, 148*
- management domains, 139, 145*
- pruning, 149–152*
- server mode, 139*
- server mode, configuring, 145*
- status, displaying, 148–149*
- summary advertisements, 142*
- transparent mode, 140, 146*
- troubleshooting, 152–153*
- version, configuring, 146*

trust boundaries, 373

configuring, 374–375

tunneling between LAPs and WLCs, 505–506

two-dimensional channel layout, 489–491

U

UDLD (Unidirectional Link Detection), 251

default message interval times, 253
 enabling, 252
 message interval, configuring, 252

udld command, 252

unidirectional links, 251

U-NII (Unlicensed National Information Infrastructure), 463

unknown unicast flooding, 63

unknown unicast frames, 149, 186

unrecognized TLV (Type-Length-Value)

support, VTP version 2, 147

uplink ports, enabling BPDU guard, 249

UpLinkFast, 234–235

V

VACLs, configuring, 413–414

verifying

active STP features on switch ports, 254
 CEF operation, 307–308
 effectiveness of EtherChannel

- load-balancing, 168

 fallback bridging, 308
 gateway redundancy, 338
 GLBP operation, 336

inline power for Cisco IP Phones, 360

MLS, interVLAN routing, 304–307

PoE power status, 360–361

QoS, 379

VLAN configuration, 116

voice QoS operation, 378–381

voice VLAN operation, 364

version-dependent transparent mode, 147

VID (VLAN Identifier), 123

viewing

CAM table entries, 74

ports in errdisable state, 391

STP information, 237

switch port speed, 99

switch ports in root-inconsistent state, 248

trunking status, 126

VTP status, 148–149

VLAN hopping, 422

thwarting, 423–424

VLANs, 15, 113

deleting, 116

deploying, 117

dynamic VLANs, 117

end-to-end, deploying, 118–119

extended-range, 115

IEEE 802.1Q, CST, 206

interVLAN routing, 291

configuring, 292–294

interface types, 292

Layer 2 ports, configuring, 292

Layer 3 ports, configuring, 293–294

SVI ports, configuring, 294

verifying, 304–307

IP addressing scheme, 117

local, deploying, 118

management addresses, assigning, 40

mapping to multiple STP instances,

274–275

IST, 275

MSTIs, 275–277

membership methods, port-based, 114

MST

IST instances, 275

MST instances, 276

PVLANs, 414–415

configuring, 416–419

PVST, 206

secondary, associating to primary VLAN

SVI, 419–420

- static VLANs, configuring, 115–116
- tagging, 121
 - IEEE 802.1Q*, 122
 - ISL*, 121–122
- troubleshooting, 128–130
- trunks, 119–120. *See also* VTP
 - configuring, 124–126
 - DTP*, 123–124
 - example configuration*, 126–127
- verifying configuration, 116
- voice VLANs, 361–362
 - configuring, 362–363
 - verifying, 365–366
 - verifying operation, 364
- VMR (Value, Mask, and Result) combinations, 71**
- voice networks, QoS**
 - implementing, 372–373
 - operation, verifying, 378–381
- voice VLANs, 361–362**
 - configuring, 362–363
 - verifying operation, 364–366
- VoIP (Voice over IP)**
 - Cisco IP Phones
 - inline power*, 359
 - PoE*, 357–361
 - QoS, 366
 - trust*, configuring, 374–375
 - verifying, 379
 - voice VLANs, 361–362
 - configuring, 362–363
 - verifying operation, 364–366
- VRRP (Virtual Router Redundancy Protocol), 327–329**
 - configuring, 328
 - status, displaying, 328
- VTP (VLAN Trunking Protocol)**
 - advertisements, 139–141
 - requests*, 143–144
 - subset advertisements*, 142
 - summary advertisements*, 142
 - client mode, 140, 146
 - configuring, 144
 - example configuration, 148
 - extended-range VLAN membership, 115
 - management domains, 139
 - configuring, 145
 - parameters, displaying, 148
 - viewing status, 148–149

- pruning, 149–152
- revision number, setting to zero, 144
- server mode, 139, 145
- synchronization problem, 141
- transparent mode, 140, 146
- troubleshooting, 152–153
- version, configuring, 146
- version 2, consistency checks, 147
- version-dependent transparent mode, 147
- vtp mode transparent command, 115**
- VTPv3, 147**

W

- W (Watts), 453**
- WAN PHY, 91**
- WCS (Cisco Wireless Control System), 507**
- WEP (Wireless Equivalence Protocol), 477**
- WLANs**
 - 802.11 standards
 - 802.11a*, 463–464
 - 802.11b*, 460–462
 - 802.11g*, 463
 - frame type compliance*, 460
 - regulatory agencies*, 459–460
 - ad-hoc, 439
 - antennas, 457
 - highly-directional*, 458–459
 - omnidirectional*, 457–458
 - semi-directional*, 458
 - APs, 440–442
 - associations*, 482–486
 - cells*, 442–445
 - roaming*, 444, 482–487
 - ASDs, 481
 - collisions, avoiding, 436–437
 - DCF*, 437–438
 - designing, 487
 - AP cells*, *sizing*, 488–489
 - channel layout*, 489–492
 - ESS, 440
 - half-duplex transmission, 436
 - modulation, 447
 - RF communication
 - factors affecting reception*, 447–452
 - signal strength*, 452–456

security, 475–476
 EAP-based, 477–479
 EAP-FAST, 479
 EAP-TLS, 478
 LEAP, 478
 PEAP, 479
 WPA, 479–480
 WPA2, 480
service sets, 438
 BSS, 440
 IBSS, 439
site surveys, 443
SSIDs, 438
supplicants, 439
versus wired LANs, 435–436
WLC, configuring, 519–524

WLC1, anchor points, 518

WLCs (wireless LAN controllers), 505

 configuring, 519–524
 functions of, 506–507
 interface types, 519
 linking to LAPs, 505–506
 mobility groups, 518
 platforms available, 507

workgroups, 18

WPA (Wi-Fi Protected Access), 479–480

WPA2, 480

**WWDM (wide-wavelength division
multiplexing), 91**

X-Y-Z

XOR (exclusive-OR) operation, 165