

Index

Numerics

802.11 Wired Equivalent Privacy (WEP), 259

802.11i, 269–272

802.1x

authentication, 278–280

EAP standard, 260–272

A

AAR (automated alternate routing), 43

access

APs. *See* APs

categories, 237

communication devices, 10

databases, 10

guest, 292

switches, 235

WFQ, 134

access points. *See* APs

ACS (Access Control Server), 260

adding

locations, 310–312

maps, 309–310

WLC, 307–308

administration

congestion, 127–130

dial plans, 45

dynamic RF, 296

EAP, 261

keys, 269

phone features, 46

radio (WLSE), 295

RF, 306

RRM, 301

SDM, 81–88

WLANs

Cisco Unified Wireless Management,
291–292

components, 294

implementations, 292–293

need for, 291

WCS, 299–313

WLSE, 295–299

WLSE, 296

WPA, 269–272

admission control, 73

AES (Advanced Encryption Standard), 260

AF (assured forwarding), 103–105

agents, call, 11

aggregation

traffic shaping, 165

troubleshooting, 127

aggressive dropping, WFQ, 135

AH (Authentication Header), 182

alarms

rogue APs, 312–313

WCS Base, 301

algorithms

codecs, 24

queuing, 128

voice compression standards, 24–25

Allowed setting, 246

amplitude, 22

analog interfaces, VoIP, 13

analog phones, 11

analog voice

converting from digital, 20–21

converting to digital, 19–20

applications

Cisco Wireless Location Appliance,
305–306

classification, 206

conferencing, 10

dynamic port, 207
interfaces, 46
QoS
 pre-classify, 181–183
 TCP, 62
 VoIP, 187
servers, 11

APs (access points), 293
autonomous, 293
Cisco WCS Servers, 308
deployment, 296
lightweight, 272–280
SSID, 258
WCS Base, 301
WLSE, 295–296

architecture
Cisco Wireless Location Appliance, 305
LWAP, 238–240
Split MAC Architecture, 238–239

asset tags, Cisco Wireless Location Appliance, 305

assigning
channels, 301
sequence numbers, 134

assured forwarding (AF), 103–105

ATM (asynchronous Transfer Mode), 99

attacks
CoPP, 192–193
DoS, 259

audio. *See also* voice
keywords, 117
signals, 31
streams, 26
VAD, 42

audits, 301
business, 70
networks, 70

authentication, 272–273
802.1x, 278–280
configuring, 272–280
EAP, 260–261
LEAP, 262–264
PEAP, 267–269
static WEP, 273–274
VPNs, 180
WPA, 269–272
WPA PSK, 274–275

Authentication Header (AH), 182

authorization
objects, 74
rogue APs, 259

authorized users, 74

auto discovery qos command, 81, 210

auto qos command, 79, 81, 210

auto qos voip cisco-phone command, 211

auto qos voip command, 81

auto qos voip trust command, 211

auto re-site surveys, 298

autodiscovery, 212, 218

automated alternate routing (AAR), 43

automated monitoring, WCS Base, 301

automation, AutoQoS, 215–217

autonomous APs, 293–296

AutoQoS, 79–81, 205–212, 215–221
automation, 215–217
configurations, 219–221
for Enterprise, 206

availability of bandwidth, 63–64

avoidance (congestion), 67, 153
CBWRED, 158–162
limitations of tail drop, 153–154
link efficiency mechanisms, 167
RED, 154–156
traffic shaping and policing, 163–167
WRED, 156–157

B

- BA (behavior aggregate), 101**
- background**
 - access, 237
 - VAD, 42
- backups, WCS Base, 301**
- backward explicit congestion notification (BECN), 99**
- bandwidth**
 - availability, 63–64
 - codecs, 35–36
 - guarantees, 67
 - CBWFQ, 139–140*
 - SLAs, 187*
 - packet telephony networks, 10
 - requirements
 - codecs, 24*
 - compression, 24–25*
 - reserving, 141
 - VAD, 41–42
 - voice, 34–36
 - VoIP, 34–42
- bandwidth command, 140, 219**
- bandwidth percent command, 140**
- BECN (backward explicit congestion notification), 99**
- behavior aggregate (BA), 101**
- benefits**
 - of CBWFQ, 140
 - of LLQ, 144
 - of telephony packet networks, 10–11
 - of WEQ, 135
- best-effort**
 - access, 237
 - models (QoS), 72
- bits, CoS, 98–99**
- boundaries, trust, 108–110, 189**
- British Telecom, 25**
- broadcast key management, 269**
- Bronze access, 237**
- buffers, increasing space, 67**
- buildups, queues, 192**
- business audits, 70**
- bytes, ToS, 102**

C

- CAC (call admission control), 15, 49, 69**
- calculating bandwidth for VoIP, 34–42**
- call**
 - agents, 11
 - control models, 16–19
 - processing, 45
 - routing, 15
- call admission control, 15, 49, 69**
- campus maps, adding, 310–312**
- campus networks, QoS, 188–190**
- carrier sense multiple access collision avoid (CSMA/CA), 236–235**
- carrier sense multiple access collision detect (CSMA/CD), 236**
- CAS (channel associated signaling), 14**
- CBWFQ (Class-Based Weighted Fair Queuing), 138–139**
 - benefits/drawbacks, 140
 - classification, 139–140
 - configuration, 141–142
 - monitoring, 161
- CBWRED (class-based weighted random early detection), 158–162**
- CCM (Cisco CallManager), 45–46**
- CCMP (Cipher Block Chaining Message Authentication Code Protocol), 271**
- CCO (Cisco Connection Online), 111**
- CCS (common channel signaling), 14**
- CDP (Cisco Discovery Protocol), 110**
- CDT (congestive discard threshold), 135**
- CEF (Cisco Express Forwarding), 209**
- cell loss priority (CLP), 99**
- centralized call control, 16–19**
- centralized RF management, LWAP, 239**
- certificates, PKI, 260**
- channel associated signaling (CAS), 14**
- channels, assigning, 301**
- characters, NBAR, 116**
- Cipher Block Chaining Message Authentication Code Protocol (CCMP), 271**
- CIR (committed information rate), 165, 186**
- Cisco Aironet 128-bit devices, 259**
- Cisco CallManager (CCM), 45–46**
- Cisco Compatible Extensions program, 291**
- Cisco Connection Online (CCO), 111**
- Cisco Discovery protocol (CDP), 110**
- Cisco Express Forwarding (CEF), 209**

Cisco IOS

- configuring, 183
- NBAR, 112–117
- policing and shaping mechanisms, 167
- switches, 210–212
- voice, 48–49

Cisco IP Communicator, 11**Cisco Key Integrity Protocol (CKIP), 260****Cisco LEAP, 259, 262–264****Cisco Message Integrity Check (CMIC), 260****Cisco Unified Communication System, 45–46****Cisco Unified Wireless Networks, 291–292****Cisco WCS, 299–313****Cisco WCS Base, 300–301****Cisco Wireless Location Appliance, 304–306****CiscoWorks WLSE, 295–299****CKIP (Cisco Key Integrity Protocol), 260****Class-Based Weighted Fair Queuing****(CBWFQ), 138–139**

- benefits/drawbacks, 140
- classification, 139–140
- configuration, 141–142
- monitoring, 161

class-based weighted random early detection**(CBWRED), 158–162****classes**

- maps, 219
- selector PHBs, 102
- service, 106–108
- statements, 78
- traffic, 106
 - AutoQoS*, 216
 - defining QoS*, 71
 - marking*, 97–100
 - SLAs*, 187

classification, 73, 97–100

- applications, 206
- AutoQoS, 79, 220
- CBWFQ, 139–140
- CoS on 802.1Q/P Ethernet frames, 98–99
- DE and CLP on ATM/Frame Relay, 99
- MPLS EXP field, 100
- NBAR, 110–112
- subport, 111
- traffic, 64, 189
- video and voice, 189
- WEQ, 133–134

class-map command, 77, 97**CLI (command-line interface), 76****clients**

- Cisco Unified Wireless Networks, 291
- EAP, 261
- LEAP, 262
- open authentication, 272–273

CLP (cell loss priority), 99**clustering over WAN models, 48****CMIC (Cisco Message Integrity Check), 260****codecs**

- compression algorithms, 24
- types, 35–36

collection (statistics), NBAR, 110–112**coloring traffic, 98****command-line interface (CLI), 76****commands**

- auto discovery qos, 81, 210
- auto qos, 79, 81, 210
- auto qos voip, 81
- auto qos voip cisco-phone, 211
- auto qos voip trust, 211
- AutoQoS, 79–81
- bandwidth, 140, 219
- bandwidth percent, 140
- class-map, 77, 97
- fair-queue 16, 135, 141
- hold-queue max-limit out, 136
- IOS, 112–117
- IP CEF, 112
- ip nbar port-map, 113
- ip nbar protocol-discovery, 114
- match protocol, 115
- max-reserved-bandwidth, 139
- mls qos, 211
- no auto discovery qos, 210
- no auto qos, 221
- police, 193
- policy-map, 77
- priority, 219
- priority-list, 131
- qos pre-classify, 181–184
- queue-limit, 141
- random-detect, 158
- service-policy, 77–78, 142, 193
- service-policy output, 114
- show, 112
- show auto discovery qos, 212
- show auto discovery qos interface, 212
- show auto qos, 212, 214, 219

- show auto qos interface, 213
- show class-map, 78
- show controllers serial, 130
- show interface, 67, 136
- show mls qos interface, 215
- show mls qos maps, 212
- show mls qos maps dscp-cos, 215
- show policy-map, 78
- show policy-map interface, 79, 142, 212–213
- show queue interface, 137
- tx-ring-limit, 129
- voices, 48–49
- committed information rate (CIR), 165, 186**
- common channel signaling (CCS), 14**
- communication, device access, 10**
- components, 261**
 - EAP, 261
 - queuing, 128
 - telephony packet networks, 11–13
 - WLANs, 294
- Compressed RTP (cRTP), 32–34, 64, 208**
- compression, 20, 64**
 - codecs, 24
 - configuring, 64
 - cRTP, 32–34
 - headers, 66, 169–170
 - Layer 2, 66
 - payload (Layer 2), 168–169
 - standards, 24–25
- concurrent calls, limiting, 49**
- conferencing**
 - applications, 10
 - DSPs, 26
- confidentiality, VPNs, 180**
- configuration**
 - 802.1x authentication, 278–280
 - APs, 308
 - AutoQoS, 79–81
 - CAC, 49
 - CBWFQ, 141–142
 - CBWRED, 158–162
 - CiscoWorks WLSE, 295
 - compression, 64
 - gateways (voice), 44–45
 - IOS (qos pre-classify command), 183
 - legacy CLIs, 76
 - LLQ, 144–145
 - NBAR, 112–117
 - open authentication, 273
 - Over the Air QoS fields, 245
 - static WEP authentication, 273–274
 - utoQoS Enterprise, 206
 - voice, 48–49
 - WCS, 299–313
 - web authentication, 276–278
 - WEQ, 135–137
 - WLANs
 - QoS, 243–246
 - security, 272–280
 - WLSE, 297
 - WPA PSK authentication, 274–275
- confluence problem, 127**
- congestion**
 - avoidance, 67, 153
 - CBWRED, 158–162
 - limitations of tail drop, 153–154
 - link efficiency mechanisms, 167
 - RED, 154–156
 - traffic shaping and policing, 163–167
 - WRED, 156–157
 - management, 127–130
 - notification, 99
- congestive discard threshold (CDT), 135**
- connections**
 - access switches, 235
 - VPNs, 180–181
- consistency, AutoQoS, 79, 206**
- consolidated network expenses, 10**
- contention window (CWmin), 237**
- control**
 - and management plane traffic, 192
 - policies (EAP), 261
- control plane policing (CoPP), 192–193**
- Controller option, 244**
- controllers**
 - WCS Base, 301
 - WLAN, 243–244
- converged networks, QoS, 62–68**
- converting voice**
 - analog to digital, 19–20
 - digital to analog, 20–21
 - Nyquist theorem, 21
 - quantization, 22–23
- CoPP (control plane policing), 192–193**
- CQ (custom queuing), 128**
- cRTP (Compressed RTP), 32–34, 64, 208**

- CSMA/CA (carrier sense multiple access collision avoid), 236–237
- CSMA/CD (carrier sense multiple access collision detect), 236
- custom queuing (CQ), 128
- customization. *See also* configuration
 - WCS, 300–302
 - Web Login Page, 277
- CWmin (contention window), 237

D

- Dashboard (Network), 303–304
- data integrity, VPNs, 180
- data links, overhead, 35–37
- Data Link Control, 235
- data plane traffic, 192
- databases
 - access, 10
 - EAP, 261
 - LEAP, 262
 - packet telephony networks, 11
- data-link connection identifier (DLCI), 207
- DCF (distributed coordinated function), 236–237
- DE (discard eligible), 99
- decimal bits, CoS bits, 98–99
- default PHBs, 103
- defining
 - AutoQoS, 216
 - QoS policies, 71
- delay
 - end-to-end (VoIP), 16, 62–65
 - link fragmentation, 171
 - processing, 65
 - propagation, 65
 - queuing, 65
 - serialization, 65
 - variation (jitter), 63, 65–66
- delivery, voice, 27–34
- denial of service, 259, 270
- deployment
 - APs, 296
 - AutoQoS
 - on Enterprise on Cisco routers, 206, 209–210*
 - on IOS-based switches, 210–212*
 - IP Telephony options, 46–48

- QoS
 - end-to-end, 185–193*
 - pre-classification options, 183–184*
- queuing, 64
- wizards (WLSE), 296

descriptors, traffic, 97

design

- 802.1x authentication, 278–280
- APs, 308
- AutoQoS, 79–81
- CAC, 49
- CBWFQ, 141–142
- CBWRED, 158–162
- CiscoWorks WLSE, 295
- compression, 64
- gateways (voice), 44–45
- IOS (qos pre-classify command), 183
- legacy CLIs, 76
- LLQ, 144–145
- NBAR, 112–117
- open authentication, 273
- Over the Air QoS fields, 245
- static WEP authentication, 273–274
- trust boundaries, 108–110
- AutoQoS Enterprise, 206
- voice, 48–49
- WCS, 299–313
- web authentication, 276–278
- WEQ, 135–137
- WLANs
 - QoS, 243–246*
 - security, 272–280*
- WLSE, 297
- WPA PSK authentication, 274–275

detection

- Cisco WCS Servers, 312–313
- IDS, 260
- rogue APs, 259

devices

- AutoQoS, 79–81
- campus LAN, 189
- Cisco Unified Wireless Networks, 291
- Cisco Wireless Location Appliance, 304–306
- communication, 10
- control, 45
- DSPs, 25–26
- SDM, 81–88
- trust boundaries, 108–110

dial plan administration, 45
Differentiated Services Code Point (DSCP), 100–105
DiffServ
 fields, 100
 models, 100–105
 QoS, 74–75
digital interfaces, VoIP, 14–15
digital signal processors. *See* DSPs
digital voice
 converting from analog, 19–20
 converting to analog, 20–21
directories, services, 46
Disables setting, 246
discard eligible, 99
discovery, 218
 autodiscovery, 212
 NBAR, 110–112
distributed call
 control, 16–19
 processing, 47
distributed coordinated function, 236–237
distribution (multilayer) switches, 235
DLC (Data Link Control), 235
DLCI (data-link connection identifier), 207
DoS (denial of service) attacks, 259, 270
drawbacks
 of CBWFQ, 140
 of WFQ, 135
drop
 input queue, 67
 output, 67
 WFQ, 135
DSCP (Differentiated Services Code Point), 100–105
 CBWRED, 160
 IP precedence, 102–105
DSPs (digital signal processors), 12, 25–26
dynamic keys, WPA2, 279
dynamic port applications, 207
dynamic queues, WFQ, 134
dynamic RF management, 296
dynamic WEP keys, 261
dynamic-queues parameter, 136

E

E&M (Earth and Magneto or Ear and Mouth), 13
EAP (Extensible Authentication Protocol), 260–272
EAP over LAN (EAPOL), 265
EAP-FAST (Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling), 264–266
EAPOL (EAP over LAN), 265
EAP-TLS (Extensible Authentication Protocol-Transport Layer Security), 266–267
early dropping, WFQ, 135
Earth and Magneto or Ear and Mouth (E&M), 13
ease, best-effort QoS model, 72
EDCF (Enhanced Distributed Coordination Function), 238
Edit QoS Profile Page, 245
editing profiles, 244
EF (expedited forwarding), 103
efficiency
 links, 167
 packet telephony networks, 10
elements of WLAN management
 Cisco Unified Wireless Networks, 291–292
 components, 294
 implementations, 292–293
 need for, 291
 WCS, 299–313
 WLSE, 295–299
employees, productivity, 10
enabling, 207–212. *See also* configuration
Encapsulating Security Payload (ESP), 182
encapsulation
 HDLC, 207
 voice packets, 27–34
encoding, 20
encryption. *See also* security
 configuring, 272–280
 EAP, 261
endpoints
 centralized call control, 17
 video, 12
end-to-end delay, VoIP, 16, 62–65
end-to-end delivery voice, 27–30

end-to-end QoS. *See also* QoS
 deployment, 185–193
 maintaining, 240

Enhanced Distributed Coordination Function (EDCF), 238

enterprise campus QoS implementations, 188–190

Enterprise mode, WPA, 272

enterprise networks, VoIP, 42–49

Enterprise on Cisco routers, deploying AutoQoS, 209–210

Equipment, packet telephony networks, 10

equivalent to direct conversation, 24

errors. *See also* troubleshooting
 frames, 67
 quantization, 22

ESP (Encapsulating Security Payload), 182

event logs, WCS Base, 301

evolution of WLAN security solutions, 259–260

EXP field (MPLS), 100

expedited forwarding (EF), 103

expressions, regular (NBAR), 116

Extensible Authentication Protocol, 260–272

Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling, 264–266

Extensible Authentication Protocol-Transport Layer Security, 266–267

extensible markup language, 10, 46

external applications, programming interfaces to, 46

F

fair-queue 16 command, 141

fair-queue command, 135

FastTrack traffic, NBAR, 116–117

fault monitoring, WLSE, 295

FECN (forward explicit congestion notification), 99

fields
 DiffServ, 100
 EXP (MPLS), 100
 inner QoS, 241
 Over the Air QoS, 245

FIFO (first in, first out), 128–132

filters, MAC, 259

firmware, WLSE, 295

first in, first out, 128–132

Foreign Exchange Office (FXO), 13

Foreign Exchange Station (FXS), 13

forward explicit congestion notification (FECN), 99

forwarding
 AutoQoS, 209
 important packets first, 66

four-way handshakes, 264

fragile flows, 66

fragment size, 171

Frame Relay, DE and CLP on, 99

frame errors, 67

FXO (Foreign Exchange Office), 13

FXS (Foreign Exchange Station), 13

G

gatekeepers, 11

gateways
 centralized call control, 17
 DSPs, 25–26
 interfaces
analog, 13
digital, 14–15
 packet telephony networks, 11
 voice, 44–45
 VoIP, 29

generating hashes, 133

global synchronization, TCP, 153

Gold access, 237

GTK (group transient key), 270

guarantees
 bandwidth, 67
CBWFQ, 139–140
SLAs, 187
 lack of service, 72
 services, 75

guest access, 292

H

hackers, 258. *See also* security

handshakes, four-way, 264

hardware
 packet telephony networks, 10
 QoS, 189
 queuing, 128

hashes, generating, 133

HDLC (high-level data link control)
encapsulation, 207

headers

compression, 66, 169–170
MPLS, 100
overhead, 32–34

hierarchies, trust boundaries, 109

high availability, WLSE, 298

high-level data link control (HDLC)
encapsulation, 207

hold-queue max-limit out command, 136

IBNS (Identity Based Networking Services),
292

IDSs (Intrusion Detection Systems), 260, 292

IEEE (Institute of Electrical and Electronics
Engineers)

802.11 Wired Equivalent Privacy (WEP),
259
802.11i, 269–272
802.1x
authentication, 278–280
EAP standard, 260–272

IETF (Internet Engineering Task Force), 15,
99

IFS (inter-frame spacing), 236

Ignore counter, 67

images, WLSE, 296

implementation. *See also* configuration

AutoQoS
enabling, 207–212
troubleshooting, 215–221
verifying, 212, 215

LLQ (policy maps), 161

QoS
AutoQoS, 205–207
best-effort model, 72
converged network issues, 62–68
DiffServ model, 74–75
enterprise campus, 188–190
IntServ model, 73–74
models, 72
policies, 62, 68–71, 76, 88, 106–108
pre-classify, 180–184
WAN edge, 190–192

trust boundaries, 109

VoIP enterprise networks, 42–49
WLANs, 239–242, 292–293

increase (upgrade) link bandwidth, 64–67
increasing capacity, comparing to queuing,
128

initialization vector (IV), 259

inner QoS fields, mapping, 241

input

keywords, 78
queue drop, 67

insertion, WEQ, 135

installation, rogue APs, 259

Institute of Electrical and Electronics
Engineers. *See* IEEE

integrity, VPNs, 180

interfaces

applications, 46
legacy CLI, 76
MQC, 76–79, 139
QoS, 183–184
queuing, 130–132
transmit, 189
VIP, 65
VoIP
analog, 13
digital, 14–15
WCS, 302
web
authentication, 276–278
users, 243–244

inter-frame spacing (IFS), 236

Internet Engineering Task Force (IETF), 15,
99

Internet Protocol. *See* IP

Internetwork Operating System. *See* IOS

Internetwork Packet Exchange (IPX), 112

interpreting AutoQoS configurations, 219–221

Intrusion Detection Systems, 260, 292

IntServ models, QoS, 73–74

IOS (Internetwork Operating System)

configuring, 183
NBAR, 112–117
policing and shaping mechanisms, 167
switches, 210–212
voice, 48–49

IP (Internet Protocol)

CEF command, 112
overhead, 35

phones, 11
precedence

CBWRED, 159
DSCP, 102–105

QoS

converged network issues, 62–68
implementing, 68–71
overview of, 62

Telephony deployment options, 46–48

ip nbar port-map command, 113

ip nbar protocol-discovery command, 114

IPsec (IP Security), VPNs, 182

IPX (Internetwork Packet Exchange), 112

IV (initialization vector), 259

J

jitter, 30, 143

converged networks, 63–66
VoIP, 16

JPEG (Joint Photographics Expert Group), 115

K

keepalives, CoPP, 192

keys

dynamic (WPA2), 279
GTK, 270
management, 269
PMK, 264
PSK, 274–275
PTK, 270
session, 260

keywords

audio, 117
input/output, 78
payload-type, 117
statistics, 215
trust, 210
video, 117
voip, 210

KPN Research, 25

L

lack of service, 72

LANs (local-area networks)

campus devices, 189
EAPOL, 265

laptops, Cisco Wireless Location Appliance, 305

Layer 2

compression, 66
payload compression, 64, 168–169
QoS
CoS on 802.1Q/P Ethernet frames, 98–99
DE and CLP on ATM/Frame Relay, 99

Layer 2, 100

layers, implementing trust boundaries, 109

LEAP (Lightweight Extensible Authentication Protocol), 259, 262–264

legacy CLIs, 76

levels, services, 70, 75

LFI (link fragmentation and interleaving), 208

LightWeight Access Point Protocol (LWAPP), 291

lightweight AP wireless architecture. See LWAP

Lightweight Extensible Authentication Protocol, 259, 262–264

limitations

of CAC, 49
of NBAR, 111
of tail drop, 153–154
of traffic rates, 163

linear quantization, 23

link fragmentation and interleaving (LFI), 208

links

efficiency, 167
utilization with/without RED, 154

LLC (Logical Link Control), 235

LLQ (Low-Latency Queuing), 142–143

AutoQoS, 208
benefits of, 144
configuration, 144–145
policy maps, 161

local-area networks. See LANs

locations

- Cisco WCS Servers, 310–312
- Cisco Wireless Location Appliance, 304–306
- rogue APs, 313
- services, 292
- WCS tracking options, 300–302
- logarithmic quantization, 23**
- Logical Link Control, 235**
- login**
 - Cisco WCS Server, 306
 - Web Login Page, 277
- logs, events, 301**
- loss, packets, 63–68**
- Low Latency Queuing. *See* LLQ**
- low-speed serial links, enabling AutoQoS, 207**
- LWAPP (Lightweight Access Point Protocol), 291**
- LWAP (lightweight AP wireless architecture, 238–239, 293**
 - tunnels in Split MAC architecture, 240
 - viewing, 308
 - WCS, 299–313

M**MAC (Media Access Control)**

- filters, 259
- Split MAC Architecture, 238–239

maintenance, call, 16**management**

- congestion, 127–130
- dial plans, 45
- dynamic RF, 296
- EAP, 261
- keys, 269
- phone features, 46
- radio (WLSE), 295
- RF, 306
- RRM, 301
- SDM, 81–88
- WLANs
 - Cisco Unified Wireless Management, 291–292*
 - components, 294*
 - implementations, 292–293*
 - need for, 291*

WCS, 299–313

WLSE, 295–299

WLSE, 296

WPA, 269–272

mapping

- Cisco WCS Server, 309–310
- inner QoS fields, 241
- LLQ, 144, 161
- markings, 107
- modifying, 219
- policies, 141
- QoS markings, 240–241

mark probability denominator (MPD), 154**marking, 97–100**

- DSCP, 100–105
- enterprise campus QoS, 189
- mapping, 107
- QoS, 240–241
- traffic, 64
- trust boundaries, 108–110

match protocol command, 115**match statements, 77, 97, 113, 219****max-reserved-bandwidth command, 139****MCUs (multipoint control units), 11****MD5 (Message Digest 5), 182****mean opinion score (MOS), 24****measurements**

- traffic rates, 165–167
- voice signals, 24

Media Access Control. *See* MAC**Media Gateway Control Protocol, 15****menus, WCS, 302****Message Digest 5 (MD5), 182****Message Integrity Check, 15****MGCP (Media Gateway Control Protocol), 15****MIC (Message Integrity Check), 260, 269****mismatch, speed, 165****missed trap polling, 301****mixed-mode conferences, 26****MLP (Multilink PPP), 207****mls qos command, 211****mobile devices, Cisco Wireless Location Appliance, 305****mobility platforms, Cisco Unified Wireless Networks, 291****models**

- call control, 16–19
- DiffServ, 100–105

QoS, 72

best-effort, 72

DiffServ, 74–75

IntServ, 73–74

modifying

AutoQoS configurations, 219–221

mapping, 219

root passwords, 306

modular QoS command-line interface

(MQC), 76–79, 139

MOH (music on hold), 41

monitoring

AutoQoS, 79, 206

CBWFQ, 141–142, 161

LLQ, 144–145

threshold-based, 296

WCS Base, 300–301

WFQ, 135–137

WLSE, 295

MOS (mean opinion score), 24

MPD (mark probability denominator), 154

MPLS (Multi-Protocol Label Switching), 100

MQC (modular QoS command-line interface), 76–79, 139

Multilink PPP (MLP), 207

multiple queues, 189

multiplexing, 31

multiport control units (MCUs), 11

Multi-Protocol Label Switching, 100

multisite

with centralized call processing model, 46

with distributed call processing model,
47–48

music on hold (MOH), 41

N

NAC (Network Admission Control), 292

National Institute of Standards and Technology (NIST), 271

navigating WCS, 302

NBAR (Network Based Application

Recognition), 97, 110–117, 205

Network Admission Control (NAC), 292

Network Based Application Recognition, 97, 110–117, 205

Network Dashboard, 303–304

network interface card, 258

network module high density voice (NM-HDV), 25

networks

audits, 70

campus, 188–190

Cisco Unified Wireless Networks, 291–292

converged, 62–68

enterprise, 42–49

outages, 62

packet telephony networks

benefits of, 10–11

components, 11–13

services, 295

unification, 291

VPNs, 180–181

NIC (network interface card), 258

NIST (National Institute of Standards and Technology), 271

NM-HDV (network module high density voice), 25

no auto discovery qos command, 210

no auto qos command, 221

notification, congestion, 99

Nyquist theorem, 21

O

off-hook, calling phones, 18

one-time password (OTP), 261

open authentication, 272–273

operating systems, LEAP support for, 262

optimizing WLSE, 298

options. *See also* configuration; customization

Controller, 244

IP Telephony deployment, 46–48

WCS tracking, 300–302

OTP (one-time password), 261

outages, networks, 62

output

drop, 67

keywords, 78

Over the Air QoS fields, configuring, 245

overhead

data link, 35–37

headers, 32–34

IP, 35

security, 37–39

tunneling, 35–39

Overrun counter, 67
 overutilization, 154

P

Packet Description Language Modules (PDLs), 111

packet voice DSP modules (PVDMs), 25

packets

- access, 134
- loss, 63, 66–68
- periods, 36
- size, 35
- telephony networks
 - benefits of, 10–11*
 - components, 11–13*
- voice, 27–34

packets per second (pps), 35

pairwise master key (PMK), 264

pairwise transient key (PTK), 270

PAM (pulse amplitude modulation), 20

parameters

- queues, 136
- traffic, 219

passwords

- OTP, 261
- root, 306

payloads

- compression (Layer 2), 168–169
- voice, 34–36

payload-type keyword, 117

PBX phones, 11

PCM (pulse code modulation), 20

PDLs (Packet Description Language Modules), 111

PDU (protocol data unit), 100

PEAP (Protected Extensible Authentication Protocol), 267–269

people, tracking with Cisco Wireless Location Appliances, 305

perceptual analysis measurement system (PAMS), 25

perceptual evaluation of speech quality (PESQ), 25

perceptual speech quality measurement (PSQM), 25

perfect conversation, 24

Per-Hop Behavior (PHB), 100–105

permanent virtual circuits (PVC), 207

per-packet keying (PPK), 269

Personal mode, WPA, 272

PESQ (perceptual evaluation of speech quality), 25

phases, EAP-FAST, 264

PHB (Per-Hop Behavior), 100–105

phones

- feature administration, 46
- IP phones, 11
- packet telephony networks, 11
- stages of phone calls, 15–19

PKI (Public Key Infrastructure) certificates, 260

placement of trust boundaries, 108–110

planning QoS policy implementation, 106–108

Platinum access, 237

PMK (pairwise master key), 264

polarity, 22

police command, 193

policies

- AutoQoS, 206
- control, 261
- drop, 135
- maps, 141
 - LLQ, 144, 161*
 - modifying, 219*
- objects, 74
- QoS
 - AutoQoS, 79*
 - converged network issues, 62–68*
 - implementing, 62, 68–71, 76, 88, 106–108*
 - pre-classify deployment, 183–184*

trust boundaries, 108–110

WCS Base, 301

WLSE, 295

policing, 73

- CoPP, 192–193
- traffic, 163–167, 189

policy-map command, 77

polling, missed trap, 301

ports

- dynamic application, 207
- subport classification, 111

PPK (per-packet keying), 269

pps (packets per second), 35

PQ (priority queuing), 128–132

precedence, IP, 159

pre-classify (QoS), implementing, 180–184
 prerequisites, enabling AutoQoS, 209
prioritization
 delay-sensitive packets, 66
 traffic, 237
priority command, 219
priority queuing (PQ), 128–132
priority-list command, 131
processes, voice, 27–34
processing
 delay, 65
 distributed call, 47
processors, DSPs, 25–26
productivity, employees, 10
profiles, 244
 RED, 155
 WRED, 156
programming interfaces to external applications, 46
propagation, delay, 65
Protected Extensible Authentication Protocol (PEAP), 267–269
protocol data unit (PDU), 100
protocols
 CCMP, 271
 CDP, 110
 CKIP, 260
 discovery, 111
 EAP, 260–272
 EAP-FAST, 264–266
 EAP-TLS, 266–267
 LEAP, 259, 262–264
 LWAPP, 291
 MGCP, 15
 PEAP, 267–269
 RTP, 65, 117, 169–170
 signaling, 15–19
 SIP, 15
 TCP
 global synchronization, 153
 header compression, 170
 starvation, 154
 TKIP, 269
 tunneling, 37
 UDP, 15
 voice, 27–34
PSQM (Perceptual speech quality measurement), 25
PSTN (public switched telephone network), 19
PTK (pairwise transient key), 270

Public Key Infrastructure (PKI) certificates, 260
public switched telephone network, 19
pulse amplitude modulation (PAM), 20
pulse code modulation (PCM), 20
PVCs (permanent virtual circuits), 207
PVDMs (packet voice DSP modules), 25

Q

QoS (Quality of Service)
 AutoQoS, 79–81, 205–207
 enabling, 207–212
 modifying configurations, 219–221
 troubleshooting, 215–221
 verifying, 212, 215
 converged network issues, 62–68
 CoPP, 192–193
 end-to-end, 185–193
 hardware, 189
 implementing, 68–71, 76, 88
 markings, 240–241
 models, 72
 best-effort, 72
 DiffServ, 74–75
 IntServ, 73–74
 MQC, 76–79
 overview of, 62
 policies, 106–108
 pre-classify, 180–184
 SDM, 81–88
 SLAs, 186–187
 WANs, 190–192
 WLANs
 configuration, 243–246
 description of, 237–238
 implementation, 239–242
 need for, 235–237
 Split MAC architecture, 238–239
qos pre-classify command, 181, 183–184
quantization, 20–23
queue-limit command, 141
queues, 73, 127–130
 buildups, 192
 CBWFQ, 138–139
 benefits/drawbacks, 140
 classification, 139–140
 configuration, 141–142
 monitoring, 161

- CQ, 128
- delay, 65
- deploying, 64
- LLQ, 142–143, 208
 - benefits of, 144*
 - configuration, 144–145*
 - policy maps, 161*
- multiple, 189
- TxQ, 128
- types of, 130–132
- WFQ, 132
 - benefits/drawbacks, 135*
 - classification, 133–134*
 - configuration, 135–137*
 - insertion and drop policies, 135*
- WRR, 128

R

- radio frequency. *See* RF
- radio frequency identification, 305
- radio management, WLSE, 295
- radio resource management (RRM), 301
- RADIUS (Remote Authentication Dial In User Service)**
 - EAP features, 260
 - servers, 262
- random early detection (RED), 154–156
- random wait timers, 236
- random-detect command, 158
- rates
 - CIR, 165, 186
 - packets, 35
 - traffic, 165–167
- RC4 vulnerabilities, 259**
- Real-Time Protocol Control Protocol (RTCP), 117**
- Real-time Transport Protocol. *See* RTP**
- REAP (Remote-Edge Access Point), 293**
- received signal strength indicator (RSSI), 296
- RED (random early detection), 154–156**
- reducing header overhead, 32–34
- regular expressions, NBAR, 116
- releasing signals, 31
- re-marking traffic, 163

- remote access VPNs, 180–181
- Remote Authentication Dial In User Service. *See* RADIUS**
- Remote-Edge Access Point (REAP), 293**
- reports**
 - AutoQoS, 79, 206
 - WLSE, 295–296
- reprioritization, packets, 66**
- Required setting, 246**
- requirements**
 - bandwidth
 - codecs, 24*
 - compression, 24–25*
 - EAP-TLS, 266
 - system, 302
 - traffic, 70–71
- reservable-queues parameter, 136**
- reserving bandwidth, 141**
- Resource Reservation Protocol (RSVP), 101**
- response times, CoPP, 192
- restrictions, AutoQoS, 207
- return on investment (ROI), 11
- RF (radio frequency)**
 - Cisco Wireless Location Appliance, 304–306
 - dynamic management, 296
 - management, 306
 - visibility, 296
- RFID (radio frequency identification), 305**
- roaming, EAP, 261**
- rogue APs. *See also* APs**
 - Cisco WCS Servers
 - detecting, 312–313*
 - viewing, 313*
 - detecting, 312–313
 - viewing, 313
- ROI (return on investment), 11**
- root passwords, modifying, 306**
- round-robin (RR) queuing, 130–132**
- routers**
 - Cisco Enterprise on, 209–210
 - congestion, 128
 - queuing, 128
 - voice, 44–45
- routing**
 - call, 15
 - updates, 192
- RR (round-robin) queuing, 130–132**
- RRM (radio resource management), 301**

RSSI (received signal strength indicator), 296
RSVP (Resource Reservation Protocol), 101
RTCP (Real-Time Protocol Control Protocol), 117
RTP (Real-Time Transport Protocol), 65, 117, 169
 header compression, 170
 VoIP, 30–32

S

samples, 20

Nyquist Theorem, 21
 voice payloads, 34–36

scalability

best-effort QoS model, 72
 DiffServ model, 75

scheduling, 74

CBWFQ, 139–140
 WFQ, 133–134

SDM (Security Device Manager), 81–88

Secure Hash Algorithm (SHA), 182

security

evolution of, 259–260
 overhead, 37–39
 SOHO, 272
 troubleshooting, 258–259
 WLANs, 296
 Cisco Wireless Location Appliance,
 306
 configuring, 272–280
 EAP, 260–272
 overview of, 258–260
 WPA, 269–272

Security Device Manager (SDM), 81–88

segments, 22

Self-Defending Network, 292

self-healing, WLSE, 298

sequence numbers, assigning, 134

serialization, delay, 65

servers

ACS, 260
 application, 11
 RADIUS
 EAP, 260
 LEAP, 262
 WCS requirements, 302

service level agreement (SLA), 101, 186–187

Service Set Identifier (SSID), 258

service-policy command, 77–78, 142, 193

service-policy output command, 114

services, 46

directories, 46
 DSPs, 25–26
 guarantees, 75
 levels
 defining, 70
 DiffServ model, 75
 networks, 295
 QoS, 106–108
 XML, 46

Session Initiation Protocol, 15

session keys, 260

set statement, 219

SHA (Secure Hash Algorithm), 182

shaping traffic, 163–167

show auto discovery qos command, 212

show auto discovery qos interface command, 212

show auto qos command, 212, 214, 219

show auto qos interface command, 213

show class-map command, 78

show command, 112

show controllers serial command, 130

show interface command, 67, 136

show mls qos interface command, 215

show mls qos maps command, 212

show mls qos maps dscp-cos command, 215

show policy-map command, 78

show policy-map interface command, 79, 142, 212–213

show queue interface command, 137

signals, 15–19

control, 45

DSPs, 25–26

releasing, 31

signal-to-noise quantization ratio (SQR), 23

Silver access, 237

single-mode conferences, 26

single-site model, IP Telephony, 46

SIP (Session Initiation Protocol), 15

site-to-site VPNs, 181. *See also* VPNs, 180–181

size

packetization, 35

voice payloads, 34–36

- SLA (service level agreement), 101, 186–187
- small office, home office (SOHO), 272
- sniffers, 258
- software, queuing, 128
- SOHO (small office, home office), 272
- space, increasing buffer, 67
- special characters, NBAR, 116
- speed mismatch
 - traffic shaping, 165
 - troubleshooting, 127
- Split MAC architecture, 238–240
- SQR (signal-to-noise quantization ratio), 23
- SSID (Service Set Identifier), 258
- stages of phone calls, 15–19
- standards
 - AES, 260
 - codecs, 35–36
 - compression, 24–25
- starvation, TCP, 154
- statements
 - class, 78
 - match, 77, 97, 113, 219
 - set, 219
- static WEP authentication, 273–274
- statistics
 - call maintenance, 16
 - keywords, 215
 - NBA, 110–112
- status, monitoring with WCS Base, 301
- streams, audio, 26
- strings, NBAR, 116
- subport classification, 111
- summaries
 - LWAPs, 308
 - WCS, 303–304
- switches
 - access, 235
 - congestion, 128
 - IOS-based, 210–212
- synchronization, TCP global, 153
- system requirements, WCS, 302

T

- tagging traffic, 98
- tail drop, 67, 128
 - limitations of, 153–154

- TCP (Transmission Control Protocol)
 - applications, 62
 - global synchronization, 153
 - header compression, 64, 170
 - starvation, 154
- TCP/IP (Transmission Control Protocol/Internet Protocol), 30–32
- telemetry, Cisco Wireless Location Appliance, 306
- telephone clients, 305
- telephony
 - IP Telephony deployment options, 46–48
 - packet networks
 - benefits of, 10–11
 - components, 11–13
- templates, WLSE, 296–297
- Temporal Key Integrity Protocol (TKIP), 269
- thresholds
 - CDT, 135
 - monitoring, 296
 - MPD, 154
- timers, random wait, 236
- TKIP (Temporal Key Integrity Protocol), 269
- tools, AutoQoS, 205
- ToS (type of service), 100–102
- tracking
 - Cisco Wireless Location Appliance, 304–306
 - WCS, 300–302
- traffic
 - classes, 106
 - AutoQoS, 216
 - defining QoS, 71
 - SLAs, 187
 - classification, 64, 97–100
 - congestion management, 127–130
 - CoPP, 192–193
 - enterprise campus QoS, 189
 - FastTrack, 116–117
 - mapping, 107
 - NBAR, 110–112
 - parameters, 219
 - policing, 163–167, 189
 - prioritization, 237
 - rates, 165–167
 - re-marking, 163
 - requirements, 70–71
 - shaping, 163–167
 - types, 70

transcoding, 12, 26
Transmission Control Protocol. See TCP
Transmission Control Protocol/Internet Protocol, 30–32
transmissions, packet telephony networks, 10
transmit interfaces, 189
transmit queue (TxQ), 128
troubleshooting, 215, 220–221
 bandwidth availability, 64
 congestion, 127–130, 153. *See also*
 congestion
 security, 258–259
trunks, CoS on 802.1Q/P Ethernet frames, 98–99
trust
 boundaries, 108–110, 189
 keywords, 210
tunneling
 interfaces, 183–184
 LWAP, 240
 modes (ESP), 182
 overhead, 35, 37–39
 protocols, 37
TxQ (transmit queue), 128
tx-ring-limit command, 129
type of service (ToS), 100
types
 of codecs, 35–36
 of queuing, 130–132
 of traffic
mapping, 107
identifying, 70

U

UDP (User Datagram Protocol), 15, 30–32
underutilization, 154
unicast key management, 269
unification, networks, 291
updating
 images, 296
 routing, 192
upgrading firmware, WLSE, 295
User Datagram Protocol. See UDP
utilization
 CoPP, 192
 Links with/without RED, 154

V

values
 AF DSCP, 104
 CoS bits, 98–99
 MOS, 24
 MPD, 154
verification, 212, 215
versatile interface processor (VIP), 65
versions
 AutoQoS, 206
 CiscoWorks WLSE, 296–297
video
 access, 237
 classification, 189
 endpoints, 12
 keywords, 117
 packet telephony networks, 10
viewing
 LWAPs, 308
 rogue APs, 313
views, WCS, 300–301
VIP (versatile interface processor), 65
VIP-DTS (virtual IP distributed traffic shaping), 163
virtual IP distributed traffic shaping (VIP-DTS), 163
virtual private networks, 180–181
visibility
 Cisco Wireless Location Appliance, 305
 RF, 296
VNMs (voice network modules), 25
voice
 access, 237
 classification, 189
 encoding
converting analog to digital, 19–20
converting digital to analog, 20–21
Nyquist Theorem, 21
quantization, 22–23
 end-to-end delivery, 27–30
 gateways, 25–26, 44–45
 IOS, 48–49
 packets
encapsulating, 27–34
telephony networks, 10
 payloads, 34–36
 signals, 24, 31

- voice interface cards (VIC) XE, 19**
- voice network modules (VNM), 25**
- VoIP (Voice over IP)**
 - AutoQoS, 210–212
 - bandwidth, 34–42
 - Cisco Wireless Location Appliance, 305
 - compression standards, 24–25
 - DSPs, 25–26
 - end-to-end delay, 62–65
 - enterprise networks, 42–49
 - IP QoS SLAs, 187
 - Nyquist Theorem, 21
 - packets
 - benefits of networks, 10–11*
 - components, 11–13*
 - encapsulating, 27–34*
 - phone calls, 15–19
 - voice encoding
 - converting analog to digital, 19–20*
 - converting digital to analog, 20–21*
 - Nyquist Theorem, 21*
 - quantization, 22–23*
- voip keyword, 210**
- VPNs (virtual private networks), 180–181**

W

- WANs (wide-area networks)**
 - clustering over model, 48
 - congestion, 128
 - QoS, 190–192
- war driving, 258**
- WCS (Wireless Control System), 299–313**
- WCS Base, 300–301**
- WCS Location + 2700 Series Wireless Location Appliance, 300–301**
- WCS Network Summary (Network Dashboard), 303–304**
- WDSs (Wireless Domain Services), 294**
- web authentication, 276–278**
- Web Login Page, customizing, 277**
- web user interfaces, 243–244**
- Weighted Fair Queuing. *See* WFQ**
- weighted random early detection (WRED), 104, 128, 156–157**
- WEP (Wired Equivalent Privacy), 259**
 - EAP, 261
 - keys, 260
 - static authentication, 273–274
- WFQ (Weighted Fair Queuing), 132**
 - benefits/drawbacks, 135
 - classification, 133–134
 - configuration, 135–137
 - insertion and drop policies, 135
- wide-area networks. *See* WANs**
- Wi-Fi, 305**
- Wi-Fi Multimedia, 237–239**
- Wi-Fi Protected Access. *See* WPA**
- Wired Equivalent Privacy. *See* WEP**
- Wireless Control System (WCS), 299–313**
- wireless devices, LEAP support, 263**
- Wireless Domain Services (WDS), 294**
- wireless LAN controller, 235, 291, 307–308**
- Wireless LAN Solution Engine (WLSE), 295–299**
- wireless local-area networks. *See* WLANs**
- wireless sniffers, 258**
- wizards**
 - deployment, 296
 - SDM QoS, 81–88
- WLANs (wireless local-area networks)**
 - controllers, 243–244
 - management
 - Cisco Unified Wireless Networks, 291–292*
 - components, 294*
 - implementations, 292–293*
 - need for, 291*
 - WCS, 299–313*
 - WLSE, 295–299*
- QoS**
 - configuration, 243–246*
 - description of, 237–238*
 - implementation, 239–242*
 - need for, 235–237*
 - Split MAC architecture, 238–239*
- security, 296
 - Cisco Wireless Location Appliance, 306*
 - configuring, 272–280*
 - EAP, 260–272*
 - overview of, 258–260*
- WLC (wireless LAN controller), 235, 291, 307–308**
- WLSE (Wireless LAN Solution Engine), 295–299**
- WMM (Wi-Fi Multimedia), 237–239**

workflow automation, Cisco Wireless

Location Appliance, 305

WPA (Wi-Fi Protected Access), 269–272

802.1x authentication, 279

PSK authentication, 274–275

WPA2, 269–272, 279

WRED (weighted random early detection),

104, 128, 156–157

WRR (weighted round-robin) queuing,

128–132

X

XML (extensible markup language), 10, 46